

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414597
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Bischofberger; Allen Albert et al.

Bicycle helmet with modular impact absorbing structures

Abstract

A helmet includes an outer shell having an interior and an exterior and an impact absorbing layer positioned on the interior of the outer shell. The impact absorbing layer includes a first impact absorbing structure having a first interface and a second impact absorbing structure having a second interface in lateral compression against the first interface.

Inventors: Bischofberger; Allen Albert (Ben Lomond, CA), Dias; Luiz Felipe de Melo (Minas Gerais, BR), Jerome; Alexander Hart (Morgan Hill, CA), Debus; David Tyler (Felton, CA), Pietrzak; Christopher Thomas (Redwood City, CA)

Applicant: Specialized Bicycle Components, Inc. (Morgan Hill, CA)

Family ID: 1000008819769

Assignee: Specialized Bicycle Components, Inc. (Morgan Hills, CA)

Appl. No.: 17/825756

Filed: May 26, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220378141 A1	Dec. 01, 2022

Related U.S. Application Data

us-provisional-application US 63194738 20210528

Publication Classification

Int. Cl.: A42B3/12 (20060101); A42B3/00 (20060101); A42B3/04 (20060101); A42B3/06 (20060101); A42B3/28 (20060101); A42B3/14 (20060101); A42B3/20 (20060101);

U.S. Cl.:

CPC **A42B3/128** (20130101); **A42B3/00** (20130101); **A42B3/0406** (20130101); **A42B3/06** (20130101); **A42B3/28** (20130101); A42B3/04 (20130101); A42B3/125 (20130101); A42B3/145 (20130101); A42B3/205 (20130101); A42B3/324 (20130101); A42B3/326 (20130101)

Field of Classification Search

CPC: A42B (3/28)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3946441	12/1975	Johnson	2/412	A42B 3/063
5035009	12/1990	Wingo, Jr.	2/425	A42B 3/121
5950244	12/1998	Fournier	2/425	A42B 3/128
6009561	12/1999	Bullock et al.	N/A	N/A
6317896	12/2000	Timms et al.	N/A	N/A
6332227	12/2000	Fang	N/A	N/A
7565704	12/2008	Wu	N/A	N/A
8015625	12/2010	Grim et al.	N/A	N/A
8032993	12/2010	Musal	N/A	N/A
8037548	12/2010	Alexander et al.	N/A	N/A
8146177	12/2011	Mangone	N/A	N/A
8176574	12/2011	Bryant et al.	N/A	N/A
8220078	12/2011	Wang	N/A	N/A
8370967	12/2012	Chen	N/A	N/A
8510870	12/2012	Rogers et al.	N/A	N/A
9357811	12/2015	Chiang	N/A	N/A
9433252	12/2015	Lebel et al.	N/A	N/A
9526291	12/2015	Beauchamp et al.	N/A	N/A
9572390	12/2016	Simpson	N/A	N/A
9572391	12/2016	McInnis	N/A	A42B 3/124
9795180	12/2016	Lowe et al.	N/A	N/A
D808083	12/2017	Durham et al.	N/A	N/A
9872532	12/2017	Muller	N/A	N/A
10021932	12/2017	Shearman et al.	N/A	N/A
10098407	12/2017	Kele	N/A	A42B 3/16
10271603	12/2018	Briggs	N/A	A42B 3/064
10321729	12/2018	Aguilera Robles et al.	N/A	N/A
10342283	12/2018	Glover et al.	N/A	N/A
10420385	12/2018	Lakes	N/A	A42B 3/145
10492555	12/2018	Lebel et al.	N/A	N/A
10736373	12/2019	Chilson	N/A	A42B 3/127

10765164	12/2019	Giroux Bernier et al.	N/A	N/A
10786028	12/2019	Cech et al.	N/A	N/A
2006/0070170	12/2005	Copeland	2/412	A63B 71/10
2006/0112477	12/2005	Schneider	N/A	N/A
2007/0157370	12/2006	Joubert Des Ouches	N/A	N/A
2010/0050324	12/2009	Musal	N/A	N/A
2013/0232670	12/2012	Janetos	N/A	N/A
2014/0223641	12/2013	Henderson	2/411	A42B 3/065
2015/0047110	12/2014	Chilson	N/A	N/A
2015/0074876	12/2014	Chiang	N/A	N/A
2015/0089725	12/2014	Lowe	2/410	A42B 3/125
2015/0282550	12/2014	Musal	N/A	N/A
2015/0305428	12/2014	Lakes et al.	N/A	N/A
2017/0318893	12/2016	Durham et al.	N/A	N/A
2018/0360151	12/2017	Desjardins et al.	N/A	N/A
2019/0045874	12/2018	Kele	N/A	N/A
2020/0229530	12/2019	Feher	N/A	N/A
2021/0007432	12/2020	Santiago et al.	N/A	N/A
2022/0087355	12/2021	Wagnac	N/A	A42B 3/124
2022/0175074	12/2021	Rietdyk	N/A	N/A
2022/0395046	12/2021	Fischer et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102017108038	12/2017	DE	N/A
2011025482	12/2010	WO	N/A
2011149895	12/2010	WO	N/A
2017152151	12/2016	WO	N/A
2019195339	12/2018	WO	N/A
2019237025	12/2018	WO	N/A

OTHER PUBLICATIONS

Audane, S. Lazer Blade helmet + aero shell product page. Oct. 15, 2015. Retrieved on Jan. 19, 2021 from <https://road.cc/content/review/161935-lazer-blade-helmet-aero-shell> (10 pages). cited by applicant

Lazersport. Blade+ webpage, 2021, Retrieved on Jan. 19, 2021 from <https://lazersport.us/collections/road/products/blade-plus> (3 pages). cited by applicant

Life Changing Products. Helmet Camera Mount for Action Camera product page, Version dated May 11, 2021, available online at

<https://web.archive.org/web/20210511063355/https://lcpshop.net/product/helmet-camera-mount-action-camera/> (21 pages). cited by applicant

Ride 509. Universal Helmet Camera Mount product page, <https://ride509.com/products/universal-helmet-camera-mount>, available online at least as early as Jan. 18, 2021, 11 pages. cited by applicant

Whitted, E. How to mount an action camera on a helmet. Oct. 2, 2019, available online at <https://myactionreviews.com/how-to-mount-an-action-camera-on-a-helmet/> (8 pages). cited by applicant

European Patent Office Extended European Search Report for application 22175924.4, dated Oct.

24, 2022 (8 pages). cited by applicant
European Patent Office Extended European Search Report for application 22175926.9, dated Oct. 24, 2022 (8 pages). cited by applicant
DHGate. Lightweight Tactical Crashworthy Protective Helment Head Protector Face Mask Outdoor Cycling Helmets for CS Paintball Game product page. Available at least as early as Feb. 11, 2021 at <<https://www.dhgate.com/product/lightweight-tactical-crashworthy-protective/415570974.html>> (9 pages). cited by applicant
Vicis Inc. Manufacturing impact absorbing structures for an athletic helmet. Jan. 5, 2017. Available online at <<https://patents.justia.com/patent/10342283>> (17 pages). cited by applicant
European Patent Office Action for Application No. 22175924.4 dated Aug. 14, 2024 (4 pages). cited by applicant

Primary Examiner: Moran; Katherine M

Attorney, Agent or Firm: Michael Best & Friedrich LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Application No. 63/194,738, filed May 28, 2021, the entire contents of which are incorporated herein by reference.

BACKGROUND

(1) The present disclosure relates generally to the field of helmets and specifically to a bicycle helmet having impact absorbing structures. The present disclosure also relates generally to the field of bicycle helmets and specifically to a system for adjusting the fit of a bicycle helmet. The present disclosure also relates generally to the field of bicycle helmets and specifically to a system for mounting items to a bicycle helmet.

(2) Bicycle helmets commonly include a hard outer shell, an impact absorbing inner shell, and a fit system that secures the helmet to a rider's head. The inner shell is made of an energy-absorbing material. The fit system often includes one or more adjustable straps that are designed to wrap around at least a portion of a rider's head. An adjustment mechanism can be used to adjust the straps to the size of the rider's head.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of a bicycle helmet according to an embodiment, including an accessory coupled to the helmet.
- (2) FIG. 2 is a perspective, exploded view of the bicycle helmet of FIG. 1.
- (3) FIG. 3 is a perspective, exploded view of a portion of the bicycle helmet of FIG. 1 illustrating a mounting structure and an accessory mount.
- (4) FIG. 4 is a cross-sectional view of a portion of the bicycle helmet of FIG. 1 taken along line 4-4 in FIG. 1 and illustrating the accessory mount coupled to the mounting structure.
- (5) FIG. 5 is a perspective view of the bicycle helmet of FIG. 1 with the accessory mount removed and a removable panel covering the mounting structure.
- (6) FIG. 6 is a perspective, exploded view of a portion of the bicycle helmet of FIG. 5 illustrating the mounting structure and the removable panel in an exploded position.

- (7) FIG. 7 is a cross-sectional view of a portion of the bicycle helmet of FIG. 5 taken along line 7-7 in FIG. 5 illustrating the removable panel coupled to the helmet.
- (8) FIG. 8 is a perspective view of the accessory mount.
- (9) FIG. 9 is a cross-sectional view of the accessory mount.
- (10) FIG. 10 is a perspective view of a bicycle helmet according to an embodiment, including an adjusting assembly coupled to the helmet.
- (11) FIG. 11 is a rear view of the bicycle helmet of FIG. 10, illustrating an adjusting input of the adjusting assembly positioned within a vent of the helmet.
- (12) FIG. 12 is a front view of the bicycle helmet of FIG. 10 illustrating the adjusting assembly.
- (13) FIG. 13 is an isolated front view of the adjusting assembly of FIG. 12.
- (14) FIG. 14 is an isolated rear view of the bicycle helmet of FIG. 10 illustrating the adjusting assembly.
- (15) FIG. 15 is a cross-sectional view of a portion of the bicycle helmet of FIG. 10 taken along line 15-15 in FIG. 10 and illustrating the adjusting assembly.
- (16) FIG. 16 is a perspective view of a bicycle helmet according to an embodiment, including an accessory mounted to the helmet, an adjusting assembly coupled to the helmet, and multiple impact absorbing structures.
- (17) FIG. 17 is a perspective, exploded view of the bicycle helmet of FIG. 16 illustrating the multiple impact absorbing structures.
- (18) FIG. 18A is a side, cross-sectional view the bicycle helmet of FIG. 16 about the line 18-18 in FIG. 16, illustrating an interface of a rear impact absorbing structure with an upper impact absorbing structure and an outer shell of the helmet.
- (19) FIG. 18B is an enlarged, partial cross-sectional view of the bicycle helmet in FIG. 18A, illustrating an intermediate layer positioned between the impact absorbing structure and the outer shell of the helmet.
- (20) FIG. 19 is a side, cross-sectional view of the bicycle helmet of FIG. 16 about the line 19-19 in FIG. 16, illustrating an interface of the upper impact absorbing structure with the outer shell of the helmet.
- (21) FIG. 20 is a front, cross-sectional view the bicycle helmet of FIG. 16 about the line 20-20 in FIG. 16, illustrating an interface of a left and a right impact absorbing structure with the outer shell of the helmet and the upper impact absorbing structure.
- (22) FIG. 21 is a front, cross-sectional view the bicycle helmet of FIG. 16 about the line 21-21 in FIG. 16, illustrating an interface of a chin strap impact absorbing structure with the outer shell of the helmet and the left and the right impact absorbing structures.
- (23) FIG. 22 is a top, cross-sectional view the bicycle helmet of FIG. 16 about the line 22-22 in FIG. 16, illustrating an interface of the rear impact absorbing structure with the left and the right impact absorbing structures.

DETAILED DESCRIPTION

(24) Before any embodiments are explained in detail, it is to be understood that the present disclosure is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The disclosure is capable of other embodiments and of being practiced or of being carried out in various ways.

(25) According to an exemplary embodiment, a helmet comprises an outer shell having an interior and an exterior and an impact absorbing layer positioned on the interior of the outer shell. The impact absorbing layer comprises a first impact absorbing structure having a first interface and a second impact absorbing structure having a second interface in lateral compression against the first interface.

(26) According to another exemplary embodiment, a helmet comprises an outer shell having a first receiving portion and an impact absorbing layer positioned on an interior side of the outer shell.

The impact absorbing layer comprises an impact absorbing structure having a first engagement portion and a second engagement portion spaced from the first engagement portion. The impact absorbing structure is mechanically secured to the outer shell by the first engagement portion engaging the first receiving portion and the second engagement portion engaging a second receiving portion spaced from the first receiving portion.

(27) According to another exemplary embodiment, a method of assembling a helmet from an outer shell and multiple impact absorbing structures comprises securing by lateral compression a first impact absorbing structure with the outer shell. The securing by lateral compression the first impact absorbing structure with the outer shell comprises contacting the first impact absorbing structure with the outer shell deflecting a first deflecting portion of at least one of the first impact absorbing structure or the outer shell from a static position to a deflected position, moving the first impact absorbing structure further toward the outer shell, and relaxing the first deflecting portion back from the deflected position toward the static position to mechanically secure the first impact absorbing structure in the outer shell.

(28) According to another exemplary embodiment, a bicycle helmet comprises a helmet body adapted to cover at least a portion of a rider's head. The helmet body including a wall portion and a vent extending through the wall portion from an exterior of the helmet body to an interior of the helmet body. An adjusting assembly is provided for adjustably securing the helmet to a user's head. The adjusting assembly includes an adjusting input movable to adjust a size of the helmet. The adjusting input is positioned at least partially in the vent.

(29) According to another exemplary embodiment, a bicycle helmet comprises a helmet body adapted to cover at least a portion of a rider's head. The helmet body comprises a mounting structure adapted to mount an accessory, and a visor coupled to the helmet body. The visor comprises a main body and a removable panel removably secured to the main body and positioned to cover the mounting structure. The helmet body may include an impact-absorbing layer, wherein the mounting structure is recessed in the impact-absorbing layer. The helmet body may include an outer shell covering at least a portion of the impact-absorbing layer, and the outer shell may include a shell opening aligned with the mounting structure. The removable panel of the visor may be aligned with the shell opening in the outer shell. The helmet body may have an outer surface adjacent the mounting structure, the outer surface defining a tangential plane, and the mounting structure may include an upper mount portion having an upper width parallel to the tangential plane, and a lower mount portion having a lower width parallel to the tangential plane, the lower width being larger than the upper width. The mounting structure may include a plurality of spaced-apart finger portions connecting the upper mount portion to the lower mount portion. The visor may include a visor opening aligned with the mounting structure, the visor opening being substantially covered by the removable panel. The visor may include a recessed ledge around at least a portion of the visor opening, the recessed ledge supporting the removable panel. An upper surface of the removable panel may be substantially flush with an upper surface of the main body of the visor.

(30) According to another exemplary embodiment, a bicycle helmet comprises a helmet body adapted to cover at least a portion of a rider's head. The helmet body comprises a mounting structure adapted to mount an accessory, a visor coupled to the helmet body, and an accessory mount adapted to support the accessory. The visor comprises a main body and a visor opening aligned with the mounting structure. The accessory mount is positioned at least partially in the visor opening and engaged with the mounting structure. The helmet body may include an impact-absorbing layer, and the mounting structure may be recessed in the impact-absorbing layer. The helmet body may include an outer shell covering at least a portion of the impact-absorbing layer, and the outer shell may include a shell opening aligned with both the mounting structure and the visor opening. The visor may include a recessed ledge around at least a portion of the visor opening, the recessed ledge supporting at least a portion of the accessory mount. The accessory

mount may include an upper surface that is substantially flush with an upper surface of the main body of the visor. The accessory mount may include a ledge extending upward from the upper surface. The accessory mount may include an elongated track and an adjustable mount movable relative to the elongated track. The adjustable mount may include a pawl movable between an engaged position that inhibits movement of the adjustable mount relative to the elongated track and a disengaged position that permits movement of the adjustable mount relative to the elongated track. The elongated track may include a plurality of recesses that are spaced along a longitudinal direction of the elongated track. The pawl of the adjustable mount may be sized to engage with one of the recesses of the elongated track to secure the adjustable mount in the engaged position. The helmet body may have an outer surface adjacent the mounting structure, the outer surface defining a tangential plane, and the mounting structure may include an upper mount portion having an upper width parallel to the tangential plane, and a lower mount portion having a lower width parallel to the tangential plane, the lower width being larger than the upper width.

(31) Referring now to an illustrated embodiment, FIG. 1 illustrates a bicycle helmet 10 having a helmet body 14 adapted to cover at least a portion of a rider's head, a visor 18 coupled to the helmet body 14, and an accessory mount 22 coupled to the helmet body 14 to support an accessory 26 (e.g., a camera, a light, etc.). The visor 18 includes a main body 20 that may be coupled to the helmet body 14 via a standard connection method (e.g., fasteners, a protrusion that engages a recess in the helmet body 14, etc.).

(32) As illustrated in FIG. 4, the helmet body 14 may include an impact absorbing layer 30 and an outer shell 34 covering the impact absorbing layer 30. The impact absorbing layer 30 may be formed of a material such as expanded polystyrene (EPS) or the like. The outer shell 34 may be formed of a material such as polycarbonate, carbon fiber, or the like.

(33) As illustrated in FIGS. 2 and 4, the outer shell 34 may have an outer surface 44 (FIG. 4). The outer surface 44 may define a tangential plane 46 (FIG. 4) and include a shell opening 38 that is sized to receive a mounting structure 42. The mounting structure 42 may be positioned within the shell opening 38 (e.g., adjacent the outer surface 44) and may be recessed in the impact absorbing layer 30. In the illustrated embodiment, the mounting structure 42 includes an upper mount portion 50 having an upper width W1 (FIG. 2) parallel to the tangential plane 46 and a lower mount portion 54 having a lower width W2 (FIG. 2) parallel to the tangential plane 46. The lower width W2 is larger than the upper width W1. In the illustrated embodiment, the upper and lower mount portions 50, 54 have an octagonal shape. In other embodiments, the upper and lower mount portions 50, 54 may have an alternative geometry (e.g., circular, rectangular, etc.). In the illustrated embodiment, the mounting structure 42 further includes a plurality of spaced-apart finger portions 58 extending between and connecting the upper and lower mount portions 50, 54. In other embodiments, the mounting structure 42 may include, for example, a continuous structure extending between the upper and lower mount portions 50, 54.

(34) With reference to FIGS. 2-4, the visor 18 may include a visor opening 62 aligned with the shell opening 38 and the mounting structure 42. Such positioning of the visor opening 62 facilitates access to the mounting structure by the accessory mount 22. In the illustrated embodiment, the visor 18 further includes a recessed ledge 78 around at least a portion of the visor opening 62.

(35) The accessory mount 22 may at least partially extend through the visor opening 62 and engage with the mounting structure 42 to secure the accessory mount 22 to the helmet body 14. In the illustrated embodiment, the accessory mount 22 includes an elongated track 66, an adjustable mount 70 that is movable relative to the elongated track 66, and a fastener assembly 74 that secures the accessory 26 to the adjustable mount 70. The elongated track 66 may include a securing structure 76 (FIG. 3) formed on a lower surface of the elongated track 66 that engages the upper mount portion 50. In the illustrated embodiment, the securing structure 76 includes a plurality of segmented structures (e.g., detents) that form a heptagonal shape and selectively engage the upper mount portion 50 (FIG. 4) to secure the elongated track 66 to the helmet body 14. Other

embodiments may include other securing structures, including other numbers and arrangements of segmented structures than that illustrated. When engaged with the mounting structure **42**, a portion of the elongated track **66** is positioned in a recess formed by the recessed ledge **78** of the visor, and thus the recessed ledge **78** supports at least a portion of the accessory mount **22** (e.g., a portion of the elongated track **66**). When the elongated track **66** of the accessory mount **22** is secured to the helmet body **14**, an upper surface **82** of the accessory mount **22** may be substantially flush with an upper surface **84** of the main body **20** of the visor **18**. In the illustrated embodiment, the elongated track **66** includes a ledge **86** extending from the upper surface **82**. During removal of the elongated track **66** from the mounting structure **42**, the user may provide a force on the ledge **86**, which deforms the securing structure **76** and moves the securing structure **76** out of engagement from the recessed ledge **78**. Alternatively, for example, the user may grasp an opposing, free end of the elongated track **66** and pivot the elongated track **66** upwards (e.g., away from the helmet body **14**) to remove the elongated track **66** from the mounting structure **42**.

(36) Referring to FIGS. **4**, **8**, and **9**, the elongated track **66** may include rail portions **88** extending from the upper surface **82** and spaced from each other to define a receiving channel **90** that selectively receives the adjustable mount **70**. The receiving channel **90** may include a plurality of recesses **94** that are sized to receive a pawl **98** of the adjustable mount **70**. In the illustrated embodiment, the recesses **94** are spaced from each other in a longitudinal direction of the elongated track **66** so the adjustable mount **70** can be positioned in a plurality of positions with respect to the elongated track **66**. The pawl **98** of the adjustable mount **70** is movable between an engaged position, where the pawl **98** engages one of the recesses **94** (FIGS. **4** and **9**), that inhibits movement of the adjustable mount **70** relative to the elongated track **66** and a disengaged position, where the pawl **98** is disengaged with the recesses **94**, that permits movement of the adjustable mount **70** relative to the elongated track **66**.

(37) The adjustable mount **70** may include an extension **102** coupled to the pawl **98**. In the illustrated embodiment, the extension **102** has a half-circle geometry and extends upward between the rail portions **88** of the elongated track **66**. The extension **102** is designed to be pivoted relative to the elongated track **66** (e.g., in the direction **106**), which causes the pawl **98** to disengage from the recesses **94**. Other embodiments may include shapes other than the half-circle shape illustrated.

(38) With continued reference to FIGS. **4** and **8**, the adjustable mount **70** may further include mounting portions **110** that are spaced from the pawl **98**. In the illustrated embodiment, the mounting portions **110** each include an aperture **114** sized to receive the fastener assembly **74** (FIGS. **1** and **2**) to secure the accessory **26** to the adjustable mount **70**. The accessory **26** includes a connection portion **116** that has an aperture that is designed to be aligned with the apertures **114**. In the illustrated embodiment, the fastener assembly **74** includes a bolt **118** that extends through the apertures **114** of the mounting portions **110** and the connection portion **116** and a nut **120** that engages the bolt **118**.

(39) Referring to FIGS. **5-7**, the helmet **10** may further include a removable panel **122** that can be removably secured to the main body **20** of the visor **18** in place of the accessory mount **22**. The removable panel **122** provides a cover for the visor opening **62** when the accessory mount **22** is not being used. The removable panel **122** may include a connection structure **126** (e.g., lip or groove, etc.) formed on a lower surface **128** of the panel **122** that is sized to engage with the recessed ledge **78** formed around the visor opening **62** (e.g., such that the recessed ledge **78** supports the removable panel **122**). In other embodiments, the removable panel **122** may be secured to the helmet through engagement with the mounting structure **42**. When the removable panel **122** is secured to the helmet **10**, an upper surface **130** (FIG. **7**) of the removable panel **122** may be substantially flush with the upper surface **84** of the main body **20** of the visor **18**. In some embodiments, the removable panel **122** may include a feature (e.g., recess formed on the upper surface **130** or a ledge (or other protrusion) that extends upwards from the upper surface **130**) for the user to grasp or otherwise engage during removal of the panel **122**.

(40) During use, the removable panel **122** may be coupled to the recessed ledge **78** of the visor **18** to cover the mounting structure **42** and enclose the visor opening **62**. In order to secure the accessory mount **22** to the helmet **10**, the removable panel **122** may be disengaged from the recessed ledge **78** to provide access to the mounting structure **42**. The accessory mount **22** may then be attached to the mounting structure **42** through the visor opening **62**. In the illustrated embodiment, the securing structure **76** of the elongated track **66** extends through the visor opening **62** and engages the upper mount portion **50** of the mounting structure **42**. The adjustable mount **70** may be inserted within the receiving channel **90** of the elongated track **66** and moved to a desired position. For example, the user may grasp the extension **102** and pivot the extension **102** and the pawl **98** relative to the elongated track **66** (e.g., in the direction **106**). When the adjustable mount **70** is in a desired position, the extension **102** may be released so the pawl **98** engages with one of the recesses **94**, which inhibits movement of the adjustable mount **70** relative to the elongated track **66**. To remove the accessory mount **22**, the user may grasp the ledge **86** to disengage the securing structure **76** of the elongated track **66** from the mounting structure **42**. Once the accessory mount **22** is removed, the removable panel **122** may be coupled to the recessed ledge **78** of the visor **18** to cover the mounting structure **42** and enclose the visor opening **62**.

(41) FIGS. **10-15** illustrate a bicycle helmet **210**. The bicycle helmet **210** is like the bicycle helmet **10** shown in FIGS. **1-9** and described above. Therefore, like features are identified with like reference numerals plus “200”, and only the differences between the two will be discussed.

(42) The bicycle helmet **210** includes a helmet body **214** adapted to cover at least a portion of a rider's head. The helmet body **214** may include a wall portion **215** having an impact absorbing layer **230** (FIG. **15**) and an outer shell **234** covering the impact absorbing layer **230**. In the illustrated embodiment, the helmet body **214** includes a lower portion **217** (FIG. **12**) that encloses an interior portion of the helmet **210** and that may provide up to 360-degree protection for the rider's head (e.g., around the user's chin). In other embodiments the lower portion **217** does not extend around a user's chin. As illustrated in FIGS. **10-15**, one or more vents **219** may extend through the wall portion **215** from an exterior of the helmet body **214** to the interior of the helmet body **214**. The vents **219** may be defined at least partially by one or more vent surfaces **223** that extend between the interior and exterior of the helmet body **214**. In the illustrated embodiment, a vent **219** is positioned along a rear portion of the helmet and above a drip line **221** (i.e., the lowest line of coverage of the helmet **210** as seen in FIGS. **14** and **15**). A vent surface **223** defines an outer boundary of the vent **219** and at least partially encloses each side of the vent **219**. In the illustrated embodiment, the vent **219** has a generally rectangular cross-sectional shape (FIG. **13**), although embodiments may include shapes and sizes other than that illustrated.

(43) With reference to FIG. **12**, an adjusting assembly **225** may be positioned at least partially in the vent **219** and positioned above the drip line **221** of the helmet **210**. The adjusting assembly **225** may be used to decrease or increase an internal volume of the helmet **210** to create a tighter or looser fit. In the illustrated embodiment, the adjusting assembly **225** includes an adjusting input **227** coupled to a strap member **229** that is positioned within the helmet body **214** to wrap at least partially around a user's head. The adjusting input **227** may be fixed to the helmet body **214** and may include, for example, a rotating dial **231** that is coupled to the helmet body **214**. In some embodiments, the adjusting input **227** is embedded at least partially within the impact absorbing layer **230** and is positioned within the vent **219** on a rear, lower portion (FIG. **11**) of the helmet body **214**. In other embodiments, the adjusting input **227** may be coupled to the helmet body **214** in an alternative fashion (e.g., via a fastener), may be located outside of the impact absorbing layer **230**, or the like. A portion **228** of the strap member **229** may be coupled to the adjusting input **227** and may be adjustable relative to the helmet body **214** via the adjusting input **227**. In the illustrated embodiment, rotation of the dial **231** of the adjusting assembly **225** causes the strap member **229** to displace, which may cause a change in the shape of an internal volume defined by the helmet **210** (e.g., to tighten or loosen the helmet on the user's head). In some embodiments, the dial **231** may be

coupled to the portion **228** of the strap member **229** in a similar fashion as the adjustment mechanisms described in U.S. Pat. No. 8,015,625 filed on May 6, 2009 or U.S. Pat. No. 10,420,385 filed on, Apr. 25, 2014, the entire contents of which are incorporated herein by reference.

(44) With reference to FIGS. **13-15**, the vent surface **223** may define a lower vent surface **233**, an upper vent surface **237**, and side vent surfaces **241**, which together at least partially enclose the vent **219**. The upper vent surface **237** may be angled relative to the lower vent surface **233** (FIG. **15**). For example, the upper vent surface **237** may taper toward the lower vent surface **233** as the upper vent surface **237** extends from the exterior of the helmet body **214** toward the interior of the helmet body **214**. The lower vent surface **233** may taper toward the upper vent surface **237** as the lower vent surface **233** extends from the exterior of the helmet body **214** toward the interior of the helmet body **214**. The upper vent surface **237** may also at least partially define a recess **245** (FIGS. **13** and **15**) that is sized to receive at least a portion of the adjusting input **227** of the adjusting assembly **225**. In some embodiments, the recess **245** is a recess located within the impact absorbing layer **230**. In some embodiments, the recess **245** may be positioned on the lower vent surface **233** or the side vent surface **241**. It should be appreciated that in some embodiments the recess **245** may be considered a portion of, or extension of, the vent **219**.

(45) With reference to FIGS. **12**, **13**, and **15**, the adjusting assembly **225** may include an adjusting housing **249** that may rotationally support the rotating dial **231** of the adjusting input **227** and may be at least partially (e.g., fully) positioned within the recess **245**. The dial **231** may have a plurality of protrusions **251** spaced circumferentially around the dial **231**. In the illustrated embodiment, the protrusions **251** define surfaces for the user to grasp during rotation of the dial **231**. As illustrated in FIG. **13**, the dial **231** may have a diameter **D1** defined between opposing protrusions on the dial **231**. The dial **231** may further have a first portion (e.g., that is disposed within the housing **249**) defined by a length **L1**, a second, recessed portion (e.g., that is disposed outside of the housing **249** and within the recess **245**) defined by a length **L2**, and a third, exposed portion (e.g., that is disposed outside of the housing **249**) defined by a length **L3**. In the illustrated embodiment, the first portion of the dial **231** is positioned within the adjusting housing **249**, the second, recessed portion is positioned within the recess **245**, and the third, exposed portion is positioned within the vent **219** (FIG. **14**). In other words, only a small portion of the dial **231** is visible when the helmet **210** is viewed from the rear (FIG. **14**). In other embodiments, the second and third portions of the dial **231** may together form a single exposed portion that is visible from a rear view of the helmet **210**. In yet other embodiments, the dial **231** may include no portions that are exposed within the vent **219** from a rear view (FIG. **14**) of the helmet. Rather, the entire dial **231** may be hidden or otherwise blocked from view when viewing the helmet **210**.

(46) In some embodiments, the length **L1** of the first portion of the dial **231** is in a range of 60%-75% of the diameter **D1** of the dial **231**. The length **L2** of the second, recessed portion of the dial **231** is in a range of 5%-30% of the diameter **D1**. The length **L3** of the third, exposed portion of the dial **231** is in a range of 1%-15% of the diameter **D1**. In the illustrated embodiment, the length **L1** of the first portion is approximately 70% of the diameter **D1**, the length **L2** of the second, recessed portion is approximately 20% of the diameter **D1**, and the third, exposed portion is approximately 10% of the diameter **D1**. In some embodiments, only the protrusions **251** may form the third, exposed portion. In some embodiments, and as described above, the second and third portions of the dial **231** may together form a single exposed portion of the dial **231** that is positioned and visible within the vent **219** from a rear view of the helmet **210**. In some embodiments, the overall exposed portion of the dial **231** may be in a range of 10%-40% of the diameter **D1**.

(47) FIGS. **16-22** illustrate a bicycle helmet **310**. The bicycle helmet **310** is like the bicycle helmet **10** shown in FIGS. **1-9** and described above and the bicycle helmet **210** shown in FIGS. **10-15** and described above. Therefore, like features are identified with like reference numerals plus “300”, and only the differences between the two will be discussed.

(48) The bicycle helmet **310** includes a helmet body **314** adapted to cover at least a portion of a rider's head. The helmet body **314** may include an impact absorbing layer **330** (FIG. 17) and an outer shell **334** covering the impact absorbing layer **330**. The outer shell **334** may define an upper wall **401**, a rear wall **403**, a left wall **405**, and a right wall **407** (FIG. 20). In the illustrated embodiment, the helmet body **314** includes a lower (e.g., chin strap) portion **317** that encloses an interior portion of the helmet **310** and that may provide up to 360-degree protection for the rider's head (e.g., around the user's chin). In other embodiments, the helmet **310** may be devoid of the lower portion **317**, similar to the helmet **10**. The illustrated helmet **310** further includes a visor **318** coupled to the helmet body **314**, an accessory mount **322**, and an adjusting assembly **325**. The accessory mount **322** extends through a visor opening **362** in the visor **318** and engages with a mounting structure **342** positioned within a shell opening **338** to support an accessory **326** (e.g., a camera, a light, etc.), similar to the accessory mount **22** described above with reference to FIGS. 1-9. The adjusting assembly **325** may be positioned at least partially in a vent **319**, positioned above a drip line **321** of the helmet **310**, and may be used to decrease or increase an internal volume of the helmet **210** to create a tighter or looser fit, similar to the adjusting assembly **225** described above with reference to FIGS. 10-15. In other embodiments the helmet **310** may not include the visor **318**, the accessory mount **322**, the adjusting assembly **325**, and/or the impact absorbing layer **330**.

(49) With reference to FIG. 17, in the illustrated embodiment the impact absorbing layer **330** includes a plurality of impact absorbing structures **411**, **415**, **419**, **423**, **427** that are coupled together (e.g., via lateral compression). As illustrated in FIGS. 17-22, the impact absorbing layer **330** may include a rear impact absorbing structure **411**, a left impact absorbing structure **415**, a right impact absorbing structure **419**, an upper impact absorbing structure **423**, and/or a lower, chin strap impact absorbing structure **427**. In other embodiments, the impact absorbing layer **330** may be formed of more impact absorbing structures (e.g., 6, 7, etc.) or less impact absorbing structures (e.g., 4, 3, 2). Each impact absorbing structure **411**, **415**, **419**, **423**, **427** includes at least one interface that interacts with an interface of an adjacent impact absorbing structure through lateral compression to form the overall impact absorbing layer **330**. It should be appreciated that such lateral compression may be formed by applying a compressive force and/or pressing one or more of the impact absorbing structures **411**, **415**, **419**, **423**, **427** laterally against an adjacent impact absorbing structure to secure the impact absorbing structures **411**, **415**, **419**, **423**, **427** together in a compressed state to form the overall impact absorbing layer **330**.

(50) With continued reference to FIG. 17, in some embodiments an additional connection structure **431** may extend between adjacent impact absorbing structures **411**, **415**, **419**, **423**, **427** to additionally mechanically secure the impact absorbing structures **411**, **415**, **419**, **423**, **427** together. In the illustrated embodiment, the additional connection structure **431** is arcuately shaped and engages a groove formed in each of the upper, left, and right impact absorbing structures **423**, **415**, **419** to form a snap-fit arrangement that helps to rigidly secure the impact absorbing structures **423**, **415**, **419** together. Other embodiments may include other types of additional connection structures **431** (e.g., straps, snaps, fasteners, etc.), or may include no additional connection structures **431**. In addition, in some embodiments additional connection structures **431** may be used to secure the rear impact absorbing structure **411** and the chin strap impact absorbing structure **427** to the upper, left, and right impact absorbing structures **423**, **415**, **419**. In some embodiments, and as noted above, the impact absorbing structures **411**, **415**, **419**, **423**, **427** may all be held together without any additional connection structures (e.g., may be held together entirely through lateral compression).

(51) With reference to FIGS. 18A-22, the impact absorbing structures **411**, **415**, **419**, **423**, **427** may be secured to various receiving portions formed in the helmet body **314**. The receiving portions may include, for example, one or more vents **319** formed in the outer shell **334**, one or more recesses formed in the outer shell **334** (e.g. indentations or other recessed areas along an interior of the helmet **310** that do not extend entirely through the outer shell **334**), and/or one or more recesses formed in an intermediate layer or inner shell **435** (FIG. 18B) positioned between the impact

absorbing layer **330** and the outer shell **334**. The vents **319** may be defined at least partially by one or more vent surfaces **323** that extend between the interior and exterior of the helmet body **314** and include a vent edge **324** (FIG. **18A**). The recesses formed in the inner shell **435** or the outer shell **334** may only extend partially between the interior and exterior of the helmet body **314**. As such, it should be appreciated that a receiving portion formed in the helmet body **314** may encompass any of the embodiments described above.

(52) With reference to FIGS. **18A** and **19**, in the illustrated embodiment the upper impact absorbing structure **423** includes a first interface **439** (e.g., lateral surface) and the rear impact absorbing structure **411** includes a second interface **443** (e.g., lateral surface) that is in lateral compression against the first interface **439**. The upper impact absorbing structure **423** further includes a first engagement portion **447** (FIG. **19**) and the rear impact absorbing structure **411** includes a second engagement portion **451** (FIG. **18A**) that engage respective receiving portions (e.g., vents) formed in the helmet body **314**. The upper impact absorbing structure **423** also engages a first supporting structure **441** formed by the outer shell **334** and the rear impact absorbing structure **411** engages a second supporting structure **445** formed by the outer shell **334**. In the illustrated embodiment, first and second supporting structures **441**, **445** are each formed as inwardly extending lips on the outer shell **334**. The first engagement portion **447** of the upper impact absorbing structure **423** may engage the vent edge **324** of the vent **319** formed in the upper wall **401** of the outer shell **334**, and/or a front portion of the upper impact absorbing structure **423** may engage the first supporting structure **441**. The second engagement portion **451** of the rear impact absorbing structure **411** may engage the vent edge **324** of the vent **319** formed in the rear wall **403** of the outer shell **334**, and/or a lower portion of the rear impact absorbing structure **411** may engage the second supporting structure **445**.

(53) The upper impact absorbing structure **423** may be held in lateral compression (e.g., between the first interface **439** and the first engagement portion **447** and/or between the first interface **439** and the first supporting structure **441**). In the illustrated embodiment, the first and second engagement portions **447**, **451** are mechanically secured to the outer shell **334** (e.g., via a snap fit connection) at the vents **319** along the top and rear of the helmet **310**. The combination of the connection of the upper and rear impact absorbing structures **423**, **411** via the engagement portions **447**, **451** and/or the supporting structures **441**, **445** secures the upper and rear impact absorbing structures **423**, **411** to the outer shell **334** and promotes the lateral compression between the interfaces **439**, **443**. In some embodiments, the first and second engagement portions **447**, **451** of the rear and upper impact absorbing structures **411**, **423** may be secured to the outer shell **334** by mechanically securing the first and second engagement portions **447**, **451** to the outer shell **334** in other ways.

(54) In some embodiments, the upper and rear impact absorbing structures **423**, **411** may be coupled to the outer shell **334** and may be held in compression against one another at the interfaces **439**, **443** solely via the contact of the upper and rear impact absorbing structures **423**, **411** with the first and second supporting structures **441**, **445** (e.g., lips of the outer shell), without the aid of the engagement portions **447**, **451**.

(55) With reference to FIG. **18B**, in the illustrated embodiment the inner shell **435**, or a portion thereof, may be secured to an outer surface of the rear impact absorbing structure **411**, and in some embodiments may be formed as part of the rear impact absorbing structure **411** (e.g., may be co-molded with the rear impact absorbing structure **411**). Each of the impact absorbing structures may thus include its own inner shell **435** (e.g., outer layer). In the illustrated embodiment, for example, the rear impact absorbing structure **411** may include an energy-absorbing layer having a first density and the inner shell **435** may be formed of a material that has a higher density than the energy absorbing layer. For example, the energy-absorbing layer may be formed of expanded polystyrene and the inner shell **435** may be formed of polycarbonate. The inner shell **435** may form part of the engagement portion **451**, which may engage the vent edge **324** to help secure the inner

shell **435** and the impact absorbing structure **411** to the outer shell **334**. The rear impact absorbing structure **411** may be coupled to the outer shell **334** via the inner shell **435**.

(56) In some embodiments, one or more of the impact absorbing structures (along for example with its associated inner shell **435**) may not be directly adhered or directly mechanically fastened to the outer shell **334**. In some embodiments, the impact absorbing structure (along for example with its inner shell **435**) may not be indirectly adhered or indirectly mechanically fastened to the outer shell **334**. The impact absorbing structures, such as the rear impact absorbing structure **411**, may be removable from the outer shell **334**. In addition, it should be appreciated that one or more of the remaining impact absorbing structures **415**, **419**, **423**, **427** may have a similar construction as the rear impact absorbing structure **411** illustrated in FIG. **18B** (e.g., may be formed of both an expanded polystyrene layer, as well as an outer polycarbonate layer).

(57) With reference to FIGS. **20** and **22**, in the illustrated embodiment the left impact absorbing structure **415** may include for example a third interface **455** and the right impact absorbing structure **419** may include a fourth interface **459**. The third and fourth interfaces **455**, **459** may each be in lateral compression against the first interface **439** of the upper impact absorbing structure **423** (FIG. **20**) and the second interface **443** of the rear impact absorbing structure **411** (FIG. **22**). The left impact absorbing structure **415** may further include a third engagement portion **463** and the right impact absorbing structure **419** may include a fourth engagement portion **467** that are sized to engage respective receiving portions (e.g., vents) formed in the helmet body **314**. The left and right impact absorbing structure **415**, **419** may engage third and fourth supporting structures **453**, **457** formed by the outer shell **334**. The third engagement portion **463** may engage the vent edge **324** of the vent **319** formed in the left wall **405** of the outer shell **334** and third supporting structure **453**. The fourth engagement portion **467** may engage the vent edge **324** of the vent **319** formed in the right wall **407** of the outer shell **334** and the fourth supporting structure **457**. The left impact absorbing structure **415** may be held in lateral compression between the first interface **439**, the third engagement portion **463**, and/or the third supporting structure **453**. The right impact absorbing structure **419** may be held in lateral compression between the first interface **439**, the fourth engagement portion **467**, and/or the fourth supporting structure **457**. In the illustrated embodiment, the third and fourth engagement portions **463**, **467** may be mechanically secured to the outer shell **334** (e.g., via a snap fit connection).

(58) With reference to FIG. **21**, the lower impact absorbing structure **427** may include a fifth interface **471** that is in lateral compression against each of the third and fourth interfaces **455**, **459** of the left and right impact absorbing structures **415**, **419**. The lower impact absorbing structure **427** may further include a fifth engagement portion **475** that engages a receiving portion (e.g., vent) formed in the lower portion **317** of the helmet body **314**. The fifth engagement portion **475** may engage the vent edge **324** of the vent **319** formed in the left wall **405** of the outer shell **334** and the vent edge **324** of the vent **319** formed in the right wall **407** of the outer shell **334**. A lower portion of the lower impact absorbing structure **427** may engage a fifth supporting structure **473** (e.g., lower lip) formed in the left and right wall **405** of the outer shell **334**. The lower impact absorbing structure **427** may be held in lateral compression between the third and fourth interfaces **455**, **459**, the fifth engagement portion **475** and/or the fifth supporting structure **473**. In the illustrated embodiment, the fifth engagement portion **475** may be mechanically secured to the outer shell **334** (e.g., via a snap fit connection).

(59) In some embodiments, during assembly of the helmet **310**, two or more of the impact absorbing structures **411**, **415**, **419**, **423**, and/or **427** may be secured to the outer shell **334** of the helmet body **314** at least in part through compressing the impact absorbing structures **411**, **415**, **419**, **423**, and/or **427** and placing them into lateral compression with one another within the helmet **310**. While the installation of the impact absorbing structures **411**, **415**, **419**, **423**, **427** are described in a sequential order below, it should be appreciated that the impact absorbing structures **411**, **415**, **419**, **423**, **427** may be installed within the helmet body **314** in any order.

(60) With reference to FIG. 19, the upper impact absorbing structure 423 may be secured to the outer shell 334. For example, the front portion of the upper impact absorbing structure 423 may be moved towards and engage the first supporting structure 441 of the outer shell 334. A first deflecting portion of at least one of the upper impact absorbing structure 423 or the outer shell 334 may be deflected from a static position to a deflected position. In some embodiments, the vent edge 324 of the outer shell 334, a recess in the helmet body 314, the first supporting structure 441, the engagement portion 447, or the inner shell 435 (FIG. 18A) of the impact absorbing structure 423 itself may form the first deflecting portion. After deflecting the first deflecting portion, the upper impact absorbing structure 423 may be moved further towards the outer shell 334 and the first deflecting portion may be relaxed back from the deflected position toward the static position. In some embodiments, with the front portion of the upper impact absorbing structure 423 engaged with the first supporting structure 441, the first engagement portion 447 of the upper impact absorbing structure 423 may then contact the vent edge 324 formed in the upper wall 401 of the outer shell 334 to further secure the upper impact absorbing structure in place.

(61) With reference to FIG. 18A, in some embodiments the rear impact absorbing structure 411 may then be inserted and laterally compressed against the upper impact absorbing structure 423 (e.g., at the interfaces 439, 443). For example, the lower portion of the rear impact absorbing structure 411 may be moved toward and engage the second supporting structure 445 of the outer shell 334. A second deflecting portion of at least one of the rear impact absorbing structure 411 or the outer shell 334 may be deflected from a second static position to a second deflected position. After deflecting the second deflecting portion, the rear impact absorbing structure 411 may be moved further toward the outer shell 334 and the second deflecting portion may be relaxed back from the second deflected position toward the second static position. In some embodiments, with the lower portion of the rear impact absorbing structure 411 engaged with the second supporting structure 445, the second engagement portion 451 of the rear impact absorbing structure 411 may then be moved to contact the vent edge 324 formed in the rear wall 403 of the outer shell 334 and the lower portion of the rear impact absorbing structure 411 may engage the second supporting structure 445 of the outer shell 334 to further secure the rear impact absorbing structure 411.

(62) In some embodiments, the vents and vent edges 324 are not utilized to help further secure the rear impact absorbing structures 411 or the upper impact absorbing structure 423 to the outer shell, or to provide any compression. Instead, the compression between the upper impact absorbing structure 423 and the rear impact absorbing structures 411 at the interfaces 439, 443 may be entirely or substantially entirely due to the front end of the upper impact absorbing structure 423 pressing against the first supporting structure 441 (e.g., inner lip) and the bottom of the rear impact absorbing structure 411 pressing against the second supporting structure 445 (e.g. inner lip).

(63) In some embodiments, the rear impact absorbing structure 411 may be laterally compressed against the upper impact absorbing structure 423 after the securing by lateral compression of the upper impact absorbing structure 423 with the outer shell 334 and the securing by lateral compression of the rear impact absorbing structure 411 with the outer shell 334. In other embodiments, the engaging of the rear impact absorbing structure 411 with the upper impact absorbing structure 423 may occur before contacting the rear impact absorbing structure 411 with the outer shell 334. In other words, the rear and upper impact absorbing structures 411, 423 may be laterally compressed together prior to mechanically securing the rear impact absorbing structures 411, 423 to the outer shell 334.

(64) With reference to FIGS. 20 and 22, the left and right impact absorbing structures 415, 419 may be laterally compressed against each of the upper and rear impact absorbing structures 423, 411 (e.g., through the interfaces 455, 439, interfaces 459, 439 (FIG. 20), interfaces 443, 455 (FIG. 22), and interfaces 443, 459) after the securing by lateral compression of the upper and rear impact absorbing structures 423, 411 with the outer shell 334. The left and right impact absorbing structures 415, 419 may then be secured by lateral compression with the outer shell 334 by

engaging each of the left and right impact absorbing structures **415, 419** with the outer shell **334**. For example, a portion of each of the left and right impact absorbing structures **415, 419** may be moved towards and engage each of the third and fourth supporting structures **453, 457** of the outer shell **334**. A third deflecting portion of at least one of the left impact absorbing structure **415** or the outer shell **334** may be deflected from a third static position to a third deflected position. After deflecting the third deflecting portion, the left impact absorbing structure **415** may be moved further toward the outer shell **334** and the third deflecting portion may be relaxed back from the third deflected position toward the third static position (e.g., to mechanically secure the left impact absorbing structure **415** in the outer shell **334**). A fourth deflecting portion of at least one of the right impact absorbing structure **419** or the outer shell **334** may be deflected from a fourth static position to a fourth deflected position. After deflecting the fourth deflecting portion, the right impact absorbing structure **419** may be moved further toward the outer shell **334** and the fourth deflecting portion may be relaxed back from the fourth deflected position toward the fourth static position (e.g., to mechanically secure the right impact absorbing structure **419** in the outer shell **334**). In some embodiments, the third and fourth engagement portions **463, 467** of the left and right impact absorbing structures **415, 419** may contact the vent edge **324** formed in the left wall **405** and right wall **407** of the outer shell **334**.

(65) With reference to FIG. **21**, the lower impact absorbing structure **427** may be laterally compressed against each of the left and right impact absorbing structures **415, 419** (e.g., through the interfaces **455, 471**, and interfaces **459, 471**) after the securing by lateral compression of the upper, rear, left, and right impact absorbing structures **423, 411, 415, 419** with the outer shell **334**. The lower impact absorbing structure **427** may be secured by lateral compression with the outer shell **334** by engaging the lower impact absorbing structure **427** with the outer shell **334**. For example, the lower portion of the lower impact absorbing structure **427** may be moved towards and engage the fifth supporting structure **473** of the outer shell **334**. A fifth deflecting portion of at least one of the lower impact absorbing structure **427** or the outer shell **334** may be deflected from a fifth static position to a fifth deflected position. After deflecting the fifth deflecting portion, the lower impact absorbing structure **427** may be moved further toward the outer shell **334** and the fifth deflecting portion may be relaxed back from the fifth deflected position toward the fifth static position to mechanically secure the lower impact absorbing structure **427** in the outer shell **334**. For example, the fifth engagement portion **475** of the lower impact absorbing structure **427** may contact the vent edges **324** formed in the left wall **405** and right wall **407** of the lower portion **317** of the outer shell **334**.

(66) Similar to the upper and rear impact absorbing structures **423, 411**, the left, right, and lower impact absorbing structures **415, 419, 427** may also rely partially or entirely on inner lips or other supporting structures (e.g., such as supporting structure **473**) on the outer shell **334** to provide compression between two or more of the impact absorbing structures. The vents and/or recesses along the outer shell **334** may then provide other locations for helping to secure the impact absorbing structures, and/or for providing additional compression to help hold the impact absorbing structures in place against one another.

(67) In some embodiments, all of the impact absorbing structures **411, 415, 419, 423, 427** may be laterally compressed together to form a single, uniform impact absorbing layer **330**. As noted above, each of the impact absorbing structures **411, 415, 419, 423, 427** may include or be coupled to a separate inner shell **435**. Other embodiments include different numbers and arrangements of impact absorbing structures than that illustrated.

(68) Clause 1: A helmet comprises an outer shell having an interior and an exterior, and an impact absorbing layer positioned on the interior of the outer shell, the impact absorbing layer comprising a first impact absorbing structure having a first interface and a second impact absorbing structure having a second interface in lateral compression against the first interface.

(69) Clause 2: The helmet of Clause 1, wherein the first impact absorbing structure includes a first

engagement portion that engages the outer shell such that the first impact absorbing structure is held in lateral compression between the first interface and the first engagement portion.

(70) Clause 3: The helmet of Clause 2, wherein the outer shell comprises a vent opening defined by a vent edge, and wherein the first engagement portion engages the vent edge.

(71) Clause 4: The helmet of Clause 2, wherein the first impact absorbing structure comprises an energy-absorbing layer and an inner shell secured to an outer surface of the energy-absorbing layer, wherein the inner shell includes the first engagement portion.

(72) Clause 5: The helmet of Clause 4, wherein the inner shell comprises a material having a higher density than the energy-absorbing layer.

(73) Clause 6: The helmet of Clause 5, wherein the inner shell comprises polycarbonate and the energy-absorbing layer comprises expanded polystyrene.

(74) Clause 7: The helmet of Clause 1, wherein the outer shell comprises an upper wall, a rear wall, a left wall and a right wall, wherein the first impact absorbing structure comprises an upper impact absorbing structure adjacent the upper wall and the second impact absorbing structure comprises a rear impact absorbing structure adjacent the rear wall.

(75) Clause 8: A helmet comprises an outer shell having a first receiving portion, and an impact absorbing layer positioned on an interior side of the outer shell, the impact absorbing layer comprising an impact absorbing structure having a first engagement portion and a second engagement portion spaced from the first engagement portion, wherein the impact absorbing structure is mechanically secured to the outer shell by the first engagement portion engaging the first receiving portion and the second engagement portion engaging a second receiving portion spaced from the first receiving portion.

(76) Clause 9: The helmet of Clause 8, wherein the impact absorbing structure is held in lateral compression between the first engagement portion and the second engagement portion.

(77) Clause 10: The helmet of Clause 8, wherein the outer shell comprises a vent, and wherein the first receiving portion comprises a vent edge defining at least a portion of the vent.

(78) Clause 11: The helmet of Clause 10, wherein the second receiving portion comprises a recess in the outer shell.

(79) Clause 12: The helmet of Clause 8, wherein the first receiving portion comprises a first recess in the outer shell, and wherein the second receiving portion comprises a second recess in the outer shell.

(80) Clause 13: The helmet of Clause 8, wherein the impact absorbing layer comprises a second impact absorbing structure, wherein the first receiving portion comprises a vent or a recess in the outer shell, and wherein the second receiving portion comprises a lateral surface of the second impact absorbing structure.

(81) Clause 14: The helmet of Clause 8, wherein the impact absorbing structure comprises an energy-absorbing layer and an inner shell secured to an outer surface of the energy-absorbing layer, wherein the inner shell includes the first engagement portion.

(82) Clause 15: The helmet of Clause 14, wherein the inner shell comprises a material having a higher density than the energy-absorbing layer.

(83) Clause 16: The helmet of Clause 14, wherein the inner shell comprises polycarbonate and the energy-absorbing layer comprises expanded polystyrene.

(84) Clause 17: The helmet of Clause 8, wherein the impact absorbing structure is not directly adhered to the outer shell, wherein the impact absorbing structure is not indirectly adhered to the outer shell, wherein the impact absorbing structure is not directly mechanically fastened to the outer shell, and wherein the impact absorbing structure is not indirectly mechanically fastened to the outer shell.

(85) Clause 18: A method of assembling a helmet from an outer shell and multiple impact absorbing structures comprises securing by lateral compression a first impact absorbing structure with the outer shell. The securing by lateral compression the first impact absorbing structure with

the outer shell comprises contacting the first impact absorbing structure with the outer shell, deflecting a first deflecting portion of at least one of the first impact absorbing structure or the outer shell from a static position to a deflected position, moving the first impact absorbing structure further toward the outer shell, and relaxing the first deflecting portion back from the deflected position toward the static position to mechanically secure the first impact absorbing structure in the outer shell.

(86) Clause 19: The method of Clause 18, wherein the outer shell comprises a vent defined by a vent edge, and wherein the contacting the first impact absorbing structure with the outer shell comprises contacting the first impact absorbing structure with the vent edge.

(87) Clause 20: The method of Clause 18, wherein the first impact absorbing structure comprises an energy-absorbing layer and an inner shell secured to an outer surface of the energy-absorbing layer, and wherein contacting the first impact absorbing structure with the outer shell comprises contacting the inner shell with the outer shell.

(88) Clause 21: The method of Clause 18, further comprising securing by lateral compression a second impact absorbing structure with the outer shell. The securing by lateral compression the second impact absorbing structure with the outer shell comprises engaging the second impact absorbing structure with the first impact absorbing structure, contacting the second impact absorbing structure with the outer shell, deflecting a second deflecting portion of at least one of the second impact absorbing structure or the outer shell from a second static position to a second deflected position, moving the second impact absorbing structure further toward the outer shell, and relaxing the second deflecting portion back from the second deflected position toward the second static position to mechanically secure the second impact absorbing structure in the outer shell.

(89) Clause 22: The method of Clause 21, wherein the second impact absorbing structure is laterally compressed against the first impact absorbing structure after the securing by lateral compression the first impact absorbing structure with the outer shell and the securing by lateral compression the second impact absorbing structure with the outer shell.

(90) Clause 23: The method of Clause 21, wherein the engaging the second impact absorbing structure with the first impact absorbing structure occurs before the contracting the second impact absorbing structure with the outer shell.

(91) Clause 24: The method of Clause 21, wherein the outer shell comprises an upper wall, a rear wall, a left wall, and a right wall, and wherein the first impact absorbing structure comprises an upper impact absorbing structure positioned adjacent the upper wall and the second impact absorbing structure comprises a rear impact absorbing structure positioned adjacent the rear wall.

(92) Clause 25: The method of Clause 24, further comprising securing by lateral compression a left impact absorbing structure with the outer shell. The securing by lateral compression the left impact absorbing structure with the outer shell comprises engaging the left impact absorbing structure with the upper impact absorbing structure, contacting the left impact absorbing structure with the outer shell, deflecting a left deflecting portion of at least one of the left impact absorbing structure or the outer shell from a third static position to a third deflected position, moving the left impact absorbing structure further toward the outer shell, and relaxing the left deflecting portion back from the third deflected position toward the third static position to mechanically secure the left impact absorbing structure in the outer shell.

(93) Clause 26: The method of Clause 25, further comprising securing by lateral compression a right impact absorbing structure with the outer shell. The securing by lateral compression the right impact absorbing structure with the outer shell comprises engaging the right impact absorbing structure with the upper impact absorbing structure, contacting the right impact absorbing structure with the outer shell, deflecting a right deflecting portion of at least one of the right impact absorbing structure or the outer shell from a fourth static position to a fourth deflected position, moving the right impact absorbing structure further toward the outer shell, and relaxing the right

deflecting portion back from the fourth deflected position toward the fourth static position to mechanically secure the right impact absorbing structure in the outer shell.

(94) Clause 27: A bicycle helmet comprises a helmet body adapted to cover at least a portion of a rider's head, the helmet body including a wall portion and a vent extending through the wall portion from an exterior of the helmet body to an interior of the helmet body, and an adjusting assembly for adjustably securing the helmet to a user's head, the adjusting assembly including an adjusting input movable to adjust a size of the helmet, the adjusting input being positioned at least partially in the vent.

(95) Clause 28: The bicycle helmet of Clause 27, wherein the helmet body comprises an outer shell, and an impact absorbing layer positioned on an interior side of the outer shell, wherein the vent is defined at least partially by a vent surface of the impact absorbing layer.

(96) Clause 29: The bicycle helmet of Clause 28, where the vent surface includes a recess and wherein the adjusting assembly is positioned at least partially in the recess.

(97) Clause 30: The bicycle helmet of Clause 29, wherein a recessed portion of the adjusting input is positioned in the recess and an exposed portion of the adjusting input is positioned in the vent.

(98) Clause 31: The bicycle helmet of Clause 30, wherein the adjusting input comprises a rotating dial.

(99) Clause 32: The bicycle helmet of Clause 31, wherein the rotating dial has a diameter, and wherein the exposed portion is 1%-15% of the diameter.

(100) Clause 33: The bicycle helmet of Clause 31, wherein the rotating dial has a diameter, and wherein the recessed portion is 5%-30% of the diameter.

(101) Clause 34: The bicycle helmet of Clause 31, wherein the adjusting assembly further comprises an adjusting housing rotationally supporting the adjusting input and fully positioned in the recess.

(102) Clause 35: The bicycle helmet of Clause 27, wherein the adjusting assembly further includes a strap member positioned to wrap at least partially around a user's head, the strap member being coupled to and movable by the adjusting input.

(103) Clause 36: The bicycle helmet of Clause 27, wherein the vent is located on a rear portion of the helmet body.

(104) Clause 37: The bicycle helmet of Clause 27, wherein the vent is located on a lower portion of the helmet body.

(105) Clause 38: The bicycle helmet of Clause 27, wherein the adjusting assembly further comprises an adjusting housing rotationally supporting the adjusting input.

(106) Clause 39: The bicycle helmet of Clause 38, wherein a first portion of the adjusting input is positioned in the adjusting housing and an exposed portion of the adjusting input is positioned in the vent.

(107) Clause 40: The bicycle helmet of Clause 39, wherein the adjusting input comprises a rotating dial.

(108) Clause 41: The bicycle helmet of Clause 40, wherein the rotating dial has a diameter, and wherein the exposed portion is 1%-15% of the diameter.

(109) Clause 42: The bicycle helmet of Clause 40, wherein the rotating dial has a diameter, and wherein the exposed portion is 10%-40% of the diameter.

(110) Clause 43: The bicycle helmet of Clause 40, wherein the vent is located on a rear portion of the helmet body.

(111) Clause 44: The bicycle helmet of Clause 43, wherein the vent is defined by a lower vent surface and an upper vent surface, wherein the upper vent surface tapers toward the lower vent surface.

(112) Clause 45: The bicycle helmet of Clause 27, wherein the helmet includes an impact absorbing layer defining a recess, wherein at least a portion of the adjusting assembly is disposed within the recess.

(113) Clause 46: The bicycle helmet of Clause 45, wherein the adjusting input comprises a rotating dial.

(114) Various features of the disclosure are set forth in the following claims.

Claims

1. A helmet comprising: an outer shell having an interior shell surface and an opposite exterior shell surface; and an impact absorbing layer positioned on the interior shell surface of the outer shell, wherein the impact absorbing layer includes a first impact absorbing structure having a first interior surface facing an interior cavity of the helmet, an opposite first exterior surface in contact with the interior shell surface, and a first interface that extends from the first interior surface to the first exterior surface, wherein the impact absorbing layer further includes a second impact absorbing structure having a second interior surface facing the interior cavity of the helmet, an opposite second exterior surface in contact with the interior shell surface, and a second interface that extends from the second interior surface to the second exterior surface, wherein at least part of the second interface is in lateral compression against at least part of the first interface; wherein the first impact absorbing structure includes a first engagement portion that engages the outer shell such that the first impact absorbing structure is held in lateral compression between the at least part of the first interface and the first engagement portion.
2. A helmet as claimed in claim 1, wherein the outer shell comprises a vent opening defined by a vent edge, and wherein the first engagement portion engages the vent edge.
3. A helmet as claimed in claim 1, wherein the second impact absorbing structure comprises an energy-absorbing layer and an inner shell secured to an outer surface of the energy-absorbing layer, wherein the inner shell includes a second engagement portion.
4. A helmet as claimed in claim 3, wherein the inner shell comprises a material having a higher density than the energy-absorbing layer.
5. A helmet as claimed in claim 4, wherein the inner shell comprises polycarbonate and the energy-absorbing layer comprises expanded polystyrene.
6. A helmet as claimed in claim 1, wherein the outer shell comprises an upper wall, a rear wall, a left wall and a right wall, wherein the first impact absorbing structure comprises an upper impact absorbing structure adjacent the upper wall and the second impact absorbing structure comprises a rear impact absorbing structure adjacent the rear wall.
7. A helmet comprising: an outer shell having a first receiving portion; and an impact absorbing layer positioned on an interior side of the outer shell, the impact absorbing layer comprising a first impact absorbing structure having a first engagement portion and a second impact-absorbing structure having a second engagement portion spaced from the first engagement portion, wherein the first impact absorbing structure is mechanically secured to the outer shell by the first engagement portion engaging the first receiving portion and the second impact-absorbing structure is mechanically secured to the outer shell by the second engagement portion engaging a second receiving portion spaced from the first receiving portion; wherein the first receiving portion comprises a vent or a recess in the outer shell, wherein the second impact-absorbing structure includes an inner shell, and wherein the inner shell includes the second engagement portion; wherein the first impact absorbing structure is held in lateral compression against the second impact absorbing structure.
8. A helmet as claimed in claim 7, wherein the first receiving portion comprises a vent edge defining at least a portion of the vent or recess.
9. A helmet as claimed in claim 8, wherein the second receiving portion comprises a recess in the outer shell.
10. A helmet as claimed in claim 7, wherein the first receiving portion is along a top of the helmet, and wherein the second receiving portion is along a rear of the helmet.

11. A helmet as claimed in claim 7, wherein the second impact absorbing structure comprises an energy-absorbing layer and wherein the inner shell is secured to an outer surface of the energy-absorbing layer.
 12. A helmet as claimed in claim 11, wherein the inner shell comprises a material having a higher density than the energy-absorbing layer.
 13. A helmet as claimed in claim 12, wherein the inner shell comprises polycarbonate and the energy-absorbing layer comprises expanded polystyrene.
 14. A helmet as claimed in claim 7, wherein the impact absorbing layer defines a rear vent along a rear of the helmet that is separate from the first receiving portion, wherein the helmet further comprises an adjusting assembly for adjustably securing the helmet to a user's head, the adjusting assembly including an adjusting input movable to adjust a size of the helmet, the adjusting input being positioned at least partially in the rear vent.
 15. A helmet comprising: an outer shell having an interior shell surface and an opposite exterior shell surface; and an impact absorbing layer positioned on the interior shell surface of the outer shell, wherein the impact absorbing layer includes a first impact absorbing structure having a first interior surface facing an interior cavity of the helmet, an opposite first exterior surface in contact with the interior shell surface, and a first interface that extends from the first interior surface to the first exterior surface, wherein the impact absorbing layer further includes a second impact absorbing structure having a second interior surface facing the interior cavity of the helmet, an opposite second exterior surface in contact with the interior shell surface, and a second interface that extends from the second interior surface to the second exterior surface, wherein at least part of the second interface is in lateral compression against at least part of the first interface; wherein the outer shell comprises an upper wall, a rear wall, a left wall and a right wall, wherein the first impact absorbing structure comprises an upper impact absorbing structure adjacent the upper wall and the second impact absorbing structure comprises a rear impact absorbing structure adjacent the rear wall.
 16. A helmet as claimed in claim 15, wherein the first impact absorbing structure includes a first engagement portion that engages the outer shell such that the first impact absorbing structure is held in lateral compression between the at least part of the first interface and the first engagement portion, wherein the outer shell comprises a vent opening defined by a vent edge, and wherein the first engagement portion engages the vent edge.
 17. A helmet as claimed in claim 16, wherein the second impact absorbing structure comprises an energy-absorbing layer and an inner shell secured to an outer surface of the energy-absorbing layer, wherein the inner shell includes a second engagement portion.
 18. A helmet as claimed in claim 17, wherein the inner shell comprises a material having a higher density than the energy-absorbing layer.
 19. A helmet as claimed in claim 18, wherein the inner shell comprises polycarbonate and the energy-absorbing layer comprises expanded polystyrene.
-