

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414629
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Stoltzfus; Amos A. et al.

Fire pit furniture

Abstract

Furniture useful around fire pits include an accessory mount to allow items such as a tray or grill to be mounted to the furniture in both useful and storage positions. The accessory mount is repositionably carried on an armrest or table edge. The position of the mount can be changed along the length of the armrest or table edge. The mount assembly allows the accessory to pivot when in the useful position. A cup holder also can be repositionably carried by the armrest or the table edge. A table has storage areas for a fire pit griddle and fire pit cover.

Inventors: Stoltzfus; Amos A. (Gordonville, PA), Miller; Jonathan C. (New Providence, PA), Allgyer; Amos Alan (Gordonville, PA), Boehmer; Christopher (Shohola, PA)

Applicant: Breeo, LLC (Kinzers, PA)

Family ID: 1000008819860

Assignee: Breeo, LLC (Kinzers, PA)

Appl. No.: 18/128516

Filed: March 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230404263 A1	Dec. 21, 2023

Related U.S. Application Data

us-provisional-application US 63412258 20220930
us-provisional-application US 63352705 20220616

Publication Classification

Int. Cl.: A47C1/00 (20060101); A47B31/00 (20060101); A47C7/54 (20060101); A47C7/70 (20060101)

U.S. Cl.:

CPC A47C1/00 (20130101); A47B31/00 (20130101); A47C7/541 (20180801); A47C7/70 (20130101); A47B2031/003 (20130101)

Field of Classification Search

CPC: A47C (1/00); A47C (1/06); A47C (7/541); A47C (7/70); A47C (7/705); A47C (7/624); A47B (31/00); A47B (2031/003); A47B (23/02); A47B (13/16); A47B (2200/0085); A47B (83/02)

USPC: 108/28; 108/11; 108/12; 108/18; 108/25; 108/26; 108/44; 108/46; 108/47; 108/50.14; 108/157.16; 108/97; 108/98; 297/162; 297/188.14; 297/161; 297/170; 297/173; 297/188.18; 297/145; 297/153; 297/188.15; 297/188; 297/2; 248/235; 248/241; 248/250

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
979070	12/1909	Hoffman	N/A	N/A
D78926	12/1928	Gottlob	N/A	N/A
2118676	12/1937	Lankton	N/A	N/A
2490884	12/1948	Rau	N/A	N/A
2600626	12/1951	Ellingson	N/A	N/A
2710051	12/1954	Greenberg	297/170	A47C 7/70
2720913	12/1954	Hoppert	N/A	N/A
3271070	12/1965	Dlouhy	108/26	A47C 1/06
4575149	12/1985	Forestal	248/240.4	A47B 23/02
5050929	12/1990	Gueringer et al.	N/A	N/A
5120071	12/1991	Thibault et al.	N/A	N/A
D334299	12/1992	Embree	N/A	N/A
D350860	12/1993	Greeson	N/A	N/A
5451092	12/1994	Gray	N/A	N/A
5899526	12/1998	LaPointe	297/188.2	A61G 5/10
6017085	12/1999	LaCroix	297/173	A47C 7/70
D509970	12/2004	Adams	N/A	N/A
7131688	12/2005	Stenson	108/157.11	A47C 7/70
7506923	12/2008	Gauss	N/A	N/A
7740312	12/2009	Johnson, Jr.	297/217.6	A47B 83/02
8025015	12/2010	Kennedy, Sr.	248/562	B60R 11/0252
D660040	12/2011	Bogdan et al.	N/A	N/A
8419124	12/2012	Kramer et al.	N/A	N/A
8596206	12/2012	Legeay	N/A	N/A
D712172	12/2013	Saylor	N/A	N/A
8905471	12/2013	Tang	N/A	N/A
D752354	12/2015	Fairbanks	N/A	N/A
D777465	12/2016	Milde	N/A	N/A

9820568	12/2016	Johnson	N/A	N/A
9924805	12/2017	Cass	N/A	N/A
D836931	12/2018	Prokofiev	N/A	N/A
D853142	12/2018	Tao	N/A	N/A
D899801	12/2019	White, III et al.	N/A	N/A
10842262	12/2019	Zimmerman	N/A	A47B 1/04
D906713	12/2020	White, III et al.	N/A	N/A
D929761	12/2020	Xiao	N/A	N/A
D972321	12/2021	Schaeffer	N/A	N/A
D972324	12/2021	Schaeffer	N/A	N/A
D981744	12/2022	Wu	N/A	N/A
11644241	12/2022	Zemel et al.	N/A	N/A
D995135	12/2022	Zhaowen	N/A	N/A
2005/0067865	12/2004	Yu	N/A	N/A
2007/0114755	12/2006	Pasternak et al.	N/A	N/A
2008/0164729	12/2007	Cavanaugh	N/A	N/A
2009/0284030	12/2008	Rein	293/142	B60R 11/00
2013/0200229	12/2012	Corey et al.	N/A	N/A
2016/0022043	12/2015	Czumaj-Bront	N/A	N/A
2020/0022498	12/2019	Howell	N/A	N/A
2021/0007495	12/2020	Snir et al.	N/A	N/A
2022/0282923	12/2021	Zemel et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
100779391	12/2006	KR	N/A

OTHER PUBLICATIONS

Breeo LLC, May 6, 2022, Youtube, Breeo X Series Furniture: Pro-Team Testimonial, <https://www.youtube.com/watch?v=068s71NfxQQ>. cited by applicant

Breeo LLC, Apr. 29, 2022, Youtube, X Series Furniture FAQ, <https://www.youtube.com/watch?v=iQbGAfPVmMY>. cited by applicant

Breeo LLC, Apr. 29, 2022, Youtube, X Series Furniture, https://www.youtube.com/watch?v=MNjGQ15a0_k. cited by applicant

Breeo LLC, Apr. 27, 2022, Youtube, Why Breeo Made Fireside Furniture, <https://www.youtube.com/watch?v=9wU6UFsy-M8>. cited by applicant

Breeo LLC, Apr. 25, 2022, Instagram, 9 images, https://www.instagram.com/p/CcyOSbNpg2N/?utm_source=ig_web_copy_link. cited by applicant

Breeo LLC, Apr. 22, 2022, Instagram, https://www.instagram.com/tv/CcqNGQalDIA/?utm_source=ig_web_copy_link. cited by applicant

Breeo LLC, Apr. 23, 2022, Instagram, https://www.instagram.com/tv/CcswW3sIJOQ/?utm_source=ig_web_copy_link. cited by applicant

Breeo LLC, Apr. 24, 2022, Instagram, https://www.instagram.com/tv/CcvVdkZI_fl/?utm_source=ig_web_copy_link. cited by applicant

Breeo LLC, Apr. 24, 2022, Instagram, https://www.instagram.com/tv/CcvVdkZI_fl/?utm_source=ig_web_copy_link. cited by applicant

Breeo LLC, Apr. 29, 2022, Instagram, https://www.instagram.com/tv/Cc8hBwxJx_E/?utm_source=ig_web_copy_link. cited by applicant

Breeo LLC, Sep. 12, 2022, Instagram, <https://www.instagram.com/p/CiaptmJg5s/>. cited by

Primary Examiner: Wilkens; Janet M

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of United States Provisional Patent Application Nos. 63/352,705 filed Jun. 16, 2022 and 63/412,258 filed Sep. 30, 2022; the disclosures of both applications are incorporated herein by reference.

BACKGROUND OF THE DISCLOSURE

1. Technical Field

(1) The disclosure relates to furniture and, more particularly, to furniture with features useful when being used around an outdoor fire pit.

2. Background Information

(2) People enjoy sitting in a ring of chairs about a camp fire provided in a fire pit. Eating and drinking while sitting around a fire pit can be more challenging. Although many chairs have flat armrests on which a bottle or a glass may be balanced, the armrests are not always level. Further, balancing a drink on one armrest while cutting a steak on a plate that is balanced on the other armrest is fraught with the risk of losing the steak or the drink to the ground. Those who enjoy cooking on fire pits and eating the food while enjoying the fire desire furniture that accommodates eating and drinking.

(3) Other issues with using fire pits is the need to continuously add wood to maintain the fire, the need to store the cover for the fire pit, the lid for the fire pit, and the need to store a hot grill if the grill is removed after cooking.

SUMMARY OF THE DISCLOSURE

(4) The disclosure provides items of furniture that support a repositionable and storable accessory such as a tray that can be used to support a plate of food that is being consumed by the person sitting on the furniture. In one configuration, the disclosure provides an armrest configuration that is part of an item of furniture such as a chair, bench, swing, glider, or the like. A mount assembly is repositionably carried on the armrest. In the exemplary configuration, the mount is repositionable because it can be slid along the length of the armrest and locked in a desirable position. The mount assembly provides at least two positions for a tray. In the exemplary configuration, the mount assembly provides a storage position and a repositionable usable position. When the user is sitting on the furniture, the user can place the tray on the mount assembly in the usable position to support a plate of food. The user can slide the mount assembly along the armrest to move the tray closer and farther from the user. Further, in the exemplary configuration, the mount assembly allows the tray to pivot with respect to the mount.

(5) The mount assembly includes a U-shaped bracket that closely fits around three sides of the armrest and slides along the length of the armrest. A locking finger is used to lock the position of the bracket with respect to the armrest. In the exemplary configuration, the mount assembly includes a first mount and a second mount carried by the bracket. The tray can be received on and carried by the first mount with a friction fit to place the tray in the usable position. The tray can be received on and carried by the second mount to place the tray in the storage position. When the armrest is horizontal, the first mount is vertical and the second mount is horizontal. Both mounts can be cylindrical to allow the tray to pivot with respect to the mount in both positions. The tray defines a mounting hole that is sized to frictionally engage both the first and second mounts while

allowing the user to remove the tray from one mount and move it to another.

(6) In the exemplary configuration, the armrest defines a slot which, in the exemplary configuration, is defined by the armrest to open at least through the bottom surface of the armrest. Alternatively, the slot also can extend through the front end of the armrest. In another configuration, the slot also extends through the rear end of the armrest or also extends through both the front and rear ends of the armrest. In a further configuration, the slot is open through the upper surface of the armrest. In one configuration, the slot is a groove of substantially constant width. In the exemplary configuration, the slot is T-shaped with the neck of the slot that is open through the bottom surface of the armrest having a width that is smaller than the top portion of the slot. The mount assembly is repositionably carried by the armrest with the locking finger extending into the slot. The user can adjust the locking finger to clamp the mount assembly to the armrest and lock the position of the mount assembly with respect to the armrest. The locking finger can be threaded to the bracket. When the slot is not used, the locking finger engages one of the armrest surfaces, for example, the lower surface of the armrest instead of the interior of the slot. When the slot is used, the locking finger provides additional stability to the mount assembly.

(7) The disclosure also provides a furniture configuration wherein a tray can be carried on both armrests. Further, when a tray is carried by one armrest, a cup holder can be carried by the other armrest using the same type of mounting bracket with the slot defined by the armrest. In an exemplary configuration, the disclosure provides a cup holder having at least a large opening for a can or cup and at least a small opening for stemware wherein the small opening is open to an edge of the cup holder.

(8) The disclosure also provides an item of furniture such as a table that receives the mounting assembly for either or both of the cup holder and tray.

(9) The disclosure further provides a grill mount that is used with an item of furniture such as a table to support a grill for food preparation or food serving. The grill mount includes a first vertical grill mount that holds the grill in a horizontal configuration while allowing the grill to rotate 360 degrees on the mount. In this condition, the grill can be loaded with food before being placed over the fire or the grill can be held while cooked food is served. The grill mount also includes a second horizontal grill mount that holds the grill in a vertical storage position where it is out of the way and can cool.

(10) The disclosure provides a table having a support structure that defines storage areas for a grill cover and one of a grill and griddle. The table also can have a storage area for wood and a shelf for other items. These can be provided individually or all combined in a single table. In an exemplary configuration, the table includes a metal rack and heat shield which are configured to support a hot grill or griddle that is used with a fire pit.

(11) The individual features described below may be combined in different combinations than specifically described below to form different configurations of the devices of the disclosure. The preceding non-limiting aspects of the disclosure, as well as other aspects, are more particularly described below. A more complete understanding of the devices, assemblies, and methods can be obtained by reference to the accompanying drawings, which are not intended to indicate relative size and dimensions of the assemblies. In those drawings and the description below, like numeric designations refer to components of like function. Specific terms used in that description are intended to refer only to the particular structure of the embodiments selected for illustration in the drawings, and are not intended to define or limit the scope of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a chair with a tray in a first position on one armrest and a cup

holder on the other armrest.

(2) FIG. 2 is a view of the chair of FIG. 1 with the tray in a second position.

(3) FIG. 3 is an end view of the cup holder mounted to the armrest.

(4) FIG. 4 is an end view of the tray mounted to the armrest in the usable position.

(5) FIG. 5 is an end view of the tray mounted to the armrest in the storage position.

(6) FIG. 6 is a front view of a table with a grill mounting post that allows the table to be used to hold a grill.

(7) FIG. 7 is a perspective view of another table with storage feature relevant to a fire pit.

(8) FIG. 8 is a rear perspective view of the table of FIG. 7 showing a fire pit cover stored in a holder.

(9) FIG. 9 is a rear perspective view of the table of FIG. 7 showing a fire pit griddle stored in a holder.

(10) FIG. 10 is a rear perspective view of the table of FIG. 7 showing a fire pit grill stored in a holder.

(11) FIG. 11.

(12) FIG. 11 is a perspective view of another grill mount for the table.

(13) FIG. 12 is a perspective view of a grill carried in a storage position by the grill mount of FIG. 11.

(14) FIG. 13 is a perspective view of a grill carried in a usable position by the grill mount of FIG. 11.

DETAILED DESCRIPTION OF THE DISCLOSURE

(15) This description of exemplary embodiments is intended to be read in connection with the accompanying drawings, which are to be considered part of the entire written description. The drawing figures are not necessarily to scale and certain features may be shown exaggerated in scale or in somewhat schematic form in the interest of clarity and conciseness. In the description, relative terms such as “horizontal,” “vertical,” “up,” “down,” “top” and “bottom” as well as derivatives thereof (e.g., “horizontally,” “downwardly,” “upwardly,” etc.) should be construed to refer to the orientation as then described or as shown in the drawing figure under discussion. These relative terms are for convenience of description and normally are not intended to require a particular orientation. Terms including “inwardly” versus “outwardly,” “longitudinal” versus “lateral” and the like are to be interpreted relative to one another or relative to an axis of elongation, or an axis or center of rotation, as appropriate. Terms concerning attachments, coupling and the like, such as “joined,” “connected,” and “interconnected,” refer to a relationship wherein structures are secured or attached to one another either directly or indirectly through intervening structures, as well as both movable or rigid attachments or relationships, unless expressly described otherwise.

(16) An exemplary item of furniture is a chair 2 depicted in FIGS. 1 and 2. The body of chair 2 includes two armrests 4. The body of chair 2 also includes a support structure that includes a seat, a back, and four legs that allow chair 2 to function to support a person in a sitting position. Armrests 4 depicted with chair 2 in these drawings can be used with other items of furniture including those that are sat on such as couches, swings, and benches.

(17) In the exemplary configuration, a cup holder 6 and a tray 8 are each selectively repositionably carried by armrests 4. Each can be repositioned such as by sliding along at least a majority of the length of armrest 4. When not repositioned by sliding, cup holder 6 or tray 8 can be removed from armrest 4, moved along the length of armrest 4, and reconnected at a different location along armrest 4. Additionally, tray 8 can be pivoted between at least the two positions depicted in FIGS. 1 and 2. Further, tray 8 can be removed from the usable position shown in FIGS. 1 and 2 and moved to a storage position shown in FIG. 5. When the user is sitting on chair 2, the user places tray 8 in its usable position wherein tray 8 is parallel to the top of armrest 4 which is desirably substantially horizontal. The user can then use tray 8 to support a plate of food, a laptop computer, a pad of paper, a game, or a drinking cup or bottle. The user can pivot tray 8 at least from the position of

FIG. 1 to the position of FIG. 2 to allow the user to easily get up from chair 2 or sit down in chair 2. In the exemplary configuration, tray 8 can rotate 360 degrees about its mount axis.

(18) Cup holder 6 is mounted to armrest 4 with a mounting assembly 10. Mounting assembly 10 includes a U-shaped bracket 12 that closely fits over at least portions of three surfaces of armrest 4 to frictionally engage armrest 4 while allowing bracket 12 to slide along the length of armrest 4. A locking finger 14 is carried by bracket 12 and is movable to an engaged condition to lock the position of bracket 12 with respect to armrest 4. In this configuration, locking finger 14 is a threaded fastener that threadedly engages bracket 12. Locking finger 14 can engage the lower surface of armrest 4. In the exemplary configuration, armrest 4 defines a slot 16 with locking finger 14 extending into slot 16. Slot 16 can be a channel having a constant width or the T-shaped slot depicted in the drawings. With either shape, the width is configured to cooperate with the diameter of locking finger 14 to provide some support to locking finger 14 when it is in slot 16. With the T-shaped slot 16, a nut can be carried on the locking finger within the wide portion of the slot to create a clamping force between the nut and bracket 12 when locking finger 14 is tightened. Also, the T-shaped slot can be used with third party accessories that fit in such T-shaped slots such as phone holders or tablet holders.

(19) Cup holder 6 includes a body 18 carried above bracket 12. Body 18 defines an opening 20 sized for bottles, wine glasses, cans, cups, and many drinking glasses. In addition, body 18 defines at least one stemware holder opening 21 which is open to an edge of body 18. Opening 21 allows a glass such as a stemmed wine glass to be stably held with the stem in opening 21 and the bowl of the glass resting on body 18. Two openings 21 can be provided. A support 22 is carried by bracket 12 or integral therewith and has a portion located directly below opening to support the bottom of the item placed in cup holder 6. Mounting assembly 10 can be metal and define an opening aligned with opening 20. The side offset portion 24 of support 22 can define a bottle opener (shown in FIGS. 1 and 2).

(20) Tray 8 has a generally flat body that defines a mounting opening 32. In a situation where the user will eat food directly from tray 8, a drip channel 34 is defined by the upper surface of the body. When the tray body is removed from the mounting assembly 40, the tray body can be placed in a dishwasher. The tray body can be made from a polymer or a polymer lumber.

(21) As noted above, mounting assembly 40 allows tray 8 to rotate 360 degrees when tray 8 is in the usable position. Mounting assembly 40 also provides a storage position for tray (FIG. To provide both tray positions, mounting assembly 40 provides first 42 and second 44 mounts carried by a bracket 46 that is supported by armrest 4. As described above with respect to cup holder 6, bracket 46 is generally U-shaped when viewed from the end as in FIGS. 4 and 5 with bracket engaging at last portions of three surfaces of armrest 4. When bracket 46 is placed on armrest 4 and the armrest 4 is substantially horizontal, first mount 42 is substantially vertical and second mount is substantially horizontal. In the exemplary configuration, second mount 44 extends from the side 48 of bracket 46 and first mount 42 extends up from second mount 44. In other configurations, second mount 44 can extend from first mount 42. In another configuration, first mount 42 can extend from the upper arm 50 of bracket 46 and second mount 44 can extend from side 48. A benefit of having first mount 42 extend from second mount 44 is that first mount 42 is located outwardly of the outer edge of armrest 4 and is up against the upper portion of tray 8 when tray 8 is in the storage position. To place tray 8 in the storage position, the user removes tray 8 from first mount 42 and places it on second mount 44. Opening 32 is sized to cause the body of tray 8 to fictionally engage each mount 42 and 44. In the exemplary configuration, tray body 30 is made from a polymer lumber with mounts 42 and 44 being stainless steel cylinders.

(22) A locking finger 60 is carried by bracket 46 and is movable to an engaged condition to lock the position of bracket 46 with respect to armrest 4. In this configuration, locking finger 60 is a threaded fastener that threadedly engages bracket 46. A nut 62 is welded to the bottom of bracket 46 to threadedly receive locking finger 60. Locking finger 60 can engage the lower surface of

armrest **4**. In the exemplary configuration, armrest **4** defines a slot **16** with locking finger **60** extending into slot **16**. Slot **16** can be a channel having a constant width or the T-shaped slot depicted in the drawings. With either shape, the width is configured to cooperate with the diameter of locking finger **60** to provide some support to locking finger **60** when it is in slot **16**. With the T-shaped slot **16**, a nut can be carried on the locking finger within the wide portion of the slot to create a clamping force between the nut and bracket **12** when locking finger **14** is tightened.

(23) The center of opening **32** defined by the tray body is spaced from the inner edge **70** of the tray body by a distance that is less than the distance from the center of first mount **42** and the inner edge **72** of armrest **4**. As such, tray **8** can be rotated to the position of FIG. **2** wherein inner edge **70** is located outward of inner edge **72** so that tray **8** does not interfere with a person sitting down or standing up. When opening **32** is centered in tray body **30**, then tray **8** can be rotated 180 degrees from the position of FIG. **2** also without interfering with the opening to chair **2**.

(24) As shown in FIG. **4**, the center of opening **32** is spaced from the outer end **80** a distance greater than the distance from the center of opening **32** to the outer end of second mount **44** such that outer end **80** of tray **8** covers second mount **44** when tray **8** is in the position of FIG. **1**. This stops people who are walking past chair **2** from becoming snagged on second mount **44**. As shown in FIG. **5**, the center of opening **32** is spaced from the outer end **80** a distance greater than the distance from the center of opening **32** to the outer end of first mount **42** such that outer end **80** of tray **8** is located above first mount **42** when tray **8** is in the position of FIG. **5**. This helps to limit snagging on the top of first mount **42** when tray **8** is in the storage position. Also as shown in FIG. **5**, second mount **44** only extends a distance from first mount **42** a distance about the same as the thickness of the tray body so that tray **8** is close to first mount **42** when tray **8** is in the storage position.

(25) Mounting assemblies **10** or **40** can be used with an item of furniture that is not designed for seating. An example is the table depicted in FIG. **6** wherein a portion of the table next to an edge is configured to receive the U-shaped portion of mounting assembly **10** or **40** so that cup holder **6** or tray **8** can be carried by the table.

(26) An exemplary grill holder is indicated generally by the number **100** in FIG. **6**. Grill holder includes a U-shaped bracket **102** that mounts to an edge of a piece of furniture such as the table **104** depicted in FIG. **6**. A locking finger **106** is connected to bracket **102** and can be used in the manner described above to secure bracket **102** to furniture **104** which can optionally include slot **16**. A hollow grill mount tube **108** extends up from bracket **102** and receives a downwardly projecting grill post (for example, the lower portion of item #**60** from US publication 2021/0045578 which is incorporated herein by reference to describe grill post #**60**) of a grill **110** that extends down from a grill tube **112**. Grill holder **100** can this be connected to an item of furniture to allow a user to load the grill **110** before the grill **110** is placed on the fire and allows the user to remove a grill from the fire and remove the cooked food from the grill.

(27) In the exemplary configuration, furniture **104** is a table that has a wood storage bin. The weight of the wood helps stabilize the table when a heavily loaded grill is connected to grill holder **100**.

(28) Table **104** includes a storage rack **120** for a circular cover **122** (with handle **124**) for a fire pit. Rack **120** includes a lower shelf or spaced protrusions upon which the lower portion of cover **122** rests. An upper finger projects down from the underside of the table top to prevent cover **122** from falling out to the right in FIG. **6**. Cover **122** may be removed by rolling or sliding it out of the ends or moving it past the upper finger and tilting it out to the right.

(29) Another exemplary configuration of a table is indicated generally by the number **200** in FIGS. **7-13**. The body of table **200** includes a table top **202** supported on a support structure that includes at least three legs with four legs shown in the exemplary configuration. The legs include two front legs **204** and two rear legs **206**. Legs **204** and **206** can be solid. Legs **204** and **206** also can be hollow such as metal (stainless steel or aluminum) open tubes with flanges to which frame

members are connected. Threaded height-adjustable feet are optionally connected to the bottom of legs **204** and **206**. Table top **202** defines constant-width slots or T-slots **16** along the underside of its overhanging edges so that accessories such as cup holder **6** can be supported from table **200**. Table **200** can be made from a polymer lumber product that resists weather. Table **200** also can be made from metal, polymer, or wood.

(30) A front lower frame member **210** extends between the lower portions of front legs **204**. A front upper frame member extends between the upper portions of front legs **204** under table top **202**. Similarly, upper and lower side frame members extend between the upper and lower portions of front **204** and rear **206** legs behind the side walls (defined by slats **220**). An upper shelf **230** is carried on pegs that fit into openings defined by the inner surfaces of some of slats **220**. The position of shelf **230** can be adjusted by moving the pegs to different openings. A lower shelf **240** is carried on the lower side frame members. Like the side walls, lower shelf **240** can be formed from a plurality of slats. Similar to the FIG. **6** configuration, lower shelf **240** can be used to store wood for the fire pit.

(31) A holder **250** extends between the lower portions of rear legs **206**. Holder is metal (such as stainless steel or aluminum) and defines a slot **252** sized to receive a portion of the edge of a fire pit cover **254** so that cover **254** can be stored in table **200** when not in use. Holder **250** projects outwardly beyond the rear surfaces of legs **206** so that cover **254** is rearward of rear legs **206** when in storage as shown in FIG. **8**.

(32) The rear wall **260** of table **200** is spaced inwardly from rear legs **206** to define a space to receive a griddle **262** or a grill **264**. Rear wall **260** can be formed from a plurality of slats. A metal heat shield **266** is carried on the rearwardly-facing surface of rear wall **260** to protect rear wall **260** from a hot griddle **262** or grill **264** so that they can be stored after being removed from use on the fire pit. A metal rear lower frame member **268** extends across the bottom of rear wall **260**. A metal rear upper frame member extends across the top of rear wall. Two metal supports **270** extend between holder and frame member **268**. Supports **270** can be rod-shaped. Griddle **262** and grill **264** can rest on supports **270** and against heat shield **266** or metal rear upper frame member. An opening **272** is defined between holder **250** and member **268** to provide air circulation about the lower portions of griddle **262** and grill **264** and to allow portions of griddle **262** and grill **264** to extend down below supports **270**.

(33) Another grill mount **280** is depicted in FIGS. **11-13**. Grill mount **280** includes the U-channel **102** as described above with fastener **106**. In this configuration, grill mount includes a first vertical grill mount **282** and a second horizontal grill mount **284**. Grill **264** includes a mounting tube **286** which allows grill **264** to be to an accessory post. The same mounting tube **286** slides over mounts **282** and **284** to mount grill **264** to grill mount **280**. In FIG. **12**, grill **264** is mounted to second horizontal mount **284** such that grill **264** hangs in a storage position along the side of table **200**. In FIG. **13**, grill **264** is mounted to first vertical mount **282** such that grill **264** is horizontal and can hold food. Also, grill **264** can rotate 360 degrees on mount **282** so that it can be positioned over table **200** or off to the side of table so that the table top can be used for other items.

(34) In the foregoing description, certain terms have been used for brevity, clearness, and understanding. No unnecessary limitations are to be implied therefrom beyond the requirement of the prior art because such terms are used for descriptive purposes and are intended to be broadly construed. Moreover, the descriptions and illustrations are exemplary and the following claims are not limited to the exact details shown or described. Modifications and alterations of these embodiments will be apparent to one who reads and understands this general description. The present disclosure should be construed as including all such modifications and alterations insofar as they come within the scope of the following claims or equivalents thereof. Throughout the description and claims of this specification the words “comprise” and “include” as well as variations of those words, such as “comprises,” “includes,” “comprising,” and “including” are not intended to exclude additives, components, integers, or steps.

Claims

1. An item of furniture comprising: a body; an accessory mount repositionably carried by the body; the accessory mount including a bracket that engages the body to support the accessory mount from the body; the accessory mount including a first mount that projects upwardly with respect to the bracket and a second mount that projects outwardly from the body and with respect to the bracket; the first mount being positioned to support an accessory in a useable position; and the second mount being positioned to support the accessory in a storage position.
2. The furniture of claim 1, wherein the body includes an armrest and the accessory is a tray; the bracket engaging the armrest.
3. The furniture of claim 2, wherein the tray is selective pivotable with respect to the first mount when the tray is in the useable position.
4. The furniture of claim 3, wherein the tray defines a mounting opening that selectively receives the first mount when in the useful position and the second mount when in the storage position.
5. The furniture of claim 1, wherein the body includes a table top and the accessory is a grill; the bracket engaging the table top.
6. The furniture of claim 5, wherein the grill includes a hollow mount that selectively receives the first mount when in the useful position and the second mount when in the storage position.
7. The furniture of claim 1, further comprising a cup holder removably and repositionably connected to the body.
8. The furniture of claim 7, wherein the body defines an elongated slot; the cup holder including a bracket and a locking finger; the bracket having a first portion extending across a portion of the elongated slot with the locking finger being adjustably carried by the first portion such that a portion of the locking finger can be adjusted to be located in the elongated slot.
9. The furniture of claim 8, wherein the cup holder can be selectively slid along a length of the elongated slot.
10. The furniture of claim 1, wherein one of the mounts is connected to and projects from the bracket and the other of the mounts is connected to and projects from the mount that is connected to and projects from the bracket.
11. The furniture of claim 10, wherein each of the mounts has a cylindrical portion adapted to be received within a portion of the accessory.
12. An item of furniture comprising: a body that includes an armrest; an accessory mount repositionably carried by the armrest; the accessory mount having a first mount and a second mount; a longitudinal axis of the first mount being perpendicular to a longitudinal axis of the second mount; the first mount being positioned to support a tray in a useable position with respect to the body; the second mount being positioned to support the tray in a storage position with respect to the body; the tray being selectively pivotable with respect to the first mount when the tray is in the useable position; the tray defining a mounting opening that selectively receives the first mount when in the useful position and the second mount when in the storage position; and a center of the mounting opening being spaced from an inner edge of the tray by a distance that is less than the distance from a center of first mount and an inner edge of the armrest.
13. The furniture of claim 12, wherein a center of the mounting opening is spaced from an outer end of the tray a distance greater than the distance from the center of the mounting opening to an outer end of the second mount when the tray is mounted to the first mount in the useable position.
14. The furniture of claim 12, wherein a center of the mounting opening is spaced from an outer end of the tray a distance greater than the distance from the center of opening to an outer end of the first mount when the tray is mounted to the second mount in the storage position.
15. The furniture of claim 12, wherein the body defines an elongated slot; the accessory mount including a bracket and a locking finger; the bracket having a first portion extending across a

portion of the elongated slot with the locking finger being adjustably carried by the first portion such that a portion of the locking finger can be adjusted to be located in the elongated slot.

16. An item of furniture comprising: a body; an accessory mount repositionably carried by the body; the accessory mount having a first mount and a second mount; a longitudinal axis of the first mount being perpendicular to a longitudinal axis of the second mount; the first mount being positioned to support an accessory in a useable position with respect to the body; the second mount being positioned to support the accessory in a storage position with respect to the body; the body defining an elongated slot; the accessory mount including a bracket and a locking finger; the bracket having a first portion extending across a portion of the elongated slot with the locking finger being adjustably carried by the first portion such that a portion of the locking finger can be adjusted to be located in the elongated slot; and the elongated slot is T-shaped in cross section.

17. The furniture of claim 16, wherein the accessory mount can be selectively slid along a length of the elongated slot.

18. The furniture of claim 16, further comprising a cup holder removably and repositionably connected to the body.

19. The furniture of claim 18, wherein the cup holder can be selectively slid along a length of the elongated slot.
