

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414749
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Okumura; Yusuke et al.

X-ray diagnosis apparatus and control method of the same

Abstract

An X-ray diagnosis apparatus according to the present embodiment comprises: an imager configured to image by irradiating X-ray to a subject to acquire a captured image by X-ray imaging and a fluoroscopic image by fluoroscope imaging; and processing circuitry configured to acquire imaging related information obtained within a certain period of time before or after the X-ray imaging, and store in a memory the fluoroscopic image captured at least one of before or after the X-ray imaging based on the imaging related information.

Inventors: Okumura; Yusuke (Nasushiobara, JP), Iwai; Haruki (Otawara, JP), Sato; Motohiro (Nasushiobara, JP)

Applicant: CANON MEDICAL SYSTEMS CORPORATION (Otawara, JP)

Family ID: 1000008819890

Assignee: CANON MEDICAL SYSTEMS CORPORATION (Otawara, JP)

Appl. No.: 18/181695

Filed: March 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230284992 A1	Sep. 14, 2023

Foreign Application Priority Data

JP	2022-039600	Mar. 14, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: A61B6/40 (20240101); A61B6/00 (20060101); A61B6/46 (20240101); G06T1/60 (20060101); G06T5/50 (20060101); G06T7/20 (20170101)

U.S. Cl.:

CPC A61B6/487 (20130101); A61B6/463 (20130101); A61B6/465 (20130101); A61B6/467 (20130101); A61B6/5235 (20130101); A61B6/5264 (20130101); A61B6/54 (20130101); G06T1/60 (20130101); G06T5/50 (20130101); G06T7/20 (20130101); G06T2200/24 (20130101); G06T2207/10121 (20130101); G06T2207/20081 (20130101); G06T2207/20212 (20130101); G06T2207/30004 (20130101); G06T2207/30168 (20130101)

Field of Classification Search

CPC: A61B (6/487); A61B (6/463); A61B (6/465)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9280837	12/2015	Grass et al.	N/A	N/A
2003/0169847	12/2002	Karellas	378/98.3	A61B 6/504
2004/0122790	12/2003	Walker	N/A	A61B 5/318
2011/0182492	12/2010	Grass et al.	N/A	N/A
2020/0121294	12/2019	Tsymbalenko	N/A	A61B 8/5246
2020/0222018	12/2019	van Walsum	N/A	A61B 6/5264
2021/0404974	12/2020	Nagatsuka	N/A	A61B 6/465
2022/0395251	12/2021	Tsymbalenko	N/A	G06N 3/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-234714	12/1997	JP	N/A
2009-183509	12/2008	JP	N/A
2012-505009	12/2011	JP	N/A

Primary Examiner: Maupin; Hugh

Attorney, Agent or Firm: Oblon, McClelland, Maier & Neustadt, L.L.P.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2022-039600, filed on Mar. 14, 2022, the entire contents of which are incorporated herein by reference.

FIELD

(2) The embodiments disclosed in the present specification and drawings relate to an X-ray diagnosis apparatus and a control method of the same.

(3) Conventionally, in medical fields, X-ray TV bed apparatuses that acquire captured image (single shot of X-ray image) or fluoroscopic image (X-ray images that are continuous in time) by irradiating X-ray to a subject and detecting the X-ray that has passed the subject, are well known. When acquiring the captured image using the X-ray TV bed apparatus, the user must acquire the fluoroscopic image by the fluoroscopic imaging that irradiates X-ray continuously and determine the X-ray imaging location with respect to the subject or the X-ray imaging region etc., while observing the acquired fluoroscopic image.

(4) Typically, the user diagnosis lesions etc. by observing captured images acquired by X-ray imaging. However, if there are blurs of a contrast agent in the captured image, there may be difficulties for the user in diagnosing the lesions etc., using the captured image with the blurs of the contrast agent. For this reason, the user must diagnose the lesions etc., observing the fluoroscopic image that are fluoroscopically imaged before or after the X-ray imaging if blurs of the contrast agent occur. That is, since fluoroscopic imaging, with the captured image, is an effective diagnostic material to the user, there is a need to store the fluoroscopic image with the captured image in the memory for the X-ray TV bed apparatuses.

(5) However, since fluoroscopic image consists of X-ray images that are continuous in time, i.e., a plurality of X-ray images, storing all fluoroscopic image that are fluoroscopically imaged in the memory will oppress the memory capacity. Thus, the user must store only the necessary fluoroscopic image in the memory; however, performing additional operations other than the imaging operation to store the fluoroscopic image in the memory is troublesome for the user, and there arises a problem that the user forgets the additional operations other than the imaging operation. Likewise, this problem similarly arises not only for X-ray TV bed apparatus but also for other X-ray diagnosis apparatus such as an X-ray Angio apparatus; thus, it is desired to store the fluoroscopic image in an appropriate and a simple manner.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a block diagram that illustrates an exemplary configuration of an X-ray diagnosis apparatus according to a first embodiment.

(2) FIG. 2 is a flowchart that describes a content of a fluoroscopic image storing control process executed in the X-ray diagnosis apparatus according to the first embodiment.

(3) FIG. 3 is a timing chart that illustrates timings of a fluoroscopic imaging, an X-ray imaging, and storing the fluoroscopic image executed in the X-ray diagnosis apparatus according to the first embodiment.

(4) FIG. 4 is a diagram that illustrates an example of the fluoroscopic image displayed on a display of the X-ray diagnosis apparatus according to the first embodiment.

(5) FIG. 5 is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus according to a first modification.

(6) FIG. 6 is a timing chart that illustrates timings of a fluoroscopic imaging, an X-ray imaging, and storing the fluoroscopic image executed in the X-ray diagnosis apparatus according to the first modification.

(7) FIG. 7 is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus according to a second modification.

(8) FIG. 8 is a timing chart that illustrates timings of a fluoroscopic imaging, an X-ray imaging, and storing the fluoroscopic image executed in the X-ray diagnosis apparatus according to the second modification.

(9) FIG. 9 is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis

apparatus according to a second embodiment.

(10) FIG. **10** is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus according to the second embodiment.

(11) FIG. **11** is a schematic diagram that schematically illustrates a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus according to the second embodiment.

(12) FIG. **12** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus according to a third embodiment.

(13) FIG. **13** is an exemplary diagram that describes an exemplary data flow during training the fluoroscopic image storing control process of the X-ray diagnosis apparatus according to the third embodiment.

(14) FIG. **14** is an exemplary diagram that describes an exemplary data flow during operating the fluoroscopic image storing control process of the X-ray diagnosis apparatus according to the third embodiment.

(15) FIG. **15** is a flowchart that describes a content of the fluoroscopic image storing control process of the X-ray diagnosis apparatus according to the third embodiment.

(16) FIG. **16** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus according to a third modification.

(17) FIG. **17** is a flowchart that describes a content of the fluoroscopic image storing control process of the X-ray diagnosis apparatus according to the third modification.

(18) FIG. **18** is a diagram that illustrates an exemplary notification screen displayed on a display of the X-ray diagnosis apparatus according to the third modification.

(19) FIG. **19** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus according to a fifth modification.

(20) FIG. **20** is a flowchart that describes a content of the fluoroscopic image storing control process of the X-ray diagnosis apparatus according to the fifth modification.

(21) FIG. **21** is a diagram that illustrates an exemplary captured image and a button displayed on the display of the X-ray diagnosis apparatus according to the fifth modification.

(22) FIG. **22** is a block diagram that illustrates the X-ray diagnosis apparatus according to a sixth modification.

(23) FIG. **23** is a flowchart that describes a content of the play control process of the X-ray diagnosis apparatus according to the sixth modification.

(24) FIG. **24** is a timing chart that illustrates a timing of inserting an interpolated image, executed in the X-ray diagnosis apparatus according to the sixth modification.

DETAILED DESCRIPTION OF THE INVENTION

(25) With reference to the drawings below, embodiments of an X-ray diagnosis apparatus and a control method of the same will be described. Note that, in the description below, same reference signs are given for components substantially identical in terms of configuration and function, and duplicate description will be given only when necessary.

First Embodiment

(26) FIG. **1** is a block diagram that illustrates an exemplary configuration of an X-ray diagnosis apparatus according to a first embodiment. The X-ray diagnosis apparatus **1** shown in FIG. **1**, for instance, is an X-ray TV bed apparatus. Note that, the X-ray diagnosis apparatus **1** according to the present embodiment is not limited to the X-ray TV bed apparatus, but for instance, may be realized by an X-ray Angio apparatus or a general X-ray imaging apparatus. In the description below, an example where the X-ray diagnosis apparatus **1** is the X-ray TV bed apparatus will be described.

(27) As shown in FIG. **1**, the X-ray diagnosis apparatus **1** according to the present embodiment comprises an imaging apparatus **10** and a console apparatus **30**.

(28) The imaging apparatus **10** irradiates X-ray to a subject P, and acquires a captured image by X-ray imaging and a fluoroscopic image by fluoroscopic imaging. Note that the imaging apparatus **10**

is an example of an imager.

(29) X-ray imaging is an imaging that acquires a single X-ray image as a captured image by discontinuously irradiating X-ray to a subject P. That is, X-ray irradiation is used when acquiring a single captured image by irradiating X-ray once to subject P at a relatively high tube voltage. Note that, X-ray imaging is not limited to be used when acquiring the single captured image, but may be used to acquire X-ray images that are continuous in time by continuously irradiating X-ray to subject P at the relative high tube voltage, i.e., for video capturing. X-ray imaging may acquire X-ray images that have higher resolutions compared to that of fluoroscopic imaging.

(30) Fluoroscopic imaging is an imaging that acquires X-ray images as a fluoroscopic image that are continuous in time by continuously or intermittently irradiating X-ray to subject P. That is, fluoroscopic imaging is used when acquiring a plurality of fluoroscopic image that are continuous in time at a preset framerate by continuously or intermittently irradiating X-ray to subject P at the relatively low voltage. fluoroscopic imaging may be used for video capturing. fluoroscopic imaging may suppress exposure dose to the subject P compared to when performing video capturing by X-ray imaging. Likewise, since fluoroscopic imaging continuously irradiates X-ray to the subject P at a relatively low voltage compared to when performing video capturing with X-ray imaging, a data amount of video capturing per unit time may also be suppressed. The fluoroscopic imaging is broadly classified into continuous fluoroscopic imaging and pulse fluoroscopic imaging.

Continuous fluoroscopic imaging is the fluoroscopic imaging where X-ray is continuously irradiated, and pulse fluoroscopic imaging is the fluoroscopic imaging where X-ray pulses are repeatedly irradiated. The pulse fluoroscopic imaging is inferior in the framerate of the fluoroscopic image but may suppress the exposure dose to the subject compared to the continuous fluoroscopic imaging. Note that, hereinafter, continuous fluoroscopic imaging and pulse fluoroscopic imaging will be simply referred to as fluoroscopic imaging when referring to without classification. Likewise, fluoroscopic imaging may acquire the single fluoroscopic image by irradiating X-ray once to the subject P.

(31) The imaging apparatus **10** also comprises an X-ray irradiating module **101**, a high voltage apparatus **103**, an X-ray detector **105**, and a bed **107**.

(32) The X-ray irradiating module **101** irradiates X-ray to the subject P. Specifically, the X-ray irradiating module **101** comprises an X-ray tube **1011** that generates X-ray and an X-ray apparatus **1013** that limits an X-ray irradiation field or weakens X-ray for a portion of the irradiation field.

(33) The X-ray tube **1011** is a vacuum tube that has a cathode (filament) that generates thermal electrons and an anode (target) that generates X-ray by receiving thermal electron collisions. The X-ray tube **1011** generates X-ray by using high voltage supplied from the high voltage apparatus **103** to irradiate thermal electrons from the cathode towards the anode. For instance, the X-ray tube **1011** may be a rotary anode type X-ray tube that generates X-ray by irradiating thermal electrons to a rotating anode.

(34) The X-ray aperture **1013** is configured by metal plates such as a lead plate. The X-ray aperture **1013** narrows the X-ray generated by the X-ray tube **1011** to control the range of X-ray irradiation to subject P. That is, the X-ray irradiation range may be narrowed by closing the aperture of the X-ray aperture **1013**, or in contrast, widen the X-ray irradiation range by opening the aperture of the X-ray aperture **1013**. Note that the X-ray aperture **1013** may be called as a collimator.

(35) The high voltage apparatus **103** supplies high voltage to the X-ray tube **1011** of the X-ray irradiating module **101** under the control of a processing circuit of the console apparatus **30**. For instance, the high voltage apparatus **103** has electric circuits such as a transformer and a rectifier, a high voltage generating apparatus that generates high voltage to apply to the X-ray tube **1011**, and an X-ray control apparatus that performs control of an output voltage in response to the X-ray irradiated by the X-ray tube **1011**. Note that the high voltage generating apparatus may be the transformer type of an inverter type.

(36) The X-ray detector **105** may be a flat panel detector (FPD) that has detection elements

arranged in a matrix shape. The X-ray detector **105** detects X-ray irradiated from the X-ray irradiating module **101** which passed through the subject P and outputs the detection signal in response to the detected amount of X-ray to the processing circuit of the console apparatus **30**. Note that the X-ray detector **105** may be an indirect conversion type detector that has a grid, scintillator array or an optical sensor array, or a direct conversion type detector that has semiconductor elements that convert incident X-ray to electrical signals.

(37) A bed **107** is a bed that accepts the subject P. X-ray imaging and/or fluoroscopic imaging are performed by the subject P lying on a top board of the bed **107**. Thus, the X-ray detector **105** is located below the bed **107**.

(38) The console apparatus **30** comprises the processing circuit **301**, a memory **303**, a display **305**, an input interface **307**, and an output interface **309**.

(39) The processing circuit **301** is a control circuit that performs an overall control of the X-ray diagnosis apparatus **1** and also an arithmetic circuit that performs various operations. For instance, the processing circuitry **301** according to the present embodiment has an imaging control function **3011**, an acquisition function **3012**, and a fluoroscopic image storing control function **3013**. The imaging control function **3011** is equivalent to an imaging control unit according to the present embodiment, the acquisition function **3012** is equivalent to an acquiring unit according to the present embodiment, and the fluoroscopic image storing control function **3013** is equivalent to a fluoroscopic image storing control unit according to the present embodiment.

(40) In the embodiment of FIG. **1**, each processing functions performed the imaging control function **3011**, the acquisition function **3012**, and the fluoroscopic image storing control function **3013** are stored in the memory **303** in a form of computer executable program. The processing circuitry **301** is a processor that realizes functions corresponding to each program by reading and executing the program from the memory **303**. Note that, in FIG. **1**, it was described that the imaging control function **3011**, the acquisition function **3012**, and the fluoroscopic image storing control function **3013** are realized by a single processing circuit **301**, but these functions may be realized by configuring the processing circuitry **301** by combining a plurality of independent processors and having each processor executing the program.

(41) The imaging control function **3011** is a function that controls an overall imaging timing of the X-ray diagnosis apparatus **1** and each functions following imaging conditions etc. In the present embodiment, the imaging control function **3011** performs X-ray imaging or fluoroscopic imaging by receiving instructions to start the X-ray imaging or fluoroscopic imaging via the input interface **307**.

(42) The acquisition function **3012** is a function that acquires imaging related information obtained within a certain period of time before or after the X-ray imaging. Imaging related information is an operation contents of the input interface **307**, information related to the subject such as the fluoroscopic image acquired by fluoroscopic imaging, or captured image acquired by X-ray imaging. In the present embodiment, the acquisition function **3012** acquires the operation contents of the input interface **307** as imaging related information.

(43) The fluoroscopic image storing control function **3013** is a function that stores the fluoroscopic image captured at least one of before or after the X-ray imaging based on the imaging related information. In the present embodiment, the fluoroscopic image storing control function **3013** determined whether to store the fluoroscopic image based on the operation contents of the input interface **307** and when determined to store the fluoroscopic image in the memory **303**, stores the fluoroscopic image captured before or after the X-ray imaging in the memory **303**.

(44) The memory **303** may be configured by a Random Access Memory (RAM), a semiconductor memory element such as a flash memory, a hard disk, or an optical disk etc. The memory **303** may be configured by a portable media such as a universal serial bus (USB) memory or a digital video disk (DVD). The memory **303** stores various processing programs used in the processing circuit **301** (includes application programs and operating systems (OS)), data necessary for executing the

program, and conditions to store the fluoroscopic image in the memory **303** set by the user.

(45) The display **305** displays various information. The display **305** may display the captured image or the fluoroscopic image acquired by the imaging apparatus **10** or a Graphical User Interface (GUI) to receive various input operation from an operator. The display **305** may be a Liquid Crystal Display (LCD), a Cathode Ray Tube (CRT) display, or an Electro Luminescence (EL) display etc. Note that the display **305** is equivalent to a display according to the present embodiment.

(46) The input interface **307**, for instance, receives various input operations from the user, converts the received input operation into electric signal, and outputs to the processing circuit **301**. The input interface **307** may be realized by a trackball, a switch button, a mouse, a keyboard, a touchpad that performs input operations by touching an operating screen, or a touch panel display where a display screen and the touchpad are integrated, etc. The input interface **307**, for instance, receives input of information about the subject P or imaging conditions etc., when imaging the subject P. The input interface **307** also has an X-ray imaging switch **3071** and a fluoroscopic imaging switch **3072**. Note that the input interface **307** may be realized by two switches that may switch between a first switch that starts X-ray imaging preparation and a second switch that starts the X-ray imaging in response to the user's pressing amount.

(47) The X-ray imaging switch **3071** is a switch to operate whether to perform X-ray imaging, i.e., whether to irradiate X-ray; and may be consisted of a hand switch. The X-ray imaging switch **3071** may also be referred to as an exposure switch. The X-ray imaging to the subject P, for instance, is performed when the X-ray imaging switch **3071** is pressed by the user until the X-ray imaging is terminated based on the imaging conditions set by the user. Note that the X-ray imaging switch **3071** may be provided in the imaging apparatus **10**.

(48) Likewise, the fluoroscopic imaging switch **3072** is a switch to operate whether to perform fluoroscopic imaging, i.e., whether to irradiate X-ray; and may be consisted of a foot switch. The fluoroscopic imaging switch **3072** may be arranged on a floor of a detecting room where the X-ray diagnosis apparatus **1** is provided. fluoroscopic imaging to the subject P, for instance, is performed when the fluoroscopic imaging switch **3072** is pressed by the user until the fluoroscopic imaging switch **3072** which was pressed is released by the user. Note that the fluoroscopic imaging switch **3072** may be provided in the imaging apparatus **10**.

(49) The output interface **309** may output signal supplied by the processing circuitry **301**. The output interface **309**, for instance, may be realized by an indicator such as a lamp, audio devices that outputs sound such as a speaker, or printed circuits such as a printer.

(50) Next, the fluoroscopic image storing control process performed in the X-ray diagnosis apparatus **1** according to the present embodiment will be described using FIGS. 2 and 3. FIG. 2 is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the present embodiment. FIG. 3 is a timing chart that illustrates timings of the fluoroscopic imaging, the X-ray imaging, and storing the fluoroscopic image. In the fluoroscopic image storing control process shown in FIG. 2, the X-ray diagnosis apparatus **1** stores the fluoroscopic image in the memory **303** based on the operation content of the X-ray imaging switch **3071**. For instance, the fluoroscopic image storing control process may be a process performed when the fluoroscopic imaging starts.

(51) As shown in FIG. 2, the X-ray diagnosis apparatus **1** first starts fluoroscopic imaging (Step S11). The process of starting the fluoroscopic imaging is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, as shown in FIG. 3, the X-ray diagnosis apparatus **1** irradiates X-ray to the subject P and starts the fluoroscopic imaging by receiving instruction to start the fluoroscopic imaging by the user. More specifically, as shown in FIG. 3, fluoroscopic imaging is turned ON and started when the fluoroscopic imaging switch **3072** is pressed. Likewise, by starting the fluoroscopic imaging, the X-ray diagnosis apparatus **1** displays the fluoroscopic image acquired by the fluoroscopic imaging on the display **305** as shown in FIG. 4. Note that the fluoroscopic imaging shown in FIG. 3 shows continuous fluoroscopic imaging that

irradiates X-ray continuously to perform fluoroscopic imaging, but the fluoroscopic imaging may be the pulse fluoroscopic imaging that irradiates X-ray intermittently to perform fluoroscopic imaging.

(52) Next, as shown in FIG. 2, the X-ray diagnosis apparatus **1** determines whether the X-ray imaging was received (Step S13). The process of determining whether the X-ray imaging was received is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether the input to start the X-ray imaging was received from the user via the X-ray imaging switch **3071**. Then, when determining that the input to start the X-ray imaging was not received (Step S13: No), the X-ray diagnosis apparatus **1** repeats the process of Step S13 and standbys. That is, the X-ray diagnosis apparatus **1** continues the fluoroscopic imaging started at Step S11.

(53) On the other hand, when determining that the input to start the X-ray imaging was received (Step S13: Yes), the X-ray diagnosis apparatus interrupts fluoroscopic imaging (Step S15). The process of interrupting the fluoroscopic imaging is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** interrupts the fluoroscopic imaging by receiving the input to start X-ray imaging via the X-ray imaging switch **3071**. More specifically, as shown in FIG. 3, the X-ray diagnosis apparatus **1** starts preparing the X-ray imaging and interrupts the fluoroscopic imaging when the X-ray imaging switch **3071** is pressed. That is, as shown in FIG. 3, fluoroscopic imaging is interrupted and X-ray imaging is preferentially performed by the X-ray imaging turned ON even when fluoroscopic imaging is performed. Preparing the X-ray imaging, for instance, may be controlling a tube current or the tube voltage based on imaging conditions of X-ray imaging.

(54) Note that if fluoroscopic imaging is interrupted, the X-ray diagnosis apparatus **1** may display on the display **305** an image of one frame of the fluoroscopic image acquired right before interrupting the fluoroscopic imaging, until the X-ray imaging is performed.

(55) Next, as shown in FIG. 2, the X-ray diagnosis apparatus **1** performs X-ray imaging (Step S17). The process of performing X-ray imaging is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** performs X-ray imaging by irradiating X-ray to subject P.

(56) Next, as shown in FIG. 2, the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging (Step S19). The process of restarting fluoroscopic imaging is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging by switching to fluoroscopic imaging after the X-ray imaging is terminated. More specifically, for instance, as shown in FIG. 3, the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging when the X-ray imaging becomes OFF and the fluoroscopic imaging ON. Also, by restarting the fluoroscopic imaging, the X-ray diagnosis apparatus **1** displays the fluoroscopic image acquired by fluoroscopic imaging on the display **305** as shown in FIG. 4.

(57) Next, as shown in FIG. 2, the X-ray diagnosis apparatus **1** acquires imaging related information obtained within the certain period of time before or after the X-ray imaging (Step S21). The process of obtaining image related information obtained within the certain period of time before or after the X-ray imaging is realized by the acquisition function **3012** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** acquires operation contents of the X-ray imaging switch **3071** which the user operates within the certain period of time before or after the X-ray imaging, as the image related information obtained within the certain period of time before or after the X-ray imaging. More specifically, as shown in FIG. 3, the X-ray diagnosis apparatus **1**, acquires a time T between when the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging at Step S19 until the user releases the X-ray imaging switch **3071**, i.e., between when the X-ray diagnosis apparatus **1** resumes fluoroscopic imaging until the X-ray imaging switch **3071** is turned OFF, as the operation content of the X-ray imaging switch **3071**.

(58) Note that at Step S21, the X-ray diagnosis apparatus **1** acquires time T between when the X-

ray diagnosis apparatus **1** restarts fluoroscopic imaging at Step **S19** until the X-ray imaging switch **3071** is released, as the operation content of the X-ray imaging switch **3071**, but the operation content of the X-ray imaging switch **3071** acquired by the X-ray diagnosis apparatus **1** is not limited to such. That is, the operation content of the X-ray imaging switch **3071** is arbitrary, and for instance, may be the time between when the user presses the X-ray imaging switch **3071** until the X-ray imaging switch **3071** is released, or a time between when the X-ray imaging is terminated until the X-ray imaging switch **3071** is released. Likewise, the operation contents of the X-ray imaging switch **3071** is not limited to the time of operating the X-ray imaging switch **3071**, but may be a predetermined operating manner such as a number of operating the X-ray imaging switch **3071** within the certain period of time before or after the X-ray imaging.

(59) Next, as shown in FIG. **2**, the X-ray diagnosis apparatus **1**, based on the image related information, determines whether to store the fluoroscopic image (Step **S23**). The process of determining whether to store the fluoroscopic image is realized by the fluoroscopic image storing control function **3013** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether to store the fluoroscopic image based on the operation content of the X-ray imaging switch **3071** acquired at Step **S21**. More specifically, the X-ray diagnosis apparatus **1** determines whether to store the fluoroscopic image in the memory **303** by comparing the time **T**, acquired at Step **S21**, between when the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging until the X-ray imaging switch **3071** turns OFF, and a threshold **a** that is preset as a condition to store the fluoroscopic image in the memory **303**, to determine whether time **T** is greater than threshold **a**.

(60) Then, at Step **S23**, if time **T** is greater than threshold **a**, i.e., when determining to store the fluoroscopic image (Step **S23**: Yes), the X-ray diagnosis apparatus **1** stores the fluoroscopic image in the memory **303** (Step **S25**). The process of storing the fluoroscopic image in the memory **303** is realized by the fluoroscopic image storing control function **3013** in the processing circuitry **301**. Specifically, as shown in FIG. **3**, the X-ray diagnosis apparatus **1** stores the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** until interrupting the fluoroscopic imaging at Step **S15**, and between restarting the fluoroscopic imaging at Step **S19** until releasing the X-ray imaging switch **3071**, in the memory **303**.

(61) Note that, at Step **S25**, the fluoroscopic image to be stored in the memory **303** is not limited to the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** until interrupting the fluoroscopic imaging at Step **S15**, and between restarting the fluoroscopic imaging at Step **S19** until releasing the X-ray imaging switch **3071**, in the memory **303**. That is, the fluoroscopic image to be stored in the memory **303** is arbitrary, and the X-ray diagnosis apparatus **1** may store the fluoroscopic image for a preset number of frames among the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** until interrupting the fluoroscopic imaging at Step **S15**, and between restarting the fluoroscopic imaging at Step **S19** until releasing the X-ray imaging switch **3071**, in the memory **303**.

(62) Likewise, the X-ray diagnosis apparatus **1** may store either of the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** until interrupting the fluoroscopic imaging at Step **S15**, and the fluoroscopic image acquired between restarting the fluoroscopic imaging at Step **S19** until releasing the X-ray imaging switch **3071**, in the memory **303**. That is, the X-ray diagnosis apparatus **1** may store the fluoroscopic image captured either before or after the X-ray imaging. Furthermore, at Step **S25**, the X-ray diagnosis apparatus **1** may select at least one of either fluoroscopic image captured before or after the X-ray imaging by the fluoroscopic image storing control function **3013** and store the selected fluoroscopic image in the memory **303**.

(63) At Step **S23**, if time **T** is less than threshold **a**, i.e., when determining not to store the fluoroscopic image (Step **S23**: No), after the process of Step **S25**, the X-ray diagnosis apparatus **1** determines whether to terminate the fluoroscopic imaging (Step **S27**). The process of determining whether to terminate the fluoroscopic imaging is realized by the imaging control function **3011** in

the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether to terminate fluoroscopic imaging by determining whether the input to start fluoroscopic imaging was received from the user via the fluoroscopic imaging switch **3072**.

(64) Then, at Step **S27**, if the fluoroscopic imaging of the user was not received via the fluoroscopic imaging switch **3072**, i.e., not terminating the fluoroscopic imaging (Step **S27**: No), the X-ray diagnosis apparatus **1** determines whether the X-ray imaging was received (Step **S29**). The step of determining whether the X-ray imaging was received is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether the input to start the X-ray imaging was received from the user via the X-ray imaging switch **3071**.

(65) Then, at Step **S29**, when determining that the input to start the X-ray imaging was not received from the user via the X-ray imaging switch **3071** (Step **S29**: No), the X-ray diagnosis apparatus **1** repeats the process of Step **S27** and Step **S29** and standbys. On the other hand, when determining that the input to start the X-ray imaging was received from the user via the X-ray imaging switch **3071** (Step **S29**: Yes), the X-ray diagnosis apparatus **1** returns to Step **S15** and repeats the process from Step **S15**.

(66) On the other hand, at Step **S27**, if the input of the fluoroscopic imaging was not received from the user via the fluoroscopic imaging switch **3072** (Step **S31**: Yes), the X-ray diagnosis apparatus **1** terminates the fluoroscopic imaging (Step **S31**). The process of terminating the fluoroscopic imaging is realized by the imaging control function **3011** in the processing circuitry **301**.

(67) By executing Step **S31**, the fluoroscopic image storing control process according to the present embodiment is terminated.

(68) As described above, in the X-ray diagnosis apparatus **1** according to the present embodiment, since the X-ray diagnosis apparatus **1** acquires the operation content of the X-ray imaging switch **3071** as the image related information acquired within the certain period of time before or after the X-ray imaging, determines whether to store in the memory **303** the fluoroscopic image captured before or after the X-ray imaging based on the operation content of the X-ray imaging switch **3071**, and stores the fluoroscopic image captured before or after the fluoroscopic imaging in the memory **303** when determining to store the fluoroscopic image captured before or after the X-ray imaging in the memory **303**, the fluoroscopic image may be stored in a simple and appropriate manner. That is, in the present embodiment, since the X-ray diagnosis apparatus **1** stores the fluoroscopic image in the memory **303** when pressing the X-ray imaging switch **3071** which the user presses to perform X-ray imaging even after the X-ray imaging is terminated, and the time T of pressing the X-ray imaging switch **3071** after the X-ray imaging is greater than the preset threshold a , the user may store the necessary fluoroscopic image without performing operations other than imaging operations.

(69) Note that in the present embodiment described above, the X-ray diagnosis apparatus **1** acquired the operation content of the X-ray imaging switch **3071**, but the operation contents which the X-ray diagnosis apparatus **1** acquires is not limited to the X-ray imaging switch **3071**. That is, a target of the operation content which the X-ray diagnosis apparatus **1** acquires is arbitrary, and for instance, may be the operation content of the fluoroscopic imaging switch **3072**, or the operation content of the input interface **307** other than the X-ray imaging switch **3071** or the fluoroscopic imaging switch **3072**.

(70) [First Modification]

(71) In the X-ray diagnosis apparatus **1** according to the first embodiment described above, it is possible to determine the number of frames to store in the memory **303** in response to an operation time of the X-ray imaging switch **3071** and store in the memory **303** the fluoroscopic image for the determined number of frames, instead of storing in the memory **303** the fluoroscopic image acquired between starting the fluoroscopic imaging until interrupting the fluoroscopic imaging and between restarting the fluoroscopic imaging until releasing the X-ray imaging switch **3071**. With a

first modification where the modification is applied to the first embodiment described above, parts that differ from the first embodiment will be described below. Note that the configuration of the X-ray diagnosis apparatus **1** according to the first modification is equivalent to that of FIG. **1**, and description will be omitted.

(72) Next, the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the first modification will be described using FIGS. **5** and **6**. FIG. **5** is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the first modification, which corresponds to FIG. **2** of the first embodiment described above. FIG. **6** is a timing chart that illustrates timings of a fluoroscopic imaging, an X-ray imaging, and storing the fluoroscopic image according to the first modification, which corresponds to FIG. **3** of the first embodiment described above. In the fluoroscopic image storing control process shown in FIG. **5**, the X-ray diagnosis apparatus **1** determines the number of frames to store in the memory **303** or store the fluoroscopic image for the determined number of frames based on the operation content of the X-ray imaging switch **3071**. For instance, the fluoroscopic image storing control process is a process executed when the fluoroscopic imaging starts. Note that the process before Step **S23** shown in FIG. **5** is equivalent to that of FIG. **2** described above, and description will be omitted.

(73) Then, at Step **S23**, if time T is greater than the threshold a , i.e., when determining to store the fluoroscopic image (Step **S23**: Yes), the X-ray diagnosis apparatus **1** acquires the operation time of the X-ray imaging switch **3071** (Step **S41**). The process of acquiring the operation time of the X-ray imaging switch **3071** is realized by the fluoroscopic image storing control function **3013** in the processing circuitry **301**. Specifically, as shown in FIG. **6**, the X-ray diagnosis apparatus **1** acquires the time between when the X-ray diagnosis apparatus **1** restarts the fluoroscopic imaging at Step **S19** until the user releases the X-ray imaging switch **3071**, i.e., time T between when the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging until the X-ray imaging switch **3071** is turned OFF.

(74) Note that the X-ray diagnosis apparatus **1** acquired time T between when the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging at Step **S19** until releasing the X-ray imaging switch **3071** as the operation time of the X-ray imaging switch **3071**, but the operation time of the X-ray imaging switch **3071** which the X-ray diagnosis apparatus **1** acquires is not limited to this. That is, the operation time of the X-ray imaging switch **3071** is arbitrary, and for instance, may be the time between pressing and releasing the X-ray imaging switch **3071** by the user, or may be the time between terminating the X-ray imaging and releasing the X-ray imaging switch **3071**. Also, at Step **S21**, when acquiring the operation time of the X-ray imaging switch **3071** as the operation content of the X-ray imaging switch **3071**, Step **S41** is omitted.

(75) Next, as shown in FIG. **5**, the X-ray diagnosis apparatus **1** determines the number of frames of the fluoroscopic image to store in the memory **303** (Step **S43**). The process of determining the number of frames of the fluoroscopic image is realized by the fluoroscopic image storing control function **3013** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines the number of frames of the fluoroscopic image to store in the memory **303** in response to the operation time of the X-ray imaging switch **3071** acquired at Step **S41**.

(76) More specifically, as shown in FIG. **6**, the X-ray diagnosis apparatus **1** determines the number of frames of the fluoroscopic image equivalent to time T before interrupting the fluoroscopic imaging among the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** and interrupting the fluoroscopic imaging at Step **S15**, and the number of frames of the fluoroscopic image equivalent to time T after restarting the fluoroscopic imaging among the fluoroscopic image acquired between restarting the fluoroscopic imaging and terminating the fluoroscopic imaging, as the number of frames of the fluoroscopic image to store in the memory **303** in response to time T , which is the operation time of the X-ray imaging switch **3071**, between when the X-ray diagnosis apparatus **1** restarts fluoroscopic imaging until the X-ray imaging switch

3071 is turned OFF. In the example shown in FIG. 6, the number of frames of the fluoroscopic image equivalent to time T before interrupting the fluoroscopic imaging among the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** and interrupting the fluoroscopic imaging at Step **S15**, and the number of frames of the fluoroscopic image equivalent to time T after restarting the fluoroscopic imaging among the fluoroscopic image acquired between restarting the fluoroscopic imaging and terminating the fluoroscopic imaging are the same.

(77) Note that the X-ray diagnosis apparatus **1**, for instance, may determine the number of frames of the fluoroscopic image equivalent to time $1.5T$ before interrupting the fluoroscopic imaging among the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** and interrupting the fluoroscopic imaging at Step **S15**, and the number of frames of the fluoroscopic image equivalent to time $0.5T$ after restarting the fluoroscopic imaging among the fluoroscopic image acquired between restarting the fluoroscopic imaging and terminating the fluoroscopic imaging, as the number of frames of the fluoroscopic image to store in the memory **303**.

(78) Also, at Step **S43**, the X-ray diagnosis apparatus **1** stored in the memory **303** the number of frames of the fluoroscopic image equivalent to time T in response to the acquired time T, but the number of frames to store in the memory **303** may not be equivalent to time T. That is, the number of frames of the fluoroscopic image to store in the memory **303** is arbitrary, and the number of frames of the fluoroscopic image before interrupting the fluoroscopic imaging among the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** and interrupting the fluoroscopic imaging at Step **S15**, and the number of frames of the fluoroscopic image after restarting the fluoroscopic imaging among the fluoroscopic image acquired between restarting the fluoroscopic imaging and terminating the fluoroscopic imaging, may not depend on time T but be different.

(79) Next, as shown in FIG. 5, the X-ray diagnosis apparatus **1** stores the fluoroscopic image in the memory **303** (Step **S45**). The process of storing the fluoroscopic image in the memory **303** is realized by the fluoroscopic image storing control function **3013** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** store the fluoroscopic image in the memory **303** by the number of frames of the fluoroscopic image determined at Step **S43**. Note that Steps **S27** to **S31** after Step **S45** is equivalent to that of FIG. 2 in the first embodiment, and description will be omitted. Then, by executing Step **S31**, the fluoroscopic image storing control process according to the first modification is terminated.

(80) As described above, since the X-ray diagnosis apparatus **1** according to the present modification acquires the operation time of the X-ray imaging switch **3071**, determines the number of frames of the fluoroscopic image to store in the memory **303** in response to the operation time of the X-ray imaging switch **3071** that is acquired, and stores the determined number of frames of the fluoroscopic image in the memory **303**, necessary fluoroscopic image may be stored while reducing oppression on the memory without additional operations other than the imaging operation. That is, fluoroscopic image may be stored in an appropriate and simple manner.

(81) Note that, in the present modification, the X-ray diagnosis apparatus **1** determined the number of frames to store in the memory **303** in response to the time of operating the X-ray imaging switch **3071**, but the operation target when determining the number of frames is not limited to the X-ray imaging switch **3071**. That is, the operation target when determining the number of frames is arbitrary, and for instance, may be the operation time of the fluoroscopic imaging switch **3072** or the operation time of the input interface **307** other than the X-ray imaging switch **3071** or the fluoroscopic imaging switch **3072**.

(82) [Second Modification]

(83) In the X-ray diagnosis apparatus **1** according to the first embodiment described above, it is possible to store in the memory **303** the fluoroscopic image captured at least one of before or after the X-ray imaging, instead of storing in the memory **303** the fluoroscopic image captured both before or after the X-ray imaging. With a second modification where the modification is applied to

the first embodiment described above, parts that differ from the first embodiment will be described below. Note that the configuration of the X-ray diagnosis apparatus **1** according to the second modification is equivalent to that of FIG. **1**, and description will be omitted.

(84) Next, the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the second modification will be described using FIGS. **7** and **8**. FIG. **7** is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the second modification, which corresponds to FIG. **2** of the first embodiment described above. FIG. **8** is a timing chart that illustrates timings of a fluoroscopic imaging, an X-ray imaging, and storing the fluoroscopic image according to the second modification, which corresponds to FIG. **3** of the first embodiment described above. In the fluoroscopic image storing control process shown in FIG. **7**, the X-ray diagnosis apparatus **1** stores in the memory **303** the fluoroscopic image captured before the X-ray imaging based on an operation content of the X-ray imaging switch **3071**. For instance, the fluoroscopic image storing control process may be a process executed when the fluoroscopic imaging starts. Note that the process of Steps **S11** and **S13** shown in FIG. **7** is equivalent to that of FIG. **2** described above, and description will be omitted.

(85) On the other hand, at Step **S13**, if the X-ray diagnosis apparatus **1** determines that the input to start X-ray imaging was received, the X-ray diagnosis apparatus **1** terminates the fluoroscopic imaging (Step **S51**). The process of terminating the fluoroscopic imaging is realized by the imaging control function **3011** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** terminates fluoroscopic imaging by receiving the input to start the X-ray imaging via the X-ray imaging switch **3071**. More specifically, as shown in FIG. **3**, the X-ray diagnosis apparatus **1** starts X-ray imaging preparation and terminates when the X-ray imaging switch **3071** is pressed. Note that, the process of Step **S17** after Step **S51** is equivalent to that of FIG. **2** in the first embodiment described above, and description will be omitted.

(86) Next, as shown in FIG. **7**, the X-ray diagnosis apparatus **1** acquires the image related information obtained within the certain period of time before or after the X-ray imaging (Step **S53**). The step of acquiring the image related information obtained within the certain period of time before or after the X-ray imaging is realized by the acquisition function **3012** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** acquires the operation content of the X-ray imaging switch **3071** which the user operates within the certain period of time before or after the X-ray imaging, as the image related information obtained within the certain period of time. More specifically, as shown in FIG. **7**, the X-ray diagnosis apparatus **1** acquires time **T** between when the X-ray imaging is terminated at Step **S17** until the user releases the X-ray imaging switch **3071**, i.e., between when the X-ray imaging is terminated at Step **S17** until the X-ray imaging switch **3071** is turned OFF. Note that the process of Step **S23** after Step **S53** is equivalent to that of FIG. **2** in the first embodiment described above, and description will be omitted.

(87) Likewise, the X-ray diagnosis apparatus **1** acquired the time between when the X-ray imaging is terminated at Step **S17** until the user releases the X-ray imaging switch **3071**, as the operation content of the X-ray imaging switch, but the operation content of the X-ray imaging switch **3071** acquired by the X-ray diagnosis apparatus **1** is not limited to this. That is, the content of the X-ray imaging switch **3071** is arbitrary, and for instance, may be the time between pressing and releasing the X-ray imaging switch **307**. Likewise, the operation content of the X-ray imaging switch **3071** is not limited to the time of operating the X-ray imaging switch **3071**, but may be preset aspect of operation of the X-ray imaging switch **3071**, such as the number of times of operating the X-ray imaging switch **3071** within the certain period of time before or after the X-ray imaging.

(88) Then, at Step **S23**, if time **T** is greater than threshold **a**, i.e., when determining to store the fluoroscopic image in the memory (Step **S23**: Yes), the X-ray diagnosis apparatus **1** stores the fluoroscopic image in the memory **303** (Step **S55**). The process of storing the fluoroscopic image in the memory is realized by the fluoroscopic image storing control function **3013** in the processing

circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** stores in the memory **303** the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** and terminating the fluoroscopic imaging at Step **S51**.

(89) Note that, at Step **S25**, the fluoroscopic image to be stored in the memory **303** is not limited to the fluoroscopic image acquired between starting the fluoroscopic imaging at Step **S11** and terminating the fluoroscopic imaging at Step **S51**. That is, the fluoroscopic image to be stored in the memory **303** is arbitrary, and for instance, may store the fluoroscopic image for the predetermined number of frames in the memory **303**, among the fluoroscopic image acquired between starting fluoroscopic imaging at Step **S11** until terminating the fluoroscopic imaging at Step **S51**, or if the fluoroscopic image captured before or after the X-ray imaging is acquired, acquire both the fluoroscopic image captured before or after the X-ray imaging, similar to the first embodiment described above.

(90) Steps **S27** to **S31** after Step **S55** are equivalent to that of FIG. **2** in the first embodiment described above, and description will be omitted. Then, by executing Step **S31**, the fluoroscopic image storing control process according to the second modification of the first embodiment is terminated.

(91) As described above, since the X-ray diagnosis apparatus **1** according to the present modification, acquires time **T** between terminating the X-ray imaging at Step **S17** and the user releasing the X-ray imaging switch **3071** as the operation content of the X-ray imaging switch as the image related information obtained within the certain period of time before or after the X-ray imaging, compares time **T** with the preset threshold **a**, and if time **T** is greater than the threshold **a**, stores the fluoroscopic image captured before the X-ray imaging in the memory **303**, the fluoroscopic image may be stored in an appropriate and simple manner. That is, in the present modification, since it is possible to store the fluoroscopic image captured before the X-ray imaging in the memory **303** by continuing to press the X-ray imaging switch **3071** which the user presses to perform the X-ray imaging even after the X-ray imaging is terminated, necessary fluoroscopic image may be stored while reducing oppression on the memory without additional operations other than the imaging operation.

(92) Note that the description of the second modification described above is a description for a case applied to the first embodiment, it is clear that the present modification may be applied to the first modification of the first embodiment. Likewise, in the present modification, the X-ray diagnosis apparatus **1** acquired the operation content of the X-ray imaging switch **3071**, but the target of the operation content is not limited to that of the X-ray imaging switch **3071**. That is, the target of the operation content which the X-ray diagnosis apparatus **1** acquires is arbitrary, and for instance, may be the operation content of the fluoroscopic imaging switch **3072**, or the operation content of the input interface **307** other than the X-ray imaging switch **3071** or the fluoroscopic imaging switch **3072**.

Second Embodiment

(93) The X-ray diagnosis apparatus **1** according to the first embodiment described above determined whether to store the fluoroscopic image in the memory **303** as the image related information based on the operation content of the X-ray imaging switch **3071** operated within the certain period of time before or after the X-ray imaging, but embodiments are not limited to this. In the second embodiment, the X-ray diagnosis apparatus **1** may acquire the fluoroscopic image as the image related information and determine whether to store the fluoroscopic image in the memory **303** based on a result of an image analysis of the acquired fluoroscopic image. Parts that differ from that of the first embodiment will be described below.

(94) FIG. **9** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus **1** according to the second embodiment, which corresponds to FIG. **1** of the first embodiment described above. As shown in FIG. **9**, in the present embodiment, the functions of the acquisition function and the fluoroscopic image storing control function differ from that of the first

embodiment and will be denoted as the acquisition function **3012a** and the fluoroscopic image storing control function **3013a**. Note that the configuration and functions other than the acquisition function **3012a** and the fluoroscopic image storing control function **3013a** are equivalent to that of FIG. **1** in the first embodiment, and description will be omitted.

(95) The acquisition function **3012a** is a function that acquires the image related information obtained within the certain period of time before or after the X-ray imaging. In the present embodiment, the acquisition function **3012a** acquires the fluoroscopic image captured either at least one of before or after the X-ray imaging.

(96) The fluoroscopic image storing control function **3013a** is a function that stores in the memory **303** the fluoroscopic image captured either at least one of before or after the X-ray imaging based on the image related information. In the present embodiment, the fluoroscopic image storing control function **3013a** performs the image analysis of the fluoroscopic image, determines whether to store the fluoroscopic image captured either at least one of before or after the X-ray imaging based on the result of the image analysis, and if determined to store the fluoroscopic image in the memory **303**, stores the fluoroscopic image in the memory **303**.

(97) Next, the fluoroscopic image storing control process that stores the fluoroscopic image, executed in the X-ray diagnosis apparatus **1** according to the present embodiment will be described using FIG. **10**. FIG. **10** is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the present embodiment, which corresponds to FIG. **1** of the first embodiment described above. In the fluoroscopic image storing control process shown in FIG. **10**, the X-ray diagnosis apparatus **1** image analyzes the fluoroscopic image and determines whether to store the fluoroscopic image in the memory **303** based on the result of the analysis result of the fluoroscopic image. For instance, the fluoroscopic image storing control process is a process executed when the fluoroscopic imaging starts. Note that the process before Step **S19** shown in FIG. **9** is equivalent to that of FIG. **2** in the first embodiment described above, and description will be omitted.

(98) Next, as shown in FIG. **10**, the X-ray diagnosis apparatus **1** acquires the fluoroscopic image as the image related information (Step **S61**). The process of acquiring the fluoroscopic image is realized by the acquisition function **3012a** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** acquires a plurality of fluoroscopic images among the fluoroscopic images acquired between starting the fluoroscopic imaging at Step **S11** and interrupting the fluoroscopic imaging at Step **S15** and the fluoroscopic images acquired within the certain period from Step **S19**.

(99) Next, as shown in FIG. **10**, the X-ray diagnosis apparatus **1** image analyzes the fluoroscopic image (Step **S63**). The process of image analyzing the fluoroscopic image is realized by the fluoroscopic image storing control function **3013a** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** image analyzes the plurality of fluoroscopic images acquired at Step **S61**. More specifically, the X-ray diagnosis apparatus **1** detects the movement of the target on the fluoroscopic image by image analyzing the fluoroscopic image acquired at Step **S61**.

(100) An example of the image analysis performed at Step **S63** will be described using FIG. **11**. FIG. **11** is an exemplary diagram that describes an exemplary image analysis executed in the X-ray diagnosis apparatus **1** according to the present embodiment; FIG. **11(a)** is the fluoroscopic image one frame before right before interrupting the fluoroscopic imaging; and FIG. **11(b)** is the fluoroscopic image right before interrupting the fluoroscopic imaging. In the example shown in FIG. **11**, the fluoroscopic image is the fluoroscopic image that fluoroscopically imaged the stomach ST of the subject P, a region surrounded by a dotted line is an exemplary region of interest ROI of the user, and a dot-shaped hatching portion within the fluoroscopic image is a contrast agent CON inserted within the target stomach ST.

(101) For instance, as shown in FIG. **11**, in an imaging using the contrast agent CON such as barium, since there is a possibility of the contrast agent CON inputting the user's region of interest when performing X-ray imaging when the contrast agent CON moves within the stomach ST, the

user may decide to observe the fluoroscopic image that is fluoroscopically imaged before or after the X-ray imaging when the contrast agent CON is moving. For this reason, in the example shown in FIG. 11 at Step S63, the X-ray diagnosis apparatus 1 calculates a motion vector of the contrast agent CON within the region of interest ROI of the fluoroscopic image for two frames by image analysis based on the fluoroscopic image for two frames right before interrupting the fluoroscopic imaging. That is, the X-ray diagnosis apparatus 1 calculates a movement amount of the contrast agent CON within the region of interest ROI based on the fluoroscopic image for two frames right before interrupting the fluoroscopic imaging.

(102) Note that the region of interest ROI is a part of the fluoroscopic image in the example shown in FIG. 11, but the region of interest ROI is not limited to be the part of the fluoroscopic image. That is, the region of interest ROI is arbitrary, and for instance, may be the whole fluoroscopic image or multiple locations on the fluoroscopic image.

(103) Likewise, in the example shown in FIG. 11, with the stomach ST as the imaging target, the image analysis of the fluoroscopic image of the stomach ST was described as an example in FIG. 11, but the fluoroscopic image of, the stomach ST is not limited to this. That is, the imaging target is arbitrary and for instance, may be blood veins or organs other than the stomach ST. Furthermore, the object that detects motion is the contrast agent CON in the example shown in FIG. 11, but the object of detecting motion is not limited to the contrast agent CON. That is, the object of detecting motion is arbitrary, and for instance, may be medical devices such as a catheter.

(104) Next, as shown in FIG. 10, the X-ray diagnosis apparatus 1 determines whether to store the fluoroscopic image based on the image related information (Step S65). The process of determining whether to store the fluoroscopic image is realized by the fluoroscopic image storing control function 3013a in the processing circuitry 301. Specifically, the X-ray diagnosis apparatus 1 determines whether to store the fluoroscopic image in the memory based on the motion of the target detected at Step S63, which is the image analysis result analyzed at Step S63. More specifically, the X-ray diagnosis apparatus 1 determines whether the movement amount of the motion vector calculated at Step S63, i.e., the movement amount of the contrast agent CON within the region of interest ROI is greater than a specified amount of a preset movement amount, and determines whether to store the fluoroscopic image in the memory 303.

(105) Then, at Step S65, if the movement amount of the contrast agent CON within the region of interest ROI is greater than the preset movement amount, i.e., when determining to store the fluoroscopic image in the memory 303 (Step S65: Yes), the X-ray diagnosis apparatus 1 stores the fluoroscopic image in the memory 303 (Step S25). On the other hand, at Step S65, if the movement amount of the contrast agent CON within the region of interest ROI is less than the preset movement amount, i.e., when determining not to store the fluoroscopic image in the memory 303 (Step S65: No), the X-ray diagnosis apparatus 1 determines whether to terminate the fluoroscopic imaging (Step S27).

(106) Steps S25 to S31 after Step S65 is equivalent to that of FIG. 2 of the first embodiment described above, and description will be omitted. Then, the fluoroscopic image storing control process according to the second embodiment is terminated by executing Step S31.

(107) As described above, in the X-ray diagnosis apparatus 1 according to the present embodiment, the X-ray diagnosis apparatus 1 acquires the fluoroscopic image as the image related information acquired within the certain period of time before or after the X-ray imaging, performs image analysis on the acquired fluoroscopic image, determines whether to store the fluoroscopic image captured before or after the X-ray imaging based on the image analysis result of the fluoroscopic image, and stores the fluoroscopic image captured before or after the X-ray imaging when determining to store in the memory 303 the fluoroscopic image captured before or after the X-ray imaging, fluoroscopic image may be stored in an appropriate and simple manner. That is, in the present embodiment, since the X-ray diagnosis apparatus 1 stores the fluoroscopic image in the memory 303 by detecting the movement amount of the object in the fluoroscopic image with the

image analysis of the fluoroscopic image and if the movement amount of the movement is greater than a specific amount, the user may store necessary fluoroscopic image without additional operation.

(108) Note that the fluoroscopic image captured before or after the X-ray imaging is stored in the memory **303** in the description of the second embodiment described above, but the X-ray diagnosis apparatus **1** may store in the memory either one of the fluoroscopic image captured before or after the X-ray imaging based on the image analysis result of the fluoroscopic image. That is, the X-ray diagnosis apparatus **1** may store at least one of the fluoroscopic image captured before or after the X-ray imaging based on the image analysis result of the fluoroscopic image. Likewise, in the second embodiment described above, the X-ray diagnosis apparatus **1** may select by the fluoroscopic image storing control function **3013** at least one of the fluoroscopic images captured before or after the X-ray imaging and store the selected fluoroscopic image in the memory **303**.

Third Embodiment

(109) In the X-ray diagnosis apparatus **1** according to the first embodiment described above, it was determined whether to store the fluoroscopic image in the memory **303** based on the operation content of the X-ray imaging switch **3071** which the user operates within the certain period of time before or after the X-ray imaging, which is the image related information, but embodiments are not limited to this. In a third embodiment, the captured image may be acquired as the image related information and it may be determined whether to store the fluoroscopic image in the memory **303** based on the image analysis result of the acquired captured image. Parts that differ from the first embodiment will be described below.

(110) FIG. **12** is a block diagram that illustrates a configuration example according to the third embodiment, which corresponds to FIG. **1** according to the first embodiment described above. As shown in FIG. **9**, the X-ray diagnosis apparatus **1** according to the present embodiment is configured by adding a training function to the X-ray diagnosis apparatus **1** according to the first embodiment described above. Likewise, since the functions of the acquisition function and the fluoroscopic image storing control function are different from that of the first embodiment, those will be referred to as the acquisition function **3012b** and the fluoroscopic image storing control function **3013b** in the present embodiment. Note that the training function **3014** is equivalent to a training unit in the present embodiment. Likewise, configurations and functions other than the acquisition function **3012b**, the fluoroscopic image storing control function **3013b**, and the training function **3014** are equivalent to that of FIG. **1** in the first embodiment described above, description will be omitted.

(111) The acquisition function **3012b** is a function that acquired the image related information obtained within the certain period of time before or after the X-ray imaging. In the present embodiment, the acquisition function **3012b** acquired the X-ray imaged captured image as the image related information.

(112) The fluoroscopic image storing control function **3013b** is a function that stores in the memory **303** at least one of the fluoroscopic images captured before and the X-ray imaging based on the image related information. In the present embodiment, the fluoroscopic image storing control function **3013b** inputs the captured image acquired by the acquisition function **3012b** to a trained model that went through machine learning to output fluoroscopic storing information related to storing at least one of the fluoroscopic image captured before and the X-ray imaging based on the captured image, and determines whether to store the fluoroscopic image in the memory **303** based on the fluoroscopic storing information related to storing at least one of the fluoroscopic image captured before and the X-ray imaging. That is, captured image is input, and the fluoroscopic image storing control function **3013b** performs image analysis on the input captured image, inputs the captured image to the trained model that outputs fluoroscopic storing information based on the image analysis result of the fluoroscopic image, and determines whether to store the fluoroscopic image in the memory **303** based on the fluoroscopic storing information output from the trained

model.

(113) The fluoroscopic storing information is information related to storing the fluoroscopic image. The fluoroscopic storing information may include information related to a necessity of storing the fluoroscopic image in the memory **303**, information related to the number of frames of the fluoroscopic image to store in the memory **303**, and information related to selecting at least one of the fluoroscopic images captured before and the X-ray imaging. In the description below, an example is shown where the fluoroscopic storing information includes information related to the necessity of storing and the information related to the number of frames of the fluoroscopic image to store. Note that the fluoroscopic storing information may be configured including the information related to the necessity of storing or may include other information related to storing the fluoroscopic image.

(114) Machine learning may use machine learning that uses a Support Vector Machine (SVM) or deep learning that uses a multilayer neural network such as a Convolutional Neural Network (CNN) or a Convolutional Deep Belief Neural Network. In the description below, an example is shown where the machine learning is the deep learning that uses the neural network and a machine learning model is a trained model that uses deep learning.

(115) The training function **3014** is a function that builds a trained model. In the present embodiment, the training function **3014** builds the trained model, using a training data set with the plurality of captured images as a training data and a fluoroscopic storing result as a validation data. The fluoroscopic storing result (validation data) may be a data created by determining whether an expert requires the fluoroscopic image captured before or after the X-ray imaging when interpreting the captured image. The fluoroscopic storing result includes information related to whether the fluoroscopic image was stored and information related to the number of frames. Note that the fluoroscopic storing result (validation data) may be a data created by the training function **3014** determining whether the fluoroscopic image acquired before or after the X-ray imaging is necessary based on whether at least one of the fluoroscopic image, captured before or after the X-ray imaging of the captured image stored in the memory **303**, is stored in the memory **303**.

(116) FIG. **13** is an exemplary diagram that describes an exemplary data flow during training the fluoroscopic image storing control function **3013b**. As shown in FIG. **13**, during training, the fluoroscopic image storing control function **3013b** sequentially updates a parameter data **505** stored in the memory **303** by performing deep learning using numerous training data set.

(117) Each training data set of the numerous training data set consists of a training data group **501** and a validation data group **503**. The training data group **501** is comprised by training data **5011**, **5012**, **5013** . . . , and each training data may consist of the captured image. Likewise, the validation data group **503** corresponding to each training data is comprised by fluoroscopic storing result **5031**, **5032**, **5033** . . . , and each fluoroscopic storing result **5031**, **5032**, **5033** . . . may consist of information related to the storing result or information related to the number of frames to store.

(118) The fluoroscopic image storing control function **3013b** is controlled by the training function **3014** and updates the parameter data **505** such that a result of processing the training data with the neural network **507** becomes closer to the verification data for every training data set that is given. That is, the fluoroscopic image storing control function **3013b** is trained. In general, when a changing rate of the parameter data **505** converges within a threshold, it is determined that training is complete. Hereinafter, the parameter data **505** for which training is complete will be referred to as a trained parameter data **505t**.

(119) FIG. **14** is an exemplary diagram that describes an exemplary data flow during operating the fluoroscopic image storing control function **3013b**. As shown in FIG. **14**, during training, the fluoroscopic image storing control function **3013b** inputs the captured image **72** acquired by the acquisition function **3012b** into the trained model and determines whether to store at least one of the fluoroscopic images captured before or after the X-ray imaging based on the fluoroscopic storing information **74** output from the trained model.

(120) Note that the trained parameter data **505t** and the neural network **507** configures the trained model **50**. Such method of training and building the trained model may use various methods. The neural network **507** is stored in the memory **303** in the form of the program. The trained parameter data **505t** may be stored in the memory **303** or a storage connected with the processing circuitry **301**. If the trained model **50** (neural network **507** and trained parameter data **505t**) is stored in the memory **303**, the fluoroscopic image storing control function **3013b** that is executed by the processor of the processing circuitry **301** may input the captured image **72** in the trained model **50** by reading and executing the trained model **50** from the memory **303** and determined whether to store at least one of the fluoroscopic image captured before or after the X-ray imaging based on the fluoroscopic storing information **74** that is output from the trained model **50**. The trained model **50** may also be built by integrated devices such as an Application Specific Integrated Circuit (ASIC) or a Field Programmable Gate Array (FPGA).

(121) Next, a fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the present embodiment will be described using FIG. **15**. FIG. **15** is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the present embodiment, which correspond to FIG. **2** of the first embodiment described above. In the fluoroscopic image storing control process shown in FIG. **15**, the X-ray diagnosis apparatus **1** determines whether to store the fluoroscopic image in the memory **303** based on the image analysis result of the captured image **72**. The fluoroscopic image storing control process may be a process executed when fluoroscopic imaging is started. Note that the process before Step **S19** shown in FIG. **15** is equivalent to that of FIG. **2** of the first embodiment described above, and description will be omitted.

(122) Next, as shown in FIG. **15**, the X-ray diagnosis apparatus **1** acquired the captured image **72** as the image related information (Step **S71**). The process of acquiring the captured image **72** is realized by the acquisition function **3012** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** acquired the captured image by the X-ray imaging at Step **S17**.

(123) Next, as shown in FIG. **15**, the X-ray diagnosis apparatus **1** image analyzes the captured image **72** (Step **S73**). The process of image analyzing the captured image **72** is realized by the fluoroscopic image storing control function **3013b** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** inputs the captured image **72** acquired at Step **S71** to the trained model **50**, image analyzes the inputted captured image **72**, and outputs the fluoroscopic storing information based on the image analysis result of the captured image **72**.

(124) Next, as shown in FIG. **15**, the X-ray diagnosis apparatus **1** determines whether to store the fluoroscopic image (Step **S75**). The process of determining whether to store the fluoroscopic image is realized by the fluoroscopic image storing control function **3013b** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether to store the fluoroscopic image based on the fluoroscopic storing information **74** that is output from the trained model **50** at Step **S73**.

(125) Then, when determining to store the fluoroscopic image at Step **S75** (Step **S75**: Yes), the X-ray diagnosis apparatus **1** stores the fluoroscopic image in the memory **303** (Step **S25**). On the other hand, when determining not to store the fluoroscopic image based on the fluoroscopic storing information **74** (Step **S75**: No), the X-ray diagnosis apparatus **1** determines whether to terminate the fluoroscopic imaging (Step **S27**).

(126) Steps **S25** to **S31** after Step **S75** is equivalent to that of FIG. **2** of the first embodiment described above, and description will be omitted. Then, the fluoroscopic image storing control process according to the third embodiment is terminated by executing Step **S31**.

(127) As described above, in the present embodiment, since the X-ray diagnosis apparatus **1** acquires the captured image **72** as the image related information obtained within the certain period of time before or after the X-ray imaging, performs image analysis on the acquired captured image **72**, determines whether to store the fluoroscopic image captured before or after the X-ray imaging

in the memory **303** based on the image analysis result of the captured image **72**, and stores the fluoroscopic image captured before or after the X-ray imaging in the memory **303** when determining to store the fluoroscopic image captured before or after the X-ray imaging in the memory **303**, it is possible to store the fluoroscopic image in an appropriate and simple manner. That is, in the present embodiment, since it is made to input the captured image **72** to the trained model **50** that outputs fluoroscopic storing information related to storing the fluoroscopic image captured before or after the X-ray imaging based on the captured image **72** by image analyzing the captured image **72**, and store the fluoroscopic image captured before or after the X-ray imaging in the memory **303** when determining that it is necessary to store the fluoroscopic image captured before or after the X-ray imaging based on the fluoroscopic storing information **74** that is output from the trained model **50**, the user may train necessary fluoroscopic image without performing additional operation.

(128) Note that the fluoroscopic image captured before or after the X-ray imaging was stored in the memory in the description of the third embodiment described above, but the X-ray diagnosis apparatus **1** may store either of the fluoroscopic image captured before or after the X-ray imaging based on the image analysis result of the fluoroscopic image. That is, the X-ray diagnosis apparatus **1** may store in the memory **303** at least one of the fluoroscopic images captured before or after the X-ray imaging based on the image analysis result of the captured image. In the third embodiment described above, the X-ray diagnosis apparatus **1** may also select by the fluoroscopic image storing control function **3013b** at least one of the fluoroscopic image captured before the X-ray imaging and the fluoroscopic image captured after the X-ray imaging and store the selected fluoroscopic image in the memory **303**.

(129) [Third Modification]

(130) In the first to third embodiments described above, when determining to store at least one of the fluoroscopic images captured before or after the X-ray imaging in the memory **303**, the X-ray diagnosis apparatus **1** may also be modified to notify the user that the fluoroscopic image is stored in the memory **303**. Parts that differ from the first embodiment will be described as a third modification where this modification is applied to the first embodiment.

(131) FIG. **16** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus **1** according to the third modification, which corresponds to FIG. **1** of the first embodiment described above. As shown in FIG. **16**, the X-ray diagnosis apparatus **1** according to the present modification is configured by adding a notification function **3015** to the processing circuitry **301** of the X-ray diagnosis apparatus **1** according to the first embodiment described above. Note that the notification function is equivalent to a notification unit in the present embodiment.

(132) The notification function **3015** is a function that notifies the user that the fluoroscopic image is stored in the memory **303**. The notification function **3015** may notify the user that the fluoroscopic image is stored in the memory **303** via a display **305**.

(133) FIG. **17** is a flowchart that describes a content of the fluoroscopic image storing control process executed in the X-ray diagnosis apparatus **1** according to the third modification. In the fluoroscopic image storing control process, the X-ray diagnosis apparatus **1** determines whether to store the fluoroscopic image based on the image related information, notifies the user when storing the fluoroscopic image, and stores the fluoroscopic image in the memory **303**. For instance, the fluoroscopic image storing control process is a process executed when fluoroscopic imaging is started. Note that the process before Step **S23** is equivalent to that of FIG. **1** described above, and description will be omitted.

(134) Then, at Step **S23** shown in FIG. **17**, when time **T** is greater than the threshold, i.e., when determining to store the fluoroscopic image in the memory **303** (Step **S23**: Yes), the X-ray diagnosis apparatus **1** notifies the user that the fluoroscopic image is stored in the memory **303** (Step **S81**). The notification process is realized by the notification function **3015** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** notifies the user that the fluoroscopic

image is stored in the memory **303** via the display **305**.

(135) FIG. **18** is a diagram that illustrates an exemplary notification screen displayed on the display **305** of the X-ray diagnosis apparatus **1** according to the present example. As shown in FIG. **18**, the X-ray diagnosis apparatus **1** may display on the display **305** a message “Storing fluoroscopic image for 6 seconds before or after imaging” as the notification screen. By such, the user may confirm that the fluoroscopic image is stored in the memory **303**.

(136) Steps **S27** to Step **S31** after Step **S81** is equivalent to that of FIG. **2** of the first embodiment described above, and description will be omitted. Then, the fluoroscopic image storing control process according to the third modification is terminated by executing Step **S31**.

(137) As described above, the X-ray diagnosis apparatus **1** according to the present third modification may, when determining to store the fluoroscopic image in the memory **303**, notify the user that the fluoroscopic image is stored in the memory via the display **305**. For this reason, the X-ray diagnosis apparatus **1** may store the fluoroscopic image in an appropriate and simple manner, and the user may confirm that the fluoroscopic image is stored in the memory **303**.

(138) Note that, in third modification, an embodiment of notifying that the fluoroscopic image is stored in the memory **303** is not limited to displaying on the display **305**. That is, the embodiment of notifying the user is arbitrary, and the X-ray diagnosis apparatus **1** may notify the user that the fluoroscopic image is stored in the memory **303** with voice via the output interface **309** or via vibration. As described, by the X-ray diagnosis apparatus **1** notifying the user that the fluoroscopic image is stored in the memory **303** via the output interface **309**, the user may confirm that the fluoroscopic image is stored in the memory **303** without looking at the display **305**.

(139) The X-ray diagnosis apparatus **1** may also display on the display **305** a screen that sets the number of fluoroscopic images to store in the memory **303**, such that the user may adjust the number of fluoroscopic images (number of frames) to store in the memory **303**. The X-ray diagnosis apparatus **1** may also display on the display **305** a selection screen that selects the fluoroscopic image to store in the memory **303** such that the user may select to store in the memory at least one of the fluoroscopic images captured before or after the X-ray imaging. Furthermore, the description of the third modification described above was a description applied to the first embodiment, but it is clear that the present modification may be applied to the first and second modifications of the first embodiment, the second embodiment, and the third embodiment.

(140) [Fourth Modification]

(141) In the X-ray diagnosis apparatus **1** according to the first to third embodiments described above, when storing the fluoroscopic image in the memory **303** in the fluoroscopic image storing control process, the captured image **72** acquired by X-ray imaging and the fluoroscopic image captured by fluoroscopic imaging at least one of before or after the X-ray imaging may be associated and stored in the memory **303**. By the X-ray diagnosis apparatus **1** associating and storing in the memory **303** the captured image acquired by X-ray imaging and the fluoroscopic image captured by fluoroscopic imaging at least one of before or after the X-ray imaging, when diagnosing using the captured image **72**, and when the fluoroscopic image captured at least one of before or after the X-ray imaging that acquired the captured image **72** becomes a diagnosis material, the user may easily notice the fluoroscopic image associated with the captured image **72**. Note that, it is clear that the description of the fourth modification described above may be applied not only to the first to third embodiments but also to the first and second modifications of the first embodiment.

(142) [Fifth Modification]

(143) Also, in the X-ray diagnosis apparatus **1** according to the first to third embodiments described above, when displaying the captured image **72** on the display **305**, a button (referred to as a “button” hereinafter) that switches the display from the captured image **72** to the fluoroscopic image captured at least one of before or after the X-ray imaging and plays the fluoroscopic image may be displayed on the display **305**. Parts that differ from the first embodiment will be described

below as a fifth modification where the modification is applied to the first embodiment.

(144) FIG. **19** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus **1** according to the fifth modification, which corresponds to FIG. **1** in the first embodiment described above. As shown in FIG. **19**, the X-ray diagnosis apparatus **1** according to the present modification is configured by adding a display control function **3016** to the processing circuitry **301** of the X-ray diagnosis apparatus **1** according to the first embodiment described above. Note that the display control function **3016** is equivalent to a display control unit of the present embodiment.

(145) The display control function **3016** is a function that displays captured image **72** on the display **305**. Also, in the present modification, the display control function **3016** displays the button on the display **305**.

(146) FIG. **20** is a flowchart that describes a content of an image display process executed in the X-ray diagnosis apparatus **1** according to the fifth modification. In the image display process, the X-ray diagnosis apparatus **1** lets the user select the captured image **72** to display or displays the button on the display **305**. The image display process may be a process executed when the user selects the captured image **72** to display on the display **305**.

(147) As shown in FIG. **20**, the X-ray diagnosis apparatus **1** first allows to select the captured image **72** (Step **S91**). The process of allowing to select the captured image **72** is realized by the display control function **3016** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** allows the user to select the captured image **72** to display on the display **305** via the input interface **307**.

(148) Next, as shown in FIG. **20**, the X-ray diagnosis apparatus **1** determines whether the fluoroscopic image is stored (Step **S93**). The process of determining whether the fluoroscopic image is stored is realized by the display control function **3016** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether the fluoroscopic image captured at least one of before or after the X-ray imaging for the captured image **72** selected at Step **S91**.

(149) Then, if the fluoroscopic image is stored at Step **S93** (Step **S93**: Yes), the X-ray diagnosis apparatus **1** displays the captured image **72** and the button (Step **S95**). The process of displaying the captured image **72** and the button is realized by the display control function **3016** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** displays the captured image selected at Step **S91** and the button on the display **305**.

(150) FIG. **21** is a diagram that illustrates an exemplary captured image **72** and the button displayed on the display **305** of the X-ray diagnosis apparatus **1** according to the present modification. As shown in FIG. **21**, the captured image **72** is displayed on the display **305** and the button **B1** is displayed on the captured image **72**.

(151) On the other hand, if the fluoroscopic image is not stored at Step **S93** (Step **S93**: No), the X-ray diagnosis apparatus **1** displays the captured image **72** (Step **S97**). The process of displaying the captured image **72** is realized by the display control function **3016** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** displays the captured image **72** selected at Step **S91** on the display **305** without displaying the button **B1**.

(152) The image control process according to the present embodiment is terminated by executing either of Steps **S95** or **S97**.

(153) As described above, in the X-ray diagnosis apparatus **1** according to the present modification, since the captured image **72** is selected by the user, and if the fluoroscopic image captured at least one of before or after the X-ray imaging for the captured image **72** is stored in the memory **303**, the captured image **72** is displayed with the button **B1** on the display **305**, switches the display from the captured image **72** to the fluoroscopic image captured at least one of before or after the X-ray imaging by the user selecting the button **B1**, and made possible to play the fluoroscopic image, the user may easily switch from the captured image **72** to the fluoroscopic image, and user convenience is improved.

(154) Note that, in the fifth modification described above, the captured image **72** and the fluoroscopic image may be displayed on the display **305** at the same time. Likewise, when displaying the captured image **72** and the fluoroscopic image at the same time, the button **B1** to switch between the captured image **72** and the fluoroscopic image may not be displayed. Likewise, when displaying the captured image **72** and the fluoroscopic image at the same time, the fluoroscopic image may be automatically played when displaying the fluoroscopic image. Furthermore, the description of the fifth modification described above was a description applied to the first embodiment, but it is clear that the present embodiment may be applied to the first and second modifications of the first embodiment, second and third embodiments, and the third and fourth modifications.

(155) [Sixth Modification]

(156) In the X-ray diagnosis apparatus **1** according to the first to third embodiments described above, when playing the fluoroscopic image on the display **305**, it is also possible to insert an interpolated image generated based on at least one of the captured image **72**, the fluoroscopic image, and a black image, and play the fluoroscopic image on the display **305** so as to maintain the framerate of the fluoroscopic image. Parts that differ from that of the first embodiment will be described as a sixth modification where the modification is applied to the first embodiment.

(157) FIG. **22** is a block diagram that illustrates an exemplary configuration of the X-ray diagnosis apparatus **1** according to the sixth modification, which corresponds to FIG. **1** according to the first embodiment described above. As shown in FIG. **22**, the X-ray diagnosis apparatus **1** according to the present modification is configured by adding a play control function **3017** to the processing circuitry **301** of the X-ray diagnosis apparatus **1** according to the first embodiment described above. Note that the play control function **3017** is equivalent to a play control unit according to the present embodiment.

(158) The play control function **3017** is a function that plays the fluoroscopic image on the display **305**. Also in the present embodiment, the play control function **3017** inserts the interpolated image generated based on at least one of the captured image **72**, the fluoroscopic image, and a black image, and plays the fluoroscopic image on the display **305** so as to maintain the framerate of the fluoroscopic image.

(159) Next, a play control process that plays the fluoroscopic image executed in the X-ray diagnosis apparatus **1** according to the present modification will be described using FIGS. **23** and **24**. FIG. **23** is a flowchart that describes a content of the play control process executed in the X-ray diagnosis apparatus **1** according to the present modification. FIG. **24** is a timing chart that describes a timing of inserting the interpolated image into the fluoroscopic image. In the play control process shown in FIG. **23**, the X-ray diagnosis apparatus **1** is a process executed when receiving an input to play the fluoroscopic image.

(160) As shown in FIG. **23**, the X-ray diagnosis apparatus **1** first determines whether the input to play the fluoroscopic image was received (Step **S101**). The process of determining whether the input to play the fluoroscopic image is realized by the play control function **3017** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** determines whether the input to play the fluoroscopic image was received from the user via the input interface **307**. Then, if the input to play the fluoroscopic image was not received from the user via the input interface **307** (Step **S101**: No), the X-ray diagnosis apparatus **1** repeats Step **S101** and standbys.

(161) On the other hand, when the input to play the fluoroscopic image was received from the user (Step **S101**: Yes), the X-ray diagnosis apparatus **1** generates the interpolated image (Step **S103**) as shown in FIG. **23**. The process of generating the interpolated image is realized by the play control function **3017** in the processing circuitry **301**. Specifically, the X-ray diagnosis apparatus **1** generates the interpolated image to insert into the fluoroscopic image that received the input to play at Step **S101**, so as to maintain the framerate of the fluoroscopic image captured before or after the X-ray imaging.

(162) More specifically, as shown in FIG. 24, when X-ray imaging is performed during fluoroscopic imaging, there is a time when fluoroscopic image cannot be acquired because the X-ray diagnosis apparatus 1 switches from fluoroscopic imaging to X-ray imaging. Since the captured image 72 is acquired during the time when the fluoroscopic image cannot be acquired, the interpolated image is generated by matching the image quality of the captured image 72, acquired during the time when the fluoroscopic image cannot be acquired, to the image quality of the fluoroscopic image. Note that, the pulse fluoroscopic imaging which performs fluoroscopic imaging by discontinuously irradiating X-ray in the fluoroscopic image shown in FIG. 24, but the fluoroscopic imaging shown in FIG. 24 may be the continuous fluoroscopic imaging that performs fluoroscopic imaging by continuously irradiating X-ray.

(163) Next, as shown in FIG. 23, the X-ray diagnosis apparatus 1 plays the fluoroscopic image (Step S105). The step of playing the fluoroscopic image is realized by the play control function 3017 in the processing circuitry 301. Specifically, as shown in FIG. 24, the X-ray diagnosis apparatus 1 plays the fluoroscopic image by inserting the interpolated image generated at Step S103 to the fluoroscopic image that received the input to play at Step S101 and displaying on the display 305. The play control process according to the present example is terminated by executing Step S105.

(164) As described above, since the X-ray diagnosis apparatus 1 according to the present modification performs X-ray imaging between fluoroscopic imaging, and even when there exists the time when fluoroscopic image is not acquired, plays the fluoroscopic image on the display 305 by inserting the interpolated image generated based on the captured image 72, the user may confirm playing the fluoroscopic image which the framerate of the fluoroscopic image is maintained and diagnose.

(165) Note that, if the interpolated image is displayed during playing the fluoroscopic image, the X-ray diagnosis apparatus 1 may display on the display 305 that this is the interpolated image. Likewise, the generated interpolated image is not limited to use the captured image 72. For instance, the X-ray diagnosis apparatus 1 may generate the interpolated image based on the fluoroscopic image captured by fluoroscopic imaging right before the X-ray imaging. That is, when playing the fluoroscopic image, the X-ray diagnosis apparatus 1 may display the fluoroscopic image captured by the fluoroscopic imaging right before the X-ray imaging for a portion where the fluoroscopic image was not obtained. Also, for instance, the X-ray diagnosis apparatus 1 may generate black image as the interpolated image, insert the black image to the fluoroscopic image, and play the fluoroscopic image. Furthermore, if the framerate cannot be maintained by the single interpolated image, the X-ray diagnosis apparatus 1 may generate a plurality of interpolated images, insert the generated plurality of interpolated images to the fluoroscopic image, and play the fluoroscopic image.

(166) As described above, in the present embodiment, the processing circuit 18, for instance, is configured by the processor. Note that the word “processor” used in above descriptions means circuits such as, for example, a Central Processing Unit (CPU), a Graphics Processing Unit (GPU), an Application Specific Integrated Circuit (ASIC), a programmable logic device (for example, a Simple Programmable Logic Apparatus (SPLD), a Complex Programmable Logic Apparatus (CPLD), and a Field Programmable Gate Array (FPGA)). The processor executes functions by reading and executing programs stored in the memory. Note that programs may be configured to be directly integrated in the processor instead of being storing in the memory. In this case, the processor realizes functions by reading and executing programs stored in the circuit. Note that the processor is not limited to be arranged as a single processor circuit, but may be configured as a single processor by combining a plurality of independent circuits to realize functions. Furthermore, a plurality of component elements in FIG. 1 may be integrated into one processor to realize the functions.

(167) While certain embodiments have been described, these embodiments have been presented by

way of example only and are not intended to limit the scope of the inventions. The embodiments may be in a variety of other forms. Furthermore, various omissions, substitutions and changes may be made without departing from the spirit of the inventions. The embodiments and their modifications are included in the scope and the subject matter of the invention, and at the same time included in the scope of the claimed inventions and their equivalents.

Claims

1. An X-ray diagnosis apparatus, comprising: an imager configured to perform imaging by irradiating an X-ray to a subject to acquire a captured image by X-ray imaging and acquire a fluoroscopic image by fluoroscope imaging; an input interface configured to receive a user operation, the input interface including an X-ray imaging switch and a fluoroscopic imaging switch, the X-ray imaging switch being a switch to control whether to perform the X-ray imaging, and the fluoroscopic imaging switch being a switch to control whether to perform fluoroscopic imaging; and processing circuitry configured to acquire an operation content of the X-ray imaging switch as imaging related information obtained within a certain period of time before or after the X-ray imaging, determine whether to store the fluoroscopic image based on the acquired operation content of the X-ray imaging switch; and store, in a memory, the fluoroscopic image, which is captured one of before or after the X-ray imaging, based on the imaging related information.
2. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured to determine a number of frames of the fluoroscopic image stored in the memory, in response to an operation time of the input interface.
3. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured to store, within the memory, to the captured image imaged by the X-ray imaging in association with the fluoroscopic image imaged by the fluoroscopic imaging related to at least one of the X-ray imaging before or after.
4. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured to select at least one of fluoroscopic images captured before the X-ray imaging and after the X-ray imaging, and store the selected at least one of the fluoroscopic images in the memory.
5. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured to notify that the fluoroscopic image is stored in the memory.
6. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured cause a display to display a button to play the fluoroscopic image by switching the display from the captured image to the fluoroscopic image, which is captured at least one of before or after the X-ray imaging, when displaying the captured image.
7. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry, while playing the fluoroscopic image, is further configured to insert an interpolated image in the fluoroscopic image, and cause the display to play the fluoroscopic image so as to maintain a framerate of the fluoroscopic image captured before or after the X-ray imaging, the interpolated image being an image generated based on at least one of the captured image, the fluoroscopic image captured at least one of before or after the X-ray imaging, and a black image.
8. The X-ray diagnosis apparatus of claim 7, wherein the processing circuitry is further configured to insert the interpolated image in the fluoroscopic image and play the fluoroscopic image on the display, the interpolated image being an image generated by changing an image quality of one of the captured image and the fluoroscopic image captured at least one of before or after the X-ray imaging so as to match to an image quality.
9. The X-ray diagnosis apparatus of claim 7, wherein the processing circuitry, when causing the display to display the interpolated image, is further configured to cause the display to display information indicating that the fluoroscopic image is the interpolated image.
10. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured

to acquire one X-ray image as the captured image by a discrete X-ray irradiation in the X-ray imaging, and acquire the X-ray image that is continuous in time as the fluoroscopic image by a continuous or discontinuous X-ray irradiation in the fluoroscopic imaging.

11. The X-ray diagnosis apparatus of claim 1, wherein the processing circuitry is further configured to: when the X-ray imaging is performed during the fluoroscopic imaging, acquire an operation content of the X-ray imaging switch as the imaging related information, and determine whether to store the fluoroscopic image based on the operation content of the X-ray imaging switch.

12. The X-ray diagnosis apparatus of claim 1, wherein the X-ray imaging switch is a hand switch, and the fluoroscopic imaging switch is a foot switch.

13. A control method of an X-ray diagnosis apparatus that comprises an input interface configured to receive a user operation, the input interface including an X-ray imaging switch and a fluoroscopic imaging switch, the X-ray imaging switch being a switch to control whether to perform the X-ray imaging, and the fluoroscopic imaging switch being a switch to control whether to perform fluoroscopic imaging, the control method comprising: performing X-ray imaging and fluoroscopic imaging by irradiating X-ray to a subject; acquiring an operation content of the X-ray imaging switch as imaging related information obtained within a certain period of time before or after the X-ray imaging; determining whether to store the fluoroscopic image based on the acquired operation content of the X-ray imaging switch; and storing, in a memory, a fluoroscopic image captured by the fluoroscopic image captured at least one of before or after the X-ray imaging based on the imaging related information.
