

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415960
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	De Ren; Jan et al.

Process for regenerating catalyst from a fluidized catalytic process

Abstract

A process for regenerating catalyst from a fluidized catalytic process is disclosed. The process comprises passing a CO.sub.2 oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO.sub.2 rich flue gas stream. The CO.sub.2 rich flue gas stream is separated into an underflow stream comprising catalyst fines and a CO.sub.2 rich flue gas overflow stream. The overflow stream is separated into a recycle stream and a power recovery stream. The recycle stream of the overflow stream is recycled to the regenerator.

Inventors: De Ren; Jan (Bracknell, GB), Durai; Sakthivelan Maadasamy (Gurugram, IN), Mehta; Rakshit (Kolkata, IN)

Applicant: UOP LLC (Des Plaines, IL)

Family ID: 1000008819868

Assignee: UOP LLC (Rosemont, IL)

Appl. No.: 18/139814

Filed: April 26, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240158703 A1	May. 16, 2024

Publication Classification

Int. Cl.: B01J38/02 (20060101); B01J38/06 (20060101); B01J38/32 (20060101); C10G11/18 (20060101)

U.S. Cl.:

CPC **C10G11/182** (20130101); **B01J38/02** (20130101); **B01J38/06** (20130101); **B01J38/32** (20130101);

Field of Classification Search

CPC: B01J (23/92); B01J (38/02); B01J (38/06); B01J (38/12); B01J (38/30); B01J (38/32);
C10G (11/182)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0247336	12/2010	Farsad	60/685	B01D 53/78
2021/0324278	12/2020	Montalbano	N/A	B01J 8/1863

Primary Examiner: McAvoy; Ellen M

Assistant Examiner: Graham; Chantel

Attorney, Agent or Firm: Paschall & Associates, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority from Indian Provisional Application No. 202211065724, filed Nov. 16, 2022, which is incorporated herein in its entirety.

FIELD

(2) The field is related to a process for regenerating catalyst from a fluidized catalytic process. Particularly, the field relates to a process for regenerating catalyst from a fluidized catalytic process with a CO₂ recycle stream.

BACKGROUND

(3) Catalytic cracking can create a variety of products from larger hydrocarbons. Often, a feed of a heavier hydrocarbon, such as a vacuum gas oil, is provided to a catalytic cracking reactor, such as a fluid catalytic cracking reactor. Various products may be produced from such a system, including a gasoline product and/or light product such as propene and/or ethene.

(4) Fluid catalytic cracking (FCC) is a hydrocarbon conversion process accomplished by contacting hydrocarbons in a fluidized reaction zone with a catalyst composed of finely divided particulate material. The reaction in catalytic cracking, as opposed to hydrocracking, is carried out in the absence of substantial added hydrogen or the consumption of hydrogen. As the cracking reaction proceeds substantial amounts of highly carbonaceous material referred to as coke is deposited on the catalyst. A high temperature regeneration operation within a regenerator zone combusts coke from the catalyst. Coke-containing catalyst, referred to herein as coked catalyst, is continually removed from the reaction zone and replaced by essentially coke-free catalyst from the regeneration zone. Fluidization of the catalyst particles by various gaseous streams allows the transport of catalyst between the reaction zone and regeneration zone. Spent catalyst from the reaction zone can be completely or partially regenerated in the regeneration zone.

(5) A common objective of these configurations is maximizing product yield from the reactor while

minimizing operating and equipment costs. Optimization of feedstock conversion ordinarily requires essentially complete removal of coke from the catalyst. This essentially complete removal of coke from catalyst is often referred to as complete regeneration. Complete regeneration produces a catalyst having less than 0.1 and preferably less than 0.05 wt-% coke. In order to obtain complete regeneration, the catalyst has to be in contact with oxygen at elevated temperature for sufficient residence time to permit thorough combustion.

(6) Alternative processes are also used for light olefins production. In one approach, hydrocarbon oxygenates and more specifically methanol or dimethyl ether are used as an alternative feedstock for producing light olefin products. Once the oxygenates are formed, the process includes catalytically converting the oxygenates, such as methanol, into the desired light olefin products in a methanol to olefin (MTO) process. In the MTO process, carbonaceous material, i.e., coke, is deposited on the catalyst as it moved through the reaction zones. The carbonaceous material is removed from the catalyst by oxidative regeneration in one or more regeneration zones wherein a moving bed of the catalyst particles withdrawn from the reaction zones is contacted with an oxygen-containing gas stream at sufficient temperature and oxygen concentration to allow the desired amount of the carbonaceous materials to be removed by combustion from the catalyst. In some cases, it is advantageous to only partially regenerate the catalyst, e.g., to remove from about 30 to 80 wt-% of the carbonaceous material.

(7) Conventional regenerators typically include a vessel having a coked catalyst inlet, a regenerated catalyst outlet and a combustion gas distributor for supplying air or other oxygen containing gas to the bed of catalyst that resides in the vessel. Cyclone separators remove catalyst entrained in the flue gas before the gas exits the regenerator.

(8) Flue gas formed by burning the coke in the regenerator is treated for removal of particulates, other contaminants including SO_x , NO_x , HCN and conversion of carbon monoxide (CO), after which the flue gas is normally discharged into the atmosphere. Further, incomplete combustion to carbon dioxide can result from poor fluidization or aeration of the coked catalyst in the regenerator or poor distribution of coked catalyst into the regenerator. Generally, the flue gas exiting the regenerator contains CO, CO_2 , N_2 and H_2O , along with smaller amounts of other species. The quantity of CO in the flue gas is based on the mode of regenerator operation by varying the quantity of air or O_2 to the regenerator. Flue gas treatment methods are effective, but the capital and operating costs are high.

(9) Usually, the air is supplied to the regenerator at a much lower temperature as compared to the operating temperature of the regenerator. So, additional heat is required to raise the temperature of the incoming air to the operating temperature of the regenerator. This additional heat is supplied through the coke combustion. However, this requirement for air would lead to a comparatively higher coke formation in a heat balanced fluidized catalytic cracking process and also increases the CO_2 formation. This may increase the capital expenditure of the unit and that of the flue gas treatment of the unit by a proportionate amount.

(10) Environmental concerns over greenhouse gas emissions have led to an increasing emphasis on separating the greenhouse gases before releasing the flue gases into atmosphere. Carbon dioxide (CO_2) is the most significant long-lived greenhouse gas in earth's atmosphere. CO_2 capture from flue gases is still expensive, both from a capital expenditures and operational utility costs standpoint. For fluidized catalytic processes, air is used for regenerating the spent catalyst. As a result of this operation, the CO_2 in the FCC flue gas has a lower concentration in contrast to the concentrations of components not desired to be captured with CO_2 . This dynamic results in high capital expenditures due to a large volume of the flue gas, but also large operational expenses due to high solvent circulation rates and solvent regeneration duties. Apart from this, the flue gas requires extensive flue gas treatment prior to carbon capture in order to meet stringent specifications to avoid high solvent degradation rates requiring high capital expenditures and operational utility costs from more extensive impurities removal operations.

(11) Therefore, there is a need for improved processes for regenerating catalyst from a fluidized catalytic process and the treatment of the flue gas containing CO.sub.2. Also, there is a need for a process and an apparatus which reduces capital expenditures and operational utility costs of the flue gas treatment section, whilst improving energy efficiency and energy recovery.

SUMMARY

(12) The present disclosure provides a process and an apparatus for regenerating catalyst from a fluidized catalytic process. Generally, air is used in the regenerator for burning the coke from spent catalyst. The air is supplied at a lower temperature than the temperature at which the regenerator is operating. So, the temperature of the incoming air stream needs to be elevated to the temperature at which the regenerator is operating. A significant amount of heat is needed just to heat the air to the temperature at which the regenerator is operating. However, this increase in heat demand for heating the air also results in significant coke generation and generation of CO.sub.2 due to combustion and increases the overall cost of the unit for flue gas separation and treatment.

(13) The present disclosure provides a process and an apparatus wherein a recycle stream is provided to the regenerator to heat up the incoming oxygen containing stream. The current process reduces or avoids the additional heat needed just for heating the incoming oxygen containing stream to raise its temperature to regeneration temperature. The present process also reduces coke generation, lowers capital and operational expenditures by reducing the intensity of flue gas treatment as compared to conventional air-based regeneration process.

(14) A process for regenerating catalyst from a fluidized catalytic process in accordance with the present disclosure comprises passing a CO.sub.2 oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO.sub.2 rich flue gas stream. The CO.sub.2 rich flue gas stream is separated into an underflow stream comprising catalyst fines and a CO.sub.2 rich flue gas overflow stream. The overflow stream is separated into a recycle stream and a power recovery stream. The recycle stream of the overflow stream is recycled to the regenerator.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The various embodiments will hereinafter be described in conjunction with the following FIGURES, wherein like numerals denote like elements.

(2) FIG. 1 is a schematic diagram of a process and an apparatus for regenerating catalyst from a fluidized catalytic process in accordance with an exemplary embodiment.

(3) FIG. 2 is a schematic diagram of a process and an apparatus for regenerating catalyst from a fluidized catalytic process in accordance with another exemplary embodiment.

(4) FIG. 3 is a graph plotted for coke yield (wt %) vs conversion (wt %) for the process for regenerating catalyst from a fluidized catalytic process in accordance with the present disclosure and a base case process.

DEFINITIONS

(5) The term “communication” means that material flow is operatively permitted between enumerated components.

(6) The term “downstream communication” means that at least a portion of material flowing to the subject in downstream communication may operatively flow from the object with which it communicates.

(7) The term “upstream communication” means that at least a portion of the material flowing from the subject in upstream communication may operatively flow to the object with which it communicates.

(8) The term “direct communication” or “directly” means that flow from the upstream component enters the downstream component without passing through a fractionation or conversion unit to

undergo a compositional change due to physical fractionation or chemical conversion.

(9) The term “column” means a distillation column or columns for separating one or more components of different volatilities. Unless otherwise indicated, each column includes a condenser on an overhead of the column to condense and reflux a portion of an overhead stream back to the top of the column and a reboiler at a bottom of the column to vaporize and send a portion of a bottoms stream back to the bottom of the column. Feeds to the columns may be preheated. The top pressure is the pressure of the overhead vapor at the vapor outlet of the column. The bottom temperature is the liquid bottom outlet temperature. Overhead lines and bottoms lines refer to the net lines from the column downstream of any reflux or reboil to the column. Stripper columns may omit a reboiler at a bottom of the column and instead provide heating requirements and separation impetus from a fluidized inert media such as steam. Stripper columns typically feed a top tray and take main product from the bottom.

(10) As used herein, the term “a component-rich stream” means that the rich stream coming out of a vessel has a greater concentration of the component than the feed to the vessel.

(11) As used herein, the term “separator” means a vessel which has an inlet and at least an overhead vapor outlet and a bottoms liquid outlet and may also have an aqueous stream outlet from a boot. A flash drum is a type of separator which may be in downstream communication with a separator that may be operated at higher pressure.

(12) As used herein, the term “rich” means greater than 50%, suitably greater than 75% and preferably greater than 90%.

DETAILED DESCRIPTION

(13) A process for regenerating catalyst from a fluidized catalytic process is disclosed. The fluidized catalytic process can be any fluid catalytic process that regenerates catalyst including an FCC process a MTO process or any such process. The present process discloses separating a recycle stream from the flue gas generated from a catalyst regenerator. The recycle stream is a CO.sub.2 rich flue gas stream which is recycled to the regenerator. Applicants have found that recycling the CO.sub.2 rich flue gas stream to the regenerator maintains the regenerator temperature, reduces the coke formation in the process, reduces the external heat requirement for the regenerator and reduces the overall capital expenditures for the unit. Applicants have also found that recycling the CO.sub.2 rich flue gas stream also optimizes the overall yield of the process as the coke formation is reduced which in turn increases the overall yield of the process.

(14) In an FCC process, the flue gas from the regenerator is generally passed to a third stage separator (TSS) to separate catalyst fines from the flue gas. A small quantity of flue gas with most of the catalyst fines is taken as an underflow stream from the TSS. The rest of the flue gas is separated in an overflow stream from the TSS. The catalyst fines from the underflow stream from the TSS are further separated. The underflow stream from the TSS may be passed to a fourth stage separator or filter or any other catalyst separation system to further separate the catalyst fines. Also, energy can be extracted from the overflow stream from the TSS in a heat exchanger. The overflow stream from the TSS can be separated into the CO.sub.2 rich flue gas stream for recycle to the regenerator and the remaining overflow stream is passed to downstream for further utilization and/or recovery. After separating the recycle stream, the remaining overflow stream can be passed to an expander turbine, in which energy is extracted in the form of work. The expander may be coupled with the main air blower, providing power for blower operation or the air blower may be driven by a separate electric motor or steam turbine with expander output used solely for electric power generation. If the expander is coupled with the air blower, a motor/generator is required in the train to balance expander output with the air blower power requirement, and a steam turbine is included to assist with start-up. The steam turbine may be designed for continuous operation as an economic outlet for excess steam, or a less expensive turbine exhausting to atmosphere may be installed for use only during start-up. In an exemplary embodiment, the expander is coupled with generator for blue electricity generation.

(15) In FIG. 1, in accordance with an exemplary embodiment, a process 101 is shown for regenerating catalyst from a fluidized catalytic process. The apparatus for regenerating catalyst comprises a regenerator unit 110, particulate removal section 120, a heat recovery section 125, a decontamination reactor 160, and a filter section 170. One aspect of the present disclosure comprises a process for regenerating catalyst from a fluidized catalytic process. The method comprises providing an oxygen containing stream in line 106 to the regenerator unit 110. In accordance with the present disclosure, the oxygen containing stream in line 106 may be selected from one or both of an air stream or an oxygen stream taken from an electrolyzer or an air separation unit (ASU). In an exemplary embodiment, the oxygen containing stream in line 106 is an oxygen stream taken from an air separation unit (ASU) or an electrolyzer. In another exemplary embodiment, the oxygen containing stream in line 106 is an air stream.

(16) In accordance with the present disclosure, the oxygen containing stream in line 106 is mixed with a recycle stream in line 124 to provide a CO.sub.2 oxidation stream in line 108. The CO.sub.2 oxidation stream in line 108 is passed to the regenerator unit 110. A spent catalyst stream from a fluidized catalytic process in line 102 is also passed to the regenerator unit 110. In an aspect, the CO.sub.2 oxidation stream in line 108 comprises an oxygen concentration of no more than 30 mole %.

(17) In an aspect of the present disclosure, a diluent stream in line 111 is also provided and passed to the regenerator unit 110. It is found that while recycling the recycle stream in line 124 to the regenerator unit 110, the water concentration in the recycle gas loop may increase to as much as about 15 vol % or to as much as about 34 vol %. The water concentration in the recycle gas loop to the regenerator unit 110 may promote a hydrothermal deactivation of the catalyst. To avoid the hydrothermal deactivation of the catalyst, the present process passes a diluent stream in line 111 to the regenerator with the recycle stream in line 124. In an aspect of the present disclosure, the diluent stream in line 111 comprises CO.sub.2. In an exemplary embodiment, the diluent stream in line 111 is a CO.sub.2 rich diluent stream. In another exemplary embodiment, the diluent stream in line 111 is a CO.sub.2 stream. In another aspect of the present disclosure, the diluent CO.sub.2 stream in line 111 can be sourced from the fluidized catalytic process after purification. Also, the diluent CO.sub.2 stream in line 111 can be sourced from a suitable source in the refinery as well. The diluent CO.sub.2 stream will help to maintain the water concentration within the allowable range in the regenerator unit 110 and avoid any hydrothermal deactivation of the catalyst.

(18) The diluent stream in line 111 can be combined with the oxygen containing stream in line 106 to provide a combined stream in line 107. The recycle stream in line 124 is mixed with the combined stream in line 107 to provide the CO.sub.2 oxidation stream in line 108 which is passed to the regenerator unit 110. However, the diluent stream in line 111 can be passed to the regenerator unit 110 separately or directly.

(19) In a fluidized catalytic process, catalyst particles are repeatedly circulated between a reaction zone and a catalyst regenerator unit 110. During regeneration, coke is deposited on the catalyst particles during reactions in the reaction zone and is removed at elevated temperatures by oxidation in the regenerator unit 110. The removal of coke deposits restores the activity of the catalyst particles to the point where they can be reused in the reaction zone. The present disclosure is directed towards optimizing the coke generated within the process and maintain the temperature/heat balance for the regenerator unit 110. The regenerated catalyst is withdrawn (not shown in FIG. 1) from the regenerator unit 110 and returned to the reaction zone.

(20) From the regenerator unit 110, a CO.sub.2 rich flue gas stream in line 112 is withdrawn. The CO.sub.2 rich flue gas stream in line 112 comprises solids including catalyst fines, and particulates. The CO.sub.2 rich flue gas stream in line 112 is passed to a particulate removal section 120. In accordance with an exemplary embodiment of the present disclosure, the particulate removal section 120 may be a third stage separator (TSS) (120).

(21) The CO.sub.2 rich flue gas stream in line 112 is passed to the TSS 120 to separate catalyst

finer in an underflow stream in line **128**. A CO.sub.2 rich flue gas stream with reduced catalyst fines is separated in an overflow stream in line **122** from the TSS **120**. The catalyst fines from the TSS **120** are further concentrated in the underflow stream in line **128**.

(22) In an embodiment of the present disclosure, the CO.sub.2 rich flue gas stream with reduced catalyst fines in the overflow stream in line **122** is separated into a recycle stream in line **124** and a power recovery stream in line **126**. The recycle stream in line **124** is recycled to the regenerator unit **110**. In an exemplary embodiment, the recycle stream in line **124** is mixed with the oxygen containing stream in line **106** and the diluent CO.sub.2 rich stream in line **111** to provide the CO.sub.2 oxidation stream which is recycled to the regenerator unit **110**. Alternatively, the recycle stream in line **124**, the oxygen containing stream in line **106** and the diluent CO.sub.2 rich stream in line **111** can be passed separately or directly to the regenerator unit **110**.

(23) In an aspect of the present disclosure, the recycle stream in line **124** is heat exchanged in a heat exchanger and compressed in a compressor before recycling the recycle stream in line **124** to the regenerator unit **110**. The recycle stream in line **124** is passed through a heat exchanger **134** to reduce a temperature of the recycle stream in line **124** to provide a heat exchanged recycle stream in line **135**. The heat exchanged recycle stream in line **135** is compressed in a compressor **136** to provide a heat exchanged and compressed recycle stream in line **137** having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.). The heat exchanged and compressed recycle stream in line **137** is passed to the regenerator unit **110**. In an embodiment, the heat exchanged and compressed recycle stream in line **137** is mixed with the combined stream in line **107** to provide the CO.sub.2 oxidation stream in line **108** which is passed to the regenerator unit **110**. However, the heat exchanged and compressed recycle stream in line **137** may be passed separately or directly to the regenerator unit **110**.

(24) In an exemplary embodiment, the recycle stream in line **124** which is recycled to the regenerator unit **110** comprises from about 5 vol % to about 80 vol % of the overflow stream in line **122**. In another exemplary embodiment, the recycle stream in line **124** which is recycled to the regenerator unit **110** comprises from about 10 vol % to about 60 vol % of the overflow stream in line **122**. In yet another exemplary embodiment, the recycle stream in line **124** which is recycled to the regenerator unit **110** comprises from about 20 vol % to about 40 vol % of the overflow stream in line **122**. In accordance with an aspect of the present disclosure, the recycle stream in line **124** comprises oxygen in an amount from about 0.01 mol % to about 5 mol % or from about 0.5 mol % to about 4 mol % or from about 0.5 mol % to about 2 mol % or from about 1 mol % to about 2 mol %.

(25) The recycle stream is at a relatively higher temperature as compared to the oxygen containing stream entering into the regenerator unit **110**. Applicants found that by passing the recycle stream at a higher temperature, the amount of heat generation needed within the regenerator for heating the incoming oxygen containing stream is reduced which in turn also reduces the amount of coke generation in the fluid catalytic process by at least 20 to 30% as compared with the case with no recycling (base case). Reducing the coke formation in the fluid catalytic process provides two advantages, first reducing the coke amount would result into additional product and thereby additional product revenue from the process and unit. Second, reducing the coke amount would also reduce the flue gas or the CO.sub.2 which would be produced during the regeneration step in the regenerator unit **110**. Applicants found that this could reduce the flue gas generation by at least 20 to 30% as compared with the case with no recycling (base case). This reduction also lowers the overall capital expenditures for the flue gas section of the unit by a proportionate amount due to the smaller volume of gas that must be transported and treated.

(26) Total coke generation in a conventional fluidized catalytic cracking process comprises conversion coke, residue coke due to the nature of the feed, and additional coke which is produced to provide for heating any process streams such as hydrocarbon, air, or steam entering into the system. Usually, the oxygen containing stream entering the regenerator unit is at a temperature of

about 130° C. (300° F.) to about 205° C. (400° F.), whereas the regenerator usually operates at a temperature of about 676° C. (1250° F.) to about 760° C. (1400° F.). So, the temperature of the oxygen containing stream needs to be elevated to this regenerator temperature. This heat comes from the coke combustion. So, the additional coke formation in the fluid catalytic process is associated with heating the incoming oxygen containing stream from about 205° C. (400° F.) to the regenerator temperature. The present process discloses bringing the recycle gas at a temperature of 260° C. (500° F.) to about 760° C. (1400° F.) to meet the heat balance on the regenerator side. This hot gas recycle reduces the delta heat needed to heat the incoming oxygen containing stream. This hot gas recycle now translates into a reduction of at least 20-30% of the coke generation in the unit. Applicants also found that hot gas recycling also helps in providing adequate density within the bed in the regenerator, so there is enough residence time for the combustion kinetics to appropriately take place. In the absence of adequate density within the bed, “after burn” in the regenerator can occur due to insufficient material to absorb the heat of combustion which will significantly increase the risk of heat damage to the equipment. The recycling of flue gas from the TSS provides direct heat to the incoming oxygen containing stream resulting in the aforesaid benefits to the process and unit.

(27) In an exemplary embodiment, third stage separator operates at a temperature from about 649° C. (1200° F.) to about 760° C. (1400° F.). The recycle stream in line **124** can be partially cooled or heat exchanged and compressed before passing the recycle stream in line **124** to the regenerator unit **110**. The recycle stream in line **124** may be heat exchanged in a heat exchanger and compressed before passing the recycle stream in line **124** to the regenerator unit **110**. Alternatively, the recycle stream in line **124** may be passed through an air cooler and compressed before passing the recycle stream in line **124** to the regenerator unit **110**. In an exemplary embodiment, the recycle stream in line **124** is recycled to the regenerator unit **110** at a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.). In another exemplary embodiment, the recycle stream in line **124** is recycled to the regenerator unit **110** at a temperature from about 593° C. (1100° F.) to about 760° C. (1400° F.).

(28) Returning to the TSS **120**, the power recovery stream **126** of the CO.sub.2 rich flue gas stream with reduced catalyst fines in the overflow stream in line **122** is passed to the flue gas expander **130** where energy is extracted in the form of work and/or electricity. In an aspect of the present disclosure, energy can be extracted from the power recovery stream **126** in the form of work in an expander turbine. In an exemplary embodiment, the expander **130** is coupled with a generator for blue electricity generation. After electricity generation, the power recovery stream now in line **132** from the flue gas expander **130** is passed to the heat recovery section **125**. The flue gas expander **130** may be optional in accordance with the disclosed process for regenerating catalyst from a fluidized catalytic process. In an aspect of the present disclosure, the power recovery stream **126** may be passed directly to the heat recovery section **125**. The heat recovery section **125** may be in direct communication with the TSS **120** via the power recovery stream **126**. In an exemplary embodiment, the heat recovery section **125** is a heat recovery steam generator (HRSG) **125**. The HRSG comprises a superheated steam section **140** and a saturated steam section **150**. The power recovery stream in line **132** is passed to the superheated steam section **140** of the HRSG **125** to produce a superheated steam stream in line **146** and a heat exchanged CO.sub.2 rich flue gas stream in line **142**. The heat exchanged CO.sub.2 rich flue gas stream in line **142** is sent to the saturated steam section **150** of the HRSG **125**. In the saturated steam section **150**, a boiler feed water stream **144** is heated by the heat exchanged with the CO.sub.2 rich flue gas stream in line **142** forming a saturated steam stream in line **154** and a partially cooled CO.sub.2 rich flue gas stream in line **152**. A condensate stream in line **153** is withdrawn from the saturated steam section **150**. A portion **155** of the saturated steam stream **154** is sent to the HRSG superheated steam section **140** to be superheated. The remainder **156** of the saturated steam stream **154** can be sent to other parts of the plant for use as needed. The partially cooled CO.sub.2 rich flue gas stream in line **152** is withdrawn

from the saturated steam section **150** and passed to the decontamination reactor **160**.

(29) The partially cooled CO.sub.2 rich flue gas stream in line **152** is passed to the decontamination reactor **160**. A reactant in line **159** is also passed to the decontamination reactor **160**. In accordance with another aspect of the present disclosure, the decontamination reactor **160** may be a scrubber **160**. In accordance with an aspect of the present disclosure, the decontamination reactor **160** can be operated at dry mode or wet mode. Therefore, the scrubber **160** can be a dry scrubber or a wet scrubber in accordance with the present process. In an exemplary embodiment, the reactant in line **159** is in dry form when the decontamination reactor **160** is operating under a dry mode or dry scrubbing. In an aspect, the partially cooled CO.sub.2 rich flue gas stream in line **152** from the heat recovery section **125** is mixed with the dry reactant **159** to provide a mixed stream in line **157** and sent to the decontamination reactor **160** together in the mixed stream in line **157**, alternatively as a combined decontaminant stream in line **158**. In the decontamination reactor **160**, the reactant reacts with sulfur-containing compounds and/or nitrogen-containing compounds in the partially cooled CO.sub.2 rich flue gas stream in line **152** to form a reactor effluent stream comprising a reactant salt in line **162**. The underflow stream in line **128** from the TSS **120** can also be passed directly to the decontamination reactor **160**. In an exemplary embodiment, the underflow stream in line **128** is combined with the partially cooled CO.sub.2 rich flue gas stream in line **152** and the reactant in line **159** and passed to the decontamination reactor **160** in the mixed stream in line **157**. In another exemplary embodiment, the partially cooled CO.sub.2 rich flue gas stream in line **152** and the underflow stream in line **128** are passed to the decontamination reactor **160** separately or directly.

(30) In a wet mode operation or a wet scrubbing, the reactant in line **159** to the decontamination reactor **160** would be in liquid form. In accordance with an exemplary embodiment, the liquid reactant in line **159** may be selected from NaOH (aq) or KOH (aq). For wet scrubbing of the partially cooled CO.sub.2 rich flue gas stream in line **152** in the decontamination reactor **160**, the partially cooled CO.sub.2 rich flue gas stream in line **152** would be quenched (not shown) to an adiabatic saturation temperature of about 60° C. (140° F.) to about 105° C. (220° F.) and thereafter passed to the decontamination reactor **160**. In wet scrubbing, the liquid reactant NaOH or KOH will react with the SO.sub.X (SO.sub.2 and/or SO.sub.3) and form a liquid slurry effluent potentially consisting of sodium sulphate (Na.sub.2SO.sub.4) and/or sodium sulfite (Na.sub.2SO.sub.3), or potassium sulfite (K.sub.2SO.sub.3) and/or potassium sulphate (K.sub.2SO.sub.4) and H.sub.2O, catalyst fines, and particulates. The liquid slurry effluent is withdrawn from the decontamination reactor **160**. For a wet decontamination reactor **160**, the filter section **170** may be omitted as the particles and/or catalyst fines are separated with the liquid slurry effluent which is withdrawn from the decontamination reactor **160**.

(31) In an exemplary embodiment, the decontamination reactor **160** operates at a temperature from about 200° C. to about 600° C. for reacting one or more of the sulfur-containing compound, the nitrogen-containing compound, or both in the partially cooled CO.sub.2 rich flue gas stream in line **152** with the reactant **159** in dry form. In another exemplary embodiment, the reactant **159** comprises one or more of sodium hydroxide (NaOH), potassium hydroxide (KOH), sodium bicarbonate (NaHCO.sub.3), calcium hydroxide (Ca(OH).sub.2) and trona salt (Na.sub.2CO.sub.3.Math.NaHCO.sub.3.Math.2H.sub.2O). In yet another exemplary embodiment, the reactant salt comprises one or more of sodium sulfite (Na.sub.2SO.sub.3), potassium nitrate (KNO.sub.3), potassium sulfate (K.sub.2SO.sub.4), sodium sulphate (Na.sub.2SO.sub.4), sodium carbonate (Na.sub.2CO.sub.3) and sodium nitrate (NaNO.sub.3). The reactor effluent stream comprising reactant salt in line **162** is passed to a filter section **170** for particle removal.

(32) The filter section **170** removes particulate and fines from the reactor effluent stream in line **162**. Electrical current in line **164** is supplied to the filter section **170** when the filter section **170** comprises an electrostatic precipitator. The filter section **170** may also comprise a bag filter. The filtered material from the filter section **170** may include one or more of Na.sub.2SO.sub.4, NaNO.sub.3, NaNO.sub.2, Na.sub.2CO.sub.3, and catalyst fines which may be removed in the

filter section **170**. A filtered material in line **175** can be collected and removed from the process in line **178**. Alternatively, or additionally, a filtered material may be recycled to the decontamination reactor **160** as a recycled filtered material in line **180** to increase the Na.sub.2CO.sub.3 conversion yield. The recycled filtered material in line **180** may be recycled with the mixed stream in line **157** and sent to the decontamination reactor **160** in the combined decontaminant stream in line **158**. Thus, the reactant salt and catalyst fines are removed from the reactor effluent stream **162** in the filter section **170** to produce a filtered reactor effluent stream in line **172**. A CO.sub.2 stream for storage in line **174** is separated from the filtered reactor effluent stream in line **172**. The remainder of the filtered reactor effluent stream in line **176** can be further used or prepared for release into the atmosphere as suitable. In an aspect of the present disclosure, the diluent CO.sub.2 stream in line **111** is taken from the filtered reactor effluent stream in line **172**. In an exemplary embodiment, the diluent CO.sub.2 stream in line **111** is taken from the CO.sub.2 stream for storage in line **174**. In another exemplary embodiment, the diluent CO.sub.2 stream in line **111** is taken from the remainder of the filtered reactor effluent stream in line **176**.

(33) Turning now to FIG. **2**, another exemplary embodiment of a process and an apparatus for regenerating catalyst from a fluidized catalytic process is addressed with reference to a process **201**. Elements of FIG. **2** may have the same configuration as in FIG. **1** and bear the same respective reference number and have similar operating conditions. Elements in FIG. **2** that correspond to elements in FIG. **1** but have a different configuration bear the same reference numeral as in FIG. **1** but are marked with a prime symbol (').

(34) As shown in FIG. **2**, a process **201** is provided for regenerating catalyst from a fluidized catalytic process. The process **201** additionally comprises an electrolyzer or an air separation unit (ASU) **103**. In accordance with an exemplary embodiment shown in FIG. **2**, the oxygen containing stream is an oxygen stream **106'** taken from an electrolyzer or an air separation unit (ASU) **103**.

(35) Various types of electrolyzer may be used as the electrolyzer **103** including but not limited to polymer electrolyte membrane/proton exchange membrane (PEM/PEMEC), alkaline electrolysis cell (AEC), anion exchange membrane (AEM), and solid oxide electrolysis cell (SOE/SOEC). In accordance with the present disclosure, the utilities generated in the fluidized catalytic process **201** may be used in the electrolysis section of the electrolyzer **103**. The electricity generated in the flue gas expander **130** may be used to power the PEM, AEC, AEM and SOEC electrolyzer. In addition, for SOEC electrolyzer, heat in the form of superheated steam from line **146** could be used in the SOEC electrolyzer to reduce the need for imported utilities.

(36) For the SOEC electrolyzer, about 25% to about 30% of the total energy requirement could be supplied by heat. In an exemplary embodiment, heat generated in fluidized bed flue gas section of the fluidized catalytic process may be supplied to the SOEC electrolyzer. Apart from taking heat generated in the fluidized catalytic process **201**, other sources of heat in the fluidized catalyst process are also envisioned for integration. For example, heat may be recovered from the main column overhead of the fluidized catalytic process. Furthermore, apart from using electricity for splitting water, electricity generated in the process unit could also be used for compression in the AEC, AEM, and PEM electrolyzer. The electrolyzer **103** may use the electricity generated in the flue gas expander **130**. In an exemplary embodiment, the electrolyzer **103** may use a portion of the electricity generated from the flue gas expander **130**. In another exemplary embodiment, the electrolyzer **103** may use the thermal energy or steam generated in the fluidized catalytic process **201**.

(37) Referring to FIG. **2**, the oxygen containing stream **106'** is an oxygen stream taken from an electrolyzer **103**. The electrolyzer **103** can be selected from one or more electrolyzer including but not limited to PEM/PEMEC, AEC, AEM, and SOE/SOEC. An air stream in line **104**, and a water stream in line **105** are provided to the electrolyzer **103**. Heat is also provided to the electrolyzer **103** from any suitable heat source. In an exemplary embodiment, the heat to the electrolyzer **103** may be supplied from any suitable process units of the fluidized catalytic process **201**. However, heat to

the electrolyzer **103** can be supplied from any other heat sources. The various utilities generated in the fluidized catalytic process can be used in the electrolyzer **103**. Hydrogen (not shown) from the electrolyzer can be withdrawn. The oxygen stream is withdrawn in line **106'** from the electrolyzer **103** and passed to the regenerator unit **110**.

(38) In an exemplary embodiment, the oxygen stream in line **106'** is mixed with the recycle stream in line **124** from the TSS **120** to provide the CO.sub.2 oxidation stream in line **108'**. The CO.sub.2 oxidation stream in line **108'** is passed to the regenerator unit **110**. In an aspect, the CO.sub.2 oxidation stream comprises an oxygen concentration of no more than about 30 mole %.

Alternatively, the recycle stream in line **124** and the oxygen stream in line **106'** can be passed separately or directly to the regenerator unit **110**. In an embodiment, an air stream in line **109** may also be passed to the regenerator unit **110**. In an exemplary embodiment, the air stream in line **109** may be combined with the CO.sub.2 oxidation stream in line **108'** or the oxygen stream in line **106'** and passed to the regenerator unit **110**. The power recovery stream **126** of the CO.sub.2 rich flue gas stream with reduced catalyst fines in the overflow stream in line **122** is passed to the flue gas expander **130**. After electricity generation, the power recovery stream now in line **132** from the flue gas expander **130** is passed to the heat recovery section **125**. In accordance with the exemplary embodiment shown in FIG. 2, the flue gas expander **130** may be optional. In an aspect of the present disclosure, the power recovery stream **126** may be passed directly to the heat recovery section **125**. The heat recovery section **125** may be in direct communication with the TSS **120** via the power recovery stream **126**.

(39) In an aspect of the present disclosure, a diluent stream in line **111** may also be passed to the regenerator unit **110**. The diluent stream in line **111** can be combined with the oxygen containing stream in line **106'** to provide a combined stream in line **107'**. The recycle stream in line **124** is mixed with the combined stream in line **107'** to provide the CO.sub.2 oxidation stream in line **108'** which is passed to the regenerator unit **110**. However, the diluent stream in line **111** can be passed to the regenerator unit **110** separately or directly. Thus, the oxygen stream in line **106'**, the diluent stream in line **111**, the recycle stream in line **124** from the TSS **120**, and the air stream in line **109** may be passed to the regenerator unit **110**. In an exemplary embodiment, the diluent stream in line **111** is a CO.sub.2 rich diluent stream. In another exemplary embodiment, the diluent stream in line **111** is a CO.sub.2 stream. In an aspect of the present disclosure, the diluent CO.sub.2 stream in line **111** can be sourced from the fluidized catalytic process after purification. Also, the diluent CO.sub.2 stream in line **111** can be sourced from any suitable source in the refinery as well. In an aspect of the present disclosure, the diluent CO.sub.2 stream in line **111** is sourced from the filtered reactor effluent stream in line **172**. In an exemplary embodiment, the diluent CO.sub.2 stream in line **111** is taken from the CO.sub.2 stream for storage in line **174**. In another exemplary embodiment, the diluent CO.sub.2 stream in line **111** is taken from the remainder of the filtered reactor effluent stream in line **176**. The rest of the process **201** is same as described in FIG. 1.

(40) Any of the above lines, conduits, units, devices, vessels, surrounding environments, zones or similar may be equipped with one or more monitoring components including sensors, measurement devices, data capture devices or data transmission devices. Signals, process or status measurements, and data from monitoring components may be used to monitor conditions in, around, and on process equipment. Signals, measurements, and/or data generated or recorded by monitoring components may be collected, processed, and/or transmitted through one or more networks or connections that may be private or public, general or specific, direct or indirect, wired or wireless, encrypted or not encrypted, and/or combination(s) thereof, the specification is not intended to be limiting in this respect. Further, the figure may include one or more exemplary sensors located on one or more conduits. Nevertheless, there may be sensors present on every stream so that the corresponding parameter(s) can be controlled accordingly.

(41) Signals, measurements, and/or data generated or recorded by monitoring components may be transmitted to one or more computing devices or systems. Computing devices or systems may

include at least one processor and memory storing computer-readable instructions that, when executed by the at least one processor, cause the one or more computing devices to perform a process that may include one or more steps. For example, the one or more computing devices may be configured to receive, from one or more monitoring component, data related to at least one piece of equipment associated with the process. The one or more computing devices or systems may be configured to analyze the data. Based on analyzing the data, the one or more computing devices or systems may be configured to determine one or more recommended adjustments to one or more parameters of one or more processes described herein. The one or more computing devices or systems may be configured to transmit encrypted or unencrypted data that includes the one or more recommended adjustments to the one or more parameters of the one or more processes described herein.

EXAMPLE

(42) A comparative analysis was conducted for the current process of recycling the recycle stream in line **124** of the overflow stream from the TSS to the regenerator unit **110**. The current process was compared with a base case process with no recycling of the overflow stream from the TSS to the regenerator unit **110**. The results are shown in TABLE A below:

(43) TABLE-US-00001 TABLE A Base Case With recycle % Reduction Conversion, Coke Yield, stream Coke in coke wt. % wt. % Yield, wt. % generation 70 5.1 3.57 30 75 5.4 3.94 27 80 5.7 4.33 24 85 6 4.74 21

(44) The results are also plotted and shown in FIG. 3. As evident from the Table and FIG. 3, the present process of recycling the recycle stream in line **124** of the overflow stream from the TSS to the regenerator unit **110** forms less coke as compared to the base case with no recycle. The present process of passing the recycle stream in line **124** to the regenerator generates 20-30% less coke as compared to the base case.

SPECIFIC EMBODIMENTS

(45) While the following is described in conjunction with specific embodiments, it will be understood that this description is intended to illustrate and not limit the scope of the preceding description and the appended claims.

(46) A first embodiment of the present disclosure is a process for regenerating catalyst from a fluidized catalytic process comprising passing a CO.sub.2 oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO.sub.2 rich flue gas stream; separating the CO.sub.2 rich flue gas stream into an underflow stream comprising catalyst fines and a CO.sub.2 rich flue gas overflow stream; separating the overflow stream into a recycle stream and a power recovery stream; and passing the recycle stream to the regenerator. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph further comprising mixing an oxygen containing stream, a diluent stream comprising CO.sub.2, and the recycle stream to provide the CO.sub.2 oxidation stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the oxygen containing stream is selected from one or both of an air stream or an oxygen stream taken from an electrolyzer or an air separation unit (ASU). An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the CO.sub.2 oxidation stream comprises an oxygen concentration of no more than 30 mole %. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the recycle stream comprises from about 5 vol % to about 80 vol % of the overflow stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph further comprising reducing a temperature of the recycle stream in a heat exchanger to provide a heat exchanged recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and passing the heat exchanged recycle stream to the regenerator. An embodiment of

the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph further comprising compressing the heat exchanged recycle stream to provide a heat exchanged and compressed recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and passing the heat exchanged and compressed recycle stream to the regenerator. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the recycle stream comprises oxygen in an amount from about 0.01 mol % to about 5 mol %. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the step of separating the CO.sub.2 rich flue gas stream comprises passing the CO.sub.2 rich flue gas stream to a third stage separator to provide the underflow stream and the overflow stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph, wherein the third stage separator is operating at a temperature from about 649° C. (1200° F.) to about 760° C. (1400° F.) and the recycle stream is recycled to the regenerator at a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.). An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph further comprising transferring heat from the power recovery stream to a boiler feed water stream in a heat recovery section to form a partially cooled CO.sub.2 rich flue gas stream and a steam stream; passing the partially cooled CO.sub.2 rich flue gas stream and the underflow stream to a decontamination reactor; reacting one or more of a sulfur-containing compound, a nitrogen-containing compound, or both in the partially cooled CO.sub.2 rich flue gas stream and/or the underflow stream with a reactant in the decontamination reactor to form a reactor effluent stream comprising reactant salt; filtering the reactor effluent stream to remove the reactant salt and catalyst fines to produce a filtered reactor effluent stream; and separating the diluent stream from the filtered reactor effluent stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph further comprising transferring heat from the power recovery stream to a boiler feed water stream in a heat recovery section to form a partially cooled CO.sub.2 rich flue gas stream and a steam stream; quenching the partially cooled CO2 rich flue gas stream to an adiabatic saturation temperature of about 60° C. to about 105° C. (140° F. to 220° F.) to provide a quenched gas stream; scrubbing the quenched gas stream with a liquid reactant comprising one or more of sodium hydroxide (NaOH) and potassium hydroxide (KOH) to produce CO2 rich reactor effluent stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph, wherein the heat recovery section is a heat recovery steam generator (HRSG) comprising transferring heat from the power recovery stream to a boiler feed water stream in the HRSG to form the partially cooled CO.sub.2 rich flue gas stream and the steam stream; and passing the partially cooled CO.sub.2 rich flue gas stream to the decontamination reactor. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the HRSG comprises a superheated steam section and a saturated steam section. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph further comprising passing the power recovery stream into the superheated steam section of the HRSG to produce a superheated steam stream and a heat exchanged CO.sub.2 rich flue gas stream; passing a boiler feed water stream and the heat exchanged CO.sub.2 rich flue gas stream into the saturated steam section of the HRSG to form the partially cooled CO.sub.2 rich flue gas stream and a saturated steam stream; introducing at least a portion of the saturated steam stream into the superheated steam section of the HRSG; and superheating the saturated steam stream with the CO.sub.2 rich flue gas stream to produce the superheated steam stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the

reactant comprises one or more of sodium hydroxide (NaOH), potassium hydroxide (KOH), sodium bicarbonate (NaHCO₃), calcium hydroxide (Ca(OH)₂) and trona salt (Na₂CO₃·Math.NaHCO₃·Math.2H₂O). An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the first embodiment in this paragraph wherein the reactant salt comprises one or more of sodium sulfite (Na₂SO₃), potassium nitrate (KNO₃), potassium sulfate (K₂SO₄), sodium sulphate (Na₂SO₄), sodium carbonate (Na₂CO₃) and sodium nitrate (NaNO₃).

(47) A second embodiment of the present disclosure is a process for regenerating catalyst from a fluidized catalytic process comprising passing a CO₂ oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO₂ rich flue gas stream; separating the CO₂ rich flue gas stream into an underflow stream comprising catalyst fines and a CO₂ rich flue gas overflow stream; separating the overflow stream into a recycle stream and a power recovery stream; and combining the recycle stream of the overflow stream with an air stream, and a diluent stream comprising CO₂ to provide the CO₂ oxidation stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the second embodiment in this paragraph wherein the recycle stream comprises from about 10 vol % to about 60 vol % of the overflow stream. An embodiment of the present disclosure is one, any or all of prior embodiments in this paragraph up through the second embodiment in this paragraph further comprising reducing a temperature of the recycle stream in a heat exchanger to provide a heat exchanged recycle stream and compressing the heat exchanged recycle stream to provide a heat exchanged and compressed recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and combining the heat exchanged and compressed recycle stream with the air stream and CO₂ rich diluent stream to provide the CO₂ oxidation stream.

(48) A third embodiment of the present disclosure is a process for regenerating catalyst from a fluidized catalytic process comprising passing a CO₂ oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO₂ rich flue gas stream; separating the CO₂ rich flue gas stream into an underflow stream comprising catalyst fines and a CO₂ rich flue gas overflow stream; separating the overflow stream into a recycle stream and a power recovery stream; reducing a temperature of the recycle stream in a heat exchanger to provide a heat exchanged recycle stream and compressing the heat exchanged recycle stream in a compressor to provide a heat exchanged and compressed recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and combining the heat exchanged and compressed recycle stream with an oxygen containing stream and a diluent stream comprising CO₂ to provide the CO₂ oxidation stream.

(49) A fourth embodiment of the present disclosure is a process for regenerating catalyst from a fluidized catalytic process comprising passing an oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO₂ rich flue gas stream; separating the CO₂ rich flue gas stream into an underflow stream comprising catalyst fines and a CO₂ rich flue gas overflow stream; separating the overflow stream into a recycle stream and a process stream; and passing the recycle stream to the regenerator.

(50) Without further elaboration, it is believed that using the preceding description that one skilled in the art can utilize the present disclosure to its fullest extent and easily ascertain the essential characteristics of this disclosure, without departing from the spirit and scope thereof, to make various changes and modifications of the disclosure and to adapt it to various usages and conditions. The preceding preferred specific embodiments are, therefore, to be construed as merely illustrative, and not limiting the remainder of the disclosure in any way whatsoever, and that it is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims.

(51) In the foregoing, all temperatures are set forth in degrees Celsius and, all parts and percentages are by weight, unless otherwise indicated.

Claims

1. A process for regenerating catalyst from a fluidized catalytic process comprising: passing a CO.sub.2 oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO.sub.2 rich flue gas stream; separating said CO.sub.2 rich flue gas stream into an underflow stream comprising catalyst fines and a CO2 rich flue gas overflow stream; separating said overflow stream into a recycle stream and a power recovery stream; and passing said recycle stream to the regenerator.
2. The process of claim 1 further comprising mixing an oxygen containing stream, a diluent stream comprising CO.sub.2, and said recycle stream to provide said CO.sub.2 oxidation stream.
3. The process of claim 2 wherein said oxygen containing stream is selected from one or both of an air stream or an oxygen stream taken from an electrolyzer or an air separation unit (ASU).
4. The process of claim 1 wherein said CO.sub.2 oxidation stream comprises an oxygen concentration of no more than 30 mole %.
5. The process of claim 1 wherein said recycle stream comprises from about 5 vol % to about 80 vol % of the overflow stream.
6. The process of claim 1 further comprising: reducing a temperature of said recycle stream in a heat exchanger to provide a heat exchanged recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and passing said heat exchanged recycle stream to the regenerator.
7. The process of claim 6 further comprising: compressing said heat exchanged recycle stream to provide a heat exchanged and compressed recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and passing said heat exchanged and compressed recycle stream to the regenerator.
8. The process of claim 1 wherein said recycle stream comprises oxygen in an amount from about 0.01 mol % to about 5 mol %.
9. The process of claim 1 wherein the step of separating said CO.sub.2 rich flue gas stream comprises passing said CO.sub.2 rich flue gas stream to a third stage separator to provide said underflow stream and said overflow stream.
10. The process of claim 9, wherein the third stage separator is operating at a temperature from about 649° C. (1200° F.) to about 760° C. (1400° F.) and said recycle stream is recycled to said regenerator at a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.).
11. The process of claim 2 further comprising: transferring heat from said power recovery stream to a boiler feed water stream in a heat recovery section to form a partially cooled CO.sub.2 rich flue gas stream and a steam stream; passing said partially cooled CO.sub.2 rich flue gas stream and said underflow stream to a decontamination reactor; reacting one or more of a sulfur-containing compound, a nitrogen-containing compound, or both in said partially cooled CO.sub.2 rich flue gas stream and/or said underflow stream with a reactant in said decontamination reactor to form a reactor effluent stream comprising reactant salt; filtering the reactor effluent stream to remove the reactant salt and catalyst fines to produce a filtered reactor effluent stream; and separating said diluent stream from said filtered reactor effluent stream.
12. The process of claim 11, wherein said heat recovery section is a heat recovery steam generator (HRSG) comprising: transferring heat from said power recovery stream to a boiler feed water stream in said HRSG to form said partially cooled CO.sub.2 rich flue gas stream and said steam stream; and passing said partially cooled CO.sub.2 rich flue gas stream to said decontamination reactor.
13. The process of claim 12 wherein the HRSG comprises a superheated steam section and a

saturated steam section.

14. The process of claim 13 further comprising: passing said power recovery stream into the superheated steam section of said HRSG to produce a superheated steam stream and a heat exchanged CO.sub.2 rich flue gas stream; passing a boiler feed water stream and said heat exchanged CO.sub.2 rich flue gas stream into the saturated steam section of the HRSG to form said partially cooled CO.sub.2 rich flue gas stream and a saturated steam stream; introducing at least a portion of the saturated steam stream into the superheated steam section of the HRSG; and superheating the saturated steam stream with said CO.sub.2 rich flue gas stream to produce the superheated steam stream.

15. The process of claim 11 wherein said reactant comprises one or more of sodium hydroxide (NaOH), potassium hydroxide (KOH), sodium bicarbonate (NaHCO.sub.3), calcium hydroxide (Ca(OH).sub.2) and trona salt (Na.sub.2CO.sub.3.Math.NaHCO.sub.3.Math.2H.sub.2O).

16. The process of claim 11 wherein the reactant salt comprises one or more of sodium sulfite (Na.sub.2SO.sub.3), potassium nitrate (KNO.sub.3), potassium sulfate (K.sub.2SO.sub.4), sodium sulphate (Na.sub.2SO.sub.4), sodium carbonate (Na.sub.2CO.sub.3) and sodium nitrate (NaNO.sub.3).

17. A process for regenerating catalyst from a fluidized catalytic process comprising: passing a CO.sub.2 oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO.sub.2 rich flue gas stream; separating said CO.sub.2 rich flue gas stream into an underflow stream comprising catalyst fines and a CO.sub.2 rich flue gas overflow stream; separating said overflow stream into a recycle stream and a power recovery stream; and combining said recycle stream of the overflow stream with an air stream and a diluent stream comprising CO.sub.2 to provide said CO.sub.2 oxidation stream.

18. The process of claim 17 wherein said recycle stream comprises from about 10 vol % to about 60 vol % of the overflow stream.

19. The process of claim 17 further comprising: reducing a temperature of said recycle stream in a heat exchanger to provide a heat exchanged recycle stream and compressing the heat exchanged recycle stream to provide a heat exchanged and compressed recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and combining said heat exchanged and compressed recycle stream with said air stream and CO2 rich diluent stream to provide said CO.sub.2 oxidation stream.

20. A process for regenerating catalyst from a fluidized catalytic process comprising: passing a CO.sub.2 oxidation stream to a regenerator in which coke is combusted from catalyst to provide a CO.sub.2 rich flue gas stream; separating said CO.sub.2 rich flue gas stream into an underflow stream comprising catalyst fines and a CO.sub.2 rich flue gas overflow stream; separating said overflow stream into a recycle stream and a power recovery stream; reducing a temperature of said recycle stream in a heat exchanger to provide a heat exchanged recycle stream and compressing the heat exchanged recycle stream in a compressor to provide a heat exchanged and compressed recycle stream having a temperature from about 260° C. (500° F.) to about 760° C. (1400° F.); and combining said heat exchanged and compressed recycle stream with an oxygen containing stream and a diluent stream comprising CO.sub.2 to provide said CO.sub.2 oxidation stream.
