

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12416164
B2
September 16, 2025
Gervasoni; Aristide et al.

Panel connection system

Abstract

Panel connection system for the corner connection of two panels which are arranged at an angled inclination to one another, having a first connecting element having a bearing portion with at least one support surface, by which the connecting element is supported on one of the two panels, and a leg portion which projects at an angled inclination from the bearing portion and which has at least one first engaging structure, and a second connecting element having a bearing portion having at least one support surface, by which the connecting element is supported on the other of the two panels, and having at least one second engaging structure which is situated opposite the support surface, wherein the at least one first engaging structure of the first connecting element is designed for engagement in the at least one second engaging structure of the second connecting element.

Inventors: Gervasoni; Aristide (Walenstadt, CH), Millon; Oliver Peter Günter (Wädenswil, CH), Rinder; Tassilo Folker (Mollis, CH), Toresan Eigenmann; André Felipe (Glarus Nord, CH), Trachsler; Martin (Engi, CH), Zanders; Carsten (Mollis, CH)

Applicant: Swisspearl Group AG (Niederurnen, CH)

Family ID: 1000008819863

Assignee: Swisspearl Group AG (Niederurnen, CH)

Appl. No.: 18/031478

Filed (or PCT Filed): October 15, 2021

PCT No.: PCT/EP2021/078561

PCT Pub. No.: WO2022/084167

PCT Pub. Date: April 28, 2022

Prior Publication Data

Document Identifier

US 20230374792 A1

Publication Date

Nov. 23, 2023

Foreign Application Priority Data

WO

PCT/EP2020/079377

Oct. 19, 2020

Publication Classification**Int. Cl.:** E04B2/00 (20060101); E04F13/08 (20060101)**U.S. Cl.:****CPC** E04F13/0892 (20130101); E04F2201/00 (20130101); E04F2201/05 (20130101)**Field of Classification Search****CPC:** E04F (2201/00); E04F (2201/05); E04F (13/0733)**USPC:** 52/656.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3113358	12/1962	Zell	52/285.3	F16B 12/20
3490797	12/1969	Platte	403/231	F16B 5/07
3618993	12/1970	Platte	52/285.3	F16B 12/26
3675955	12/1971	Hajduk	217/65	F16B 12/26
5437130	12/1994	Raynak	52/656.1	E06B 1/52
5720571	12/1997	Frobosilo	403/231	E04B 2/96
6000179	12/1998	Musculus	403/231	E04B 2/7425
6213679	12/2000	Frobosilo	403/14	E04B 2/96
6481177	12/2001	Wood	403/231	F16B 12/50
7137227	12/2005	Franz	52/712	E04B 1/38
8028489	12/2010	Lawrence	52/204.58	E06B 3/9641
9528315	12/2015	Kim	N/A	E06B 3/9765
12158008	12/2023	Ochi	N/A	E04F 13/0805
2006/0156679	12/2005	Pierret	52/698	A44B 17/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108360786	12/2017	CN	N/A
93 14 313	12/1992	DE	N/A
195 14 378	12/1995	DE	N/A
203 19 664	12/2004	DE	N/A
10-1327534	12/2012	KR	N/A

OTHER PUBLICATIONS

International Search Report for PCT/EP2021/078561 dated Nov. 18, 2021. cited by applicant

Primary Examiner: Katcheves; Basil S

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a National Stage of International Application No. PCT/EP2021/078561 filed Oct. 15, 2021, claiming priority based on International Application No. PCT/EP2020/079377 filed Oct. 19, 2020.

TECHNICAL FIELD

(2) The present invention relates to a panel connection system for the connection of two panels inclined at an angle to one another as claimed in claim 1, and to an assembly having two panels and said panel connection system, and to a method for installing the assembly.

PRIOR ART

(3) Façade cladding systems having panels are known from the prior art. Such panels are joined at the corners of buildings in different ways.

(4) In DE 93 14 313 U1 it is proposed to provide the panels with mitered edges in the corner region and to connect the panels together using an angle piece.

(5) DE 195 14 378 A1 likewise discloses an angle piece for the connection of two panels.

(6) DE 203 19 664 U1 discloses various embodiments of a two-part angle piece, wherein the two parts can be fixedly connected together. The connecting parts of DE 203 19 664 U1 are configured such that the connecting parts are displaceable relative to one another transverse to the two legs of the connecting parts.

(7) A disadvantage of the systems known from the prior art is the way in which they are installed. From a substructure on which the panels are to be installed, all the systems require a comparatively large amount of space for installation. This is a disadvantage in particular when there is also a scaffold in front of the substructure, which in most cases is erected very close to the substructure for reasons of occupational safety.

DESCRIPTION OF THE INVENTION

(8) Proceeding from this prior art, one object of the present invention is to provide a panel connection system for the connection of two panels arranged at an angle to one another, which overcomes the disadvantages of the prior art. A particularly preferred object is to provide a panel connection system which can be installed even in confined conditions.

(9) This object is achieved by the panel connection system as claimed in claim 1. According to that claim, a panel connection system for the corner connection of two panels arranged inclined at an angle, in particular at a right angle, to one another comprises a first connecting element comprising a mounting portion having at least one contact surface with which the connecting element lies directly or indirectly against one of the two panels, and a leg portion projecting from the mounting portion in a manner inclined at an angle and having at least one first engagement structure, and a second connecting element comprising a mounting portion having at least one contact surface with which the connecting element lies directly or indirectly against the other of the two panels, and having at least one second engagement structure situated opposite the contact surface. The at least one first engagement structure of the first connecting element is configured for engagement into the at least one second engagement structure of the second connecting element. In an engaged position, the two engagement structures engage into one another in a mechanically fixed manner, such that the two panels are fixedly connected together by way of the engagement structures. The two engagement structures are configured such that the two connecting elements can be connected together by way of a connecting movement along a longitudinal axis, which longitudinal axis is inclined at an angle to the contact surface of the first connecting element.

(10) The connection of the two connecting elements along said longitudinal axis has the advantage that the two panels can be connected together at a small distance from a substructure. The panels are here displaced in their panel plane and toward one another, which is particularly advantageous.

(11) In one embodiment, the two panels are at an angle of 90° to one another. The panels here lie directly against the contact surface.

(12) In another embodiment, the panels are inclined at an angle of from 78° to 102° to one another. At least one of the two panels here lies against the contact surface indirectly. For indirect contact, a wedge element described below is provided.

(13) The longitudinal axis extends along a straight line. A straight line is understood as being a straight line in the geometrical sense.

(14) The first engagement structure and the second engagement structure are configured to be complementary to one another, so that the above-mentioned engagement is made possible.

(15) The panel connection system can be used for various applications. Particularly preferably for façade panels or interior cladding. The panel connection system is typically fastened to the rear side of the panels.

(16) The panel is preferably a fiber-cement panel. Fiber-cement panels typically consist of cement and high tensile strength fibers. Such panels are typically produced by the Hatschek process. The

panel can, however, also be made of a different material. Examples which may be mentioned here include wood, natural slate, natural stone (e.g. granite, gneiss, quartzite, porphyry, sandstone or marble), ceramics (e.g. porcelain stoneware, stoneware, terracotta), fiber-reinforced fine-grained concrete (e.g. Cemfor, Rebeton), fiber-reinforced slate/stone chippings (e.g. Cottostone), fiber-reinforced laminates, metals (e.g. coated steel sheets, copper-titanium-zinc, aluminum, copper or chrome steel), layered composite materials (laminates, e.g. Alucobond), glass, or fully plastered supporting panels.

(17) In principle, homogeneous, organic and inorganic materials or combinations, such as fiber composite structures or layered composite structures, can be used.

(18) The geometric dimensions, such as thickness, format, or the appearance, such as the color, of the panel are independent of the fastening concept proposed herein. Likewise, the visible side can be provided with esthetic elements, such as paints or surface structures.

(19) Preferably, each of the two connecting elements has at least one sliding surface in the region of the engagement structures, wherein the sliding surfaces are arranged such that the two connecting elements are in contact with one another by way of the sliding surfaces during connection. Accordingly, there is a sliding movement between the two connecting elements during the connection process.

(20) The sliding surfaces provide a guide for the two connecting elements. During installation, the two connecting elements slide toward one another over the sliding surfaces in the direction of the longitudinal axis, such that the engagement structures are moved toward one another.

(21) Preferably, two engagement structures are provided per connecting element and thus form two pairs of engagement structures. A pair of engagement structures is provided by a first engagement structure and a second engagement structure. The arrangement of two pairs of engagement structures has the advantage of a properly guided and above all durable connection between the two connecting elements.

(22) Preferably, a first pair of engagement structures is arranged in the region of the transition from the mounting portion to the leg portion, and a second pair of engagement structures is arranged in the region of a free end of the leg portion.

(23) Preferably, one of the engagement structures is in the form of a receiver and the other of the engagement structures is in the form of a lug, wherein the lug can be inserted into the receiver along the longitudinal axis.

(24) The receiver is preferably so configured that the lug comes to lie substantially wholly in the receiver.

(25) Preferably, the receiver and/or the lug has a latching element which permits mechanically fixed latching of the two interengaging engagement structures.

(26) Preferably, the engagement structure having the latching element is interrupted by at least one slot extending in the longitudinal direction. The slot has the advantage that the latching force of the latching element can better be dimensioned.

(27) Preferably, the lug engages into the receiver substantially without play.

(28) In a particularly preferred embodiment, there are exactly two pairs of engagement structures. One pair has said latching elements. The other pair does not have latching elements, the two engagement structures here engage into one another without latching together. Preferably, the pair of engagement structures without the latching elements is arranged in the corner region or mitered region of the two panels. Precise positioning of the two panels in the region of the corners can thus be achieved. Said pair of engagement structures without the latching elements is further so configured that the engagement structures engage into one another up to their limit.

(29) Preferably, one of the two connecting elements has a screw opening which has an aperture that is open to the other connecting element, wherein a screw can be screwed into the screw opening, such that the screw exerts a clamping force on both connecting elements.

(30) The aperture extends through the side wall, which surrounds the screw opening. In the region

of the aperture, the screw opening is delimited by a wall region of the other connecting element. The screw is preferably a self-tapping metal screw which screws into the wall of the screw opening and said wall region.

(31) Preferably, the mounting portion has at least one fastening opening through which a fastening screw connected to the panel can be guided, such that the connecting element can be fixedly connected to said panel.

(32) Particularly preferably, two fastening openings situated spaced apart from one another are provided per connecting element.

(33) Preferably, the leg portion has one slot per fastening screw, which creates a passage region for the at least one fastening screw of the second connecting element on connection of the two connecting elements.

(34) Preferably, the leg portion is supported on the mounting portion by way of a support portion, wherein the support portion is arranged opposite the contact surface and the engagement structure. The support portion is preferably strut-like and acts against a force which would cause relative bending between the leg portion and the bearing portion.

(35) Particularly preferably, the support portion is connected by means of an intermediate leg to a side wall surrounding the screw opening. The stability of the first connecting element can thus be increased further.

(36) Preferably, there are two contact surfaces arranged spaced apart from one another per connecting element. Preferably, the contact surfaces are in the form of strip-shaped contact surfaces.

(37) Preferably, one of the contact surfaces of the first connecting element and/or of the second connecting element is configured with a lateral edge, wherein the lateral edge defines an intersection line for the rear sides of the two panels. In the connected state, the lateral edge comes to lie in the corner region of the two panels, whereby a precise alignment of the two panels can be achieved.

(38) Preferably, the first and second connecting elements are produced from a metal profile, in particular an aluminum profile, wherein the metal profile is processed by a machining operation after it has been cut to length.

(39) An assembly comprises at least one panel connection system as described above and two panels, wherein the first connecting element is mounted on the rear side of one panel and the second connecting element is mounted on the rear side of the other panel.

(40) The two panels with their connecting elements can be moved toward one another by a relative movement along the longitudinal axis, wherein engagement of the respective connection structures takes place as a result.

(41) Preferably, the two panels can be brought into contact with one another by way of their facing end faces, wherein the end faces are in the form of mitered faces.

(42) Preferably, multiple panel connection systems are provided in each case. The distance between the mentioned panel connection systems can be between 20 and 100 centimeters. In the case of panels with greater rigidity, a greater distance can be chosen than in the case of panels with lower rigidity.

(43) Preferably, the angle between the contact surface of the first connecting element and the contact surface of the second connecting element is substantially 90° , such that, when the connecting elements lie directly against the respective panel, the two panels are arranged at a right angle to one another.

(44) In a further embodiment, the panel connection system further comprises at least one wedge element which can be arranged or is arranged on at least one of the mentioned contact surfaces and at least one of the rear sides of the panel such that the at least one contact surface lies against the rear side of the panel indirectly by way of the wedge element and the panels are inclined at an angle to one another that is other than a right angle.

(45) Preferably, the further embodiment is characterized in that the wedge element has a latching portion with which the wedge element can be connected to the connecting element in question by way of a latching connection; and/or the wedge element has a contact surface with which the wedge element lies against the panel in question; and/or the wedge element is made of a metal, such as aluminum, or a plastics material, such as polypropylene; and/or the mentioned angle is between 91° and 102° or between 78° and 89°.

(46) A method for installing an assembly as described above is characterized in that, in a first step, the first and second connecting elements are connected to the respective panel and in that, in a subsequent step, the two panels with the connecting elements are moved relative to one another by way of a connecting movement along a longitudinal axis, such that the at least one first engagement structure of the first connecting element engages into the at least one second engagement structure of the second connecting element. The connecting elements are preferably connected directly or, where the wedge element is present, indirectly to the panel in question.

(47) Further embodiments are indicated in the dependent claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Preferred embodiments of the invention will be described in the following with reference to the drawings, which serve merely for explanatory purposes and are not to be interpreted as being limiting. In the drawings:

(2) FIGS. **1a** and **1b** are a perspective view and a plan view of a panel connection system according to the invention having two panels prior to connection;

(3) FIGS. **2a** and **2b** are the views according to FIG. **1a/1b** during connection;

(4) FIG. **3** is a further perspective view of the preceding figures during installation;

(5) FIGS. **4a** and **4b** are the views according to FIG. **1a/1b** after connection has taken place;

(6) FIG. **5** is the view of FIG. **4b** with a screw inserted;

(7) FIG. **6** is a perspective view of a first connecting element according to the preceding figures;

(8) FIG. **7** is a perspective view of FIG. **6** from a different direction;

(9) FIG. **8** is a perspective view of a second connecting element according to the preceding figures;

(10) FIG. **9** is a perspective view of FIG. **8** from a different direction;

(11) FIG. **10** is a perspective view of the panel connection system according to the invention with two panels;

(12) FIGS. **11a** to **11c** are views of a further embodiment in a first configuration;

(13) FIGS. **12a** to **12c** are views of the further embodiment in a second configuration;

(14) FIGS. **13a** to **13c** are views of the further embodiment in a third configuration;

(15) FIGS. **14a** to **14c** are views of the further embodiment in a fourth configuration; and

(16) FIG. **15** is an exemplary view of one of the further embodiments.

DESCRIPTION OF PREFERRED EMBODIMENTS

(17) In the figures, a panel connection system **1** for the corner connection of two panels **2, 3** arranged inclined at an angle, in particular at a right angle, to one another is shown. The panels **2, 3** are, for example, façade cladding panels or panels which are to be arranged in a different way. The panels **2, 3** with the panel connection system **1** are referred to as an assembly. The panels **2, 3** typically stand vertically but may also be oriented horizontally and vertically or in any other spatial position.

(18) The panels each have a visible side **31, 32** and a rear side **27, 28**. The rear sides **27, 28** are each oriented against a substructure or against a house wall or the like. The panels further have end faces **29, 30**. In the installed position, the end faces **29, 30** of the two panels **2, 3** are oriented toward one another. Particularly preferably, the end faces **29, 30** are mitered so that the two end faces **31, 32** lie

against one another such that from outside a defined edge **38** can be created in the region of the corner **39** of the two panels **2, 3**.

(19) The panel connection system **1** comprises a first connecting element **4** and a second connecting element **9**. The first connecting element **4** is fixedly connected to the panel **2**, and the second connecting element **9** is fixedly connected to the panel **3**. Depending on the size of the panels, multiple connection systems are to be used.

(20) The first connecting element **4** comprises a mounting portion **5** having at least one contact surface **6**. The connecting element **4** lies with the at least one contact surface **6** against the rear side **27** of the panel **2**. The first connecting element **4** further comprises a leg portion **7** which projects in a manner inclined at an angle, here at a right angle, from the mounting portion **4**. The leg portion **7** has at least one first engagement structure **8**. In the embodiment shown, two first engagement structures **8** are arranged spaced apart from one another.

(21) The second connecting element **9** comprises a mounting portion **10** having at least one contact surface **11**. The second connecting element **9** lies with the at least one contact surface **11** against the rear side **28** of the panel **3**. The second connecting element **9** further comprises at least one engagement structure **12** situated opposite the contact surface **11**. In the embodiment shown, two second engagement structures **12** are arranged spaced apart from one another.

(22) In FIGS. **1** to **10**, the connecting elements **4, 9** are in direct contact with the respective panels **2, 3**. FIGS. **11** to **14** show a further embodiment in which the connecting elements **4, 9** are in indirect contact with the respective panel **2, 3**. For indirect contact, a wedge element **43** is arranged between the panel in question and at least one of the connecting elements **4, 9**.

(23) The two engagement structures **8, 12** are configured such that the two connecting elements **4, 9** can be connected together by way of a displacement movement **V**. The displacement movement **V** extends along a straight longitudinal axis **L**. The longitudinal axis **L** extends inclined at an angle, here at a right angle, to the contact surface **6** of the first connecting element **4**, or parallel to the at least one contact surface **11** of the second connecting element **9**. Typically, the longitudinal axis **L** is accordingly parallel to the rear side **28** of the panel **3** and at a right angle to the rear side **27** of the panel **2**.

(24) In FIGS. **1a** and **1b**, the panel connection system **1** with the two panels **2, 3** is shown in a position prior to the actual connection. Starting from this position, the two panels **2, 3** are connected together by means of the first connecting element **4** and the second connecting element **9** by way of the displacement movement **V** along the longitudinal axis **L**.

(25) FIGS. **2a** and **2b** show the progression of the displacement movement **V** relative to FIGS. **1a** and **1b**, wherein the two panels **2, 3** are shown moved closer to one another. The engagement structures **8, 9** are here about to come into mechanical engagement with one another.

(26) FIG. **3** is a further perspective view of the displacement.

(27) FIGS. **4a** and **4b** then show the end position. The two panels **2, 3** are in contact by way of their end faces **29, 30** or are at a very small distance from one another. Furthermore, the engagement structures **8** of the first connecting element **4** and the engagement structures **12** of the second connecting element **9** are in mechanically fixed engagement with one another and the two panels **2, 3** are thus connected together by way of the engagement of the engagement structures **8, 12**.

(28) It is further apparent from FIGS. **1a** to **4b** that the mounting portion **5** of the first connecting element **4** and the mounting portion **10** of the second connecting element **9** each have at least one fastening opening **21**. In the embodiment shown, each of the mounting portions **5, 10** has two fastening openings **21**. By way of these fastening openings **21**, the connecting element **4, 9** can be fixedly connected to the respective panel **2, 3**. In the embodiment shown, a fastening screw **22** connected to the panel **2, 3** has been guided through the fastening opening **21** such that the connecting element **4, 9** can be fixedly connected to said panel **2, 3**. In the embodiment shown, a nut **33** is further provided for the connection, which nut is screwed onto the fastening screw **22** and thus presses the connecting element **4, 5** in question against the rear side **27, 28** of the panel **2, 3**.

Other types of connection are also conceivable. For example, it would be conceivable that the two connecting elements **4**, **9** are adhesively bonded to the panels **2**, **3**.

(29) The leg portion **7** of the first connecting element **4** has one slot **17** per fastening screw **22**.

(30) The slot **17** creates a passage region for the fastening screw **22** on connection of the two connecting elements **4**, **9**. This passage is shown accordingly in FIGS. **2a** and **3**. It can clearly be seen here how the fastening screw **22**, on connection by way of the displacement movement **V** along the longitudinal axis **L**, correspondingly enters the slot and is guided through the slot **17**.

(31) With regard to the displacement movement **V**, it is advantageous if the first connecting element **4** and the second connecting element **9** have corresponding sliding surfaces **13**. The two connecting elements **4**, **9** each have at least one sliding surface **13** in the region of the engagement structures **8**, **12**. FIG. **1b** shows the first contact of the sliding surfaces **13** of the two connecting elements **4**, **9**. The sliding surfaces **13** serve to allow the two connecting elements **4**, **9** to be in contact with one another during connection by way of the displacement movement **V** by way of the sliding surfaces **13**, so that a sliding displacement movement **V** can be achieved. FIG. **2b** shows the further progression of the displacement movement **V**. It can easily be seen here that a further sliding surface **13** on the second connecting element **9** comes into contact with the sliding surface **13** of the first connecting element **4**.

(32) As mentioned, the first connecting element **4** has two first engagement structures **8**, and the second connecting element **9** has two second engagement structures **12**. Two pairs of engagement structures **8**, **12** are thus formed. A first pair of engagement structures **8**, **12** is arranged in the region of the corner **39** of the two panels **2**, **3**. A second pair is arranged at the end of the leg portion **7**, that is to say spaced apart from said corner **39**. By means of this spaced apart arrangement of the two pairs of engagement structures **8**, **12**, it can be achieved that the two connecting elements **4**, **9** are stably connected together.

(33) In the embodiment shown, the two engagement structures **8** on the first connecting element are each in the form of a receiver. The engagement structures **12** on the second connecting element **9** are each in the form of a lug **15**. The lug **15** can be inserted along the longitudinal axis **L** into the receiver **14** and, as is shown in FIGS. **4a** and **4b**, is accommodated substantially completely in the receiver.

(34) In the embodiment shown, one of the receivers **14**, namely the receiver **14** arranged spaced apart from the above-mentioned corner **39** of the two panels **2**, **3**, has a latching element **16**. The latching element **16** allows mechanically fixed latching of the two interengaging engagement structures **8**, **12**. In the embodiment shown, the lug **15** has a corresponding counter-piece **34**, on which the latching element **16** correspondingly latches. The other of the two pairs of engagement structures **8**, **12** does not have a latching structure in the embodiment shown. In the case of the other of the two pairs, a lug **41** engages into a receiver **42**. The lug **41** and the receiver **42** are dimensioned such that the lug **41** abuts the base of the receiver **42**. Exact positioning of the two connecting elements **4**, **9** and thus also of the two panels **2**, **3** is thereby achieved. Preferably, both pairs of engagement structures **8**, **12** are so positioned that, when the lug **41** abuts the base of the receiver **42**, the latching element **16** latches on the counter-piece **34**. In this position, the two connecting elements **4**, **9** are preferably situated without play relative to one another with respect to a movement in the direction of the longitudinal axis **L**.

(35) Preferably, the engagement structures **8**, **12** engage into one another substantially without play.

(36) The receiver **14** and/or the lug **15** can further have beveled portions **35**, which correspondingly facilitates the connection between the receiver **14** and the lug **15**.

(37) FIG. **5** shows the mechanical securing between the first connecting element **4** and the second connecting element **9**. In order to mechanically secure the first connecting element **5** to the second connecting element **9**, the first connecting element **4** has a screw opening **18**. The screw opening **18** has an aperture **19** which is open to the second connecting element **9**. A screw **20** can be screwed into the screw opening **18** and, owing to the aperture **19**, the screw **20** is then located in the screw

opening **18** such that the screw **20** exerts a clamping force on both connecting elements **4, 9**. In the region of the aperture **21**, the screw opening **18** is delimited by a wall region **36** of the second connecting element **9**. As the screw **20** is screwed in, the screw **20** comes into contact with the side walls of the aperture **19** and with the wall region **36** of the second connecting element **9**. A clamping force is thus provided between the two connecting elements **4, 9**. The screw **20** is preferably a self-tapping metal screw.

(38) During installation, the screw opening can also serve to receive a threaded rod, so that two panel connection systems **1** arranged adjacent to one another can be aligned relative to one another by way of the threaded rod.

(39) It can further be seen from all the figures that the leg portion **7** is supported on the mounting portion **5** by way of a support portion **23**. The support portion **23** extends at the rear, that is to say opposite the contact surface **6** and the sliding surface **13** of the first connecting element **4**, between the mounting portion **5** and the leg portion **7**. In the embodiment shown, the support portion **23** further comprises an intermediate leg **24**, which is connected to the side wall **25** surrounding the screw opening **18**. The support portion **23** can prevent the contact surface **6** from bending relative to the mounting portion **5**. In the embodiment shown, the support portion **23** has a concavity **40**. The concavity **40** provides a free space for a substructure, such as, for example, wooden battens or a metal structure.

(40) Further preferred features of the two connecting elements **4, 9** will now be explained with reference to FIGS. **6** to **9**.

(41) In the embodiment shown, there is preferably more than one contact surface **6, 11** per connecting element **4, 9**. On the first connecting element **4** there are two contact surfaces **6, 11** spaced apart from one another. The contact surfaces **6** are arranged in the form of strip-like contact surfaces **6**. The fastening openings **21** are arranged between the two contact surfaces **6**. The fastening openings **21** emerge through a surface **37** against the panel **2**. The surface **37** is arranged offset with respect to the contact surfaces **6**, so that the surface **37** does not come into contact with the rear side **27** of the panel **2**. This has the advantage that a slightly resilient connection can be provided in the region of the surface **37**. Likewise, the second connecting element **9** also has two contact surfaces **11**. These two contact surfaces **11** are also arranged spaced apart from one another, and the fastening openings **21** are located between them. Here too, a surface **37** is arranged between the two contact surfaces **11**, so that the same spring effect can be achieved.

(42) Preferably, the contact surfaces **6, 11** are so arranged that they merge into one another in the region of the corner **39** of the two panels **2, 3**. Particularly preferably, the contact surfaces **6, 11**, located in the corner region, of the first connecting element **8** and of the second connecting element **9** are configured with a lateral edge **26**. The lateral edge **26** defines an intersection line for the rear sides **27, 28** of the two panels **2, 3**. The connecting element can accurately be aligned with the corresponding edge of the panel **2** by means of the lateral edge **26**.

(43) In FIG. **10**, the above-mentioned assembly of the two panels **2, 3** with multiple panel connection systems **1** is shown in the end position. The panel connection systems **1** are arranged spaced apart from one another by a distance **A**. The chosen distance **A** can be larger or smaller according to the stability of the panel. In the case of fiber-cement panels, the typical distance is between 20 centimeters and 100 centimeters.

(44) FIGS. **11a** to **14b** show a further embodiment in different configurations. The panel connection system **1** according to this further embodiment further comprises at least one wedge element **43**. The wedge element **43** is arranged between the contact surface **6, 11** and the rear side **27, 28** of the panel **2, 3** such that the contact surface **6, 11** lies against the rear side **27, 28** of the panel **2, 3** indirectly by way of the wedge element **43**.

(45) Preferably, the wedge element **43** is connected to the connecting element **4, 9** in question by way of a latching portion **44**. The latching portion **44** has a base surface **48** and at least one latching hook **49**. The wedge element lies against the contact surface **6, 11** of the connecting element **4, 9** in

question by way of the base surface **48**.

(46) The wedge element **43** has a contact surface **45** with which the wedge element **43** lies against the rear side **27**, **28** of the panel **2**, **3** in question. The contact surface **45** is situated opposite the latching portion **44**.

(47) The latching portion **44**, in particular the base surface **48** thereof, and said contact surface **45** are arranged at an angle to one another, so that said angle between the two panels can be achieved.

(48) Preferably, the wedge element **43** has at least one fastening opening **47** through which the fastening screw **22** can be guided.

(49) In a first configuration according to FIGS. **11a** to **11c**, a wedge element **43** is arranged between the second connecting element **9** and the second panel **3**. The first connecting element **4** is in direct contact with the first panel **3**. The wedge element **43** according to this configuration is configured such that the two panels **2**, **3** are at an angle of greater than 90° , or 91° , to one another.

(50) In a second configuration according to FIGS. **12a** to **12c**, a wedge element **43** is arranged both between the first connecting element **4** and the first panel **2** and between the second connecting element **9** and the second panel **3**. The wedge element **43** according to this configuration is configured such that the two panels **2**, **3** are at an angle of greater than 90° , or 91° , to one another. Compared to the first configuration, larger angles can be achieved in the second configuration.

(51) In the first and second configurations, the wedge element **43** is configured and arranged such that the two connecting elements **4**, **9** define with their lateral edges **26** the intersection line for the rear sides **27**, **28** of the two panels **2**, **3**.

(52) In a third configuration according to FIGS. **13a** to **13c**, a wedge element **43** is arranged between the second connecting element **9** and the second panel **3**. The first connecting element **4** is in direct contact with the first panel **3**. The wedge element **43** according to this configuration is configured such that the two panels **2**, **3** are at an angle of less than 90° , or 89° , to one another.

(53) In a fourth configuration according to FIGS. **14a** to **14c**, a wedge element **43** is arranged both between the first connecting element **4** and the first panel **2** and between the second connecting element **9** and the second panel **3**. The wedge element **43** according to this configuration is configured such that the two panels **2**, **3** are at an angle of less than 90° , or 89° , to one another. Compared to the third configuration, larger angles can be achieved in the fourth configuration.

(54) In the third and fourth configurations, the wedge element **43** is configured and arranged such that the wedge element has a lateral edge **26** which defines the intersection line for the rear sides **27**, **28** of the two panels **2**, **3**.

(55) Finally, FIG. **15** is a further view of the different configuration, wherein a compensation element **50** is inserted here for angle compensation of the angle between the contact surface of the nut and the connecting element. The compensation element **50** can be used in all the embodiments according to FIGS. **11a** to **14b**. Preferably, the compensation element **50** compensates for the angle such that the underside of the nut **33** is able to lie flat against the compensation element **50**. The compensation element **50** is preferably made of a metallic material, in particular of aluminum, or of plastics material, in particular of polypropylene or of a recycled plastics material.

LIST OF REFERENCE SIGNS

(56) TABLE-US-00001 1 panel 2 panel 3 panel 4 first connecting element 5 mounting portion 6 contact surface 7 leg portion 8 engagement structure 9 second connecting element 10 mounting portion 11 contact surface 12 engagement structure 13 sliding surface 14 receiver 15 lug 16 latching element 17 slot 18 screw opening 19 open aperture 20 screw 21 fastening openings 22 fastening screw 23 support portion 24 intermediate leg 25 side wall 26 lateral edge 27 rear side 28 rear side 29 end face 30 end face 31 visible side 32 visible side 33 nut 34 counter-piece 35 bevel 36 wall region 37 surface 38 defined edge 39 corner 40 concavity 41 receiver 42 lug 43 wedge element 44 latching portion 45 contact surface 47 fastening opening 48 base surface 49 latching hook 50 compensation element A distance V displacement movement L longitudinal axis

Claims

1. A panel connection system for the corner connection of two panels arranged inclined at an angle to one another, comprising a first connecting element comprising a first mounting portion having at least one contact surface with which the connecting element lies against one of the two panels, and a leg portion projecting from the first mounting portion in a manner inclined at an angle and having at least one first engagement structure, and a second connecting element comprising a second mounting portion having at least one contact surface with which the connecting element lies against the other of the two panels, and having at least one second engagement structure situated opposite the contact surface, wherein the at least one first engagement structure of the first connecting element is configured for engagement into the at least one second engagement structure of the second connecting element, wherein the two engagement structures are configured such that the two connecting elements can be connected together by way of a connecting movement along a longitudinal axis, which longitudinal axis is inclined at an angle to the contact surface of the first connecting element, wherein two first and two second engagement structures are provided per connecting element and thus form two pairs of engagement structures and wherein a first pair of engagement structures is arranged in a region of the transition from the first mounting portion to the leg portion, and wherein a second pair of engagement structures is arranged in a region of a free end of the leg portion.
2. The panel connection system as claimed in claim 1, wherein each of the two connecting elements has at least one sliding surface in a region of the engagement structures, wherein the sliding surfaces are arranged such that the two connecting elements are in contact with one another by way of the sliding surfaces during connection.
3. The panel connection system as claimed in claim 1, wherein one of the engagement structures is in the form of a receiver, and wherein another of the engagement structures is in the form of a lug, wherein the lug can be inserted into the receiver along the longitudinal axis.
4. The panel connection system as claimed in claim 3, wherein the lug engages into the receiver substantially without play.
5. The panel connection system as claimed in claim 1, wherein one of the engagement structures is in the form of a receiver, and wherein another of the engagement structures is in the form of a lug, wherein the lug can be inserted into the receiver along the longitudinal axis, and wherein the receiver and/or the lug has a latching element which permits mechanically fixed latching of the two interengaging engagement structures.
6. The panel connection system as claimed in claim 5, wherein the engagement structure having the latching element is interrupted by at least one slot extending in the longitudinal direction; and/or wherein the lug engages into the receiver substantially without play.
7. The panel connection system as claimed in claim 1, wherein one of the two connecting elements has a screw opening which has an aperture that is open to the other connecting element, wherein a screw can be screwed into the screw opening, such that the screw exerts a clamping force on both connecting elements.
8. The panel connection system as claimed in claim 1, wherein at least one of said mounting portions has at least one fastening opening through which a fastening screw connected to the panel can be guided, such that the connecting element can be fixedly connected to said panel.
9. The panel connection system as claimed in claim 1, wherein at least one of said mounting portions has at least one fastening opening through which a corresponding fastening screw connected to the panel can be guided, such that the connecting element can be fixedly connected to said panel and wherein the leg portion has one slot per fastening screw, wherein each slot creates a passage region for the corresponding fastening screw on connection of the two connecting elements.

10. The panel connection system as claimed in claim 1, wherein the leg portion is supported on the first mounting portion and/or on the second mounting portion by way of a support portion, wherein the support portion is arranged opposite the contact surface and the engagement structure.
11. The panel connection system as claimed in claim 1, wherein one of the two connecting elements has a screw opening which has an aperture that is open to the other connecting element, wherein a screw can be screwed into the screw opening, such that the screw exerts a clamping force on both connecting elements, wherein the leg portion is supported on the first mounting portion and/or on the second mounting portion by way of a support portion, wherein the support portion is arranged opposite the contact surface and the engagement structure, and wherein the support portion is connected by means of an intermediate leg to a side wall surrounding the screw opening.
12. The panel connection system as claimed in claim 1, wherein there are two contact surfaces arranged spaced apart from one another per connecting element.
13. The panel connection system as claimed claim 1, wherein one of the contact surfaces of the first connecting element and/or of the second connecting element is configured with a lateral edge, wherein, in an assembled state of the panel connection system, the lateral edge aligns with a joint between rear sides of the two panels.
14. The panel connection system as claimed in claim 1, wherein an angle between the contact surface of the first connecting element and the contact surface of the second connecting element is substantially 90° , such that, when the connecting elements lie directly against the respective panel, the two panels are arranged at a right angle to one another.
15. The panel connection system as claimed in claim 1, wherein the panel connection system further comprises at least one wedge element which can be arranged on at least one of the mentioned contact surfaces and at least one of the rear sides of the panel such that the at least one contact surface lies against the rear side of the panel indirectly by way of the wedge element and the panels are inclined at an angle to one another that is other than a right angle.
16. The panel connection system as claimed in claim 15, wherein the wedge element has a latching portion with which the wedge element can be connected to the connecting element by way of a latching connection; and/or the wedge element has a contact surface with which the wedge element lies against the panel; and/or the wedge element is made of a metal, such as aluminum, or a plastics material, such as polypropylene; and/or the mentioned angle is between 91° and 102° or between 78° and 89° .
17. An assembly comprising at least one panel connection system and two panels arranged inclined at an angle to one another, wherein said panel connection system is provided for the corner connection of the two panels and said panel connection system comprises a first connecting element comprising a first mounting portion having at least one contact surface with which the connecting element lies against one of the two panels, and a leg portion projecting from the first mounting portion in a manner inclined at an angle and having at least one first engagement structure, and a second connecting element comprising a second mounting portion having at least one contact surface with which the connecting element lies against the other of the two panels, and having at least one second engagement structure situated opposite the contact surface, wherein the at least one first engagement structure of the first connecting element is configured for engagement into the at least one second engagement structure of the second connecting element, wherein the two engagement structures are configured such that the two connecting elements can be connected together by way of a connecting movement along a longitudinal axis, which longitudinal axis is inclined at an angle to the contact surface of the first connecting element, wherein the first connecting element is mounted on a rear side of one panel and the second connecting element is mounted on a rear side of the other panel, wherein two first and two second engagement structures are provided per connecting element and thus form two pairs of engagement structures and wherein a first pair of engagement structures is arranged in a region of the transition from the first mounting portion to the leg portion, and wherein a second pair of engagement structures is arranged in a

region of a free end of the leg portion.

18. A method for installing the assembly as claimed in claim 17, comprising providing the at least one panel connection system and the two panels, and wherein, in a first step, the first and second connecting elements are connected to the respective panel and wherein, in a subsequent step, the two panels with the connecting elements are moved relative to one another by way of a connecting movement along a longitudinal axis, such that the at least one first engagement structure of the first connecting element engages into the at least one second engagement structure of the second connecting element.

19. An assembly comprising at least one panel connection system and two panels arranged inclined at an angle to one another, wherein said panel connection system is provided for the corner connection of the two panels and said panel connection system comprises a first connecting element comprising a mounting first portion having at least one contact surface with which the connecting element lies against one of the two panels, and a leg portion projecting from the first mounting portion in a manner inclined at an angle and having at least one first engagement structure, and a second connecting element comprising a second mounting portion having at least one contact surface with which the connecting element lies against the other of the two panels, and having at least one second engagement structure situated opposite the contact surface, wherein the at least one first engagement structure of the first connecting element is configured for engagement into the at least one second engagement structure of the second connecting element, wherein the two engagement structures are configured such that the two connecting elements can be connected together by way of a connecting movement along a longitudinal axis, which longitudinal axis is inclined at an angle to the contact surface of the first connecting element, wherein the first connecting element is mounted on a rear side of one panel and the second connecting element is mounted on a rear side of the other panel, wherein the two panels can be brought into contact with one another by way of end faces, wherein the end faces are in the form of mitered surfaces, wherein two first and two second engagement structures are provided per connecting element and thus form two pairs of engagement structures and wherein a first pair of engagement structures is arranged in a region of the transition from the first mounting portion to the leg portion, and wherein a second pair of engagement structures is arranged in a region of a free end of the leg portion.

20. A method for installing the assembly as claimed in claim 19, comprising providing the at least one panel connection system and the two panels, and wherein, in a first step, the first and second connecting elements are connected to the respective panel and wherein, in a subsequent step, the two panels with the connecting elements are moved relative to one another by way of a connecting movement along a longitudinal axis, such that the at least one first engagement structure of the first connecting element engages into the at least one second engagement structure of the second connecting element.
