

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416520
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Yoda; Yukihide et al.

Specifying system, specifying apparatus, and specifying method

Abstract

A specifying system according to the present disclosure includes an optical fiber (30) laid along a levee (20) of a river (10), a communication unit (41) configured to receive, from the optical fiber (30), an optical signal containing a pattern that changes according to a state of the levee (20), and a specifying unit (51) configured to specify a water level of the river (10) based on the pattern that changes according to the state of the levee (20).

Inventors:	Yoda; Yukihide (Tokyo, JP), Mori; Koyo (Tokyo, JP), Iwano; Tadayuki (Tokyo, JP)
Applicant:	NEC Corporation (Tokyo, JP)
Family ID:	1000008819787
Assignee:	NEC CORPORATION (Tokyo, JP)
Appl. No.:	18/032138
Filed (or PCT Filed):	October 28, 2020
PCT No.:	PCT/JP2020/040376
PCT Pub. No.:	WO2022/091242
PCT Pub. Date:	May 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230384141 A1	Nov. 30, 2023

Publication Classification

Int. Cl.: G01F23/14 (20060101); E02B3/04 (20060101); G01F23/22 (20060101); G01N21/95 (20060101); G08C23/06 (20060101); H04N7/22 (20060101); H04N23/661 (20230101)

U.S. Cl.:

CPC G01F23/14 (20130101); E02B3/04 (20130101); G01F23/22 (20130101); G01N21/95 (20130101); G08C23/06 (20130101); H04N7/22 (20130101); H04N23/661 (20230101);

Field of Classification Search

USPC: 348/125

References Cited

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H06-74768	12/1993	JP	N/A
2001-249035	12/2000	JP	N/A
2001-296151	12/2000	JP	N/A
2002-054974	12/2001	JP	N/A
2002269656	12/2001	JP	N/A
2003-232043	12/2002	JP	N/A
2004-361323	12/2003	JP	N/A
2012-198079	12/2011	JP	N/A

OTHER PUBLICATIONS

International Search Report for PCT Application No. PCT/JP2020/040376, mailed on Dec. 28, 2020. cited by applicant

Primary Examiner: Shahnam; Amir

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

(1) This application is a National Stage Entry of PCT/JP2020/040376 filed on Oct. 28, 2020, the contents of all of which are incorporated herein by reference, in their entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a specifying system, a specifying apparatus, and a specifying method.

BACKGROUND ART

(3) In recent years, disasters such as river flooding and floods have frequently occurred due to typhoons and other storms.

(4) Therefore, in order to improve the efficiency of responses to disasters, it is necessary to collect, in real time, information about the water levels of rivers where flooding or a flood could occur.

(5) Under the present circumstances, the water levels of rivers are checked by visually checking video images taken by cameras and/or visually observing the rivers with the human eye.

(6) However, regarding the visual observation with the human eye, the range of an area that can be

observed at one time is limited to a localized area. Further, regarding the visual observation with the human eye, it may be difficult to accurately determine the state of a river depending on the weather (rough weather or the like) and time of day (nighttime or the like).

(7) Therefore, it is necessary to check the state of a river(s) in a wide area and in real time without relying on visual observation with the human eye.

(8) Meanwhile, recently, a technology called optical fiber sensing, which enables sensing in a wide area and in real time by using optical fibers as sensors, has attracted attention, and various proposals for using optical fiber sensing have been made.

(9) For example, in a technology disclosed in Patent Literature 1, optical fibers are buried under the ground in such manner that they extend along a bank. Then, an amount of a distortion at each of a plurality of points of an optical fiber is calculated by detecting scattered light that is emitted from the optical fiber when pulsed light is applied to the optical fiber. The amount of the distortion at each point of the optical fiber increases according to the increase in an amount of movement of soil. Therefore, an occurrence of a disaster such as a landslide is detected based on the amount of the distortion at each point calculated as described above.

(10) Further, in a technology disclosed in Patent Literature 2, optical fibers are buried inside a levee and parallel to the inclined surface of the levee. Further, a change in the state of the levee is detected by applying light to an optical fiber and measuring a change in scattered light caused by a distortion of the optical fiber.

CITATION LIST

Patent Literature

(11) Patent Literature 1: Japanese Unexamined Patent Application Publication No. 2003-232043

Patent Literature 2: Japanese Unexamined Patent Application Publication No. 2001-249035

SUMMARY OF INVENTION

Technical Problem

(12) However, the technology disclosed in Patent Literature 1 is a technology for detecting an occurrence of a disaster such as a landslide, and the technology disclosed in Patent Literature 2 is a technology for detecting a change of a levee, such as damage thereto.

(13) Therefore, it is impossible to specify (i.e., measure or determine) the water level of a river by using the technologies disclosed in Patent Literatures 1 and 2.

(14) Therefore, an object of the present disclosure is to solve the above-described problem and to provide a specifying system, a specifying apparatus, and a specifying method capable of specifying the water level of a river.

Solution to Problem

(15) A specifying system according to an aspect includes: an optical fiber laid along a levee of a river; a communication unit configured to receive, from the optical fiber, an optical signal containing a pattern that changes according to a state of the levee; and a specifying unit configured to specify a water level of the river based on the pattern.

(16) A specifying apparatus according to an aspect includes: a communication unit configured to receive, from an optical fiber laid along a levee of a river, an optical signal containing a pattern that changes according to a state of the levee; and a specifying unit configured to specify a water level of the river based on the pattern.

(17) A specifying method according to an aspect is a specifying method performed by a specifying apparatus, including: a receiving step of receiving, from an optical fiber laid along a levee of a river, an optical signal containing a pattern that changes according to a state of the levee; and a specifying step of specifying a water level of the river based on the pattern.

Advantageous Effects of Invention

(18) According to the above-described aspect, an advantageous effect that it is possible to provide a specifying system, a specifying apparatus, and a specifying method capable of specifying the water level of a river is obtained.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 shows an example of an image of a specifying system according to a first example embodiment;
- (2) FIG. 2 shows an example of a configuration of the specifying system according to the first example embodiment;
- (3) FIG. 3 is a cross-sectional diagram showing an example of a levee in a normal state;
- (4) FIG. 4 is a cross-sectional diagram showing an example of the levee when the levee has been eroded due to overtopping of water of the river;
- (5) FIG. 5 is a cross-sectional diagram showing an example of the levee when the levee has been eroded due to overtopping of water of the river;
- (6) FIG. 6 shows an example of a vibration pattern contained in an optical signal received by a communication unit according to the first example embodiment;
- (7) FIG. 7 shows an example of a vibration pattern contained in an optical signal received by the communication unit according to the first example embodiment;
- (8) FIG. 8 shows an example of a vibration pattern contained in an optical signal received by the communication unit according to the first example embodiment;
- (9) FIG. 9 shows an example of a frequency characteristic of a vibration pattern contained in an optical signal received by the communication unit according to the first example embodiment;
- (10) FIG. 10 shows an example of a frequency characteristic of a vibration pattern contained in an optical signal received by the communication unit according to the first example embodiment;
- (11) FIG. 11 is a cross-sectional diagram showing an example of a levee when an optical fiber is exposed and inundated with water due to overtopping and erosion of the levee;
- (12) FIG. 12 is a cross-sectional diagram showing an example of a levee when an optical fiber is exposed and inundated with water due to overtopping and erosion of the levee;
- (13) FIG. 13 shows an example of a temperature pattern contained in an optical signal received by the communication unit according to the first example embodiment;
- (14) FIG. 14 shows an example of a temperature pattern contained in an optical signal received by the communication unit according to the first example embodiment;
- (15) FIG. 15 shows an example of the signal strength of an optical signal received by the communication unit according to the first example embodiment;
- (16) FIG. 16 shows an example of the signal strength of an optical signal received by the communication unit according to the first example embodiment;
- (17) FIG. 17 shows an example of an overall flow of operations performed by a specifying system according to the first example embodiment;
- (18) FIG. 18 shows an example of a configuration of a specifying system according to a second example embodiment;
- (19) FIG. 19 shows an example of a GUI screen that a reporting unit according to the second example embodiment displays in a specified terminal;
- (20) FIG. 20 shows an example of an overall flow of operations performed by a specifying system according to the second example embodiment;
- (21) FIG. 21 shows an example of a configuration of a specifying system according to a third example embodiment;
- (22) FIG. 22 shows an example of camera information held by a camera control unit according to the third example embodiment;
- (23) FIG. 23 shows an example of an overall flow of operations performed by a specifying system according to the third example embodiment;
- (24) FIG. 24 shows an example of an aspect in which an optical fiber and a camera are installed in

a specifying system according to a fourth example embodiment;

(25) FIG. 25 shows an example of an aspect in which an optical fiber and a camera are installed in the specifying system according to the fourth example embodiment;

(26) FIG. 26 is a cross-sectional diagram showing an example of a levee in which a camera is installed when an optical fiber is exposed and inundated with water due to overtopping and erosion of the levee;

(27) FIG. 27 is a cross-sectional diagram showing an example of a levee in which a camera is installed when an optical fiber is exposed and inundated with water due to overtopping and erosion of the levee;

(28) FIG. 28 shows an example of a configuration of a specifying system according to another example embodiment; and

(29) FIG. 29 is a block diagram showing an example of a hardware configuration of a computer that implements a specifying apparatus according to an example embodiment.

EXAMPLE EMBODIMENT

(30) An example embodiment according to the present disclosure will be described hereinafter with reference to the drawings. Note that the following descriptions and drawings are partially omitted and simplified as appropriate for clarifying the explanation. Further, the same reference numerals (or symbols) are assigned to the same components throughout the drawings, and duplicate descriptions thereof are omitted as appropriate.

First Example Embodiment

(31) Firstly, an example of an image of a specifying system according to a first example embodiment will be described with reference to FIG. 1.

(32) As shown in FIG. 1, the specifying system according to the first example embodiment includes an optical fiber 30 laid along a levee 20 of a river 10. In particular, the optical fiber 30 is buried inside the levee 20 and along the levee 20. Note that FIG. 1 shows a state in which water W of the river 10 has overtopped (i.e., has overflowed over) the levee 20 and flowed out onto a road running along the levee 20.

(33) Further, one end of the optical fiber 30 is connected to a sensing apparatus and the sensing apparatus 40 is connected to a specifying apparatus 50. The specifying apparatus 50 can be disposed in a place remote from the sensing apparatus 40, for example, in a cloud system.

(34) Next, an example of the configuration of the specifying system according to the first example embodiment will be described with reference to FIGS. 2 and 3. Note that FIGS. 2 and 3 show cross sections of the levee 20 in a normal state. In particular, FIG. 2 shows a cross section parallel to the river 10 and FIG. 3 shows a cross section perpendicular to the river 10.

(35) As shown in FIGS. 2 and 3, the specifying system according to the first example embodiment includes the optical fiber 30, the sensing apparatus 40, and the specifying apparatus 50 as described above. Further, the sensing apparatus includes a communication unit 41, and the specifying apparatus 50 includes a specifying unit 51.

(36) The communication unit 41 applies pulsed light to the optical fiber 30, and receives reflected light and/or scattered light, which are caused (or generated) as the pulsed light is transmitted through the optical fiber 30, as an optical signal through the optical fiber 30.

(37) Note that when the water level of the river 10 rises and overtopping occurs, the levee 20 vibrates. The vibrations are transmitted to the optical fiber and change the characteristics (e.g., the wavelength) of the optical signal transmitted through the optical fiber 30. Therefore, the optical fiber 30 can detect the vibrations that have occurred in the levee 20. Further, since the characteristics of the optical signal transmitted through the optical fiber 30 change according to the vibrations caused in the levee 20, the optical signal contains a vibration pattern that changes according to the state of the vibrations of the levee 20. This vibration pattern is a unique pattern having a different (i.e., unique) strength of vibrations, a different (i.e., unique) place where the vibrations occurred, a different (i.e., unique) transition of changes in frequency, and the like.

(38) Further, when the water level of the river **10** rises and hence overtopping occurs, the temperature of the levee **20** changes. This change in temperature is also transferred to the optical fiber **30**. Therefore, the optical signal transmitted through the optical fiber **30** also contains a temperature pattern that changes according to the temperature state of the levee **20**.

(39) Therefore, by analyzing the dynamic changes in the pattern that changes according to the vibration state or the temperature state of the levee **20**, contained in the optical signal received by the communication unit **41**, the specifying unit **51** can specify the rise of the water level of the river **10** and an occurrence of overtopping, i.e., can specify the water level of the river **10**.

(40) Therefore, the specifying unit **51** specifies the water level of the river **10** based on the pattern that changes according to the state (the vibration state or the temperature state) of the levee **20**, contained in the optical signal received by the communication unit **41**.

(41) An example of a method for specifying the water level of the river **10** performed in the specifying unit **51** will be described hereinafter.

(42) (1) First Method

(43) Firstly, a first method for specifying the water level of the river **10** will be described with reference to FIGS. **4** to **7**. The first method is an example in which, as shown in FIGS. **4** and **5**, the overtopping of the water **W** of the river **10** is specified (i.e., determined) when the levee **20** has been eroded due to the overtopping of the water **W** of the river **10**. Note that, in each of FIGS. **4** and **5**, a cross section of the levee **20** in a state in which the levee **20** has been eroded due to the overtopping is shown. In particular, FIG. **4** shows a cross section parallel to the river **10** and FIG. **5** shows a cross section perpendicular to the river **10**. Each of FIGS. **6** and **7** shows an example of a vibration pattern contained in the optical signal received by the communication unit **41**, in which the horizontal axis indicates the position on the levee **20** (i.e., the distance from the sensing apparatus **40**) and the vertical axis indicates the transition of the vibrations over time. For example, the movement of a vehicle or a pedestrian over time is represented by one diagonal line in each of FIGS. **6** and **7**. In particular, FIG. **6** shows an example of a vibration pattern when the levee **20** is normal, and FIG. **7** shows an example of a vibration pattern when the levee **20** is abnormal (an occurrence of erosion in this example).

(44) For example, the specifying unit **51** can specify, based on a time difference between a time when the communication unit **41** applied pulsed light to the optical fiber **30** and a time when the communication unit **41** received an optical signal from the optical fiber **30**, the position on the levee **20** (i.e., the distance from the sensing apparatus **40**) where a vibration pattern contained in the optical signal has occurred.

(45) As shown in FIG. **6**, when the levee **20** is normal, vibrations occur due to the movements of vehicles and pedestrians, but the sections (i.e., the durations) of such vibrations are narrow.

(46) In contrast to this, as shown in FIG. **7**, when erosion has occurred in the levee **20**, the section (i.e., the duration) of the vibrations is wide, indicating that the vibrations continuously occur over a long time.

(47) Therefore, in the example shown in FIG. **7**, the specifying unit **51** can determine that overtopping of the water **W** of the river **10** has occurred. Further, the specifying unit **51** can determine that a defect (erosion in this example) has occurred in the levee **20** based on the result of the above-described determination. Further, since the specifying unit **51** can specify the position on the levee **20** (i.e., the distance from the sensing apparatus **40**) where the vibration pattern contained in the optical signal has occurred as described above, it can specify the position on the levee **20** (i.e., the distance from the sensing apparatus **40**) where the defect has occurred.

(48) (2) Second Method

(49) Next, a second method for specifying the water level of the river **10** will be described referring to FIGS. **8** to **10**. Similarly to the first method, the second method is an example in which the overtopping of the water **W** of the river **10** is specified (i.e., determined) when the levee **20** has been eroded due to the overtopping of the water **W** of the river **10** (see, for example, FIGS. **4** and

5). FIG. 8 shows an example of a vibration pattern at a certain position on the levee 20, contained in the optical signal received by the communication unit 41, in which the horizontal axis indicates the time and the vertical axis indicates the strength of vibrations. Further, each of FIGS. 9 and 10 shows an example of frequency characteristics of a vibration pattern at a certain position on the levee 20, contained in the optical signal received by the communication unit 41, in which the horizontal axis indicates the time and the vertical axis indicates the strength of vibrations. In particular, FIG. 9 shows an example of a vibration pattern when the levee 20 is normal, and FIG. 10 shows an example of a vibration pattern when the levee 20 is abnormal (an occurrence of erosion in this example).

(50) There is a peak of the strength of vibrations in each of the vibration patterns shown in FIGS. 9 and 10. The magnitude of the peak of the strength of vibrations and the frequency at which the peak occurs change according to the state of the levee 20. Specifically, the magnitude of the peak of the strength of vibrations is large when erosion has occurred in the levee 20 (FIG. 10) as compared with when the levee 20 is normal (FIG. 9). Further, when erosion has occurred in the levee 20, the frequency at which the peak occurs has been shifted to the high frequency side from the peak that occurs when the levee 20 is normal.

(51) Therefore, the specifying unit 51 determines whether or not overtopping has occurred based on the magnitude of the peak of the strength of vibrations and the frequency at which the peak occurs. For example, the specifying unit 51 holds (i.e., stores) information about the magnitude of the peak of the strength of vibrations in the state where the levee 20 is normal (FIG. 9) and the frequency at which the peak occurs, and determines whether or not overtopping has occurred by a comparison with the held information.

(52) In the example shown in FIG. 10, the magnitude of the peak of the strength of vibrations is large as compared with the held information (the information shown in FIG. 9), and the frequency at which the peak occurs is shifted to the high frequency side. Therefore, the specifying unit 51 can determine that overtopping of the water W of the river 10 has occurred. Further, the specifying unit 51 can determine that a defect (erosion in this example) has occurred in the levee 20 based on the result of the above-described determination. Further, the specifying unit 51 can specify the position on the levee 20 (i.e., the distance from the sensing apparatus 40) where the defect has occurred.

(53) (3) Third Method

(54) Next, a third method for specifying the water level of the river 10 will be described with reference to FIGS. 11 to 14. As shown in FIGS. 11 and 12, the third method is an example in which when the levee 20 has been eroded due to the overtopping of the water W of the river 10, and the optical fiber 30 has been exposed and inundated with water due to the erosion of the levee 20, the overtopping of the river 10 is specified (i.e., determined). Note that, in each of FIGS. 11 and 12, a cross section of the levee 20 in a state in which the optical fiber 30 has been exposed and inundated with water due to the overtopping and the erosion of the levee 20 is shown. FIG. 11 shows a cross section parallel to the river 10 and FIG. 12 shows a cross section perpendicular to the river 10. Each of FIGS. 13 and 14 shows a temperature pattern contained in the optical signal received by the communication unit 41, in which the horizontal axis indicates the position on the levee 20 (i.e., the distance from the sensing apparatus 40) and the vertical axis indicates the temperature. In particular, FIG. 13 shows an example of a temperature pattern when the levee 20 is normal, and FIG. 14 shows an example of a temperature pattern when the levee 20 is abnormal (an occurrence of erosion in this example).

(55) As shown in FIG. 13, when the levee 20 is normal, changes in the temperature according to the position on the levee 20 (i.e., the distance from the sensing apparatus 40) is gentle.

(56) In contrast to this, as shown in FIG. 14, when erosion has occurred in the levee 20, a sudden change (a sudden drop) in the temperature occurs in the section where the erosion has occurred. It is presumed that this phenomenon has occurred because a part of the optical fiber 30 has been exposed and inundated with water due to the erosion.

(57) Therefore, in the example shown in FIG. 14, the specifying unit 51 can determine that the overtopping of the water W of the river 10 has occurred. Further, the specifying unit 51 can determine that a defect (erosion in this example) has occurred in the levee 20 based on the result of the above-described determination. Further, the specifying unit 51 can specify the position on the levee 20 (i.e., the distance from the sensing apparatus 40) where the defect has occurred.

(58) (4) Fourth Method

(59) Next, a fourth method for specifying the water level of the river 10 will be described referring to FIGS. 15 and 16. Similarly to the third method, the fourth method is an example in which when the levee 20 has been eroded due to the overtopping of the water W of the river 10, and the optical fiber 30 has been exposed and inundated with water due to the erosion of the levee 20 (see, for example, FIGS. 11 and 12), the overtopping of the river 10 is specified (i.e., determined). Each of FIGS. 15 and 16 shows the strength of the optical signal received by the communication unit 41, in which the horizontal axis indicates the position on the levee 20 (i.e., the distance from the sensing apparatus 40) and the vertical axis indicates the strength of the signal. In particular, FIG. 15 shows an example of the strength of the signal when the levee 20 is normal, and FIG. 16 shows an example of the strength of the signal when the levee 20 is abnormal (an occurrence of erosion in this example).

(60) As shown in FIG. 15, when the levee 20 is normal, changes in the strength of the optical signal according to the position on the levee 20 (i.e., the distance from the sensing apparatus 40) is gentle.

(61) In contrast to this, as shown in FIG. 16, when erosion has occurred on the levee 20, the strength of the optical signal has decreased in the section where the erosion has occurred. It is presumed that this phenomenon has occurred because a part of the optical fiber 30 has been exposed and inundated with water due to the erosion, and this part, which has been exposed and inundated with water, has been significantly bent due to the pressure of the water W, so that the loss of the optical signal has increased.

(62) Therefore, in the example shown in FIG. 16, the specifying unit 51 can determine that the overtopping of the water W of the river 10 has occurred. Further, the specifying unit 51 can determine that a defect (erosion in this example) has occurred in the levee 20 based on the result of the above-described determination. Further, the specifying unit 51 can specify the position on the levee 20 (i.e., the distance from the sensing apparatus 40) where the defect has occurred.

(63) Next, an example of an overall flow of operations performed by the specifying system according to the first example embodiment will be described with reference to FIG. 17.

(64) As shown in FIG. 17, the communication unit 41 receives an optical signal containing a pattern that changes according to the state of the levee 20 from the optical fiber 30 that is laid along the levee 20 of the river 10 (Step S11).

(65) Next, the specifying unit 51 specifies the rise of the water level of the river 10 and an occurrence of overtopping, i.e., specifies the water level of the river 10 based on the pattern that changes according to the state of the levee 20, contained in the optical signal received by the communication unit 41 (Step S12). This specifying process may be carried out, for example, by using any of the above-described first to fourth methods.

(66) As described above, according to the first example embodiment, the communication unit 41 receives an optical signal containing a pattern that changes according to the state of the levee 20 from the optical fiber 30 that is laid along the levee 20 of the river 10. The specifying unit 51 specifies the water level of the river 10 based on the pattern that changes according to the state of the levee 20, contained in the optical signal received by the communication unit 41. In this way, it is possible to specify the water level of the river 10.

(67) Further, the specifying unit 51 may specify a defect such as erosion of the levee 20 based on the water level of the river 10, and a place where the defect of the levee 20 has occurred based on the optical signal received by the communication unit 41. In this way, it is possible to specify a defect of the levee 20 caused by the water level of the river 10 as well as the water level of the river

10 itself, and also to specify the place where the defect of the levee **20** has occurred.

Second Example Embodiment

(68) Next, an example of a configuration of a specifying system according to a second example embodiment will be described with reference to FIG. **18**.

(69) As shown in FIG. **18**, the configuration of the specifying system according to the second example embodiment differs from that of the above-described first example embodiment in that the specifying apparatus **50** includes a reporting unit **52**.

(70) When the specifying unit **51** specifies a defect of the levee **20** and specifies the place where the defect of the levee **20** has occurred, the reporting unit **52** reports the occurrence of the defect of the levee **20** and the place where the defect has occurred to a predetermined terminal (not shown). The predetermined terminal is, for example, a terminal possessed by a monitoring staff present at the site or a terminal installed in a monitoring center. The reporting method may be, for example, a method in which a GUI (Graphical User Interface) screen (e.g., a GUI window) is displayed on a display, a monitor, or the like of the predetermined terminal, or may be a method in which a voice (or sound) message is output from a speaker of the predetermined terminal.

(71) For example, when the above-described reporting is performed by displaying a GUI screen, the reporting unit **52** operates as follows. The reporting unit **52** holds (i.e., stores) information indicating the place where the optical fiber **30** is laid and map information in association with each other in advance. When the specifying unit **51** specifies a defect of the levee **20** and the place where the defect has occurred, the reporting unit **52** displays, on a predetermined terminal, a GUI screen on which the defect occurrence place specified by the specifying unit **51** is superimposed on the map. FIG. **19** shows an example of the above-described GUI screen. On the GUI screen shown in FIG. **19**, the place where the optical fiber **30** is laid, a message indicating that overtopping may have occurred, and the place where the overtopping may have occurred are superimposed on the map.

(72) Next, an example of an overall flow of operations performed by the specifying system according to the second example embodiment will be described with reference to FIG. **20**.

(73) As shown in FIG. **20**, firstly, steps **S21** and **S22**, which are similar to the steps **S11** and **S12** shown in FIG. **17**, are performed.

(74) Next, the specifying unit **51** attempts to specify a defect such as erosion of the levee **20** based on the water level of the river **10** (Step **S23**).

(75) When the specifying unit **51** specifies a defect of the levee **20** in the step **S23** (Yes in Step **S23**), then, it specifies the place where the defect of the levee **20** has occurred based on the optical signal received by the communication unit **41** (Step **S24**).

(76) After that, the reporting unit **52** reports, to the predetermined terminal, the fact that the defect of the levee **20** has occurred and the place where the defect has occurred (Step **S25**). This reporting may be carried out, for example, by using a GUI screen like the one shown in FIG. **19**.

(77) As described above, according to the second example embodiment, when the specifying unit **51** specifies a defect of the levee **20** and the place where the defect has occurred, the reporting unit **52** reports, to the predetermined terminal, the fact that the defect of the levee **20** has occurred and the place where the defect has occurred. In this way, for example, it is possible to notify a monitoring staff or the like that the defect of the levee **20** has occurred and the place where the defect has occurred.

(78) Other effects are similar to those in the above-described first example embodiment.

Third Example Embodiment

(79) Next, an example of a configuration of a specifying system according to a third example embodiment will be described with reference to FIG. **21**. Note that FIG. **21** shows a cross section of the levee **20** in a normal state, parallel to the river **10**.

(80) As shown in FIG. **21**, the configuration of the specifying system according to the third example embodiment differs from that of the above-described first example embodiment in that it

includes a camera **60** and its specifying apparatus includes a camera control unit **53**.

(81) The camera **60** is a camera for monitoring the river **10**, and is implemented by, for example, a fixed camera, a PTZ (Pan Tilt Zoom) camera, or the like. The camera **60** has a function of wirelessly receiving a shooting instruction from the camera control unit **53**, a function of taking a video image according to the shooting instruction, and a function of wirelessly transmitting the taken camera video image to the camera control unit **53**. Note that the specifying system may include at least one camera **60**, and the number of cameras **60** is not limited to any particular number.

(82) As shown in FIG. **22**, the camera control unit **53** holds camera information indicating an identifier of the camera **60** and an area or the like where the camera can take an image. FIG. **22** is an example of the camera information when three cameras **60** are installed, and areas where the cameras can take an image is indicated by distances from the sensing apparatus **40**.

(83) When the specifying unit **51** specifies a defect of the levee **20** and specifies the place where the defect of the levee **20** has occurred, the camera control unit **53** selects a camera **60** that will photograph (or film) an area including the place where the defect has occurred based on the camera information like the one shown in FIG. **22**, and controls the selected camera **60** so as to photograph (or film) the place where the defect has occurred. For example, the camera control unit **53** wirelessly transmits, to the selected camera **60**, a shooting instruction specifying the angles (the azimuth and the elevation) of the camera **60** for photographing the place where the defect has occurred, the zoom magnification, and the like.

(84) Therefore, when the specifying unit **51** specifies a defect of the levee **20**, it can acquire a camera video image of the place where the defect of the levee **20** has occurred, so that it can specify details of the defect of the levee **20** (e.g., details, the extent, and the like of the defect) based on the camera video image.

(85) Next, an example of an overall flow of operations performed by the specifying system according to the third example embodiment will be described with reference to FIG. **23**.

(86) As shown in FIG. **23**, firstly, steps **S31** to **S34**, which are similar to the steps **S21** to **S24** shown in FIG. **21**, are performed.

(87) After that, the camera control unit **53** selects a camera **60** that will photograph an area including the place where the defect of the levee **20** has occurred and controls the selected camera **60** so as to photograph (or film) the place where the defect has occurred (Step **S35**).

(88) As described above, according to the third example embodiment, when the specifying unit **51** specifies a defect of the levee **20** and the place where the defect has occurred, the camera control unit **53** controls the camera **60** so as to photograph (or film) the place where the defect has occurred. In this way, the specifying unit **51** can specify details of the defect of the levee **20** (e.g., details, the extent, and the like of the defect) based on the camera video image.

(89) Note that although the third example embodiment has been described as a modified example of the above-described first example embodiment, it is not limited to such an example. The third example embodiment can also be a modified example of the above-described second example embodiment.

Fourth Example Embodiment

(90) In the above-described third example embodiment, it has been assumed that the optical fiber **30** is an optical fiber **30** that is exclusively used for the sensing and the camera **60** wirelessly transmits/receives a camera video image, a shooting instruction, and the like to/from the specifying apparatus **50**.

(91) In contrast, in a fourth example embodiment, the optical fiber **30** is an optical fiber that is used for both the communication and the sensing, and is connected to the camera **60**. Further, the camera **60** transmits/receives a camera video image, a shooting instruction, and the like to/from the specifying apparatus through the optical fiber **30** and the sensing apparatus **40**.

(92) Next, an example as to how the optical fiber **30** and the camera **60** in the specifying system

according to the fourth example embodiment are arranged will be described with reference to FIGS. 24 and 25. Note that FIGS. 24 and 25 show cross sections of the levee 20 in a normal state. In particular, FIG. 24 shows a cross section parallel to the river 10 and FIG. 25 shows a cross section perpendicular to the river 10.

(93) As shown in FIGS. 24 and 25, in the specifying system according to the fourth example embodiment, the camera(s) 60 is fixed to a pole(s), such as a telephone pole(s), present on the levee 20. Further, the optical fiber 30 is buried inside the levee 20. However, a part of the optical fiber 30 is branched off, and the branched part of the optical fiber 30 is connected to the camera 60.

(94) Note that the rest of the configuration of the specifying system according to the fourth example embodiment is similar to that of the above-described specifying system according to the third example embodiment, and therefore the description thereof is omitted.

(95) As described above, in the specifying system according to the fourth example embodiment, since a part of the optical fiber 30 is connected to the camera 60 fixed to the pole, the part of the optical fiber 30 is exposed at all times.

(96) Therefore, as shown in FIGS. 26 and 27, even when overtopping has occurred to such a degree that the levee 20 is slightly eroded, the optical fiber 30 is partially inundated with water and hence vibrations and/or changes in temperature occur in the water-inundated part. Note that FIGS. 26 and 27 show cross sections of the levee 20 when the optical fiber 30 has been inundated with water due to overtopping of the water W of the river 10 and slight erosion of the levee 20. FIG. 26 shows a cross section parallel to the river 10 and FIG. 27 shows a cross section perpendicular to the river 10.

(97) Further, even when overtopping has occurred to such a degree that the levee 20 is not eroded, the optical fiber 30 is partially inundated with water and hence vibrations and/or changes in temperature occur in the water-inundated part.

(98) Therefore, in the specifying system according to the fourth example embodiment, even when slight overtopping has occurred, the specifying unit 51 can specify the water level of the river 10 by using any of the above-described first to third methods.

(99) Note that the overall operation and other effects of the specifying system according to the fourth example embodiment are similar to those of the above-described specifying system according to the third example embodiment, and therefore the descriptions thereof are omitted.

Other Example Embodiment

(100) The communication unit 41 is separated from the specifying apparatus 50 in the above-described example embodiments, it is not limited to such an example. The communication unit 41 may be provided inside the specifying apparatus 50. FIG. 28 shows an example of a configuration of a specifying system in which the communication unit 41 is provided inside the specifying apparatus 50. Note that the specifying system shown in FIG. 28 may include a reporting unit 52 inside the specifying apparatus 50 as in the above-described second example embodiment, or may include a camera 60 and include a camera control unit 53 inside the specifying apparatus 50 as in the above-described third example embodiment. Alternatively or additionally, the optical fiber 30 may be connected to the camera 60 as in the above-described fourth example embodiment.

(101) <Hardware Configuration of Specifying Apparatus>

(102) Next, a hardware configuration of a computer 70 by which the specifying apparatus 50 is implemented will be described with reference to FIG. 29.

(103) As shown in FIG. 29, the computer 70 includes a processor 701, a memory 702, a storage 703, an input/output interface (input/output I/F) 704, a communication interface (communication I/F) 705, and the like. The processor 701, the memory 702, the storage 703, the input/output interface 704, and the communication interface 705 are connected to each other through data transmission paths for transmitting/receiving data to/from each other.

(104) The processor 701 is, for example, an arithmetic processing unit such as a CPU (Central Processing Unit) or a GPU (Graphics Processing Unit). The memory 702 is, for example, a

memory such as a RAM (Random Access Memory) or a ROM (Read Only Memory). The storage **703** is, for example, a storage device such as an HDD (Hard Disk Drive), an SSD (Solid State Drive), a memory card, or the like. Further, the storage **703** may be a memory such as a RAM or a ROM.

(105) The storage **703** stores programs for implementing the functions of the components included in the specifying apparatus **50**. The processor **701** implements each of the functions of the components included in the specifying apparatus **50** by executing a respective one of the programs. Note that when the processor **701** executes each of the above-described programs, it may execute the program after loading it into the memory **702** or may execute it without loading it into the memory **702**. Further, the memory **702** and the storage **703** also serve to store information and data held by the components included in the specifying apparatus **50**.

(106) Further, the above-described program may be stored in various types of non-transitory computer readable media and thereby supplied to computers (including the computer **70**). The non-transitory computer readable media includes various types of tangible storage media. Examples of the non-transitory computer readable media include a magnetic recording medium (such as a flexible disk, a magnetic tape, and a hard disk drive), a magneto-optic recording medium (such as a magneto-optic disk), a CD-ROM (Compact Disc-ROM), a CD-R (CD-Recordable), a CD-R/W (CD-ReWritable), and a semiconductor memory (such as a mask ROM, a PROM (Programmable ROM), an EPROM (Erasable PROM), a flash ROM, and a RAM). Further, the programs may be supplied to computers by using various types of transitory computer readable media. Examples of the transitory computer readable media include an electrical signal, an optical signal, and an electromagnetic wave. The transitory computer readable media can be used to supply programs to a computer through a wired communication line such as an electric wire and an optical fiber or a wireless communication line.

(107) The input/output interface **704** is connected to a display device **7041**, an input device **7042**, a sound (or voice) output device **7043**, and the like. The display device **7041** is a device, such as an LCD (Liquid Crystal Display), a CRT (Cathode Ray Tube) display, or a monitor, that displays a screen corresponding to drawing data processed by the processor **701**. The input device **7042** is a device that receives an operation input by an operator, such as a keyboard, a mouse, and a touch sensor, or the like. The display device **7041** and the input device **7042** may be integrated with each other and hence implemented as a touch panel. The sound output device **7043** is a device, such as a speaker, that outputs a sound (or a voice) corresponding to acoustic data processed by the processor **701**.

(108) The communication interface **705** transmits/receives data to/from an external apparatus. For example, the communication interface **705** communicates with an external apparatus through a wired or wireless communication path.

(109) Although the present disclosure is described above with reference to example embodiments, the present disclosure is not limited to the above-described example embodiments. Various modifications that can be understood by those skilled in the art can be made to the configuration and details of the present disclosure within the scope of the disclosure.

(110) For example, the above-described example embodiments may be used while combining the whole or parts of two or more example embodiments with each other.

(111) Further, the whole or part of the embodiments disclosed above can be described as, but not limited to, the following supplementary notes.

(112) (Supplementary Note 1)

(113) A specifying system comprising: an optical fiber laid along a levee of a river; a communication unit configured to receive, from the optical fiber, an optical signal containing a pattern that changes according to a state of the levee; and a specifying unit configured to specify a water level of the river based on the pattern.

(Supplementary Note 2)

(114) The specifying system described in Supplementary note 1, wherein the specifying unit specifies the water level of the river based on a pattern that changes according to a vibration state or a temperature state of the levee, contained in the optical signal.

(115) (Supplementary Note 3)

(116) The specifying system described in Supplementary note 1 or 2, wherein the specifying unit specifies a defect of the levee based on a strength of the optical signal and specifies a place where the defect of the levee has occurred based on the optical signal.

(117) (Supplementary Note 4)

(118) The specifying system described in Supplementary note 1 or 2, wherein the specifying unit specifies a defect of the levee based on the water level of the river and specifies a place where the defect of the levee has occurred based on the optical signal.

(119) (Supplementary Note 5)

(120) The specifying system described in Supplementary note 3 or 4, further comprising: a camera configured to monitor the river; and a camera control unit configured to control the camera so as to photograph the place where the defect of the levee has occurred.

(Supplementary Note 6)

(121) A specifying apparatus comprising: a communication unit configured to receive, from an optical fiber laid along a levee of a river, an optical signal containing a pattern that changes according to a state of the levee; and a specifying unit configured to specify a water level of the river based on the pattern.

(Supplementary Note 7)

(122) The specifying apparatus described in Supplementary note 6, wherein the specifying unit specifies the water level of the river based on a pattern that changes according to a vibration state or a temperature state of the levee, contained in the optical signal.

(123) (Supplementary Note 8)

(124) The specifying apparatus described in Supplementary note 6 or 7, wherein the specifying unit specifies a defect of the levee based on a strength of the optical signal, and specifies a place where the defect of the levee has occurred based on the optical signal.

(125) (Supplementary Note 9)

(126) The specifying apparatus described in Supplementary note 6 or 7, wherein the specifying unit specifies a defect of the levee based on the water level of the river, and specifies a place where the defect of the levee has occurred based on the optical signal.

(127) (Supplementary Note 10)

(128) The specifying apparatus described in Supplementary note 8 or 9, further comprising a camera control unit configured to control a camera configured to monitor the river so that the camera photographs the place where the defect of the levee has occurred.

(129) (Supplementary Note 11)

(130) A specifying method performed by a specifying apparatus, comprising: a receiving step of receiving, from an optical fiber laid along a levee of a river, an optical signal containing a pattern that changes according to a state of the levee; and a specifying step of specifying a water level of the river based on the pattern.

(Supplementary Note 12)

(131) The specifying method described in Supplementary note 11, wherein in the specifying step, the water level of the river is specified based on a pattern that changes according to a vibration state or a temperature state of the levee, contained in the optical signal.

(132) (Supplementary Note 13)

(133) The specifying method described in Supplementary note 11 or 12, wherein in the specifying step, a defect of the levee is specified based on a strength of the optical signal, and a place where the defect of the levee has occurred is specified based on the optical signal.

(134) (Supplementary Note 14)

(135) The specifying method described in Supplementary note 11 or 12, wherein in the specifying step, a defect of the levee is specified based on the water level of the river, and a place where the defect of the levee has occurred is specified based on the optical signal.

(136) (Supplementary Note 15)

(137) The specifying method described in Supplementary note 13 or 14, further comprising a step of controlling a camera configured to monitor the river so that the camera photographs the place where the defect of the levee has occurred.

REFERENCE SIGNS LIST

(138) **10 RIVER 20 LEVEE 30 OPTICAL FIBER 40 SENSING APPARATUS 41 COMMUNICATION UNIT 50 SPECIFYING APPARATUS 51 SPECIFYING UNIT 52 REPORTING UNIT 53 CAMERA CONTROL UNIT 60 CAMERA 70 COMPUTER 701 PROCESSOR 702 MEMORY 703 STORAGE 704 INPUT/OUTPUT INTERFACE 7041 DISPLAY DEVICE 7042 INPUT DEVICE 7043 SOUND OUTPUT DEVICE 705 COMMUNICATION INTERFACE W WATER**

Claims

1. A specifying system comprising: an optical fiber laid along a levee of a river; at least one memory storing instructions; and at least one processor configured to execute the instructions to: receive, from the optical fiber, an optical signal containing a pattern that changes according to a state of the levee; specify a water level of the river based on the pattern; and specify the water level of the river based on a pattern that changes according to a vibration state or a temperature state of the levee, contained in the optical signal.
2. The specifying system according to claim 1, wherein the at least one processor is further configured to execute the instructions to specify a defect of the levee based on a strength of the optical signal and specify a place where the defect of the levee has occurred based on the optical signal.
3. The specifying system according to claim 1, wherein the at least one processor is further configured to execute the instructions to specify a defect of the levee based on the water level of the river and specify a place where the defect of the levee has occurred based on the optical signal.
4. The specifying system according to claim 2, further comprising: a camera configured to monitor the river, wherein the at least one processor is further configured to execute the instructions to control the camera to photograph the place where the defect of the levee has occurred.
5. A specifying apparatus comprising: at least one memory storing instructions, and at least one processor configured to execute the instructions to: receive, from an optical fiber laid along a levee of a river, an optical signal containing a pattern that changes according to a state of the levee; specify a water level of the river based on the pattern; and specify the water level of the river based on a pattern that changes according to a vibration state or a temperature state of the levee, contained in the optical signal.
6. The specifying apparatus according to claim 5, wherein the at least one processor is further configured to execute the instructions to specify a defect of the levee based on a strength of the optical signal, and specify a place where the defect of the levee has occurred based on the optical signal.
7. The specifying apparatus according to claim 5, wherein the at least one processor is further configured to execute the instructions to specify a defect of the levee based on the water level of the river, and specify a place where the defect of the levee has occurred based on the optical signal.
8. The specifying apparatus according to claim 6, wherein the at least one processor is further configured to execute the instructions to control a camera, configured to monitor the river, to photograph the place where the defect of the levee has occurred.
9. A specifying method performed by a specifying apparatus, comprising: receiving, from an

optical fiber laid along a levee of a river, an optical signal containing a pattern that changes according to a state of the levee; and specifying a water level of the river based on the pattern, wherein the water level of the river is specified based on a pattern that changes according to a vibration state or a temperature state of the levee, contained in the optical signal.

10. The specifying method according to claim 9, wherein a defect of the levee is specified based on a strength of the optical signal, and a place where the defect of the levee has occurred is specified based on the optical signal.

11. The specifying method according to claim 9, wherein a defect of the levee is specified based on the water level of the river, and a place where the defect of the levee has occurred is specified based on the optical signal.

12. The specifying method according to claim 10, further comprising controlling a camera, configured to monitor the river, to photograph the place where the defect of the levee has occurred.
