

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417117
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Morgan; Tucker B. et al.

Automatic determination of application state in a multi-user environment

Abstract

A state of a multi-user communication session is saved in response to detection of an application state saving event, or a session state saving event. During runtime, application state saving events may be detected for each application executing during a session. Application state parameters are saved in response to each application state saving event, from which the application may be launched to the saved state. In response to a state saving event, the most recent application state information for each application executing in the session are collected and stored such that the multi-user communication session may be launched to the saved state, including each application executing in the session.

Inventors: Morgan; Tucker B. (Sunnyvale, CA), Deliz Centeno; Luis R. (Fremont, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008819870

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/061199

Filed: December 02, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230315509 A1	Oct. 05, 2023

Related U.S. Application Data

continuation parent-doc US 17998422 ABANDONED WO PCT/US2021/029398 20210427 child-doc US 18061199
us-provisional-application US 63022967 20200511

Publication Classification

Int. Cl.: G06F9/46 (20060101); G06F9/54 (20060101); H04L65/401 (20220101)

U.S. Cl.:

CPC G06F9/461 (20130101); G06F9/542 (20130101); H04L65/4015 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10304252	12/2018	Tadros	N/A	N/A
2005/0071760	12/2004	Jaeger	715/705	G06F 9/453
2011/0265099	12/2010	Tobe	719/314	G06F 9/542
2013/0218315	12/2012	Jaeger	700/94	G06F 3/16
2014/0366038	12/2013	Mckeown	N/A	N/A
2018/0061132	12/2017	Lanier	N/A	N/A
2018/0121054	12/2017	Van Wie	N/A	N/A
2018/0359448	12/2017	Harries	N/A	N/A
2019/0310757	12/2018	Lee	N/A	N/A

OTHER PUBLICATIONS

Feick, et al., "Mixed-Reality for Object-Focused Remote Collaboration," UIST '18 Adjunct, Oct. 14-17, 2018. cited by applicant

Teo, et al., "Investigating the use of Different Visual Cues to Improve Social Presence within a 360 Mixed Reality Remote Collaboration," The 17th International Conference on Virtual-Reality Continuum and its Applications in Industry, Nov. 2019. cited by applicant

Primary Examiner: Dorais; Craig C

Attorney, Agent or Firm: Blank Rome LLP

Background/Summary

BACKGROUND

(1) This disclosure relates generally to image processing. More particularly, but not by way of limitation, this disclosure relates to techniques and systems for automatically determining application state in a multi-user communication session.

(2) Some devices are capable of generating and presenting extended reality (XR) environments. An XR environment may include a wholly or partially simulated environment that people sense and/or interact with via an electronic system. In XR, a subset of a person's physical motions, or representations thereof, are tracked, and, in response, one or more characteristics of one or more

virtual objects simulated in the XR environment are adjusted in a manner that comports with at least one law of physics. Some XR environments allow multiple users to interact with each other within the EX environment. However, when an XR environment is initiated, what is needed is an improved technique for determining a saved state of an application or a session.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows, in block diagram form, exemplary systems for use in various extended reality technologies according to one or more embodiments.
- (2) FIG. 2 shows a diagram of example operating environments, according to one or more embodiments.
- (3) FIG. 3 shows a flowchart of a method for collecting session state data, according to one or more embodiments.
- (4) FIG. 4 shows a flowchart for initiating a multi-user communication session in accordance with saved state information, according to one or more embodiments.
- (5) FIG. 5 shows an example timing diagram of a technique for saving state information for a session state saving event, in accordance with one or more embodiments.
- (6) FIGS. 6A and 6B show, in block diagram form, exemplary systems for use in various extended reality technologies according to one or more embodiments.

DETAILED DESCRIPTION

- (7) This disclosure pertains to systems, methods, and computer readable media to save state information for a multi-user communication session in which multiple user devices are active in a single session. According to one or more embodiments, state information for applications running in a multi-user communication session may be stored from time to time. A session may include multiple applications which may be utilized by the participants. The applications executing within the multi-user communication session may save application state information from time to time, which may be utilized by a device to re-launch the particular application to the saved state. Session state information may be collected stored based on a latest saved state information for each of the applications executing within the multi-user communication session, as well as additional session state information.
- (8) A person can interact with and/or sense a physical environment or physical world without the aid of an electronic device. A physical environment can include physical features, such as a physical object or surface. An example of a physical environment is physical forest that includes physical plants and animals. A person can directly sense and/or interact with a physical environment through various means, such as hearing, sight, taste, touch, and smell. In contrast, a person can use an electronic device to interact with and/or sense an extended reality (XR) environment that is wholly or partially simulated. The XR environment can include mixed reality (MR) content, augmented reality (AR) content, virtual reality (VR) content, and/or the like. With an XR system, some of a person's physical motions, or representations thereof, can be tracked and, in response, characteristics of virtual objects simulated in the XR environment can be adjusted in a manner that complies with at least one law of physics. For instance, the XR system can detect the movement of a user's head and adjust graphical content and auditory content presented to the user similar to how such views and sounds would change in a physical environment. In another example, the XR system can detect movement of an electronic device that presents the XR environment (e.g., a mobile phone, tablet, laptop, or the like) and adjust graphical content and auditory content presented to the user similar to how such views and sounds would change in a physical environment. In some situations, the XR system can adjust characteristic(s) of graphical content in response to other inputs, such as a representation of a physical motion (e.g., a vocal

command).

(9) Many different types of electronic systems can enable a user to interact with and/or sense an XR environment. A non-exclusive list of examples include heads-up displays (HUDs), head mountable systems, projection-based systems, windows or vehicle windshields having integrated display capability, displays formed as lenses to be placed on users' eyes (e.g., contact lenses), headphones/earphones, input systems with or without haptic feedback (e.g., wearable or handheld controllers), speaker arrays, smartphones, tablets, and desktop/laptop computers. A head mountable system can have one or more speaker(s) and an opaque display. Other head mountable systems can be configured to accept an opaque external display (e.g., a smartphone). The head mountable system can include one or more image sensors to capture images/video of the physical environment and/or one or more microphones to capture audio of the physical environment. A head mountable system may have a transparent or translucent display, rather than an opaque display. The transparent or translucent display can have a medium through which light is directed to a user's eyes. The display may utilize various display technologies, such as uLEDs, OLEDs, LEDs, liquid crystal on silicon, laser scanning light source, digital light projection, or combinations thereof. An optical waveguide, an optical reflector, a hologram medium, an optical combiner, combinations thereof, or other similar technologies can be used for the medium. In some implementations, the transparent or translucent display can be selectively controlled to become opaque. Projection-based systems can utilize retinal projection technology that projects images onto users' retinas. Projection systems can also project virtual objects into the physical environment (e.g., as a hologram or onto a physical surface).

(10) For purposes of this disclosure, a multi-user communication session can include a communication session in which two or more devices are participating in an XR environment.

(11) For purposes of this disclosure, a local multi-user communication device refers to a current device being described, or being controlled by a user being described, in a multi-user communication session.

(12) For purposes of this disclosure, colocated multi-user communication devices refer to two devices that share a physical environment and an XR environment, such that the users of the colocated devices may experience the same physical objects and ER objects.

(13) For purposes of this disclosure, a remote multi-user communication device refers to a secondary device that is located in a separate physical environment from a current, local multi-user communication device. In one or more embodiments, the remote multi-user communication device may be a participant in the multi-user communication session.

(14) For purposes of this disclosure, shared virtual elements refer to XR objects that are visible or otherwise able to be experienced by participants in a common XR session.

(15) In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed concepts. As part of this description, some of this disclosure's drawings represent structures and devices in block diagram form in order to avoid obscuring the novel aspects of the disclosed concepts. In the interest of clarity, not all features of an actual implementation may be described. Further, as part of this description, some of this disclosure's drawings may be provided in the form of flowcharts. The boxes in any particular flowchart may be presented in a particular order. It should be understood however that the particular sequence of any given flowchart is used only to exemplify one embodiment. In other embodiments, any of the various elements depicted in the flowchart may be deleted, or the illustrated sequence of operations may be performed in a different order, or even concurrently. In addition, other embodiments may include additional steps not depicted as part of the flowchart. Moreover, the language used in this disclosure has been principally selected for readability and instructional purposes, and may not have been selected to delineate or circumscribe the inventive subject matter, resort to the claims being necessary to determine such inventive subject matter. Reference in this disclosure to "one embodiment" or to "an embodiment" means

that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the disclosed subject matter, and multiple references to “one embodiment” or “an embodiment” should not be understood as necessarily all referring to the same embodiment.

(16) It will be appreciated that in the development of any actual implementation (as in any software and/or hardware development project), numerous decisions must be made to achieve a developers' specific goals (e.g., compliance with system- and business-related constraints), and that these goals may vary from one implementation to another. It will also be appreciated that such development efforts might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the design and implementation of graphics modeling systems having the benefit of this disclosure.

(17) Referring to FIG. 1, a simplified block diagram of an electronic device **100** is depicted, communicably connected to additional electronic devices **110** and a network storage **115** over a network **105**, in accordance with one or more embodiments of the disclosure. Electronic device **100** may be part of a multifunctional device, such as a mobile phone, tablet computer, personal digital assistant, portable music/video player, wearable device, head-mounted systems, projection-based systems, base station, laptop computer, desktop computer, network device, or any other electronic systems such as those described herein. Electronic device **100**, additional electronic device **110**, and/or network storage **115** may additionally, or alternatively, include one or more additional devices within which the various functionality may be contained, or across which the various functionality may be distributed, such as server devices, base stations, accessory devices, and the like. Illustrative networks, such as network **105** include, but are not limited to, a local network such as a universal serial bus (USB) network, an organization's local area network, and a wide area network such as the Internet. According to one or more embodiments, electronic device **100** is utilized to participate in a multi-user communication session in an XR environment. It should be understood that the various components and functionality within electronic device **100**, additional electronic device **110** and network storage **115** may be differently distributed across the devices, or may be distributed across additional devices.

(18) Electronic Device **100** may include one or more processors **125**, such as a central processing unit (CPU). Processor(s) **125** may include a system-on-chip such as those found in mobile devices and include one or more dedicated graphics processing units (GPUs). Further, processor(s) **125** may include multiple processors of the same or different type. Electronic device **100** may also include a memory **135**. Memory **135** may include one or more different types of memory, which may be used for performing device functions in conjunction with processor(s) **125**. For example, memory **135** may include cache, ROM, RAM, or any kind of transitory or non-transitory computer readable storage medium capable of storing computer readable code. Memory **135** may store various programming modules for execution by processor(s) **125**, including XR module **165**, state tracking module **170**, and other various applications **175**. Electronic device **100** may also include storage **130**. Storage **130** may include one more non-transitory computer-readable mediums including, for example, magnetic disks (fixed, floppy, and removable) and tape, optical media such as CD-ROMs and digital video disks (DVDs), and semiconductor memory devices such as Electrically Programmable Read-Only Memory (EPROM), and Electrically Erasable Programmable Read-Only Memory (EEPROM). Storage **130** may be configured to store state tracking data **160**, according to one or more embodiments. Electronic device may additionally include network interface **150**, from which additional network components may be accessed via network **105**.

(19) Electronic device **100** may also include one or more cameras **141**) or other sensors **145**, such as depth sensor, from which depth or other characteristic of an environment may be determined. In one or more embodiments, each of the one or more cameras **140** may be a traditional RGB camera, or a depth camera. Further, cameras **140** may include a stereo- or other multi-camera system, a

time-of-flight camera system, or the like. Electronic device **100** may also include a display **155**. The display device **155** may utilize digital light projection, OLEDs, LEDs, uLEDs, liquid crystal on silicon, laser scanning light source, or any combination of these technologies. Display device **155** may be utilized to present a representation of a multi-user communication session, including shared virtual elements within the multi-user communication session and other ER objects.

(20) Storage **130** may be utilized to store various data and structures which may be utilized for providing state information in order to track an application and session state. Storage **130** may include, for example, state tracking data store **160**. State tracking data store may be utilized to store state information for applications, such as applications **175**, and/or multi-user communication sessions, in which multiple applications may execute. In accordance with one or more embodiments, the state tracking data store **160** may store state information from which an application and/or session may resume upon initialization.

(21) According to one or more embodiments, memory **135** may include one or more modules that comprise computer readable code executable by the processor(s) **125** to perform functions. The memory may include, for example an XR module **165** which may be used to provide a multi-user communication session in an XR environment. The multi-user communication session XR environment may be a computing environment which supports a shared experience by electronic device **100** as well as additional electronic devices **110** within a multiuser communication session. In one or more embodiments, application state data may be stored occasionally, periodically, or in response to a trigger, such as an application state saving event, or a request from another module or device. In one or more embodiments, session state information may also be stored in state tracking data store **160**. In one or more embodiments, session state information may include data required to boot an XR environment to a particular state. In one or more embodiments, the session state information may include application state information for all applications running at the time the state is stored. Additionally, or alternatively, the session state information may include a reference to application state information which should be obtained in order to reboot the multi-user communication session to a particular state. In one or more embodiments, the state information may be stored locally at each system, such as electronic device **100** and additional electronic devices **110**, and/or the state information may be stored in global state tracking data store **120** as part of network storage **115**.

(22) The state tracking module **170** may detect when state should be captured on a periodic basis, based on user input, or based on automatic trigger, such as by detecting an application state saving event or a session state saving event, as will be described in greater detail below. Applications **175** may include, for example, computer applications that may be experienced in an XR environment by multiple devices, such as electronic device **100** and additional electronic devices **110**. In one or more embodiments, the applications **175** may respond to a request for state information from state tracking module **170** by providing state information which will allow each application to boot to a particular state.

(23) State tracking data store **160** may include various types of state information. For example, state tracking data store **160** may include application state information for the various applications **175**, which may be captured by the state tracking module **170** in response to an application state saving event. The application state information may include information from which a device can re-launch the application to a given state. State tracking data store **160** may also store session state information. Session state information may include an aggregate of application state information that is pre-stored or that is obtained at the time of a session state saving event for a particular multi-user communication session. In one or more embodiments, the session state information may be stored in association with session parameters, which may provide context as to what state the state information refers. As an example, session parameters may include day, time, identity or other information regarding active users or devices in the application or session, physical location of one or more of the users or devices during the session, security parameters, and the like. Session state

information may include additional information, such as a particular configuration of applications, user preferences, and the like.

(24) According to one or more embodiments, data stored as state information may be utilized to determine how one or more applications or sessions are re-launched. As an example, geometric information or other characteristics about one or more physical environments in which virtual objects are presented within an application may be stored to determine how the virtual objects should be presented upon re-launch. As an example, state information may include information regarding physical objects or surfaces with which virtual objects are interfacing. As an example, a virtual object displayed to appear to be sitting on a physical table may require state information that includes information regarding the table, such as a plane, dimensions of the table, location of the table in the environment, and the like. Accordingly, a state tracking module **170** may determine where to place the virtual object upon re-launch. In one or more embodiments, if upon relaunch, the physical surface or object has moved, or if the device is determined to be in a different physical environment, then an alternative physical surface may be found, or a virtual surface may be generated and presented to replace the original surface.

(25) Although electronic device **100** is depicted as comprising the numerous components described above, in one or more embodiments, the various components may be distributed across multiple devices. Accordingly, although certain calls and transmissions are described herein with respect to the particular systems as depicted, in one or more embodiments, the various calls and transmissions may be made differently directed based on the differently distributed functionality. Further, additional components may be used, some combination of the functionality of any of the components may be combined.

(26) FIG. 2 shows a diagram of example operating environments, according to one or more embodiments. While pertinent features are shown, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity and so as not to obscure more pertinent aspects of the example among implementations disclosed herein. To that end, as a nonlimiting example, the operating environment **240** includes a first physical environment, whereas operating environment **250** includes a second physical environment.

(27) As shown in FIG. 2, the first environment **240** includes a first user **220** that is utilizing a first electronic device **200**, and the second environment **250** includes a second user **232** that is utilizing a second electronic device **210**. In one or more embodiments, the first electronic device **200** and the second electronic device **210** include mobile devices, such as handheld devices, wearable devices, and the like.

(28) In one or more embodiments the first electronic device **200** and the second electronic device **210** communicate with each other via a network **205**. Examples of network **205** may include, for example, the Internet, a wide area network (WAN), a local area network (LAN), etc. In one or more embodiments, the first electronic device **200** and the second electronic device **210** may be participating in a common multi-user communication session in an ER environment.

(29) Although electronic device **200** and electronic device **210** may be participating in a common multi-user communication session, the XR environment may be presented differently on each device. As shown, the electronic device **200** may depict physical objects of the environment **240**. As shown, physical table **222** may be depicted on the display **242** as a virtual table **224**. In one or more embodiments, the display **242** may be a see-through display, and virtual table **224** may simply be a view of physical table **222** through display **242**. As another example, the table or other surfaces may be presented in the form of a virtual surface, such as a plane. Dimensions of the physical object may be detected and saved, for example, as state information, without storing details about the specific table. In one or more embodiments, a privacy protecting abstraction layer may be applied by obtaining and storing limited information about real objects in a real environment.

(30) Display **242** of electronic device **200** may also include an avatar **226** corresponding to user **232**. For purposes of this disclosure, an avatar may include a virtual representation of a user. The avatar may depict real-time actions of the corresponding user **232**, including movement, updated location, and/or interactions with various physical components and/or virtual components within the multi-user communication session XR environment. An avatar may or may not mimic physical characteristics of the user, and may or may not mimic facial expressions of the user.

(31) According to one or more embodiments, a multi-user communication session may support one or more multi-user communication applications or other modules which allow for depictions of shared virtual objects across all participating devices within a multi-user communication session, such as electronic device **200** and electronic device **210**. As shown in display **242**, presentation panel **230A** is an example of a shared virtual object which may be visible to all participating devices.

(32) As an example, returning to environment **250**, electronic device **210** includes a display **252**, on which the presentation panel virtual object **230B** is depicted. It should be understood that in one or more embodiments, although the same XR object may be visible across all participating devices, the XR object may be rendered differently according to the location of the electronic device, the orientation of the electronic device, or other physical or virtual characteristics associated with electronic devices **200** and **210** and/or the multi-user communication session for which a representation is presented within displays **242** and **252**.

(33) Returning to environment **250**, physical chair **234** is depicted as virtual chair **236**. As described above, and in one or more embodiments, display **252** may be a see-through display, and virtual chair **236** may be a view of physical chair **234** through the see-through display **252**. In addition, electronic device **210** depicts an avatar **238** corresponding to user **220**. Another characteristic of a multi-user communication session XR environment is that while virtual objects may be shared across participating devices, physical worlds may appear different. For instance, the XR environment depicted in display **242** includes presentation panel **230A** that also appears in the XR environment depicted in display **252**. However, the XR environment depicted in display **242** includes virtual table **224** which is a representation of physical table **222**, which is not included in the XR environment depicted in display **252**. Similarly, the XR environment depicted in display **252** includes representation **236** of physical chair **234**, which is not included in the XR environment depicted in display **242**.

(34) According to one or more embodiments, the shared virtual objects, such as presentation panel **230**, may be rendered as part of an application. In one or more embodiments, multiple applications may be executed within the multi-user communication session XR environment depicted in **242** and **252**.

(35) FIG. **3** shows a flowchart of a method for saving application and session state, according to one or more embodiments. For purposes of explanation, the flowchart is described utilizing example components from FIG. **1**. Although the flowchart shows various procedures performed by particular components in a particular order, it should be understood that according to one or more embodiments, the various processes may be performed by alternative devices or modules. In addition, the various processes may be performed in an alternative order, and various combinations of the processes may be performed simultaneously. Further, according to some embodiments, one or more of the processes may be omitted, or others may be added.

(36) The flowchart begins at **305** where the XR module **165** presents a representation of a first multi-user communication session for a first device in the multiuser communication session with a second device. In one or more embodiments, presenting the representation of the multi-user communication session may include presenting an XR environment that includes avatar representations of active users, a set of shared virtual objects that are visible to one or more devices active within the session, or the like.

(37) The flowchart continues at block **310**, where the state tracking module **170** monitors

application and session events. According to some embodiments, the communication session may include the execution of one or more applications. Each application may be associated with particular state saving events, which may be application-specific, session-specific, or the like, according to one or more embodiments. An application state saving event may include a particular event or combination of characteristics that trigger state information to be stored such that the application can be relaunched to a state consistent with the stored state. As such, an application state saving event may include events specific to the application, such as reaching a particular point of execution in the application, a predetermined periodic trigger at which point state information should be stored, an identification of a particular configuration of the application, or the like. Further, in one or more embodiments, the application state saving event may be associated with external parameters which may comprise the application state saving event. As an example, the application state saving event may include a particular physical location in which a device is located during execution of the application, a combination of active users utilizing an application in a multiuser communication session, an indication of one or more additional applications executing within the multiuser communication session concurrently with the application, and the like.

(38) The flowchart continues at **315**, where a determination is made as to whether an application state saving event is detected. If an application state saving event is detected, then the flowchart continues to block **320**, where the state tracking module **170** stores application information associated with the application state saving event. The application state information may include data which, when provided to the application, allow the application to relaunch to the saved state. In one or more embodiments, the application state information may also be associated with an identifier that may be utilized to reference the state information later. Application state information may include, for example, geometric information regarding a physical environment in which the multi-user communication session is running, such as surfaces or other portions of the physical environment which affect the display of the placement of virtual objects. State information may include other data, such as users that are participating in the application and/or in the session, menus that are opened or closed, a time and/or date when the application was opened or closed, and the like. According to one or more embodiments, the application state information may be stored in association with the application state saving event that caused the application state information to be obtained. According to one or more embodiments, the stored application state information may be reference with a particular application state saving event in accordance with the association. Once the state information is stored, the flowchart continues at block **310**, where the state tracking module **170** continues to monitor application and session events.

(39) Returning to **310**, the flowchart also continues at **325**, where determination is made regarding whether session state saving events are detected. According to one or more embodiments, session state saving events may be specific to a particular multiuser communication session. As an example, a session state saving event may include a change in a combination of users or devices that are active within the session, a change in a physical location of one or more of the users or devices active within the session, termination of the multi-user communication session, and the like. As another example, the session state saving event may be intrinsic to the session. For example, a particular multiuser communication session may be associated with a predetermined time period after which state information should be stored. As another example, a change in combination of applications executing within the session may indicate a session state saving event. The flowchart returns to block **310** and the session is monitored until a determination is made at block **325** that a session state saving event is detected.

(40) If the session state saving event is detected at **325**, then the flowchart continues to block **330**. At block **330**, the state tracking module **170** aggregates current application state parameters to generate session state data. In one or more embodiments, the current application state information may be obtained from the most recently stored application state data at block **320** for each application executing in the multiuser communication session. In one or more embodiments, the

state tracking module **170** may request application state information from each application executing in a multiuser communication session in response to the session state saving event at block **325**.

(41) The flowchart concludes at **340**, where the state tracking module **170** stores the aggregated application state information in association with the session state saving event. In one or more embodiments, the session state information may include the aggregated application state information from which the application state information may be obtained.

(42) FIG. **4** depicts a flowchart of a technique for launching a multi-user communication session into a particular state. For purposes of clarity, the description of the various processes will be described in relation to the components described in FIG. **1**.

(43) The flowchart begins at **405**, where the state tracking module **170** detects initiation of a second session of the multi-user communication XR environment for a multiuser communication session. According to one or more embodiments, the initiation of the second session may be detected in response to the electronic device **100** booting up, electronic device **100** initiating the XR module **165**, as well as changes to a context of an ongoing multi-user communication session which effectively changes the state parameters. As an example, if an initiation of a second session may be detected a combination of the users active in the multi-user communication session changes, a physical location changes in which the XR environment is presented, a combination of applications that are active within the multi-user communication session, and the like.

(44) The flowchart continues at **410**, where the state tracking module **170** determines a session context. In one or more embodiments, the session context may include various characteristics of the multi-user communication session, or the computational environment or physical environment in which the multi-user communication session is presented. In addition, in one or more embodiments, the session context may also include such contextual information as time of day, day of the week, active applications, and the like. In one or more embodiments, the system context may also be determined in accordance with other data provided by electronic device **100**, such as a calendar entry, and the like.

(45) At block **415**, the state tracking module **170** identifies session parameters for the second session in accordance with the determined session context. As described above, the session parameters may include identifying information for the session from which a determination may be made as to which state the session should be launched.

(46) The flowchart continues at block **420**, where the state tracking module **170** identifies a saved session state based on the identified session parameters for the second session. As described above, state information may be stored in state tracking data store **160**, global state tracking data store **120**, or the like. In one or more embodiments, state information for a session may be stored in accordance with session parameters which characterize the session. As such, the identified session parameters for the second session may be utilized to identify an appropriate state to which the session should be launched. Accordingly, the state information for the identified saved session state may be obtained from the state tracking data store **160** or the global state tracking data store **120** in accordance with the identified session parameters. Session state information may additionally include information related to the presentation of the various applications and other shared virtual objects within the multi-user communication session. As an example, session state information may include relational information as to how applications are presented, locations of avatars, and the like.

(47) The flowchart concludes at block **425**, where the state tracking module **170** launches one or more applications in accordance with state information stored within the saved session state data. As described above, during a prior session, one or more applications may be running. According to embodiments, each application may occasionally or periodically store application state information in accordance with application-specific state saving events, session specific state saving triggers, or the like. In one or more embodiments, the same session state may identify applications which

should be bootable to reach the identified session state, and the session state data may include application state information for each of the applications that are to be launched as part of the saved session state. Further, the applications that are to be launched may additionally be identified with a state to which the applications should be launched. Accordingly, the electronic device may utilize the state information to launch one or more applications **175** to a particular state. In one or more embodiments, electronic device **100** may also utilize XR module **165** to ensure consistent presentation of virtual objects within the multi-user communication session.

(48) In one or more embodiments, the device may utilize the state information to perform a hierarchical technique to re-launch an application and/or a session. As an example, the state information may indicate physical parameters, such as physical surfaces or other characteristics which affect the presentation of the virtual objects of the application and/or session. For example, the state information may indicate where a virtual object has been placed. As another example, if the shape or geometry of the virtual object is unknown or inconsistent, then the geometry of the physical environment may also be saved and used as state information. State information may also include developer-defined information or application-specific information which may be useful for re-launching the application in a consistent or different physical environment.

(49) As an example, a chess application may include as state information data regarding a physical location and a physical surface on which the chess board is placed, as well as a state of the game (e.g., positions, turns, etc.). When the chess application is re-launched, a determination may be made regarding whether a current location is the same as the stored location in the state information. If so, then a determination may be made regarding whether the original surface on which the virtual chessboard was placed is still available in the physical environment. If so, then the chess application may be re-launched to be presented in a consistent manner as the instance represented by the state information. If the original surface is no longer available, an alternative surface may be identified which may accommodate the size of the original surface and the like. If an alternative surface is unavailable, then a virtual surface may be generated and utilized to place the chess board. Similarly, if it is determined that the device is in a different physical environment than the physical environment represented by the state information, then a new physical surface may be identified, or a virtual surface may be generated and utilized to place the chess board.

(50) FIG. 5 depicts an example timing diagram for saving application state information and session state information, according to one or more embodiments. The various components and processes will be described in relation to the components of FIG. 1. However, it should be understood that the various processes may be formed performed by alternative components, and the identified components may be replaced by alternative components.

(51) The timing diagram presents a timeline **560** over which various events occur within a multi-user communication session. The flow diagram begins at **500** where the multi-user communication session is initiated. The multi-user communication session may be initiated, for example when a device enters a shared XR environment with one or more other devices. As described above, within the XR session, various applications may be launched which may be synchronized and utilized by the various devices active in the multi-user communication session. In one or more embodiments, and in a particular multi-user communication session may be initiated when the characteristics of the particular session are modified in a meaningful manner. As an example, if the parameters that define a particular session or changed, then a new multi-user communication session may be determined to be initiated. For example, a multi-user communication session may be determined to be initiated. When a particular combination of devices or users are active in the session, if a physical environment in which the session is occurring changes, if a particular combination of applications executing in the session changes, and the like.

(52) Continuing to block **505**, at time one (indicated by **T1**), a first application is launched. In one or more embodiments, the first application may be a multi-user communication session application, which supports activity from the various users or devices active within the multi-user

communication session. Then, at block **510** at **T2**, a first application state saving event occurs. As described above, an application state saving event may be a triggering combination of characteristics of an application that indicate that state information should be saved such that the current state may be returned to later on. The application state saving event may be directed by the application, such as the first application launched at **505**, or may be directed by the multi-user communication session in which the application is executing. In response to the first state saving event, application state information are stored at block **515**. In one or more embodiments, the application state information may indicate the characteristics of the executing application that caused the triggering event. For example, reaching a particular state of execution in the first application, a predetermined amount of time has lapsed since the application is launched and/or since the last state saving event, a user directed state saving event such as a user request, a particular state of execution of the first applications reached, and the like. The state information for the application state may include an indication of the current state of the application such that when provided to the first application, the first application may be returned to the saved state.

(53) Moving on to block **520**, at time three (indicated by **T3**) a second application is launched within the multi-user communication session. The second application may be a same or different type of application as the first application launch at block **505**. The second application may be utilized by one or more devices in the multi-user communication session. The second application may be a multi-user communication session application such that the second application may be launched on multiple devices active in the multi-user communication session, where in the users of the multiple devices may utilize the second application together.

(54) Next in timeline **560**, at block **525**, a second state saving event is detected for the first application at time four (indicated by **T4**). As described above, the second state saving event may be a particular configuration or event indicated by the multi-user communication session and/or the first application that indicates a current state should be saved. The second state saving event may be the same type or different type than the first saving event from block **510**. At block **530**, the state tracking module **170** stores the application state information for the second state saving event for the first application. In addition, state information for the first application at the second state saving event may be stored in conjunction with the application state parameters for the second state saving event.

(55) The timeline **560** continues on to time five (indicated by **T5**) at block **535**, where a first state saving event for the second application is detected. As described above, the application state saving event for the second application may be indicated by the second application, the multi-user communication session, a user, or the like. The state saving event for the second application may be the same as one or more state saving events for the first application, or maybe different. At block **540**, the state tracking module **170** stores the application state information for the first saving event for the second application. The state information stored in conjunction with the application state information at block **540** may be data which when provided to the second application will allow the second application to return to these saved application state.

(56) At block **545**, a session state saving event is detected. A session state saving event may be based on a particular time that has elapsed since the last session state saving event, or a change in context of the multi-user communication session, such as a change in applications active in the multi-user communication session, a change in a combination of active devices or users in the multi-user communication session, a particular configuration or location has changed for the multi-user communication session, and the like. At block **550**, the state tracking module **170** aggregates the current application state information. In one or more embodiments, aggregating the current application state information may include obtaining or otherwise linking to a latest saved state for each application executing in the multi-user communication session. As such, in the current example, the application state from the second state saving event for the first application and the first state saving event for the second application may be utilized to aggregate current application

state information.

(57) The timing diagram concludes at block **555**, when the state tracking module **170** stores the aggregated application state information in association with the session state saving event. According to some embodiments, the session state saving event may be stored with an association to the application state information for the latest application state saving event from each application executing in the multi-user communication session. In one or more embodiments, the state tracking module **170** may additionally store other state information for the multi-user communication session, such as particular configuration of the applications, layout of an environment, and the like.

(58) FIG. **6A** and FIG. **6B** depict exemplary system **600** for use in various extended reality technologies.

(59) In some examples, as illustrated in FIG. **6A**, system **600** includes device **600a**. Device **600a** includes various components, such as processor(s) **602**, RF circuitry(ies) **604**, memory(ies) **606**, image sensor(s) **608**, orientation sensor(s) **610**, microphone(s) **612**, location sensor(s) **616**, speaker(s) **618**, display(s) **620**, and touch-sensitive surface(s) **622**. These components optionally communicate over communication bus(es) **650** of device **600a**.

(60) In some examples, elements of system **600** are implemented in a base station device (e.g., a computing device, such as a remote server, mobile device, or laptop) and other elements of system **600** are implemented in a second device (e.g., a head-mounted device). In some examples, device **600a** is implemented in a base station device or a second device.

(61) As illustrated in FIG. **6B**, in some examples, system **600** includes two (or more) devices in communication, such as through a wired connection or a wireless connection. First device **600b** (e.g., a base station device) includes processor(s) **602**, RF circuitry(ies) **604**, and memory(ies) **606**. These components optionally communicate over communication bus(es) **650** of device **600b**. Second device **600c** (e.g., a head-mounted device) includes various components, such as processor(s) **602**, RF circuitry(ies) **604**, memory(ies) **606**, image sensor(s) **608**, orientation sensor(s) **610**, microphone(s) **612**, location sensor(s) **616**, speaker(s) **618**, display(s) **620**, and touch-sensitive surface(s) **622**. These components optionally communicate over communication bus(es) **650** of device **600c**.

(62) System **600** includes processor(s) **602** and memory(ies) **606**. Processor(s) **602** include one or more general processors, one or more graphics processors, and/or one or more digital signal processors. In some examples, memory(ies) **606** are one or more non-transitory computer-readable storage mediums (e.g., flash memory, random access memory) that store computer-readable instructions configured to be executed by processor(s) **602** to perform the techniques described below.

(63) System **600** includes RF circuitry(ies) **604**. RF circuitry(ies) **604** optionally include circuitry for communicating with electronic devices, networks, such as the Internet, intranets, and/or a wireless network, such as cellular networks and wireless local area networks (LANs). RF circuitry(ies) **604** optionally includes circuitry for communicating using near-field communication and/or short-range communication, such as Bluetooth®.

(64) System **600** includes display(s) **620**. Display(s) **620** may have an opaque display. Display(s) **620** may have a transparent or semi-transparent display that may incorporate a substrate through which light representative of images is directed to an individual's eyes. Display(s) **620** may incorporate LEDs, OLEDs, a digital light projector, a laser scanning light source, liquid crystal on silicon, or any combination of these technologies. The substrate through which the light is transmitted may be a light waveguide, optical combiner, optical reflector, holographic substrate, or any combination of these substrates. In one example, the transparent or semi-transparent display may transition selectively between an opaque state and a transparent or semi-transparent state. Other examples of display(s) **620** include heads up displays, automotive windshields with the ability to display graphics, windows with the ability to display graphics, lenses with the ability to display

graphics, tablets, smartphones, and desktop or laptop computers. Alternatively, system **600** may be designed to receive an external display (e.g., a smartphone). In some examples, system **600** is a projection-based system that uses retinal projection to project images onto an individual's retina or projects virtual objects into a physical setting (e.g., onto a physical surface or as a holograph).

(65) In some examples, system **600** includes touch-sensitive surface(s) **622** for receiving user inputs, such as tap inputs and swipe inputs. In some examples, display(s) **620** and touch-sensitive surface(s) **622** form touch-sensitive display(s).

(66) System **600** includes image sensor(s) **608**. Image sensors(s) **608** optionally include one or more visible light image sensor, such as charged coupled device (CCD) sensors, and/or complementary metal-oxide-semiconductor (CMOS) sensors operable to obtain images of physical elements from the physical setting. Image sensor(s) also optionally include one or more infrared (IR) sensor(s), such as a passive IR sensor or an active IR sensor, for detecting infrared light from the physical setting. For example, an active IR sensor includes an IR emitter, such as an IR dot emitter, for emitting infrared light into the physical setting. Image sensor(s) **608** also optionally include one or more event camera(s) configured to capture movement of physical elements in the physical setting. Image sensor(s) **608** also optionally include one or more depth sensor(s) configured to detect the distance of physical elements from system **600**. In some examples, system **600** uses CCD sensors, event cameras, and depth sensors in combination to detect the physical setting around system **600**. In some examples, image sensor(s) **608** include a first image sensor and a second image sensor. The first image sensor and the second image sensor are optionally configured to capture images of physical elements in the physical setting from two distinct perspectives. In some examples, system **600** uses image sensor(s) **608** to receive user inputs, such as hand gestures. In some examples, system **600** uses image sensor(s) **608** to detect the position and orientation of system **600** and/or display(s) **620** in the physical setting. For example, system **600** uses image sensor(s) **608** to track the position and orientation of display(s) **620** relative to one or more fixed elements in the physical setting.

(67) In some examples, system **600** includes microphones(s) **612**. System **600** uses microphone(s) **612** to detect sound from the user and/or the physical setting of the user. In some examples, microphone(s) **612** includes an array of microphones (including a plurality of microphones) that optionally operate in tandem, such as to identify ambient noise or to locate the source of sound in space of the physical setting.

(68) System **600** includes orientation sensor(s) **610** for detecting orientation and/or movement of system **600** and/or display(s) **620**. For example, system **600** uses orientation sensor(s) **610** to track changes in the position and/or orientation of system **600** and/or display(s) **620**, such as with respect to physical elements in the physical setting. Orientation sensor(s) **610** optionally include one or more gyroscopes and/or one or more accelerometers.

(69) Various processes defined herein consider the option of obtaining and utilizing a user's personal information. For example, such personal information may be utilized in order to automatically determine state information in a multi-user communication session. However, to the extent such personal information is collected, such information should be obtained with the user's informed consent. As described herein, the user should have knowledge of and control over the use of their personal information.

(70) Personal information will be utilized by appropriate parties only for legitimate and reasonable purposes. Those parties utilizing such information will adhere to privacy policies and practices that are at least in accordance with appropriate laws and regulations. In addition, such policies are to be well-established, user-accessible, and recognized as in compliance with or above governmental/industry standards. Moreover, these parties will not distribute, sell, or otherwise share such information outside of any reasonable and legitimate purposes.

(71) Users may, however, limit the degree to which such parties may access or otherwise obtain personal information. For instance, settings or other preferences may be adjusted such that users

can decide whether their personal information can be accessed by various entities. Furthermore, while some features defined herein are described in the context of using personal information, various aspects of these features can be implemented without the need to use such information. As an example, if user preferences, account names, and/or location history are gathered, this information can be obscured or otherwise generalized such that the information does not identify the respective user.

(72) It is to be understood that the above description is intended to be illustrative, and not restrictive. The material has been presented to enable any person skilled in the art to make and use the disclosed subject matter as claimed and is provided in the context of particular embodiments, variations of which will be readily apparent to those skilled in the art (e.g., some of the disclosed embodiments may be used in combination with each other). Accordingly, the specific arrangement of steps or actions shown in FIGS. 2-5 or the arrangement of elements shown in FIGS. 1, 2, and 6 should not be construed as limiting the scope of the disclosed subject matter. The scope of the invention therefore should be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.”

Claims

1. A method for facilitating collaboration in a multi-user environment, comprising: presenting, by a first device, a first representation of a multi-user communication session in which one or more applications are executing, and in which a first user and a second user are active, wherein the first user is active in the multi-user communication session via the first device; in accordance with detecting an application state saving event for one of the one or more applications: determining a first application state information for the one of the one or more applications; and storing the first application state information; in accordance with detecting a session state saving event: obtaining aggregated application state information for the one or more applications, the aggregated application state information comprising the first application state information; and storing the aggregated application state information in association with the session state saving event to obtain first session state information.
2. The method of claim 1, wherein storing the first application state information further comprises: associating the detected application state saving event with the first application state information.
3. The method of claim 1, further comprising: monitoring session parameters for the multi-user communication session, wherein the session parameters comprise active participants, users provided access to the session, and one or more physical environments in which each active participant is participating, wherein the session state saving event comprises a change in one or more of the session parameters, and wherein the one or more physical environments comprise one or more physical locations in which the active participants are located during the multi-user communication session.
4. The method of claim 3, further comprising, in accordance with detecting the session state saving event: storing the monitored session parameters in accordance with the detected change as first session parameters.
5. The method of claim 4, further comprising, in accordance with detecting initiation of a second multi-user communication session: in accordance with determining that current session parameters for the second multi-user communication session are compatible with the first session parameters, launching the second multi-user communication session to a first session state according to the first session state information, wherein the current session parameters comprise one or more of active participants in the second session, users provided access to the second session, and one or more physical environments in which each active participant is participating in the second session.

6. The method of claim 1, further comprising: in accordance with detecting initiation of a second multi-user communication session: determining a session context for the second multi-user communication session; and presenting a representation of the second multi-user communication session and the one or more applications according to the session context.
7. The method of claim 6, wherein the session context comprises a determined physical environment in which the device is located, and wherein the representation of the second multi-user communication session is presented in accordance with application state information corresponding to stored session parameters for the determined physical environment.
8. The method of claim 1, wherein detecting the session state saving event comprises a determination that the first device is exiting the multi-user communication session.
9. The method of claim 1, wherein the multi-user communication session comprises an extended reality environment.
10. The method of claim 1, wherein the application state saving event comprises a triggering event by which the one of the one or more applications determines to save a current application state.
11. The method of claim 1, wherein the first application state information comprises data from which the application can be returned to a particular state.
12. A non-transitory computer readable medium comprising computer readable code for facilitating collaboration in a multi-user environment, the computer readable code executable by one or more processors to: present, by a first device, a first representation of a multi-user communication session in which one or more applications are executing, and in which a first user and a second user are active, wherein the first user is active in the multi-user communication session via the first device; in accordance with detecting an application state saving event for one of the one or more applications: determine a first application state information for the one of the one or more applications; and store the first application state information; in accordance with detecting a session state saving event: obtain aggregated application state information for the one or more applications, the aggregated application state information comprising the first application state information; and store the aggregated application state information in association with the session state saving event to obtain first session state information.
13. The non-transitory computer readable medium of claim 12, wherein the computer readable code to store the first application state information further comprises computer readable code to: associate the detected application state saving event with the first application state information.
14. The non-transitory computer readable medium of claim 12, further comprising computer readable code to: monitor session parameters for the multi-user communication session, wherein the session parameters comprise active participants, users provided access to the session, and one or more physical environments in which each active participant is participating, wherein the session state saving event comprises a change in one or more of the session parameters, and wherein the one or more physical environments comprise one or more physical locations in which the active participants are located during the multi-user communication session.
15. The non-transitory computer readable medium of claim 14, further comprising computer readable code to, in accordance with detecting the session state saving event: store the monitored session parameters in accordance with the detected change as first session parameters.
16. The non-transitory computer readable medium of claim 15, further comprising computer readable code to, in accordance with detecting initiation of a second multi-user communication session: in accordance with determining that current session parameters for the second multi-user communication session are compatible with the first session parameters, launch the second multi-user communication session to a first session state according to the first session state information, wherein the current session parameters comprise one or more of active participants in the second multi-user communication session, users provided access to the second multi-user communication session, and one or more physical environments in which each active participant is participating in the second session.

17. The non-transitory computer readable medium of claim 12, further comprising computer readable code to, in accordance with detecting initiation of a second multi-user communication session: determine a session context for the second multi-user communication session; and present a representation of the second multi-user communication session and the one or more applications according to the session context.
18. The non-transitory computer readable medium of claim 17, wherein the session context comprises a determined physical environment in which the device is located, and wherein the representation of the second multi-user communication session is presented in accordance with application state information corresponding to stored session parameters for the determined physical environment.
19. The non-transitory computer readable medium of claim 12, wherein detecting the session state saving event comprises a determination that the first device is exiting the multi-user communication session.
20. A system for facilitating collaboration in a multi-user environment, comprising: a display; one or more processors; one or more computer readable media comprising computer readable code executable by the one or more processors to: present, by a first device, a first representation of a multi-user communication session in which one or more applications are executing, and in which a first user and a second user are active, wherein the first user is active in the multi-user communication session via the first device; in accordance with detecting an application state saving event for one of the one or more applications: determine a first application state information for the one of the one or more applications; and store the first application state information; in accordance with detecting a session state saving event: obtain aggregated application state information for the one or more applications, the aggregated application state information comprising the first application state information; and store the aggregated application state information in association with the session state saving event to obtain first session state information.
-