

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417423
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Jayathirtha; Srihari et al.

Methods and dashboard systems for real-time recommendations for optimized operations

Abstract

Systems and methods are disclosed for worker performance scoring and evaluation of a job site, wherein the operation can include determine, by an insight module, dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from the sensor devices and the worker computing devices; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, the plurality of worker performance metrics, the plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity score, an aggregated idle time per worker; and generate on the dashboard of the display a dynamic real-time summary of the plurality of worker performance metrics.

Inventors: Jayathirtha; Srihari (Johns Creek, GA), Lindsey; Wade (Canton, GA), Hussaini; Syed Khaja Afzal (Hyderabad, IN), Pillutla; Krishna (Marietta, GA), Rysko; Garrett (Bellevue, WA)

Applicant: Honeywell International Inc. (Charlotte, NC)

Family ID: 1000008819804

Assignee: HONEYWELL INTERNATIONAL INC. (Charlotte, NC)

Appl. No.: 18/062477

Filed: December 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240054431 A1	Feb. 15, 2024

Foreign Application Priority Data

Publication Classification**Int. Cl.:** G06Q10/0639 (20230101); G06Q10/105 (20230101)**U.S. Cl.:****CPC** G06Q10/06398 (20130101); G06Q10/06393 (20130101); G06Q10/105 (20130101);**Field of Classification Search****CPC:** G06Q (10/00-50/00)**USPC:** 705/7.11-

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8190468	12/2011	Drew	705/7.42	G06Q 10/06398
9830567	12/2016	Weiss	N/A	G06Q 10/06311
9833197	12/2016	Elhawary	N/A	A61B 5/0022
10062042	12/2017	Kelly	N/A	G06Q 10/063112
10235646	12/2018	Perry	N/A	G06Q 10/063112
10674965	12/2019	Elhawary	N/A	A61B 5/1118
10872160	12/2019	Athuluru Tirumala	N/A	G06Q 10/0633
11327795	12/2021	Mundra	N/A	G06F 11/3433
11803795	12/2022	Aoki	N/A	G06Q 10/0633
2009/0063238	12/2008	Storzum et al.	N/A	N/A
2011/0227740	12/2010	Wohltjen	340/686.6	G01S 11/16
2016/0300178	12/2015	Perry	N/A	G06Q 10/063116
2018/0240140	12/2017	Whitley	N/A	G06Q 50/22
2019/0080274	12/2018	Kovach	N/A	G06Q 10/0639
2019/0108747	12/2018	Stenning	N/A	G08B 21/187
2019/0122036	12/2018	Ward	N/A	G06Q 10/06393
2019/0340346	12/2018	Gibbs	N/A	G06Q 10/0639
2019/0343429	12/2018	Elhawary	N/A	A61B 5/6823
2019/0347598	12/2018	Sandusky	N/A	G06Q 10/06393
2019/0370721	12/2018	Issac	N/A	B07C 5/36
2020/0074376	12/2019	Kotake	N/A	N/A

2020/0174517	12/2019	Martinez	N/A	G06Q 10/06398
2020/0219004	12/2019	Daly	N/A	G06N 20/00
2020/0234220	12/2019	Ma	N/A	G08G 1/148
2021/0035043	12/2020	Burgess	N/A	G06F 9/541
2021/0090195	12/2020	Lee et al.	N/A	N/A
2022/0164728	12/2021	Aoki	N/A	G06Q 50/04
2022/0207452	12/2021	Rorro et al.	N/A	N/A
2022/0245557	12/2021	Minter	N/A	G06N 20/00
2022/0309079	12/2021	Kurniawan	N/A	H04L 12/12
2023/0419232	12/2022	Kaufmann	N/A	G06Q 10/06393

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3009968	12/2015	EP	N/A
2020-035331	12/2019	JP	N/A
2021-532436	12/2020	JP	N/A

OTHER PUBLICATIONS

Extended European search report Mailed on Nov. 27, 2023 for EP Application No. 23187956, 14 page(s). cited by applicant

GB Combined Search Report and Abbreviated Examination Report Mailed on Jan. 25, 2024 for GB Application No. 2311569, 5 page(s). cited by applicant

CL Office Action Mailed on Oct. 17, 2024 for CL Application No. 202302300, 17 page(s). cited by applicant

English Translation of CA Office Action, including Search Report dated Oct. 29, 2024 for CA Application No. 3207502, 4 page(s). cited by applicant

English Translation of Office Action dated Oct. 17, 2024 for CL Application No. 202302300, 17 page(s). cited by applicant

GB Office Action Mailed on Oct. 11, 2024 for GB Application No. 2311569, 5 page(s). cited by applicant

English Translation of JP Office Action dated Aug. 8, 2024 for JP Application No. 2023125493, 3 page(s). cited by applicant

JP Office Action Mailed on Aug. 8, 2024 for JP Application No. 2023125493, 3 page(s). cited by applicant

CL Notice of Allowance Mailed on Feb. 4, 2025 for CL Application No. 202302300, 1 page(s). cited by applicant

CL Office Action Mailed on Jan. 15, 2025 for CL Application No. 202302300, 11 page(s). cited by applicant

English translation of CL Notice of Allowance dated Feb. 4, 2025 for CL Application No. 202302300, 1 page(s). cited by applicant

English Translation of JP Office Action dated Dec 25, 2024 for JP Application No. 2023125493, 2 page(s). cited by applicant

English Translation of Office Action dated Jan. 15, 2025 for CL Application No. 202302300, 11 page(s). cited by applicant

JP Office Action Mailed on Dec. 25, 2024 for JP Application No. 2023125493, 2 page(s). cited by applicant

SA Office Action Mailed on Mar. 4, 2025 for SA Application No. 123450109, 32 page(s). cited by applicant

Primary Examiner: Miller; Alan S

Attorney, Agent or Firm: ALSTON & BIRD LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This patent application claims the benefit of priority to Indian Application No. 202211045468, filed Aug. 9, 2022, which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates generally to methods and systems to optimize operations in a workplace such as a warehouse, distribution center, airport ground operations, and retail generally.

BACKGROUND

(3) Warehouses and distribution centers where employees are often engaged in a multitude of tasks can benefit from receiving real time and historical data from other sources. Further, overall operations can benefit from transmitting real time and historical data to optimize employee operations. Data patterns and trends can be determined from the received data, and the recipient can utilize the data patterns and trends to perform meaningful actions. In practice, employee task optimization is often lacking since a significant amount of optimization benefits have remained unreachable. Therefore, there is a need for a system for collecting and analyzing real-time data from employees, and also for sharing critical data through a streamlined communication network.

(4) The background description provided herein is for the purpose of generally presenting the context of the disclosure. Unless otherwise indicated herein, the materials described in this section are not prior art to the claims in this application and are not admitted to be prior art, or suggestions of the prior art, by inclusion in this section.

SUMMARY

(5) One embodiment provides computer system for controlling worker performance in a job site, such as a connected warehouse. A plurality of sensor devices can be located throughout the connected warehouse and connected over a network. A plurality of worker computing devices can be included corresponding to at least one of a plurality of workers of the warehouse. A memory can be connected to the network and a user interface can be connected to the network include a display configured to display a real-time dashboard comprising a menu displaying a plurality of worker performance metrics in the warehouse. A processor connected to the network configured to determine, by an insight module, dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from the sensor devices and the worker computing devices; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, the plurality of worker performance metrics, the plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity score, an aggregated idle time per worker; and generate on the dashboard of the display a dynamic real-time summary of the plurality of worker performance metrics.

(6) In some aspects, the insight module determines the plurality of worker performance metrics by aggregating and analyzing data from a plurality of connected warehouse service systems, a plurality of connected performance management systems, a connected labor management system

(LMS), and a gateway device, and wherein the plurality of worker performance metrics comprise one or more worker performance scores.

(7) In some aspects, the processor is configured to connect the plurality of sensor devices to one or more Internet-of-Things (IoT) devices connected to the gateway device, the plurality of sensor devices including one or a combination of leak detection sensors, vibration sensors, and process sensors of the connected warehouse.

(8) In some aspects, the plurality of worker performance metrics in the dynamic summary include at least one of an overall workforce scorecard dashboard, an individual worker scorecard dashboard, and a management view option (MVO) performance scorecard dashboard.

(9) In some aspects, the overall workforce scorecard dashboard comprises a plurality of dynamically updated performance notifications including at least one of a workforce startup module, an idle worker scorecard, a top/poor performer scorecard, a recent hire scorecard, and a worker allocation scorecard.

(10) In some aspects, the individual worker scorecard dashboard includes a dynamically updated scorecard. The processor is configured to, upon determining whether worker performance metrics of an assigned task of a first worker of the plurality of workers satisfy a key performance indicator (KPI) task target deviation and/or a task performance standard, generate dynamic individual performance insights on the individual worker scorecard dashboard of the display.

(11) In some aspects, the MVO performance scorecard dashboard includes a plurality of dynamically updated performance dashboards viewable by a management user and including at least one of a startup advisor dashboard, an idle worker advisor dashboard, a worker performance monitor and/or scorecard dashboard, and a schedule delay monitor.

(12) In some aspects, the processor is configured to determine, by logic and analytics of the schedule delay monitor, a schedule delay insight score of the plurality of workers, the schedule delay score being based on worker performance and engagement scores.

(13) In some aspects, the plurality of worker performance metrics includes a smart warehouse score summarizing overall warehouse workforce performance scores in real-time.

(14) One embodiment provides a computer implemented method of operating a connected warehouse is disclosed by performing, by at least one processor, operations including determine, by an insight module, dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from a plurality of sensor devices located throughout the warehouse and connected over a network and a plurality of worker computing devices, each worker computing device corresponding to at least one of a plurality of workers of the warehouse; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, a plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity score, an aggregated idle time per worker; and generate on a real-time dashboard of a display a dynamic real-time summary of the plurality of worker performance metrics, the display being on a user interface connected to the network.

(15) One embodiment provides a system for exchanging real-time worker performance data in a connected warehouse. The system includes one or more processors. The system includes a non-transitory computer readable medium storing instructions that, when executed by the one or more processors, cause the one or more processors to perform determine, by an insight module, dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from a plurality of sensor devices located throughout the warehouse and connected over a network and a plurality of worker computing devices, each worker computing device corresponding to at least one of a plurality of workers of the warehouse; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, a plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity

score, an aggregated idle time per worker; and generate on a real-time dashboard of a display a dynamic real-time summary of the plurality of worker performance metrics, the display being on a user interface connected to the network.

(16) To the accomplishment of the foregoing and related ends, certain illustrative aspects are described herein in connection with the following description and the appended drawings, including the appendix attached to this disclosure including other examples of the herein disclosed solution and which is incorporated by reference in its entirety as if set forth verbatim here. These aspects are indicative, however, of but a few of the various ways in which the principles of the claimed subject matter may be employed and the claimed subject matter is intended to include all such aspects and their equivalents. Other advantages and novel features may become apparent from the following detailed description when considered in conjunction with the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments of the disclosure will now be described, by way of example only, with reference to the accompanying drawings in which:

(2) FIG. 1 is a schematic diagram illustrating an example environment implementing methods and systems of this disclosure.

(3) FIG. 2 is a diagram of architecture of a connected warehouse system of this disclosure.

(4) FIG. 3 is a flowchart illustrating a method for monitoring safety.

(5) FIG. 4A depicts an example user interface dashboard in a mode, according to an exemplary embodiment.

(6) FIG. 4B depicts an example user interface dashboard in another mode, according to an exemplary embodiment.

(7) FIG. 4C depicts an example user interface summary dashboard in another mode, according to an exemplary embodiment.

(8) FIG. 5 depicts an example user interface including a plurality of dashboards according to an exemplary embodiment.

(9) FIG. 6A depicts an example user interface, according to an exemplary embodiment.

(10) FIG. 6B depicts an example alert message, according to an exemplary embodiment.

(11) FIG. 7 depicts an example user interface dashboard in a first mode, according to an exemplary embodiment.

(12) FIG. 8 is a flowchart illustrating a method for managing unplanned tasks, according to an exemplary embodiment.

(13) FIG. 9 is a diagram of architecture of a connected warehouse system of this disclosure.

(14) FIG. 10 is a diagram of architecture of a connected warehouse system of this disclosure.

(15) FIG. 11 depicts a schematic block diagram of a framework of a platform of a connected warehouse system.

(16) FIG. 12A depicts an exemplary diagram of a data flow of a connected warehouse, according to one or more embodiments.

(17) FIG. 12B depicts an exemplary diagram of a data flow of a connected warehouse, according to one or more embodiments.

(18) FIG. 13 is a diagram of architecture of a workforce scorecard dashboard of a connected warehouse system of this disclosure.

(19) FIG. 14 is a diagram of architecture of an individual worker scorecard dashboard of a connected warehouse system of this disclosure.

(20) FIG. 15 is a diagram of architecture of a management view option (MVO) performance scorecard dashboard of a connected warehouse system of this disclosure.

(21) FIG. 16A depicts an example user interface for a job site (e.g., a connected warehouse) including a plurality of dashboards according to an exemplary embodiment.

(22) FIG. 16B depicts an example close-up user interface dashboard of FIG. 16A in a worker overview mode, according to an exemplary embodiment.

(23) FIG. 16C depicts an example close-up user interface dashboard of FIG. 16A in a worker performance mode, according to an exemplary embodiment.

(24) FIG. 17 illustrates an exemplary device in which one or more embodiments may be implemented.

DETAILED DESCRIPTION

(25) The following embodiments describe systems and methods for facilitating a connected warehouse as between employees, managers, and other users as well as inter- and intra-warehouse edge communications systems.

(26) Previous warehouse systems have included workers, such as employees, as well as operations managers and shift supervisors. Operations managers can be responsible for meeting production quotas, managing labor fluctuations, and quickly identifying restrictions and bottlenecks. Shift supervisors can be responsible for worker performance, overseeing specific work-sites and/or warehouse areas, and being generally “hands-on” on the warehouse floor. Collectively, each can balance warehouse staffing to prevent bottlenecks, ensure quality and timeliness of orders are fulfilled, improve throughput, maximize utilization, monitor and manage each site, and ensure smooth working of the warehouse.

(27) That said, current approaches used to-date have suffered from various drawbacks. For example, current approaches are disconnected from viewing worker productivity until the end of a shift or workday. Real-time worker visibility is also lacking, making bottlenecks difficult to track and/or predict. In addition, unexpected workforce issues commonly lead to production and maintenance delays. Current approaches also fail to provide sufficient tools to react to such unexpected issues, such as unplanned events, and fail to adequately reallocate workers or take any corrective action. Further, root-causes of issues are presently not being tracked and thus problems are repeatedly occurring. In turn, worker attrition increases and performance declines.

(28) A dynamic and decentralized technique for implementing a connected warehouse system is provided. An embodiment or implementation described herein as “dynamic” is intended to reflect or indicate that the embodiment(s) is or can be marked by continuous and productive activity or change, though not necessarily constantly changing. The system and corresponding techniques facilitate communications within one or more warehouses, between users (e.g., worker, teams of workers, manager, etc.), and between warehouses, third parties associated therewith, and data centers. Such communications may be facilitated by edge systems and gateway systems. The edge and gateway systems may be located in warehouses (i.e., on-site) as embedded or fixed systems and/or other user devices such as tablet PCs and mobile phones (e.g., devices controlled by or in communication with an operations manager, etc). Each edge system may be coupled to a warehouse system from which warehouse operations data may be collected, and in communication with other edge systems and gateway systems. Each gateway system may be in communication with warehouse operation systems and edge systems of the warehouse in which the gateway system is resident (e.g., with the operations manager), and may also be in communication with gateway systems located in other warehouses, all or some of which may provide data to the gateway system. By facilitating communication with gateway systems located in other warehouses, the gateway system may enable exchange of data among edge systems installed in different warehouses. Independent user computing devices, such as tablet PCs and mobile phones, may be directly coupled to and/or in communication with the edge systems and/or gateway systems, to request, filter, view, and/or analyze data.

(29) Hardware for all or some of the edge systems and gateway systems may be installed in warehouses. Therefore, software may be installed on the corresponding warehouse hardware. The

software implemented in the edge systems and gateway systems may comprise computer-executable code for performing various data functions, including but not limited to, data request, data query, data retrieval, data transmission, and data analytics. The edge systems and gateway systems each identify source(s) of relevant data, and request that data be provided dynamically (as needed) or statically (all the time) from the identified source(s), such as from other edge systems coupled to warehouse systems in the warehouse or other warehouses, gateway systems in the warehouse or other warehouses, decentralized system(s) such as cloud computing center(s), and centralized system(s) such as dedicated server farms. The decentralized system(s) and centralized system(s) may be owned by the operators of the warehouses, or by a third party such as a government or a commercial entity.

(30) Each edge system in a warehouse may be coupled to a sensor of a corresponding warehouse system in the same warehouse, enabling data captured by the sensor to be provided directly to the edge system. Also, a gateway system in a warehouse may be coupled to one or more sensors of warehouse systems in the same warehouse, enabling data captured by the one or more sensors to be provided directly to the gateway system. In another embodiment, each edge system in a warehouse may be coupled to warehouse system of a corresponding warehouse system in the same warehouse. Also, a gateway system in a warehouse may be coupled to warehouse system machines of warehouse systems in the same warehouse. In some aspects, warehouse system machines may be configured to collect data from the coupled one or more sensors, perform computations and/or analysis of the collected data, store the collected and/or analyzed data in memory, and provide the collected and/or analyzed data to one or more connected edge systems and/or gateway system. In some embodiments, the warehouse system may not be implemented, or may not be coupled to the one or more sensors of the warehouse system. If the warehouse system machine is not implemented or not coupled to the one or more sensors, data captured by the one or more sensors may be provided directly to the one or more connected edge systems and/or gateway system.

(31) Each warehouse system may be in communication with, through an edge system or not, a gateway system. Edge systems in a warehouse may be in direct communication with one another. For example, any data retained by one edge system may be transmitted directly to another edge system within the same warehouse, without a gateway system acting as an intermediary. In another embodiment, an edge system may send to or receive data from another edge system located in the same warehouse through a gateway system. The communication between the edge systems and the communication between the edge systems and the gateway system may be through a wired or wireless connection.

(32) A gateway system of a warehouse may be in communication with gateway systems of other warehouses. Through this communication path, an edge system or a gateway system of a warehouse may transmit data to and obtain data from edge systems or gateway systems of other warehouses. The communication path between gateway systems of different warehouses may be through satellite communications (e.g., SATCOM), cellular networks, Wi-Fi (e.g., IEEE 802.11 compliant), WiMAX (e.g., AeroMACS), optical fiber, and/or air-to-ground (ATG) network, and/or any other communication links now known or later developed. An edge system in a warehouse may communicate with another edge system in a different warehouse via gateway systems of the respective warehouses. For example, an edge system in a warehouse may transmit data to one or more edge systems in other warehouses via the gateway systems of the respective warehouses communicating over the communication path discussed above.

(33) Each edge system and gateway system may comprise state machines, such as processor(s) coupled to memory. Both the edge systems and the gateway systems may be configured with a common operating system to support portable, system-wide edge software implementations. In other words, each of the edge systems and the gateway systems may be equipped with standard software to facilitate inter-operability among the edge systems and the gateway systems. In the discussion below, such software will be referred to as edge software. The edge software may enable

each edge system or gateway system to perform various functions listed below (non-exhaustive) to enable data analysis and data exchange among the various systems illustrated herein (e.g., edge systems, gateway systems, warehouse operations centers, remote systems): Filter and analyze real-time and stored data collected from other edge systems, warehouse systems, gateway systems, and/or operations center(s), and generate events based on the analysis; Identify dynamic (i.e., as needed) and static (i.e., all the time) data transmission targets (e.g., edge systems within the same warehouse, edge systems in other warehouses, operations center(s)); Transmit data over an Internet connection to the operations centers; Transmit data and events to other edge and gateway systems within an aircraft that are connected over wired/wireless networks, or to other edge and gateway systems external to the aircraft that are connected over the Internet; Provide a request/response interface for other edge/gateway systems, warehouse borne computer systems, operations centers, and remote systems connected over wired/wireless networks or Internet to query the stored data and to dynamically select/change data filters; Use request/response interfaces provided by other edge systems, gateway systems, and operations centers connected over wired/wireless networks or Internet to obtain data and to dynamically select/change data filters; Receive events from other edge systems, gateway systems, and operations centers; and Specify and communicate generic purposes (i.e., types of data the edge/gateway system is interested in) to other edge systems, gateway systems, and operations centers.

(34) Each edge system or gateway system may autonomously select and deliver data to one or more transmission targets, which may be other edge systems in the same warehouse, edge systems in other warehouses, gateway system in the same warehouse, gateway systems in other warehouses, or operations center(s). Each of the receiving edge or gateway systems (i.e., transmission targets) may be configured to filter the received data using a pre-defined filter, overriding the autonomous determination made by the edge system transmitting the data. In some embodiment, each receiving edge or gateway system may notify the other systems, in advance of the data transmission, of the types of data and/or analysis the receiving system wants to receive (i.e., generic “purposes”). Also, each edge or gateway system may maintain a list including static data transmission targets (transmission targets that always need the data) and dynamic data transmission targets (transmission targets that need the data on as-needed basis).

(35) A gateway system of a warehouse may also be in communication with one or more operations centers, which may be located remotely from the warehouse (i.e., off-site). In some embodiments, however, the operations center(s) may be located on-site at the warehouse. Each of the warehouse systems of this disclosure may be implemented in a dedicated location, such as a server system, or may be implemented in a decentralized manner, for example, as part of a cloud system. The communication path between the gateway systems and the operations center(s) may be through satellite communications (e.g., SATCOM), cellular networks, Wi-Fi (e.g., IEEE 802.11 compliant), WiMAX (e.g., AeroMACS), optical fiber, and/or air-to-ground (ATG) network, and/or any other communication links now known or later developed.

(36) Subject matter will now be described more fully hereinafter with reference to the accompanying drawings, which form a part hereof, and which show, by way of illustration, specific exemplary embodiments. An embodiment or implementation described herein as “exemplary” is not to be construed as preferred or advantageous, for example, over other embodiments or implementations; rather, it is intended reflect or indicate that the embodiment(s) is/are “example” embodiment(s). Subject matter be embodied in a variety of different forms and, therefore, covered or claimed subject matter is intended to be construed as not being limited to any exemplary embodiments set forth herein; exemplary embodiments are provided merely to be illustrative. Likewise, a reasonably broad scope for claimed or covered subject matter is intended. Among other things, for example, subject matter may be embodied as methods, devices, components, or systems. Accordingly, embodiments may, for example, take the form of hardware, software, firmware or any combination thereof (other than software per se). Furthermore, the method presented in the

drawings and the specification is not to be construed as limiting the order in which the individual steps may be performed. The following detailed description is, therefore, not intended to be taken in a limiting sense.

(37) Throughout the specification and claims, terms may have nuanced meanings suggested or implied in context beyond an explicitly stated meaning. Likewise, the phrase “in one embodiment” as used herein does not necessarily refer to the same embodiment and the phrase “in another embodiment” or “in some embodiments” as used herein does not necessarily refer to a different embodiment. It is intended, for example, that claimed subject matter include combinations of exemplary embodiments in whole or in part.

(38) FIG. 1 illustrates an exemplary warehouse and/or distribution center environment **100** with certain components, including delivery transportation **105** (e.g., supply chain delivery truck) to load into inventory **108**. An operational control tower **112** may monitor and/or otherwise control operations **110** within environment **100**. Operations **110** can be performed and/or managed by labor **109**. Operations **110** can include loading **101** and assembly machines **107**. Once assembled, packaged, and otherwise processed for distribution, transportation **116** (e.g., a freight truck) can be loaded by labor **109** and depart for its subsequent destination. The environment **100** is configured to optimize worker performance by selectively scheduling and assigning tasks and worker equipment, as discussed more particularly below. The term “worker” can be understood as a human, a non-human animal (e.g., a trained animal such as a dog) or any other asset that performs tasks at a job site (e.g., a robotic device).

(39) FIG. 2 is a diagram of architecture associated with of a connected warehouse system **200** of this disclosure. System **200** can include enterprise performance management (EPM) control tower **210a-n**, including components and databases such as but not limited to global operations, labor optimization, site operations, asset performance, and worker performance. System **200** can also include a networked warehouse system of record **220a-n**, including components and databases such as but not limited to sites (e.g., locations, benchmarks, performance service level, etc.), labor (e.g., schedule, shifts, certification, skills, etc.), operations (e.g., plans, equipment, inventory type, throughput, etc.), assets (e.g., sortation, palletizers, robots, etc.), and workers (e.g., trends, profiles, task performance such as sorters, pickers, maintenance works, etc.). EPM control tower **210a-n** and networked warehouse system of record **220a-n** can reside in a cloud based computing system **242** (e.g., a cloud computing network, one or more remote servers) and be communicatively coupled to forge data transformation and integration layer **230**.

(40) System **242** may be communicatively coupled to an edge computing system **244**. System **244** can be an edge computing system or node with a dedicated unit onsite at the work site (e.g., factory, distribution center, warehouse, etc.). System **244** can be configured to process data and information from labor database **238**, asset control systems **236** (e.g., components related to control of robots, material handling, etc.) and worker tasks database **232**. Database **238** can include databases for warehouse management services (WMS) and warehouse execution systems (WES).

(41) Database **232** can include one or more telemetry components operatively coupled to features of distribution center environment **100** so as to process and transmit control information generated subscribing to incoming control information for consumption by one or more controllers of system **240** over a network. Database **232** can be configured for data validation and modification for incoming telemetry or attributes before saving to the database; copy telemetry or attributes from devices to related assets so you can aggregate telemetry, e.g., data from multiple subsystems can be aggregated in related asset; create/update/clear alarms based on defined conditions; trigger actions based on edge life-cycle events, e.g., create alerts if device is online/offline; load additional data required for processing, e.g., load threshold value for a device that is defined in a user, device, and/or employee attribute; raise alarms/alerts when complex event occurs and use attributes of other entities inside email template; and/or consider user preferences during event processing. In some aspects, messages transmitted from database **232**, such as triggers and/or alerts, can be

configured for transmitting information to an end user (e.g., site lead, crew in the control tower, etc.) for optimization purposes. System **200** can also be configured to detect near accidents or other misses to build a trend model for early detection of anomalies before faults or malfunctions occur increasing safety. In some aspects, the trend model can perform statistical analysis of worker trends including assigned tasks, event datasets to derive insights on worker performance considering the nature of work, skillset, criticality, labor intensity, etc. In some aspects, the trend model can classify data on a variety of key performance parameters to generate reports, dashboards, and insights that can be presented to users. In some aspects, the trend model can determine benchmarks based on statistics for type of task, skill set, geographical location, industry etc. to enable performance-based assessment, incentives and target setting for worker operations.

(42) Database **232** can include mobile warehouse solutions focused on picking, sorting, and other such tasks. Database **232** can include maintenance and inspection components configured to provide one or more checklists with standard operating procedures (SOPs), maintenance processes, and the like. Database **232** can include guided work and voice maintenance and inspection components configured where hands-free work is required by employees to complete a task.

(43) FIG. 3 is a flowchart illustrating a method **300** for optimizing operations of a job site. In step **310**, the method can include providing visibility into real-time workforce productivity before an issue occurs. In step **320**, the method can include viewing worker productivity by location across functional areas. In step **330**, the method can include providing worker recommendations to return to a worker plan. In step **340**, the method can include providing tools to reallocate workers, assignment tasks, and react to unplanned events. In step **350**, the method can include measuring the impact of changes to make persistent improvement and trend to an optimized job site (e.g., a golden site).

(44) FIG. 4A is an example user interface dashboard **410** associated with the worker performance database of EPM control tower **210a-n**. As shown, dashboard **410** can present information related to overall worker utilization including utilization from a plurality of locations (e.g., picking location, shipping location, packing location, etc.) of a job site and/or multiple job sites. Dashboard **410** can present inferences from processed data associated with the plurality of locations, including operational status as to current and planned events, total workers, labor efficiency rates (e.g., cartons per labor/min) and effective throughput metrics (e.g., cartons/worker or some other worker specific metric to measure performance). The information presented in dashboard **410** can be presented in any number of ways, including color coded (e.g., red for events that require immediate attention, green for metrics that are in excess of an objective goal, grey for events that are neutral or within a range of compliance for an objective goal, etc.).

(45) FIG. 4B is an example user interface dashboard **420** associated with the worker performance database of EPM control tower **210a-n**. As shown, dashboard **420** can present information related to worker performance. Through dashboard **420**, a user can observe real-time performance, how current performance measures against objective planned performance goal(s), object measures of worker engagement, and or the like. In some aspects, one or more alerts can be presented or otherwise pushed onto dashboard **420** instructing a user (e.g., an employee, a manager, etc.) to take one or more corrective actions to improve productivity (e.g., return to a task, improve one criteria of a task that is lacking, improve engagement in an area of engagement, etc.) of one or more operational disruptions. In some aspects, corrective actions can include determining the right worker for a particular task based on the worker's profile and/or preferences, including job location or zone with job location, physical demand, temperature, shift, seniority, performance against the necessary tasks etc. to inform recommendations to move workers from area to another to mitigate attrition and maximize worker satisfaction. In some aspects, the one or more messages include workplace hazard avoidance, employee efficiency, work area efficiency, worker performance metrics, and worker performance safety. In some aspects, messages transmitted in or by dashboard **420**, such as triggers and/or alerts, can be configured for transmitting information to remote

computing systems, locations, and/or other interested users. Dashboard **420** can also be configured to detect near performance misses, trends, or other performance related events to build a trend model for early detection of anomalies before performance faults or malfunctions occur increasing worker engagement and performance.

(46) Dashboard **420** can present worker performance summaries from processed data associated with a worker or plurality of workers, including operational status as to the worker or plurality of workers being below standard, on standard, above standard, etc. Other metrics and/or alerts can be presented in dashboard **420**, including information related to location or worker area and metrics related thereto as to workers performing below, at, or above standard (e.g., a message can indicate that 10 workers in a location are performing below standard, a message can recommend to move a specific employee to another location, etc.). The information presented in dashboard **420** can be presented in any number of ways, including color coded (e.g., red for worker(s) who are performing below standard, green for worker(s) who are performing above standard, blue for worker(s) who are performing on standard, etc.).

(47) FIG. **4C** is an example user interface summary dashboard **430** associated with the worker performance database of EPM control tower **210a-n**. As shown, dashboard **430** can be in communication with an insight module to present summary information related to a worker scorecard. Through dashboard **430**, a user can observe or otherwise track performance metrics of interest, including but not limited to worker productivity, and match preferences of a respective worker to work-related tasks. By so dynamically matching, churn or wasteful time allocation can be minimized, and insights into worker coaching-related needs can be determined. As can be seen, dashboard **430** can present information such as worker name, worker address, worker status (e.g., on duty, off duty, etc.), schedule summary (e.g. at a location on Monday, Wednesday, and Friday), how long the worker has been active in the system, worker preferences, and worker job title.

(48) In some aspects, a user can toggle dashboard **430** to investigate more information related to the user previously summarized in dashboard **430** to initiate presentation of dashboard **435**. Dashboard **435** can include more real-time task-related performance metrics, such as specific metrics (e.g., minutes or percentage of shift time) the respective worker has dedicated doing specific tasks (e.g., picking, shipping, packing, etc.) across a period of time (e.g., a shift, a day, a week, a year, an entirety of the worker's time spent with a company, etc.). In some aspects, dashboards **430** and **435** facilitate tracking top performing workers as well as outlier poorer performance performances according to certain metrics (e.g., worker area, specific tasks, time allocation management, etc.). The information presented in dashboards **430** and **435** can be presented in any number of ways, including color coded similar to other previous dashboards of this disclosure.

(49) FIG. **5** depicts an example user enterprise warehouse management interface **500** including any of the herein disclosed dashboards **410**, **420**, **430**, **435** positioned in a single frame. In certain aspects, each of the dashboards of interface **500** can be positioned as tiles capable of being toggled to enlarge or otherwise accessed by user. Interface **500** can also present sub-dashboards such as ones configured to present work risk summaries (e.g., with names, risk percentage, and worker area), total numbers of workers, performance status indicators, overall labor, labor utilization, and/or the like. Interface **500** can also include a dashboard directed towards summarizing worker opportunities by area and recommendations for potential workers in respective areas. Interface **500** can also include a notification dashboard with filter options, event logs, and a presentation of notifications compliant with user-selected or system-selected notification filter and/or notification settings. In some aspects, interface **500** can present summaries of resources against a set of tasks that need to be executed. For example and without limitation, based on the workflow lifecycle, interface **500** can be configured to transmit to connected workers a queue of one of more tasks based on the operations of the overall system. The queue can be available so that when a respective worker successfully completes a task, one or more subsequent tasks are presented.

(50) FIG. 6A depicts an example user interface **610** to create tasks so as to optimize worker performance. Specifically, user interface **610** can be used to generate real-time task instructions for employees (e.g., crew members) or any related user based on operations feedback, including human and analytics feedback related to one or more work sites. As can be seen, interface **610** can include automatically and/or manually generating tasks with task-related information, such as a template(s) for task creation, a work site location (e.g., zone, 1, zone 2, etc.), a worker pulldown menu (e.g., team 1, team 2, individual 1, individual 2, etc.), and a priority pulldown menu (e.g., move to top, objective categorizing of a task such as urgent, non-urgent, etc.). In some aspects, user interface **610** can be used to oversee worker execution of a work-related plan (e.g., daily plan, a weekly plan, a monthly plan, a quarterly plan, etc.) so as to encourage and remain present to advise and address issues that prevent employees from completing tasks. In some aspects, user interface **610** is used to optimize workplace performance by automatically assigning and/or scheduling the appropriate tasks for the appropriate employee at the appropriate time (e.g., based on one or more relationships determined as between detected criteria such as employee skills, availability, experience, history, and/or the like).

(51) FIG. 6B depicts an example alert message **620** notifying of an event of interest affecting employee performance. For example, a notification associated with alert message **620** can be pushed to a user interface (e.g., interface **610**) to inform that the event of interest has occurred which may impact performance. As can be seen, alert message **620** indicates that trouble has been reported, that a device, such as, for example printer **622** is out of media, a time of the event of interest, to whom the related job tasks have been assigned to resolve, and buttons for related user engagement. For example, message **620** can include a button to dismiss and/or snooze the message **620**. Message **620** can also be configured to re-assign tasks(s) associated with the event of interest or otherwise control performance of task(s) associated with the event of interest.

(52) FIG. 7 depicts an example user interface **710** for of an example computing device **722**. As seen, via user interface **710** one or more tasks can be assigned, created, and/or otherwise communicated to one or more users (e.g., crew member). Such notifications related to a newly assigned task or feedback related to an already-assigned task can include information controls for users to accept, snooze, and/or otherwise interact with a respective task (e.g., propose or execute modifications to a task, work plan, and/or the like).

(53) FIG. 8 is a flowchart illustrating a method **800** for managing unplanned tasks (e.g., tasks of job site(s), area(s) of job site(s), employee(s), group(s) of employees, etc.). In step **810**, the method can include viewing, by employee user (e.g., a ramp agent) a list of tasks for a shift (e.g., an upcoming shift). In step **820**, the method can include presenting an assigned first task to the user, the assigned task being unexpected (e.g., a tug operator employee can be inspecting a tug and then receive a first task). In step **830**, the method can include the employee completing a first subtask (e.g., arriving to a job site associated with the assigned task) and updating status of the assigned task based on a status of the first subtask (e.g., the employee has arrived to the job site). In some aspects, the tug operator employee can arrive to an airplane (e.g., the job site) and the status of the first subtask can be that the tug operator employee has arrived to the airplane. The status can be automatically updated and/or communicated based on information the employee detected or tracked from the computing device of the employee (e.g., GPS data automatically transmitted from a location tracker of the computing device of the employee). In some aspects, the status can be manually updated and/or communicated (e.g., the employee can manually enter into a computing device that she has arrived to the job site).

(54) In step **840**, the method can include the employee completing a second subtask (e.g., arriving to a second job site associated with the assigned task) and updating status of the assigned task based on a status of the second subtask (e.g., the employee has arrived to the second job site to sort). In some aspects, the tug operator employ can return with a load from the first job site and the status of the second subtask can be that the tug operator employee has returned from the airplane

with the load for sorting or that that the load has already been sorted. The status of the second subtask can be automatically updated and/or communicated based on data of the computing device of the employee and/or any items associated with the second subtask (e.g., GPS data automatically transmitted from the computing device of the employee, tracking information of any items associated with the second subtask, etc.). In some aspects, the status can be manually updated and/or communicated (e.g., the employee can manually enter into a computing device that she has returned, that the load has been sorted, etc.). In some aspects, task updates can be semi-automated and/or automated based on input from one or more feedback mechanisms such as voice input, scanning, device usage, network activity, location-based events, visual recognition events, etc.

(55) In some aspects, completion of the first and second subtasks can automatically mark the assigned task as being completed. In this respect, in step **850**, the method can include upon completion of the first assigned task, automatically assigning a second assigned task to the employee (e.g., the tug operator employee receives a new task since the aforementioned load has been retrieved from the airplane, sorted, and returned).

(56) In step **860**, the method can include viewing, by a second employee (e.g., an employee other than the tug operator such as a ramp agent), a real-time status of all other employees of a team associated with the first employee (e.g., other tug operators of the first tug operator's team).

(57) In step **870**, the method can include reviewing, by a third employee (e.g., an employee who is a manager or OPS lead other than the tug operators), a real-time status of all task operations of the job site and employee task performance metrics.

(58) FIG. **9** is a diagram of architecture associated with of a connected warehouse system **900** of this disclosure. System **900** can include workforce analytic modules **915**, including but not limited to modules for dynamic work allocation, real-time worker performance metrics, worker satisfaction, etc. Workforce analytic modules **915** can also include one or more worker performance dashboards **923** and improvement recommendations **925**. Improvement recommendations **925** can be for training, rewarding, coaching, engagement, etc. opportunities to maximize worker retention, performance, and overall work operations

(59) In certain aspects, worker performance dashboards **923** and improvement recommendations **925** can be updated (e.g., in real-time) by a system **917** of record for worker activities and performance. System **917** can be in communication with workforce analytic modules **915**. System **917** can improve schedule worked productivity via labor management module **910** and planning systems module **920**. Specifically, management module **910** can include one or more discrete components (e.g., components to manage manufacturing operations management (MOM) labor, 3rd party activities, as well as homegrown activities) that in real-time communicate with a comprehensive data model of system **917**. The comprehensive data model of system **917** can include a plan performance module bi-directionally coupled to labor management module **910**. The comprehensive data model of system **917** can also include modules with digital task performance and task-level granularity. In some aspects, the plan performance module can include a database of worker digital task performance and task-level granularity (e.g., showing discrete subtasks of a task or granular performance metrics of a respective worker task).

(60) In practice, a layer **926** for identifying and reporting adverse conditions can be included in system **917**. Layer **926** can include an asset performance manager (APM) as well as systems to manage worker orders. In some aspects, layer **926** can include an operation intel manager and trouble-found reporting system that collectively work to enable layer **926** to communicate with aspects of assignment layer **924** downstream thereof. Layer **926** can include a plan system in bi-directionally coupled to planning systems module **920**, including but not limited to warehouse management systems (WMS), third party systems, and the like. The operation intel manager and trouble-found of assignment layer **926** can communicate with digital task creation and digital task assignment systems of assignment layer **924**. Assignment layer **924** in turn can communicate with aspects of execution layer **922** downstream thereof.

(61) Layer **922** can include or be coupled to one or more mobile devices (e.g., mobile devices of users and/or personnel associated therewith including employees, managers, and personnel of third parties). Layer **922** can also include guided work software (GWS) systems. In some aspects, the digital task creation and digital task assignment systems of assignment layer **924** can be in communication with the mobile devices of layer **922** as well as a digital task execution system of layer **922**. In some examples, mobile devices of layer **922** as well as a digital task execution system of layer **922** can communicate with the task level granularity system, the plan performance system, and digital task performance system of the comprehensive data model of system **917** to dynamically update worker performance dashboard **923** and improvement recommendations **925**.

(62) FIG. **10** is a diagram of architecture of a connected warehouse system **1000** of this disclosure. System **1000** can be a multi-layered system including an applications layer **1010**, a platform services layer **1020**, a common services layer **1052a-n**, a standards and processes layer **1054a-n**, a connectivity services layer **1040**, a data sources layer **1048a-n**, and an enterprise systems layer **1050a-n**.

(63) Applications layer **1010** can include a plurality of components such as applications for portfolio operations, site operations, asset performance management, predictive asset maintenance, asset health management, asset maintenance optimization, downtime reporter, instrument asset management, vertical specific extension, and worker performance.

(64) Platform services layer **1020** can be in communication with applications layer **1010** and include a plurality of system components, including domain services **1022a-n**, application services **1024a-n**, data services **1026a-n**, managed storage **1028a-n**, and data ingestion **1030a-n**. Domain services **1022a-n** can include modules and/or components for asset model service, asset digital service, asset key performance indicator (KPI) service, event management service, asset data service, asset annotation service, downtime management service, asset analytics service, task/activity service, and people worker service. Preferably, domain services **1022a-n** includes asset analytics service systems, task/activity service systems, and people worker service systems.

(65) Application services **1024a-n** can include modules and/or components for portal navigation service, dashboard builder, report writer, content search, analytics workbench, notification service, execution scheduler, event processing, rules engine, business workflow services, analytics model services, and location services. Some or all of components of application services **1024a-n** can be in communication with applications of layer **1010**.

(66) Data services **1026a-n** can include modules and/or components for time series, events, activities and states, configuration model, knowledge graph, data search, data dictionary, application settings, and personal identifying information (PII) services. Managed storage services **1028a-n** can include databases for time series, relational, document, blob storage, graph databases, file systems, real-time analytics databases, batch analytics databases, and data caches. Managed storage services **1030a-n** can include modules and/or components for device registration, device management, telemetry, command and control, data pipeline, file upload/download, data prep, messaging, and IoT V3 connector.

(67) Connectivity services layer **1040** can include edge services **1042a-n**, edge connectors **1044a-n**, and enterprise integration **1046a-n**. Edge services **1042a-n** can include modules and/or components for connection management, device management, edge analytics, and execution runtime. Edge connectors **1044a-n** can include OPC unified architecture (OPC UA), file collectors, and domain connectors. Enterprise integration **1046a-n** can include modules and/or components for streaming, events, and/or files. Data sources layer **1048a-n** can include modules and/or components for streaming, events, and/or files, as well as time series.

(68) In some aspects, common services **1052a-n** can include one or more API gateways as well as components for logging and monitoring, application hosting, identify management, access management, tenant management, entitlements catalogues, licensing, metering, subscription billing, user profiles, and/or secret store.

(69) In some aspects, standards and processes **1054a-n** can include one or more UX libraries as well as components for cybersecurity, IP protection, data governance, usage analytics, tenant provisioning, localization, app lifecycle management, deployment models, mobile app development, and/or marketplace.

(70) FIG. 11 depicts a schematic block diagram of a framework of a platform of a connected warehouse system **1100**. System **1100** can include an asset management system **1110**, operations management system **1112**, worker insights and task management system **1114**, and configuration builder system **1116**. Each of systems **1110**, **1112**, **1114**, and **1116** can be in communication with API **1120**, whereby API **1120** can be configured to read/write tasks, events, and otherwise coordinate working with workers of system **1100**. API **1120** can include a task monitoring engine configured to track status, schedule, and facilitate task creation. API **1120** can present or otherwise be accessed via a worker mobile application (e.g., a graphical user interface on a computing device) to similarly present and manage operations related to tasks, events, and asset information.

(71) API **1120** can be in communication with model store **1126** whereby model store **1126** can include models such as worker models, asset models, operational models, task models, event models, workflow models, and the like. API **1120** can be in communication with time series databases **1124a-n** and transaction databases **1122a-n**. Time series databases **1124a-n** can include knowledge databases, graph databases, as well as extensible object models (EOMs). Transaction databases **1122a-n** can include components and/or modules for work orders, labor, training data, prediction results, events, fault, costs, reasons, status, tasks, events, and reasons.

(72) Each of databases **1124a-n**, **1122a-n** can be in communication with analytics model **1134**, which can be a machine learning model to effectively process, analyze, and classify operations of system **1100**. Model **1134** can be a trained machine learning system having been trained using a learned set of parameters to predict one or more learned performance parameters of system **1100**. Learned parameters can include but are not limited to predictive asset maintenance of a connected warehouse, asset health management, asset maintenance optimization, worker downtime reporter, instrument asset management, vertical specific extension, and worker performance. One or more corrective actions can be taken in response to predictions rendered by model **1134**. Model **1134** can be trained with a regression loss (e.g., mean squared error loss, Huber loss, etc.) and for binary index values it may be trained with a classification loss (e.g., hinge, log loss, etc.). Machine learning systems that may be trained include, but are not limited to convolutional neural network (CNN) trained directly with the appropriate loss function, CNN with layers with the appropriate loss function, capsule network with the appropriate loss function, Transformer network with the appropriate loss function, Multiple instance learning with a CNN (for a binary resistance index value), multiple instance regression with a CNN (for a continuous resistance index value), etc.

(73) In certain aspects, databases **1124a-n** and **1122a-n** can operate together to perform exception event detection **1128**. Exception event detection **1128** can utilize data from one or more data sources to detect low limit violations, fault symptoms, KPI target deviations, etc. In certain aspects of exception event detection **1128**, a data ingestion pipeline **1136** and enterprise integration framework **1138** can exchange information for energy and emission calculations per asset/units of system **1100**. Pipeline **1136** can utilize contextual data and data preprocessing while framework **1138** can include extensible integration service with standard and customer connectors.

(74) In certain aspects, an IoT gateway **1140** can be communicatively coupled to pipeline **1136**. IoT gateway **1140** can be communicatively coupled to IoT devices **1154** such as sensors **1158a-n**, including leak detection sensors, vibration sensors, process sensors, and/or the like. IoT gateway **1140** can also be in communication with data historian **1156** including historical data related to the warehouse.

(75) Framework **1138** can be in communication with event manager modules **1142a-n**, including workflow module, work order integration module, worker performance module, asset event module, and the like. For events, the workflow module can be configured to bidirectionally

communicate with framework **1138** and components of process workflow data **1152a-n**, including Process Safety Suite (PSS) maintenance and inspection (M&I) and PSS GWS. For event streaming, work order integration module and worker performance module can both be configured to bidirectionally communicate with framework **1138** and labor management systems (LMS) **1150**. In some aspects, for event streaming asset event module can also be configured to bidirectionally communicate with PSS operational intelligence systems **1146** and framework **1138**. PSS operational intelligence systems **1146** in turn can be cloud-based and/or on premises and be in bidirectional communication with devices **1148a-n**, including voice devices, mobility devices, hand-held devices, printers, scanners, and/or the like. Framework **1138** can also be in communication with start talk module **1144** for corresponding API and event control.

(76) In aspects of system **1100**, pipeline **1136** and framework **1138** work together to perform step **1132** to calculate energy and emission calculations for assets and/or associated units. Model **1134** can be used in performing step **1132** as well as other native and/or external models connected therewith, whereby step **1132** can utilize data received from pipeline **1136** and framework **1138**.

(77) Upon completing step **1132**, key performance monitoring calculations can be performed in step **1130**. Step **1130** can be performed based on energy and emission calculations from step **1132** by aggregating and rollup across one or multiple reporting periods. Upon performing step **1130**, the aforementioned event exception detection step **1128** can be performed to detect exception events. In some aspects, step **1128** can be performed based on the key performance monitoring calculations of step **1130**.

(78) FIG. **12A** is a diagram of data flow **1200** of a connected warehouse system, including one with connective workers and performance management (EPM) service systems. In FIG. **12A** depicts an exemplary diagram of a data flow **1200**, according to one or more embodiments. In step **1204**, an operator and/or engineer may use a computing device **1206** to manage system performance through a user interface (e.g., a web-based or browser-based application) using system gateway **1210**, which can be a cloud based. In step **1202**, a user (e.g., worker, manager, and/or the like) may use an app in a computing device **1208** (e.g., mobile device such as a tablet or smart phone or any personal computing device) via an API to communicate and exchange data with gateway **1210**.

(79) Warehouse system services **1212a-n** can be configured in communication with gateway **1210** (e.g., receive data from gateway **1210** from steps **1202** and **1204**). Services **1212a-n** can be configurable to communicate and/or update in real-time functions such as identify and access management (IAM), system extensible object model (EOM), notifications, fire and gas instrumented function (FIF), etc. Performance management system **1214a-n** can be configured to transmit data to warehouse system services **1212a-n** while receiving data from LMS **1216**. Based on said data from LMS **1216**, real-time adjustments can be determined for a labor management plan associated with the warehouse and/or workers. In some aspects, the labor management plan can be updated by system **1214a-n** being in bidirectional communication with gateway **1210**. System **1214a-n** can include or otherwise be in communication with corresponding web apps, asset performance management (APM) services, connected worker services, LMS integration applications, site operation services, and global operation services. System **1214a-n** can be connected to one or more cloud-based databases (e.g., azure SQL **1216**). One or more components of system **1214a-n** can be part of computing devices and/or sensors associated with workers connected to the system.

(80) LMS **1216** can be configured to control labor costs, track performance, and predict one or more parameters associated with performance (e.g., project fulfillment execution) and transmit and/or otherwise present such information in LMS system integration applications (e.g., using FIF). In turn, system **1214a-n** can be configured to consume data from LMS **1216**, gateway **1210**, devices **1208** and **1206**, and services **1212a-n** to deliver one or more inferences to end users (e.g., one or more actions that the end-user can take or a corresponding employee or employees associated with one or more tasks) to result in changing a warehouse operation, such as warehouse operation

savings. Warehouse operation savings can be directed towards safety, maintenance, performance, resource conservation, deliverable management, inventory management, etc.). An actionable update (e.g., a sync) may then be made to data flow **1200**.

(81) FIG. **12B** is a diagram of data flow **1200'** of a connected warehouse system. In addition to previous steps **1202** and **1204**, data flow **1200'** provides step **1201** in which a system administrator and/or application engineer may manage system performance through a user interface (e.g., a web-based or browser-based application) using system gateway **1210**, which can be a cloud based. In data flow **1200'**, one or more services of services **1212a-n** (e.g., such as the notifications module) can push messages or otherwise push notify (e.g., azure notification via webhook) from services **1212a-n** to device **1208**. In some aspects, data flow **1200'** provides that performance management system **1214a-n** can receive data from LMS **1216** and one or more third party systems **1217**. Based on said data from LMS **1216** and one or more third party systems **1217**, real-time adjustments can be determined for a labor management plan associated with the warehouse and/or workers. In some aspects of data flow **1200'**, the labor management plan can be updated by system **1214a-n** being in bidirectional communication with gateway **1210**. FIG. **13** depicts architecture **1300** of a workforce scorecard dashboard **1310** of a connected warehouse system of this disclosure. In some aspects, scorecard dashboard **1310** can include objective information related to one or more worker performance parameters. For example, based on information from an insight module of the connected warehouse, scorecard dashboard **1310** can present a smart warehouse score on a numeric scale or present a color rating summarizing workforce performance scores in real-time. It is understood that an insight module of or associated with scorecard dashboard **1310** can include aspects of any herein disclosed connected warehouse, including connected warehouse system **1000** and its warehouse system services **1212a-n**, performance management system **1214a-n**, LMS **1216**, gateway, and/or the like, whereby data can be aggregated from corresponding sensor devices, worker computing devices, and connected systems to calculate one or more worker performance scores.

(82) By way of example and without limitation, scorecard dashboard **1310** can also be communication with aspects of previously discussed systems, such as time series databases **1124a-n** and transaction databases **1122a-n** so that these databases can operate together to perform exception event detection **1128** to calculate worker performance and related scores (e.g., exception event detection **1128** can utilize data from one or more data sources to detect low limit worker performance violations, fault or anomaly worker performance symptoms, KPI target deviations, etc.). In certain aspects of exception event detection **1128**, a data ingestion pipeline **1136** and enterprise integration framework **1138** can exchange information for energy and emission calculations per asset/units of system **1100**. Pipeline **1136** can utilize contextual data and data preprocessing while framework **1138** can include extensible integration service with standard and customer connectors.

(83) Any of the herein disclosed computer systems can provide operation of the smart warehouse score system associated with scorecard dashboard **1310**. One or more databases associated with workers, tasks, teams of workers, the warehouse, and the like can be provided at the job site (e.g., warehouse) or remotely (e.g., via the cloud) for memory needs such as functions of scorecard dashboard **1310**. Sensor devices of one or more areas and/or assets of the warehouse may be connected therewith and/or with a corresponding insight module along with worker computing device actively sensing information from respective workers. Changes in scorecard dashboard **1310** may reveal deltas or changes so that the system or system user (e.g., shift manager) can take action preemptively and/or in real-time in response to such changes and/or performance anomalies.

(84) In some aspects, workforce startup module **1312** can be included with scorecard dashboard **1310**. Scorecard **1312** can in certain aspects be indicated in a worker dashboard, whereby notifications related to one or more anomalies can be transmitted to supervisors (e.g., if worker(s) did not start work after a scheduled start time following signing into a job site, or if worker(s) did

not start one or more tasks after returning from a break, etc.). Module **1312** can receive and aggregate data from the sensor devices of the respective job site (e.g., warehouse) as well as area(s) within the job site. Module **1312** can also receive and aggregate data from worker the computing devices of or otherwise connected to workers (e.g., worker computing devices such as mobile devices or other personal computing devices, wearable biometric devices, smart badges, etc.). Module **1312** can track one or more workers or one or more teams of workers to determine whether progress at the start of a task (e.g., at the beginning of a shift or returning from a break) is below, at, or exceeding task expectations so that performance can be optimized.

(85) For example, at the beginning of a shift or returning from a break, it can be common for worker(s) to perform tasks at a rate slower or otherwise less efficient than an optimized and/or expected rate. The system can analyze the aggregated information and via module **1312** present feedback so that the system and/or system user(s) can in real-time monitor task(s) to determine whether tasks at startup are below, at, or exceeding task expectations and corrective action(s) can be promptly taken. For example, a shift manager and/or another worker in a team of workers can be notified, or the respective worker herself can be notified, that startup task performance is below the expected rate and one or more corrective actions of solving problems of the respective worker can be promptly initiated. Corrective actions can include encouraging the respective worker (e.g., with incentivizing compensation, bonuses, etc.), providing a corrective task, inviting another user(s) to help the respective user, and the like. In some aspects, information of module **1312** can be transmitted directly to shift managers as well as other managerial users (e.g., shift supervisor, site operations manager, etc.).

(86) In some aspects, an idle worker scorecard **1314** can be included with scorecard dashboard **1310**. Similar to module **1312**, scorecard **1314** can receive and aggregate data from the sensor devices and worker the computing devices. Scorecard **1314** can track one or more workers or one or more teams of workers to view all on-shift workers who have not scanned or otherwise provided a task update (e.g., worked tasks, scanned task, completed task, etc.) in a predetermined amount of time (E.g., the previous 5 minutes, the previous 10 minutes, the last hour, a duration of the current shift).

(87) In an associated user interface, an idle worker dashboard view can be provided including the amount of time related to the task update and including visible filters. This amount of time can be automatically or manually updated by the end user (e.g., adjusted to current day, current week, current month, current year, or any previous period of time). In the associated user interface of scorecard **1314**, information related to idle workers can be readily presented including but not limited to the number of workers currently idle, of the number of workers who may be repeated idle workers, and a running calculation of total time lost to idle time across a period of time (e.g., the past day, the past week, the current shift, the past month, etc.). Scorecard **1314** can also include a trend number of idle workers as well as predicted idle workers according to current information aggregated from corresponding sensor and worker computing devices in comparison to idle worker historical information.

(88) In some aspects, a top/poor performer scorecard **1316** can be included with scorecard dashboard **1310**. Similar to scorecards **1312**, **1314**, scorecard **1316** can similarly receive and aggregate data from the sensor devices and worker computing devices. Scorecard **1316** can identify outlier performers (top performers, poor performers) so that responsive action can be taken (e.g., rewarding action, encouragement action, etc.). In some aspects, such outlier performers can be determined by comparing performance parameters against others (e.g., in a peer comparison view to compare peers in a respective team, members of other teams, etc.). Performance parameters can include task type, worker level (e.g., seniority related to others, worker certifications, etc.). In some aspects, scorecard **1316** can include and continually provide dynamically update lists of top performers and poor performers (e.g., top 5 and bottom 5 workers) based on performance parameters such as overall shift performance, on-standard performance, effectiveness at a

respective task or sub-task, as well as engagement.

(89) In some aspects, a recent hire scorecard **1318** can be included with scorecard dashboard **1310**. Similar to scorecards **1312**, **1314**, **1316**, scorecard **1318** can similarly receive and aggregate data from the sensor devices and worker computing devices. Scorecard **1318** can identify and provide insights for recently hired workers so that responsive action can be taken (e.g., provide onboarding training, training for a skill or task that the respective recent hire needs support with based on analytics associated with task performance by the respective recent hire). This is particularly advantageous since recent hires are typically the most likely to leave a company, scorecard **1318** provides a prompt, efficient, and results-oriented solution to in real-time determine and present recent-hire worker performance insights and to both provide corrective actions as well as maintain levels of engagement and encouragement for recent hire retention.

(90) In some aspects, a worker allocation scorecard **1320** can be included with scorecard dashboard **1310**. Similar to scorecards **1312**, **1314**, **1316**, **1318**, scorecard **1320** can similarly receive and aggregate data from the sensor devices and worker computing devices. Scorecard **1320** can monitor and provide insights for worker allocation. In certain aspects, scorecard **1320** can provide visibility related to which workers have arrived for shifts, how each department of a worksite is performing related to worker allocation and status of arrived workers, and present this information relative to expected worker allocation, expected worker performance, and/or status of related tasks. Upon monitoring and determining that allocation anomalies are present or trending to be present, corrective actions can be recommended and/or taken, including practical allocation adjustments to adapt to allocation variations as they occur. Other scorecards, modules, dashboards, and/or related databases are contemplated for use or inclusion with scorecard dashboard **1310**.

(91) FIG. **14** depicts architecture **1400** of an individual scorecard dashboard **1410** of a connected warehouse system of this disclosure. In some aspects, scorecard dashboard **1410** can include objective information related to one or more individual worker performance parameters. For example, scorecard dashboard **1410** can present an individual worker score on a numeric scale or present a color rating summarizing workforce performance in real-time.

(92) Any of the herein disclosed computer systems, including the connected warehouse systems, can provide operation of the individual worker score system associated with individual scorecard dashboard **1410**. One or more databases associated with individual workers and related tasks, respective team(s) of individual worker(s), related warehouse(s), and the like can be provided at the job site (e.g., warehouse) or remotely (e.g., via the cloud) for memory needs such as functions of scorecard dashboard **1410**. Sensor devices of one or more areas and/or assets of the warehouse may be connected therewith along with worker computing device actively sensing information from respective workers. Changes in scorecard dashboard **1410** may reveal deltas or changes so that the individual worker, the overall system or any other system user aside from the respective individual worker (e.g., an associated shift manager) can take action preemptively and/or in real-time in response to such changes and/or performance anomalies.

(93) In some aspects, a scorecard dashboard **1412** to view individual workers scores can be included with scorecard dashboard **1410**. Scorecard dashboard **1412** can receive and aggregate data from the sensor devices of the respective job site (e.g., warehouse) as well as area(s) within the job site. Scorecard dashboard **1412** can also receive and aggregate data from worker the computing devices of or otherwise connected to workers (e.g., worker computing devices such as mobile devices or other personal computing devices, wearable biometric devices, smart badges, etc.). Scorecard dashboard **1412** can track for individual workers task progress against task expectations, task performance, overall performance and the like. Other performance indicators tracked and used to determine individual performance metrics and related dynamic individual performance insights include but are not limited to overall performance against a predetermined plan (e.g., time worked versus number of units moved), “on standard” which is understood as time worked versus site goal per task (e.g., a KPI task target deviation, a task performance standard, etc.), percent effectiveness

(e.g., time worked versus planned breaks), attendance, engagement (e.g., determined objectively from worker computing devices), clicks per hour by the individual worker, time spent with eyes on a display screen, etc. In some aspects, scorecard dashboard **1412** can also include aspects which are dimensioned by task or rate of a predetermined performance parameter (e.g., frequency of updating worker preferences, frequency that worker checks their performance score, frequency of worker's career trajectory, frequency of worker performing one or more of the same tasks).

(94) Scorecard dashboard **1412** can also include aspects such as individual performance quality score, which can be determined based on objective performance quality parameters detected from worker computing devices and/or sensor devices. For example, each completed or ongoing tasks can receive a quality score, which can be tracked and presented by scorecard dashboard **1412**.

(95) In some aspects, scorecard dashboard **1412** can provide or otherwise present individual worker profiles to facilitate viewing worker task assignments in alignment with individual worker profiles, preferences, career incentives, career promotions, etc. Profile attributes, which can be tracked and used to populate worker profiles and related profile insights, include but are not limited to worker profile picture, name, salary, role, functional area, work schedule, days at a job, preferences, work groups, certifications, hours active, location preference, career trajectory, seniority, etc.

(96) Scorecard dashboard **1412** can also include aspects such as individual worker satisfaction score, which can be determined based on objective satisfaction parameters detected from worker computing devices and/or sensor devices herein discussed metrics and/or insights determined in connection with scorecard dashboard **1412** as to engagement and performance. Individual worker satisfaction scores are particularly advantageous for determining and preemptively providing corrective actions for potential schedule delays based on the individual worker satisfaction score(s).

(97) FIG. **15** depicts architecture **1500** of a management view option (MVO) performance scorecard dashboard **1510** of a connected warehouse system of this disclosure. In some aspects, scorecard dashboard **1510** can include objective information related to MVO performance parameters. For example, scorecard dashboard **1510** can present an MVO performance score on a numeric scale or present a color rating summarizing workforce performance in real-time.

(98) The MVO performance dashboard **1510** can include any herein described scores and/or dashboards and be viewable by a management user (e.g., a shift manager). However, other users are contemplated to view or otherwise access or use the MVO performance dashboard **1510**. For example, a startup advisor dashboard **1520** can be included similar to previously discussed workforce startup module **1312**. Dashboard **1520** can be used to analyze aggregated information from system connected worker computing devices and/or warehouse sensor devices and present feedback so that the system and/or system user(s) can in real-time monitor task(s) to determine whether tasks at startup are below, at, or exceeding task expectations and corrective action(s) and related insights can be promptly taken. Corrective actions can include encouraging the respective worker, providing a corrective task, inviting another user(s) to help the respective user, and the like.

(99) An idle worker advisor dashboard **1522** can also be included similar to previously discussed idle worker scorecard **1314**. Dashboard **1522** can track one or more workers or one or more teams of workers to view all on-shift workers who have not scanned or otherwise provided a task update (e.g., worked tasks, scanned task, completed task, etc.) in a predetermined amount of time (E.g., the previous 5 minutes, the previous 10 minutes, the last hour, a duration of the current shift).

Dashboard **1522** can include an idle worker monitor engine **1532** configured to actively monitor for workers who are performing below performance standards (e.g., worker(s) who have not scanned or completed task(s) in some predetermined time range). Engine **1532** can be configured to track and present insights such as impact of idle time per worker(s).

(100) A performance advisor dashboard **1524** can also be included, similar to previously discussed scorecard **1316**. Similar to scorecard **1316**, dashboard **1524** can identify outlier performers (top performers, poor performers) so that responsive action can be taken (e.g., rewarding action, encouragement action, etc.) whereby outlier performers can be determined by comparing

performance parameters against others (e.g., peers in a respective team, members of other teams, etc.). Performance parameters can include task type, worker level (e.g., seniority related to others, worker certifications, etc. Dashboard **1524** can include a worker performance monitor engine **1534** configured to actively monitor for workers who are performing in excess of or below performance standards. Engine **1534**, in turn, can include worker allocation module **1536**, worker recommendation module **1538**, and worker training module **1540**.

(101) Module **1536** can be configured similar to scorecard **1320**, whereby module **1536** can monitor and provide insights for worker allocation. In certain aspects, module **1536** can be used so that dashboard **1510** can provide worker allocation visibility (e.g., which workers have arrived for shifts, how each department of a worksite is performing related to worker allocation and status of arrived workers, etc.) and present worker allocation insights relative to expected worker allocation, expected worker performance, and/or status of related tasks. Upon monitoring and determining that allocation anomalies are present or trending to be present, corrective actions can be recommended and/or taken by corresponding worker allocation recommendation module **1538**, including practical allocation adjustments to adapt to allocation variations as they occur. Other modules are contemplated, including but not limited to a training module **1540** configured to actively present recommended training protocols for worker allocation and/or improving worker performance.

(102) In some aspects, scorecard **1316** can include and continually dynamically update lists of top performers and poor performers (e.g., top 5 and bottom 5 workers) based on performance parameters such as overall shift performance, on-standard performance, effectiveness at a respective task or sub-task, as well as engagement.

(103) A worker performance monitor and/or scorecard dashboard **1526** can also be included, similar to previously discussed scorecard dashboard **1412**. Dashboard **1526** can present information such as tracked individual workers task progress against task expectations, task performance, overall performance and the like. Other performance indicators used in dashboard **1526** tracked and used to determine individual performance metrics and related insights include but are not limited to overall performance against a predetermined plan (e.g., time worked versus number of units moved), “on standard”, percent effectiveness, attendance, engagement (e.g., determined objectively from worker computing devices), clicks per hour by the individual worker, time spent with eyes on a display screen, etc. In some aspects, similar scorecard dashboard **1412**, scorecard dashboard **1526** includes aspects which are dimensioned by task or rate of a predetermined performance parameter (e.g., frequency of updating worker preferences, frequency that worker checks their performance score, frequency of worker's career trajectory, frequency of worker performing one or more of the same tasks, etc.).

(104) Scorecard dashboard **1526** can also include individual performance quality score as well as individual worker profiles so as to facilitate viewing worker task assignments in alignment with individual worker profiles, preferences, career incentives, career promotions, etc. Profile attributes, which can be tracked and used to populate worker profiles and related profile insights, include but are not limited to worker profile picture, name, salary, role, functional area, work schedule, days at a job, preferences, work groups, certifications, hours active, location preference, career trajectory, seniority, etc.

(105) Scorecard dashboard **1526** can also include or be in communication with worker engagement advisor dashboard **1528**. Dashboard **1528** can include aspects, such as logic and analytics, to determine individual worker satisfaction based on objective satisfaction parameters detected from worker computing devices and/or sensor devices to track worker engagement and performance. Based on insights determined by or in connection with dashboard **1528**, a connect-to-task engine **1542** can prompt specific real-time recommendations for workers to get back on or otherwise improve task performance of one or more specific tasks.

(106) Scorecard dashboard **1526** can also include or be in communication with schedule delay monitor **1530**. Monitor **1530** in turn can include aspects, such as logic and analytics, to determine

or otherwise present information related to workers, including high-value workers and low-value workers, who according to schedule delays scores and/or related schedule delay insights are potential schedule delays. In some aspects, schedule delay scores and/or related schedule delay insights can be calculated based on aggregated data measuring worker engagement and performance.

(107) FIG. **16A** depicts an example user enterprise warehouse management interface **1600** including a plurality of selectable dashboards. The dashboards of interface **1600** can include a warehouse performance management dashboard **1602**, a site operations dashboard **1603**, an asset performance dashboard **1604**, a trends and events dashboard **1605**, a worker dashboard **1606** which can include a worker performance dashboard **1640**, and a worker overview performance dashboard **1610**. In some aspects, one or more of the plurality of dashboards of interface **1600** can be positioned in a single frame or multiple frames. In certain aspects, each of the dashboards of interface **1600** can be positioned as tiles capable of being toggled to enlarge or otherwise accessed by user. Interface **1600** can also present sub-dashboards key performance indicator (KPI) summaries (e.g., with names and/or one or more KPI summaries and related metrics).

(108) FIG. **16B** depicts example user interface dashboard **1610** associated with interface **1600**. As shown, dashboard **1610** can present information of an overall worker overview including a plurality of worker information and related KPIs. For example and without limitation, dashboard **1610** can include a list of one or more workers **1612** currently at the job site, present associated status **1616** (e.g., active, inactive, on break, idle, etc.) for each of the one or more workers **1612**, the area **1620** of a respective worker at the job site (e.g., shipping area, picking area, packing area, etc.), a color coded user time indicator **1624**, idle time **1628** for each worker relative to current shift, performance percentage **1632** per worker, and effectiveness percentage **1636** per worker.

Dashboard **1610** can also include one or more filter options to facilitate viewing of aspects thereof.

(109) FIG. **16C** depicts example user interface dashboard **1640** associated with interface **1600**. As shown, dashboard **1640** can present information related to worker performance including overall active worker KPIs such as active worker metrics **1650** (e.g., percent performance, number of active workers versus available workers), production rate **1654** (e.g., units per hour for the job site, KPIs related to production rates of workers, production trends, etc), and/or the like. One or more individual worker performance dashboards **1642**, **1644**, **1646** can also be provided. Each dashboard **1642**, **1644**, **1646** can indicate information related to a respective worker, including worker name, worker picture, and worker KPIs such as rates of effectiveness, on standard, idle time, production, site location, and task progress. One or more graphical performance interfaces can also be included in dashboards **1642**, **1644**, **1646**, such as line graphs comparing KPIs of workers (e.g., top performers, bottom performers, etc.). Dashboard **1640** can also include one or more filter options to facilitate viewing of aspects thereof.

(110) Aspects of FIGS. **1-16C** are advantageous for measuring Worker assignment/task progress in contextually relevant dimensions, visualize in real-time, and alert users (e.g., supervisor(s) and/or stakeholder(s)) upon identified anomalous trend deviations from rates of worker KPIs.

(111) Various embodiments of the present disclosure (e.g., edge systems, gateway systems, operations centers, remote systems, warehouse systems, connected worker systems, etc.), as described above with reference to FIGS. **1-16C** may be implemented using device **1700** in FIG. **17**. After reading this description, it will become apparent to a person skilled in the relevant art how to implement embodiments of the present disclosure using other computer systems and/or computer architectures. Although operations may be described as a sequential process, some of the operations may in fact be performed in parallel, concurrently, and/or in a distributed environment, and with program code stored locally or remotely for access by single or multi-processor machines. In addition, in some embodiments the order of operations may be rearranged without departing from the spirit of the disclosed subject matter.

(112) As shown in FIG. **17**, device **1700** may include a central processing unit (CPU) **1720**. CPU

1720 may be any type of processor device including, for example, any type of special purpose or a general purpose microprocessor device. As will be appreciated by persons skilled in the relevant art, CPU **1720** also may be a single processor in a multi-core/multiprocessor system, such system operating alone, or in a cluster of computing devices operating in a cluster or server farm. CPU **1720** may be connected to a data communication infrastructure **1710**, for example, a bus, message queue, network, or multi-core message-passing scheme.

(113) Device **1700** may also include a main memory **1740**, for example, random access memory (RAM), and may also include a secondary memory **1730**. Secondary memory **1730**, e.g., a read-only memory (ROM), may be, for example, a hard disk drive or a removable storage drive. Such a removable storage drive may comprise, for example, a floppy disk drive, a magnetic tape drive, an optical disk drive, a flash memory, or the like. The removable storage drive in this example reads from and/or writes to a removable storage unit in a well-known manner. The removable storage unit may comprise a floppy disk, magnetic tape, optical disk, etc., which is read by and written to by the removable storage drive. As will be appreciated by persons skilled in the relevant art, such a removable storage unit generally includes a computer usable storage medium having stored therein computer software and/or data.

(114) In alternative implementations, secondary memory **1730** may include other similar means for allowing computer programs or other instructions to be loaded into device **1700**. Examples of such means may include a program cartridge and cartridge interface (such as that found in video game devices), a removable memory chip (such as an EPROM, or PROM) and associated socket, and other removable storage units and interfaces, which allow software and data to be transferred from a removable storage unit to device **1700**.

(115) Device **1700** may also include a communications interface (“COM”) **1760**. Communications interface **1760** allows software and data to be transferred between device **1700** and external devices. Communications interface **1760** may include a modem, a network interface (such as an Ethernet card), a communications port, a PCMCIA slot and card, or the like. Software and data transferred via communications interface **1760** may be in the form of signals, which may be electronic, electromagnetic, optical, or other signals capable of being received by communications interface **1760**. These signals may be provided to communications interface **1760** via a communications path of device **1700**, which may be implemented using, for example, wire or cable, fiber optics, a phone line, a cellular phone link, an RF link or other communications channels.

(116) The hardware elements, operating systems and programming languages of such equipment are conventional in nature, and it is presumed that those skilled in the art are adequately familiar therewith. Device **1700** also may include input and output ports **1750** to connect with input and output devices such as keyboards, mice, touchscreens, monitors, displays, etc. Of course, the various server functions may be implemented in a distributed fashion on a number of similar platforms, to distribute the processing load. Alternatively, the servers may be implemented by appropriate programming of one computer hardware platform.

(117) The systems and methods of this disclosure can be cloud-based, multi-tenant solutions configured to deliver optimized work instructions tailored for specific vertical workflows utilizing an easy to deploy, scalable, and configurable data model and software suite to deliver performance insights and improve worker productivity.

(118) The disclosure provides one or more user interface systems for smart worker performance scoring and evaluation of a job site (e.g., one or more warehouses), whereby information from sensors and/or connected worker computing devices may provide dynamic data about job performance (e.g., productivity of worker(s), task productivity, production productivity, etc.), a processor and database(s) for receiving and processing the dynamic data, and having a program that aggregates and analyzes the dynamic data for one or more categories of the one or more worker performance. The data analysis may determine performance scores for each of the one or

more performance categories, and calculate an overall worker performance score. The worker performance score for each category of this disclosure may be displayed on a dashboard and/or related scorecards. In some aspects, one or more functions are used to calculate scores (e.g., assigning a coefficient factor to values of categories such as time on task, time between tasks, number of tasks completed, idle state, etc.). The coefficient factor may be determined from a comparison value based on some predetermined standard and/or worker performance historical data of the one or more categories. Any of the herein disclosed dashboards and related user interfaces may present worker performance scores and related details of the dynamic data for detecting and solving worker performance issues (e.g., recommended corrective actions) without changing the dashboard or the monitor.

(119) The worker performance scores of this disclosure can include numerous scores and sub-scores, including performance scores, environmental scores related to the job site and/or areas of a job site (e.g., utility consumption, carbon footprint, emissions, etc.), health scores, safety scores, maintenance scores, job site asset scores, happiness scores, etc. Such scores are also advantageous for use in using trained machine learning models to predict performance impacts depending on trends of all such scores of this disclosure.

(120) Other embodiments of the disclosure will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

Claims

1. A system for controlling worker performance in a warehouse, comprising: a plurality of sensor devices located throughout the warehouse and connected over a network; a plurality of worker computing devices, each worker computing device corresponding to at least one of a plurality of workers of the warehouse; a memory connected to the network; a user interface connected to the network and including a display configured to display a real-time dashboard comprising a menu displaying a plurality of worker performance metrics in the warehouse; and a processor connected to the network configured to: determine, by an insight module, a dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from the sensor devices and the worker computing devices; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, the plurality of worker performance metrics, the plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity score, an aggregated idle time per worker; determine, using a schedule delay monitor, a schedule delay score associated with the plurality of workers; store the schedule delay score associated with the plurality of workers in a storage service connected to the network; generate on the dashboard of the display a dynamic real-time summary of the plurality of worker performance metrics, wherein the dynamic real-time summary comprises a management view option (MVO) performance scorecard dashboard comprising a first dynamically updated performance dashboard indicative of the schedule delay score; generate on the dashboard of the display a plurality of selectable dashboard tiles, wherein the plurality of selectable dashboard tiles comprises a selectable worker performance dashboard tile corresponding to one or more of the plurality of worker performance metrics; receive, via the display, a toggle operation corresponding to the selectable worker performance dashboard tile; expand, based on the toggle operation, the selectable worker performance dashboard tile to render on the dashboard of the display a worker performance dashboard comprising a first subsidiary worker performance metric interface component and a second subsidiary worker performance metric interface component, wherein the first subsidiary worker performance metric interface component is configured to display a first

worker performance metric of the plurality of worker performance metrics and the second subsidiary worker performance metric interface component is configured to display a second worker performance metric of the plurality of worker performance metrics; and assign, based on at least one of the first worker performance metric displayed on the first subsidiary worker performance metric interface component or the second worker performance metric displayed on the second subsidiary worker performance metric interface component, at least one task or at least one equipment.

2. The system of claim 1, wherein the insight module determines the plurality of worker performance metrics by aggregating and analyzing data from a plurality of connected warehouse service systems, a plurality of connected performance management systems, a connected labor management system (LMS), and a gateway device, and wherein the plurality of worker performance metrics comprise one or more worker performance scores.

3. The system of claim 2, wherein the processor is configured to: upon determining whether the plurality of worker performance metrics are below a performance standard and/or satisfy a key performance indicator (KPI) target deviation, generate on the dashboard of the display a dynamic corrective action to resolve one or more fault or anomalous worker performance symptom attributes.

4. The system of claim 2, wherein the processor is configured to: connect the plurality of sensor devices to one or more Internet-of-Things (IoT) devices connected to the gateway device, the plurality of sensor devices including one or a combination of leak detection sensors, vibration sensors, and process sensors of the connected warehouse.

5. The system of claim 1, wherein the dynamic real-time summary further comprises at least one of an overall workforce scorecard dashboard and an individual worker scorecard dashboard.

6. The system of claim 5, wherein the overall workforce scorecard dashboard comprises a plurality of dynamically updated performance notifications comprising at least one of a workforce startup module, an idle worker scorecard, a top/poor performer scorecard, a recent hire scorecard, and a worker allocation scorecard.

7. The system of claim 5, wherein the individual worker scorecard dashboard comprises a dynamically updated notifications, and wherein the processor is configured to, upon determining whether worker performance metrics of an assigned task of a first worker of the plurality of workers satisfy a key performance indicator (KPI) task target deviation and/or a task performance standard, generate dynamic individual performance insights on the individual worker scorecard dashboard of the display.

8. The system of claim 5, wherein the MVO performance scorecard dashboard comprises a plurality of dynamically updated performance dashboards viewable by a management user and comprising at least one of a startup advisor dashboard, an idle worker advisor dashboard, and a worker performance monitor and/or scorecard dashboard.

9. The system of claim 1, wherein the plurality of worker performance metrics comprise a smart warehouse score summarizing overall warehouse workforce performance scores in real-time.

10. The system of claim 1, wherein the storage service comprises a real-time analytics database in which the schedule delay score is stored.

11. The system of claim 1, wherein the processor is configured to: determine, using the schedule delay monitor, an updated schedule delay score associated with the plurality of workers; and update, in real-time, the first dynamically updated performance dashboard to be indicative of the updated schedule delay score.

12. A computer implemented method of operating a connected warehouse by performing, by at least one processor, operations comprising: determine, by an insight module, a dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from a plurality of sensor devices located throughout the warehouse and connected over a network and a plurality of worker computing

devices, each worker computing device corresponding to at least one of a plurality of workers of the warehouse; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, a plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity score, an aggregated idle time per worker; determining, using a schedule delay monitor, a schedule delay score associated with the plurality of workers; storing the schedule delay score associated with the plurality of workers in a storage service connected to the network; generate on a real-time dashboard of a display a dynamic real-time summary of the plurality of worker performance metrics, the display being on a user interface connected to the network, wherein the dynamic real-time summary comprises a management view option (MVO) performance scorecard dashboard comprising a first dynamically updated performance dashboard indicative of the schedule delay score; generate on the dashboard of the display a plurality of selectable dashboard tiles, wherein the plurality of selectable dashboard tiles comprises a selectable worker performance dashboard tile corresponding to one or more of the plurality of worker performance metrics; receive, via the display, a toggle operation corresponding to the selectable worker performance dashboard tile; expand, based on the toggle operation, the selectable worker performance dashboard tile to render on the dashboard of the display a worker performance dashboard comprising a first subsidiary worker performance metric interface component and a second subsidiary worker performance metric interface component, wherein the first subsidiary worker performance metric interface component is configured to display a first worker performance metric of the plurality of worker performance metrics and the second subsidiary worker performance metric interface component is configured to display a second worker performance metric of the plurality of worker performance metrics; and assign, based on at least one of the first worker performance metric displayed on the first subsidiary worker performance metric interface component or the second worker performance metric displayed on the second subsidiary worker performance metric interface component, at least one task or at least one equipment.

13. The method of claim 12, wherein the insight module determines the plurality of worker performance metrics by aggregating and analyzing data from a plurality of connected warehouse service systems, a plurality of connected performance management systems, a connected labor management system (LMS), and a gateway device, and wherein the plurality of worker performance metrics comprise one or more worker performance scores.

14. The method of claim 13, further comprising: upon determining whether the plurality of worker performance metrics are below a performance standard and/or satisfy a key performance indicator (KPI) target deviation, generating on the dashboard of the display a dynamic corrective action to resolve one or more fault or anomalous worker performance symptom attributes.

15. The method of claim 12, wherein the dynamic real-time summary further comprises at least one of an overall workforce scorecard dashboard and an individual worker scorecard dashboard.

16. The method of claim 15, wherein the overall workforce scorecard dashboard comprises a plurality of dynamically updated performance scorecards comprising at least one of a workforce startup module, an idle worker scorecard, a top/poor performer scorecard, a recent hire scorecard, and a worker allocation scorecard.

17. The method of claim 15, wherein the individual worker scorecard dashboard comprises a dynamically updated scorecard, wherein the method further comprises: upon determining whether worker performance metrics of an assigned task of a first worker of the plurality of workers satisfy a key performance indicator (KPI) task target deviation and/or a task performance standard, generate dynamic individual performance insights on the individual worker scorecard dashboard of the display.

18. The method of claim 15, wherein the MVO performance scorecard dashboard comprises a plurality of dynamically updated performance dashboards viewable by a management user and comprising at least one of a startup advisor dashboard, an idle worker advisor dashboard, and a

worker performance monitor and/or scorecard dashboard.

19. A system for exchanging real-time worker performance data in a connected warehouse, comprising: one or more processors; and a non-transitory computer readable medium storing instructions that, when executed by the one or more processors, cause the one or more processors to perform: determine, by an insight module, a dynamic allocation of workers of the warehouse according to locations within the warehouse, wherein the insight module is configured to aggregate and analyze data from a plurality of sensor devices located throughout the warehouse and connected over a network and a plurality of worker computing devices, each worker computing device corresponding to at least one of a plurality of workers of the warehouse; determine, by the insight module based on data aggregated in real-time from the sensor devices and the worker computing devices, a plurality of worker performance metrics comprising at least one of a dynamic worker performance score, a worker productivity score, an aggregated idle time per worker; determine, using a schedule delay monitor, a schedule delay score associated with the plurality of workers; store the schedule delay score associated with the plurality of workers in a storage service connected to the network; generate on a real-time dashboard of a display a dynamic real-time summary of the plurality of worker performance metrics, the display being on a user interface connected to the network, wherein the dynamic real-time summary comprises a management view option (MVO) performance scorecard dashboard comprising a first dynamically updated performance dashboard indicative of the schedule delay score; generate on the dashboard of the display a plurality of selectable dashboard tiles, wherein the plurality of selectable dashboard tiles comprises a selectable worker performance dashboard tile corresponding to one or more of the plurality of worker performance metrics; receive, via the display, a toggle operation corresponding to the selectable worker performance dashboard tile; expand, based on the toggle operation, the selectable worker performance dashboard tile to render on the dashboard of the display a worker performance dashboard comprising a first subsidiary worker performance metric interface component and a second subsidiary worker performance metric interface component, wherein the first subsidiary worker performance metric interface component is configured to display a first worker performance metric of the plurality of worker performance metrics and the second subsidiary worker performance metric interface component is configured to display a second worker performance metric of the plurality of worker performance metrics; and assign, based on at least one of the first worker performance metric displayed on the first subsidiary worker performance metric interface component or the second worker performance metric displayed on the second subsidiary worker performance metric interface component, at least one task or at least one equipment.

20. The system of claim 19, wherein the insight module determines the plurality of worker performance metrics by aggregating and analyzing data from a plurality of connected warehouse service systems, a plurality of connected performance management systems, a connected labor management system (LMS), and a gateway device, and wherein the plurality of worker performance metrics comprise one or more worker performance scores; and wherein the processor is configured to, upon determining whether the plurality of worker performance metrics are below a performance standard and/or satisfy a key performance indicator (KPI) target deviation, generating on the dashboard of the display a dynamic corrective action to resolve one or more fault or anomalous worker performance symptom attributes.
