

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418983
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Noguchi; Koji et al.

Electronic module and apparatus

Abstract

An electronic module includes a rigid printed circuit member having a first electrode, a flexible printed wiring member having a second electrode, and a solder member having first, second, and third portions. A first direction is perpendicular to, and a second direction is parallel to, a joined surface between the first electrode and the solder member. In the first direction, a second region of the first electrode partially overlaps a leading edge of the second electrode. In the second direction, the second portion is located between the first portion and the third portion and is continuous to each of the first portion and the third portion. A height of the third portion from a reference surface including the joined surface is larger than a height of the second portion from the reference surface and is smaller than a height of the first portion from the reference surface.

Inventors: Noguchi; Koji (Tokyo, JP), Higuchi; Satoru (Tokyo, JP), Hasegawa; Mitsutoshi (Kanagawa, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 1000008819904

Assignee: Canon Kabushiki Kaisha (Tokyo, JP)

Appl. No.: 18/187311

Filed: March 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230319996 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2022-056601	Mar. 30, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: H05K1/18 (20060101); H05K1/14 (20060101)

U.S. Cl.:

CPC H05K1/147 (20130101); H05K1/181 (20130101);

Field of Classification Search

CPC: H05K (1/147); H05K (1/181)

USPC: 361/749

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6829398	12/2003	Ouchi	385/129	G02B 6/4214

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H0685454	12/1993	JP	N/A
H1027957	12/1997	JP	N/A
2006245108	12/2005	JP	N/A
2006253569	12/2005	JP	N/A
2008112911	12/2007	JP	N/A
2012195538	12/2011	JP	N/A
2017017318	12/2016	JP	N/A
2021168378	12/2020	JP	N/A

Primary Examiner: Tran; Binh B

Attorney, Agent or Firm: Canon U.S.A., Inc. IP Division

Background/Summary

BACKGROUND

Field

(1) The present disclosure relates to an electronic module having a configuration in which a flexible printed wiring member is joined to a rigid printed wiring member with solder.

Description of the Related Art

(2) A technique for joining a flexible printed wiring member to a rigid printed wiring member with solder is known. Japanese Patent Application Laid-Open No. 2021-168378 discusses an imaging sensor module having a configuration in which a flexible wiring board is connected to a printed wiring board with solder at a connection portion.

(3) In the technique for joining a flexible printed wiring member to a rigid printed wiring member with solder, it is desirable to improve the strength of the connection portion between the printed

wiring board and the flexible wiring substrate.

SUMMARY

(4) The present disclosure is directed to providing a technique advantageous in improving a connection strength between a rigid printed wiring member and a flexible printed wiring member.

(5) According to an aspect of the present disclosure, an electronic module includes a rigid printed circuit member including a first electrode, a flexible printed wiring member including a second electrode, and a solder member joined to each of the first electrode and the second electrode, wherein, in a case where a direction perpendicular to a joined surface between the first electrode and the solder member is a first direction and a direction parallel to the joined surface between the first electrode and the solder member is a second direction, the solder member includes a first portion located between the rigid printed circuit member and a first region of the second electrode in the first direction, wherein the first portion includes one end of a joined surface between the second electrode and the solder member, a second portion located between a first region of the first electrode and a second region of the second electrode in the first direction, and a third portion located on a second region of the first electrode in the first direction, wherein the third portion includes one end of the joined surface between the first electrode and the solder member, wherein, in the first direction, the second region of the first electrode partially overlaps a leading edge of the second electrode, wherein, in the second direction, the second portion is located between the first portion and the third portion and is continuous to each of the first portion and the third portion, and wherein a height of the third portion from a reference surface including the joined surface between the first electrode and the solder member is larger than a height of the second portion from the reference surface and is smaller than a height of the first portion from the reference surface.

(6) Further features of the present disclosure will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIGS. 1A and 1B are schematic views each illustrating an electronic module.

(2) FIG. 2 is a schematic view illustrating an electronic module.

(3) FIGS. 3A to 3G are schematic views each illustrating an electronic module.

(4) FIGS. 4A and 4B are schematic views each illustrating an electronic module.

(5) FIGS. 5A and 5B are schematic views each illustrating an image capturing unit.

(6) FIGS. 6A and 6B are schematic views each illustrating an image capturing unit.

(7) FIG. 7 is a schematic view illustrating an electronic apparatus.

DESCRIPTION OF THE EMBODIMENTS

(8) Exemplary embodiments of the present disclosure will be described below with reference to the drawings. In the following description and the drawings, components common among a plurality of drawings are denoted by the same reference numerals.

(9) Accordingly, the common components will be described with cross reference to a plurality of drawings, and the description of the components denoted by the same reference numerals will be omitted as appropriate.

(10) FIGS. 1A and 1B are partially enlarged schematic views of an electronic module **14**. The electronic module **14** includes a circuit member **11** and a wiring member **12**. The circuit member **11** includes a pad electrode **9**. The wiring member **12** includes a connection electrode **4**. The electronic module **14** includes a solder member **5** that is joined to each of the pad electrode **9** and the connection electrode **4**. The circuit member **11** and the wiring member **12** are electrically and mechanically connected with the solder member **5**. FIG. 1A is an enlarged view of a connection portion **10** that includes the solder member **5** and electrically and mechanically connects the circuit

member **11** and the wiring member **12**. The circuit member **11** is a rigid printed circuit member. The rigid printed circuit member is hereinafter abbreviated as the circuit member **11**. The circuit member **11** is called a printed circuit board (PCB), and is also called a rigid printed wiring member. A predetermined wiring pattern is formed on the circuit member **11**. Circuit components, such as integrated circuit components and passive components, are mounted on the circuit member **11**. The wiring member **12** is a flexible printed wiring member. The flexible printed wiring member is hereinafter abbreviated as the wiring member **12**. The wiring member **12** has a configuration in which a predetermined wiring pattern is formed on a flexible insulating substrate. The wiring member **12** is called flexible printed circuits (FPC), and is also called a flexible printed circuit member. Two or more wiring members **12** can be connected to the circuit member **11**.

(11) The circuit member **11** includes an insulating substrate **6** and a conductive layer **7** that is supported on the insulating substrate **6**. An insulating layer **8** covers each of the insulating substrate **6** and the conductive layer **7**. The insulating layer **8** is provided with an opening **80** between a backward insulating portion **81** and a forward insulating portion **82** of the insulating layer **8**. The pad electrode **9** corresponds to a portion of the conductive layer **7** that is not covered with the insulating layer **8**, that is, a portion located below the opening **80**. At least a part of the solder member **5** is located between the backward insulating portion **81** of the insulating layer **8** and the forward insulating portion **82** of the insulating layer **8**.

(12) The wiring member **12** includes an insulating base material **1** and a wiring layer **2** supported on the insulating base material **1**. A cover lay **3** covers the insulating base material **1** and the wiring layer **2**. The wiring layer **2** is located between the insulating base material **1** and the cover lay **3**. The connection electrode **4** corresponds to a portion of the wiring layer **2** that is not covered with the cover lay **3**.

(13) The following description is given assuming that a direction perpendicular to a joined surface between the pad electrode **9** and the solder member **5** is defined as a Z-direction, and directions parallel to the joined surface between the pad electrode **9** and the solder member **5** are defined as an X-direction and a Y-direction. The X-direction and the Y-direction cross the Z-direction or are typically perpendicular to the Z-direction. In the X-direction, the backward insulating portion **81** and the forward insulating portion **82** are located side by side through the opening **80**. The direction that crosses the X-direction is defined as the Y-direction. The direction that crosses the X-direction is typically perpendicular to the Y-direction. A +X-direction is referred to as a forward direction and a -X-direction is referred to as a backward direction.

(14) An exemplary embodiment is described assuming that the connection portion **10** is divided into a plurality of regions in the X-direction. The connection portion **10** is divided into a backward region **26**, an intermediate region **27**, and a forward region **28**. The intermediate region **27** is located between the backward region **26** and the forward region **28**. The forward region **28** includes a leading edge of the connection electrode **4**.

(15) The intermediate region **27** can be continuous to each of the backward region **26** and the forward region **28**. The backward region **26**, the intermediate region **27**, and the forward region **28** each include a region or a portion where the pad electrode **9** or the solder member **5** overlaps the corresponding connection electrode **4** in the Z-direction.

(16) The backward region **26** includes a backward region **91** of the pad electrode **9**, a backward region **41** of the connection electrode **4**, and a backward portion **51** of the solder member **5**. The backward region **91** of the pad electrode **9** includes a first backward region **96** and a second backward region **97**. The backward region **41** of the connection electrode **4** includes a first backward region **46**, a second backward region **47**, and a third backward region **48**. The backward portion **51** of the solder member **5** includes a first backward portion **56**, a second backward portion **57**, and a third backward portion **58**.

(17) In the X-direction, the first backward region **96** is located between the second backward region **97** and an intermediate region **92**. The first backward region **96** is continuous to each of the second

backward region **97** and the intermediate region **92**. The second backward region **47** is located between the first backward region **46** and the third backward region **48**. The second backward region **47** can be continuous to each of the first backward region **46** and the third backward region **48**. The first backward region **46** is located between the second backward region **47** and an intermediate region **42**. The first backward region **46** can be continuous to each of the second backward region **47** and the intermediate region **42**. The second backward portion **57** is located between the first backward portion **56** and the third backward portion **58**. The second backward portion **57** can be continuous to each of the first backward portion **56** and the third backward portion **58**. In the X-direction, the first backward portion **56** is located between the second backward portion **57** and an intermediate portion **52**. The first backward portion **56** can be continuous to each of the second backward portion **57** and the intermediate portion **52**.

(18) In the Z-direction, the backward portion **51** of the solder member **5** is located between the circuit member **11** and the backward region **41** of the connection electrode **4**. The backward portion **51** is joined to each of the backward region **41** and the backward region **91**. In the Z-direction, the first backward portion **56** of the solder member **5** is located between the first backward region **96** of the pad electrode **9** and the first backward region **46** of the connection electrode **4**. In the Z-direction, the second backward portion **57** of the solder member **5** is located between the second backward region **97** of the pad electrode **9** and the second backward region **47** of the connection electrode **4**.

(19) The first backward portion **56** is joined to each of the first backward region **46** and the first backward region **96**. In contrast, the second backward portion **57** is joined to the second backward region **47** and is spaced apart from the second backward region **97**.

(20) A boundary portion between the first backward region **96** and the second backward region **97** can be determined based on whether these regions are joined with the solder member **5**.

Specifically, in the backward region **91**, the first backward region **96** is joined with the solder member **5** and the second backward region **97** is not joined with the solder member **5**.

(21) In the Z-direction, the third backward portion **58** of the solder member **5** is located between the backward insulating portion **81** of the insulating layer **8** and the third backward region **48** of the connection electrode **4**. The third backward portion **58** is joined to the third backward region **48**. In the Z-direction, the backward insulating portion **81** of the insulating layer **8** is located between the conductive layer **7** and the backward portion **51**. Specifically, in the Z-direction, the backward insulating portion **81** of the insulating layer **8** is located between the conductive layer **7** and the third backward portion **58**. A boundary portion between the second backward region **47** and the third backward region **48** can be determined based on whether these regions overlap the insulating layer **8**. Specifically, in the backward region **41**, the third backward region **48** overlaps the insulating layer **8** and the second backward region **47** does not overlap the insulating layer **8**.

(22) The intermediate region **27** includes the intermediate region **92** of the pad electrode **9**, the intermediate region **42** of the connection electrode **4**, and the intermediate portion **52** of the solder member **5**.

(23) In the X-direction, the intermediate region **92** of the pad electrode **9** is located between the backward region **91** of the pad electrode **9** and a forward region **93** of the pad electrode **9**. The intermediate region **92** of the pad electrode **9** can be continuous to each of the backward region **91** of the pad electrode **9** and the forward region **93** of the pad electrode **9**. In the X-direction, the intermediate portion **52** of the solder member **5** is located between the backward portion **51** of the solder member **5** and a forward portion **53** of the solder member **5**. The intermediate portion **52** of the solder member **5** can be continuous to each of the backward portion **51** of the solder member **5** and the forward portion **53** of the solder member **5**.

(24) In the Z-direction, the intermediate portion **52** of the solder member **5** is located between the intermediate region **92** of the pad electrode **9** and the intermediate region **42** of the connection electrode **4**. The intermediate portion **52** is joined to each of the intermediate region **42** and the

intermediate region **92**.

(25) The forward region **28** includes the forward region **93** of the pad electrode **9**, a forward region **43** of the connection electrode **4**, and the forward portion **53** of the solder member **5**. The forward region **28** and the forward region **43** each include a leading edge **40** of the connection electrode **4**. The forward region **93** of the pad electrode **9** includes a first forward region **94** and a second forward region **95**. The forward portion **53** of the solder member **5** includes a first forward portion **54** and a second forward portion **55**.

(26) In the X-direction, the first forward region **94** is located between the second forward region **95** and the intermediate region **92**. The first forward region **94** can be continuous to the second forward region **95** and the intermediate region **92**. In the X-direction, the first forward portion **54** is located between the second forward portion **55** and the intermediate portion **52**. The first forward portion **54** can be continuous to each of the second forward portion **55** and the intermediate portion **52**.

(27) In the Z-direction, the forward portion **53** of the solder member **5** is located above the forward region **93** of the pad electrode **9**. In the Z-direction, the leading edge **40** of the connection electrode **4** is located above the forward region **93** of the pad electrode **9**. Accordingly, in the Z-direction, a part of the forward region **93** of the pad electrode **9** overlaps the leading edge **40** of the connection electrode **4**. A part of the forward region **93** of the pad electrode **9** that overlaps the leading edge **40** of the connection electrode **4** can correspond to a boundary portion between the first forward region **94** and the second forward region **95**. In the Z-direction, the first forward portion **54** of the solder member **5** is located between the first forward region **94** of the pad electrode **9** and the forward region **43** of the connection electrode **4**. In the Z-direction, the second forward portion **55** of the solder member **5** is located above the second forward region **95** of the pad electrode **9**, does not overlap the connection electrode **4**, and is not located between the connection electrode **4** and the pad electrode **9**. The boundary portion between the first forward region **94** and the second forward region **95** can be determined based on whether these regions overlap the connection electrode **4**. Specifically, in the forward region **93**, the first forward region **94** overlaps the connection electrode **4** and the second forward region **95** does not overlap the connection electrode **4**.

(28) The backward portion **51** includes one end **546** of a joined surface between the solder member **5** and the connection electrode **4**. In the present exemplary embodiment, the third backward portion **58** includes the one end **546** of the joined surface between the solder member **5** and the connection electrode **4**. The forward portion **53** includes another end **548** of the joined surface between the solder member **5** and the connection electrode **4**. In the present exemplary embodiment, the second forward portion **55** includes the other end **548** of the joined surface between the solder member **5** and the connection electrode **4**.

(29) The forward portion **53** includes one end **598** of a joined surface between the solder member **5** and the pad electrode **9**. In the present exemplary embodiment, the second forward portion **55** includes the one end **598** of the joined surface between the solder member **5** and the pad electrode **9**. The backward portion **51** includes another end **594** of the joined surface between the solder member **5** and the pad electrode **9**. In the present exemplary embodiment, the third backward portion **58** includes the other end **594** of the joined surface between the solder member **5** and the pad electrode **9**.

(30) As described above, the backward portion **51** ranges from the boundary between the backward portion **51** and the intermediate portion **52** to the one end **546**. The forward portion **53** ranges from the boundary between the forward portion **53** and the intermediate portion **52** to the one end **598**.

(31) In the X-direction, the backward portion **51** is located between the backward insulating portion **81** and the intermediate portion **52**. In the X-direction, the forward portion **53** is located between the forward insulating portion **82** and the intermediate portion **52**.

(32) FIG. 2 illustrates the height of each portion of the solder member **5** from a reference surface.

In the present exemplary embodiment, a flat surface including the joined surface between the pad electrode **9** and the solder member **5** is defined as the reference surface. The joined surface between the pad electrode **9** and the solder member **5** is formed of an alloy layer including a component metal of the pad electrode **9** and a component metal of the solder member **5**. For ease of illustration, the illustration of some of the components is omitted in FIG. **2**. The height of each portion of the solder member **5** from the reference surface is represented by the peak height of each portion of the solder member **5** from the reference surface.

(33) In the present exemplary embodiment, a height H_c of the forward portion **53** from the reference surface is larger than a height H_b of the intermediate portion **52** from the reference surface ($H_c > H_b$). A height H_a of the backward portion **51** from the reference surface is larger than the height H_b of the intermediate portion **52** from the reference surface ($H_a > H_b$). The height H_a of the backward portion **51** from the reference surface is larger than the height H_c of the forward portion **53** from the reference surface ($H_a > H_c$).

(34) Accordingly, the height H_c of the forward portion **53** from the reference surface is larger than the height H_b of the intermediate portion **52** from the reference surface, and is smaller than the height H_a of the backward portion **51** from the reference surface ($H_b < H_c < H_a$).

(35) In the example illustrated in FIG. **2**, a height H_h of the third backward portion **58** is larger than a height H_f of the first backward portion **56** ($H_h > H_f$). Accordingly, the height H_a of the backward portion **51** is defined by the height H_h . The height H_h corresponds to the height of the one end **546** illustrated in FIG. **1A**. In the example illustrated in FIG. **2**, a height H_e of the second forward portion **55** is larger than a height H_d of the first forward portion **54** ($H_d < H_e$). Accordingly, the height H_c of the forward portion **53** is defined by the height H_e . The height H_e corresponds to the height of the other end **548** illustrated in FIG. **1A**.

(36) In the connection portion **10** between the connection electrode **4** of the wiring member **12** and the solder member **5**, the region joined with the solder member **5** extends to the cover lay **3**. The maximum heights H_a and H_h in the Z-direction of the connection portion **10** of the solder member **5** on the side of the cover lay **3** from the upper surface of the pad electrode **9** are larger than the height of the leading edge of the wiring member **12**. The one end **546** of the solder member **5** on the side of the cover lay **3** in the connection portion **10** of the solder member **5** is formed on the outside of an end face of the opening of the insulating layer **8**. This configuration increases the volume of the solder member **5** (backward portion **51**) on the side of the cover lay **3** in the connection portion **10** between the connection electrode **4** and the solder member **5**, and the fillet-like solder member **5** is formed. This makes it possible to improve the strength of the connection portion **10** of the solder member **5**. In the example illustrated in FIGS. **1A** and **1B**, the joined surface between the connection electrode **4** and the solder member **5** is spaced apart from the end portion of the cover lay **3**. However, the joined surface between the connection electrode **4** and the solder member **5** can be located in contact with an end face of the cover lay **3**.

(37) All electrodes on the wiring member **12** may desirably have the shape as described in the present exemplary embodiment. However, the electrodes on the wiring member **12** may desirably have this shape at least in the connection portion **10** in the vicinity of the both ends of the wiring member **12**.

(38) The forward region **43** of the wiring member **12** can be formed to warp upward from the intermediate region **42**. Thus, the height H_c of the first forward portion **54** is larger than the height H_b of the intermediate portion **52**. The upward warping of the wiring member **12** in the forward region **28** increases the volume of the forward portion **53** (first forward portion **54**) of the solder member **5**. The increase in the volume of the solder member **5** makes it possible to bear a high load. That is, the connection strength of the connection portion **10** of the solder member **5** can be improved.

(39) The height H_d of the first forward portion **54** from the reference surface and the height H_e of the second forward portion **55** from the reference surface are larger than the height H_b of the

intermediate portion **52** from the reference surface (H_d & $H_e > H_b$). The height H_f of the first backward portion **56** from the reference surface and the height H_h of the third backward portion **58** from the reference surface are larger than the height H_b of the intermediate portion **52** from the reference surface (H_f & $H_h > H_b$).

(40) A length L_e of the second forward portion **55** in the X-direction may preferably be larger than the height H_e of the second forward portion **55** ($L_e > H_e$). A length L_d of the first forward portion **54** in the X-direction may preferably be larger than the height H_d of the first forward portion **54** in the X-direction ($L_d > H_d$).

(41) The length L_e of second forward portion **55** in the X-direction may preferably be larger than the length L_d of the first forward portion **54** in the X-direction ($L_e > L_d$). In the forward region **28** of the connection portion **10**, the length in the X-direction from the leading edge of the wiring member **12** to the leading edge of the solder member **5** on the connection electrode **4** is larger than the height from the upper surface of the pad electrode **9** in the Z-direction to the peak of the connection portion **10** between the connection electrode **4** and the solder member **5**. This configuration makes it possible to distribute the load on the solder member **5** and improves the connection strength.

(42) The height H_h of the backward portion **51** from the reference surface may be preferably larger than a thickness T_a of the backward insulating portion **81**. The height of the forward portion **53** from the reference surface is smaller than a thickness T_b of the forward insulating portion **82**.

(43) This configuration improves the connection strength of the connection portion **10**.

(44) In the example illustrated in FIGS. **1A** and **1B** and FIG. **2**, a void **800** is located between the backward portion **51** and the pad electrode **9** in the Z-direction. The end face of the cover lay **3** that covers the connection electrode **4** is located on the outside of the end face of the opening **80** in the insulating layer **8** of the circuit member **11**. The solder member **5** may not be joined to a part of the connection electrode **4**. However, the void **800** may not be located between the backward portion **51** and the pad electrode **9** in the Z-direction, like in modified examples illustrated in FIGS. **3A** to **3C**.

(45) In the example illustrated in FIGS. **1A** and **1B** and FIG. **2**, the second backward portion **57** that is continuous to the first backward portion **56** that is joined to each of the connection electrode **4** and the pad electrode **9** is joined to the connection electrode **4** and is spaced apart from the pad electrode **9**. However, like in the modified example illustrated in FIG. **3A**, the second backward portion **57** can be spaced apart from the connection electrode **4** and can be joined to the pad electrode **9**.

(46) In the example illustrated in FIGS. **1A** and **1B** and FIG. **2** and the modified example illustrated in FIG. **3A**, the second backward portion **57** is spaced from one of the connection electrode **4** and the pad electrode **9**, and is provided to the other of the connection electrode **4** and the pad electrode **9**. However, like in the modified examples illustrated in FIGS. **3B** and **3C**, the third backward portion **58** and the first backward portion **56** that overlap the backward insulating portion **81** can be continuously formed without forming the second backward portion **57**.

(47) In the example illustrated in FIGS. **1A** and **1B** and FIG. **2** and the modified example illustrated in FIG. **3A**, the backward portion **51** is spaced apart from the backward insulating portion **81**. However, like in the modified examples illustrated in FIGS. **3B** and **3C**, the backward portion **51** can be in contact with the backward insulating portion **81**.

(48) In the example illustrated in FIGS. **1A** and **1B** and FIG. **2** and the modified examples illustrated in FIGS. **3B** and **3C**, the backward insulating portion **81** is located between the conductive layer **7** and the backward portion **51** in the Z-direction. However, like in the modified example illustrated in FIG. **3A**, the backward insulating portion **81** may not be located between the conductive layer **7** and the backward portion **51** in the Z-direction.

(49) In the example illustrated in FIGS. **1A** and **1B** and FIG. **2** and modified examples illustrated in FIGS. **3E** and **3F**, the second forward portion **55** is provided. However, like in a modified example

illustrated in FIG. 3D, the second forward portion 55 can be omitted if the height of the first forward portion 54 is larger than the height of the intermediate portion 52.

(50) In the example illustrated in FIGS. 1A and 1B and FIG. 2 and the modified examples illustrated in FIGS. 3D and 3F, the height of the first forward portion 54 is larger than the height of the intermediate portion 52. However, like in the modified example illustrated in FIG. 3E, the height of the first forward portion 54 cannot be larger than the height of the intermediate portion 52 if the height of the second forward portion 55 is larger than the height of the intermediate portion 52.

(51) In the example illustrated in FIGS. 1A and 1B and FIG. 2 and the modified example illustrated in FIG. 3E, the height of the second forward portion 55 is larger than the height of the first forward portion 54. However, like in the modified example illustrated in FIG. 3F, the height of the second forward portion 55 can be equal to the height of the first forward portion 54, or can be smaller than the height of the first forward portion 54.

(52) In the example illustrated in FIGS. 1A and 1B and FIG. 2 and the modified examples illustrated in FIGS. 3D and 3E, the forward portion 53 is spaced apart from the forward insulating portion 82. However, like in the modified example illustrated in FIG. 3F, the forward portion 53 can be in contact with the forward insulating portion 82. The region connected with the solder member 5 extends to the leading edge of the connection electrode 4 of the wiring member 12. The connection area between the solder member 5 and the connection electrode 4 increases. This makes it possible to reduce peeling of the solder member 5 and the wiring member 12 and improves the connection strength.

(53) As illustrated in FIG. 3G, a length L_b of the intermediate portion 52 in the X-direction can be larger than a length L_a of the backward portion 51 in the X-direction. The length L_b of the intermediate portion 52 in the X-direction can be larger than a length L_c of the forward portion 53 in the X-direction. The length L_b of the intermediate portion 52 in the X-direction can be larger than the sum (L_a+L_c) of the length L_a of the backward portion 51 in the X-direction and the length L_c of the forward portion 53 in the X-direction ($L_b>L_a+L_c$).

(54) As illustrated in FIG. 3G, the wiring member 12 can be bent to include a portion where the wiring layer 2 and the insulating base material 1 are located between the cover lay 3 and the circuit member 11. In the connection portion 10, the connection electrode 4 is located between the insulating base material 1 and the pad electrode 9. In the vicinity of the connection portion 10, the wiring layer 2 and the cover lay 3 are arranged between the insulating base material 1 and the circuit member 11. However, in a portion that is spaced apart from the connection portion 10 when the wiring member 12 is bent to be turned inside out, the wiring layer 2 and the insulating base material 1 are located between the cover lay 3 and the circuit member 11. Thus, even when the wiring member 12 is bent, a sufficient connection strength can be obtained at the connection portion 10 provided with the backward portion 51 and the forward portion 53. The load on the connection portion 10 between the wiring member 12 and the circuit member 11 can be reduced.

(55) Also, in the configuration in which the wiring member 12 is turned back once, the end portion of the cover lay 3 that covers the connection electrode 4 is located on the outside of the opening 80 in the insulating layer 8. In other words, the end portion of the cover lay 3 is located above the backward insulating portion 81.

(56) FIGS. 4A and 4B are sectional views taken along the Y-direction and including the connection portion 10. A plurality of pad electrodes 9 is arrayed along the Y-direction in the circuit member 11. The plurality of pad electrodes 9 is located between a side insulating portion 83 of the insulating layer 8 and a side insulating portion 84 of the insulating layer 8. A plurality of connection electrodes 4 is arrayed along the Y-direction in the wiring member 12. The plurality of solder members 5 is joined to any one of the plurality of pad electrodes 9 and any one of the plurality of connection electrodes 4. The plurality of solder members 5 is surrounded by the backward insulating portion 81, the forward insulating portion 82, and the side insulating portions 83 and 84.

Each of the plurality of pad electrodes **9** includes not only an opposed surface facing the corresponding connection electrode **4**, but also side surfaces **99** that face the adjacent pad electrodes **9**. The opposed surface of each pad electrode **9** facing the corresponding connection electrode **4** extends along the X-direction and the Y-direction and crosses (is orthogonal to) the Z-direction. The side surfaces **99** extend along the Z-direction and the X-direction and cross (are orthogonal to) the Y-direction. The side surfaces **99** of each pad electrode **9** face the side surfaces **99** of the adjacent pad electrodes **9**. Each of the plurality of connection electrodes **4** includes not only an opposed surface facing the corresponding pad electrode **9**, but also side surfaces **49** that face the adjacent connection electrodes **4**.

(57) The opposed surface of each connection electrode **4** facing the corresponding pad electrode **9** extends along the X-direction and the Y-direction and crosses (is orthogonal to) the Z-direction. The side surfaces **49** extend along the Z-direction and the X-direction and cross (are orthogonal to) the Y-direction. The side surfaces **49** of each connection electrode **4** face the side surfaces **49** of the adjacent connection electrodes **4**. The solder member **5** is joined to each of the side surfaces **99** of each pad electrode **9** and the side surfaces **49** of each connection electrode **4**. The solder member **5** covers the region ranging from the side surfaces of each connection electrode **4** and the side surfaces of each pad electrode **9**. This configuration makes it possible to increase the connection area of the solder member **5** and improves the connection strength of the connection portion **10**.

(58) The electronic module **14** will now be described in detail.

(59) The circuit member **11** includes the insulating substrate **6**, the conductive layer **7**, and the insulating layer **8**. The circuit member **11** is formed by stacking a plurality of conductive layers **7** through the insulating substrate **6**. Unlike the wiring member **12**, the circuit member **11** is a rigid wiring substrate.

(60) For example, the circuit member **11** can be formed of a glass epoxy material or a ceramic substrate. For example, the circuit member **11** of a land grid array (LGA) type or a ceramic leadless chip carrier (CLCC) type can also be used.

(61) While the present exemplary embodiment illustrates an example where four conductive layers **7** are formed in the circuit member **11**, the number of conductive layers **7** is not limited to four. One or more conductive layers **7** can be formed in the circuit member **11**. Specifically, four or less conductive layers **7** or four or more conductive layers **7** can be formed.

(62) The insulating substrate **6** is an insulating base material on a substrate formed of, for example, a hard composite material. Unlike the insulating base material **1**, the insulating substrate **6** is hard. An insulating material forming the insulating substrate **6** can have electrical insulating properties. The insulating substrate **6** can be, for example, a resin substrate obtained by curing resin such as epoxy resin, or a ceramic substrate formed using ceramics.

(63) Each conductive layer **7** is a conductive layer formed of metal foil such as copper foil. Each conductive layer **7** includes a wiring pattern. The conductive layers **7** are formed on one or both of the surfaces of the insulating substrate **6**. One or more conductive layers **7** are also formed in the insulating substrate **6**. FIGS. 3A to 3G and FIGS. 4A and 4B each illustrate an example where four conductive layers **7**, including two conductive layers **7** on both surfaces of the insulating substrate **6** and two conductive layers **7** in the insulating substrate **6**, are formed. A via-hole **13** that electrically connects the conductive layers **7** is formed in the insulating substrate **6**. Some of the pad electrodes **9** can be directly connected to the via-hole **13**. In the solder member **5** that connects each connection electrode **4** and each pad electrode **9**, the conductor of each of the conductive layer **7** and the via-hole **13** is made of a material having higher conductivity and thermal conductivity than those of the insulating material. The material is, for example, metal such as copper or gold.

(64) The insulating layer **8** is an insulating protective film that protects each circuit formed of the conductive layer **7**. The insulating layer **8** is formed using hardened liquid resist, film-like solder resist, or the like.

(65) The insulating layer **8** can be referred to as a solder resist layer. The insulating layer **8** is

formed to cover the conductive layers 7 on one of the surfaces to which the wiring member 12 of the circuit member 11 is connected. The insulating layer 8 is also formed to cover the conductive layers 7 on the other surface where an image capturing device 15 of the circuit member 11 is mounted.

(66) The insulating layer 8 is provided with an opening through which each conductive layer 7 is exposed. The exposed portion of each conductive layer 7 forms the corresponding pad electrode 9. The pad electrodes 9 are arranged on, for example, a central portion of the circuit member 11. The upper surface of each pad electrode 9 is electrically connected to an electrode in the wiring member 12 via the solder member 5.

(67) In the case of connecting each connection electrode 4 and each pad electrode 9 with the solder member 5, the connection electrode 4 and the pad electrode 9 can be bonded and connected to the solder member 5 in a state where the solder member 5 is heated to a melting point or higher. The solder member 5 can be, for example, paste supplied with Sn-3.0% Ag-0.5% Cu solder, Sn-58Bi solder, or the like, together with flux.

(68) The wiring member 12 includes the insulating base material 1, the wiring layer 2, and the cover lay 3. The wiring member 12 has a configuration in which one or more conductive layers are formed as the wiring layer 2, and the conductor layers are stacked as the insulating layer 8 through the insulating base material 1. While the present exemplary embodiment illustrates an example where a single conductive layer 7 is formed in the wiring member 12, the number of conductive layers 7 is not limited to one. Two or more conductive layers 7 can be formed.

(69) Although not illustrated, one or more conductive shielding layers, one or more protective films, one or more reinforcing films, or the like can be formed on one or both of the insulating base material 1 of the wiring member 12 and the cover lay 3. These layers can cover the entire surface of the wiring member 12, or can cover a part of the wiring member 12.

(70) The insulating base material 1 is a sheet-like or film-like insulating base material made of resin or the like, and has plasticity and flexibility. Accordingly, the wiring member 12 is deformable. For example, the wiring member 12 is bendable. The insulating material forming the insulating base material 1 can have electrical insulating properties. Examples of the insulating material forming the insulating base material 1 include polyimide and polyethylene terephthalate.

(71) The wiring layer 2 is a conductive layer formed of metal foil such as copper foil. The wiring layer 2 includes a wiring pattern. The wiring layer 2 is formed on one or both of the surfaces of the insulating base material 1. The conductor forming the wiring layer 2 is a material having higher conductivity and thermal conductivity than those of the insulating materials. The conductor is metal such as copper, silver, or gold. The wiring layer 2 can be formed on at least one surface of the insulating base material 1.

(72) The cover lay 3 is an insulating layer that protects each circuit formed of the wiring layer 2. The cover lay 3 is formed using a cover film or an overcoat. The cover lay 3 is formed to cover the wiring layer 2 on the surface where the wiring layer 2 of the insulating base material 1 is formed.

(73) At one of the leading edges of the wiring member 12, the cover layer 3 is not formed and the wiring layer 2 is exposed. Each connection electrode 4 is formed at an exposed portion 24 of the wiring layer 2. The surface of each connection electrode 4 can be plated with gold or tin. The plurality of connection electrodes 4 is arranged at a predetermined pitch. All the connection electrodes 4 can be arranged at the same pitch, or can be arranged at different pitches. Thus, the connection electrodes 4 are each formed of the wiring layer 2 exposed at the leading edge of the wiring member 12. One of the leading edges of the wiring member 12 at which the connection electrode 4 is formed is configured as an insertion terminal.

(74) Although not illustrated, the other one of the leading edges of the wiring member 12 can also be configured as the insertion terminal at which the connection electrode 4 is formed. Alternatively, an electrode on which a connector component having a surface mounting configuration is mounted can be exposed to the upper surface of the cover lay 3.

(75) Although not illustrated, the wiring member **12** can be provided with a foil-like or mesh-like shielding layer formed of silver or the like. Further, a protective layer for protecting the shielding layer can be formed on the shielding layer.

(76) One of the connection electrodes **4** in the wiring member **12** in which the connection electrodes **4** are formed is connected to the corresponding pad electrode **9** in the circuit member **11** via the solder member **5**. The other of the connection electrodes **4** in the wiring member **12** is connected to a connector mounted on a circuit member of a circuit unit (not illustrated) via a connector component mounted on the wiring member **12**. Alternatively, the other of the connection electrodes **4** in the wiring member **12** is inserted into the connector mounted on the circuit member of the circuit unit (not illustrated). More alternatively, the other of the connection electrodes **4** in the wiring member **12** is joined to the circuit member of the circuit unit (not illustrated) with solder. Thus, the wiring member **12** electrically connects the circuit member **11** and the circuit unit to each other.

(77) A configuration in which the electronic module **14** according to the present exemplary embodiment is used as an image capturing module and is applied to an image capturing unit **400** will now be described with reference to FIGS. 5A and 5B and FIGS. 6A and 6B. FIG. 5A is a top schematic view illustrating a schematic configuration of the image capturing unit **400**. FIG. 5B is a schematic view illustrating a schematic configuration of the image capturing unit **400** according to the present exemplary embodiment, and illustrates a sectional view taken along a line B-B' in FIG. 5A.

(78) The image capturing unit **400** includes the circuit member **11** on which the image capturing device **15** is mounted, and the wiring member **12** connected to the circuit member **11**. The image capturing unit **400** further includes a driving device **410** that drives the circuit member **11** to move. The driving device **410** provides an image stabilizer function, such as a camera-shake correction function. The electronic module **14** serving as the image capturing module includes the circuit member **11**, the image capturing device **15**, a frame body **17**, and a lid body **16**. The circuit member **11** is bonded to the frame body **17** with an adhesive, such as ultraviolet (UV)-curing resin, and is fixed to the frame body **17**. The electronic module **14** is held on the driving device **410** in such a manner that the electronic module **14** can move relative to the driving device **410** as described below.

(79) A configuration can also be employed in which the image capturing device **15** is mounted on a ceramic substrate and the ceramic substrate and the circuit member **11** are connected with a pair of electrodes via the solder member **5**. In this case, it can also be said that the image capturing device **15** is mounted on the circuit member **11**.

(80) The image capturing device **15** is a solid-state image sensor, such as a complementary metal oxide semiconductor (CMOS) image sensor or a charge-coupled device (CCD) image sensor. The image capturing device **15** is mounted on the circuit member **11** such that the image capturing device **15** is not in contact with the lid body **16** in a hollow portion surrounded by the circuit member **11**, the lid body **16** serving as a cover glass, and the frame body **17**. The frame body **17** can be made of metal or resin. The image capturing device **15** is electrically connected with a wire pad **23** of the circuit member **11** via a metal wire **18**. The wire pad **23** is plated with, for example, gold. While the present exemplary embodiment illustrates an example where the frame body **17** is mounted, the location where the frame body **17** is disposed is not limited to an upper portion in the vicinity of the circuit member **11**. A substrate can also be buried in the frame body **17** on a cavity. The image capturing device **15** can also be disposed in a structure with a counterbore, such as a cavity substrate, in which a hollow portion of the circuit member **11** is not formed.

(81) Although not illustrated, electronic components used for operation of the image capturing device **15** are mounted on the circuit member **11**. Although not illustrated, only the both ends in the width direction on the insulating base material **1**, or the front surface in the width direction can be covered with UV-curing resin, thermosetting resin, or a film-like reinforcing member. With this

configuration, the structure of the connection portion **10** of the solder member **5** and the reinforcing member **21** improve the connection strength. While FIGS. 5A and 5B illustrate an example where the wiring member **12** is mounted in parallel to the short sides of the circuit member **11**, the wiring member **12** can also be mounted in parallel to the long sides of the circuit member **11**. While FIGS. 5A and 5B illustrate an example where only one wiring member **12** is connected to the circuit member **11**, two or more wiring members **12** can also be connected. If a plurality of wiring members **12** is mounted, the wiring members **12** can be drawn out in the same direction or in different directions.

(82) The driving device **410** supports the frame body **17** such that the electronic module **14** fixed to the frame body **17** can be moved in the X-direction and the Y-direction and can be rotated in a θ -direction in the X-Y plane. The driving device **410** moves or rotates the electronic module **14** depending on a camera shake, thereby making it possible to correct the camera shake.

(83) The circuit unit connected to the wiring member **12** can be an information processing unit that processes information based on a signal obtained by the image capturing device **15**. Examples of the information based on the signal obtained by the image capturing device **15** include an image, an image feature amount, and distance information.

(84) The image capturing unit **400** according to the present exemplary embodiment has the configuration as described above.

(85) An electronic apparatus including the electronic module **14** will now be described with reference to FIG. 7. FIG. 7 is a schematic view illustrating a schematic configuration of a camera as an example of the electronic apparatus according to the present exemplary embodiment.

(86) A digital camera **100** that is an image capturing apparatus used as an example of the electronic apparatus according to the present exemplary embodiment is, for example, a lens-interchangeable mirrorless camera. The digital camera **100** includes a camera body **200** and an interchangeable lens **300** that is detachably mounted on the camera body **200**. The interchangeable lens **300** includes a lens barrel **301** and a plurality of lenses **311** accommodated in the lens barrel **301**. The circuit member **11** on which the image capturing device **15** is mounted and the wiring member **12** joined to the circuit member **11** with solder are stored in a casing **210** of the camera body **200**. The wiring member **12** is connected to a connector **430** of a circuit unit **420**. The driving device **410** is provided in the casing **210**, and the driving device **410** causes the circuit unit **420** to move the circuit member **11** relative to the circuit unit **420**. A force applied when the circuit member **11** moves relative to the circuit unit **420** is added to the connection portion **10**. However, the connection portion **10** according to the present exemplary embodiment has a high strength, and thereby the reliability can be ensured. The circuit unit **420** processes the information based on the signal obtained by the image capturing device **15**. The wiring member **12** can be configured to establish high-speed and large-capacity communication so that a large amount of information can be transferred from the image capturing device **15**. An image generated by the circuit unit **420** is displayed on a display device **450** via a wiring member **440**.

(87) The image capturing device **15** in the electronic module **14** is a solid-state image sensor, such as a CMOS image sensor or a CCD image sensor, that photoelectrically converts an optical image formed by an image capturing optical system. As described above, the digital camera **100** is configured as the image capturing apparatus including the image capturing unit **400**.

(88) As described above, according to the present exemplary embodiment, the load occurring at the connection portion **10** between the wiring member **12** and the circuit member **11** even in a case of, for example, a drop impact or carrying of the mirrorless camera, can be reduced, which leads to an improvement in performance of the camera. While the present exemplary embodiment described above illustrates an example where the interchangeable lens **300** is mounted on the camera body **200** to capture images, the present disclosure is not limited to this example. The camera body **200** on which the interchangeable lens **300** is not mounted can also be used for the electronic apparatus.

(89) While the present exemplary embodiment described above illustrates an example where the

camera is divided into the camera body **200** and the interchangeable lens **300**, an integrated camera in which lenses are incorporated in the camera body **200** can also be used.

(90) While the present exemplary embodiment described above illustrates an example where a camera is used as the image capturing apparatus as an example of the electronic apparatus, the present disclosure is not limited to this example.

Example 1

(91) The image capturing unit **400** including the connection portion **10** having the configuration illustrated in FIG. 3G in the layout configuration of the image capturing unit **400** illustrated in FIGS. 5A and 5B was produced as the image capturing unit **400** according to Example 1.

(92) In the image capturing unit **400** according to Example 1, the frame body **17** made of resin and having a thickness of 2 mm was used. As the image capturing device **15**, an image sensor having a flat rectangular surface of 30 mm×20 mm was used. As the lid body **16**, a glass plate (cover glass) having a planar rectangular shape of 28 mm×38 mm was used.

(93) The wiring member **12** having a configuration in which the insulating base material **1** and the cover lay **3** are made of a polyimide material and the wiring layer **2** and each connection electrode **4** are made of a Cu material was used. The thickness of each of the flexible wiring base material and the cover lay **3** was 12.5 μm, and the thickness of the wiring layer **2** was 12 μm.

(94) The circuit member **11** having a configuration in which the insulating substrate **6** is made of a glass epoxy material and the conductive layer **7** and each pad electrode **9** are made of a Cu material was used. The thickness of each of the conductive layer **7** and the pad electrode **9** was about 30 μm. The insulating layer **8** that is formed of film resist and has a thickness of 20 μm (Ta=Tb=20 μm) was used.

(95) As the adhesive used to fix the circuit member **11** to the metallic frame body **17**, UV-curing resin was used. The metallic frame body **17** having an outer shape of 50 mm×60 mm was used.

(96) The connection electrodes **4** in the wiring member **12** and the pad electrodes **9** in the circuit member **11** were connected with the solder member **5**. The pad electrodes **9** were arranged at a pitch of 0.2 mm. The width of each pad electrode **9** was 0.15 mm, and 80 wires were used. The size of the opening in the insulating layer **8** through which the pad electrodes **9** are exposed was 1.1 mm×20 mm. The connection electrodes **4** were arranged at a pitch of 0.2 mm. The width of each connection electrode **4** was 0.15 mm, and 80 wires were used. The size of the opening in the cover lay **3** through which the pad electrodes **9** are exposed was 1.2 mm from the leading edge. The width of the wiring member **12** was 22 mm, which was larger than the opening width of 20 mm in the insulating layer **8**. The pitch between the electrodes, the width of each electrode, and the number of electrodes were appropriately set depending on the specifications of the electronic module **14**.

(97) The solder member **5** made of Sn-3.0% Ag-0.5% Cu solder was used. The driving device **410** having an L-shape in which a rectangle of 70 mm×55 mm was cut from a rectangle of 85 mm×70 mm was used.

(98) The connection portion **10** of the solder member **5** was formed with a structure in which the leading edge and the trailing edge of the wiring member **12** warp upward. The intermediate region **42** connecting the forward region **43** and the backward region **41** of the wiring member **12** was parallel to the upper surface of the pad electrode **9**.

(99) The wiring member **12** was formed to warp upward in a range from the position that is spaced apart by 0.1 mm in the backward direction from the leading edge of the wiring member **12** to the leading edge of the wiring member **12** (Ld=0.1 mm). The leading edge of the wiring member **12** warps upward only by 2 μm from the intermediate region **42**. The height of the connection portion **10** of the solder member **5** from the corresponding pad electrode **9** below the leading edge of the wiring member **12** was 5 μm (Hd=5 μm). The solder member **5** was joined to the end face of each connection electrode **4**, and the peak height of the forward portion **53** of the solder member **5** was 17 μm (He=Hc=17 μm). The length of the second forward portion **55** of the solder member **5** was 0.08 mm (Le=0.08 mm). The height of the solder member **5** at the position that is spaced apart by

0.1 mm in the backward direction from the leading edge of the wiring member **12** was 3 μm . The height of the solder member **5** from the upper surface of the pad electrode **9** in the intermediate region **27** of the connection portion **10** of the solder member **5** was 3 μm ($H_b=3\ \mu\text{m}$). The length of the intermediate region **27** of the connection portion **10** of the solder member **5** was 0.6 mm ($L_b=0.6\ \text{mm}$). The backward region **41** of the wiring member **12** was located on the backward side of the position that is spaced apart by 0.7 mm from the leading edge of the wiring member **12** ($L_b+L_d=0.7\ \text{mm}$). The wiring member **12** warps in the +Z-direction from this position. The distance from this position to the backward insulating portion **81** of the insulating layer **8** was 0.2 mm ($L_f=0.2\ \text{mm}$). In the configuration illustrated in FIG. 3G, the first backward portion **56** illustrated in FIG. 1A is in contact with the backward insulating portion **81**. Accordingly, the second backward portion **57** illustrated in FIG. 1A is not present, and thus the third backward portion **58** and the first backward portion **56** are continuously formed. The second backward region **97** and the second backward region **47** are also not present ($L_g=0\ \text{mm}$). The height of the solder member **5** in the +Z-direction from the pad electrode **9** located immediately above the end portion on the side of the opening **80** of the backward insulating portion **81** of the insulating layer **8** was 35 μm ($H_f=35\ \mu\text{m}$). The solder member **5** was connected to the connection electrode **4** in a range from the end portion on the side of the opening **80** of the backward insulating portion **81** of the insulating layer **8** to the position that is spaced apart by 0.1 mm in the -X-direction ($L_h=0.1\ \text{mm}$). The height of the connection portion **10** between the connection electrode **4** and the solder member **5** from the upper surface of the pad electrode **9** at this position was 40 μm ($H_a=H_h=40\ \mu\text{m}$). In the image capturing apparatus incorporating the completed image capturing unit **400** according to Example 1, the satisfactory optical performance of the CMOS image sensor incorporated in the image capturing apparatus was ensured.

Example 2

(100) The image capturing unit **400** according to Example 2 differs from the image capturing unit **400** according to Example 1 in that the layout configuration of the image capturing unit **400** illustrated in FIGS. 6A and 6B was employed. In addition, the image capturing unit **400** according to Example 2 differs from the image capturing unit **400** according to Example 1 in that the wiring member **12** was drawn out on the opposite side of the driving device **410** as illustrated in FIGS. 6A and 6B and was turned back once. The other features of the image capturing unit **400** according to Example 2 may be the same as those of the image capturing unit **400** according to Example 1.

(101) In the image capturing apparatus incorporating the completed image capturing unit **400** according to Example 2, the satisfactory optical performance of the CMOS image sensor incorporated in the image capturing apparatus was ensured. According to Example 2, the load occurring at the connection portion **10** between the wiring member **12** and the circuit member **11** can be reduced even in a bent state. Although not illustrated, formation of a hemisphere or semi-elliptic UV-curing resin having a diameter of 3 mm and a height of about 1 mm at both ends of the wiring member **12** can further reduce the load occurring at the connection portion **10** of the solder member **5**.

(102) According to the exemplary embodiments described above, it is possible to provide a technique advantageous in improving a connection strength between a rigid printed wiring member and a flexible printed wiring member.

(103) The above-described exemplary embodiments can be modified, as needed, without departing from the technical idea of the disclosure. For example, a plurality of exemplary embodiments can be combined. Further, features in at least some of exemplary embodiments can be deleted or replaced. A new feature can also be added to at least one of the exemplary embodiments.

(104) The disclosed content in the present specification includes not only features expressly described in the present specification, but also all of the features which are understandable from the present specification and the drawings attached to the present specification. The disclosed content of the present specification also includes complementary sets of concepts described in the present

specification. Specifically, if there is a description in the present specification to the effect that “A is B”, for example, it is assumed that the present specification discloses or suggests that “A is not B”, even if a description to the effect that “A is not B” is omitted. This is because it is a premise that a description to the effect that “A is B” takes into consideration the case where “A is not B”. (105) While the present disclosure has been described with reference to exemplary embodiments, it is to be understood that the disclosure is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(106) This application claims the benefit of Japanese Patent Application No. 2022-056601, filed Mar. 30, 2022, which is hereby incorporated by reference herein in its entirety.

Claims

1. An electronic module comprising: a rigid printed circuit member including a first electrode; a flexible printed wiring member including a second electrode; and a solder member joined to each of the first electrode and the second electrode, wherein, in a case where a direction perpendicular to a joined surface between the first electrode and the solder member is a first direction and a direction parallel to the joined surface between the first electrode and the solder member is a second direction, the solder member includes: a first portion located between the rigid printed circuit member and a first region of the second electrode in the first direction, wherein the first portion includes one end of a joined surface between the second electrode and the solder member, a second portion located between a first region of the first electrode and a second region of the second electrode in the first direction, and a third portion located on a second region of the first electrode in the first direction, wherein the third portion includes one end of the joined surface between the first electrode and the solder member, wherein, in the first direction, the second region of the first electrode partially overlaps a leading edge of the second electrode, wherein, in the second direction, the second portion is located between the first portion and the third portion and is continuous to each of the first portion and the third portion, and wherein a height of the third portion from a reference surface including the joined surface between the first electrode and the solder member is larger than a height of the second portion from the reference surface and is smaller than a height of the first portion from the reference surface, wherein the rigid printed circuit member includes a conductive layer including the first electrode and an insulating layer covering the conductive layer, and at least a part of the solder member is located between a first insulating portion of the insulating layer and a second insulating portion of the insulating layer.
2. The electronic module according to claim 1, wherein, in the second direction, the first portion is located between the first insulating portion and the second portion, and wherein, in the second direction, the third portion is located between the second insulating portion and the second portion.
3. The electronic module according to claim 2, wherein the height of the first portion from the reference surface is larger than a thickness of the first insulating portion.
4. The electronic module according to claim 2, wherein the third portion is in contact with the second insulating portion.
5. The electronic module according to claim 2, wherein the height of the second portion from the reference surface is smaller than a thickness of the second insulating portion.
6. The electronic module according to claim 2, wherein the first portion is in contact with the first insulating portion.
7. The electronic module according to claim 2, wherein, in the first direction, the first insulating portion is located between the conductive layer and the first portion.
8. The electronic module according to claim 1, wherein, in the first direction, a void is located between the first portion and the first electrode.
9. The electronic module according to claim 1, wherein the third portion further includes a fourth

portion overlapping the second electrode in the first direction, and a height of the fourth portion from the reference surface is larger than the height of the second portion from the reference surface.

10. The electronic module according to claim 1, wherein the third portion further includes a fourth portion and a fifth portion, and the fourth portion overlaps the second electrode in the first direction and the fifth portion does not overlap the second electrode in the first direction.

11. The electronic module according to claim 1, wherein the solder member is joined to a side surface of the first electrode along the first direction and is joined to a side surface of the second electrode along the first direction.

12. An apparatus comprising: the electronic module according to claim 1; and a circuit unit connected to the rigid printed circuit member via the flexible printed wiring member.

13. The apparatus according to claim 12, further comprising a driving device configured to move the rigid printed circuit member relative to the circuit unit.

14. The apparatus according to claim 12, wherein an image capturing device is mounted on the rigid printed circuit member.

15. The apparatus according to claim 14, wherein the circuit unit is configured to process information based on a signal obtained by the image capturing device.

16. An electronic module comprising: a rigid printed circuit member including a first electrode; a flexible printed wiring member including a second electrode; and a solder member joined to each of the first electrode and the second electrode, wherein, in a case where a direction perpendicular to a joined surface between the first electrode and the solder member is a first direction and a direction parallel to the joined surface between the first electrode and the solder member is a second direction, the solder member includes: a first portion located between the rigid printed circuit member and a first region of the second electrode in the first direction, wherein the first portion includes one end of a joined surface between the second electrode and the solder member, a second portion located between a first region of the first electrode and a second region of the second electrode in the first direction, and a third portion located on a second region of the first electrode in the first direction, wherein the third portion includes one end of the joined surface between the first electrode and the solder member, wherein, in the first direction, the second region of the first electrode partially overlaps a leading edge of the second electrode, wherein, in the second direction, the second portion is located between the first portion and the third portion and is continuous to each of the first portion and the third portion, and wherein a height of the third portion from a reference surface including the joined surface between the first electrode and the solder member is larger than a height of the second portion from the reference surface and is smaller than a height of the first portion from the reference surface, wherein the electronic module satisfies at least one of conditions (i), (ii) and (iii) comprising: (i) a height of the fifth portion from the reference surface is larger than a height of the fourth portion from the reference surface; (ii) a length of the fifth portion in the second direction is larger than a height of the fifth portion from the reference surface; and (iii) a height of the fourth portion from the reference surface is larger than the height of the second portion from the reference surface.

17. An apparatus comprising: the electronic module according to claim 16; and a circuit unit connected to the rigid printed circuit member via the flexible printed wiring member.

18. The apparatus according to claim 17, further comprising a driving device configured to move the rigid printed circuit member relative to the circuit unit.

19. The apparatus according to claim 17, wherein an image capturing device is mounted on the rigid printed circuit member.

20. An electronic module comprising: a rigid printed circuit member including a first electrode; a flexible printed wiring member including a second electrode; and a solder member joined to each of the first electrode and the second electrode, wherein, in a case where a direction perpendicular to a joined surface between the first electrode and the solder member is a first direction and a direction parallel to the joined surface between the first electrode and the solder member is a

second direction, the solder member includes: a first portion located between the rigid printed circuit member and a first region of the second electrode in the first direction, wherein the first portion includes one end of a joined surface between the second electrode and the solder member, a second portion located between a first region of the first electrode and a second region of the second electrode in the first direction, and a third portion located on a second region of the first electrode in the first direction, wherein the third portion includes one end of the joined surface between the first electrode and the solder member, wherein, in the first direction, the second region of the first electrode partially overlaps a leading edge of the second electrode, wherein, in the second direction, the second portion is located between the first portion and the third portion and is continuous to each of the first portion and the third portion, and wherein a height of the third portion from a reference surface including the joined surface between the first electrode and the solder member is larger than a height of the second portion from the reference surface and is smaller than a height of the first portion from the reference surface, wherein the flexible printed wiring member includes a wiring layer including the second electrode, an insulating base material configured to support the wiring layer, and a cover lay covering the wiring layer, and wherein the wiring layer is located between the insulating base material and the cover lay, and the first electrode is located between the insulating base material and the second electrode.

21. The electronic module according to claim 20, wherein the flexible printed wiring member is bent to include a portion where the wiring layer and the insulating base material are located between the cover lay and the rigid printed circuit member.

22. An apparatus comprising: the electronic module according to claim 20; and a circuit unit connected to the rigid printed circuit member via the flexible printed wiring member.

23. The apparatus according to claim 22, further comprising a driving device configured to move the rigid printed circuit member relative to the circuit unit.

24. The apparatus according to claim 22, wherein an image capturing device is mounted on the rigid printed circuit member.

25. An apparatus comprising: a rigid printed circuit member including a first electrode; a flexible printed wiring member including a second electrode; and a solder member joined to each of the first electrode and the second electrode; and a circuit unit connected to the rigid printed circuit member via the flexible printed wiring member, wherein an image capturing device is mounted on the rigid printed circuit member, wherein, in a case where a direction perpendicular to a joined surface between the first electrode and the solder member is a first direction and a direction parallel to the joined surface between the first electrode and the solder member is a second direction, the solder member includes: a first portion located between the rigid printed circuit member and a first region of the second electrode in the first direction, wherein the first portion includes one end of a joined surface between the second electrode and the solder member, a second portion located between a first region of the first electrode and a second region of the second electrode in the first direction, and a third portion located on a second region of the first electrode in the first direction, wherein the third portion includes one end of the joined surface between the first electrode and the solder member, wherein, in the first direction, the second region of the first electrode partially overlaps a leading edge of the second electrode, wherein, in the second direction, the second portion is located between the first portion and the third portion and is continuous to each of the first portion and the third portion, and wherein a height of the third portion from a reference surface including the joined surface between the first electrode and the solder member is larger than a height of the second portion from the reference surface and is smaller than a height of the first portion from the reference surface.

26. The apparatus according to claim 25, wherein the circuit unit is configured to process information based on a signal obtained by the image capturing device.

27. The apparatus according to claim 25, wherein the rigid printed circuit member includes a conductive layer including the first electrode and an insulating layer covering the conductive layer,

and at least a part of the solder member is located between a first insulating portion of the insulating layer and a second insulating portion of the insulating layer, wherein, in the second direction, the first portion is located between the first insulating portion and the second portion, and wherein, in the second direction, the third portion is located between the second insulating portion and the second portion.

28. The apparatus according to claim 25, further comprising a driving device configured to move the rigid printed circuit member relative to the circuit unit.
