



US 20250276443A1

(19) **United States**

(12) **Patent Application Publication**
Hosek et al.

(10) **Pub. No.: US 2025/0276443 A1**

(43) **Pub. Date: Sep. 4, 2025**

(54) **ROBOT WITH SLAVED END EFFECTOR MOTION**

Publication Classification

(71) Applicant: **Persimmon Technologies Corporation**,
Wakefield, MA (US)

(51) **Int. Cl.**

B25J 9/04 (2006.01)

B25J 9/10 (2006.01)

H01L 21/677 (2006.01)

(72) Inventors: **Martin Hosek**, Salem, MA (US);
Leonard T. Lilliston, Roxbury, MA (US);
Jacob Lipcon, Arlington, MA (US)

(52) **U.S. Cl.**

CPC **B25J 9/042** (2013.01); **B25J 9/043**

(2013.01); **B25J 9/104** (2013.01); **H01L**

21/67742 (2013.01); **Y10S 901/15** (2013.01);

Y10S 901/21 (2013.01); **Y10S 901/27**

(2013.01); **Y10S 901/28** (2013.01); **Y10S**

901/29 (2013.01)

(21) Appl. No.: **19/194,098**

(22) Filed: **Apr. 30, 2025**

Related U.S. Application Data


(60) Division of application No. 18/211,810, filed on Jun. 20, 2023, now Pat. No. 12,296,473, which is a continuation of application No. 15/067,684, filed on Mar. 11, 2016, now Pat. No. 11,691,268.

(60) Provisional application No. 62/132,066, filed on Mar. 12, 2015, provisional application No. 62/135,490, filed on Mar. 19, 2015, provisional application No. 62/137,458, filed on Mar. 24, 2015, provisional application No. 62/264,436, filed on Dec. 8, 2015, provisional application No. 62/275,884, filed on Jan. 7, 2016.

(57)

ABSTRACT

An apparatus having a drive unit having a first drive axis rotatable about a first axis of rotation and a second drive axis rotatable about a second axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis. A robot arm has an upper arm connected to the drive unit at the first drive axis, a forearm coupled to the upper arm, the forearm being coupled to the upper arm at a first rotary joint and rotatable about the first rotary joint, the first rotary joint being actuatable by a first band arrangement coupled to the second drive axis, and an end effector coupled to the forearm, the end effector being coupled to the forearm at a second rotary joint and rotatable about the second rotary joint, the second rotary joint being actuatable by a second band arrangement coupled to the first rotary joint. The second band arrangement is configured to provide a variable transmission ratio.






FIG.1




FIG.4




FIG. 2





FIG. 3A






FIG. 5




FIG. 6




FIG. 10






FIG. 7







FIG. 11






FIG. 13B




FIG. 13A




FIG. 13C




FIG.14A




FIG. 14B






FIG.15B

FIG.15C

FIG.15A




FIG. 16





FIG. 17









FIG. 18B






FIG. 20B




FIG. 20A




FIG. 20C




FIG. 21B




FIG. 21A




FIG. 21C




FIG. 22







FIG. 24








FIG. 26B




FIG. 26A




FIG. 26C




FIG. 27B




FIG. 27A




FIG. 27C




FIG. 28B




FIG. 28A




FIG. 28C




FIG. 29A




FIG. 29B





FIG. 30B

FIG. 30A






FIG. 33A




FIG. 33B




FIG. 34B




FIG. 34C




FIG. 34A




FIG. 35B




FIG. 35C







FIG. 35A








FIG. 37B




FIG. 38A




FIG. 38B




FIG.48

FIG.40




FIG. 41A




FIG. 41B




FIG. 42A




FIG. 42B




FIG. 42C




FIG. 42D




FIG. 42E




FIG.43

PHASED ARM DIAGRAM, STRAIGHT LINE EXTEND, SINGLE ARM




FIG. 44




FIG.45

PHASED ARM DIAGRAM, VIA POINT EXTEND, SINGLE ARM




FIG.46




FIG.47





FIG.49A



PHASED ARM DIAGRAM, STRAIGHT LINE EXTEND, DUAL ARM




FIG.50




FIG.51

PHASED ARM DIAGRAM, VIA LINE EXTEND, SINGLE ARM




FIG.52




FIG.53

ROBOT WITH SLAVED END EFFECTOR MOTION

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application is a divisional of copending U.S. patent application Ser. No. 18/211,810 filed Jun. 20, 2023, which is a continuation of U.S. patent application No. Ser. 15/067,684 filed Mar. 11, 2016, which claims priority under 35 USC 119(e) to U.S. Provisional Patent Application No. 62/132,066 filed Mar. 12, 2015, U.S. Provisional Patent Application No. 62/135,490 filed Mar. 19, 2015, U.S. Provisional Patent Application No. 62/137,458 filed Mar. 24, 2015, U.S. Provisional Patent Application No. 62/264,436 filed Dec. 8, 2015, U.S. Provisional Patent Application No. 62/275,884 filed Jan. 7, 2016, which are hereby incorporated by reference in their entireties.

BACKGROUND

Technical Field

[0002] The exemplary and non-limiting embodiments relate generally to a robot having an end effector and, more particularly, to a robot having slaved end effector motion.

Brief Description of Prior Developments

[0003] Vacuum, atmospheric and controlled environment processing for applications such as associated with manufacturing of semiconductor, LED, Solar, MEMS or other devices utilize robotics and other forms of automation to transport substrates and carriers associated with substrates to and from storage locations, processing locations or other locations. Such transport of substrates may be moving individual substrates, groups of substrates with single arms transporting one or more substrates or with multiple arms, each transporting one or more substrate. Much of the manufacturing, for example, as associated with semiconductor manufacturing is done in a clean or vacuum environment where footprint and volume are at a premium. Further, much of the automated transport is conducted where minimization of transport times results in reduction of cycle time and increased throughput and utilization of the associated equipment.

SUMMARY

[0004] The following summary is merely intended to be exemplary. The summary is not intended to limit the scope of the claims.

[0005] In accordance with one aspect, an apparatus has a drive unit having a first drive axis rotatable about a first axis of rotation and a second drive axis rotatable about a second axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis. A robot arm has an upper arm connected to the drive unit at the first drive axis, a forearm coupled to the upper arm, the forearm being coupled to the upper arm at a first rotary joint and rotatable about the first rotary joint, the first rotary joint being actuatable by a first band arrangement coupled to the second drive axis, and an end effector coupled to the forearm, the end effector being coupled to the forearm at a joint and rotatable about the second rotary joint, the second rotary joint being actuatable

by a second band arrangement coupled to the first rotary joint. The second band arrangement is configured to provide a variable transmission ratio.

[0006] In accordance with another aspect, an apparatus has a drive unit having a first drive axis rotatable about a first axis of rotation, a second drive axis rotatable about a second axis of rotation, and a third drive axis rotatable about a third axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis, and the third drive axis being coaxial with and partially within the second drive axis and axially rotatable within the second drive axis. A robot arm has an upper arm connected to the drive unit at the first drive axis, a forearm coupled to the upper arm, the forearm being coupled to the upper arm at a first rotary joint and rotatable about the first rotary joint, the first rotary joint being actuatable by a single-stage band arrangement comprising a first shoulder pulley actuatable by the third drive axis, a first elbow pulley partially forming the first rotary joint, and a belt, band or cable configured to transmit motion between the first shoulder pulley and the first elbow pulley, a first end effector and a second end effector coupled to the forearm, the first end effector and the second end effector being coupled to the forearm at a second rotary joint, orientation of the first end effector and the second end effector being controlled via a two-stage band arrangement. A first stage of the two-stage band arrangement comprises a second shoulder pulley actuatable by the second drive axis, a second elbow pulley partially forming the first rotary joint, and an upper band, belt, or cable configured to transmit motion between the second shoulder pulley and the second elbow pulley. A second stage of the two-stage band arrangement comprises a third elbow pulley coupled to the second elbow pulley, a first wrist pulley coupled to the first end effector, and a first lower belt, band, or cable configured to transmit motion between the third elbow pulley and the first wrist pulley, and wherein the second stage of the two-stage band arrangement further comprises a fourth elbow pulley coupled to the second elbow pulley, a second wrist pulley coupled to the second end effector, and a second lower belt, band, or cable configured to transmit motion between the fourth elbow pulley and the second wrist pulley. At least one of the motion between the first shoulder pulley and the first elbow pulley, the motion between the second shoulder pulley and the second elbow pulley, the motion between the third elbow pulley and the first wrist pulley, and the motion between the fourth elbow pulley and the wrist second pulley are at a variable transmission ratio.

[0007] In accordance with another aspect, an apparatus has a drive unit having a first drive axis rotatable about a first axis of rotation, a second drive axis rotatable about a second axis of rotation, and a third drive axis rotatable about a third axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis, and the third drive axis being coaxial with and partially within the second drive axis and axially rotatable within the second drive axis. A first robot arm has a first upper arm connected to the drive unit at the first drive axis, a first forearm coupled to the first upper arm, the first forearm being coupled to the first upper arm at a first rotary joint, the first rotary joint being actuatable by the second drive axis using a first band arrangement, and a first end effector coupled to the first forearm, the first end effector being coupled to the first forearm at a third rotary joint, the

third rotary joint being actuatable by the first rotary joint using a third band arrangement. A second robot arm has a second upper arm connected to the drive unit at the third drive axis, a second forearm coupled to the second upper arm, the second forearm being coupled to the second upper arm at a second rotary joint, the second rotary joint being actuatable by the second drive axis using a second band arrangement, and a second end effector coupled to the second forearm, the second end effector being coupled to the second forearm at a fourth rotary joint, the fourth rotary joint being actuatable by the second rotary joint using a fourth band arrangement. At least one of the first band arrangement, the second band arrangement, the third band arrangement, and the fourth arrangement has band a variable transmission ratio.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The foregoing aspects and other features are description, taken in explained in the following connection with the accompanying drawings, wherein:

[0009] FIG. 1 is a top view of a transport apparatus;
 [0010] FIG. 2 is a top view of a transport apparatus;
 [0011] FIG. 3A is a side view of a transport apparatus;
 [0012] FIG. 3B is a top view of the transport apparatus of FIG. 3A;
 [0013] FIG. 4 is a top view of a transport apparatus;
 [0014] FIG. 5 is a top view of a transport apparatus;
 [0015] FIG. 6 is a top view of a transport apparatus;
 [0016] FIG. 7 is a top view of a transport apparatus;
 [0017] FIG. 8 is a top view of a transport apparatus;
 [0018] FIG. 9 is a side view of a transport apparatus;
 [0019] FIG. 10 is a top view of a transport apparatus;
 [0020] FIG. 11 is a top view of a transport apparatus;
 [0021] FIG. 12 is a side view of a transport apparatus;
 [0022] FIGS. 13A-13C are top views of a transport apparatus;
 [0023] FIG. 14A is a top view of a transport apparatus;
 [0024] FIG. 14B is a side view of a transport apparatus;
 [0025] FIGS. 15A-15C are top views of a transport apparatus;
 [0026] FIG. 16 is a top view of a transport apparatus;
 [0027] FIG. 17 is a side view of a transport apparatus;
 [0028] FIG. 18A is a top view of a transport apparatus;
 [0029] FIG. 18B is a side view of a transport apparatus;
 [0030] FIGS. 19A-19C are top views of a transport apparatus;
 [0031] FIGS. 20A-20C are top views of a transport apparatus;
 [0032] FIGS. 21A-21C are top views of a transport apparatus;
 [0033] FIG. 22 is a side view of a transport apparatus;
 [0034] FIG. 23A is a side view of a transport apparatus;
 [0035] FIG. 23B is a side view of a transport apparatus;
 [0036] FIG. 24 is a side view of a transport apparatus;
 [0037] FIG. 25A is a top view of a transport apparatus;
 [0038] FIG. 25B is a side view of a transport apparatus;
 [0039] FIGS. 26A-26C are top views of a transport apparatus;
 [0040] FIGS. 27A-27C are top views of a transport apparatus;
 [0041] FIGS. 28A-28C are top views of a transport apparatus;
 [0042] FIG. 29A is a top view of a transport apparatus;
 [0043] FIG. 29B is a side view of a transport apparatus;

[0044] FIG. 30A is a side view of a transport apparatus;
 [0045] FIG. 30B is a side view of a transport apparatus;
 [0046] FIG. 31 is a top view of a transport apparatus;
 [0047] FIG. 32 is a side view of a transport apparatus;
 [0048] FIG. 33A is a top view of a transport apparatus;
 [0049] FIG. 33B is a side view of a transport apparatus;
 [0050] FIGS. 34A-34C are top views of a transport apparatus;
 [0051] FIGS. 35A-35C are top views of a transport apparatus;
 [0052] FIG. 36 is a side view of a transport apparatus;
 [0053] FIG. 37A is a top view of a transport apparatus;
 [0054] FIG. 37B is a side view of a transport apparatus;
 [0055] FIG. 38A is a top view of a transport apparatus;
 [0056] FIG. 38B is side view of a transport apparatus;
 [0057] FIG. 39 is a top view of a transport apparatus;
 [0058] FIG. 40 is a side view of a transport apparatus;
 [0059] FIG. 41A is a top view of a transport apparatus;
 [0060] FIG. 41B is a side view of a transport apparatus;
 [0061] FIG. 42A is a diagram of a partial pulley profile;
 [0062] FIGS. 42B-42E are top views of a transport apparatus;
 [0063] FIG. 43 is a diagram of a partial pulley profile;
 [0064] FIG. 44 is a top view of a transport apparatus;
 [0065] FIG. 45 is a diagram of shaft position trajectories;
 [0066] FIG. 46 is a top view of a transport apparatus;
 [0067] FIG. 47 is a diagram of shaft position trajectories;
 [0068] FIG. 48 is a side view of a transport apparatus;
 [0069] FIG. 49A is a top view of a transport apparatus;
 [0070] FIG. 49B is a side view of a transport apparatus;
 [0071] FIG. 50 is a top view of a transport apparatus;
 [0072] FIG. 51 is a diagram of shaft position trajectories;
 [0073] FIG. 52 is a top view of a transport apparatus; and
 [0074] FIG. 53 is a diagram of shaft position trajectories.

DETAILED DESCRIPTION OF EMBODIMENTS

[0075] Referring to FIG. 1, there is shown a top view of a transport apparatus 10 incorporating features of an example embodiment. Although the features will be described with reference to the example embodiments shown in the drawings, it should be understood that features can be embodied in many alternate forms of embodiments. In addition, any suitable size, shape or type of elements or materials could be used. Disclosed here in are multi-link, for example, three-link robot arm mechanisms which may be used to transfer material to and/or from side-by-side, for example, laterally offset stations in a semiconductor wafer processing tool.

[0076] An example layout of a semiconductor wafer processing tool 10 is diagrammatically depicted in the top view of FIG. 1. In this particular example, the tool features 4 pairs of side-by-side stations, e.g., one pair of load locks 12 and 3 pairs of process module stations 14, 16, 18. The present three-link arm mechanisms are designed to provide access to each of the stations in the tool along a predefined path, e.g., substantially straight-line path, with predefined orientation of the end-effector, e.g., along the straight-line path 20, as illustrated in the example of FIG. 1. The straight line paths may be parallel to each other on a given facet 22 or alternately angled relative to each other. In alternate aspects, any suitable path or combination of paths may be defined, linear, circular or any suitable shape or combination of shapes.

[0077] FIGS. 2, 3A and 3B show diagrams of the top and side views of a robot arm mechanism 30 according to the

disclosed embodiment installed on a robot drive unit **32**. The arm mechanism may consist of a first link (upper arm) **34** a second link (forearm) **36** and a third link (end-effector) **38** supporting substrate **40**. An example internal arrangement of the robot **28** is depicted diagrammatically in FIG. 3A. The arm mechanism may be driven by a two-axis spindle with two coaxial shafts, e.g., an outer T1 shaft **42** and an inner T2 shaft **44**. The inner T2 shaft **44** may be partially within the outer T1 shaft **42** such that the inner T2 shaft **44** is rotatable within the outer T1 shaft **42**. The first link **34** of the robot arm mechanism may be attached directly to the T1 shaft **42**. The second link **36** may be coupled to the first link **34** via a rotary joint **46**, and actuated by the T2 shaft **44** using a band arrangement **48**. The band arrangement **48** may comprise a shoulder pulley **50**, which may be attached to the T2 shaft **44**, an elbow pulley **52**, which may be attached to the second link **36**, and a band, belt or cable **54**, which may transmit motion between the two pulleys **50**, **52**. The belt arrangement may feature a constant transmission ratio, for instance, 1:1 ratio may conveniently be used. However, any other suitable arrangement may be used. The third link **38** may be coupled to the second link **36** via a rotary joint **56**, and its orientation may be constrained by another band arrangement **58**. The band arrangement **58** may comprise an elbow pulley **60**, which may be connected to the first link **34**, a wrist pulley **62**, which may be connected to the third link **38**, and a band, belt or cable **64**, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The transmission variable ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIG. 3B, the wrist pulley may feature a non-circular profile. An example of an arm that utilizes non circular pulleys is disclosed in U.S. patent application Ser. No. 13/833,732 filed Mar. 15, 2013 and entitled "Robot Having Arm With Unequal Link Lengths" which is hereby incorporated by reference herein in its entirety.

[0078] The variable transmission ratio may be selected so that the orientation of the third link (end-effector) **38** changes in a predefined manner as a function of the relative position of the first and the second links **34**, **36**. The relative position of the first and second links **34**, **36** may be conveniently expressed in terms of the included angle between the two links. Alternately, the orientation of the third link (end-effector) **38** may change in a predefined manner as a function of the relative position of links, shafts or otherwise. By way of example, the transmission ratio may be selected in a manner that may allow a reference point on the third link (typically the nominal center **70** of the end-effector) to follow a predetermined path with a predetermined (but not necessarily constant) orientation of the third link (end-effector) when the first and second links are actuated accordingly. As an example, the path **72**, **74**, **76**, **78** may be selected as an access path to one of the stations **82** of FIG. 1, as illustrated in FIG. 4. Furthermore, the transmission ratio may be selected so that the arm can access the neighboring station **82**, as shown in FIG. 5. The T1 and T2 shafts **42**, **44** may also rotate to reorient the arm mechanism to access another pair of stations **86**, **88** or **90**, **92**, as illustrated in FIGS. 6 and 7.

[0079] Although the initial position of the robot arm mechanism is shown on the axis of symmetry between the neighboring side-by-side stations, it is noted that any other initial position may be used. It also is noted that the drive

unit of the robot may feature an additional axis to facilitate vertical lift of the arm mechanism, e.g., to pick and place wafers carried by the end-effector. In alternate aspects, other additional rotary axis and/or arms may be provided. In alternate aspects, a band arrangement between the shoulder pulley attached to the T2 shaft and the elbow pulley attached to the second link features a variable transmission ratio, e.g., using at least one non-circular pulley. The variable transmission ratio is selected so that extension of the arm is driven by the T1 shaft while the T2 shaft remains stationary. In aspects, alternate the variable transmission ratio may be selected so that the T2 shaft follows a predetermined motion profile as the robot arm extends along the predefined path. In alternate aspects, the mechanism that constrains the orientation of the third link includes an additional band arrangement.

[0080] For example, as depicted diagrammatically in FIG. 8, the orientation of the third link **102** may be constrained by a band arrangement **104** that may comprise an elbow pulley **106**, which may be coaxial with the elbow joint **108** (the rotary joint between the first link and the second link) and free to rotate with respect to the two first **110** and second **112** links, a wrist pulley **114**, which may be connected to the third link **102**, and a band, belt or cable **116**, which may transmit motion between the two pulleys. The motion of the elbow pulley is constrained by another band arrangement **118** that may comprise a pulley **120** attached to the T2 shaft **122**, a pulley **124** attached to the elbow pulley **106**, and a band, belt or cable **126**, which may transmit motion between the two pulleys. The two band arrangements may feature a constant or variable transmission ratio. As an example, if the two band arrangements feature a constant 1:1 ratio, and if the second link is coupled to the T2 shaft, the end-effector keeps a constant orientation as the arm extends and retracts by actuating the T1 shaft.

[0081] The disclosed aspects may similarly be applied to dual-end-effector arm mechanisms which may be used to transfer material to/from side-by-side (laterally offset) stations in a semiconductor wafer processing tool. Here, an example layout of a semiconductor wafer processing tool **210** is diagrammatically depicted in the top view of FIG. 10. In this particular example, the tool features 4 pairs of side-by-side stations, e.g., one pair of load locks **220** and 3 pairs of process module stations **230** and a transport chamber or module **232**.

[0082] The present embodiment arm mechanisms may be designed to provide access to each of the stations in the tool along a predefined path **236**, e.g., substantially straight-line path, with predefined orientation of the end-effector, e. g., along the straight-line path, as illustrated in the example of FIG. 10.

[0083] FIGS. 11 and 12 show diagrams of the top and side views of the robot arm mechanism **250** installed on a robot drive unit **252**. The arm mechanism may consist of a first link (upper arm) **254** a second link (forearm) **256**, pivoting end-effector A and pivoting end-effector B **258**, **260**. An example internal arrangement of the robot is depicted diagrammatically in FIGS. 11 and 12. The arm mechanism may be driven by a three-axis spindle with three coaxial shafts, e.g., an outer T1 shaft **262**, a T2 shaft **264** and an inner T3 shaft **266**. The T2 shaft **264** may be partially within the outer T1 shaft **262**, and the inner T3 shaft **266** may be partially within the T2 shaft **264**. The first link of the robot arm mechanism may be attached directly to the T1 shaft. The

second link may be coupled to the first ring via a rotary joint (elbow joint), and actuated by the T3 shaft using a band arrangement. The band arrangement may comprise a first shoulder pulley, which may be attached to the T3 shaft, a first elbow pulley, which may be attached to the second link, and a band, belt or cable, which may transmit motion between the two pulleys. The belt arrangement may feature a constant or variable transmission ratio, for instance, 1:1 ratio may be conveniently used. However, any other suitable arrangement may be used. End-effector A may be coupled to the second link via a rotary joint (wrist joint), and its orientation may be controlled by a two stage band arrangement. The first stage of the band arrangement may include a second shoulder pulley, which may be connected to the T2 shaft, a second elbow pulley and a band, belt or cable, which may transmit motion between the two pulleys. The first stage of the belt arrangement may feature a constant or variable transmission ratio, for instance, 1:1 ratio may be conveniently used. The second of stage the band arrangement may comprise a third elbow pulley, which may be connected to the second elbow pulley, a first wrist pulley, which may be connected to end-effector A, and a band, belt or cable, which may transmit motion between the two pulleys. The second stage of the band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 11 and 12, the wrist pulley may feature a non-circular profile. An example of an arm that utilizes non circular pulleys is disclosed in U.S. patent application Ser. No. 13/833,732 filed Mar. 15, 2013 and entitled "Robot Having Arm With Unequal Link Lengths" which is hereby incorporated by reference herein in its entirety. Another example of an arm that utilizes non circular pulleys is disclosed in U.S. Provisional Patent Application No. 62/132,066 filed Mar. 12, 2015 and entitled "2-Degree-of-Freedom 3-Link Robot Arm Mechanisms" which is hereby incorporated by reference herein in its entirety.

[0084] The variable transmission ratio may be selected so that the orientation of end-effector A changes in a predefined manner as a function of the relative position of the first and second links and the T2 shaft. For instance, it may be selected so that end-effector A may follow a path to a station, as illustrated in FIGS. 13A-13C, or, depending on the motion of the T2 shaft, fold to the side, as also shown in FIGS. 13A-13C. Similarly, end-effector B may be coupled to the second link via a rotary joint (wrist joint), and its orientation may be controlled by a two stage band arrangement. The first stage of the band arrangement is shared with end-effector A. The second stage of the band arrangement may comprise a fourth elbow pulley, which may be connected to the second elbow pulley, a second wrist pulley, which may be connected to end-effector B, and a band, belt or cable, which may transmit motion between the two pulleys. The second stage of the band arrangement may be configured in a crossover configuration, as illustrated in FIGS. 11 and 12, and may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 11 and 12, the wrist pulley may feature a non-circular profile. The variable transmission ratio may be selected so that the orientation of end-effector B changes in a predefined manner as a function of the relative position of the first and second links and the

T2 shaft. For instance, it may be selected so that end-effector A may follow a path to a station, as illustrated in FIGS. 13A-13C, or, depending on the motion of the T2 shaft, fold to the side, as also shown in FIGS. 13A-13C.

[0085] Although the arm mechanism is shown as right-handed (the elbow joint is on the right-hand side of the line from the shoulder joint to the wrist joint) when it accesses the left station in FIGS. 13A-13C and left-handed when accessing the right station in FIGS. 13A-13C, in an alternative embodiment, the mechanism may be configured so that it is left-handed when accessing the left station and right-handed when accessing the right station.

[0086] In yet another alternative embodiment, the second link may be actuated by the T2 shaft and the orientation of the end-effectors may be controlled by the T3 shaft. Referring now to FIGS. 14A and 14B, there are shown diagrams of the top and side views of the robot arm mechanism 300 installed on a robot drive unit 302, including an example internal arrangement of the robot. The arm mechanism may consist of a left linkage 304 and a right linkage 306. The arm mechanism may be driven by a three-axis spindle with three coaxial shafts, e.g., an outer T1 shaft 308, a T2 shaft 310 and an inner T3 shaft 312. The T2 shaft 310 may be partially within the outer T1 shaft 308, and the inner T3 shaft 312 may be partially within the T2 shaft 310. The left linkage may consist of a left first link (upper arm) 314 a left second link (forearm) 316 and a left third link (end-effector) 318. The left first link of the may be attached directly to the T1 shaft. The left second link may be coupled to the left first ring via a rotary joint, and constrained by the T2 shaft using a band arrangement. The band arrangement may comprise a first shoulder pulley, which may be attached to the T2 shaft, a left elbow pulley, which may be attached to the second link, and a band, belt or cable, which may transmit motion between the two pulleys. The belt arrangement may feature a variable transmission ratio. However, any other suitable arrangement may be used. The left third link may be coupled to the left second link via a rotary joint, and its orientation may be constrained by another band arrangement. The band arrangement may comprise a left elbow pulley, which may be connected to the left first link, a left wrist pulley, which may be connected to the left third link, and a band, belt or cable, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 14A and 14B, the wrist pulley may feature a non-circular profile. The variable transmission ratio may be selected so that the orientation of the left third link (end-effector) changes in a predefined manner as a function of the relative position of the left first and left second links. The relative position of the left first and left second links may be conveniently expressed in terms of the included angle between the two links. For instance, the transmission ratios of the two band arrangements may be selected in a manner that may allow a reference point on the left third link (typically the nominal center of the end-effector) to follow a predetermined path with a predetermined (e.g., constant) orientation of the left third link (end-effector) when the left first link is actuated by the T1 shaft and the T2 shaft is kept stationary.

[0087] As an example, the path may be selected as an access path to one of the stations of FIG. 10, as illustrated in FIGS. 15A-15C. Referring to FIGS. 14A and 14B again,

the right linkage may be configured substantially as a mirror image of the left linkage. It may consist of a right first link (upper arm) **320** a right second link (forearm) right third link (end-effector) **324**. The right first link may be attached directly to the T3 shaft. The right second link may be coupled to the right first ring via a rotary joint, and constrained by the T2 shaft using a band arrangement. The band arrangement may comprise a second shoulder pulley, which may be attached to the T2 shaft, a left elbow pulley, which may be attached to the second link, and a band, belt or cable, which may transmit motion between the two pulleys. Similarly to the left linkage, the belt arrangement may feature a variable transmission ratio. However, any other suitable arrangement may be used.

[0088] The remaining components of the right linkage may be configured substantially as a mirror image of the right linkage, and the operation of the right linkage is substantially equivalent to the left linkage in a mirrored manner. Further, the T1, T2 and T3 shafts may rotate in sync to reorient the arm mechanism to access another pair of stations.

[0089] Although the left linkage is shown as left-handed (the elbow joint is on the left-hand side of the line from the shoulder joint to the wrist joint) in FIGS. **15A-15C** and the right linkage is depicted as right-handed in FIGS. **15A-15C**, in an alternative embodiment, the mechanism may be configured so that the left linkage is right-handed and the right linkage is left-handed.

[0090] In yet another alternative embodiment, the right upper arm may be actuated by the T2 shaft and the orientation of the right and left forearms may be constrained by the T3 shaft.

[0091] The disclosed aspects may similarly be applied to dual-end-effector robot arm mechanisms which may be used to transfer material to/from side-by-side (laterally offset) stations in a semiconductor wafer processing tool. An example layout of a semiconductor wafer processing tool **410** is diagrammatically depicted in the top view of FIG. **16**. In this particular example, the tool features 4 pairs of side-by-side stations, for example, one pair of load locks **412** and 3 pairs of process module stations **414** coupled to transport chamber **416**.

[0092] The disclosed arm mechanisms may provide access to each of the stations in the tool along a predefined path, for example, substantially straight-line path **418**, **420**, with predefined orientation of the end-effector, for example, along the straight-line path **418**, **420**, as illustrated in the example of FIG. **16**.

[0093] FIG. **17** shows a diagram of a side view of robot **50** with an example robot arm mechanism **452** according to one embodiment installed on a robot drive unit **454**. The arm mechanism may consist of a first link (upper arm) **456** a second link (forearm) **A 458**, end-effector **A 460**, second link (forearm) **B 462** and end-effector **B 464**. An example internal arrangement of the robot **450** of FIG. **17** is depicted diagrammatically in FIGS. **18A** and **18B**. The arm mechanism may be driven by a three-axis spindle **454** with three coaxial shafts, for example, an outer T1 shaft **470**, a T2 shaft **472** and an inner T3 shaft **474**. The first link **456** of the robot arm mechanism may be attached directly to the T1 shaft **70**. The second link **A 458** may be coupled to the first link **456** via a rotary joint (elbow joint) **480**, and actuated by the T3 shaft **474** using a band arrangement **482**. The band arrangement may **482** comprise shoulder pulley **A 484**, which may

be attached to the T3 shaft **474**, an elbow pulley **A 486**, which may be attached to the second link **A 458**, and a band, belt or cable **488**, which may transmit motion between the two pulleys. The belt arrangement may feature a constant or variable transmission ratio, for instance, 1:1 ratio may be conveniently used. However, any other suitable arrangement may be used. Similarly, the second link **B 462** may be coupled to the first link **456** via a rotary joint (elbow joint) **480**, and actuated by the T2 shaft **472** using a band arrangement **483**. End-effector **A 460** may be coupled to second link **A 458** via a rotary joint (wrist joint) **490**, and its orientation may be constrained by another band arrangement **492**. The band arrangement may include an elbow pulley **494**, which may be connected to the first link, and a wrist pulley **496**, which may be connected to end-effector **A 460**, and a band **498**, belt or cable, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. **18A** and **18B**, the wrist pulley may feature a non-circular profile. An example of an arm that utilizes non circular pulleys is disclosed in U.S. patent application Ser. No. 13/833,732 filed Mar. 15, 2013 and entitled "Robot Having Arm With Unequal Link Lengths" which is hereby incorporated by reference herein in its entirety. Another example of an arm that utilizes non circular pulleys is disclosed in U.S. Provisional Patent Application No. 62/132,066 filed Mar. 12, 2015 and entitled "2-Degree-of-Freedom 3-Link Robot Arm Mechanisms" which is hereby incorporated by reference herein in its entirety. Another example of an arm that utilizes non n circular pulleys is disclosed in U.S. Provisional Patent Application No. 62/135,490 filed Mar. 19, 2015 and entitled "Arm Mechanisms with Two End Effectors" which is hereby incorporated by reference herein in its entirety.

[0094] The variable transmission ratio may be selected so that the orientation of end-effector **A 460** changes in a predefined manner as a function of the relative position of the first link **456** and second link **A 458**. For instance, it may be selected so that end-effector **A 460** may follow a path to a station, as illustrated in FIGS. **19A-19C**.

[0095] Similarly, end-effector **B 464** may be coupled to second link **B 462** via a rotary joint (wrist joint) **502**, and its orientation may be constrained by yet another band arrangement **504**. The band arrangement **504** may comprise an elbow pulley **506**, which may be connected to the first link **56**, a wrist pulley **508**, which may be connected to end-effector **B 464**, and a band, belt or cable **510**, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. **18A** and **18B**, the wrist pulley may feature a non-circular profile. The variable transmission ratio may be selected so that the orientation of end-effector **B** changes in a predefined manner as a function of the relative position of the first link and second link **B**. For instance, it may be selected so that end-effector **B** may follow a path to a station, as illustrated in FIGS. **19A-19C**.

[0096] Typical operations of the robot are illustrated in FIGS. **19-21**. FIGS. **19A-19C** shows the robot **450** in the retracted position, accessing the left station **530** with end-effector **A** and accessing the same station using end-effector **B**. This allows the robot to perform rapid material exchange

in the left station. Similarly, FIGS. 20A-20C depicts the robot 450 as it accesses station B 532 with end-effectors A and B, allowing the robot to perform rapid material exchange in station B. Finally, FIGS. 21A-21C illustrates that the robot may extend both end-effectors 460, 464 to access the left 530 and right 532 stations simultaneously. Further, the T1, T2 and T3 shafts may rotate in sync to reorient the arm mechanism to access another pair of stations or any suitable combination of location(s).

[0097] The examples of FIGS. 17 to 21 show the robot arm mechanism with the elbow joints configured in a coaxial manner. However, the elbow joints may be configured in an offset manner 540 as two separate joints 542, 544, as depicted diagrammatically in the example robot 450' of FIG. 22. Additional alternative example embodiments are shown diagrammatically in FIGS. 23A and 23B. FIG. 23A shows robot 600 having drive 602, common upper arm 604, forearm A 606 and forearm B 608 having common elbow 610. Here, robot 600 is shown with end effectors mounted to the top surface of forearms 604, 606 at respective wrist joints where robot 600 may be driven and utilized in a similar fashion as robot 450. FIG. 23B shows robot 600' having drive 602, common upper arm 604, forearm A 606' and forearm B 608 having common elbow 610. Here, robot 600' is shown with end effectors mounted to the top and bottom surfaces respectively of forearms 604, 606' at respective wrist joints where robot 600' may be driven and utilized in a similar fashion as robot 450.

[0098] FIG. 24 shows a diagram of a side view robot of the robot arm mechanism 702 according to an embodiment installed on a robot drive unit 704. The arm mechanism may consist of linkage A 706 and linkage B 708. An example internal arrangement of the robot 700 of FIG. 24 is depicted diagrammatically in FIGS. 25A and 25B. The arm mechanism may be driven by a three-axis spindle 704 with three coaxial shafts, for example, an outer T1 shaft 710, a T2 shaft 712 and an inner T3 shaft 714. The T2 shaft 712 may be partially within the outer T1 shaft 710, and the inner T3 shaft 714 may be partially within the T2 shaft 712. Linkage A 706 may consist of a first link (upper arm) 716, a second link (forearm) 718 and third link (end-effector A) 720. The first link may be attached directly to the T3 shaft 714. The second link may be coupled to the first link via a rotary joint 722, and constrained by the T2 712 shaft using a band arrangement 724. The band arrangement may 724 comprise a shoulder pulley, which may be attached to the T2 shaft 712, an elbow pulley, which may be attached to the second link 718, and a band, belt or cable, which may transmit motion between the two pulleys. The belt arrangement may feature a variable transmission ratio. However, any other suitable arrangement may be used. The third link of linkage A 720 may be coupled to the second link 716 via a rotary joint 726, and its orientation may be constrained by another band arrangement 728. The band arrangement 728 may comprise a left elbow pulley, which may be connected to the first link 716, a wrist pulley, which may be connected to the third link 720, and a band, belt or cable, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 25A and 25B, the wrist pulley may feature a non-circular profile. The variable transmission ratio may be selected so that the orientation of the third link (end-effector

A) of linkage A changes in a predefined manner as a function of the relative position of the first and second links. The relative position of the first and second links may be conveniently expressed in terms of the included angle between the two links. By way of example, the transmission ratios of the two band arrangements of linkage A 706 may be selected in a manner that may allow a reference point on the third link (typically the nominal center of end-effector A) to follow a predetermined path with a predetermined (for example, constant) orientation of the left third link (end-effector A) when the first link is actuated by the T3 shaft and the T2 shaft is kept stationary.

[0099] As an example, the path may be selected as an access path to one of the stations 132 of FIG. 16, as illustrated in FIGS. 26A-26C. Referring to FIGS. 25A and 25B again, linkage B 708 may consist of a first link (upper arm) 732 a second link 734 (forearm) and a right third link (end-effector B) 736. The first link 732 may be attached directly to the T1 shaft 710. The second link 734 may be coupled to the first link 732 via a rotary joint 738, and constrained by the T2 shaft 312 using a band arrangement 740. The band arrangement may comprise another shoulder pulley, which may be attached to the T2 shaft 712, an elbow pulley, which may be attached to the second link 734, and a band, belt or cable, which may transmit motion between the two pulleys. Similarly to left linkage A, the belt arrangement may feature a variable transmission ratio. However, any other suitable arrangement may be used. The remaining components of linkage B may be configured in a manner similar to linkage A, and the operation of the linkage B is also substantially equivalent to linkage A except that the T1 shaft 310 takes the role of the T3 shaft 314.

[0100] Typical operations of the robot are illustrated in FIGS. 26 to 28. FIGS. 26A-26C shows the robot 700 in the retracted position, accessing the left station 532 with end-effector A 720 and accessing the same station using end-effector B 736. This allows the robot 700 to perform rapid material exchange in the left station 532. Similarly, FIGS. 27A-27C depicts the robot 700 as it accesses station B 534 with end-effectors A 720 and B 736, allowing the robot to perform rapid material exchange in station B 534. Further, FIGS. 28A-28C illustrate that the robot may extend both end-effectors to access the left and right stations simultaneously. Further, the T1, T2 and T3 shafts may rotate in sync to reorient the arm mechanism to access another pair of stations or any suitable position.

[0101] As seen in FIGS. 29A and 29B, alternatively, the arm mechanism may be driven by a four-axis spindle 750 with four coaxial shafts, for example, an outer T1 752 shaft, a T2 shaft 754, a T3 shaft 756 and an inner T4 shaft 758, as illustrated in the example of FIG. 29. In this particular the T1 352 example, shaft may be connected to the first link 760 of linkage A, the T2 shaft 754 may actuate the second link 762 of linkage A, the T3 756 may actuate the second link 764 of linkage B, and the T4 shaft 758 may be connected to the first link 766 of linkage B. However, any suitable configuration of the four shafts may be used.

[0102] Additional alternative example embodiments are shown diagrammatically in FIGS. 30A and 30B. FIG. 30A shows robot 780 with drive 782, arm A 784 and arm B 786 nested as shown. Robot 780 may have features and be driven similar to robots 700, 750 or otherwise. Here, robot 780 is shown with end effectors mounted to the top surface of respective forearms at respective wrist joints where robot

780 may be driven and utilized in a similar fashion. FIG. 30B shows robot **780'** with drive **782**, arm **A 784'** and arm **B 786** nested as shown. Robot **780** may have features and be driven similar to robots **700**, **750** or otherwise. Here, robot **780'** is shown with end effectors mounted to the bottom and top surfaces of respective forearms at respective wrist joints where robot **780'** may be driven and utilized in a similar fashion.

[0103] The disclosed aspects may similarly be applied to dual-end-effector robot arm mechanisms which may be used to transfer material to/from side-by-side (laterally offset) stations in a semiconductor wafer processing tool. An example layout of a semiconductor wafer processing tool **810** is diagrammatically depicted in the top view of FIG. 31. In this particular example, the tool features 4 pairs of side-by-side stations, for example, one pair of load locks **812** and 3 pairs of process module stations **814** coupled to transport chamber **816**.

[0104] The present arm mechanisms may provide access to each of the stations in the tool along a predefined path, for example, substantially straight-line path **818**, **820**, with predefined orientation of the end-effector, for example, along the straight-line path **818**, **820**, as illustrated in the example of FIG. 31.

[0105] FIG. 32 shows a diagram of a side view of robot **850** with an example robot arm mechanism **852** according to one embodiment installed on a robot drive unit **854**. The arm mechanism may consist of a first link (upper arm) **856** a second link (forearm) **A 858**, end-effector **A 860**, second link (forearm) **B 862** and end-effector **B 864**. An example internal arrangement of the robot **850** of FIG. 32 is depicted diagrammatically in FIGS. 33A and 33B. The arm mechanism may be driven by a three-axis spindle **854** with three coaxial shafts, for example, an outer T1 shaft **870**, a T2 shaft **872** and an inner T3 shaft **874**. The first link **856** of the robot arm mechanism may be attached directly to the T1 shaft **870**. The second link **A 858** may be coupled to the first link **856** via a rotary joint (elbow joint) **880**, and actuated by the T3 shaft **874** using a band arrangement **882**. The band arrangement **882** may comprise shoulder pulley **A 884**, which may be attached to the T3 shaft **874**, an elbow pulley **A 886**, which may be attached to the second link **A 858**, and a band, belt or cable **888**, which may transmit motion between the two pulleys. The band arrangement may feature a constant or variable transmission ratio, for instance, 1:1 ratio may be conveniently used. However, any other suitable arrangement may be used. Similarly, the second link **B 862** may be coupled to the first link **856** via a rotary joint (elbow joint) **880**, and actuated by the T2 shaft **872** using a band arrangement **883**. End-effector **A 860** may be coupled to second link **A 858** via a support structure **861** and a rotary joint (wrist joint) **890**. As depicted in the example of FIG. 32, support structure **861** may be attached to rotary joint **890** below second link **A 858** and shaped to avoid mechanical interference, for instance, with second link **A 858** and second link **B 862**, during operation. Support structure **861** may be formed by one or multiple components, integrated with end-effector **A 860** or rotary joint **890**, or implemented in any other suitable manner. Orientation of end-effector **A 860** may be constrained by band arrangement **892**. The band arrangement may include an elbow pulley **894**, which may be connected to the first link, and a wrist pulley **896**, which may be connected to support structure **861** with end-effector **A 860**, and a band, belt or cable **898**, which may transmit

motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 33A and 33B, the wrist pulley may feature a non-circular profile. An example of an arm that utilizes non circular pulleys is disclosed in U.S. patent application Ser. No. 13/833,732 filed Mar. 15, 2013 and entitled "Robot Having Arm With Unequal Link Lengths" which is hereby incorporated by reference herein in its entirety. Another example of an arm that utilizes non circular pulleys is disclosed in U.S. Provisional Patent Application No. 62/132,066 filed Mar. 12, 2015 and entitled "2-Degree-of-Freedom 3-Link Robot Arm Mechanisms" which is hereby incorporated by reference herein in its entirety. Another example of an arm that utilizes non circular pulleys is disclosed in U.S. Provisional Patent Application No. 62/135,490 filed Mar. 19, 2015 and entitled "Arm Mechanisms with h Two End Effectors" which is hereby incorporated by reference herein in its entirety. Another example of an arm that utilizes non circular pulleys is disclosed in U.S. Provisional Patent Application No. 62/137,458 filed Mar. 24, 2015 and entitled "Robot Arm Mechanisms with Two End Effectors" which is hereby incorporated by reference herein in its entirety.

[0106] The variable transmission ratio may be selected so that the orientation of end-effector **A 860** changes in a predefined manner as a function of the relative position of the first link **856** and second link **A 858**. For instance, it may be selected so that end-effector **A 860** may follow a path to a station, as illustrated in FIGS. 34A-34C. End-effector **B 864** may be coupled to second link **B 862** via a rotary joint (wrist joint) **902**, and its orientation may be constrained by yet another band arrangement **904**. The band arrangement **904** may comprise an elbow pulley **906**, which may be connected to the first link **856**, a wrist pulley **908**, which may be connected to end-effector **B 864**, and a band, belt or cable **910**, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 33A and 33B, the wrist pulley may feature a non-circular profile.

[0107] The variable transmission ratio may be selected so that the orientation of end-effector **B** changes in a predefined manner as a function of the relative position of the first link and second link **B**. For instance, it may be selected so that end-effector **B** may follow a path to a station, as illustrated in FIGS. 34A-34C. Example operations of the robot are illustrated in FIGS. 34 and 35. FIGS. 34A-34C shows the robot **850** in the retracted position in front of the left station **530**, accessing the left station **530** with end-effector **A** and accessing the same station using end-effector **B**. This allows the robot to perform rapid material exchange in the left station. Referring still to FIGS. 34A-34C, end-effector **A 860** may be extended to left station **530** along a desired path, for instance, a substantially straight-line path **820**, by rotating T3 shaft **874** in the clockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T3 shaft **74** so that end-effector **A 860** follows the desired straight-line path **820**. At the same time, end-effector **B 864** may be kept folded on top of second link **B 862** by rotating T2 shaft **862** in sync with T1 shaft **870**. Similarly, end-effector **A 860** may be retracted from left station **530** along a desired path, for instance, the same substantially straight-line path **820**, by

rotating T3 shaft **874** in the counterclockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T3 shaft **874** so that end-effector A **860** follows the desired straight-line path **820**. Again, end-effector B **864** may be kept folded on top of second link B **862** by rotating T2 shaft **862** in sync with T1 shaft **870**. End-effector B **864** may then be extended to left station **530** along a desired path, for instance, a substantially straight-line path **820**, by rotating T2 shaft **872** in the clockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T2 shaft **872** so that end-effector B **864** follows the desired straight-line path **820**. At the same time, end-effector A **860** may be kept folded on top of second link A **858** by rotating T3 shaft **874** in sync with T1 shaft **870**. Further, end-effector B **864** may be retracted from left station **530** along a desired path, for instance, the same substantially straight-line path **820**, by rotating T2 shaft **872** in the counterclockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T2 shaft **872** so that end-effector B **864** follows the desired straight-line path **820**. Again, end-effector A **860** may be kept folded on top of second link A **58** by rotating T3 shaft **874** in sync with T1 shaft **870**. Further, the T1, T2 and T3 shafts may be rotated in sync to reorient the arm mechanism to access another location, for instance, right station **532**.

[0108] FIGS. 35A-35C depict the robot **850** as it accesses the right station **532** with end-effectors A and B, allowing the robot to perform rapid material exchange in the right station **532**. In FIGS. 35A-35C, end-effector A **860** may be extended to right station **532** along a desired path, for instance, a substantially straight-line path **818**, by rotating T3 shaft **74** in the counterclockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T3 shaft **874** so that end-effector A **860** follows the desired straight-line path **818**. At the same time, end-effector B **864** may be kept folded on top of second link B **862** by rotating T2 shaft **862** in sync with T1 shaft **870**. Similarly, end-effector A **860** may be retracted from right station **532** along a desired path, for instance, the same substantially straight-line path **818**, by rotating T3 shaft **874** in the clockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T3 shaft **874** so that end-effector A **860** follows the desired straight-line path **818**. Again, end-effector B **864** may be kept folded on top of second link B **862** by rotating T2 shaft **862** in sync with T1 shaft **870**. End-effector B **864** may then be extended to right station **532** along a desired path, for instance, a substantially straight-line path **818**, by rotating T2 shaft **872** in the counterclockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T2 shaft **872** so that end-effector B **864** follows the desired straight-line path **818**. At the same time, end-effector A **860** may be kept folded on top of second link A **858** by rotating T3 shaft **874** in sync with T1 shaft **870**. Further, end-effector B **864** may be retracted from right station **532** along a desired path, for instance, the same substantially straight-line path **818**, by rotating T2 shaft **872** in the clockwise direction while the rotation of T1 shaft **870** is coordinated with the rotation of T2 shaft **872** so that end-effector B **864** follows the desired straight-line path **818**. Again, end-effector A **860** may be kept folded on top of second link A **858** by rotating T3 shaft **874** in sync with T1 shaft **870**.

[0109] The operations and motions of FIGS. 34 and 35 represent examples, and the arm mechanism may perform any other desired operations and suitable motions. For

instance, rotations of some or all shafts **870**, **872** and **874** may be defined and coordinated so that the amount of motion of the retracted end-effector, for instance, end-effector A **860**, during the extension and retraction of the other end-effector, for instance, end-effector B **864**, is minimized. As another example, individual moves, such as extensions, retractions and rotations, may be blended and/or overlapped to achieve smooth motion paths and to reduce the overall duration of motion.

[0110] The examples of FIGS. 32 and 33 show the robot arm mechanism with the support structure **861** attached to rotary joint **890** below second link A **858**. However, support structure **861** may be attached to rotary joint **890** above second link A **858**, as shown diagrammatically in FIG. 36. An example internal arrangement of the example embodiment of FIG. 36 is depicted diagrammatically in FIGS. 37A and 37B. Alternatively, support structure **861** may be attached to rotary joint **90** in any suitable manner and may have any suitable shape.

[0111] The examples of FIGS. 32 to 37 depict the robot arm mechanism with second link A **858** and second link B **862** having equal lengths. However, second link A **858** and second link B **862** may have any suitable overall and joint-to-joint lengths. Similarly, although end-effector A **860** and end-effector B **864** are shown with equal lengths in the examples of FIGS. 32 to 37, the end-effectors may have any suitable lengths.

[0112] Although the example embodiments of FIGS. 32 to 37 are described with band arrangements **882** and **883**, any other suitable single- or multi-stage transmission arrangements with fixed or variable transmission ratios, including but not limited to chains and gears, may be used. Similarly, any other suitable single- or multi-stage transmission arrangements with appropriate variable transmission ratios, including but not limited to chains and gears, may be employed in place of band arrangements **92** and **104**. Furthermore, chains (e.g., in place of or in conjunction with bands, belts, or cables) as well as gears may be used in any embodiment disclosed herein.

[0113] One example of a suitable arrangement is shown in FIGS. 36 and 37 where robot **850'** is shown with end effector **860'** having a bridge that is mounted on an upper surface of a wrist joint as opposed to a bottom surface of a wrist joint as shown in FIG. 32. Another example of a suitable arrangement is shown in FIGS. 38A and 38B where robot **850''** is shown with offset shoulder joints **897**, **899**.

[0114] An example layout of a semiconductor wafer processing tool **1010** is diagrammatically depicted in the top view of FIG. 39. In this example, the tool features 4 pairs of side-by-side stations **1012**, for example, one pair of load locks and 3 pairs of process module stations **1012** coupled to the transport chamber **1014**. FIG. 40 shows a diagram of a side view of a robot **1050** with an example 2-degree-of-freedom 3-link robot arm mechanism **1054** installed on a robot drive unit **1056**. The arm mechanism **1054** may consist of a first link (upper arm) **1058**, a second link (forearm) **1060** and a third link (end-effector) **1062**. An example internal arrangement of the robot **1050** of FIG. 40 is depicted diagrammatically in FIGS. 41A and 41B. The arm mechanism may be driven by a two-axis **1064** with two coaxial shafts, for example, an outer T1 shaft **1066** and an inner T2 shaft **1068**. As illustrated in FIGS. 41A and 41B, orientation of the end-effector **1062** may be constrained by a band arrangement **1068**. The band arrangement **1068** may include

an elbow pulley **1070**, which may be connected to the first link **1058**, and a wrist pulley **1072**, which may be connected to the end-effector **1062** and a band, belt or cable, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. **41A** and **41B**, the wrist pulley **1072** may feature a non-circular profile and the elbow pulley **1070** may have a substantially circular profile. The variable transmission ratio may be selected so that the orientation of the end-effector changes in a predefined manner as a function of the relative position of the first link and the second link. For instance, it may be selected so that the end-effector may follow a path to a station, as illustrated in FIG. **39**.

[0115] An example with arrangement a variable transmission ratio that provides such functionality will be discussed, for example, see FIGS. **42A** to **45**. A suitable geometry of the arm mechanism, i.e., the joint-to-joint link and end-effector lengths, may be conveniently derived from the location of the station(s), the required reach of the end-effector, and the constraints and obstacles in the work space (which may determine the allowable swing radius of the arm mechanism in its retracted pose).

[0116] Determining an example length of the third link **1062**: The length of the third link, L_3 , may be conveniently defined as the distance between the axis of rotation of the wrist joint **1080** and a reference point on the third link **1082** (typically the nominal center of the end-effector). When the end-effector is extended to a station, there are three constraints in effect: 1) the position of the reference point on the third link (typically the nominal center of the end-effector) should be substantially aligned with the station location, 2) the end-effector should have a desired orientation, for instance, it may point straight along the access path to the station, and 3) the wrist joint should be far back enough so that it does not collide with any obstacles in the path to the station. The above constraints may be used to determine the length of the third link (end-effector), for instance, as the minimum value that complies with the constraints. an example, the following expression may be used:

$$L_3 = Y_{stm} - \sqrt{R_s^2 - X_{stm}^2} \quad (1)$$

where X_{stm} and Y_{stm} represent respectively the x-and y-axis offsets of the station location in a Cartesian coordinate system centered on the robot, i.e., the robot center (shoulder joint) is at (0, 0), and where R_s denotes the allowable swing radius R_s , which defines a circular space where the retracted robot arm mechanism can rotate freely.

[0117] Determining an example length of the second link: The joint-to-joint length of the second link, L_2 , may be defined as the distance between the axis of rotation of the elbow joint and the axis of rotation of the wrist joint. For a semiconductor wafer processing tool with pairs of side-by-side stations, such as the example layout of FIG. **39**, the length of the forearm may be conveniently selected to be equal to or, if necessary, larger than the offset of the station locations from the axis of symmetry of the side-by-side stations, i.e., as half of the distance between the station locations:

$$L_2 \geq X_{stm} \quad (2)$$

[0118] An L_2 larger than x_{stm} may be required to allow the end-effector of the arm mechanism to reach the required extension to a station without overextending its elbow joint.

[0119] Determining an example length of the first link: The joint-to-joint length of the first link, L_1 , may be defined as the distance between the axis of rotation of the shoulder joint and the axis of rotation of the elbow joint. Given the values of L_2 and L_3 , the length of the first link may be determined, for instance, so that the arm mechanism fits within the allowable swing radius when it is retracted:

$$L_1 = R_s - R_w + L_2 - L_3 \quad (3)$$

[0120] Here, R_w represents radius of a circular payload, such as a wafer, carried by the end-effector.

[0121] As an example, a station location may be selected with an x-axis offset X_{stm} of 388.6 mm and a y-axis offset Y_{stm} of 1,030.2 mm. The allowable swing radius R_s , which defines a circular space where the retracted robot arm mechanism can rotate freely, may be selected, for example, as 605.8 mm. The payload carried by the arm mechanism may be, for example, a circular wafer with a radius R_w of 150 mm. Based on the above example guidelines, the geometry of a suitable example arm mechanism, i.e., the joint-to-joint link and end-effector lengths, may be determined as follows: $L_3=565.5$ mm, $L_2=397.6$ mm $> X_{stm}=388.6$ mm and $L_1=287.9$ mm.

[0122] Considering the example arm mechanism of FIGS. **40** and **41** where the orientation of the end-effector may be constrained, for instance, by a band arrangement with a circular elbow pulley and a non-circular wrist pulley, and assuming the above example station locations and arm mechanism geometry, the wrist pulley may have a profile as depicted by the line **1102** in FIG. **42A** (the figure shows one half of the profile for clarity). The relative orientation of the wrist pulley with respect to the third link (end-effector) is illustrated by the solid arrow **1104**, which points from the axis (center) of the wrist joint along the longitudinal axis of the third link toward the center of the end-effector. For comparison, the circular elbow is represented by the line **1106**.

[0123] FIGS. **42B-42E** illustrates how the orientation of the end-effector **1062** of the above example arm mechanism with the wrist pulley profile defined according to FIG. **4A** is constrained as a function of the relative angle of the second link **1060** with respect to the first link **1058** (i.e., relative angle between the first and second links).

[0124] FIG. **43** shows a pulley profiles that may be used for the same arm geometry as the previous pulley profile example, and may produce the same or similar motion. Here, end effector orientation **1120** is shown by the black arrow and elbow pulley profile **1124** and wrist pulley profile **1122** are shown as non-circular.

[0125] A belt/band/cable arrangement may be provided that constraints the orientation of the end-effector using two non-circular pulleys. For example, this may be applied both to the single end-effector configuration (FIGS. **42A-42E** or otherwise) as well as the two end-effector configurations

(FIGS. 32 and 36 or otherwise), which all may share substantially the same kinematics. In this additional example, the elbow pulley connected to the upper arm is non-circular and so is the wrist pulley connected to the end-effector. This may be provided as an alternative to examples of pulley profiles for a special case where the elbow pulley was circular and the wrist pulley was non-circular. By way of example, pulley profiles are shown in the FIG. 43. Similarly to FIG. 42A, only one half of each non-circular pulley is shown. Here, the profiles are generated for the same arm geometry (link lengths) as the previous example of non-circular pulley.

[0126] An example phased motion of the robot arm mechanism as the end-effector of the robot arm mechanism extends along a straight path to the above example station is depicted in FIG. 44. In order for the end-effector of the robot arm mechanism to follow the example motion of FIG. 44, the shafts of the robot drive unit may be actuated as shown in the diagram 1150 in FIG. 45 showing T1 shaft position vs time 1152 and T2 shaft position vs time 1154.

[0127] Another example phased motion of the robot arm mechanism as the end-effector extends to the same example station, this time along a path formed by two segments 1200, 1202 blended around a common via-point 1204, is depicted in FIG. 46. In order to achieve the example motion of FIG. 46, the shafts of the robot drive unit may be rotated as shown in diagram 1250 in FIG. 47 showing T1 shaft position vs time 1252 and T2 shaft position vs time 1254.

[0128] In FIGS. 45 and 47, the zero point for the angles of the shafts of the robot drive unit is defined as follows: when the arm mechanism is in the folded pose (retracted pose) with the third link (end-effector) pointing along the x-axis (i.e., pointed at 3 o'clock), the T1 shaft angle is 0 deg and the T2 shaft angle is at 180 deg. The angle of the first link is 0 deg, the angle of the second link is 180 deg, and the angle of the third link (end-effector) is 0 deg in this situation.

[0129] FIG. 48 shows a diagram of a side view of a robot 300 with an example robot arm mechanism 1310 with two end-effectors installed on a robot drive unit 1312. The arm mechanism may consist of a first link 1314 (upper arm), a second link 1316 (forearm) A, a third link 1318 (end-effector) A, a second link 1320 (forearm) B and a third link 1322 (end-effector) B.

[0130] An example internal arrangement of the robot of FIG. 48 is depicted diagrammatically in FIGS. 49A and 49B. The arm mechanism may be driven by a three-axis spindle with three coaxial shafts, for example, an outer T1 1340 shaft, a T2 shaft 1342 and an inner T3 shaft 1344. In embodiments, some the T2 shaft 1342 may be partially within the outer T1 1340 shaft, and the inner T3 shaft 1344 may be partially within the T2 shaft 1342. Orientation of end-effector A may be constrained by a band arrangement. The band arrangement may include an elbow pulley, which may be connected to the first link, and a wrist pulley, which may be connected to the support structure with end-effector A, and a band, belt or cable, which may transmit motion between the two pulleys. The band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIG. 49, the wrist pulley may feature a non-circular profile and the elbow pulley may have a substantially circular profile. Similarly, orientation of end-effector B may be constrained by another band arrangement. The band

arrangement may comprise an elbow pulley, which may be connected to the first link, a wrist pulley, which may be connected to end-effector B, and a band, belt or cable, which may transmit motion between the two pulleys. Again, the band arrangement may feature a variable transmission ratio. The variable transmission ratio may be implemented, for instance, using at least one pulley with a non-circular profile. As an example, referring to FIGS. 49A and 49B, the wrist pulley may feature a non-circular profile and the elbow pulley may have a substantially circular profile. The variable transmission ratios may be selected so that the orientation of each of the two the end-effectors changes in a predefined manner as a function of the relative position of the first link and the corresponding second link. For instance, it may be selected so that the end-effectors may follow a path to a station, as illustrated in FIG. 39. An example is discussed below.

[0131] A suitable geometry of the arm mechanism of FIGS. 48 and 49, i.e., the joint-to-joint link and end-effector lengths, may be determined based on the same guidelines as described above for the example 2-degree-of-freedom 3-link robot arm mechanism of FIG. 40.

[0132] Similarly, considering the example arm mechanism of FIGS. 40 and 41 where the orientation of the end-effectors may be constrained, as an example, by band arrangements with circular elbow pulleys and non-circular wrist pulleys, and assuming the example station locations and arm mechanism geometry selected earlier ($X_{sm}=388.6$ mm, $Y_{sm}=1,030.2$ mm, $L1=287.9$ mm, $L2A=L2B=L2=397.6$ mm and $L3A=L3B=L3=565.5$ mm), the same profile as discussed earlier with respect to FIG. 4 may be used for the two wrist pulleys.

[0133] An example phased motion of the robot arm mechanism as end-effector A extends along a straight path 1440 to the above example station is depicted in FIG. 50. In this particular example, end-effector B along with second link B remain folded on top of the first link so that they stay within the allowable swing radius of the robot arm mechanism. In order for the robot arm mechanism to follow the example motion of FIG. 50, the shafts of the robot drive unit may be actuated according to the example motion profiles of diagram 490 of FIG. 51 showing T1 shaft position vs time 1492 and T2 shaft position vs time 1494 and T3 shaft position vs time 1496.

[0134] Another example phased motion of the robot arm mechanism as end-effector A extends to the same example station, this time along a path formed by two segments 1540, 1542 blended around a common via-point 1544, is depicted in FIG. 52. In this example, the motion of second link B and, consequently, end-effector B is controlled to limit the range of motion of the payload carried on end-effector B. In order to achieve the example motion of FIG. 52, the shafts of the robot drive unit may be rotated as shown in the example of diagram 1640 of FIG. 53 showing T1 shaft position vs time 1642 and T2 shaft position vs time 1644 and T3 shaft position vs time 1646.

[0135] In FIGS. 51 and 53, the zero point for the angles of the shafts of the robot drive unit is defined as follows: when the arm mechanism is in the folded pose (retracted pose) with the third links (end-effectors) A and B pointing along the x-axis (i.e., pointed at 3 o'clock), the T1 shaft angle is 0 deg while the T2 and T3 shaft angles are at 180 deg. The angle of the first link is 0 deg, the angles of the second links

A and B are at 180 deg, and the angles of the third links (end-effectors) A and B are at 0 deg in this situation.

[0136] In accordance with one aspect, an apparatus has a drive unit having a first drive axis rotatable about a first axis of rotation and a second drive axis rotatable about a second axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis. A robot arm has an upper arm connected to the drive unit at the first drive axis, a forearm coupled to the upper arm, the forearm being coupled to the upper arm at a first rotary joint and rotatable about the first rotary joint, the first rotary joint being actuatable by a first band arrangement coupled to the second drive axis, and an end effector coupled to the forearm, the end effector being coupled to the forearm at a second rotary joint and rotatable about the second rotary joint, the second rotary joint being actuatable by a second band arrangement coupled to the first rotary joint. The second band arrangement is configured to provide a variable transmission ratio.

[0137] In accordance with another aspect, the first band arrangement comprises a shoulder pulley attached to the second drive axis, a first elbow pulley coupled to the forearm, and a band, belt, or cable arranged between the shoulder pulley and the first elbow pulley to transmit motion between the shoulder pulley and the first elbow pulley.

[0138] In accordance with another aspect, the second band arrangement comprises a second elbow pulley coupled to the upper arm, a wrist pulley coupled to the end effector, and a band, belt, or cable arranged between the second elbow pulley and the wrist pulley to transmit motion between the second elbow pulley and the wrist pulley.

[0139] In accordance with another aspect, at least one of the second elbow pulley and the wrist pulley have a non-circular profile to provide the variable transmission ratio.

[0140] In accordance with another aspect, the variable transmission ratio is selected such that orientation of the end effector changes in a predefined manner as a function of relative positions of the upper arm and forearm.

[0141] In accordance with another aspect, one or more of the first drive axis and the second drive axis are axially movable to facilitate vertical movement of the robot arm.

[0142] In accordance with another aspect, an apparatus has a drive unit having a first drive axis rotatable about a first axis of rotation, a second drive axis rotatable about a second axis of rotation, and a third drive axis rotatable about a third axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis, and the third drive axis being coaxial with and partially within the second drive axis and axially rotatable within the second drive axis. A robot arm has an upper arm connected to the drive unit at the first drive axis, a forearm coupled to the upper arm, the forearm being coupled to the upper arm at a first rotary joint and rotatable about the first rotary joint, the first rotary joint being actuatable by a single-stage band arrangement comprising first shoulder pulley actuatable by the third drive axis, a first elbow pulley partially forming the first rotary joint, and a belt, band or cable configured to transmit motion between the first shoulder pulley and the first elbow pulley, a first end effector and a second end effector coupled to the forearm, the first end effector and the second end effector being coupled to the forearm at a second rotary joint, orientation of the first end effector and the second end effector being controlled via a two-stage band arrangement. A first stage of the two-stage

band arrangement comprises a second shoulder pulley actuatable by the second drive axis, a second elbow pulley partially forming the first rotary joint, and an upper band, belt, or cable configured to transmit motion between the second shoulder pulley and the second elbow pulley. A second stage of the two-stage band arrangement comprises a third elbow pulley coupled to the second elbow pulley, a first wrist pulley coupled to the first end effector, and a first lower belt, band, or cable configured to transmit motion between the third elbow pulley and the first wrist pulley, and wherein the second stage of the two-stage band arrangement further comprises a fourth elbow pulley coupled to the second elbow pulley, a second wrist pulley coupled to the second effector, and a second lower belt, band, or cable configured to transmit motion between the fourth elbow pulley and the second wrist pulley. At least one of the motion between the first shoulder pulley and the first elbow pulley, the motion between the second shoulder pulley and the second elbow pulley, the motion between the third elbow pulley and the first wrist pulley, and the motion between the fourth elbow pulley and the second wrist pulley are at a variable transmission ratio.

[0143] In accordance with another aspect, at least one of the third elbow pulley and the first wrist pulley have a non-circular profile to provide the variable transmission ratio to the two-stage band arrangement.

[0144] In accordance with another aspect, at least one of the fourth elbow pulley and the second wrist pulley have a non-circular profile to provide the variable transmission ratio to the two-stage band arrangement.

[0145] In accordance with another aspect, at least one of the first lower belt, band, or cable and the second lower belt, band, or cable is configured in a crossover configuration.

[0146] In accordance with another aspect, the variable transmission ratio is selected such that orientations of the first end effector and the second end effector change in predefined manners as a function of relative positions of the upper arm and forearm and the second drive axis.

[0147] In accordance with another aspect, the first rotary joint is one of on a right hand side of an imaginary line extending from the first shoulder pulley to the first wrist pulley and on a left hand side of an imaginary line extending from the first shoulder pulley to the first wrist pulley.

[0148] In accordance with another aspect, an apparatus has a drive unit having a first drive axis rotatable about a first axis of rotation, a second drive axis rotatable about a second axis of rotation, and a third drive axis rotatable about a third axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis, and the third drive axis being coaxial with and partially within the second drive axis and axially rotatable within the second drive axis. A first robot arm has a first upper arm connected to the drive unit at the first drive axis, a first forearm coupled to the first upper arm, the first forearm being coupled to the first upper arm at a first rotary joint, the first rotary joint being actuatable by the second drive axis using a first band arrangement, and a first end effector coupled to the first forearm, the first end effector being coupled to the first forearm at a third rotary joint, the third rotary joint being actuatable by the first rotary joint using a third band arrangement. A second robot arm has a second upper arm connected to the drive unit at the third drive axis, a second forearm coupled to the second upper arm, the second forearm being coupled to the second upper

arm at a second rotary joint, the second rotary joint being actuatable by the second drive axis using a second band arrangement, and a second end effector coupled to the second forearm, the second end effector being coupled to the second forearm at a fourth rotary joint, the fourth rotary joint being actuatable by the second rotary joint using a fourth band arrangement. At least one of the first band arrangement, the second band arrangement, the third band arrangement, and the fourth band arrangement has a variable transmission ratio.

[0149] In accordance with another aspect, the first band arrangement comprises a first shoulder pulley attached to the first drive axis, a first elbow pulley attached to the first forearm, and a first band, belt, or cable configured to transmit motion between the first shoulder pulley and the first elbow pulley.

[0150] In accordance with another aspect, at least one of the first shoulder pulley and the first elbow pulley have a non-circular profile to provide the variable transmission ratio to the first band arrangement.

[0151] In accordance with another aspect, the third band arrangement comprises a second elbow pulley operable with the first elbow pulley, a first wrist pulley coupled to the first end effector, and a third band, belt, or cable configured to transmit motion between the second elbow pulley and the first wrist pulley.

[0152] In accordance with another aspect, at least one of the second elbow pulley and the first wrist pulley have a non-circular profile to provide the variable transmission ratio to the third band arrangement.

[0153] In accordance with another aspect, the second band arrangement comprises a second shoulder pulley attached to the third drive axis, a third elbow pulley attached to the second forearm, and a second band, belt, or cable configured to transmit motion between the second shoulder pulley and the third elbow pulley.

[0154] In accordance with another aspect, at least one of the second shoulder pulley and the third elbow pulley have a non-circular profile to provide the variable transmission ratio to the second band arrangement.

[0155] In accordance with another aspect, the fourth band arrangement comprises a fourth elbow pulley operable with the third elbow pulley, a second wrist pulley coupled to the second end effector, and a fourth band, belt, or cable configured to transmit motion between the fourth elbow pulley and the second wrist pulley.

[0156] In accordance with another aspect, at least one of the fourth elbow pulley and the second wrist pulley have a non-circular profile to provide the variable transmission ratio to the fourth band arrangement.

[0157] In accordance with another aspect, the variable transmission ratio is selected such that orientations of the first end effector change in predefined manners as a function of relative positions of the first upper arm and first forearm.

[0158] In accordance with another aspect, a transmission ratio of the first band arrangement and a transmission ratio of the third band arrangement are selected such that a center point on the first end effector is configured to follow a predetermined path with a predetermined orientation of the first end effector when the first upper arm is actuated by the first drive axis and the second drive axis is stationary.

[0159] In accordance with another aspect, the variable transmission ratio is selected such that orientations of the

second end effector change in predefined manners as a function of relative positions of the second upper arm and second forearm.

[0160] In accordance with another aspect, a transmission ratio of the second band arrangement and a transmission ratio of the fourth band arrangement are selected such that a center point on the second end effector is configured to follow a predetermined path with a predetermined orientation of the second end effector when the second upper arm is actuated by the third drive axis and the second drive axis is stationary.

[0161] It should be understood that the foregoing description is only illustrative. Various alternatives and modifications can be devised by those skilled in the art. For example, features recited in the various dependent claims could be combined with each other in any suitable combination(s). In addition, features from different embodiments described above could be selectively combined into a new embodiment. Accordingly, the description is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

What is claimed is:

1. A transport apparatus, comprising:

a drive unit having a first drive axis rotatable about a first axis of rotation, a second drive axis rotatable about a second axis of rotation, and a third drive axis rotatable about a third axis of rotation, the second drive axis being coaxial with and partially within the first drive axis and axially rotatable within the first drive axis, and the third drive axis being coaxial with and partially within the second drive axis and axially rotatable within the second drive axis;

a robot arm comprising:

an upper arm connected to the drive unit at the first drive axis,

a forearm coupled to the upper arm, the forearm being coupled to the upper arm at a first rotary joint and rotatable about the first rotary joint, the first rotary joint being actuatable by a single-stage band arrangement comprising a first shoulder pulley actuatable by the third drive axis, a first elbow pulley partially forming the first rotary joint, and a belt, band or cable configured to transmit motion between the first shoulder pulley and the first elbow pulley,

a first end effector and a second end effector coupled to the forearm, the first end effector and the second end effector being coupled to the forearm at a second rotary joint, orientation of the first end effector and the second end effector being controlled via a two-stage band arrangement which comprises at least one pulley with a non-circular profile,

wherein a first stage of the two-stage band arrangement comprises a second shoulder pulley actuatable by the second drive axis, a second elbow pulley partially forming the first rotary joint, and an upper band, belt, or cable configured to transmit motion between the second shoulder pulley and the second elbow pulley,

wherein a second stage of the two-stage band arrangement comprises a third elbow pulley coupled to the second elbow pulley, a first wrist pulley coupled to the first end effector, and a first lower belt, band, or cable configured to transmit motion between the third elbow pulley and the first wrist pulley, and wherein the second stage of the two-stage band arrangement further comprises a

fourth elbow pulley coupled to the second elbow pulley, a second wrist pulley coupled to the second effector, and a second lower belt, band, or cable configured to transmit motion between the fourth elbow pulley and the second wrist pulley,

wherein at least one of the motion between the first shoulder pulley and the first elbow pulley, the motion between the second shoulder pulley and the second elbow pulley, the motion between the third elbow pulley and the first wrist pulley, and the motion between the fourth elbow pulley and the second wrist pulley are at a variable transmission ratio.

2. The apparatus of claim 1, wherein at least one of the third elbow pulley and the first wrist pulley have a non-circular profile to provide the variable transmission ratio to the two-stage band arrangement.

3. The apparatus of claim 1, wherein at least one of the fourth elbow pulley and the second wrist pulley have a

non-circular profile to provide the variable transmission ratio to the two-stage band arrangement.

4. The apparatus of claim 1, wherein at least one of the first lower belt, band, or cable and the second lower belt, band, or cable is configured in a crossover configuration.

5. The apparatus of claim 1, wherein the variable transmission ratio is selected such that orientations of the first end effector and the second end effector change in predefined manners as a function of relative positions of the upper arm and forearm and the second drive axis.

6. The apparatus of claim 1, wherein the first rotary joint is one of on a right hand side of an imaginary line extending from the first shoulder pulley to the first wrist pulley and on a left hand side of an imaginary line extending from the first shoulder pulley to the first wrist pulley.

* * * * *