

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415141
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Wu; Jinhong

Joystick fastening device

Abstract

The present invention discloses a joystick fastening device and a joystick application assembly, comprising the components: an reception cavity whose one end has a joystick receiving opening; a connection, of which one end opposite to the reception cavity shell has a first connecting portion; and an extension having a second connecting portion and connected with the first connecting portion via the second connecting portion to realize the special movement of the joystick via the extension. The present invention can prevent the joystick from releasing, significantly reduce shake-off of the joystick, and provide better gaming experience.

Inventors:	Wu; Jinhong (Shenzhen, CN)
Applicant:	Wu; Jinhong (Shenzhen, CN)
Family ID:	1000008820226
Appl. No.:	18/660292
Filed:	May 10, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250073603 A1	Mar. 06, 2025

Foreign Application Priority Data

CN	202322405737.9	Sep. 04, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: A63F13/98 (20140101); A63F13/245 (20140101)

U.S. Cl.:

Field of Classification Search**CPC:** A63F (13/98); A63F (13/245); A63F (2300/1043); A63F (2300/1062); A63F (2300/8082)**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4630823	12/1985	Grant	273/148B	A63F 13/24
4909514	12/1989	Tano	273/148B	A63F 13/803
5046739	12/1990	Reichow	273/148B	A63F 13/02
5207791	12/1992	Scherbarth	224/678	F16M 11/00
5419613	12/1994	Wedeking	248/205.2	A63F 13/24
5801918	12/1997	Ahearn	361/679.55	G06F 15/0216
6688571	12/2003	Pauls	248/282.1	A61G 5/10
D568882	12/2007	Ashida	D21/333	N/A
D583875	12/2007	Roberts	D21/324	N/A
D590893	12/2008	Roberts	D21/324	N/A
D599352	12/2008	Takamoto	D21/333	N/A
D631098	12/2010	Ashida	D21/333	N/A
8057309	12/2010	Mead	463/47	A63F 13/837
D654118	12/2011	Sogabe	D14/218	N/A
8298090	12/2011	Kazama	463/47	A63F 13/837
8419541	12/2012	Mao	463/37	A63F 13/285
8568233	12/2012	Block	463/47	A63F 13/98
8870653	12/2013	Yamashita	463/36	A63F 13/213
8894490	12/2013	Brandt	463/3	A63F 13/98
D769373	12/2015	Sogabe	D14/218	N/A
10471344	12/2018	Nokuo	N/A	A63F 13/245
10857471	12/2019	Hirose	N/A	A63F 13/98
D931374	12/2020	Meng	D21/333	N/A
11426651	12/2021	Jensen	N/A	A63F 13/245
11577173	12/2022	Armand	N/A	A63F 13/98
D988409	12/2022	Chen	D21/333	N/A
D997249	12/2022	Wu	D21/333	N/A
2004/0180719	12/2003	Feldman	463/36	A63B 24/00
2008/0015017	12/2007	Ashida	463/37	A63F 13/803

2009/0082108	12/2008	Ye	463/39	A63F 13/20
2009/0149255	12/2008	Fu	463/36	A63F 13/98
2010/0255913	12/2009	Kidakarn	463/37	A63F 13/98
2011/0034250	12/2010	Brandt	463/37	A63F 13/245
2011/0081968	12/2010	Mar	463/37	A63F 13/245
2011/0190056	12/2010	Xu	345/169	G06F 3/02
2011/0244962	12/2010	Kidakarn	463/36	A63F 13/245
2011/0306424	12/2010	Kazama	463/37	A63F 13/98
2012/0122576	12/2011	Mao	463/32	A63F 13/245
2013/0196769	12/2012	Shocklee	463/37	A63B 15/00
2021/0077912	12/2020	Armand	N/A	A63F 13/98
2023/0294004	12/2022	O'Dowd	463/47	A63F 13/98

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201133614	12/2007	CN	A63F 13/02
218106714	12/2021	CN	N/A
2010279817	12/2009	JP	N/A
2014060419	12/2013	JP	A63F 13/02
WO-2007016660	12/2006	WO	A63F 13/06
WO-2007095082	12/2006	WO	A63F 11/00

OTHER PUBLICATIONS

“Characteristics of Thermosets Part 20: Tensile Testing Part One,” by Jeffrey Gotro, published Oct. 2, 2017, Polymer Innovation Blog. (Year: 2017). cited by examiner

“ZyberVR Quest 2 Gorilla Tag Long Arms Fitness Dual Sticks,” published Apr. 5, 2023. Source: <https://zybervr.com/products/zybervr-dual-handles-extension-grips-for-oculus-quest-2?> (Year: 2023). cited by examiner

“Hands On Review Yoges Handle Attachments for Quest 2 Controllers,” by Jon Jaehnig. Published Aug. 10, 2023. Source: <https://arpost.co/2023/08/10/review-yoges-adapters-quest-2-controllers/> (Year: 2023). cited by examiner

Primary Examiner: Hylinski; Steven J

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority to Chinese Patent Application No. 202322405737.9, filed on Sep. 4, 2023, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) The present invention relates to the technical field of joysticks, in particular to a joystick fastening device.

BACKGROUND

(3) Joystick or joystick assembly is a common interactive device for games or virtual reality (VR). By gripping the joystick, a user can make a corresponding action and manipulate a game or simulate a realistic action in a virtual scenario for better gaming experience. Although the authentic joystick can satisfy the user's gaming operation in the basic functions, but some special gaming scenarios, for example, saber, golf, table tennis, shooting and fishing, have certain requirements for the size and grip sense of the joystick, while the authentic joystick is too small to enable the user to achieve good experience and a greater level of immersion in conceivable ways.

(4) In order to further enhance the realistic experience of the game, some joysticks will be equipped with external extensions, some of which are directly equipped with a lengthened shell on the lower part of the joystick and the shell will be connected to the original shell by using a rope passing through the cable of the joystick. Nevertheless, such structure is not reliable, and sometimes the joystick and the lengthened shell are disconnected during gaming, thereby causing accidental release of the joystick and hitting against on people or other objects, and resulting in bad effects and poor gaming experience.

SUMMARY

(5) The technical solution of the present invention is to provide a joystick fastening device, which can solve the technical problems in the prior art that the authentic joystick is too small to enable the user to achieve good experience and a greater level of immersion in conceivable ways, and the joystick and the lengthened shell are disconnected during gaming, thereby causing accidental release of the joystick and hitting against on people or other objects, and resulting in bad effects and poor gaming experience. At any rate, the joystick is not released during gaming, significantly reducing shake-off of the joystick, avoiding risks and providing a better gaming experience.

(6) A technical solution of the present invention for solving the above technical problems is:

(7) A joystick fastening device, comprising the components: An reception cavity whose one end has an opening for receiving a joystick; the other end of the reception cavity away from the opening in the longitudinal direction of the opening is a cavity bottom whose size is less than or equal to that of the opening; the reception cavity further comprises a hole, and the hole is arranged at a position outside the opening; A connection, which extends from a reception cavity shell at a preset angle to a central axis of the reception cavity, and one end of the connection opposite to the reception cavity shell has a first connecting portion; An extension, which has a second connecting portion matched with the first connecting portion of the connection, and is connected to the first connecting portion via the second connecting portion so as to realize spatial movement of the joystick via the extension; and A fastener for fastening the joystick.

(8) Preferably, the preset angle ranges from 0° (included) to 180° (included); the fastener comprises at least one of a strap, a buckle, a screw, or a nut; the fastener is designed to lock the joystick to limit movement of the joystick in the reception cavity.

(9) Preferably, the strap has a first end and a second end arranged outside the first end, wherein the first end of the strap is fixedly connected to the joystick, and the second end passes through the hole or is fixed on the connection or the reception cavity shell; the strap may be tightened to provide the joystick with a pulling force along the bottom of the reception cavity as the second end passes through the hole.

(10) Preferably, the buckle has a raised member which snaps into the hole to provide the joystick with a pushing force along the cavity bottom so as to limit the longitudinal movement of the joystick along the reception cavity.

(11) Preferably, the buckle is mounted on the joystick at a distance from the opening in the longitudinal direction of the reception cavity, and the raised member of the buckle snaps into the hole to provide the joystick with a pushing force along the cavity bottom so as to limit the longitudinal movement of the joystick along the reception cavity.

(12) Preferably, the buckle has a rotary shaft, the rotary shaft is mounted on the reception cavity shell, and the buckle can rotate along the direction of rotation of the rotary shaft.

(13) Preferably, a screw passes through the hole, and by means of rotating the screw, the reception volume of the reception cavity may be changed to limit the movement of the joystick in the reception cavity.

(14) Preferably, a nut is mounted on the reception cavity shell, and by means of rotating the nut, the reception volume of the reception cavity may be changed to limit the movement of the joystick in the reception cavity.

(15) Preferably, the joystick further comprises an elastic material, and the joystick is fixed at an inner wall of the reception cavity by the elastic material, and the friction between the joystick and the inner wall of the reception cavity is increased by the elastic material.

(16) Preferably, the connection further comprises a rotary member arranged between the first connecting portion and the reception cavity wall for fastening or tightening the strap.

(17) Preferably, the first connecting portion of the connection comprises at least one of a fixing hole, a threading, a slot, and a raised member, and the connection is designed to fixedly connect the extension; the second connecting portion of the extension comprises at least one of a fixing hole, a threading, a slot, and a raised member to fixedly connect the connection.

(18) Preferably, the rotary member comprises a rotary shell and a rotary fixed shaft, wherein the rotary shell has a strap fixing part for fixing the strap, the inner wall of the rotary shell has a concave structure, the rotary fixed shaft has a convex structure corresponding to the concave structure of the rotary shell, the concave structure and the convex structure can be clamped and rotated to tighten the strap.

(19) Preferably, one end of the extension has a grip at the second connecting portion away from the reception cavity.

(20) Preferably, the grip has a male-female anti-slip structure made of resilient material.

(21) Preferably, the extension further comprises a telescopic structure for adjusting the length of the extension.

(22) Preferably, the telescopic structure comprises: An outer extension, which is designed for limiting the shortest length of the extension and provided with a grip; the outer extension has a through-hole structure, the first end of the outer extension has a threading structure, the size of the through-hole corresponding to the outlet of the first end of the outer extension is smaller than outer diameter of the first end of the inner extension, and the size of the through-hole of the outer extension is larger than the outer diameter of the first end of the inner extension, except for the outlet of the first end of the outer extension; A locking elastic member for locking the movement of the inner extension, comprising at least one of a slotted deformation structural member and an elastic material; A locking rotary member, which is designed for adjusting the deformation of the locking elastic member, and provided with a through-hole structure and with an internal threading, and the size of a first end opening of the locking rotary member is greater than a second end opening corresponding to the first end opening of the locking rotary member; The inner extension is sleeved inside the outer extension, a first end portion of the non-inner extension of the inner extension can pass through a first end outlet of the outer extension, a locking elastic member is mounted on the through-hole of the locking rotary member, the locking elastic member and locking rotary member pass through the inner extension which extends out of the first end outlet portion of the outer extension, and are rotatably connected to a threading structure of the outer extension, when the locking member is locked, the locking elastic member deforms to lock the movement of the inner extension, and when the locking member is released, the locking elastic member deforms slightly to release the inner extension, and the inner extension can move telescopically. Preferably, the reception cavity is transparent.

(23) More preferably, the material of the reception cavity is PC.

(24) One or more technical solutions provided in the present application have at least the following technical effects or advantages:

(25) The technical solution above provides a reception cavity for receiving the joystick, a

connection extending from the reception cavity and an extension connected to the connection, and can satisfy users' experience demand in different game scenarios. The joystick with a lengthened extension can satisfy users' experience demands in recreational games such as golf, fencing or billiards, and the joystick with a short extension can satisfy users' experience demands in such games as table tennis and saber for better experience feel.

(26) With the adoption of one or more fasteners of a strap, a buckle, a screw and a nut, the movement of the joystick may be limited in combination with the hole of the reception cavity, i.e. the strap provides a pulling force, the buckle limits or provides a pushing force, and the screw and nut limit the volume of the reception cavity in combination with the elastic material, thereby preventing the joystick from releasing from the reception cavity during use, or shake-off, avoiding any risks and providing a better game experience.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a schematic diagram of the stereostructure of the present invention;
- (2) FIG. 2 is a schematic diagram of the joystick application assembly when connected to the joystick fastening device of the present invention;
- (3) FIG. 3 is a schematic diagram of the present invention in a separated state;
- (4) FIG. 4 is a schematic diagram of the present invention when a buckle is used as a fastener;
- (5) FIG. 5 is a schematic diagram of the present invention when a nut is used as a fastener;
- (6) FIG. 6 is a schematic diagram of the present invention when a screw is used as a fastener;
- (7) FIG. 7 is a schematic diagram of the rotatory fixed shaft of the present invention.
- (8) In the figures, **100** means reception cavity, **1001** opening, **1003** cavity bottom, **1005** hole, **1007** shell, **200** connection, **2001** first connecting portion, **2003** second connecting portion, **2011** concave structure, **2013** raised structure, **250** rotary member, **251** rotary fixed shaft, **2511** first rotary fixed shaft, **2513**, second rotary fixed shaft, **2515** first limiting post, **2517** second limiting post, **300** extension, **310** grip, **400**, joystick application assembly, **500** fastener, **501** buckle, **5011** raised member, **503** nut and **505** screw.

DESCRIPTION OF EMBODIMENTS

(9) The following describes the present invention in detail with reference to embodiments and the figures. It is noted that the following embodiments are only used to explain the present invention, and do not constitute a limitation on the present invention. Moreover, the technical features related to the embodiments of the present invention described as follows can combine with each other when they are not conflict with each other.

(10) The technical solutions of the embodiments of the present application solve the problems in the prior art in some special game scenarios, such as saber, golf, table tennis, shooting and fishing by providing a joystick fastening device, which comprises a joystick application assembly **400** connected to the joystick fastening device. For the problems that the authentic joystick is too small to enable the user achieve good experience and a greater level of immersion in conceivable ways, and the joystick (or joystick application assembly **400**) and the extension **300** are disconnected during gaming, thereby causing accidental release of the joystick and hitting against on people or other objects, bad effects and poor gaming experience, a connection **200** is connected in the reception cavity **100**, an extension **300** is connected with the connection **200**, and the joystick (or joystick application assembly) is fastened with a fastener **500** to prevent the joystick releasing during use, significantly reducing shake-off of the joystick, avoiding risks and providing a better gaming experience.

(11) The general idea of the embodiments of the present invention for solving the above technical problems is as follows:

(12) Providing a joystick fastening device, which comprises a joystick application assembly **400** connected to the joystick fastening device, as shown in FIGS. **1** and **2**, wherein the joystick fastening device comprises a reception cavity **100**, a connection **200**, an extension **300** and a fastener **500**; the reception cavity **100** is connected to the connection **200**, the connection is connected to the extension **300**, and fixes the joystick (or the joystick application assembly **400**) via the fastener **500**. Thus, the extension **300** with proper length can enhance the gaming experience with the joystick (VR joystick) or joystick application assembly **400** (VR joystick application assembly **400**). Meanwhile, the joystick or the joystick application assembly **400** may be prevented from releasing during use via the fastener **500**, significantly reducing shake-off of the joystick or joystick application assembly **400**, avoiding risks and providing a better gaming experience. The lengthened extension **300** can satisfy consumers' good experience feel demands for such games as golf, fencing or billiards.

(13) To make the technical solutions above clear, the following further describes the present invention in detail with reference to the drawings of the specification and embodiments.

(14) A joystick fastening device, as shown in FIG. **3**, comprising the components:

(15) An reception cavity **100** whose one end has an opening **1001** for receiving a joystick or joystick application assembly **400**; the other end of the reception cavity **100** away from the opening **1001** in the longitudinal direction of the opening **1001** is a cavity bottom **1003**, and the size of the cavity bottom **1003** is less than or equal to the size of the opening **1001**; the reception cavity **100** further comprises a hole **1005**, and the hole **1005** is arranged at a position outside the opening **1001**;

(16) A connection **200**, which extends from the shell **1007** of the reception cavity **100** at a preset angle to the central axis of the reception cavity **100**, and one end of the connection **200** opposite to the reception cavity **100** shell **1007** has a first connecting portion **2001**;

(17) An extension **300**, which has a second connecting portion **2003** matched with the first connecting portion **2001** of the connection **200**, and is connected to the first connecting portion **2001** via the second connecting portion **2003** so as to realize spatial movement of the joystick via the extension **300**.

(18) The embodiments of the present invention also provide a joystick application assembly **400** that can be connected to the joystick fastening device of any of the above.

(19) Specifically, the joystick application assembly **400** comprises a VR hand-held application assembly, wherein application game scenarios of the VR hand-held application assembly comprise saber, golf, table tennis, shooting and fishing.

(20) Specifically, the preset angle ranges from 0° (included) to 180° (included); the joystick application assembly also comprises a fastener **500** designed for fixing the joystick and comprising at least one of a strap, a buckle **501**, a screw **505**, or a nut **503**; the fastener is designed to lock the joystick to limit movement of the joystick in the reception cavity **100**.

(21) Specifically, the strap has a first end and a second end (not shown in the figure) arranged outside the first end, wherein the first end of the strap is fixedly connected to the joystick, and the second end passes through the hole **1005** or is fixed on the connection **200** or the reception cavity **100** shell **1007**; the strap may be tightened to provide the joystick with a pulling force along the reception cavity **100** bottom as the second end passes through the hole **1005**.

(22) Specifically, the joystick further comprises an elastic material, and the joystick is fixed at an inner wall of the reception cavity **100** by the elastic material, and the friction between the joystick and the inner wall of the reception cavity **100** is increased by the elastic material.

(23) Specifically, the connection **200** further comprises a rotary member **250** arranged between the first connecting portion **2001** and the reception cavity **100** wall for fastening or tightening the strap.

(24) Specifically, the first connecting portion **2001** of the connection **200** comprises at least one of a fixing hole, a threading, a slot, and a raised member **5011**, and the connection **200** is designed to fixedly connect the extension **300**; the second connecting portion **2003** of the extension **300**

comprises at least one of a fixing hole, a threading, a slot, and a raised member **5011** to fixedly connect the connection **200**.

(25) Specifically, the rotary member **250** comprises a rotary shell **1007** and a rotary fixed shaft **251**, wherein the rotary shell **1007** has a strap fixing part for fixing the strap, the inner wall of the rotary shell **1007** has a concave structure **2011**, the rotary fixed shaft **251** has a convex structure **2013** corresponding to the concave structure **2011** of the rotary shell **1007**, the concave structure **2011** and the convex structure **2013** can be clamped and rotated to tighten the strap. The concave structure **2011** can be a plurality of continuous grooves, the clamping device (one of the connection **200**) has a positioning assembly which is engaged with the grooves and has elasticity, and one end of the positioning assembly is placed in the grooves and is rotatably clamped with the rotary shell **1007**;

(26) The user rotates the rotary shell **1007**, and when the rotational force exceeds the elastic force of the positioning assembly, the positioning assembly rotates from the groove engaged with the original groove to another groove for engagement, and the rotary shell **1007** is limited and fixed in the circumferential direction by the positioning assembly and the groove, and when the rotary shell **1007** rotates, the strap of the joystick is driven to rotate and tighten and wind around the mounting assembly; because the rotary shell **1007** is limited and fixed, the strap of the joystick is reliably fixed inside the reception cavity **100**, the joystick is stably mounted and fixed inside the reception cavity **100**, preventing them from releasing during use so as to make users have better gaming experience.

(27) More specifically, as shown in FIG. 7, the rotary fixed shaft **251** further comprises a first rotary fixed shaft **2511** and a second rotary fixed shaft **2513**, wherein the first rotary fixed shaft **2511** extends from the reception cavity **100** shell **1007** at an angle (ranging from 0° (included) and 180° (included) and has a first limiting end for the rotary groove, and the first rotary fixed shaft **2511** has a first limiting post **2515**.

(28) More specifically, the second rotary fixed shaft **2513** has a first connecting portion **2001** connected to the extension, a second limiting end for the rotary shell and an extension fixing hole, and the second rotary fixed shaft **2513** has a second limiting post **2517** which is open and hollow at the other end corresponding to the first connecting portion **2001**; the first limiting post **2515** can be embedded in or coupled inside the second limiting post **2517**; a third mounting hole is provided on the first limiting post **2515**; and a screw passes through the second limiting post **2517** and is screwed and fixed in the third mounting hole.

(29) Specifically, one end of the extension **300** has a grip **310** at the second connecting portion **2003** away from the reception cavity **100**.

(30) Specifically, the grip **310** has a male-female anti-slip structure made of resilient materials, including EVA or silicone.

(31) Specifically, the extension **300** further comprises a telescopic structure for adjusting the length of the extension **300**.

(32) Specifically, the telescopic structure comprises: An outer extension **300**, which is designed for limiting the shortest length of the extension **300** and provided with a grip **310**; the outer extension **300** has a through-hole structure, the first end of the outer extension **300** has a threading structure, the size of the through-hole corresponding to the outlet of the first end of the outer extension **300** is smaller than outer diameter of the first end of the inner extension **300**, and the size of the through-hole of the outer extension **300** is larger than the outer diameter of the first end of the inner extension **300**, except for the outlet of the first end of the outer extension **300**; A locking elastic member for locking the movement of the inner extension **300**, comprising at least one of a slotted deformation structural member and an elastic material; A locking rotary member **250**, which is designed for adjusting the deformation of the locking elastic member, and provided with a through-hole structure and with an internal threading, and the size of a first end opening of the locking rotary member **250** is greater than a second end opening **1001** corresponding to the first end

opening **1001** of the locking rotary member **250**; The inner extension **300** is sleeved inside the outer extension **300**, a first end portion of the non-inner extension of the inner extension **300** can pass through a first end outlet of the outer extension **300**, a locking elastic member is mounted on the through-hole of the locking rotary member **250**, the locking elastic member and locking rotary member **250** pass through the inner extension **300** which extends out of the first end outlet portion of the outer extension **300**, and are rotatably connected to a threading structure of the outer extension **300**, when the locking member is locked, the locking elastic member deforms to lock the movement of the inner extension **300**, and when the locking member is released, the locking elastic member deforms slightly to release the inner extension **300**, and the inner extension can move telescopically.

(33) The application scenarios of the embodiments of the present invention are as follows:

(34) When the buckle is used as a fastener, as shown in FIG. 4, the buckle **501** has a raised member **5011** that snaps into the hole **1005** to provide the joystick with a pushing force along the cavity bottom **1003** so as to limit longitudinal movement of the joystick along the reception cavity **100**.

(35) Specifically, the buckle **501** is mounted on the joystick at a distance from the opening in the longitudinal direction of the reception cavity **100**, and the raised member **5011** of the buckle snaps into the hole **1005** to provide the joystick with a pushing force along the cavity bottom **1003** so as to limit the longitudinal movement of the joystick along the reception cavity **100**.

(36) Specifically, the buckle **501** has a rotary shaft, the rotary shaft is mounted on the reception cavity **100** shell, and the buckle **501** can rotate along the direction of rotation of the rotary shaft.

(37) When a nut is used as a fastener in the embodiments of the present invention, as shown in FIG. 5, a nut **503** is mounted on the reception cavity **100** shell **1007**, and by means of rotating the nut **503**, the reception volume of the reception cavity **100** may be changed to limit the movement of the joystick in the reception cavity **100**.

(38) When a screw is used as a fastener in the embodiment of the present invention, as shown in FIG. 6, the screw **505** passes through the hole **1005**, and by means of rotating the screw **505**, the reception volume of the reception cavity **100** may be changed to limit the movement of the joystick in the reception cavity **100**.

(39) In order to reduce the effect of poor signal transmission when the joystick application assembly **400** receives a signal, the reception cavity **100** is designed as a transparent reception cavity **100**. The material of the reception cavity **100** is preferably PC. The penetration rate of the signal through the transparent reception cavity **100** is higher than that through the non-transparent one.

(40) The embodiments of the present invention have been described in detail above with reference to the accompanying drawings, but the present invention is not limited to the described embodiments. It will be apparent to those skilled in the art that various changes, modifications, substitutions and variations can be made in these embodiments without departing from the principles and spirit of the present invention and yet fall within the scope of the present invention.

Claims

1. A joystick fastening device, comprising the components: a reception cavity whose one end has an opening for receiving a joystick; the other end of the reception cavity away from the opening in a longitudinal direction of the opening is a cavity bottom whose size is less than or equal to that of the opening; the reception cavity further comprises a hole, and the hole is arranged at a position outside the opening; a connection, which extends from a reception cavity shell at a pre-set angle to a central axis of the reception cavity, and one end of the connection opposite to the reception cavity shell has a first connecting portion; an extension, which has a second connecting portion matched with the first connecting portion of the connection, and is connected to the first connecting portion via the second connecting portion so as to realize spatial movement of the joystick via the

- extension; wherein one end of the extension has a grip at the second connecting portion away from the reception cavity; wherein the connection further comprise a rotary member arranged between the first connecting portion and the reception cavity for fastening or tightening the strap.
2. The joystick fastening device according to claim 1, wherein the preset angle ranges from 0° (included) to 180° (included); the joystick also comprises a fastener designed for fixing the joystick and comprising at least one of a strap, a buckle, a screw, or a nut; the faster is designed to lock the joystick to limit movement of the joystick in the reception cavity.
 3. The joystick fastening device according to claim 2, wherein the strap has a first end and a second end arranged outside the first end, wherein the first end of the strap is fixedly connected to the joystick, and the second end passes through the hole or is fixed on the connection or the reception cavity shell; the strap may be tightened to provide the joystick with a pulling force along the bottom of the reception cavity as the second end passes through the hole.
 4. The joystick fastening device according to claim 2, wherein the buckle has a raised member which snaps into the hole to provide the joystick with a pushing force along the cavity bottom so as to limit the longitudinal movement of the joystick along the reception cavity.
 5. The joystick fastening device according to claim 4, wherein the buckle is mounted on the joystick at a distance from the opening in the longitudinal direction of the reception cavity, and the raised member of the buckle snaps into the hole to provide the joystick with a pushing force along the cavity bottom so as to limit the longitudinal movement of the joystick along the reception cavity.
 6. The joystick fastening device according to claim 4, wherein the buckle has a rotary shaft, the rotary shaft is mounted on the reception cavity shell, and the buckle can rotate along the direction of rotation of the rotary shaft, and the raised member of the buckle snaps into the hole to provide the joystick with a pushing force so as to limit the longitudinal movement of the joystick along the reception cavity.
 7. The joystick fastening device according to claim 2, wherein a screw passes through the hole, and by means of rotating the screw, the reception volume of the reception cavity may be changed to limit the movement of the joystick in the reception cavity.
 8. The joystick fastening device according to claim 2, wherein a nut is mounted on the reception cavity shell, and by means of rotating the nut, the reception volume of the reception cavity may be changed to limit the movement of the joystick in the reception cavity.
 9. The fastening device of joystick according to claim 1, wherein the joystick further comprises an elastic material, and the joystick is fixed at an inner wall of the reception cavity by the elastic material, and the friction between the joystick and the inner wall of the reception cavity is increased by the elastic material.
 10. The fastening device of joystick according to claim 1, wherein the first connecting portion of the connection comprises at least one of a fixing hole, a threading, a slot, and a raised member, and the connection is designed to fixedly connect the extension; the second connecting portion of the extension comprises at least one of a fixing hole, a threading, a slot, and a raised member to fixedly connect the connection.
 11. The fastening device of joystick according to claim 1, wherein the rotary member comprises a rotary shell and a rotary fixed shaft, wherein the rotary shell has a strap fixing part for fixing the strap, the inner wall of the rotary shell has a concave structure, the rotary fixed shaft has a convex structure corresponding to the concave structure of the rotary shell, the concave structure and the convex structure can be clamped and rotated to tighten the strap.
 12. The fastening device of joystick according to claim 1, wherein the grip has a male-female anti-slip structure made of resilient material.
 13. The fastening device of joystick according to claim 1, wherein the extension further comprises a telescopic structure for adjusting a length of the extension.
 14. The fastening device of joystick according to claim 13, wherein the telescopic structure

comprises: an outer extension, which is designed for limiting a shortest length of the extension and provided with a grip; the outer extension has a through-hole structure, a first end of the outer extension has a threading structure, a size of the through-hole corresponding to an outlet of the first end of the outer extension is smaller than an outer diameter of the first end of the inner extension, and the size of the through-hole of the outer extension is larger than the outer diameter of the first end of the inner extension, except for the outlet of the first end of the outer extension; a locking elastic member for locking a movement of the inner extension, comprising at least one of a slotted deformation structural member and an elastic material; a locking rotary member, which is designed for adjusting a deformation of the locking elastic member, and provided with a through-hole structure and with an internal threading, and a size of a first end opening of the locking rotary member is greater than a second end opening corresponding to the first end opening of the locking rotary member; an inner extension is sleeved inside the outer extension, a first end portion of the non-inner extension of the inner extension can pass through a first end outlet of the outer extension, a locking elastic member is mounted on the through-hole of the locking rotary member, the locking elastic member and locking rotary member pass through the inner extension which extends out of the first end outlet portion of the outer extension, and are rotatably connected to a threading structure of the outer extension, when the locking member is locked, the locking elastic member deforms to lock the movement of the inner extension, and when the locking member is released, the locking elastic member deforms slightly to release the inner extension, and the inner extension can move telescopically.

15. The fastening device of joystick according to claim 1, wherein: the reception cavity is transparent.
