

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416886
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Doda; Kazuhiro et al.

Heater including a plurality of heat generation members, fixing apparatus, and image forming apparatus

Abstract

The heater including a substrate, a first heat generation member, a second heat generation member having a length substantially a same in a longitudinal direction as a length of the first heat generation member, a third heat generation member having a length shorter than lengths of the first heat generation member and the second heat generation member in the longitudinal direction, and a fourth heat generation member having a length shorter than length of the third heat generation member in the longitudinal direction, wherein the first heat generation member, the second heat generation member, the third heat generation member and the fourth heat generation member are arranged on the substrate.

Inventors: Doda; Kazuhiro (Yokohama, JP), Nakagawa; Ken (Yokohama, JP), Yoshida; Tsuguhiro (Yokohama, JP), Sato; Yutaka (Koma, JP), Wakatsu; Kohei (Kawasaki, JP)

Applicant: Canon Kabushiki Kaisha (Tokyo, JP)

Family ID: 1000008820103

Assignee: Canon Kabushiki Kaisha (Tokyo, JP)

Appl. No.: 18/456569

Filed: August 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230400803 A1	Dec. 14, 2023

Foreign Application Priority Data

JP	2019-006469	Jan. 18, 2019
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 17883799 20220809 US 11774891 child-doc US 18456569
continuation parent-doc US 17352770 20210621 US 11442385 20220913 child-doc US 17883799
continuation parent-doc US 16744669 20200116 US 11073778 20210727 child-doc US 17352770

Publication Classification

Int. Cl.: G03G15/20 (20060101)

U.S. Cl.:

CPC G03G15/2053 (20130101); G03G15/2042 (20130101); G03G15/2064 (20130101);
G03G2215/2035 (20130101)

Field of Classification Search

CPC: G03G (15/2053)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6336009	12/2001	Suzumi et al.	N/A	N/A
6580883	12/2002	Suzumi	N/A	N/A
7283145	12/2006	Kato et al.	N/A	N/A
8995859	12/2014	Ogura	N/A	N/A
9639043	12/2016	Kimura et al.	N/A	N/A
10152007	12/2017	Narahara et al.	N/A	N/A
11073778	12/2020	Doda et al.	N/A	N/A
11442385	12/2021	Doda et al.	N/A	N/A
11774891	12/2022	Doda	399/122	G03G 15/2042
2005/0036809	12/2004	Fukita et al.	N/A	N/A
2005/0280682	12/2004	Kato et al.	N/A	N/A
2009/0230114	12/2008	Taniguchi et al.	N/A	N/A
2011/0058864	12/2010	Fujimoto et al.	N/A	N/A
2012/0269535	12/2011	Mine et al.	N/A	N/A
2014/0076878	12/2013	Shimura	N/A	N/A
2014/0138372	12/2013	Ogura	N/A	N/A
2015/0331376	12/2014	Shimmura et al.	N/A	N/A
2016/0234882	12/2015	Takagi	N/A	N/A
2017/0013676	12/2016	Aritaki et al.	N/A	N/A
2017/0023894	12/2016	Cao	N/A	G03G 15/2053
2017/0075269	12/2016	Iwasaki et al.	N/A	N/A
2018/0173140	12/2017	Imaizumi et al.	N/A	N/A
2020/0233346	12/2019	Sato et al.	N/A	N/A
2020/0233349	12/2019	Takano	N/A	N/A
2020/0249600	12/2019	Yoshida et al.	N/A	N/A

2020/0333736 12/2019 Lee N/A N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102749830	12/2011	CN	N/A
103676575	12/2013	CN	N/A
106527084	12/2016	CN	N/A
107683437	12/2017	CN	N/A
2000-162909	12/1999	JP	N/A
2000-162919	12/1999	JP	N/A
2000-250337	12/1999	JP	N/A
2002-162847	12/2001	JP	N/A
2006-004860	12/2005	JP	N/A
2008-040082	12/2007	JP	N/A
2012-128170	12/2011	JP	N/A
2012-226079	12/2011	JP	N/A
2013-235181	12/2012	JP	N/A
2019/124664	12/2018	WO	N/A

OTHER PUBLICATIONS

Chinese Office Action issued on Oct. 28, 2022 in counterpart Chinese Patent Application No. 202010050010.1. cited by applicant

Japanese Office Action issued on Nov. 22, 2022 in counterpart Japanese Patent Application No. 2019-006469. cited by applicant

Chinese Office Action issued on Mar. 8, 2023 in counterpart Chinese Patent Application No. 202010050010.1. cited by applicant

Japanese Office Action issued Mar. 26, 2024 in counterpart Japanese Patent Appln. No. 2023-071327. cited by applicant

Primary Examiner: Therrien; Carla J

Attorney, Agent or Firm: Venable LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of U.S. patent application Ser. No. 17/883,799, filed on Aug. 9, 2022, which is a Continuation of U.S. patent application Ser. No. 17/352,770, filed on Jun. 21, 2021, issued as U.S. Pat. No. 11,442,385 on Sep. 13, 2022, which is a Continuation of U.S. patent application Ser. No. 16/744,669, filed on Jan. 16, 2020, issued as U.S. Pat. No. 11,073,778 on Jul. 27, 2021, which claims priority to Japanese Patent Application No. 2019-006469, filed on Jan. 18, 2019, the entire disclosures of which are hereby incorporated by reference herein.

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to a heater, a fixing apparatus, and an image forming apparatus, and particularly relates to a fixing apparatus and a heater in an image forming apparatus utilizing an electrophotography recording system, such as a laser printer, a copying machine and a facsimile.

Description of the Related Art

(2) A fixing apparatus heats and fixes, to a paper, an unfixed toner image on the paper by using a

heating member that includes a heat generation member having the almost same width (hereinafter referred to as the maximum width) as the maximum paper width that is able to be conveyed (hereinafter referred to as sheet feeding) in a nip portion. On the other hand, the paper sizes used by a user are varied in size, such as A4, B5 and A5. In a case where an A4 size sheet having a wide width is used, since the paper passes through an entire area (hereinafter referred to as a heating area) heated by the heating member including the heat generation member with the maximum width, the heating member and the fixing apparatus maintain a uniform temperature in the entire area. On the other hand, in a case where an A5 paper with a narrow width is used, the paper does not necessarily pass through the entire heating area of the heating member including the heat generation member having the maximum width. That is, although the A5 paper passes through a part of the heating area, the A5 paper does not pass through a part of the heating area. In an area (hereinafter referred to as the sheet feeding area) through which a paper passed in the heating area, since heat is taken by the paper, the temperature is low. On the other hand, in an area (hereinafter referred to as a non-sheet feeding area) through which a paper did not pass in the heating area, since heat is not taken by the paper, the temperature becomes high (temperature rise). There is a possibility of generating adverse image effects due to the temperature rise in this non-sheet feeding area. Therefore, for a paper with a narrow width, the temperature rise in the non-sheet feeding area is suppressed in advance by control that reduces the productivity. In order to suppress this reduction of productivity, for example, in Japanese Patent Application Laid-Open No. 2000-162909, a heat generation member having a wide width and a heat generation member having a narrow width are provided in a heating member, and the heat generation member with the narrow width is used when feeding a paper with a narrow width. Accordingly, the temperature rise of the non-sheet feeding area can be reduced, and high productivity can be maintained.

(3) However, in a case where an unexpected circumstance is assumed in which a part of an apparatus breaks down, and power is excessively supplied to one of the heat generation members, there is a possibility that a substrate of the heating member (hereinafter referred to as the heating member substrate) is greatly deformed due to a rapid temperature rise of the heating member. When the temperature of the heating member substrate is partially and greatly increased, a portion having a great temperature rise and a portion having a small temperature rise are generated. In the portion having the great temperature rise, the heating member substrate is greatly extended. On the other hand, in the portion having the small temperature rise, the heating member substrate is hardly extended. Depending on the difference in the extension that differs for each portion of the heating member substrate, a distortion (heat stress) will occur in the heating member substrate. The greater the temperature rise or the temperature gradient generated in the heating member substrate, the greater the distortion (heat stress) generated in the heating member substrate will become.

SUMMARY OF THE INVENTION

(4) One aspect of the present invention is a heater including a substrate, a first heat generation member, a second heat generation member having a length substantially a same in a longitudinal direction as a length of the first heat generation member, a third heat generation member having a length shorter than lengths of the first heat generation member and the second heat generation member in the longitudinal direction, and a fourth heat generation member having a length shorter than length of the third heat generation member in the longitudinal direction, wherein the first heat generation member, the second heat generation member, the third heat generation member and the fourth heat generation member are arranged on the substrate, the first heat generation member is arranged at one end of the substrate in a width direction, the second heat generation member is arranged at another end of the substrate in the width direction, to be symmetrical with the first heat generation member, and the third heat generation member and the fourth heat generation member are arranged between the first heat generation member and the second heat generation member in the width direction of the substrate.

(5) Another aspect of the present invention is a heater including a first heat generation member, a

second heat generation member, a third heat generation member having a length shorter than the first heat generation member and the second heat generation member in a longitudinal direction, a fourth heat generation member having a length shorter than the third heat generation member in the longitudinal direction, a first contact to which one ends of the first heat generation member and the second heat generation member are electrically connected, a second contact to which another ends of the first heat generation member and the second heat generation member, and one end of the third heat generation member are electrically connected, a third contact to which another end of the third heat generation member and one end of the fourth heat generation member are electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected.

(6) A further aspect of the present invention is a fixing apparatus for fixing an unfixed toner image carried by a recording material, the fixing apparatus including a heater including a substrate, a first heat generation member, a second heat generation member having a length substantially a same in a longitudinal direction as a length of the first heat generation member, a third heat generation member having a length shorter than lengths of the first heat generation member and the second heat generation member in the longitudinal direction, and a fourth heat generation member having a length shorter than length of the third heat generation member in the longitudinal direction, wherein the first heat generation member, the second heat generation member, the third heat generation member and the fourth heat generation member are arranged on the substrate, the first heat generation member is arranged at one end of the substrate in a width direction, the second heat generation member is arranged at another end of the substrate in the width direction, to be symmetrical with the first heat generation member, and the third heat generation member and the fourth heat generation member are arranged between the first heat generation member and the second heat generation member in the width direction of the substrate, a first rotary member heated by the heater, and a second rotary member forming a nip portion with the first rotary member.

(7) A still further aspect of the present invention is a fixing apparatus for fixing an unfixed toner image carried by a recording material, the fixing apparatus including a heater having a first heat generation member, a second heat generation member, a third heat generation member having a length shorter than the first heat generation member and the second heat generation member in a longitudinal direction, a fourth heat generation member having a length shorter than the third heat generation member in the longitudinal direction, a first contact to which one ends of the first heat generation member and the second heat generation member are electrically connected, a second contact to which another ends of the first heat generation member and the second heat generation member, and one end of the third heat generation member are electrically connected, a third contact to which another end of the third heat generation member and one end of the fourth heat generation member are electrically connected, and a fourth contact to which another end of the fourth heat generation member is electrically connected.

(8) A still further aspect of the present invention is an image forming apparatus including an image forming unit configured to form an unfixed toner image on a recording material, and a fixing apparatus for fixing an unfixed toner image carried by a recording material, the fixing apparatus including a heater including a substrate, a first heat generation member, a second heat generation member having a length substantially a same in a longitudinal direction as a length of the first heat generation member, a third heat generation member having a length shorter than lengths of the first heat generation member and the second heat generation member in the longitudinal direction, and a fourth heat generation member having a length shorter than length of the third heat generation member in the longitudinal direction, wherein the first heat generation member, the second heat generation member, the third heat generation member and the fourth heat generation member are arranged on the substrate, the first heat generation member is arranged at one end of the substrate in a width direction, the second heat generation member is arranged at another end of the substrate in the width direction, to be symmetrical with the first heat generation member, and the third heat

generation member and the fourth heat generation member are arranged between the first heat generation member and the second heat generation member in the width direction of the substrate, a first rotary member heated by the heater, and a second rotary member forming a nip portion with the first rotary member, wherein the fixing apparatus fixes the unfixed toner image to the recording material.

(9) A still further aspect of the present invention is an image forming apparatus including an image forming unit configured to form an unfixed toner image on a recording material, and a fixing apparatus for fixing an unfixed toner image carried by a recording material, the fixing apparatus including a heater having a first heat generation member, a second heat generation member, a third heat generation member having a length shorter than the first heat generation member and the second heat generation member in a longitudinal direction, a fourth heat generation member having a length shorter than the third heat generation member in the longitudinal direction, a first contact to which one ends of the first heat generation member and the second heat generation member are electrically connected, a second contact to which another ends of the first heat generation member and the second heat generation member, and one end of the third heat generation member are electrically connected, a third contact to which another end of the third heat generation member and one end of the fourth heat generation member are electrically connected, and a fourth contact to which another end of the fourth heat generation member is electrically connected, wherein the fixing apparatus fixes the unfixed toner image to the recording material.

(10) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a general configuration diagram of an image forming apparatus of Embodiments 1 to 3.

(2) FIG. 2 is a control block diagram of the image forming apparatus of Embodiments 1 to 3.

(3) FIG. 3A and FIG. 3B are diagrams illustrating a fixing apparatus and a heater of Embodiments 1 to 3.

(4) FIG. 4 is a diagram illustrating the heater of Embodiment 1.

(5) FIG. 5 is a diagram illustrating the heater of Comparison Example 1 for comparison with Embodiment 1.

(6) FIG. 6A is a diagram illustrating electric power supply to the heater of Embodiment 1. FIG. 6B is a diagram illustrating the electric power supply to the heater of Comparison Example 1.

(7) FIG. 7 is a diagram illustrating a comparison verification result 1 of Embodiment 1 and Comparison Example 1.

(8) FIG. 8 is a diagram illustrating a comparison verification result 2 of Embodiment 1 and Comparison Example 1.

(9) FIG. 9A and FIG. 9B are diagrams illustrating modifications of the heater of Embodiment 1.

(10) FIG. 10 is a diagram illustrating a modification of the heater of Embodiment 1.

(11) FIG. 11 is a diagram illustrating a modification of the heater of Embodiment 1.

(12) FIG. 12 is a graph illustrating the relationship between the maximum current amount and the power density of Embodiment 2.

(13) FIG. 13A illustrates a cross-sectional view of a fixing apparatus of Embodiment 3. FIG. 13B is a graph illustrating the nip pressure corresponding to the cross-sectional view of the fixing apparatus of Embodiment 3.

DESCRIPTION OF THE EMBODIMENTS

(14) Referring to the drawings, embodiments of the present invention will be described below. In

the following embodiments, letting a paper pass through a fixation nip portion will be referred to as sheet feeding. Additionally, in the area in which the heat generation member is generating heat, the area through which a paper is not fed is referred to as the non-sheet feeding area (or the non-sheet feeding portion), and the area through which a paper is fed is referred to as the sheet feeding area (or the sheet feeding portion). Further, the phenomenon in which the temperature in the non-sheet feeding area becomes higher compared with that in the sheet feeding area is referred to as the non-sheet feeding portion temperature rise.

Embodiment 1

(15) [Image Forming Apparatus]

(16) FIG. 1 is a configuration diagram illustrating a color image forming apparatus of the in-line system, which is an example of an image forming apparatus carrying a fixing apparatus of Embodiment 1. The operation of the color image forming apparatus of the electrophotography system will be described by using FIG. 1. Note that it is assumed that a first station is a station for toner image formation of a yellow (Y) color, and a second station is a station for toner image formation of a magenta (M) color. Additionally, it is assumed that a third station is a station for toner image formation of a cyan (C) color, and a fourth station is a station for toner image formation of a black (K) color.

(17) In the first station, a photosensitive drum **1a**, which is an image carrier, is an OPC photosensitive drum. The photosensitive drum **1a** is formed by stacking, on a metal cylinder, a plurality of layers of functional organic materials including a carrier generation layer exposed and generates an electric charge, a charge transport layer transporting the generated electric charge, etc., and the outermost layer has a low electric conductivity and is almost insulated. A charge roller **2a**, which is a charging unit, abuts the photosensitive drum **1a**, and uniformly charges a surface of the photosensitive drum **1a** while performing following rotation with the rotation of the photosensitive drum **1a**. The voltage superimposed with one of a DC voltage and an AC voltage is applied to the charge roller **2a**, and when an electric discharge occurs in minute air gaps on the upstream side and the downstream side of a rotation direction from a nip portion between the charge roller **2a** and the surface of the photosensitive drum **1a**, the photosensitive drum **1a** is charged. A cleaning unit **3a** is a unit that cleans a toner remaining on the photosensitive drum **1a** after the transfer, which will be described later. A development unit **8a**, which is a developing unit, includes a developing roller **4a**, a nonmagnetic monocomponent toner **5a** and a developer application blade **7a**. The photosensitive drum **1a**, the charge roller **2a**, the cleaning unit **3a** and the development unit **8a** form an integral-type process cartridge **9a** that can be freely attached to and detached from the image forming apparatus.

(18) An exposure device **11a**, which is an exposing unit, includes one of a scanner unit scanning a laser beam with a polygon mirror, and an LED (light emitting diode) array, and irradiates a scanning beam **12a** modulated based on an image signal on the photosensitive drum **1a**. Additionally, the charge roller **2a** is connected to a high voltage power supply for charge **20a**, which is a voltage supplying unit to the charge roller **2a**. The developing roller **4a** is connected to a high voltage power supply for development **21a**, which is a voltage supplying unit to the developing roller **4a**. A primary transfer roller **10a** is connected to a high voltage power supply for primary transfer **22a**, which is a voltage supplying unit to the primary transfer roller **10a**. The first station is configured as described above, and the second, third and fourth stations are also configured in the same manner. For the other stations, the identical numerals are assigned to the components having the identical functions as those of the first station, and b, c and d are assigned as the subscripts of the numerals for the respective stations. Note that, in the following description, the subscripts a, b, c and d are omitted, except for a case where a specific station is described.

(19) An intermediate transfer belt **13** is supported by three rollers, i.e., a secondary transfer opposing roller **15**, a tension roller **14**, and an auxiliary roller **19**, as its stretching members. The force in the direction of stretching the intermediate transfer belt **13** is applied only to the tension

roller **14** by a spring, and a suitable tension force for the intermediate transfer belt **13** is maintained. The secondary transfer opposing roller **15** is rotated in response to the rotation drive from a main motor (not illustrated), and the intermediate transfer belt **13** wound around the outer circumference is rotated. The intermediate transfer belt **13** moves at substantially the same speed in a forward direction (for example, the clockwise direction in FIG. **1**) with respect to the photosensitive drums **1a** to **1d** (for example, rotated in the counter clockwise direction in FIG. **1**). Additionally, the intermediate transfer belt **13** is rotated in an arrow direction (the clockwise direction), and the primary transfer roller **10** is arranged on the opposite side of the photosensitive drum **1** across the intermediate transfer belt **13**, and performs the following rotation with the movement of the intermediate transfer belt **13**. The position at which the photosensitive drum **1** and the primary transfer roller **10** abut each other across the intermediate transfer belt **13** is called a primary transfer position. The auxiliary roller **19**, the tension roller **14** and the secondary transfer opposing roller **15** are electrically grounded. Note that, also in the second to fourth stations, since primary transfer rollers to **10d** are configured in the same manner as the primary transfer roller **10a** of the first station, a description will be omitted.

(20) Next, the image forming operation of the image forming apparatus of Embodiment 1 will be described. An image forming apparatus starts the image forming operation, when a print command is received in a standby state. The photosensitive drum **1**, the intermediate transfer belt **13**, etc. start rotation in the arrow direction at a predetermined process speed by the main motor (not illustrated). The photosensitive drum **1a** is uniformly charged by the charge roller **2a** to which the voltage is applied by the high voltage power supply for charge **20a**, and subsequently, an electrostatic latent image according to image information is formed by the scanning beam **12a** irradiated from the exposure device **11a**. A toner **5a** in the development unit **8a** is charged in negative polarity by the developer application blade **7a**, and is applied to the developing roller **4a**. Then, a predetermined developing voltage is supplied to the developing roller **4a** by the high voltage power supply for development **21a**. When the photosensitive drum **1a** is rotated, and the electrostatic latent image formed on the photosensitive drum **1a** reaches the developing roller **4a**, the electrostatic latent image is visualized when the toner of negative polarity adheres, and a toner image of the first color (for example, Y (yellow)) is formed on the photosensitive drum **1a**. The respective stations (process cartridges **9b** to **9d**) of the other colors M (magenta), C (cyan) and K (black) are also similarly operated. An electrostatic latent image is formed on each of the photosensitive drums **1a** to **1d** by exposure, while delaying a writing signal from a controller (not illustrated) with a fixed timing, according to the distance between the primary transfer positions of the respective colors. A DC high voltage having the reverse polarity to that of the toner is applied to each of the primary transfer rollers **10a** to **10d**. With the above-described processes, toner images are sequentially transferred to the intermediate transfer belt **13** (hereinafter referred to as the primary transfer), and a multi toner image is formed on the intermediate transfer belt **13**.

(21) Thereafter, according to imaging of the toner image, a paper P that is a recording material loaded in a cassette **16** is fed (picked up) by a sheet feeding roller **17** rotated and driven by a sheet feeding solenoid (not illustrated). The fed paper P is conveyed to a registration roller (hereinafter referred to as the resist roller) **18** by a conveyance roller. The paper P is conveyed by the resist roller **18** to a transfer nip portion, which is an abutting portion between the intermediate transfer belt **13** and a secondary transfer roller **25**, in synchronization with the toner image on the intermediate transfer belt **13**. The voltage having the reverse polarity to that of the toner is applied to the secondary transfer roller **25** by a high voltage power supply for secondary transfer **26**, and the four-color multi toner image carried on the intermediate transfer belt **13** is collectively transferred onto the paper P (onto the recording material) (hereinafter referred to as the secondary transfer). The members (for example, the photosensitive drum **1**) that have contributed to the formation of the unfixed toner image on the paper P function as an image forming unit. On the other hand, after completing the secondary transfer, the toner remaining on the intermediate

transfer belt **13** is cleaned by a cleaning unit **27**. The paper P to which the secondary transfer is completed is conveyed to a fixing apparatus which is a fixing unit, and is discharged to a discharge tray **30** as an image formed matter (a print, a copy) in response to fixing of the toner image. A film **51** of the fixing apparatus **50**, a nip forming member **52**, a pressure roller **53** and a heater **54** will be described later.

(22) [Block Diagram of Image Forming Apparatus]

(23) FIG. **2** is a block diagram for describing the operation of the image forming apparatus, and referring to this drawing, the print operation of the image forming apparatus will be described. APC **110**, which is a host computer, outputs a print command to a video controller **91** inside the image forming apparatus, and plays the role of transferring image data of a printing image to the video controller **91**.

(24) The video controller **91** converts the image data from the PC **110** into exposure data, and transfers it to an exposure control device **93** inside an engine controller **92**. The exposure control device **93** is controlled from a CPU **94**, and performs turning on and off of exposure data, and control of the exposure device **11**. The CPU **94**, which is a control unit, starts an image forming sequence, when a print command is received.

(25) The CPU **94**, a memory **95**, etc. are mounted in the engine controller **92**, and the operation programmed in advance is performed. The high voltage power supply **96** includes the above-described high voltage power supply for charge **20**, high voltage power supply for development **21**, high voltage power supply for primary transfer **22** and high voltage power supply for secondary transfer **26**. Additionally, a power control unit **97** includes a bidirectional thyristor (hereinafter referred to as the triac) **56**, a heat generation member switching device **57** as a switching unit that exclusively selects a heat generation member supplying power, etc. The power control unit **97** selects the heat generation member that generates heat in the fixing apparatus **50**, and determines the electric energy to be supplied. Additionally, a driving device **98** includes a main motor **99**, a fixing motor **100**, etc. In addition, a sensor **101** includes a fixing temperature sensor **59** that detects the temperature of the fixing apparatus **50**, a sheet presence sensor **102** that has a flag and detects the existence of the paper P, etc., and the detection result of the sensor **101** is transmitted to the CPU **94**. The CPU **94** obtains the detection result of the sensor **101** in the image forming apparatus, and controls the exposure device **11**, the high voltage power supply **96**, the power control unit **97** and the driving device **98**. Accordingly, the CPU **94** performs the formation of an electrostatic latent image, the transfer of a developed toner image, the fixing of a toner image to the paper P, etc., and controls an image formation process in which the exposure data is printed on the paper P as the toner image. Note that the image forming apparatus to which the present invention is applied is not limited to the image forming apparatus having the configuration described in FIG. **1**, and may be an image forming apparatus that can print papers P having different widths, and that includes the fixing apparatus **50** including the heater **54**, which will be described later.

(26) [Fixing Apparatus]

(27) FIG. **3A** illustrates a cross-section of the fixing apparatus **50** used in Embodiment 1. FIG. **3B** illustrates a rear surface of the heater **54**. Referring to FIG. **3A** and FIG. **3B**, the fixing apparatus **50** will be described below. The fixing apparatus **50** includes a cylindrical film **51**, the pressure roller **53** forming the fixation nip portion N with the film **51**, the heater **54**, which is a heating member, a nip forming member **52** holding the heater **54**, and a stay **60** for maintaining the strength in the longitudinal direction. The film **51**, which is a first rotary member, includes a silicone rubber layer having a film thickness of 200 μm on a polyimide substrate having a film thickness of 50 μm , and a PFA release layer having a film thickness of 20 μm on the silicone rubber layer. The pressure roller **53**, which is a second rotary member, includes an SUM cored bar having an outer diameter of 13 mm, a silicone rubber elastic layer having a film thickness of 3.5 mm on the SUM cored bar, and further includes a PFA release layer having a film thickness of 40 μm on the silicone rubber elastic layer. The pressure roller **53** is rotated by a driving source (not illustrated), and the film **51**

performs the following rotation following the driving of the pressure roller 53.

(28) The heater 54 is provided to contact the inner surface of the film 51, and is held by the nip forming member 52, and the inner periphery surface of the film 51 and the top surface of the heater 54 contact each other. Here, in the heater 54, the surface on which heat generation members 54b1 to 54b4 described later are provided is the top surface, and the surface on which a thermo switch 58, etc. described later is provided is the rear surface. The stay 60 is pressurized on both ends by a unit that is not illustrated, and the pressurizing force is received by the pressure roller 53 via the nip forming member 52 and the film 51. Accordingly, a fixation nip portion N at which the film 51 and the pressure roller 53 are pressed and contact each other is formed. The nip forming member 52 is required to have rigidity, heat resistance and thermal insulation properties, and is formed by a liquid crystal polymer. As illustrated in FIG. 3B, the thermo switch 58, which is a safety element, and the fixing temperature sensor 59 such as a thermistor, which is a temperature detecting unit, contact and are arranged on the rear surface of the heater 54.

(29) The thermo switch 58 arranged on the rear surface of the heater 54 is, for example, a bimetal thermo switch, and the heater 54 and the thermo switch 58 are electrically connected to each other. When the thermo switch 58 detects that the temperature of the rear surface of the heater 54 has excessively risen (hereinafter referred to as the excessive temperature rise), a bimetal inside the thermo switch 58 is operated, and the power supplied to the heater 54 can be cut off. The fixing temperature sensor 59 arranged on the rear surface of the heater 54 is a chip resistor-type thermistor. The fixing temperature sensor 59 detects chip resistance, and the detection result is used for the temperature control of the heater 54. The fixing temperature sensor 59 can also detect the excessive temperature rise.

(30) [Heater]

(31) The configuration of the heater 54 of Embodiment 1 is illustrated in FIG. 4, and the details will be described below. A substrate 54a is a plate-like ceramic substrate formed with alumina, etc., and the sizes are, for example, the thickness $t=1$ mm, the width $W=6.3$ mm, and the length $l=280$ mm. The heat generation members 54b1, 54b2, 54b3 and 54b4, a conductor 54c, which is an electric conduction route, and contacts 54d1, 54d2, 54d3 and 54d4 for supplying power are formed on the substrate 54a by a printing process. Hereinafter, the heat generation members 54b1 to 54b4 may be collectively referred to as the heat generation member 54b. In FIG. 4, the heat generation member 54b is indicated by white, the conductor 54c is indicated by hatched lines, and the contacts 54d1 to 54d4 are indicated by black.

(32) The heat generation members 54b are arranged at equal intervals in the order of the heat generation member 54b1 having the longest length (hereinafter also referred to as the width) in the longitudinal direction, the heat generation member 54b3 having the second longest width, the heat generation member 54b4 having the third longest width, and the heat generation member 54b2 having the longest width. The heat generation member 54b1 and the heat generation member 54b2 have substantially the same width. The interval between the heat generation members 54b is, for example, 0.7 mm in Embodiment 1. The sizes of the heat generation members 54b1 and 54b2 are, for example, the thickness $t=10$ μm , the width $W=0.7$ mm, and the length $l=222$ mm in Embodiment 1. The sizes of the heat generation member 54b3 are, for example, the thickness $t=10$ μm , the width $W=0.7$ mm, and the length $l=188$ mm in Embodiment 1. The sizes of the heat generation member 54b4 are, for example, the thickness $t=10$ μm , the width $W=0.7$ mm, and the length $l=154$ mm in Embodiment 1.

(33) The heat generation members 54b1 and 54b2 have the length $l=222$ mm, and are used when printing an A4 size sheet having a width of 210 mm. The heat generation member 54b3 has the length $l=188$ mm, and is used when printing a B5 paper having a width of 182 mm. The heat generation member 54b4 has the length $l=154$ mm, and is used when printing an A5 paper having a width of 148.5 mm.

(34) The heat generation member 54b is a conducting material containing silver and palladium as

the main components, and a conducting material containing silver as the main component is used for the conductor **54c** and the contacts **54d1** to **54d4**. It is assumed that the electrical resistances across both ends of the heat generation members **54b** in the longitudinal direction are 20Ω in both the longest heat generation members **54b1** and **54b2**, 30Ω in the second longest heat generation member **54b3**, and also 30Ω in the third longest heat generation member **54b4**. One ends of the longest heat generation members **54b1** and **54b2** are electrically connected by the common contact **54d1**, and the other ends are electrically connected by the common contact **54d2**. Since the heat generation member **54b1** and the heat generation member **54b2** are connected in parallel, the combined electrical resistance of the longest heat generation members **54b1** and **54b2** between the contacts **54d1** and **54d2** is 10Ω . In this manner, the combined resistance of the heat generation member **54b1** and the heat generation member **54b2** is 10Ω , and is smaller than the resistance (30Ω) of the heat generation member **54b3** and the heat generation member **54b4**.

(35) As described above, the heater **54** includes the heat generation member **54b1**, which is a first heat generation member, and the heat generation member **54b2**, which is a second heat generation member having substantially the same length as the heat generation member **54b1** in the longitudinal direction. Further, the heater **54** includes the heat generation member **54b3**, which is a third heat generation member having a shorter length than the heat generation members **54b1** and **54b2** in the longitudinal direction, and the heat generation member **54b4**, which is a fourth heat generation member. The heat generation member **54b1** is provided in one end of the substrate **54a** in the width direction, and the heat generation member **54b2** is provided in the other end of the substrate **54a** in the width direction. The heat generation members **54b3** and **54b4** are provided between the heat generation member **54b1** and the heat generation member **54b2** in the width direction of the substrate **54a**.

(36) Additionally, in Embodiment 1, the contact **54d1**, which is a first contact, is the contact to which one ends of the heat generation members **54b1** and **54b2** are electrically connected. The contact **54d2**, which is a second contact, is the contact to which the other ends of the heat generation member **54b1**, the heat generation member **54b2**, and the heat generation member **54b3** are electrically connected. The contact **54d3**, which is a third contact, is the contact to which one ends of the heat generation member **54b3** and the heat generation member **54b4** are electrically connected. The contact **54d4**, which is a fourth contact, is the contact to which the other end of the heat generation member **54b4** is electrically connected.

(37) Note that, although all the widths W of the heat generation members **54b** are the identical width of 0.7 mm in Embodiment 1, there are cases where the selection of material of a conducting material is difficult in order to form the heat generation members **54b** having the same width W , depending on the performance required for the fixing apparatus **50**. In that case, the widths W of the heat generation members **54b** may be different according to the performance required for the fixing apparatus **50**.

(38) (Regarding Heat Generation Members **54b1** and **54b2**)

(39) The characteristics of the heat generation members **54b1** and **54b2** having the longest width in the above-described heater **54** will be described below. If the fixing apparatus **50** can quickly reach a sufficiently heated fixable state (hereinafter also referred to as the sheet feeding enabled state), a printed matter can be quickly provided to the user. Therefore, the power supply capability of the longest heat generation members **54b1** and **54b2** that can heat the entire area in the longitudinal direction can be maximized, so that any size of paper P may be chosen. The heat generation members **54b3** and **54b4** having the shorter lengths than the longest heat generation members **54b1** and **54b2** in the longitudinal direction are used after the fixing apparatus **50** is sufficiently heated by the longest heat generation members **54b1** and **54b2**. Therefore, since the electric energy for fixing a toner image to the paper P at the time of sheet feeding may be supplemented, in a case where the heat generation members **54b3** and **54b4** are used, the heat generation members **54b3** and **54b4** can have lower power supply capability compared to the high power supply capability of the

longest heat generation members **54b1** and **54b2**.

(40) When the longest heat generation members **54b1** and **54b2** have the high power supply capability, it means that the deformation risk of the substrate **54a** is high in a case where power is excessively supplied to the longest heat generation members **54b1** and **54b2** due to an unexpected apparatus failure. In Embodiment 1, the longest heat generation members include the two heat generation members **54b1** and **54b2**, one heat generation member **54b1** is arranged on one end of the substrate **54a** in the width direction, and the other heat generation member **54b2** is arranged on the other end of the substrate **54a** in the width direction. Accordingly, the two longest heat generation members **54b1** and **54b2** are arranged so that they are symmetrical in the width direction of the substrate **54a**.

(41) Further, each of the heat generation members **54b1** and **54b2** is electrically connected to each other by the common contacts **54d1** and **54d2**, and the two heat generation members **54b1** and **54b2** are configured such that power is always supplied substantially at the same time. Accordingly, since the both ends of the heater **54** in the width direction always generate heat when power is supplied to the longest heat generation members **54b1** and **54b2**, the supplied electric energy can be distributed, and the temperature gradient of the substrate **54a** in the width direction can be reduced.

(42) As described above, the fixing apparatus **50** can be made to reach the sheet feeding enabled state in a short time, and even if an unexpected apparatus failure occurs, and results in an excessive power supplying state, the temperature gradient of the substrate **54a** in the width direction can be reduced, and the deformation risk of the substrate **54a** can be reduced.

(43) (Regarding Heat Generation Members **54b3** and **54b4**)

(44) Next, the characteristics of the two kinds of non-longest heat generation members **54b3** and **54b4** will be mentioned below. One ends of the heat generation member **54b3** and the heat generation member **54b4** are electrically connected to the one contact **54d3**. On the other hand, in the heat generation member **54b3** and the heat generation member **54b4**, the other end of the heat generation member **54b3** is electrically connected to the contact **54d2**, and the other end of the heat generation member **54b4** is electrically connected to the contact **54d4**. That is, the heat generation member **54b3** and the heat generation member **54b4** are configured so that either one of them will generate heat.

(45) As described above, the heat generation member **54b3** is used at the time of printing of a B5 paper, and the heat generation member **54b4** is used at the time of printing of an A5 paper. The width (hereinafter referred to as the paper width) of the paper P and the lengths of the heat generation members **54b3** and **54b4** in the longitudinal direction are almost the same length, and the paper P passes through most of the area (hereinafter referred to as the heat generation area) in which the heat generation members **54b3** and **54b4** generate heat. Therefore, since most of the heat generated by the heat generation members **54b3** and **54b4** can be provided to the paper P, the temperature rise in the non-sheet feeding area through which the paper P does not pass can be suppressed. Accordingly, maintaining a high productivity is enabled. Additionally, since the longest heat generation members **54b1** and **54b2** are responsible for heating the fixing apparatus to the sheet feeding enabled state, the non-longest heat generation members **54b3** and **54b4** may supplement the electric energy for fixing a toner image to the paper P at the time of sheet feeding. Therefore, the power supply capability of the non-longest heat generation members **54b3** and **54b4** can be reduced, and the degree of temperature rise of the heat generation members **54b3** and **54b4** at the time of malfunction can be reduced.

(46) Additionally, the above-described two kinds of heat generation members **54b3** and **54b4** are arranged between the longest heat generation member **54b1** and the longest heat generation member **54b2**, and the heat generation members **54b3** and **54b4** are arranged close to the center of the substrate **54a** in the width direction as much as possible. Accordingly, the temperature rise can be performed almost equally in either of a first end, which is one end of the substrate **54a** in the width direction, and a second end, which is the other end of the substrate **54a**, and the temperature

gradient of the substrate **54a** in the width direction can be reduced.

(47) As described above, the power supply capability of the non-longest heat generation members **54b3** and **54b4** is reduced, and the non-longest heat generation members **54b3** and **54b4** are arranged as symmetrically as possible in the width direction of the substrate **54a**. Accordingly, even an unexpected apparatus failure results in an excessive power supplying state, since the temperature gradient in the width direction of the substrate **54a** can be reduced, the deformation risk of the substrate **54a** can be reduced. Additionally, by making the number of only the longest heat generation members **54b1** and **54b2** that require the high power supply capability two, and the number of the non-longest heat generation members **54b3** and **54b4** one, which is the minimally required number, while considering their symmetry in the width direction, the reduction of the size of the substrate **54a** can be achieved at the same time.

Comparison Examples

(48) FIG. 5 illustrates a heater **200** in Comparison Example 1, and the details of the configuration will be described below. A substrate **207** is a plate-like ceramic substrate formed with alumina, etc., and the sizes are, for example, the thickness $t=1$ mm, the width $W=6.3$ mm, and the length $l=280$ mm. Heat generation members **201** and **202**, a conductor **254**, and contacts **203**, **204**, **205** and **206** are formed on the substrate **207** by a printing process. In FIG. 5, the heat generation members **201** and **202** are indicated by white, the conductor **254** is indicated by hatched lines, and the contacts **203** to **206** are indicated by black.

(49) In the heater **200**, two heat generation members, i.e., the heat generation member **201** having the longest width and the heat generation member **202** having the second longest width, are arranged on the substrate **207** with an interval of 3.5 mm. The sizes of the heat generation member **201** are the thickness $t=10$ μm , the width $W=0.7$ mm, and the length $l=222$ mm. The sizes of the heat generation member **202** are the thickness $t=10$ μm , the width $W=0.7$ mm, and the length $l=188$ mm. The heat generation member **201** is used when printing an A4 (210 mm in the width) paper, and the heat generation member **202** is used when printing a B5 (182 mm) paper. The electrical resistances across both ends of the heat generation members **201** and **202** in the longitudinal direction are 10Ω in the longest heat generation member **201**, and 30Ω in the second longest heat generation member **202**. The both ends of the longest heat generation member **201** are electrically connected to the contacts **203** and **204** via the conductor **254**, and the both ends of the second longest heat generation member **202** are electrically connected to the contacts **205** and **206** via the conductor **254**.

Embodiment 1 and Comparison Example 1

(50) FIG. 6A illustrates a power supplying circuit of Embodiment 1. FIG. 6B illustrates the power supplying circuit of Comparison Example 1. The comparison verification in these circuits to which Embodiment 1 and Comparison Example 1 are applied will be described. Each of the power supplying circuit will be described below. In Embodiment 1 of FIG. 6A, the contacts **54d1** to **54d4** are connected to a heat generation member switching device **57** for switching the power supply passages. Note that, since the heat generation member **54b** that generates heat is switched by switching the power supply passages by the heat generation member switching device **57**, the switching of the power supply passages is also expressed as the switching of the heat generation member **54b**. In Embodiment 1, specifically, the heat generation member switching devices **57** are electromagnetic relays **57a** and **57b** having c-contact configurations.

(51) The electromagnetic relay **57a** includes a contact **57a1** connected to a first pole of an AC power supply **55** via a triac **56**, a contact **57a2** connected to the contact **54d1**, and a contact **57a3** connected to the contact **54d3**. The electromagnetic relay **57a** is brought into either one of the states, i.e., the state where the contact **57a1** and the contact **57a2** are connected to each other, and the state where the contact **57a1** and the contact **57a3** are connected to each other, by the control of the engine controller **92**. The electromagnetic relay **57b** includes a contact **57b1** connected to a second pole of the AC power supply **55**, a contact **57b2** connected to the contact **54d2**, and a

contact **57b3** connected to the contact **54d4**. The electromagnetic relay **57b** is brought into one of the states, i.e., the state where the contact **57b1** and the contact **57b2** are connected to each other, and the state where the contact **57b1** and the contact **57b3** are connected to each other, by the control of the engine controller **92**.

(52) FIG. **6A** illustrates the electromagnetic relays **57a** and **57b** at the time of non-operation, the contact **57a1** and the contact **57a2** are connected to each other in the electromagnetic relay **57a**, and the contact **57b1** and the contact **57b2** are connected to each other in the electromagnetic relay **57b**. Since power is supplied between the contact **54d1** and the contact **54d2** at the time of non-operation of the electromagnetic relays **57a** and **57b**, the longest heat generation members **54b1** and **54b2** generate heat.

(53) In a case where the electromagnetic relays **57a** and **57b** are operated, the contact **57a1** and the contact **57a3** are connected to each other in the electromagnetic relay **57a**, and the contact **57b1** and the contact **57b3** are connected to each other in the electromagnetic relay **57b**. Since power is supplied between the contact **54d3** and the contact **54d4** at the time of operation of the electromagnetic relays **57a** and **57b**, only the heat generation member **54b4** generates heat. In a case where only the electromagnetic relay **57a** is operated, it will be in a state where the contact **57a1** and the contact **57a3** are connected to each other in the electromagnetic relay **57a**, and the contact **57b1** and the contact **57b2** are connected to each other in the electromagnetic relay **57b**. Since power is supplied between the contact **54d3** and the contact **54d2** at the time of operation of only the electromagnetic relay **57a**, only the heat generation member **54b3** generates heat.

(54) In Comparison Example 1 of FIG. **6B**, the contacts **203** to **206** are connected to electromagnetic relays **208** and **209** having the c-contact configurations, which are heat generation member switching devices for switching power supply passages. The electromagnetic relay **208** includes a contact **208a** connected to the first pole of the AC power supply **55** via the triac **56**, a contact **208b1** connected to the contact **203**, and a contact **208b2** connected to the contact **205**. The electromagnetic relay **208** is brought into either one of the states, i.e., the state where the contact **208a** and the contact **208b1** are connected to each other, and the state where the contact **208a** and the contact **208b2** are connected to each other, by the control of the engine controller **92**. The electromagnetic relay **209** includes a contact **209a** connected to the second pole of the AC power supply **55**, a contact **209b1** connected to the contact **204**, and a contact **209b2** connected to the contact **206**. The electromagnetic relay **209** is brought into either one of the states, i.e., the state where the contact **209a** and the contact **209b1** are connected to each other, and the state where the contact **209a** and the contact **209b2** are connected to each other, by the control of the engine controller **92**.

(55) FIG. **6B** illustrates the electromagnetic relays **208** and **209** at the time of non-operation, the contact **208a** and the contact **208b1** are connected to each other in the electromagnetic relay **208**, and the contact **209a** and the contact **209b1** are connected to each other in the electromagnetic relay **209**. Since power is supplied between the contact **203** and the contact **204** at the time of non-operation of the electromagnetic relays **208** and **209**, the longest heat generation member **201** generates heat.

(56) In a case where the electromagnetic relays **208** and **209** are operated, the contact **208a** and the contact **208b2** are connected to each other in the electromagnetic relay **208**, and the contact **209a** and the contact **209b2** are connected to each other in the electromagnetic relay **209**. Since power is supplied between the contact **205** and the contact **206** at the time of operation of the electromagnetic relays **208** and **209**, only the heat generation member **202** generates heat. Note that a contact switch, such as an electromagnetic relay having the a-contact configuration, or an electromagnetic relay having the b-contact configuration may be used for the electromagnetic relay, or a contactless switch, such as a solid state relay (SSR), a photoMOS relay, and a triac, may be used for the electromagnetic relay.

Temperature Gradient of Embodiment 1 and Comparison Example 1

(57) (i) In order to estimate the deformation amount of the substrate at the time when an excessive power is supplied to the heat generation member, the temperature profile of the back surface of the substrate (the position indicated by an A-A' line) after 3 seconds since the power was supplied was measured, in a case where AC voltage of 100V was continued to be supplied to the respective heat generation members of Embodiment 1 and Comparison Example 1. It is shown that the larger the difference between the maximum value and the minimum value of the temperature profile, the higher the deformation risk of the substrate.

(58) FIG. 7 illustrates Embodiment 1, Comparison Example 1, etc. in the first row, and illustrates the heat generation pattern of the heater in the second row. Note that the heat generation members to which power was supplied are indicated by vertical stripes. FIG. 7 illustrates the difference (hereinafter referred to as the temperature difference) between the maximum value and the minimum value of the temperature profile in the third row, and illustrates the temperature profile (substrate back surface temperature profile) of the back surface corresponding to the position indicated by the A-A' line of the substrate in the fourth row. In the graphs of the temperature profile, the horizontal axes represent the width direction (temperature width) [mm] of the substrate, and the vertical axes represent the temperature (substrate back surface temperature) [° C.]. Note that in the diagrams of the heat generation patterns, numerals are omitted for visibility. Note that, in the graph of Embodiment 1, Embodiment 1 (1) is represented by a solid line, Embodiment 1 (2) is represented by a dotted line, and Embodiment 1 (3) is represented by a broken line. Additionally, in the graph of Comparison Example 1, Comparison Example 1 (1) is represented by a solid line, and Comparison Example 1 (2) is represented by a broken line.

(59) Additionally, Embodiment 1 (1) represents a case where power is supplied to the two longest heat generation members **54b1** and **54b2** corresponding to an A4 size sheet. Embodiment 1 (2) represents a case where power is supplied to the second longest heat generation member **54b3** corresponding to a B5 paper. Embodiment 1 (3) represents a case where power is supplied to the shortest heat generation member **54b4** corresponding to an A5 paper. Comparison Example 1 (1) represents a case where power is supplied to the longest heat generation member **201** corresponding to an A4 size sheet, and Comparison Example 1 (2) represents a case where power is supplied to the second longest heat generation member **202** corresponding to a B5 paper.

Embodiment 1 (1)

(60) In Embodiment 1 (1), the highest temperature of the back surface of the substrate **54a** reached 472° C. near the heat generation member **54b1** or the heat generation member **54b2**, and the lowest temperature was 391° C. between the two heat generation members **54b1** and **54b2**. The difference between the highest temperature and the lowest temperature was 81° C., and the temperature gradient in the substrate **54a** was small. In the configuration of Embodiment 1 (1), the two longest heat generation members **54b1** and **54b2** are used to distribute the electric energy, and are symmetrically arranged on the both ends of the substrate **54a** in the width direction, and the two heat generation members **54b1** and **54b2** share the common contacts **54d1** and **54d2** to always generate heat at the same time. Accordingly, the temperature gradient generated in the substrate **54a** was able to be reduced.

Embodiment 1 (2)

(61) In Embodiment 1 (2), the highest temperature of the back surface of the substrate **54a** reached 271° C. near the heat generation member **54b3**, and the lowest temperature was 174° C. at one end in the width direction, which is the farther end from the heat generation member **54b3**. The difference between the highest temperature and the lowest temperature was 97° C., and the temperature gradient in the substrate **54a** was small. Since the power supply capability of the second longest heat generation member **54b3** of Embodiment 1(2) is made to be the minimum value required, and the second longest heat generation member **54b3** is arranged in almost the center of the substrate **54a** in the width direction to be symmetrical with the heat generation member **54b4** as much as possible, the temperature gradient generated in the substrate **54a** was able

to be reduced.

Embodiment 1 (3)

(62) In Embodiment 1 (3), the highest temperature of the back surface of the substrate **54a** reached 316° C. near the heat generation member **54b4**, and the lowest temperature was 196° C. at one end in the width direction, which is the farther end from the heat generation member **54b4**. The difference between the highest temperature and the lowest temperature was 120° C. For the same reason as the reason described in the Embodiment 1 (2), the temperature gradient generated in the substrate **54a** was able to be reduced.

Comparison Example 1 (1)

(63) In Comparison Example 1 (1), the highest temperature of the back surface of the substrate **207** reached 673° C. near the heat generation member **201**, and the lowest temperature was 208° C. at one end in the width direction, which is the farther end from the heat generation member **201**. The difference between the highest temperature and the lowest temperature was 465° C., and the temperature gradient in the substrate **207** was large. In Comparison Example 1 (1), since the number of the longest heat generation member **201** that gives the maximum power supply capability is one, and the longest heat generation member **201** is arranged at one end of the substrate **207** in the width direction, the increase in the temperature at the one end became large.

Comparison Example 1 (2)

(64) In Comparison Example 1 (2), the highest temperature of the back surface of the substrate **207** reached 341° C. near the heat generation member **202**, and the lowest temperature was 136° C. at one end in the width direction, which is the farther end from the heat generation member **202**. The difference between the highest temperature and the lowest temperature was 205° C., and the temperature gradient in the substrate **207** was large. Since the heat generation member **202** has a low power supply capability compared with the heat generation member **201** of Comparison Example 1 (1), although the temperature gradient is smaller than that in Comparison Example 1 (1), the increase in the temperature at one end became large, since the heat generation member **202** is arranged at the one end of the substrate **207** in the width direction.

(65) From the above, while the maximum temperature difference in Embodiment 1 is 120° C., which is shown in the Embodiment 1 (3), the maximum temperature difference in Comparison Example 1 is 465° C., which is shown in Comparison Example 1 (1), and the temperature difference in Comparison Example 1 is three or more times larger than that in Embodiment 1. The extension of the substrate is large in a portion with a high temperature, and the extension of the substrate is small in a portion with a low temperature, and the substrate is deformed due to the difference in the amount of extension. In Embodiment 1, it was able to confirm that, in any of the heat generation members **54b**, the temperature difference was 120° C. or less, which is sufficiently small compared with that in Comparison Example 1, and the risk of deformation of the substrate **54a** was small. Even if the material of the substrate and the sizes of the substrate are changed, the same effects can be obtained by using the configuration illustrated in the Embodiment 1.

Productivity of Embodiment 1 and Comparison Example 1

(66) (ii) FIG. 8 illustrates the confirmation results of the maximum productivity for a B5 paper and an A5 paper in Embodiment 1 and Comparison Example 1. FIG. 8 illustrates Embodiment 1 and Comparison Example 1 in the first row, and illustrates the patterns of the heat generation member in the second row. The width of a B5 paper and the width of an A5 paper are also illustrated in the heat generation member patterns. FIG. 8 illustrates the maximum productivity at the time when B5 papers are continuously printed in the third row, and illustrates the maximum productivity at the time when A5 papers are continuously printed in the fourth row.

(67) The conditions for an image forming apparatus and a fixing apparatus at the time of confirming the productivity will be mentioned. A paper P previously printed is hereinafter referred to as the preceding paper, and the subsequent paper printed subsequently to the paper P is hereinafter referred to as the subsequent paper. Additionally, the interval between the bottom end of

the preceding paper and the top end of the subsequent paper is hereinafter also referred to as the paper interval. The image process speed of the image forming apparatus is 200 mm/sec, the interval (paper interval) between the preceding paper and the subsequent paper is 50 mm (0.4 second), and papers P having the same size are continuously fed while maintaining the maximum productivity. Sheet feeding is performed by performing the temperature control by the engine controller **92**, so that the back surface of the substrate becomes 180° C. by the fixing temperature sensor **59** installed in the back surface of the substrate. As for the papers P, Canon CS680 having the B5 (182 mm in width×257 mm in length×92 μm in thickness, a basis weight of 68 g/m.sup.2) size, and Canon PBPAPER having the A5 (148.5 mm in width×210 mm in length×83 μm in thickness, a basis weight of 64 g/m.sup.2) size were used. Additionally, in a case where the temperature of the film **51** in the non-sheet feeding area through which the papers P do not pass at the time of sheet feeding is measured, and the temperature exceeds 200° C., the interval (paper interval) between the preceding paper and the subsequent paper is increased. The maximum productivity refers to the productivity at the time when the temperature of the film **51** becomes 200° C. or less.

(68) Embodiment 1 includes the heat generation members **54b3** and **54b4** for a plurality of small sizes corresponding to the B5 and A5 papers, and the temperature rise of the film **51** is small for any of the papers P, and the adjustment of the paper interval is not required. In Embodiment 1, the maximum productivity for the B5 paper was 39 sheets/minute, and the maximum productivity for the A5 paper was 46 sheets/minute. On the other hand, in Comparison Example 1, since only one kind of heat generation member **202** corresponding to the B5 paper is provided as the heat generation member, when printing B5 papers, the adjustment of the paper interval was not required, and the maximum productivity was 39 sheets/minute. However, since the heat generation member **202** corresponding to the B5 paper is used even when printing A5 papers, the temperature rise of the film **51** was large, and it was necessary to increase the paper interval so that the temperature rise in the non-sheet feeding portion will not occur, and it was found that the maximum productivity was as low as 16 sheets/minute.

(69) As described above, according to Embodiment 1, since the heat generation member having a first length includes two heat generation members, i.e., a first heat generation member and a second heat generation member, the power provided to the heat generation member having the first length can be distributed. Additionally, since the power is always supplied to the first heat generation member and the second heat generation member at the same time, the temperature rise does not unevenly occur only in one end of the substrate in the width direction. Accordingly, assuming an unexpected apparatus failure, even if an electric power is excessively supplied to the heat generation member having the first length, the temperature gradient generated in the substrate in the width direction can be reduced. The fact that the temperature gradient is small enables the reduction of distortion (heat stress) generated in the substrate, and the deformation of the substrate can be suppressed.

(70) Next, the power supply capability of a third heat generation member and a fourth heat generation member having the lengths shorter than the first length in the longitudinal direction, and having different lengths in the longitudinal direction is made smaller than that of the heat generation member having the first length. Then, the third heat generation member and the fourth heat generation member are arranged between the first heat generation member and the second heat generation member in the width direction of the substrate, and the symmetry in the width direction of the substrate is maintained as much as possible. Accordingly, assuming an unexpected apparatus failure, even if an electric power is excessively supplied to one of the third heat generation member and the fourth heat generation member, the temperature gradient generated in the substrate in the width direction can be reduced, and the deformation of the substrate due to distortion can be suppressed. Then, since the third heat generation member and fourth heat generation member having the lengths shorter than the first length in the longitudinal direction, and having different lengths in the longitudinal direction are provided, the productivity for a plurality of kinds of papers

having narrow widths can be improved. Finally, the reduction of the sizes of the heater can also be achieved at the same time by including two heat generation members only for the heat generation members having the first length, and including one heat generation member for each of the other heat generation members having shorter lengths in the longitudinal direction.

Modification 1

(71) In Embodiment 1, although the details have been described about the configuration in which the two longest heat generation members **54b1** and **54b2** are electrically connected in parallel, and the power is supplied to the two longest heat generation members **54b1** and **54b2** at the same time, the configuration is not limited to this configuration. FIG. 9A is a diagram illustrating the configuration of the heater **54**, and FIG. 9B is a diagram illustrating the heater **54** and the power control unit **97**. As illustrated in FIG. 9A, the heater may be a heater in which the first contact **54d1**, the first heat generation member **54b1**, the second heat generation member **54b2**, and the second contact **54d3** are electrically connected in series in this order. Specifically, in the heat generation member **54b1**, one end is connected to the contact **54d1**, and the other end is connected to the other end of the heat generation member **54b2** via the conductor **54c** without any contacts. In the heat generation member **54b2**, one end is connected to the contact **54d3**, and the other end is connected to the other end of the heat generation member **54b1** via the conductor **54c** without any contacts. In the heat generation member **54b3**, one end is connected to the contact **54d1**, and the other end is connected to the contact **54d3**. In the heat generation member **54b4**, one end is connected to the contact **54d3**, and the other end is connected to the contact **54d4**.

(72) As illustrated in FIG. 9B, the electromagnetic relay **57a** includes the contact **57a1** connected to the first pole of the AC power supply **55** via the triac **56**, the contact **57a2** connected to the contact **54d1**, and the contact **57a3** connected to the contact **54d4**. The electromagnetic relay **57a** is brought into either one of the states, i.e., the state where the contact **57a1** and the contact **57a2** are connected to each other, and the state where the contact **57a1** and the contact **57a3** are connected to each other, by the control of the engine controller **92**. The electromagnetic relay **57b** includes the contact **57b1** connected to the second pole of the AC power supply **55**, the contact **57b2** connected to the contact **54d2**, and the contact **57b3** connected to the contact **54d3**. The electromagnetic relay **57b** is brought into either one of the states, i.e., the state where the contact **57b1** and the contact **57b2** are connected to each other, and the state where the contact **57b1** and the contact **57b3** are connected to each other, by the control of the engine controller **92**.

(73) FIG. 9A illustrates the electromagnetic relays **57a** and **57b** at the time of non-operation, the contact **57a1** and the contact **57a2** are connected to each other in the electromagnetic relay **57a**, and the contact **57b1** and the contact **57b2** are connected to each other in the electromagnetic relay **57b**. At the time of non-operation of the electromagnetic relays **57a** and **57b**, since power is supplied between the contact **54d1** and the contact **54d2**, the longest heat generation members **54b1** and **54b2** generate heat.

(74) In a case where only the electromagnetic relay **57b** is operated, the contact **57a1** and the contact **57a2** are connected to each other in the electromagnetic relay **57a**, and the electromagnetic relay **57b** is brought into the state where the contact **57b1** and the contact **57b3** are connected to each other. At the time of operation of only the electromagnetic relay **57b**, since power is supplied between the contact **54d1** and the contact **54d3**, only the heat generation member **54b3** generates heat. In a case where only the electromagnetic relay **57a** is operated, the contact **57a1** and the contact **57a3** are connected to each other in the electromagnetic relay **57a**, and the electromagnetic relay **57b** is brought into the state where the contact **57b1** and the contact **57b2** are connected to each other. At the time of operation of only the electromagnetic relay **57a**, since power is supplied between the contact **54d4** and the contact **54d2**, only the heat generation member **54b4** generates heat.

(75) As described above, in FIG. 9A and FIG. 9B of the modification, one ends of the heat generation member **54b1** and the heat generation member **54b3** are electrically connected to the

contact **54d1**, which is the first contact. One ends of the heat generation member **54b4** and the heat generation member **54b2** are electrically connected to the contact **54d2**, which is the second contact. The other end of the heat generation member **54b3** is electrically connected to the contact **54d3**, which is the third contact. The other end of the heat generation member **54b4** is electrically connected to the contact **54d4**, which is the fourth contact. Then, the other end of the heat generation member **54b1** and the other end of the heat generation member **54b2** are electrically connected to each other.

(76) Also in the configuration of FIG. 9A and FIG. 9B, since it is the configuration in which power is supplied to the longest heat generation members **54b1** and **54b2** at the same time, the same effects as those in Embodiment 1 are exhibited. The suppliable power to the longest heat generation members **54b1** and **54b2** can be made equivalent to that in Embodiment 1, and the electrical resistance across both ends of each of the first heat generation member **54b1** and the second heat generation member **54b2**, which are the longest heat generation members, may be 552Ω . In FIG. 9A and FIG. 9B, the heat generation member **54b1** and the heat generation member **54b2** are connected in series, and the combined resistance value is 10Ω . The other heat generation members may be the same as those in Embodiment 1. In this manner, also in Modification 1, the combined resistance of the heat generation member **54b1** and the heat generation member **54b2** is 10Ω , and is smaller than the resistances (30Ω) of the heat generation member **54b3** and the heat generation member **54b4**. The effects exhibited by the heater **54** illustrated in FIG. 9A and FIG. 9B are the same as those in Embodiment 1.

Modification 2

(77) In Embodiment 1, although the details have been described about the case where the number of the non-longest heat generation members **54b3** and **54b4** are two, the configuration is not limited to this configuration. For example, as illustrated in FIG. even with the configuration in which the number of the non-longest heat generation members is three, the same effects described in Embodiment 1 can be exhibited. That is, Modification 2 includes a heat generation member **54b5**, which is a fifth heat generation member whose length in the longitudinal direction is shorter than that of the heat generation member **54b4**, which is the fourth heat generation member. In the heat generation member **54b1** and the heat generation member **54b2**, one ends are connected to the contact **54d1**, which is a first common contact, and the other ends are connected to the contact **54d2**, which is a second common contact. In the heat generation member **54b3**, one end is connected to the contact **54d3**, which is the third contact, and the other end is connected to the contact **54d2**. In the heat generation member **54b4**, one end is connected to the contact **54d4**, which is the fourth contact, and the other end is connected to the contact **54d2**. In the heat generation member **54b5**, one end is connected to the contact **54d5**, which is a fifth contact, and the other end is connected to the contact **54d2**. That is, the other ends of all the heat generation members **54b1** to **54b5** are connected to the contact **54d2**. Additionally, the three heat generation members **54b3** to **54b5** are arranged between the two heat generation members **54b1** and **54b2** in the width direction of the substrate **54a**. Further, the heat generation member **54b5** is arranged between the heat generation members **54b3** and **54b4** in the width direction of the substrate **54a**.

(78) The heater **54** illustrated in FIG. 10 will be described. The longest heat generation members **54b1** and **54b2** are arranged on the both ends of the substrate **54a** in the width direction, and power is supplied from the common contacts **54d1** and **54d2** to the longest heat generation members **54b1** and **54b2** at the same time. As in Embodiment 1, the electrical resistance across both ends of each of the longest heat generation members **54b1** and **54b2** is set to $20[\Omega]$. The lengths of the heat generation members **54b1** and **54b2** in the longitudinal direction are 222 mm.

(79) The lengths in the longitudinal direction are 188 mm in the heat generation member **54b3**, 154 mm in the heat generation member **54b4**, and 111 mm in the heat generation member **54b5**. The heat generation member **54b3** is used at the time of printing of a B5 paper, the heat generation member **54b4** is used for printing of an A5 paper, and the heat generation member **54b5** is used at

the time of printing of an A6 paper. The electrical resistance across both ends of each of these non-longest heat generation members **54b3** to **54b5** is set to $30[\Omega]$. In this manner, also in Modification 2, the combined resistance of the heat generation member **54b1** and the heat generation member **54b2** is 10Ω , and is smaller than the resistances (30Ω) of the heat generation member **54b3** to the heat generation member **54b5**. By increasing the number of kinds of the non-longest heat generation members to three, the maximization of the productivity for the three kinds of papers, a B5 paper, an A5 paper and an A6 paper, is enabled.

(80) In the non-longest heat generation members, assuming an excessive electric power supply, the power supplied to each of the heat generation members **54b3** to **54b5** is the same. Since the length of the heat generation member **54b5** in the longitudinal direction is the shortest, the degree of concentration of power is the highest, and the deformation risk of the substrate **54a** at the time of temperature rise is high. For the purpose of removing this risk as much as possible, the shortest heat generation member **54b5** can be arranged in the center portion in the width direction of the substrate **54a** to give the symmetry in the width direction. Additionally, the heat generation members **54b3** and **54b4** can be arranged on both sides of the heat generation member **54b5** in the width direction, to be close to the center as much as possible. The effects exhibited by the heater **54** illustrated in FIG. **10** are the same as those in Embodiment 1.

Modification 3

(81) In Modification 2, four contacts are arranged at one end of the substrate **54a** in the longitudinal direction, and one contact is arranged at the other end. In Modification 3, an example will be described in which three contacts are arranged at one end in the longitudinal direction, and two contacts are arranged at the other end. In Modification 3, since the heat generation member can be arranged in the center in the longitudinal direction of the substrate **54a** to the utmost, it is an arrangement preferable for making the heat generation distribution in the longitudinal direction uniform.

(82) Modification 3 includes the heat generation member **54b5**, which is the fifth heat generation member whose length in the longitudinal direction is shorter than that of the heat generation member **54b4**, which is the fourth heat generation member. In the heat generation member **54b1** and the heat generation member **54b2**, one ends are connected to the contact **54d1**, which is the first common contact, and the other ends are connected to the contact **54d2**, which is the second common contact. In the heat generation member **54b3**, one end is connected to the contact **54d3**, which is the third contact, and the other end is connected to the contact **54d2**. In the heat generation member **54b4**, one end is connected to the contact **54d3**, and the other end is connected to the contact **54d4**, which is the fourth contact. In the heat generation member **54b5**, one end is connected to the contact **54d5**, which is the fifth contact, and the other end is connected to the contact **54d4**. Among the five heat generation members, the first heat generation member **54b1** and the second heat generation member **54b2** having the longest length, and the fourth heat generation member **54b3** having the second longest length are connected to the second contact **54d2**. The fourth heat generation member **54b3** having the second longest length, and the fourth heat generation member **54b4** having the third longest length are connected to the third contact **54d3**. The fourth heat generation member **54b4** having the third longest length, and the fifth heat generation member **54b5** having the fourth longest length are connected to the fourth contact **54d4**. That is, the heat generation member **54b** is connected to the contact common to another heat generation member **54b** with which the difference in length from the heat generation member **54b** is the minimum. Additionally, the three heat generation members **54b3** to **54b5** are arranged between the two heat generation members **54b1** and **54b2** in the width direction of the substrate **54a**. Further, the heat generation member **54b5** is arranged between the heat generation members **54b3** and **54b4** in the width direction of the substrate **54a**.

(83) The heater **54** illustrated in FIG. **11** will be described. The longest heat generation members **54b1** and **54b2** are arranged on the both ends of the substrate **54a** in the width direction, and power

is supplied from the common contacts **54d1** and **54d2** to the longest heat generation members **54b1** and **54b2** at the same time. As in Embodiment 1, the electrical resistance across both ends of each of the longest heat generation members **54b1** and **54b2** is set to $20[\Omega]$. The lengths of the heat generation members **54b1** and **54b2** in the longitudinal direction are 222 mm.

(84) The lengths in the longitudinal direction are 188 mm in the heat generation member **54b3**, 154 mm in the heat generation member **54b4**, and 111 mm in the heat generation member **54b5**. The heat generation member **54b3** is used at the time of printing of a B5 paper, the heat generation member **54b4** is used for printing of an A5 paper, and the heat generation member **54b5** is used at the time of printing of an A6 paper. The electrical resistance across both ends of each of these non-longest heat generation members **54b3** to **54b5** in the longitudinal direction is set to $30[\Omega]$. In this manner, also in Modification 3, the combined resistance of the heat generation member **54b1** and the heat generation member **54b2** is 10Ω , and is smaller than the resistances (30Ω) of the heat generation member **54b3** to the heat generation member **54b5**. By increasing the number of kinds of the non-longest heat generation members to three, the maximization of the productivity for the three kinds of papers, a B5 paper, an A5 paper and an A6 paper, is enabled.

(85) Assuming an excessive electric power supply in the non-longest heat generation members **54b**, the power supplied to each of the heat generation members **54b3** to **54b5** is the same. Since the length of the heat generation member **54b5** in the longitudinal direction is the shortest, the degree of concentration of power is the highest, and the deformation risk of the substrate **54a** at the time of temperature rise is high. For the purpose of removing this risk as much as possible, the shortest heat generation member **54b5** can be arranged in the center portion in the width direction of the substrate **54a** to give the symmetry in the width direction. Additionally, the heat generation members **54b3** and **54b4** can be arranged on both sides of the heat generation member **54b5** in the width direction, to be close to the center as much as possible. The effects exhibited by the heater **54** illustrated in FIG. 11 are the same as those in Embodiment 1.

(86) Conventionally, the resistance of each of a plurality of heat generation members has the same resistance value, and the suppliable power is also the same. Conventionally, in a case where power is continuously supplied to a heat generation member having a wide width, an excessive temperature rise occurs in one end of a substrate in the width direction. Therefore, the temperature gradient in the substrate becomes large, and there is a possibility that the substrate is greatly distorted. Additionally, conventionally, since only one kind of a heat generation member having a narrow width is provided, in papers having a plurality of kinds of sizes, it is difficult to suppress the temperature rise in the non-sheet feeding area, and it is difficult to provide a high productivity. On the other hand, according to Embodiment 1, the deformation of a substrate on which a heater is mounted can be suppressed.

Embodiment 2

(87) Since the shape of the heater **54** of Embodiment 2 is the same as that in Embodiment 1, and is as illustrated in FIG. 4, a description will be omitted. In Embodiment 2, among the non-longest heat generation members **54b3** and **54b4**, the power density (described later) of the shorter heat generation member **54b4** is made higher than the power density of the longer heat generation member **54b3**. The non-longest heat generation members **54b3** and **54b4** have a large non-heating area that cannot be heated in the longitudinal direction. The shorter the length in the longitudinal direction of the heat generation member **54b** is, the wider this non-heating area becomes, and the heat of the heat generation member **54b** is easily taken away by the non-heating area. The fixing apparatus **50** cannot sufficiently perform heating in the vicinity of this non-heating area, and there is a possibility that a toner image cannot be fixed to the paper P. Therefore, at least the power density of the shorter heat generation member **54b4** can be made higher than the power density of the longer heat generation member **54b3**.

(88) Additionally, among the non-longest heat generation members **54b3** and **54b4**, the resistance value of the shorter heat generation member **54b4** is made to be equal to or higher than the

resistance value of the longer heat generation member 54b3. Accordingly, the fixing apparatus 50 can be operated with a certain current amount or less, irrespective of whether the shorter heat generation member 54b4 or the longer heat generation member 54b3 is used. Accordingly, low rating and low cost wires, elements, etc. can be chosen for bundled wires, electric elements, etc. to be connected to the non-longest heat generation members 54b3 and 54b4.

(89) Here, the power density is defined as the value (in the unit of W/mm) obtained by dividing the power generated when 100V is provided to the heat generation member 54b by the length of the heat generation member 54b in the longitudinal direction. Let the electric resistance value of the longer heat generation member 54b3 be R1, the electric resistance value of the shorter heat generation member 54b4 be R2, the length of the longer heat generation member 54b3 in the longitudinal direction be L1, and the length of the shorter heat generation member 54b4 in the longitudinal direction be L2. In that case, the power of the longer heat generation member 54b3 is expressed by “100.sup.2/R1”, and the power of the shorter heat generation member 54b4 is expressed by “100.sup.2/R2.” Since the respective powers are divided by the length of the heat generation member 54b, the power density of the longer heat generation member 54b3 is expressed by “100.sup.2/R1/L1”, and the power density of the shorter heat generation member 54b4 is expressed by “100.sup.2/R2/L2.” Embodiment 2 has the characteristic in the relationship “100.sup.2/R1/L1<100.sup.2/R2/L2.” This relational expression can also be expressed as “R1L1>R2L2.”

(90) [Power Density and Whether or not Fixing can be Performed]

(91) The power density of the heat generation member 54b, and the confirmation conditions for confirming whether fixing of a toner image to the paper P can be performed will be described below. The image process speed of an image forming apparatus is 200 mm/sec, and the interval (paper interval) between the preceding paper and the subsequent paper is set to 0.25 second. Sheet feeding is performed by performing the temperature control by the engine controller 92, so that the back surface of the substrate 54a becomes 180° C. by the fixing temperature sensor 59 installed in the back surface of the substrate 54a. Note that the fixing apparatus 50 including the heater 54 is kept in the state where it is sufficiently cooled.

(92) Among the non-longest heat generation members 54b3 and 54b4, when using the longer heat generation member 54b3, Canon CS680 paper having the B5 (182 mm in width×257 mm in length×92 μm in thickness, a basis weight of 68 g/m.sup.2) size is used. When using the shorter heat generation member 54b4, the above-described CS680 paper is cut into the A5 size (148.5 mm in width×210 mm in length×92 μm in thickness, a basis weight of 68 g/m.sup.2), and feeding of 10 papers are continuously performed in any case. Note that the toner image on the paper P is uniformly formed in the entire area of the paper P (each of the top margin, the bottom margin, the left margin, and the right margin is set to 5 mm), and a toner amount is 1.0 mg/cm 2.

(93) Whether or not there is a portion in which the toner image on the paper P is unfixed is confirmed, and the case where all is fixed is considered to have no fixability problem and indicated by “○”, and the case where there is an unfixed portion is considered to have a fixation failure and indicated by “x”. The fixability is confirmed for the five kinds of longer heat generation members 54b3 having different power densities, and for the five kinds of shorter heat generation members 54b4 having different power densities. The confirmation results are illustrated in Table 1.

(94) TABLE-US-00001 TABLE 1 heat generation member power length density fixability longer heat generation member 188 1.90 pass 188 1.77 pass 188 1.72 pass 188 1.66 fail 188 1.56 fail shorter heat generation member 154 2.03 pass 154 1.91 pass 154 1.80 pass 154 1.76 fail 154 1.71 fail

(95) In Table 1, the left side table illustrates the longer heat generation member 54b3, and the right side table illustrates the shorter heat generation member 54b4. In each table, the length of the heat generation member 54b in the longitudinal direction is shown in the first row, the power density is shown in the second row, and the above-described fixability (○ or x) is shown in the third row.

(96) As illustrated in Table 1, in the longer heat generation member **54b3**, the entire toner image was fixed to the paper P with the power density of 1.72 [W/mm] or more, and there was no problem in the fixability. Additionally, in the shorter heat generation member **54b4**, the entire toner image was fixed to the paper P with the power density of 1.8 [W/mm] or more, and there was no fixability problem. Further, it was able to confirm that the heat generation member **54b4**, having a larger non-heating area in which heat is easily taken away by the non-heating area near the ends of the heat generation member **54b4**, and having a shorter length in the longitudinal direction, required a higher power density compared with the heat generation member **54b3**.

(97) [Maximum Current Amount and Whether or not Fixing can be Performed]

(98) Here, the maximum current amount refers to the current amount that flows when 100V is applied to the heat generation member **54b**. The smaller the value of this maximum current amount is, the more it is enabled to choose low cost and low rating wires, elements, etc. for bundled wires, electric elements, etc. to be connected to the heat generation member **54b**. FIG. 12 illustrates the relationship between the maximum current amount [A] and the power density [W/mm], and indicates the cases without a fixability problem with “○”, and the cases with a fixation failure with “x”.

(99) In the longer heat generation member **54b3**, it is a plot Lg1 that has “○” for the fixability, and has the smallest maximum current amount. In the plot Lg1, the power density is 1.72 [W/mm], and the maximum current amount is 3.23 [A]. The electrical resistance of the heat generation member **54b3** at this time is 31[Ω]. In the shorter heat generation member **54b4**, it is a plot St1 that has “○” for the fixability, and has the smallest maximum current amount. In the plot St1, the power density is 1.80 [W/mm], and the maximum current amount is 2.78 [A]. The electrical resistance of the heat generation member **54b4** at this time is 36[Ω]. That is, in the shorter heat generation member **54b4** of the plot St1, the power density becomes higher, and the resistance value also becomes higher compared with the longer heat generation member **54b3** of the plot Lg1. In this manner, assuming that the longer heat generation member **54b3** is 31[Ω], and the shorter heat generation member **54b4** is 36[Ω], the fixability can be satisfied, and the maximum current amount can be kept to 3.23 [A] or less. Then, low cost and low rating wires, elements, etc. can be chosen for bundled wires, electric elements, etc. to be connected to the heat generation member **54b**.

(100) Note that, in the shorter heat generation member **54b4**, although the conditions of the plot St1 were recommended, also in a plot St2 indicated by a black dot, the power density is as low as 2.09 [W/mm], and the maximum current amount is 3.23 [A] or less. The electric resistance value of the shorter heat generation member **54b4** at this time is 31[Ω]. Even if the electrical resistances are set to the same value, i.e., 31[Ω] for the longer heat generation member **54b3**, and 31[Ω] for the shorter heat generation member **54b4**, the fixability can be satisfied, and the maximum current amount can be kept to 3.23 [A] or less. That is, in the shorter heat generation member **54b4** of the plot St2, the power density becomes higher, and the resistance value is equal compared with the longer heat generation member **54b3** of the plot Lg1. From the above, in the graph of FIG. 12, the shorter heat generation member **54b4** can be used in the range from the plot St1 to the plot St2.

(101) From the above confirmation results, among the non-longest heat generation members **54b3** and **54b4**, the power density of the shorter heat generation member **54b4** is made higher than the power density of the longer heat generation member **54b3**. Accordingly, irrespective of which one of the heat generation members **54b** is used, the fixability near the non-heating area in the both sides of the heat generation member **54b** can be satisfied. Further, by making the resistance value of the shorter heat generation member **54b4** equal to or higher than the resistance value of the longer heat generation member **54b3**, the fixing apparatus 50 can be operated with a certain current amount or less, and inexpensive bundled wires, etc. can be used.

(102) As described above, according to Embodiment 2, the deformation of the substrate on which the heater is mounted can be suppressed.

Embodiment 3

(103) FIG. 13A is a cross-sectional view of a fixation nip portion N of the fixing apparatus 50, and illustrates a part of the film 51, a part of the nip forming member 52, the heater 54 and the pressure roller 53. It is assumed that the center of the rotation axis of the pressure roller 53 is C, among the non-longest heat generation members 54b3 and 54b4, the position of the shorter heat generation member 54b4 is H1, and the position of the longer heat generation member 54b3 is H2. The distance from the center C to the position H1 is defined as RL1, and the distance from the center C to the position H2 is defined as RL2. Embodiment 3 is characterized in that the heater 54 is arranged at a position where the distance RL1 becomes smaller than the distance RL2 ($RL1 < RL2$). Since the closer the distance between the center C of the pressure roller 53 and the heat generation member 54b is, the greater the amount of collapse of the elastic layer of the pressure roller 53 becomes, the pressure in the fixation nip portion N at the position H1 can be made higher than that at the position H2.

(104) FIG. 13B illustrates the profile of the pressure (nip pressure) of the fixation nip portion N in the conveyance direction of the paper P. In FIG. 13B, the horizontal axis represents the position in the conveyance direction corresponding to the fixation nip portion N illustrated in FIG. 13A, and the vertical axis represents the nip pressure. As illustrated in FIG. 13B, in the conveyance direction of the paper P, the nip pressure is the highest at the position of the center C of the pressure roller 53. Additionally, as illustrated in FIG. 13B, it can be seen that the nip pressure at the position H1 is higher than the nip pressure at the position H2.

(105) As described above, the distance from the position of the center of rotation of the pressure roller 53 to the heat generation member 54b (the heat generation member 54b4 in FIG. 4, etc., and the heat generation member 54b5 in FIG. 10) having the shortest length in the longitudinal direction among the third heat generation member and the fourth heat generation member 54b is RL1. The distance from the position of the center of rotation of the pressure roller 53 to the other heat generation members, except for the shortest heat generation member among the third heat generation member and the fourth heat generation member, is RL2. Then, in Embodiment 3, the heat generation members 54b are arranged on the substrate at predetermined positions (for example, a center portion) in the longitudinal direction, so that the distance RL1 becomes shorter than the distance RL2.

(106) Since the nip pressure is high, the thermal resistance due to contact can be reduced between the heater 54 and the film 51, and between the film 51 and the pressure roller 53, and the heat transfer property between each component can be improved. With this improvement in the heat transfer property, even if power is excessively supplied to the heat generation member 54b at the time of occurrence of an unexpected failure, the excessive heat generated by the heater 54 can be quickly conducted to the pressure roller 53 having a high thermal capacity, etc. That is, the deformation risk of the substrate 54a can be reduced.

(107) Since the shorter the length of the heat generation member 54b in the longitudinal direction is, the larger the non-heating area becomes, and the more heat is taken away, the power density of the shorter heat generation member 54b4 can be made higher than the power density of the longer heat generation member 54b3. On the other hand, the risk of deformation of the substrate 54a at the time of failure is slightly high. In order to reduce this risk, the shorter heat generation member 54b4 can be arranged at the position H1 having a higher nip pressure. In Embodiment 3, even if power is excessively supplied to the shorter heat generation member 54b4, the generated heat can be quickly transferred to the pressure roller 53, etc., and the risk of deformation of the substrate 54a can be reduced. As described above, when incorporating the heater 54 described in Embodiment 1 and Embodiment 2 into the fixing apparatus 50, among the non-longest heat generation members 54b3 and 54b4, the shorter heat generation member 54b4 is arranged closer to the center C of the pressure roller 53 than the longer heat generation member 54b3. Accordingly, the risk of deformation of the substrate 54a can be reduced.

(108) As described above, according to Embodiment 3, the deformation of the substrate on which

the heater is mounted can be suppressed.

(109) According to the present invention, the deformation of the substrate on which the heater is mounted can be suppressed.

(110) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(111) This application claims the benefit of Japanese Patent Application No. 2019-006469, filed Jan. 18, 2019, which is hereby incorporated by reference herein in its entirety.

Claims

1. A heater comprising: a substrate; a first heat generation member having a length in a longitudinal direction; a second heat generation member having a length in the longitudinal direction, the length being substantially equal to the length of the first heat generation member; a third heat generation member having a length in the longitudinal direction, the length being shorter than the lengths of the first heat generation member and the second heat generation member; a fourth heat generation member having a length in the longitudinal direction, the length being shorter than the length of the third heat generation member; and wherein the first heat generation member, the second heat generation member, the third heat generation member, and the fourth heat generation member are arranged on the substrate, wherein the first heat generation member is arranged at one end of the substrate in a width direction, wherein the second heat generation member is arranged at another end of the substrate in the width direction, to be symmetrical with the first heat generation member, wherein the third heat generation member and the fourth heat generation member are arranged between the first heat generation member and the second heat generation member in the width direction of the substrate, wherein the first heat generation member, the third heat generation member, the fourth heat generation member and the second heat generation member are arranged in this order in the width direction, wherein a relationship of $R1 < R2$ is satisfied, and wherein a relationship of $R1 \times L1 > R2 \times L2$ is satisfied, where $L1$ is the length of the third heat generation member in the longitudinal direction, $R1$ is a value of a resistance of the third heat generation member, $L2$ is the length of the fourth heat generation member in the longitudinal direction, and $R2$ is a value of a resistance of the fourth heat generation member.

2. A heater according to claim 1, wherein a value of a combined resistance of the first heat generation member and the second heat generation member is smaller than a value of a resistance of the third heat generation member, and a value of a resistance of the fourth heat generation member, and wherein the first heat generation member and the second heat generation member are electrically connected in parallel.

3. A heater according to claim 1, wherein the third heat generation member and the fourth heat generation member are arranged to be symmetrical in the width direction of the substrate.

4. A heater according to claim 1, further comprising: a first contact to which one end of the first heat generation member and one end of the second heat generation member are electrically connected; a second contact to which another end of the first heat generation member and another end of the second heat generation member and one end of the third heat generation member are electrically connected; a third contact to which another end of the third heat generation member and one end of the fourth heat generation member are electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected.

5. A heater according to claim 1, further comprising: a first contact to which one end of the first heat generation member and one end of the third heat generation member are electrically connected; a second contact to which one end of the fourth heat generation member and one end of the second heat generation member are electrically connected; a third contact to which another end

of the third heat generation member is electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected, wherein another end of the first heat generation member and another end of the second heat generation member are electrically connected to each other.

6. A heater according to claim 1, further comprising: a first contact to which one end of the first heat generation member and one end of the second heat generation member are electrically connected; a second contact to which another end of the first heat generation member and another end of the second heat generation member and one end of the third heat generation member are electrically connected; a third contact to which another end of the third heat generation member and one end of the fourth heat generation member are electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected.

7. A fixing apparatus for fixing an unfixed toner image carried by a recording material, the fixing apparatus comprising: a heater; a first rotary member heated by the heater; and a second rotary member forming a nip portion with the first rotary member, wherein the heater comprising: a substrate; a first heat generation member having a length in a longitudinal direction; a second heat generation member having a length in the longitudinal direction, the length being substantially equal in to a length of the first heat generation member; a third heat generation member having a length in the longitudinal direction, the length being shorter than the lengths of the first heat generation member and the second heat generation member; a fourth heat generation member having a length in the longitudinal direction, the length being shorter than the length of the third heat generation member; and wherein the first heat generation member, the second heat generation member, the third heat generation member, and the fourth heat generation member are arranged on the substrate, wherein the first heat generation member is arranged at one end of the substrate in a width direction, wherein the second heat generation member is arranged at another end of the substrate in the width direction, to be symmetrical with the first heat generation member, wherein the third heat generation member and the fourth heat generation member are arranged between the first heat generation member and the second heat generation member in the width direction of the substrate, wherein the first heat generation member, the third heat generation member, the fourth heat generation member and the second heat generation member are arranged in this order in the width direction, wherein a relationship of $R1 < R2$ is satisfied, and wherein a relationship of $R1 \times L1 > R2 \times L2$ is satisfied, where $L1$ is the length of the third heat generation member in the longitudinal direction, $R1$ is a value of a resistance of the third heat generation member, $L2$ is the length of the fourth heat generation member in the longitudinal direction, and $R2$ is a value of a resistance of the fourth heat generation member.

8. A fixing apparatus according to claim 7, wherein the first rotary member is a film.

9. A fixing apparatus according to claim 8, wherein the heater is provided in an inner space of the film, wherein the heater and the second rotary member pinch the film, and wherein an image on a recording material is heated at the nip portion formed between the film and the second rotary member, through the film.

10. A fixing apparatus according to claim 7, wherein at a predetermined position in the longitudinal direction, a distance from a position of a center of rotation of the second rotary member to a heat generation member having a shortest length in the longitudinal direction among other heat generation members except for the first heat generation member and the second heat generation member is shorter than a distance from the position of the center of rotation of the second rotary member to a heat generation member except for the heat generation member having the shortest length among the other heat generation members.

11. An image forming apparatus comprising: an image forming unit configured to form an unfixed toner image on a recording material; and a fixing apparatus according to claim 7, wherein the fixing apparatus is configured to fix the unfixed toner image on the recording material.

12. An image forming apparatus according to claim 11, wherein a value of a combined resistance of

the first heat generation member and the second heat generation member is smaller than a value of a resistance of the third heat generation member, and a value of a resistance of the fourth heat generation member.

13. An image forming apparatus according to claim 11, wherein the third heat generation member and the fourth heat generation member are arranged to be symmetrical in the width direction of the substrate.

14. An image forming apparatus according to claim 11, further comprising: a first contact to which one end of the first heat generation member and one end of the second heat generation member are electrically connected; a second contact to which another end of the first heat generation member and another end of the second heat generation member and one end of the third heat generation member are electrically connected; a third contact to which another end of the third heat generation member and one end of the fourth heat generation member are electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected.

15. An image forming apparatus according to claim 11, further comprising: a first contact to which one end of the first heat generation member and one end of the third heat generation member are electrically connected; a second contact to which one end of the fourth heat generation member and one end of the second heat generation member are electrically connected; a third contact to which another end of the third heat generation member is electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected, wherein another end of the first heat generation member and another end of the second heat generation member are electrically connected to each other.

16. A fixing apparatus according to claim 7, wherein a value of a combined resistance of the first heat generation member and the second heat generation member is smaller than a value of a resistance of the third heat generation member, and a value of a resistance of the fourth heat generation member.

17. A fixing apparatus according to claim 7, wherein the third heat generation member and the fourth heat generation member are arranged to be symmetrical in the width direction of the substrate.

18. A fixing apparatus according to claim 7, further comprising: a first contact to which one end of the first heat generation member and one end of the third heat generation member are electrically connected; a second contact to which one end of the fourth heat generation member and one end of the second heat generation member are electrically connected; a third contact to which another end of the third heat generation member is electrically connected; and a fourth contact to which another end of the fourth heat generation member is electrically connected, wherein another end of the first heat generation member and another end of the second heat generation member are electrically connected to each other.
