

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12417449

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Robell; James Frederick et al.

Technologies for creating and transferring non-fungible token based identities

Abstract

The present disclosure is related to blockchain technologies, tokenization and non-fungible token (NFT) technologies, identity verification, account verification, information security (InfoSec), and fraud prevention technologies, and in particular, to technologies for creating NFT identities (IDs) for individuals and/or organizations. An NFT ID service interacts with users to obtain ID information such as ID documents, biographical data, biometric data, and/or any other suitable data. The NFT ID service includes an NFT ID engine that generates an NFT-based form of digitized and/or tokenized ID, using blockchain technology, smart contracts, distributed ledgers, digital wallets, and the ID information. Other embodiments may be described and/or claimed.

Inventors: Robell; James Frederick (Beaverton, OR), Hart; James G. (Hillsboro, OR), Hoang; Qui Quoc (Portland, OR), Hoang; Viet Quoc (Portland, OR)

Applicant: FORTIOR SOLUTIONS, LLC (Hillsboro, OR)

Family ID: 1000008820186

Assignee: FORTIOR SOLUTIONS, LLC (Hillsboro, OR)

Appl. No.: 18/175791

Filed: February 28, 2023

Prior Publication Data

Document Identifier

Publication Date

US 20230281604 A1

Sep. 07, 2023

Related U.S. Application Data

us-provisional-application US 63315396 20220301

Publication Classification

Int. Cl.: G06Q20/00 (20120101); G06Q20/36 (20120101); G06Q20/38 (20120101)

U.S. Cl.:

CPC G06Q20/3672 (20130101); G06Q20/389 (20130101);

Field of Classification Search

CPC: G06Q (20/3672); G06Q (20/389); G06Q (20/4014); G06Q (30/018); G06Q (50/265); G06Q (20/36)

USPC: 705/16; 705/21; 705/59; 380/44; 380/262; 380/278

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8874770	12/2013	Ruff et al.	N/A	N/A
8954742	12/2014	Moreira et al.	N/A	N/A
9696966	12/2016	Edwards et al.	N/A	N/A
9763064	12/2016	Ruff et al.	N/A	N/A
9836619	12/2016	Goldston	N/A	N/A
9893889	12/2017	Enguent et al.	N/A	N/A
9934460	12/2017	Enguent et al.	N/A	N/A
10108894	12/2017	Pic	N/A	N/A
10333705	12/2018	Smith et al.	N/A	N/A
10333706	12/2018	Smith et al.	N/A	N/A
10361849	12/2018	Smith et al.	N/A	N/A
10558974	12/2019	Smith et al.	N/A	N/A
10652018	12/2019	Smith et al.	N/A	N/A
10666434	12/2019	Smith et al.	N/A	N/A
10841307	12/2019	Smith et al.	N/A	N/A
10860910	12/2019	Boiron et al.	N/A	N/A
10965673	12/2020	Smith et al.	N/A	N/A
11099709	12/2020	McNeil et al.	N/A	N/A
11106753	12/2020	Fowler	N/A	N/A
11139956	12/2020	Shirley et al.	N/A	N/A
11170582	12/2020	McNeil et al.	N/A	N/A
11184437	12/2020	Shirley et al.	N/A	N/A
11210844	12/2020	McEroy Flavelle et al.	N/A	N/A
11227010	12/2021	Vieira De Souza et al.	N/A	N/A
11265166	12/2021	Seraj et al.	N/A	N/A
11281800	12/2021	Riedel et al.	N/A	N/A
11393162	12/2021	McEroy Flavelle et al.	N/A	N/A
11394550	12/2021	Youssef et al.	N/A	N/A
11520806	12/2021	Shih et al.	N/A	N/A
11526251	12/2021	McNeil et al.	N/A	N/A
11533467	12/2021	McNeil et al.	N/A	N/A

11546332	12/2022	Smith et al.	N/A	N/A
11605208	12/2022	McNeil et al.	N/A	N/A
2011/0191590	12/2010	Darbellay et al.	N/A	N/A
2014/0195626	12/2013	Ruff et al.	N/A	N/A
2015/0019666	12/2014	Ruff et al.	N/A	N/A
2016/0105776	12/2015	Ruff et al.	N/A	N/A
2016/0196112	12/2015	Edwards et al.	N/A	N/A
2017/0183135	12/2016	Pic et al.	N/A	N/A
2017/0193347	12/2016	Enguent et al.	N/A	N/A
2017/0195120	12/2016	Enguent et al.	N/A	N/A
2017/0200154	12/2016	Dubreucq et al.	N/A	N/A
2017/0203895	12/2016	Pic et al.	N/A	N/A
2017/0316390	12/2016	Smith et al.	N/A	N/A
2017/0316409	12/2016	Smith et al.	N/A	N/A
2017/0316410	12/2016	Smith et al.	N/A	N/A
2017/0317833	12/2016	Smith et al.	N/A	N/A
2017/0317834	12/2016	Smith et al.	N/A	N/A
2017/0317997	12/2016	Smith et al.	N/A	N/A
2018/0197057	12/2017	Pic	N/A	N/A
2018/0253703	12/2017	Smith et al.	N/A	N/A
2018/0253724	12/2017	Smith et al.	N/A	N/A
2018/0253725	12/2017	Smith et al.	N/A	N/A
2018/0255038	12/2017	Smith et al.	N/A	N/A
2018/0316507	12/2017	Smith et al.	N/A	N/A
2019/0114522	12/2018	Boiron et al.	N/A	N/A
2019/0280861	12/2018	Smith et al.	N/A	N/A
2019/0296904	12/2018	Smith et al.	N/A	N/A
2019/0303926	12/2018	Yantis	N/A	N/A
2019/0349371	12/2018	Smith et al.	N/A	N/A
2019/0349372	12/2018	Smith et al.	N/A	N/A
2020/0021589	12/2019	Smith et al.	N/A	N/A
2020/0177377	12/2019	Smith et al.	N/A	N/A
2021/0064780	12/2020	Smith et al.	N/A	N/A
2021/0065267	12/2020	Smith et al.	N/A	N/A
2021/0067511	12/2020	Smith et al.	N/A	N/A
2021/0264444	12/2020	Chen	N/A	N/A
2021/0273993	12/2020	Shirley et al.	N/A	N/A
2021/0336769	12/2020	Shirley et al.	N/A	N/A
2021/0390531	12/2020	Voorhees	N/A	N/A
2021/0409220	12/2020	Seraj et al.	N/A	N/A
2022/0006642	12/2021	Maj	N/A	N/A
2022/0029786	12/2021	Shirley et al.	N/A	N/A
2022/0038285	12/2021	Youssef et al.	N/A	N/A
2022/0159069	12/2021	Shirley et al.	N/A	N/A
2022/0166624	12/2021	Seraj et al.	N/A	N/A
2022/0171877	12/2021	Riedel et al.	N/A	N/A
2022/0309491	12/2021	Shapiro	N/A	G06F 21/64
2022/0326836	12/2021	McNeil et al.	N/A	N/A
2022/0350833	12/2021	Schwenck Bismarque et al.	N/A	N/A
2022/0350841	12/2021	Vieira De Souza et al.	N/A	N/A

2022/0358737	12/2021	McNeil et al.	N/A	N/A
2022/0360761	12/2021	McNeil et al.	N/A	N/A
2022/0383305	12/2021	Smith et al.	N/A	N/A
2022/0383306	12/2021	Smith et al.	N/A	N/A
2023/0033434	12/2022	Giang et al.	N/A	N/A
2023/0046383	12/2022	McNeil et al.	N/A	N/A
2023/0051057	12/2022	McNeil et al.	N/A	N/A
2023/0080322	12/2022	Smith et al.	N/A	N/A
2023/0139878	12/2022	Clark et al.	N/A	N/A
2023/0169498	12/2022	Sado	705/41	G06F 3/167

OTHER PUBLICATIONS

“Programmable Privacy for the Metaverse”, Photochromic | Whitepaper, pp. 1-16 (revised Jul. 2022), <https://photochromic.io/pdf/PhotoChromic-Whitepaper.pdf?v14>. cited by applicant

Russell, “PhotoChromic Launches Biometrically Secured Identification NFTs”, NFT Plazas, 3 pages (Dec. 18, 2021), <https://nftplazas.com/photochromic-launches-biometrically-secured-identification-nfts/>. cited by applicant

Quest et al., “Digital Trust: How banks can secure our digital identity”, Oliver Wyman and Int'l Banking Federation, 8 pages (Dec. 2021), <https://www.oliverwyman.com/our-expertise/insights/2021/dec/how-banks-can-secure-our-digital-identity-ibfed.html>. cited by applicant

Curran, “The Future of Digital Identity: Separating the digital from the individual”, Finextra, 5 pages (May 27, 2022), <https://www.finextra.com/the-long-read/421/the-future-of-digital-identity-separating-the-digital-from-the-individual>. cited by applicant

“Identity Verification for Crypto, Blockchain, & NFT Compliance”, iDenfy.com, 7 pages (retrieved May 16, 2023), <https://www.idenfy.com/identity-verification-crypto/>. cited by applicant

Vostrikov, “The Guide to Decentralized Identity in 2023”, iDenfy.com, 8 pages (Jan. 19, 2023), <https://www.idenfy.com/blog/the-guide-to-decentralized-identity-in-2023/>. cited by applicant

Vostrikov, “Frauds in NFTs And The Need For KYC”, iDenfy.com, 10 pages (Nov. 15, 2022), <https://www.idenfy.com/blog/frauds-in-nfts-and-the-need-for-kyc/>. cited by applicant

Gabija Stankevičiūtė, “10 Tips for Successful Identity Verification with iDenfy”, iDenfy.com, 11 pages (Jan. 18, 2021), <https://www.idenfy.com/blog/10-tips-successful-identity-verification-idenfy/>. cited by applicant

“SelfKey”, White Paper, The SelfKey Foundation, pp. 1-29 (Sep. 11, 2017), <https://docsend.com/view/mj3d47wtq4ih64gv>. cited by applicant

“Civic Pass—identity management tools for Web3”, Civic Technologies, Inc., 17 pages (accessed on May 15, 2023), <https://www.civic.com/>. cited by applicant

Reed et al., “The Technical Foundations of Sovrin: A White Paper from the Sovrin Foundation”, white paper, The Sorvin Foundation, 26 pages (Sep. 29, 2016), <https://evernym.wpenginepowered.com/wp-content/uploads/2017/07/The-Technical-Foundations-of-Sovrin.pdf>. cited by applicant

“Performant and modular APIs for Verifiable Data and SSI”, Veramo, 6 pages (accessed on May 15, 2023), <https://veramo.io/>. cited by applicant

“Immutable X Whitepaper”, version 1.1, 17 pages (Oct. 20, 2021), https://assets.website-files.com/646557ee455c3e16e4a9bcb3/646557ee455c3e16e4a9be87_Immutable%20X%20Whitepaper.pdf. cited by applicant

“The Sandbox: Play. Create. Own. Govern. Earn. Welcome to the Metaverse”, white paper, The Sandbox, 44 pages (Sep. 2020), https://installers.sandbox.game/The_Sandbox_Whitepaper_2020.pdf. cited by applicant

“Official Axie Infinity Whitepaper”, white paper, 32 pages (updated Nov. 2021), <https://whitepaper.axieinfinity.com/>. cited by applicant

International Search Report and Written Opinion issued in PCT/US2023/014152, dated Jun. 7, 2023; 8 pages. cited by applicant

Background/Summary

RELATED APPLICATIONS (1) The present application claims priority to U.S. Provisional App. No. 63/315,396 filed on Mar. 1, 2022, the contents of which is hereby incorporated by reference in its entirety.

FIELD

(1) The present disclosure generally relates to the fields of computing, data processing, cryptography, blockchain technologies, tokenization and non-fungible tokens (NFTs), identity verification, account verification, information security (InfoSec), and fraud prevention technologies, and in particular, to technologies for creating NFT-based identifiers and/or identities for individuals and/or organizations.

BACKGROUND

(2) Identity verification services are often used by businesses and/or government agencies to ensure that information provided by users is associated with the identity of a real person. The identity of the real person may be verified using identity information indicated by physical identity documents (e.g., identity card, driver's license, passport, national identification card, and/or the like). The identity document is usually used to connect a person to information about the person, often in a database such as those provided by one or more authoritative sources (e.g., credit bureaus, government database(s), corporate database(s), and/or the like).

(3) In some places, such as in the United State of America (US), individuals may be issued numerous forms of identity cards such as state-issued driver's license or other state-issued ID, social security card, passport, health insurance cards, company (e.g., employer) ID cards, and/or the like. These physical forms of ID have varying levels of security, trustworthiness, and identity assurance, and can be susceptible to counterfeit.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments and/or implementations will be readily understood by the following detailed description in conjunction with the accompanying drawings. The accompanying drawings illustrate by way of example, and not by way of limitation, the embodiments and/or implementations. To facilitate the present description, like reference numerals designate like structural elements.

(2) FIG. 1 depicts an example of existing identity ecosystems.

(3) FIG. 2 depicts an NFT ID ecosystem.

(4) FIG. 3 depicts elements of an example NFT/blockchain service that can be used to generate NFT IDs as discussed herein.

(5) FIG. 4 depicts components of an example NFT ID engine.

(6) FIG. 5 depicts an example procedure for minting NFT IDs.

(7) FIG. 6 illustrates an example computing system suitable for practicing various aspects of the present disclosure.

(8) FIG. 7 depicts examples processes for practicing various aspects of the present disclosure.

DETAILED DESCRIPTION

1. Non-Fungible Token Identity Embodiments

(9) Embodiments described herein include technologies for creating NFT-based IDs including creating NFT IDs derived from other forms of IDs such as physical identity documents. The ID

ecosystems of many jurisdictions, such as the US, are complex and fragmented. Identity documents are not easily verifiable as genuine or connected to the correct person. Identity theft and financial fraud are prevalent risks in the current ecosystem. The embodiments discussed herein provide a technical means for generating identity documents that defragment existing identity ecosystems, are easily verifiable as genuine and connected to the correct individual, and prevent or reduce the likelihood of identity theft or other forms of fraud.

(10) FIG. 1 depicts the existing ID ecosystem **100** in the US. Throughout the present disclosure, the US ID ecosystem is used as an example use case. However, the embodiments discussed herein may be applicable to the identity ecosystem of any geopolitical entity, legal jurisdiction, enterprise or corporate entity, and/or ad-hoc/non-formal entity or group.

(11) As there is no compulsory federal-level ID card that is issued to all US citizens, most US citizens and US non-citizen residents use a patchwork of identity documents issued by federal, state, and local governments as de facto identity cards. The government-issued identity documents used by most persons in the US typically include a state-issued driver's license or other state-issued ID, a social security (SS) card (or just the SS number), passport or (US passport card), permanent resident card (colloquially referred to as a "green card"), and in some cases a Common Access Card (CAC). In addition, birth certificates, car registrations, health insurance cards, organization/company ID cards, school (e.g., university, secondary school, and/or the like) ID cards, firearms permits, and many other physical forms of ID are also used for various purposes. However, these other forms of ID are fragmented and siloed solutions, which are usually not accepted outside of their specific domains. Despite their low assurance as a physical token for verifying identity, existing identity documents are used for various purposes, such as proving one's identity to obtain services from governmental agencies or private entities, as well as obtaining credit and other regulated financial services in banking, investments, and tax.

(12) The Real ID Act of 2005, H.R. 1268 Title II §§ 201-207, Pub. Law 109-13, 109th Cong. (2005) established uniform standards for the design and content of state drivers' licenses. Real ID is an example of an attempt by the Government sector to improve the security, trustworthiness, and identity assurance of existing forms of identity documents. Even with passage of the Real ID Act, most US citizens and US non-citizen residents are required to use different identity documents to prove their identity with different governmental bodies. Additionally, Real ID compliant identity documents have yet to be implemented as a required form of ID for flying on commercial airlines or other purposes, and Real ID compliant identity documents are still not required in many States.

(13) Furthermore, the aforementioned identity documents have varying levels of security, trustworthiness, and identity assurance and add complexity to the current ID ecosystem **100**. For example, many identity documents are printed on basic card stock that lacks meaningful security features, some of which do not include a photo of the individual. For this reason, fake identity documents (e.g., fake driver's licenses) are still widely and cheaply available on the internet.

(14) Some identity documents include an integrated circuit chip (ICC) that contains information (info) about the owner, including a personal identification number (PIN) and one or more public key infrastructure (PKI) digital certificates. However, a smartcard reader is usually needed in order to utilize the info stored in the ICC, and many governmental agencies and business lack these devices.

(15) Some websites and social media platforms previously or currently offer identity verification processes (also known as "account verification"). Account verification is a process of verifying that a new or existing account (e.g., account with the social media platform) is owned and/or operated by a specified individual or organization. Verified accounts are often visually distinguished by an icon (e.g., check mark, badge, and/or the like) somewhere in the profile of the verified account, incorporated in or with the account's avatar, next to the user name of verified individual or organization, and/or somewhere that is visually identifiable by other users of the platform. Account verification, at least in theory, enhances the quality of online services, mitigating sock puppetry, bots, trolling, online harassment, spam, vandalism, fake news, disinformation, and election interference. Examples of account verification processes include Facebook® blue verified badges, YouTube® grey

check mark, and Twitter® blue check mark. However, these social media account verification processes and icons only work with one platform. Additionally, some platforms have requirements preventing most users from accessing the account verification services (e.g., at present, YouTube® requires at least 100,000 subscribers and other requirements to receive a Grey Check).

(16) The embodiments herein simplify the ID ecosystem and also improve security and identity verification in comparison to existing technologies. In particular, the embodiments herein enhance the ID ecosystem, by providing for an NFT-based form of digitized/tokenized personal IDs using blockchain technology, smart contracts, digital wallets, and/or biometric data. The embodiments herein bring many identity-proofed physical IDs to the digital world as individual NFTs. Additionally, the NFT IDs are platform agnostic, meaning that the NFT IDs can be used across any and all platforms regardless of platform type and functionality. Furthermore, the NFT IDs are extremely difficult to duplicate or fake thereby enhancing InfoSec. The NFT IDs provide a more secure, trustworthy form of identification for all activities, online and offline that can be used anywhere, anytime, in any domain, Web2 or Web3.

(17) FIG. 2 depicts an example NFT ID ecosystem including various data inputs and outputs to/from an example NFT/blockchain service(s) **250**. The NFT/blockchain service(s) **250** provides various NFT ID services as discussed herein, and supports a wide range of usage models, which can be decided by the users and/or ID holders. Example usage models for the NFT/blockchain service(s) **250** (also referred to herein as “NFT ID service **250**”, “NFT service **250**”, “blockchain service **250**”, and/or the like) include government sector **202**, non-governmental organization (NGO) sector **204**, and social media sector **206** models. The government sector **202** includes governmental entities and/or regulatory bodies. The NGO sector **204** includes any non-profit and/or commercial entities including financial services organizations (orgs) and/or the like. The social media sector **206** includes any social media platform or other like entity that desires account verification and/or the like. Other usage models may be included in other implementations.

(18) In an example use case, the NFT IDs discussed herein can be used by government agencies, as well as the commercial sector and other non-government agency entities, to create trustable NFT IDs based on their own security requirements and/or policies. In another example use case, the NFT IDs discussed herein allow social media influencers and content creators to identify themselves and their contents across multiple platforms, or if they move from one platform to another, through their NFT IDs.

(19) FIG. 3 depicts various elements/components of the NFT/blockchain service **250**. In this example, the NFT/blockchain service **250** includes an NFT ID engine **350** communicatively coupled with one or more app servers **320** and one or more database (DB) servers **330**. The server(s) **320**, **330**, and/or **350** operate distributed applications to provide the NFT/blockchain service **250** to client/wallet devices **310**. The server(s) **320**, **330**, and/or **350** may be located in one or more data centers (e.g., provided by a cloud computing service and/or the like), at the network's “edge”, and/or in some other arrangement or configuration. One or more of the servers **320**, **330**, and/or **350** may be virtual machines (VMs) or other isolated user-space instances provided by a cloud computing service, edge computing service, and/or the like. Furthermore, some or all of the server(s) **320**, **330**, and/or **350** may also provide various administration capabilities to support the various aspects discussed herein. In various implementations, the servers **320**, **330**, and/or **350** can be located at different geographic locations such as, for example, in different data centers, co-located with different network access nodes, and/or the like. In one example implementation, the infrastructure may include a full stack in the cloud, the servers **320**, **330**, and **350** implementing a suitable Linux distribution (distro), operating NGINX and/or Apache® web/app servers, where the server-side languages of the distributed apps are written using PHP, Python, JavaScript, and Solidity, and the DB systems (e.g., NFT ID DBs **340**) are implemented using MySQL, MongoDB, and InterPlanetary File System (IPFS).

(20) In some implementations, the server(s) **320** receive ID info (e.g., ID info **513** in FIG. 5) as inputs (e.g., inputs **401** in FIG. 4) via a front-end NFT ID portal (e.g., mobile app and/or website, not shown by FIGS. 2 and 3). The ID info may include, for example, physical or electronic ID documents and/or

other info such as contact info, authentication credentials, biometric data, and/or the like. In some implementations, physical IDs may be scanned in and uploaded by individual users (using their client/wallet **310**, **360**) to the server(s) **320** using a suitable user interface provided by the front-end NFT ID portal. This user interface can also be used to provide (upload) electronic documents/info to the server(s) **320**. Additionally or alternatively, the ID info can be provided to the server(s) **320** via third party web/mobile apps and/or Web2 apps using suitable APIs and/or the like. The term “user”, “individual”, “wallet”, “client”, “device”, “user device”, “administrator”, “admin”, and/or the like (in singular or plural form) may be used interchangeably throughout the present disclosure, and these terms may refer to one or more client applications, client devices (e.g., any of the client devices/systems **310**, **360**, **650**), and/or one or more users of the client applications and/or client devices.

(21) Web 2.0 platforms (“Web2” in FIG. 2) are websites and/or apps that emphasize user-generated content, ease of use, participatory culture and interoperability (i.e., compatibility with other products, systems, and devices) for end users (e.g., users **310**, **360**). A Web2 platform allows users (e.g., users **310**, **360**) to interact and collaborate with each other through, for example, social media dialogue as creators of user-generated content in a virtual community. Data and content are centralized in a relatively small group of companies sometimes referred to as “Big Tech”. Examples of Web2 platforms include social networking sites or social media platforms (e.g., Facebook®, Instagram®, Twitter®, and/or the like); blogs, wikis, and folksonomies (“tagging” keywords on websites and links); video sharing platforms (e.g., YouTube®, Vimeo®, TikTok®, and/or the like); image sharing platforms (e.g., Flickr®, Imgur®, and/or the like); hosted services; Web apps and mobile apps; collaborative consumption platforms; and mashup apps. Web 3.0 platforms (“Web3” in FIG. 2) represent a new iteration of the World Wide Web based upon blockchain technologies, which incorporates concepts including decentralization and token-based economics. Web3 platforms usually revolve around the idea of decentralization and often incorporate blockchain technologies, such as various cryptocurrencies and NFTs.

(22) The received ID info may be provided to the DB servers **330**, which may store the data in the NFT ID DB(s) **340** for temporary and/or persistent storage. The DB(s) **340** can be any suitable relational and/or non-relational DB(s) stored by one or more suitable data storage devices. The DB servers **330** may also be configurable to destroy the stored info within a predefined or configurable period of time (e.g., by deleting such info from the DB(s) **340**). In some implementations, the servers **320**, **330**, and/or **350** can also be configurable or operable to generate reports and statistics to authorized recipients upon request. In embodiments, the received ID info is provided to the NFT ID engine **350** for generation of suitable NFT IDs according to the various embodiments discussed herein.

(23) The NFT ID engine **350** is an adaptable and multipurpose software and/or hardware element that generates an NFT-based form of digitized/tokenized ID, using blockchain technology, smart contracts, distributed ledgers, digital wallets **310**, and/or identity data (e.g., identity documents, personal info, biometric data, and/or the like). In some implementations, the NFT ID engine **350** is an application operated by one or more computing devices such as one or more servers (e.g., a cluster of cloud compute nodes, one or more edge compute nodes, and/or the like). Additionally or alternatively, the NFT ID engine **350** may be a distributed application operated by multiple app servers **320**. Additionally or alternatively, the NFT ID engine **350** may be a special-purpose hardware device or a collection of special-purpose hardware devices that are accessible by the app servers **320**.

(24) The NFT ID engine **350** accepts inputs (e.g., inputs **401** in FIG. 4) from any number of sources, processes the inputs, and produces NFT IDs (e.g., outputs **402** in FIG. 4) that can be used on Web2 and/or Web3 platforms (see e.g., FIG. 2), and/or carried by individuals via digital wallets **310**. In various implementations, the NFT ID engine **350** can take any form of physical ID, digital ID, and/or other info, process them in complex ways as defined by the users (e.g., users **310**, **360**), and generate and output an NFT ID form to be used in various applications (apps) such as Web2 and/or Web3 apps (see e.g., FIG. 2). The generated NFT IDs are then stored in the NFT ID DB(s) **340** via the DB

servers **330** in one or more distributed ledgers or blockchains (e.g., blockchains **415** in FIG. **4**).

(25) The term “blockchain” refers to a set of technologies that use cryptography to create secure linkages between records (referred to as “blocks”). A blockchain (e.g., a blockchain **415** in FIG. **4**) is a type of distributed DB that can record transactions in a public or private peer-to-peer network. Additionally or alternatively, a blockchain is a DB containing info (e.g., records of financial transactions and/or other transactions) that can be simultaneously used and shared within a large decentralized, publicly accessible network. Additionally or alternatively, a blockchain is a shared, immutable ledger that facilitates the process of recording transactions and tracking (tangible and intangible) assets in a network. A blockchain (or copies of the blockchain) can be distributed to some or all participants in a blockchain network. The participants in a blockchain network are referred to as “peers” or “nodes”. In some examples, the client device(s) **310**, **360**, server(s) **320**, **330**, **350**, and/or other compute nodes/devices (such as any of those discussed herein) may operate as blockchain nodes in a blockchain network.

(26) A blockchain includes a growing list of records (or a DB of transactions) that are linked together using some identifier and/or other like mechanism. This list of records/blocks may be referred to as a “ledger”. In the context of blockchain technologies, a “ledger” refers to a series of interconnected records or blocks (a “distributed ledger” is another term for a blockchain). The ledger is shared, replicated, and synchronized among nodes in a blockchain network. In some implementations, a blockchain has no central administrator or centralized data storage system. However, in other implementations a centralized system may be used to validate blocks or perform other functions. Most ledgers are used to track a specific type of info or transactions such as cryptocurrency, securities, asset tokens and/or NFTs, smart contracts, and/or the like.

(27) Typically, blocks are linked together using cryptography where each block contains a cryptographic hash of a previous block, a timestamp, and transaction data. In some implementations, the cryptographic hash of the previous block may act as a block identifier (ID) of the block, or the cryptographic hash of the block itself (including a hash of the previous block) may act as a block ID of the block. In some implementations, blocks may be encrypted to enhance security. The timestamp proves that the transaction data existed when the block was published in order to get into its hash.

(28) Because each block contains info about the block previous to it, a chain is formed with each additional block reinforcing the ones before it. This makes blockchains resistant to modification of their data because, once recorded, the data in any given block cannot be altered retroactively without altering all subsequent blocks. An advantage of using blockchain technology is that transactions performed on a blockchain are immutable, which means that the transactions cannot be changed or altered without permission from the network. This creates an accurate and nearly unchangeable record (or chain of records) that can be used to verify each transaction, such as each transfer of title or ownership, identity changes and/or changes/updates to identifying info, and/or the like. Publishing an update to an individual record can be done, but requires altering the cryptographic hash that was generated as the record was created, and any records added to the ledger after an altered record must be re-validated and re-added to the ledger (also with updated hashes). In a blockchain, a change to a record's value is typically published as a new ledger entry. When this single blockchain is connected to some kind of network that can handle communication between nodes and provide an agreed upon system for each node to verify changes to network data, then an individual blockchain can be replicated across different nodes in the network. This replication creates multiple blockchain ledgers, containing identical records that have been independently verified. In these ways, a blockchain provides immutability for the transactions that are tracked.

(29) Example info that may be included in a block includes a timestamp (e.g., the time when the block was mined or created), a block number (e.g., the length of the blockchain in number of blocks), fee per gas or gas price (e.g., the minimum fee per gas required for a transaction to be included in the block), difficulty (e.g., the effort required to mine the block), mix hash (e.g., a unique identifier for the block), parent hash (e.g., a unique identifier for the block that came before (i.e., the previous block or the top-most block)), transaction data (e.g., the transaction included in the block (e.g., inputs

401 in FIG. 4)), state root (e.g., the entire state of the system including, for example, account balances, contract storage, contract code, account nonces, identity documents and/or identity data, and/or the like), and a nonce (e.g., a hash that, when combined with the mix hash, proves that the block has gone through a consensus (e.g., proof-of-work, proof-of-stake, and/or the like)). Additional or alternative info may be included in a block in other implementations.

(30) Blockchains can be managed by a peer-to-peer network for use as a publicly distributed ledger, where nodes collectively adhere to a protocol to communicate and validate new blocks. These blockchains are referred to as “public blockchains”. Public blockchains are permission-less by nature, allowing most users to join, and are usually decentralized (e.g., stored and updated by multiple compute nodes). By contrast, a private blockchain is a blockchain network where only one or a few authorities or organizations have control over the blockchain network including, for example, rules and/or policies for adding new blocks to the blockchain and/or the like.

(31) A non-fungible token (NFT) is a unique and non-interchangeable unit of data stored on a blockchain. NFTs use a digital ledger to provide a public certificate of authenticity or proof of ownership, but do not restrict the sharing or copying of the underlying digital files. The lack of interchangeability (fungibility) distinguishes NFTs from blockchain cryptocurrencies, such as Bitcoin, Ethereum, and/or the like. The mapping from original data to a token uses methods which render tokens infeasible to reverse in the absence of the tokenization system, for example, using tokens created from random numbers. Tokenization systems provide data processing applications with the authority and interfaces to request tokens, or detokenize back to sensitive data. NFTs can be associated with reproducible digital files such as photos, videos, and audio.

(32) As mentioned previously, the NFT IDs generated by the NFT ID engine **350** can be stored in a client wallet **310** (also referred to as a “digital wallet **310**”, “cryptocurrency wallet **310**”, “wallet device **310**”, “wallet **310**”, and/or the like). The wallet **310** is a device, physical medium, program, software engine, and/or a service that stores a user's credentials (e.g., cryptographic private keys and/or public keys, digital certificates, and/or the like) for completing transactions such as cryptocurrency and/or other blockchain-related transactions. In some implementations, the wallet **310** may be, or part of, a software element, such as a mobile payment app operated by a user device (e.g., Apple Pay®, Google Pay®, PayPal®, Venmo®, and/or the like).

(33) In some implementations, the user device **310**, **360** is a mobile device, such as a laptop, smartphone, tablet, wearable device (e.g., smartwatch and/or the like), virtual reality (VR)/augmented reality (AR) headset, and/or the like, or any other suitable computing device, such as any of those discussed herein. In these implementations, the wallet **310** may be a platform-specific app (e.g., iOS® app, Android® app, and/or the like). In other implementations, the wallet **310** is a standalone hardware device such as the Ledger Nano X™ provided by Ledger SAS®, the YubiHSM2™ provided by Yubico®, the Trezor Model T® provided by SatoshiLabs S.R.O., and/or the like. In these implementations, the standalone hardware device may be specifically designed to operate as a wallet device, or may be designed as a secure element (e.g., a hardware authentication device, security token, and/or the like). Additionally or alternatively, the wallet **310** is a secure element within a larger computing system such as, for example, a trusted platform module (TPM), a secure cryptoprocessor, software and/or hardware-based secure enclaves, a trusted execution environment (TEE) (see e.g., TEE **609** in FIG. 6), a protected location, and/or the like. Additionally or alternatively, the wallet **310** may be a “hot wallet” (e.g., a wallet that stores the user credentials, a network-connected application, and/or the like) or a “cold wallet” (e.g., a wallet that stores the user credentials offline and/or disconnected from the internet or other network).

(34) In various implementations, the user credentials are associated with a state of a user's account in a blockchain-based framework. The wallet **310** allows the user to make transactions, where the public key of the public/private key pair allows other wallets to make payments to the wallet **310** (e.g., using the wallet's **310** network address, app/wallet identifier, and/or the like) and the private key of the public/private key pair allows the wallet **310** spend currency or cryptocurrency stored by the wallet **310** and/or in the blockchain. In addition to this basic function of storing the keys, the wallet **310** also

offers the functionality of encrypting and/or digitally signing info or electronic documents. Signing can for example result in executing a smart contract, a cryptocurrency transaction, identification process, legally signing a document, and/or the like.

(35) Additionally, an administrator (admin) that operates the admin wallet **360** (also referred to as “admin **360**”) associated with an org/entity defines the requirements and functions of each NFT ID type. The admin **360** may be the same or similar as the client **310**, but is operated by a user having administrator privileges. For example, the admin **360** may represent a client app, client device, and/or any other type of app or device/system, such as any of those discussed herein. In some implementations, the admin **360** is involved in the creation of the NFT IDs by coding, compiling, deploying, and running a smart contract in/at the NFT ID engine **350**. Additionally or alternatively, the admin **360** gathers info provided by individual users, encrypts the info, and then uploads the info to the NFT/blockchain service **250**. In some implementations, the admin **360** uploads the info to a distributed file system and/or a private data storage server (e.g., file system microservice **414** in FIG. **4** and file system **560** in FIG. **5** via the NFT ID engine **350**). In some examples, the distributed file system is implemented using [IPFS]. The admin **360** uses a client/wallet device **360**, which may be the same or similar as the wallet **310**, or may be (or access) a different admin portal/interface. In addition to the aspects discussed previously with respect to (w.r.t) the wallet **310**, the wallet **360** may also perform monitoring and/or housekeeping functionality.

(36) Furthermore, the wallets **310**, **360** implement a wallet interface with the NFT/blockchain service **250** in order to provide inputs (e.g., inputs **401** in FIG. **4**) to the NFT/blockchain service **250**, and to accept outputs (e.g., NFT IDs/outputs **402** in FIG. **4**) such as accepting transfers and/or the like. This wallet interface may be the aforementioned NFT ID front-end portal or some other interface.

(37) FIG. **4** depicts an example implementation of the NFT ID engine **350**. The NFT ID engine **350** is or includes one or more multi-use applications that include multiple microservices and business logic. In this example, the microservices of the NFT ID engine **350** include a smart contracts engine (SCE) **410**, one or more smart contracts **411**, authentication engine **412**, metadata **413**, file system microservice **414**, one or more blockchains **415**, issuance microservice **416**, transaction content **417**, on-chain microservice **418**, off-chain microservice **419**, and minting engine **420**. Although the example of FIG. **4** shows the NFT ID framework **403** as being a separate entity than the NFT engine **350**, in other implementations, the NFT ID framework **403** is an element or component of the NFT engine **350** or the NFT engine **350** is an element or component of the NFT ID framework **403**.

(38) As alluded to previously, the NFT ID engine **350** accepts various inputs **401** (e.g., the ID info **513** and/or other info/data discussed herein), performs various operations (e.g., using the microservices **411-420**), and produces NFT ID(s) as outputs **402** (also referred to herein as “NFT IDs **402**” and/or the like). The inputs **401** may include various identity documents (e.g., electronic identity documents and/or physical identity documents scanned in or otherwise transformed into electronic form) and/or other data associated with a particular individual or user. Additionally or alternatively, the inputs **401** may include user-supplied/provided PII such as, for example, name, physical home address, physical employment address, phone number, email address, social media profile data, medical data (e.g., electronic health records (EHRs), lab test results, vaccination records, and/or the like), KYC data, KBA data, and/or any other PII. Additionally or alternatively, the inputs **401** may include other info related to a user such as, for example, rental agreements, mortgage statements, utility bills, cell phone service bills, and/or other financial instruments and/or financial institution documents. Additionally or alternatively, the web/app interface may request other info to be provided by the user such as biometric data and/or the like.

(39) Additionally or alternatively, the inputs **401** may include other info collected from the user device such as any type or combination of: a user ID (userId) associated with the user **310**, **360**, timestamp of when the NFT/blockchain service **250** is accessed, geolocation info associated with the user's access of the NFT/blockchain service **250**, digital certificate(s), client app data, service provider platform (SPP) data, device/system info, network-related data, and/or any other like data/info with a particular user **310**, **360** or user/wallet devices **310**, **360**. Examples of the client app

data include client app ID, client app type (e.g., browser, wallet/payment app, web app, native app, and/or the like), client app version, client app vendor, client app session ID, user agent string, and/or the like. Examples of the SPP data includes SPP account data (e.g., social media profile URL and other relevant data), login user name or credentials for accessing the SPP, SPP session ID, SPP session time, and/or the like. Examples of the device/system include info (e.g., operating system (OS) type and/or version, OS vendor, a network session ID, a device ID (e.g., serial number, product ID, EPC, RFID tag, and/or the like), Unix-like OS assigned ID (e.g., effective user ID (euid), file system user ID (fsuid), saved user id (suid), real user id (ruid), and/or the like), device fingerprint of a user/wallet device **310, 360**, hardware and/or software configuration info, and/or the like. Examples of the network-related data include network address(es) associated with the client device **310, 360**, session ID, cookie IDs, realm name, domain name, network credentials (e.g., SIM card info and/or the like), and/or the like. Some or all of the aforementioned info may be collected by program code/script embedded in webpages/web apps of the NFT ID front-end portal, which when executed by the user device **310, 360**, causes the user device to collect such data and send it to the NFT/blockchain service **250** as inputs **401**. Additionally or alternatively, sensitive data and/or confidential info may be collected. The personal, sensitive, and/or confidential data can be anonymized and/or pseudonymized or otherwise de-identified using suitable anonymization and/or pseudonymization technique(s).

(40) The particular types of inputs **401** used may be specified or configured by an admin **360** associated with a particular platform, agency, org, or other entity. In some implementations, individual users **310, 360** provide the inputs **401** to the NFT/blockchain service **250** (e.g., using their client/user devices). Additionally or alternatively, an admin **360** collects the necessary, relevant, and/or predefined info and provides the info as inputs **401** to the NFT/blockchain service **250** (e.g., using their client/user devices and/or a specialized/secure admin portal). Additionally or alternatively, a configuration (or smart contract **411**) can specify that a first set of inputs **401** are to be provided by users **310** and a second set of inputs **401** are to be provided by an admin **360**. For example, the first set of inputs **401** provided by a user **310** can include scanned identity documents (e.g., driver's license, passport, and/or the like), biometric data, and/or other identity data/info (e.g., KYC data, KBA data, social media profile, and/or the like), and the admin **360** may be required to provide a second set of inputs **401** including org-specific codes or electronic documents (e.g., password, digital certificate, and/or the like).

(41) In a first example implementation, the inputs **401** include government-issued and/or government-approved physical identity documents, and the NFT ID engine **350** produces identify-proofed NFT IDs **402**. In one implementation, the identify-proofed NFT IDs **402** are government forms of identification in NFT format. Additionally or alternatively, the identify-proofed NFT IDs **402** can be loaded onto a smart card that is also used as a governmental identity card/document. In this example implementation, the particular inputs **401** used to create the NFT IDs **402** may be defined by the relevant agency, regulatory body, and/or other government sector **202** org. Here, different government sector **202** orgs may define or require different types and/or combinations of inputs **401** that are needed to produce an NFT ID **402** for their org (e.g., the U.S. Central Intelligence Agency may require more and/or different types of inputs **401** than those defined for various offices of the U.S. Department of Commerce).

(42) In a second example implementation, the inputs **401** include identity documents and/or other info/data as defined by an NGO sector **204** entity such as non-profit orgs (e.g., schools, religious orgs, and/or the like), for-profit orgs (e.g., corporations, LLCs, and/or the like), and/or the like. The info and usage model for each NGO NFT ID **402** is decided by the users **310** and/or admins **360** of such orgs. In this example, the NFT ID engine **350** generates NGO/commercial NFT IDs from the accepted inputs. In one example, the NGO/commercial NFT IDs **402** generated by the NFT ID engine **350** may be access credentials in NFT format that are used to access computing systems, physical buildings, and/or specific areas of an enterprise.

(43) In a third example implementation, the inputs to the NFT ID engine **350** include social media

handles, channel IDs, and/or the like, and the NFT ID engine **350** produces social NFT IDs **402** that can be used by various social media users **310, 360** (e.g., influencers, content creators, followers/viewers, and/or the like) across multiple platforms. These social NFT IDs **402**, and the inputs **401** used to generate the social NFT IDs **402**, may be defined by individual social media platforms (e.g., social media sector **206**), or may be standardized by the NFT/blockchain service **250** itself. In the new “work from home”/remote work environment, the social NFT IDs **402** allow people to work, interact, and consume content virtually and remotely. The social NFT IDs **402** are not dependent upon—and are independent of—any particular social media platform and can be used for any and all social media platforms and/or other (non-social media) platforms. In some implementations, individual users **310, 360** can create more than one social NFT ID **402** for themselves. The social NFT IDs enable individuals to protect their online creations and brands on various social platforms (e.g., YouTube®, Twitter®, Instagram®, TikTok®, and/or the like) and/or verify their identities in virtual reality (VR) environments (e.g., Metaverse® and/or the like) and Web3 platforms. Presently, social media platforms can pause, freeze, suspend, or cancel long-established accounts, thereby destroying users' **310, 360** social capital built into those accounts. The social NFT IDs allow users **310, 360** to seamlessly transfer, transport, export, move or otherwise use their online personas to/with alternative platforms regardless of whether their account is shut down by a single social media platform.

(44) In addition to or alternatively to identity documents, other data may be provided as inputs **401** such as, for example, user generated text, images, video, audio content, and/or other like data. In some implementations, biometric analysis and/or processing may be incorporated into the NFT ID generation process (e.g., including biometrics being provided as inputs **401**). The biometric inputs **401** may include physiological biometrics (e.g., fingerprints, face/facial features, DNA, palm print, body part geometry, vein patterns, eye features, odor/scent, voice features or voiceprint, neural oscillations and/or brainwaves, pulse, electrocardiogram (ECG), pulse oximetry, and/or the like) and/or behavioral biometrics (or “behaviometrics”) (e.g., typing rhythm, gait, signature, behavioral profile features, voice features, and/or the like). In these implementations, the NFT ID engine **350** accepts one or more biometrics as inputs **401**, which are then combined together (and/or with other inputs **401**) and hashed. This hash will then become part of a smart contract **411** (e.g., as generated and/or operated by the smart contracts engine **410**) to generate NFT IDs **402** where use of biometrics is/are desired (e.g., identify-proofed NFT IDs **402**, NGO/commercial NFT IDs **402**, and/or social NFT IDs **402**).

(45) The authentication engine **412** is a microservice that authenticates individual users **310, 360** that submit or otherwise provide inputs **401** to the NFT ID engine **350**. In some implementations, individuals **310, 360** register or enroll with the NFT/blockchain service **250** by providing ID info as inputs **401** to the NFT/blockchain service **250**. This ID info may be the same or similar as the ID info **513** discussed infra w.r.t FIG. 5. A user interface and/or suitable client app operated by a user/client device (e.g., wallet devices **310, 360**) is used to provide the ID info is provided to the NFT/blockchain service **250**. For example, a web/app interface may be provided to the user system and/or wallet devices **310, 360** to access a web/app server **320** to provide the info to the NFT ID engine **350**, which is then stored by the DB server(s) **330** in NFT ID DB **340**. This web/app interface may include form fields for users **310, 360** to enter various ID info, PII, KYC/KBA data, and/or other info/data, an upload component for users **310, 360** to upload content (e.g., electronic ID documents, and/or the like); client-side code and/or web components that allow users **310, 360** to access content from cloud storage services (e.g., via APIs and/or SDKs provided by cloud storage providers); and/or other components and/or control elements. Additionally or alternatively, client-side script, tags, program code, and/or the like may be included in the NFT ID front-end portal/interface that collects some of the ID info/inputs **401** from the user **310, 360** when accessed by the user/wallet devices **310, 360**. The info used for authentication may be the same or similar to the ID info/inputs **401** used to create the NFT IDs **402** and/or may be a subset of the ID info/inputs **401**. In some implementations, the authentication engine **412** may verify the ID info/inputs **401** against authoritative sources (e.g.,

credit bureaus, government database(s), corporate database(s), and/or the like). Additionally or alternatively, the authentication engine **412** authenticates a user's **310, 360** identity using authentication or authorization credentials, biometric data, and/or knowledge-based authentication (KBA) data. The authentication engine **412** also provides access control to restrict what accounts can mint items, including defining and enforcing ownership and role-based access schemes (see e.g., [OZContracts]). Additionally or alternatively, the authentication engine **412** authenticates a user's **310, 360** identity using third party identity verification services, in which case the authentication engine **412** can communicate with the third party identity verification service via suitable APIs and/or the like.

(46) The NFT IDs **402** and/or other tokens may be created (or “minted” in the parlance of the NFT arts) by the minting engine **420**. Various aspects of the minting engine **420** are discussed in more detail infra. The minting process may be governed, controlled, or otherwise based on one or more smart contracts **411**. In some implementations, individual smart contracts **411** are generated by the SCE **410** according to corresponding configurations, which may be developed or otherwise provided by admins **360**. A configuration may be a collection or set of policies, rules (or rule sets), templates, definitions, schemas, parameters, criteria, conditions, data, settings, preferences, options, and/or other data structures that define aspects of NFT IDs **402** for an org and/or how such NFT IDs **402** should be minted or created. For example, a configuration may dictate or specify the specific types of inputs **401** that are to be provided by individual users **310** for minting an NFT ID **402**, specific types of inputs **401** that are to be provided by individual admins **360** for minting an NFT ID **402** for individual users **310**, network addresses (or address ranges) and/or domains that are permitted to mint NFT IDs **402** for the org, apps and/or wallets that are permitted to be used to mint/create NFT IDs **402**, device/system types that are permitted to be used to mint/create NFT IDs **402**, content types and/or formats of the inputs **401**, cryptographic mechanisms (e.g., encryption standards, hash functions, and/or the like) to be used for the inputs **401** and/or outputs **402**, content type(s) and/or data/file formats of the minted NFT IDs **402**, arrangement of graphical elements (or “style”) of the NFT IDs **402** (or the identity data structure used to mint the NFT IDs **402**), a location or location range (e.g., Uniform Resource Identifier (URI), Uniform Resource Locator (URL), Persistent URL (PURL), Uniform Resource Name (URN), Digital Object Identifier (DOI), magnet link, IPFS content address, file path, and/or the like) for storing metadata **413**, a location or location range (e.g., URI, URL, PURL, URN, DOI, magnet link, IPFS content address, file path, and/or the like) for storing minted NFT IDs **402**, parameters and/or criteria for transferring NFT IDs **402** to owners, a list of verification nodes, parameters and/or criteria for blockchain nodes to act as verification nodes, and/or other criteria and/or parameters. The specific parameters, criteria, conditions, data, and/or other data structures defined or specified by a configuration may be based on an org's InfoSec policies, regulatory and/or auditing policies, access control lists (ACLs), and/or any other preferences, and as such, each configuration may be org-specific and/or may vary based on design choices and/or use cases. Any suitable programming languages, markup languages, schema languages, and/or the like, may be used to define individual policies **137** and instantiate instances of those policies **137**. As examples, the policies **137** may be defined using Abstract Syntax Notation One (ASN.1), Apache® Thrift™, Apex®, Capirca™, CUE, IFTTT (“If This Then That”), Human-Optimized Config Object Notation (HOCON), HTML, INI, JSON, Markdown, MessagePack, Nettle, PADS/ML, Protocol Buffers (protobuf), TOML, XML, YAML, [Solidity], [OZContracts], [Flow], [Cadence], [Vyper], [Yul+], and/or some other suitable language and/or data format, such as those discussed herein. In some implementations, a suitable integrated development environment (IDE) or software development environment may be used to define and generate the configurations used by the SCE **410** to generate and deploy the smart contracts **411**. Additionally or alternatively, a suitable web-based interface can be provided by the NFT/blockchain service **250** that allows admins **360** to create and submit their configurations for generating NFT IDs **402**. In some implementations, a configuration may be a smart contract **411** pushed or otherwise deployed to one or more blockchains **415**. In these implementations, the smart contract **411** acting as a configuration may be used to

generate a different smart contract **411** used to generate or mint NFT IDs **402**.

(47) The SCE **410** may be or implement any suitable smart contract mechanism (see e.g., [Solidity], [OZContracts], [Flow], [Cadence], [Vyper], [Yul+], and/or the like) to generate and/or execute smart contracts **411**. In some implementations, the SCE **410** includes or provides runtime environment(s) in which smart contracts **411** can be executed. During operation, the SCE **410** combines one or more inputs **401** (e.g., as specified by a suitable configuration and/or the like) and hashes the combined inputs **401**. The hash will then become part of a smart contract **411** (e.g., as generated and/or operated by the SCE **411**), which are then executed by the minting engine **420** to generate corresponding NFT IDs **402**.

(48) Smart contracts **411** are reusable snippets of code (e.g., computer programs, scripts, applications, set of trigger functions, transaction protocol, and/or the like) that are intended to automatically execute, control, or document relevant events and actions according to some predefined criteria or conditions. Smart contracts **411** can be executed by nodes in a blockchain network (e.g., any of the compute nodes discussed herein) to digitally facilitate, verify, and/or enforce the negotiation or performance of a contract, which may be made partially or fully self-executing and/or self-enforcing. In these ways, smart contracts **411** can implement contracts between parties, where the execution is guaranteed and auditable.

(49) Typically, smart contracts **411** include one or more functions that take relevant, desired, predefined, and/or configured data/inputs **401** as arguments and assign it/them to appropriate variables. As examples, the data/inputs **401** can include unique IDs, content items, metadata, ID documents, identity data, and/or any other relevant data structures, variables, parameters, and/or the like. Smart contracts **411** can also include transfer logic for transferring corresponding assets, such as cryptocurrency and/or an NFT ID **402**. This typically involves defining one or more functions that take a new owner's address as an argument and updates the contract's internal state to reflect the transfer. Additionally or alternatively, the smart contracts **411** can include logic for calculating and distributing royalties, which may include one or more functions defined to obtain a sale price as an argument and uses it to calculate the royalty payment. In some implementations, the smart contracts **411** specify unique identity-based digital asset ownership elements. Additionally or alternatively, the smart contracts **411** specify transaction(s) or transaction type(s) that can be used to mint (generate), purchase, or otherwise obtain/transfer a corresponding NFT ID **402**. The specific syntax and/or code of a smart contract **411** may depend on the specific language being used and/or the platform on which the smart contract **411** is to be deployed.

(50) Smart contracts **411** can be written in higher-level programming languages and compiled to smart contract-specific bytecode. The higher-level programming languages may be a smart contract-specific language such as, for example, Ethereum® Virtual Machine (EVM) bytecode, [Solidity], [Vyper] (Python derived), [Yul+], Bamboo, Lisp Like Language (LLL), C++ for EOS.IO, Simplicity provided by Blockstream™, Rholang, Michelson, Counterfactual, Plasma, Plutus, Sophia, EOS.IO, [Cadence], and/or the like, or may be any of the other programming languages discussed herein, and/or combination(s) thereof. Once a smart contract is written/developed and compiled, it can then be deployed to one or more blockchains via a suitable interface. Once deployed, one or more blockchain nodes in a blockchain network can execute or run the smart contract code.

(51) Each smart contract **411** includes a set of rules that govern what happens whenever an interaction with an NFT ID **402** takes place. Each NFT ID **402** is associated with a smart contract **411** which includes functions of the NFT ID **402** that allow applications to interact with it. Every time a transaction is made on the NFT ID **402**, the code of the smart contract **411** checks for certain conditions and executes relevant actions. This transaction is then stored as transaction content **417**. For example, when an NFT ID **402** is requested by an entity that wishes to verify an individual's identity, the smart contract **411** will update and/or manage relevant permissions, and execute a transaction when permitted by the owner of the NFT ID **402**. Some smart contracts **411** determine whether nodes, accounts, and/or platforms can access, or perform specific actions on or using a particular NFT ID **402**, or on a particular blockchain **415** (see e.g., discussion of permissioning smart

contract in [EEA-CS7]). In some implementations, when an NFT ID **402** is used to verify an account holder's identity, the corresponding smart contract **411** can automatically allocate payments or asset transfers to the owner of the NFT ID **402** based on the rates set and/or other conditions in the smart contract **411** when the NFT ID **402** was created or updated.

(52) In some implementations, a smart contract **411** comprises a collection of code (e.g., its functions) and data (e.g., its state) that resides at a specific address on a blockchain. In Ethereum implementations, a developer publishes smart contract code into Ethereum Virtual Machine (EVM) memory. EVM is a global virtual computer whose state every participant on the Ethereum network stores and agrees on. Ethereum participants can request the execution of arbitrary code on the EVM, and code execution changes the state of the EVM. Individuals (e.g., wallet devices **310** and/or **360**) can request smart contract code be executed by making a transaction request. An example smart contract is shown by Table 1.

(53) TABLE-US-00001 TABLE 1 example pseudocode for a smart contract //SPDX-License-Identifier: MIT pragma solidity {circumflex over ()}0.7.0; import "hardhat/console.sol"; import "@openzeppelin/contracts/token/ERC721/ERC721.sol"; import "@openzeppelin/contracts/utils/Counters.sol"; contract NFTMinter is ERC721 { using Counters for Counters.Counter; Counters.Counter private _tokenIds; constructor(string memory tokenName, string memory symbol) ERC721(tokenName, symbol) { _setBaseURI("ipfs://"); } function mintToken(address owner, string memory metadataURI) public returns (uint256) { tokenIds.increment(); uint256 id = _tokenIds.current(); _safeMint(owner, id); _setTokenURI(id, metadataURI); return id; } }

(54) In Table 1, the pragma directive is used to enable certain compiler features or checks (see e.g., [Solidity], [OZContracts]). The contract is a function that is similar to classes in object-oriented languages, which contains persistent data in state variables and functions that can modify these variables. Here, the contract is NFTMinter, which is set to be an ERC721 object where the ERC721 object is an implementation of [EIP-721]. The ERC721 object comprises a set of interfaces, contracts, and utilities that are all related to [EIP-721]. The constructor is a special function that is executed during the creation of the contract and cannot be called afterwards. In this case, the constructor sets the resource address or base URI (e.g., "ipfs://") based on the token name ("tokenName") and token symbol ("symbol"). In some implementations, the token name and token symbol are concatenated to generate the resource address or base URI. In some implementations, after the constructor has executed, the final code of the contract is stored on the blockchain **415**.

(55) The token name in Table 1 is a human-readable name of the token (or type of token) being generated. In some implementations, a generic token name may be used for the NFT IDs **402** (e.g., "NFT-ID" and/or the like). Additionally or alternatively, the token name may include a name of the particular sector for which the NFT is created (e.g., government sector **202**, NGO sector **204**, social media sector **206**, and/or the like), a particular platform type for which the NFT ID **402** is created (e.g., social media platform, ecommerce platform, Web2, Web3, or other platform types), and/or a specific org for which the NFT ID **402** is created (e.g., a specific platform, enterprise, company, government agency or regulatory body, and/or the like).

(56) The token symbol usually refers to the currency symbol (or currency sign) used to represent a currency (e.g., the symbol "custom character" representing U.S. dollars, the symbol "custom character" representing Yen, the symbol "custom character" representing Bitcoin, the symbol "custom character" representing Ether, and/or the like). In some implementations, such as when an NFT ID **402** is a government NFT ID **402**, the symbols used for NFT IDs **402** may be based on the jurisdiction for which the NFT ID **402** is created (e.g., a two or three character country codes or geocodes as defined by ISO 3166-1:2020 and/or ISO 3166-2:2020, currency codes such as those defined by ISO 4217:2015, ITU letter codes, international telephone country codes, mobile country codes (MCCs), and/or the like). Additionally or alternatively, when an NFT ID **402** is an NGO/commercial NFT IDs, the symbols used for NFT IDs **402** may be based on an abbreviation or acronym of the org/entity, a ticker or stock symbol of the org/entity, and/or some other symbol as

defined by the entity or org. Additionally or alternatively, a generic symbol may be used or the symbol may be omitted.

(57) In some implementations, the smart contracts **411** may be part of one or more decentralized apps (Dapps), which are apps running on a decentralized peer-to-peer network, often a blockchain **415**. A DApp may include a user interface running on another (centralized or decentralized) system and may include decentralized storage and/or a message protocol and platform. In these implementations, a DApp may be a web user interface and a smart contract **411**.

(58) Furthermore, the SCE **410** and minting engine **420** may implement a suitable NFT framework **403**, such as the Ethereum® platform (e.g., as discussed in [EIP-20], [EIP-165], [EIP-173], [EIP-721], [EIP-777], [EIP-1155], [EIP-3525], [EIP-5528], [EIP-5679], [EIP-5727], [EthereumDoc], [EEA-CS7], and/or the like), Ethereum® Immutable X platform, Polygon (formerly known as Matic Network), the Flow blockchain (see e.g., [Flow] and/or [Flow-NFT]), Bitcoin Cash, Cardano, and/or the like.

(59) The metadata **413** may include any data about individual NFT IDs **402** such as, for example, NFT type and/or data identifying an asset/object to which the NFT represents (e.g., a particular type of ID that the NFT ID **402** represents), approval identities/entities, owners of an individual NFT IDs **402**, an org associated with the NFT ID **402** (e.g., an issuer of the NFT ID **402**), transferor ID (e.g., someone to which the NFT ID **402** is transferred, a description of the asset/object to which the NFT ID **402** represents (e.g., usage and/or permissions associated with the NFT ID **402**), a URI pointing to a resource with an image (e.g., a MIME type image) representing the asset to which the NFT ID **402** represents, and/or other like metadata. In some implementations, the metadata **413** can reside on one or more blockchains **415**, which may be stored in the NFT ID DB(s) **340**. In other implementations, the metadata **413** is stored off-chain when a token URI includes the resource/location of the metadata **413**, which may be stored either on a centralized server or in or at a file system location (e.g., an IPFS location/content address, which may be indicated by a content identifier (CID) and/or another label used to point to material in IPFS).

(60) The file system microservice **414** may include APIs (e.g., API(s) **555** of FIG. 5) and/or functions to access data stored in a file system (e.g., file system **560** of FIG. 5). As an example, the file system **560** is implemented using [IPFS] and the file system microservice **414** is an IPFS microservice. In another example, the file system **560** is implemented using one or more private data storage devices and/or storage servers and the file system microservice **414** includes one or more file access and/or transfer mechanisms and/or protocols, such as any of those discussed herein. Additionally or alternatively, the file system microservice **414** includes an update feature, where an ID history can be updated without touching the original data. In these implementations, the update procedure may include reading or otherwise accessing current metadata from the file system **560**; updating the metadata **413** with new data entry/entries (e.g., new ID info **513**); adding new metadata **413** to the file system **560**; and updating content hash on one or more smart contracts **411**.

(61) The minted NFT IDs **402** may be stored in one or more blockchains **415**. Some or all of the blockchains **415** may be private blockchains **415** and/or some or all of the blockchains **415** may be public blockchains **415**. In some implementations, individual blockchains **415** are owned or are otherwise associated with a particular org or sector. For example, a blockchain **415** owned or otherwise corresponding to a State's Department of Motor Vehicles (DMV) may include blocks for respective driver's license NFTs **402**. In other implementations, individual blockchains **415** are owned or are otherwise associated with an individual, where each block corresponds to minted NFT ID **402** for that person, and new blocks are added whenever the NFT ID **402** is updated with new or alternative ID info **513**.

(62) The transaction content **417** (also referred to as “transaction data **417**”, “transaction parameters **417**”, and/or the like) includes content or data associated with transactions involving the minted NFT IDs **402**. In general, a transaction **417** involves a request to execute operations on a blockchain **415** that changes the state of one or more accounts. More specifically, transaction content **417** may include data committed to a blockchain **415**, which may be signed by an originating account and

targeting a specific address. The transaction content **417** also contains metadata **413**. Some transaction content **417** may include a contract creation transaction, which is a special transaction **417** with a zero address (e.g., an address of all zeros, “0”) as the recipient, which is used to register a contract and record it on the blockchain **415**.

(63) The transaction content **417** include data and/or parameters that is/are passed to a smart contract **411** for minting an NFT ID **402**. In these implementations, the transaction content **417** can include, for example, a token ID for an NFT ID **402**, ownership info (e.g., info related to a user/wallet **310** that is a subject of the NFT ID **402**), a pointer or other reference (e.g., URI, URL, PURL, URN, DOI, magnet link, IPFS content address, file path, and/or the like) to metadata **413** that is to be used for minting the NFT ID **402**, and supply info (e.g., a number and/or type of NFT IDs **402** to be generated; usually 1 in most use cases). Additionally or alternatively, a transaction **417** can involve a transfer of ownership of an NFT ID **402** and/or a new/updated association of an NFT ID **402**. For example, a first transaction **417** of an NFT ID **402** can include issuing the NFT ID **402** to a user (e.g., user **501** in FIG. 5), a second transaction **417** of the NFT ID **402** can include associating the NFT ID **402** with a social media profile of a first social media network, a third transaction **417** of the NFT ID **402** can include associating the NFT ID **402** with a social media profile of a second social media network, a fourth transaction **417** of the NFT ID **402** can include associating the NFT ID **402** with a financial institution, and so forth. Each of these transactions **417** can be recorded as or in one or more blocks (or as respective blocks) in one or more blockchains **415**.

(64) Nodes processing transactions **417** is the basis of adding blocks to a blockchain **415**, and may be subject to the permissions defined in the corresponding smart contracts **411**. When mining new blocks, a processing node checks the validity of a transaction **417** using the appropriate smart contract **411** with the state at the block's parent. If not permitted, the transaction is discarded. If permitted, the transaction is included as a new block and the block is dispatched to other nodes (e.g., for inclusion in local versions of the blockchain **415**). When receiving a block, the receiving node checks each included transactions **417** using the appropriate smart contract **411** with the state at the block's parent. If any of the transactions **417** in the new block are not permitted, the block is considered invalid and discarded. If all transactions **417** are permitted, the block passes the permissioning validation check and is then subject to any other validity assessments the client **310**, **360** might usually perform.

(65) Transactions **417** can be on-chain transactions **418** or off-chain transactions **419**. On-chain transactions **418** (simply referred to as “transactions **418**” or “on-chain **418**”) are transactions that occur on a blockchain **415** that are reflected on the distributed ledger. On-chain transactions **418** are transactions that have been validated or authenticated and lead to an update to the overall blockchain network. An on-chain transaction **418** occurs and is considered valid when the blockchain **415** is modified. By contrast, an off-chain transaction **419** (simply referred to as “off-chain **419**”) takes the value outside of the blockchain **415** and/or transactions **417** that do not occur on the blockchain network, but instead, are transacted on another electronic system.

(66) The minting engine **420** is a microservice or facility that generates NFT IDs **402**. Similar to the way metal coins are minted and put into circulation, the NFT IDs **402** are also “minted” after they are created. The minting process turns the collection of inputs **401** into an NFT ID **402**. During the minting process, the owner of the NFT ID **402** can schedule reviews or identity verification using the NFT ID **402**. Once the NFT ID **402** is generated, the issuance microservice **416** issues or otherwise distributes the NFT ID **402** to the wallet **310** of the owner of the NFT ID **402**.

(67) Minting an NFT ID **402** involves the use of a smart contract **411** that is specifically designed to produce an NFT ID **402**. Here, the smart contract code defines the rules for the NFT ID **402**, and how the NFT ID **402** will be minted and transferred. Once the smart contract **411** is written or developed, the smart contract **411** is deployed to a blockchain **415**. This can be done using, for example, any of the programming languages, development tools, command line interface(s), and/or other suitable interface provided by the blockchain/NFT service **250**. Once the smart contract **411** is deployed, it can be used to mint one or more NFT IDs **402**. This may involve calling specific function(s) in the

smart contract **411** and passing data and/or parameters to the smart contract **411** for the NFT ID **402**. The exact steps for minting the NFT ID **402** may depend on aspects of the blockchain/NFT service **250**, the specific smart contract **411** (and/or functions therein), configuration data/parameters, and/or other conditions, parameters, and/or criteria. In some cases, minting an NFT ID **402** requires payment of transaction fees on a blockchain **415**, which may be in the form of fiat currency and/or cryptocurrency.

(68) In some implementations, the minted NFT ID **402** can include royalty payment mechanisms, which are also specified in the smart contract **411** that governs the NFT ID **402**. Here, the corresponding smart contract **411** is written to include the necessary logic for calculating and distributing royalties, including events or conditions to trigger the payments. In some examples, the royalty payment mechanism is or specifies a percentage of a sale price that is automatically paid to the NFT ID **402** owner each time the NFT ID **402** is transferred among third party platforms (e.g., among different social media platforms, service provider platforms, and/or the like). Other conditions, parameters, or criteria can be defined in such smart contracts **411**. When someone buys the minted NFT ID **402**, the smart contract **411** will automatically calculate the royalty payment and transfer that payment amount to the wallet **310** of the NFT ID **402** owner. In some cases, receiving royalties from an NFT ID **402** involves paying transaction fees on the blockchain **415**, which can be the same or similar as those discussed previously w.r.t to NFT minting and/or the like.

(69) In some implementations, the minted NFT ID **402** can include identity authentication verification, and/or validation mechanisms, which are also specified in the corresponding smart contract **411** that governs the NFT ID **402**. Here, the corresponding smart contract **411** is written to include the necessary logic for authenticating, verifying, and/or validating the NFT ID **402** owner's identity, such as for accessing a third party platforms (e.g., among different social media platforms, service provider platforms, and/or the like) and/or accessing specified resources. For example, the identity authentication mechanisms can indicate the manner in which (and the relevant data to be provided) to log into a website or third party platform. In another example, the identity authentication mechanisms can indicate permissions and/or resources (e.g., including virtual and physical resources) that the NFT ID **402** owner is permitted to access. In some examples, the identity authentication mechanisms specify data (e.g., timestamps, location data, and/or the like) that is automatically logged to a blockchain **415** each time the NFT ID **402** owner's identity is authenticated/verified/validated. Other conditions, parameters, or criteria can be defined in such smart contracts **411**. When someone attempts to access a platform and/or other resources using the minted NFT ID **402**, the smart contract **411** will automatically perform the specified authentication mechanisms, and log the transaction in the relevant blockchain(s) **415**.

(70) In some implementations, each NFT ID **402** is identified by a unique ID (UID) and/or token ID (tokenId) inside a smart contract **411**. This UID does not change for the life of the smart contract **411**. An attribute-value pair including the contract address and the tokenId is a globally unique and fully-qualified identifier for a specific asset on a blockchain **415**. Additionally or alternatively, the tokenId is a specific identifier used to uniquely identify a particular instance of a token (e.g., a specific NFT ID **402**). The UID may be any value or data structure that uniquely identifies an individual and/or their user devices **310**, **360**. In one example, the UID may be a randomly generated number or string, which may be generated using a suitable random number generator, pseudorandom number generators (PRNGS), and/or the like. Additionally or alternatively, the UID may be a version 4 Universally Unique Identifier (UUID) that is randomly generated according to Leach et al., "A Universally Unique Identifier (UUID) URN Namespace", Internet Engineering Task Force (IETF), Network Working Group, Request for Comments (RFC): 4122 (July 2005) ("[RFC4122]"), which is hereby incorporated by reference in its entirety. In one example implementation, the random UID is generated for an individual device **310**, **360** upon completing the registration process.

(71) Additionally or alternatively, the UID may be a hash value calculated from one or more inputs (which may or may not be unique to the individual/user devices **310**, **360**). In one example implementation, the UID may be generated using supplied identity data/info (or a portion thereof) as

an input to a suitable hash function (e.g., such as sha3 and/or any cryptographic mechanism discussed herein). For example, the UID may be a version 3 or 5 UUID that is generated according by hashing a namespace identifier and name using MD5 (UUID version 3) or SHA-1 (UUID version 5) as discussed in [RFC4122]. In another example, the UID may be generated using any suitable hash function and using any combination of PII and/or device or system info supplied by a user and/or extracted from the user devices **310, 360** during the NFT ID generation process.

(72) Additionally or alternatively, the UID may be a digital certificate supplied by a suitable certificate authority, or may be generated using the digital certificate (e.g., hashing the digital certificate). In another embodiment, the UID may be a specific identifier or may be generated using the specific identifier (e.g., as discussed previously). The specific identifier may be any suitable identifier associated with a user and/or user devices **310, 360**, associated with a network session, an application, an app session, an app instance, an app-generated identifier, and/or some other identifier (ID). The specific identifier may be a user ID or unique ID for a specific user on a specific client app (e.g., client app **655** of FIG. **6**) and/or a specific user devices **310, 360**. Additionally or alternatively, the user ID may be or include one or more of a uid (e.g., positive integer assigned to a user by a Unix-like OS), euid, fsuid, suid, ruid, a cookie ID, a realm name, domain ID, logon user name, network credentials, social media account name, user session ID, and/or any other like ID associated with a particular user devices **310, 360**. Additionally or alternatively, the specific identifier may be a device identifier such as a device ID, product ID/code, serial number of the user devices **310, 360**, a document of conformity (DoC), electronic product code (EPC), RFID tag, and/or the like. Additionally or alternatively, the specific identifier may be a network ID such as an international mobile subscriber identity (IMSI), internet protocol (IP) address, and/or some other suitable network address such as any of those discussed herein. Any of the aforementioned identifiers and/or info may be combined to produce the UID, and/or other info, such as any info discussed infra, may be used to produce the UID.

(73) Additionally or alternatively, the UID may be based on a device fingerprint of the user devices **310, 360**. The device fingerprint may be any info collected about the software and hardware of a computing device for the purpose of identification, which may or may not be incorporated into an identifier (e.g., the aforementioned UID and/or the like). In one example implementation, the device fingerprint may be based on system data, sensor data, and/or the like that is/are collected and combined using some known mechanism (e.g., a hash function and/or the like). In another example implementation, the device fingerprint may be the output of a physical unclonable function (PUF) implemented by a tamper-resistant chipset in the user devices **310, 360** (e.g., TEE **690** of FIG. **6** discussed infra). When a physical stimulus (e.g., electric impulse) is applied to the PUF, it may react in an unpredictable way due to the complex interaction of the stimulus with the physical microstructure of the PUF. This exact microstructure may depend on physical factors introduced during manufacture which may be unpredictable. The PUF outputs the device fingerprint that may serve as the UID. Any of the aforementioned embodiments/implementations may be combined and/or used to generate the NFT ID **402**.

(74) FIG. **5** depicts an example logical flow **500** for minting NFT IDs **402**. Process **500** begins at step **5.1** where a user **501** logs in to their wallet **310**. As mentioned previously, the wallet **310** could be an iOS app, Android app, a browser extension, a web app, a standalone hardware device, and/or the like.

(75) At step **5.2**, the smart contract **411** and/or minting process is triggered **510**. The smart contract **411** is inside and a part of the NFT ID engine **350**. The trigger **510** can cause the smart contract **411** inside of the NFT ID engine **350** to be executed, which kicks off the minting process. The admin **360** defines various requirements and functions of each NFT ID type, and creates it. The admin **360** can code, compile, deploy, and run the smart contract **411** within the NFT ID engine **350**. The power, flexibility, and multiuse functionality may come from proprietary coding used for generating such smart contracts **411**. Deployment scripts are also included at step **5.2**. The smart contracts **411** can be written in any suitable smart contract language (see e.g., [Solidity], [OZContracts], [Flow], [Cadence], [Vyper], [Yul+], and/or the like) and/or any other programming language and/or

development tool, including any of those discussed herein.

(76) At step 5.3a, the NFT ID engine 350 (or the minting engine 420) mints a new NFT ID 402 or causes a new NFT ID 402 to be minted. In some examples, execution of the smart contract 411 causes the new NFT ID 402 to be minted. For example, the smart contract 411 defines various rules and logic for creating/minting the NFT ID 402 and managing the minted NFT ID 402 on the blockchain 415. In some implementations, the smart contract 411 is deployed on the blockchain 415, which makes the smart contract 411 available to be executed by individuals who want to mint NFT IDs 402 (e.g., users 310). In some examples, the trigger 510 can include transaction data/parameters 417 for minting the NFT ID 402. In other examples, the trigger 510 can cause the NFT ID engine 350 to generate the transaction data/parameters 417 for minting the NFT ID 402. In either example, the transaction data/parameters 417 can include, for example, a token ID for the to-be-minted NFT ID 402, ownership info for the to-be-minted NFT ID 402 (e.g., info related to the user/wallet 310), pointer or other reference to metadata 413 (e.g., URI, URL, PURL, URN, DOI, magnet link, IPFS content address, file path, and/or the like to storage location of the metadata location 413), and supply info (e.g., number and type of NFT IDs 402 to be generated; usually 1 in most use cases). When the smart contract 411 receives the transaction data/parameters 417, the smart contract 411 checks that the required conditions are met (e.g., various conditions specified by the admin-provided configuration and/or within the smart contract 411 itself) and then triggers the minting/creation of the NFT ID 402.

(77) The NFT ID engine 350 triggers the minting/creation of the NFT ID 402 by interacting with the NFT framework 403 to mint the new NFT ID 402. For example, the smart contract 411 can request or instruct the NFT framework 403 to begin the minting process by sending transaction data/parameters 417 to the NFT framework 403 via suitable APIs. The NFT ID 402 can be minted or otherwise generated using any suitable technology or platform, and/or using any suitable minting techniques, such as those discussed in [EIP-20], [EIP-721], [EIP-998], [EIP-1155], [EIP-1559], [EIP-3525], [EIP-5375], [EIP-5528], [EIP-5679], [EIP-5727], [EthereumDoc], and/or other standards provided by Ethereum® (e.g., such as any of those discussed herein), Ethereum® Immutable X platform, Polygon, The Flow blockchain (see e.g., [Flow]), Bitcoin Cash, Cardano, and/or the like.

(78) To create a new NFT ID 402, at step 5.3b, the NFT ID engine 350 provides ID info 513 to a file system 560 via one or more APIs 555. In some examples, the admin 360 encrypts the ID info 513 and uploads the encrypted ID info 513 to the NFT ID engine 350. In another example, user 310 and/or admin 360 uploads the ID info 513 to the NFT ID engine 350, and the NFT ID engine 350 encrypts or anonymizes the ID info 513. In either of these examples, the NFT ID engine 350 provides the encrypted/anonymized ID info 513 to the file system 560 via the API(s) 555 when the trigger 510 is executed or otherwise detected at step 5.2.

(79) In some implementations, the APIs 555 (or the functions/methods of the APIs 555) are part of the file system microservice 414 discussed previously. As an example, the distributed file system 560 is implemented using IPFS (see e.g., [IPFS]) and the API(s) 555 is/are implemented using one or more IPFS APIs. In another example, the file system 560 is implemented using one or more private data storage devices and/or storage servers and the API(s) 555 is/are implemented using any suitable file transfer mechanisms and/or protocols, such as any of those discussed herein. Additionally or alternatively, the file system 560 is implemented by the DB server(s) 330. Step 5.3b also includes storing the ID info 513 as metadata 413, which is then provided to the NFT ID framework 403 based on the request to mint the NFT ID 402 (step 5.3a). In some examples, the NFT ID engine 350 translates or converts the ID info 513 into the metadata 413 prior to storing the metadata 413 in the file system 560, the API 555 calls cause the ID info 513 to be translated/converted into the metadata 413, or the file system 560 translates/converts the ID info 513 into the metadata 413. Any suitable translation and/or conversion technique or algorithm can be used to translate/convert the ID info 513 into the metadata 413.

(80) The ID info 513 includes identity data, PII, and/or other info associated with the user 310, and can include other info associated with the org for which the NFT ID is to be created. Examples of ID

info **513** that is submitted to, or collected by, the NFT ID engine **350** include driver's license, phone number, email address(es); social media handle(s); YouTube channel name or ID; work/school ID; residential, academic, and/or financial history and/or related documentations (e.g., these can be periodically updated if needed or desired); KYC and/or KBA data; biometric data; electronic health records; any other info the users **310**, **360** require; and/or any other info or data such as any of those discussed herein.

(81) In some examples, the ID info **513** is provided to the NFT ID engine **350** by the user **310** and/or the admin **360** (e.g., at step **5.1** and/or step **5.2**). Additionally or alternatively, the NFT ID engine **350** gathers some or all of the ID info **513** from one or more external sources (e.g., governmental databases, private or enterprise databases, social media networks, and/or the like). Additionally or alternatively, the NFT ID engine **350** encrypts the ID info **513** prior to, or concurrently with providing the ID info **513** to the distributed file system **560**. In any of these implementations, the ID info **513** is stored by the distributed file system **560** as metadata **413**. The metadata **413** is also provided to (or accessed by) the NFT framework **403** for the minting process. In some implementations, the ID info **513** and/or metadata **413** is not stored on the blockchain **415**. In these implementations, the metadata **413** is used to generate a data structure representing an identity of the user **310** (referred to as an "identity data structure"), and this data structure is then stored as a block in the block chain **415**. In some examples, the identity data structure is a graphical representation (e.g., a graphical or other digitized ID document). Additionally or alternatively, the identity data structure is an information object (InOb) including various data fields and data elements in a suitable data/file format, such as any of those discussed herein. Step **5.3a** may be performed before, after, or concurrently with step **5.3b**. Additionally or alternatively, a pointer or other reference that points to or otherwise refers to the metadata **413** in storage **560** is stored on the blockchain **415**.

(82) In response to the mint/read NFT ID command at step **5.3a**, the NFT ID framework **403** mints an NFT ID **402** using the metadata **413** as discussed previously. At step **5.4**, the minted NFT ID **402** is provided by the NFT ID framework **403** to the NFT ID engine **350**. In some implementations, at step **5.4**, a pointer or other reference (e.g., URI, URL, PURL, URN, DOI, magnet link, IPFS content address, file path, and/or the like) that points to the data (also called metadata **413**) is returned to the NFT ID engine **350**. In some implementations, the minting process stores the pointer or other reference to the metadata **413** inside the NFT ID **402**. Additionally or alternatively, the minted NFT ID **402** is recorded as a transaction **417** (e.g., as a block) on the blockchain **415**, and ownership of the minted NFT ID **402** is transferred to the owner specified in the transaction data **417** at step **5.5**.

(83) At step **5.5**, the minted NFT ID **402** is added to the admin wallet **360**. The newly minted NFT ID **402** initially belongs to whoever did (or requested) the actual minting, which in this example is the admin **360** (e.g., by sending the minting request/trigger at step **5.3a**). The NFT ID **402** is then transferred to the individual's wallet **310** during an issuance process at step **5.6**. The admin **360** issues the new NFT ID **402** by transferring the newly minted NFT ID **402** to the wallet **310** of the new ID holder **501** via the NFT ID engine **350** or using some API, web service (WS), protocol, and/or other transfer mechanism, such as any of those discussed herein. The transfer of the minted NFT ID **402** from the admin wallet **360** to the wallet **310** of the new ID holder **501** may be recorded as a transaction **417** and/or is added as a block to the relevant blockchain(s) **415**.

(84) In some implementations, an update feature can also be included, where an ID history (e.g., historical and/or already stored ID info **513**) can be updated with or without touching the original data (e.g., the already stored ID info **513**). In these implementations, the current metadata **413** is read from the file system **560**, and one or more data elements/DBOs of the metadata **413** is/are updated with one or more new entries. New metadata **413** is added or stored in the file system **560**, and a content hash on a corresponding smart contract **411** is updated.

(85) In various implementations, an individual **501** can have multiple NFT IDs **402**, for example, a first NFT ID **402** for a driver's license, a second NFT ID **402** for a work ID, a third NFT ID **402** for a social media platform (e.g., Twitter® and/or the like), a fourth NFT ID **402** for a content sharing platform (e.g., YouTube® and/or the like), and so forth. Additionally, each of the multiple NFT IDs

402 can be minted using the same or different smart contracts **411**.

(86) In one example, a user **501** can operate the wallet **310** to scan one or more identity documents and/or input various identity data (e.g., one or more biometrics, such as facial image data, fingerprint, voiceprint, and/or the like), which is then provided to the NFT engine **350** (step **5.1**). The user **501** can also provide info regarding the type of NFT ID **402** to be generated and/or the org(s) (e.g., third party platform, governmental agency/body, NGO, and/or the like) that the NFT ID **402** should be associated with (step **5.1**). If a smart contract **411** for generating the NFT ID **402** already exists (e.g., the relevant org has already defined or developed a suitable smart contract **411**), the wallet **310** triggers execution of the smart contract **411** (step **5.2**), which causes the NFT engine **350** to provide the supplied info to the file system (step **5.3b**) and request the NFT framework **403** to mint an NFT ID **402** (step **5.3a**). If a smart contract **411** for generating the NFT ID **402** does not exist (e.g., the relevant org has not defined or developed a suitable smart contract **411**), the wallet **310** triggers the NFT engine **350** to generate a suitable smart contract **411** (step **5.2**, step **5.3a**), which is then executed to mint the NFT ID **402** (step **5.3a**, step **5.3b**, step **5.4**). The NFT framework **403** mints the NFT ID **402** by, for example, conceptualizing the NFT ID **402**, creating the digital asset, tokenizing the asset, and then minting the NFT. Conceptualizing the NFT ID **402** can involve the NFT framework **403** determining the identity that the NFT ID **402** will represent according to a predefined configuration. Creating the digital asset can involve the NFT framework **403** creating a digital representation of the identity (also referred to as a “digital ID”). The digital ID can be or include an image, video, audio data, text, and/or any other content/data. The digital ID can be provided by the user **501** and/or created by the NFT framework **403**. The NFT framework **403** can use various image and/or audio generation mechanisms to generate the digital ID. Tokenizing the asset can involve the NFT framework **403** linking the digital ID to a unique ID (e.g., a hash of the digital ID, a random number, and/or the like), which is to be stored on a blockchain **415**. This allows the NFT ID **402** to be verified and tracked as a unique and original digital asset. Then, the NFT ID **402** is minted or created by assigning it a specific number of tokens and adding it to the blockchain. The NFT can then be bought, sold, and traded just like any other cryptocurrency.

2. Example Hardware and Software Systems and Configurations

(87) In FIGS. **1-6**, the client devices **310**, **360**, **650** (also referred to as a “client system,” “user system,” “user device,” and/or the like) include physical hardware devices and software components capable of accessing content and/or services provided by the NFT ID service **200**. In order to access the content/services, the client devices **310**, **360**, **650** include components such as processors, memory devices, communication interfaces, and/or the like. Additionally, the client devices **310**, **360**, **650** may include, or be communicatively coupled with, one or more sensors (e.g., image capture device(s), microphones, and/or the like), which is/are used to capture biometric data. As discussed in more detail infra, the captured biometric data is then provided to the NFT ID service **200** for NFT ID purposes. The client devices **310**, **360**, **650** communicate with the NFT/blockchain service **250** to obtain content/services using, for example, Hypertext Transfer Protocol (HTTP) over Transmission Control Protocol (TCP)/Internet Protocol (IP), or one or more other common Internet protocols such as File Transfer Protocol (FTP); Session Initiation Protocol (SIP) with Session Description Protocol (SDP), Real-time Transport Protocol (RTP), Secure RTP (SRTP), and/or Real-time Streaming Protocol (RTSP); Real-Time Communication (RTC) and/or WebRTC; Secure Shell (SSH); Extensible Messaging and Presence Protocol (XMPP); WebSocket; and/or some other communication technology such as those discussed herein. In this regard, the client devices **310**, **360**, **650** may establish a communication session with the NFT/blockchain service **250**. As used herein, a “session” refers to a persistent interaction between a subscriber (e.g., client device **310**) and an endpoint that may be either a relying party (RP) such as a web server, app server, or a Credential Service Provider (CSP) such as NFT/blockchain service **250**. A session begins with an authentication event and ends with a session termination event. A session is bound by use of a session secret (e.g., a password, digital certificate, and/or the like) that the subscriber's software (a browser, app, or OS) can present to the RP or CSP in lieu of the subscriber's authentication credentials. A “session secret” refers to a

secret used in authentication that is known to a subscriber and a verifier. The client devices **310, 360, 650** can be implemented as any suitable computing system or other data processing apparatus usable by users to access content/services provided by the NFT/blockchain service **250**. In the example of FIGS. **3-5**, the client devices **310, 360, 650** are depicted as digital wallets or mobile cellular phones (e.g., a “smartphones”); however, the client systems can be any other suitable computer system such as laptops, tablets, desktop computers, workstations, portable media players, wearable computing devices (e.g., smart watches and/or the like), or some other computing systems/devices.

(88) In some examples, the NFT/blockchain service **250** may represent a cloud computing service, an intranet, enterprise network, or some other like private network that is unavailable to the public. In one example implementation, the entirety of NFT/blockchain service **250** including both the front end and the back end may be implemented in or by a cloud computing service (e.g., a “full stack” cloud implementation). The cloud computing service (or “cloud”) includes networks of physical and/or virtual computer systems (e.g., one or more servers), data storage systems/devices, and/or the like within or associated with a data center or data warehouse that provide access to a pool of computing resources. The one or more servers in a cloud include user computer systems, where each of the servers includes one or more processors, one or more memory devices, input/output (I/O) interfaces, communications interfaces, and/or other like components. The servers may be connected with one another via a Local Area Network (LAN), fast LAN, message passing interface (MPI) implementations, and/or any other suitable networking technology. Various combinations of the servers may implement different cloud elements or nodes, such as cloud manager(s), cluster manager(s), master node(s), one or more secondary (slave) nodes, and/or the like. The one or more servers may implement additional or alternative nodes/elements in other implementations. In some cloud implementations, at least some of the servers in the cloud (e.g., servers that act as secondary nodes) may implement app server and/or web server functionality, which includes, inter alia, obtaining various messages from the client devices **310, 360, 650**; processing data contained in those messages; routing data to other nodes in the cloud for further processing, storage, retrieval, and/or the like; generating and communicating messages including data items, content items, program code, renderable webpages and/or documents (e.g., including the various GUIs discussed herein), and/or other info to/from client devices **310, 360, 650**; and/or other like app server functions. In this way, various combinations of the servers may implement different cloud elements/nodes configured to perform the implementations discussed herein.

(89) The NFT/blockchain service **250** includes one or more servers **320, 330**, and/or **350** and a DB (e.g., NFT ID DB **340** and/or the like). The web server(s) (e.g., servers **320**) serve static content from a file system of the web server(s). The servers **320, 330**, and/or **350** may be virtual or physical systems that provide NFT ID services to individual users (e.g., using a client system(s) **310, 360**) and/or for customer platforms. In some implementations, some or all of the NFT ID services may be provided by or accessed from third party systems/services, and the info provided by the third party systems/services may be enhanced or amended using info collected by the NFT/blockchain service **250**. The virtual and/or physical systems may include app servers, web servers, and/or other like computing systems/devices. The particular NFT ID services provided by the servers **320, 330**, and/or **350** (or remote system **690**) may depend on the architecture or implementation of the NFT/blockchain service **250**, and may vary from embodiment to embodiment. In one example, one or more of the servers **320, 330**, and/or **350** (or remote system **690**) may operate as an app server and may provide respective NFT ID services (e.g., registration, NFT ID minting, report generation, and so forth) as separate processes, or by implementing autonomous software agents. In another example, individual NFT ID server(s) **320, 330**, and/or **350** (or remote system **690**) may be dedicated to perform separate NFT ID services, where app servers **320** are used to obtain requests from client devices **310, 360, 650** and provide info/data to the NFT ID server(s) **330** and/or **350** to perform their respective NFT ID related services.

(90) The app servers **320** comprise one or more physical and/or virtualized systems for providing content and/or functionality (e.g., services) to one or more clients (e.g., client system **310, 360, 650**)

over a network. The physical and/or virtualized systems include one or more logically or physically connected servers and/or data storage devices distributed locally or across one or more geographic locations. Generally, the web/app servers **320** are configured to use IP/network resources to provide web pages, forms, apps, data, services, and/or media content to the client system. Additionally or alternatively, the web/app servers **320** may generate and serve dynamic content (e.g., server-side programming, database connections, dynamic generation of web documents) using an appropriate plug-in (e.g., a ASP.NET plug-in). The app server(s) **320** implement an app platform, which is a framework that provides for the development and execution of server-side apps as part of an app hosting service. The app platform enables the creation, management, and execution of one or more server-side apps developed by the NFT/blockchain service **250** and/or third-party app developers, which allow users and/or third-party app developers to access the NFT/blockchain service **250** via respective client systems **310**, **360**, **650**. The client systems **310**, **360**, **650** may operate respective client apps (e.g., client app **655** in FIG. **6**) to access the dynamic content, for example, by sending appropriate HTTP messages and/or the like, and in response, the server-side app(s) may dynamically generate and provide source code documents to the client app, and the source code documents are used for generating and rendering graphical objects (or simply “objects”) within the client app. The server-side apps may be developed with any suitable server-side programming languages or technologies, such as PHP; Java™ based technologies such as Java Servlets, JavaServer Pages (JSP), JavaServer Faces (JSF), and/or the like; ASP.NET; Ruby or Ruby on Rails; and/or any other like technology that renders HyperText Markup Language (HTML), such as those discussed herein. The apps may be built using a platform-specific and/or proprietary development tool, and/or programming languages.

(91) The servers **320**, **330**, and/or **350** serve one or more instructions or source code documents to client systems, which may then be executed within a client app (e.g., a wallet app as discussed previously, which may be the same or similar as client app **655**) to render one or more objects (e.g., graphical user interfaces (GUIs)). The GUIs comprise graphical control elements (GCEs) that allow the client systems to perform various functions and/or to request or instruct the NFT/blockchain service **250** to perform various functions. The servers **320**, **330**, and/or **350** (or remote system **690**) may provide various interfaces such as those discussed herein. The interfaces may be developed using website development tools and/or programming languages (e.g., HTML, Cascading Stylesheets (CSS), JavaScript, Jscript, Bash, Python, PowerShell, Ruby, and/or the like) and/or using platform-specific development tools (e.g., Android® Studio™ integrated development environment (IDE), Microsoft® Visual Studio® IDE, Apple® iOS® software development kit (SDK), Nvidia® Compute Unified Device Architecture (CUDA)® Toolkit, and/or the like). The term “platform-specific” may refer to the platform implemented by the client systems and/or the platform implemented by the servers **320**, **330**, and/or **350**. Example interfaces are shown and described with regard to FIGS. **1-6**. In an example implementation, the servers **320**, **330**, and/or **350** (or remote system **690**) may implement Apache HTTP Server (“httpd”) web servers or NGINX™ web servers on top of the Linux® OS. In this example implementation, PHP and/or Python may be employed as server-side languages, MySQL may be used as the DQL/DBMS. In an example implementation, the mobile apps may be developed for Android®, iOS®, and/or some other mobile platform.

(92) Furthermore, one or more servers **320**, **330**, **350**, **690** may hash, digitally sign, and/or encrypt/decrypt data using, for example, a cryptographic hash algorithm, such as a function in the Secure Hash Algorithm (SHA) 2 set of cryptographic hash algorithms (e.g., SHA-226, SHA-256, SHA-512, and/or the like), SHA 3, and so forth, or any type of keyed or unkeyed cryptographic hash function and/or any other function discussed herein; an elliptic curve cryptographic (ECC) algorithm, Elliptic Curve cryptography Digital Signature Algorithm (ECDSA), Rivest-Shamir-Adleman (RSA) cryptography, Merkle signature scheme, advanced encryption system (AES) algorithm, a triple data encryption algorithm (3DES), and/or the like.

(93) The NFT ID DB **340** may be stored in one or more data storage devices or storage systems that act as a repository for persistently storing and managing collections of data according to one or more

predefined DB structures. The data storage devices/systems may include one or more primary storage devices, secondary storage devices, tertiary storage devices, non-linear storage devices, and/or other like data storage devices. In some implementations, at least some of the servers **320, 330, 350, 690** may implement a suitable database management system (DBMS) to execute storage and retrieval of info against various database object(s) in the NFT ID DB **340**. These servers **320, 330, 350, 690** may be storage servers, file servers, or other like computing systems. The DBMS may include a relational database management system (RDBMS), an object database management system (ODBMS), a non-relational DBMS (e.g., a NoSQL DB system), and/or some other DBMS used to create and maintain the NFT ID DB **340**. The NFT ID DB **340** can be implemented as part of a single database, a distributed database, a collection of distributed databases, a database with redundant online or offline backups or other redundancies, and/or the like, and can include a distributed database or storage network. These servers **320, 330, 350, 690** may implement one or more query engines that utilize one or more data query languages (DQLs) to store and retrieve info in/from the NFT ID DB **340**, such as Structured Query Language (SQL), Structured Object Query Language (SOQL), Procedural Language/SOQL (PL/SOQL), GraphQL, Hyper Text SQL (HTSQL), Query By Example (QBE), object query language (OQL), object constraint language (OCL), non-first normal form query language (N1QL), XQuery, and/or any other DQL or combinations thereof. The query engine(s) may include any suitable query engine technology or combinations thereof including, for example, direct (e.g., SQL) execution engines (e.g., Presto SQL query engine, MySQL engine, SOQL execution engine, Apache® Phoenix® engine, and/or the like), a key-value datastore or NoSQL DB engines (e.g., DynamoDB® provided by Amazon.com®, MongoDB query framework provided by MongoDB Inc.®, Apache® Cassandra, Redis™ provided by Redis Labs®, and/or the like), MapReduce query engines (e.g., Apache® Hive™, Apache® Impala™, Apache® HAWQ™, IBM® Db2 Big SQL®, and/or the like for Apache® Hadoop® DB systems, and/or the like), relational DB (or “NewSQL”) engines (e.g., InnoDB™ or MySQL Cluster™ developed by Oracle®, MyRocks™ developed by Facebook.com®, FaunaDB provided by Fauna Inc.), PostgreSQL DB engines (e.g., MicroKernel DB Engine and Relational DB Engine provided by Pervasive Software®), graph processing engines (e.g., GraphX of an Apache® Spark® engine, an Apache® Tez engine, Neo4J provided by Neo4j, Inc.™, and/or the like), pull (iteration pattern) query engines, push (visitor pattern) query engines, transactional DB engines, extensible query execution engines, package query language (PaQL) execution engines, LegoBase query execution engines, and/or some other query engine used to query some other type of DB system (such as any processing engine or execution technology discussed herein). In some implementations, the query engine(s) may include or implement an in-memory caching system and/or an in-memory caching engine (e.g., memcached, Redis, and/or the like) to store frequently accessed data items in a main memory of the servers **320, 330, 350, 690** for later retrieval without additional access to the persistent data store. Suitable implementations for the database systems and storage devices are known or commercially available, and are readily implemented by persons having ordinary skill in the art.

(94) The NFT ID DB **340** stores a plurality of database objects (DBOs). The DBOs may be arranged in a set of logical tables containing data fitted into predefined or customizable categories, and/or the DBOs may be arranged in a set of blockchains or ledgers wherein each block (or DBO) in the blockchain is linked to a previous block. Each of the DBOs may include data associated with individual users, such as identity data and/or ID info (e.g., ID info **513** of FIG. 5), and/or other personal info of users **310, 360, 650**, UIDs, and/or, in certain embodiments, other data such as biographic data; biometric data; data collected from various external sources; session IDs; and/or other like data, including any of the data or data types discussed herein. Some of the DBOs may store info pertaining to relationships between any of the data items discussed herein. Some of the DBOs may store permission or access-related info for each user. These DBOs may indicate specific third parties that are permitted to access identity data of a particular user. In some implementations, the permission or access-related DBOs for each user may be arranged or stored as a blockchain to control which third parties can access that user's identity data and/or NFT ID. In these embodiments, the

blockchain(s) do not actually store user biometric and/or biographic data, but instead are used to authorize specific third party platforms to access specific identity data items and/or NFT IDs and to grant accesses to their platforms, to validate or verify a user's identity, and/or for other purposes.

(95) As alluded to previously, the client system(s) **310, 360, 650** is/are configured to run, execute, or otherwise operate a client app **655**. The client app **655** is a software app designed to generate and render objects, which include various types of content. At least some of the objects include graphical user interfaces (GUIs) and/or graphical control elements (GCEs) that enable interactions with the NFT/blockchain service **250**. In some embodiments, the client app **655** is an app container/skeleton in which an NFT ID app operates (e.g., a wallet app, payment app, web browser, and/or the like). For example, the objects may represent a web app that runs inside the client app **655**, and the client app **655** may be an HTTP client, such as a “web browser” (or simply a “browser”) for sending and receiving HTTP messages to and from a web/app servers **320** of the NFT/blockchain service **250**. In some examples, a NFT ID browser extension or plug-in may be configured to allow the client app **655** to render objects that allow the user to interact with the NFT/blockchain service **250** for generating NFT IDs **402** according to the embodiments discussed herein. Example browsers include WebKit-based browsers, Microsoft's Internet Explorer browser, Microsoft's Edge browser, Apple's Safari, Google's Chrome, Opera's browser, Mozilla's Firefox browser, and/or the like. In some embodiments, the client app **655** is an app specifically developed or tailored to interact with the NFT/blockchain service **250**. For example, the client app **655** may be a desktop or native (mobile) app that runs directly on the client system(s) **310, 360, 650** without a browser, and which communicates (sends and receives) suitable messages with the NFT/blockchain service **250**. In some embodiments, the client app **655** is an app specifically developed or tailored to interact with the NFT/blockchain service **250** for generating NFT IDs **402**.

(96) The client app **655** may be developed using any suitable programming languages and/or development tools, such as those discussed herein or others known in the art. The client app **655** may be platform-specific, such as when the client system(s) **310, 360, 650** is/are implemented as a mobile device, such as a smartphone, tablet computer, and/or the like. In these embodiments, the client app **655** may be a mobile web browser, a native app (or “mobile app”) specifically tailored to operate on the mobile client system(s) **310, 360, 650**, or a hybrid app wherein objects (or a web app) is embedded inside the native app. In some implementations, the client app **655** and/or the web apps that run inside the client app **655** is/are specifically designed to interact with server-side apps implemented by the app platform of the provider system (discussed infra). In some implementations, the client app **655**, and/or the web apps that run inside the client app **655** may be platform-specific or developed to operate on a particular type of client system(s) **310, 360, 650** or a particular (hardware and/or software) client system(s) configuration. The term “platform-specific” may refer to the platform implemented by the client system(s) **310, 360, 650**, the platform implemented by the NFT/blockchain service **250**, and/or a platform of a third-party system/platform.

(97) In the aforementioned embodiments, the client system(s) **310, 360, 650** implementing a client app **655** is capable of controlling its communications/network interface(s) to send and receive HTTP messages to/from the NFT/blockchain service **250**, render the objects in the client app **655**, request connections with other devices, and/or perform (or request performance) of other like functions. The header of these HTTP messages includes various operating parameters and the body of the HTTP messages include program code or source code documents (e.g., HTML, XML, JSON, and/or some other like object(s)/document(s)) to be executed and rendered in the client app **655**. The client app **655** executes the program code or source code documents and renders the objects (or web apps) inside the client app **655**.

(98) The rendered objects (or executed web app) allows the user of the client system(s) **310, 360, 650** to view content provided by the NFT/blockchain service **250**, which may include the results of a requested service, visual representations of data, hyperlinks or links to other resources, and/or the like. The rendered objects also include interfaces for interacting with the NFT/blockchain service **250**, for example, to request additional content or services from the NFT/blockchain service **250**. In

an example, the rendered objects may include GUIs, which are used to manage the interactions between the user of the client system(s) **310, 360, 650** and the NFT/blockchain service **250**. The GUIs comprise one or more GCEs (or widgets) such as buttons, sliders, text boxes, tabs, dashboards, and/or the like. The user of the client system(s) **310, 360, 650** may select or otherwise interact with one or more of the GCEs (e.g., by pointing and clicking using a mouse, or performing a gesture for touchscreen-based systems) to request content or services from the NFT service **250**.

(99) In some cases, the user of client system(s) **310, 360, 650** may be required to authenticate their identity in order to obtain content and/or services from the NFT/blockchain service **250**, and the NFT/blockchain service **250** serves the user of client system(s) **310, 360, 650** so that the user can access the content/services from the NFT/blockchain service **250**. To provide the NFT ID services to the user, the client app **655** may be, or may include, a secure portal to the NFT/blockchain service **250** (e.g., the previously discussed NFT ID front-end portal and/or the like). The secure portal may be a stand-alone app, embedded within a web or mobile app provided by NFT/blockchain service **250**, and/or invoked or called by the web/mobile app provided by NFT/blockchain service **250** (e.g., using an API, Remote Procedure Call (RPC), and/or the like). In these cases, graphical objects rendered and displayed within the client app **655** may be a GUI and/or GCEs of the secure portal, which allows the user to share data (e.g., ID documents, contact info, biographic data, biometric data, and/or the like) with the NFT/blockchain service **250**. In any of the aforementioned embodiments and example use cases, the secure portal allows user devices **310, 360, 650**, to enroll with the NFT/blockchain service **250** for NFT ID purposes. The secure portal also allows enrolled users to access and/or perform various NFT ID creation tasks. For example, the secure portal may provide access to a dashboard GUI that allows admins **360** to submit smart contracts **411**, configurations to generate such smart contracts **411**, (encrypted) ID info **513**, update and improve the quality of collected information, and set notifications for automatically receiving updates related to various individuals.

(100) Additionally or alternatively, the client app **655** may collect various data from the client system(s) **310, 360, 650** without direct user interaction with the client app **655**. For example, the client app **655** may cause the client system(s) **310, 360, 650** to generate and transmit one or more HTTP messages with a header portion including, inter alia, an IP address of the client system(s) **310, 360, 650** in an X-Forwarded-For (XFF) field, a time and date that the message was sent in a Date field, and/or a user agent string contained in a User Agent field. The user agent string may indicate an operating system (OS) type/version being operated by the client system(s) **310, 360, 650**, system information of the client system(s) **310, 360, 650**, an app version/type or browser version/type of the client app **655**, a rendering engine version/type implemented by the client app **655**, a device and/or platform type of the client system(s) **310, 360, 650**, and/or other like information. These HTTP messages may be sent in response to user interactions with the client app **655** (e.g., when a user submits biographic or biometric data as discussed infra), or the client app **655** may include one or more scripts, which when executed by the client system(s) **310, 360, 650**, cause the client system(s) **310, 360, 650** to generate and send the HTTP messages upon loading or rendering the client app **655**. Other message types may be used and/or the user and/or client system(s) **310, 360, 650** information may be obtained by other means in other embodiments.

(101) In addition to (or alternative to) obtaining information from HTTP messages as discussed previously, the servers **320, 330**, and/or **350** may determine or derive other types of user information associated with the client system(s) **310, 360, 650**. For example, the servers **320, 330**, and/or **350** may derive a time zone and/or geolocation in which the client system(s) **310, 360, 650** is/are located from an obtained IP address. In some embodiments, the user and/or client system(s) **310, 360, 650** information may be sent to the servers **320, 330**, and/or **350** when the client system(s) **310, 360, 650** loads or renders the client app **655**. For example, the login page may include JavaScript or other like code that obtains and sends back information (e.g., in an additional HTTP message) that is not typically included in an HTTP header, such as time zone information, global navigation satellite system (GNSS) and/or Global Positioning System (GPS) coordinates, screen or display resolution of the client system(s) **310, 360, 650**, and/or other like information. Other methods may be used to

obtain or derive information in other embodiments.

(102) FIG. 6 illustrates an example compute node **600** (also referred to as “platform **600**,” “device **600**,” “appliance **600**,” “system **600**”, and/or the like), and various components therein, for implementing the techniques (e.g., operations, processes, methods, and methodologies) described herein. In FIG. 6, like numbered items are the same as discussed previously w.r.t FIGS. 1-5. The compute node **600** provides a closer view of the respective components of node **600** when implemented as or as part of a computing device or system. The compute node **600** can include any combination of the hardware or logical components referenced herein, and may include or couple with any device usable with a communication network or a combination of such networks. In particular, any combination of the components depicted by FIG. 6 can be implemented as individual ICs, discrete electronic devices, or other modules, instruction sets, programmable logic or algorithms, hardware, hardware accelerators, software, firmware, or a combination thereof adapted in the compute node **600**, or as components otherwise incorporated within a chassis of a larger system. Additionally or alternatively, any combination of the components depicted by FIG. 6 can be implemented as a system-on-chip (SoC), a single-board computer (SBC), a system-in-package (SiP), a multi-chip package (MCP), and/or the like, in which a combination of the hardware elements are formed into a single IC or a single package.

(103) The compute node **600** includes physical hardware devices and software components capable of providing and/or accessing content and/or services to/from the remote system **690**. The compute node **600** and/or the remote system **690** can be implemented as any suitable computing system or other data processing apparatus usable to access and/or provide content/services from/to one another. The compute node **600** communicates with remote systems **690**, and vice versa, to obtain/serve content/services using any suitable communication protocol, such as any of those discussed herein. In some implementations, the remote system **690** may have some or all of the same or similar components as the compute node **600**. As examples, the compute node **600** and/or the remote system **690** can be embodied as desktop computers, workstations, laptops, mobile phones (e.g., “smartphones”), tablet computers, portable media players, wearable devices, server(s), network appliances, smart appliances or smart factory machinery, network infrastructure elements, robots, drones, sensor systems and/or IoT devices, cloud compute nodes, edge compute nodes, an aggregation of computing resources (e.g., in a cloud-based environment), and/or some other computing devices capable of interfacing directly or indirectly with network **699** or other network(s). For purposes of the present disclosure, the compute node **600** may represent any of the computing devices discussed herein, and may be, or be implemented in one or more of NFT/blockchain service **250**, client systems **310**, **360**, **650**, servers **320**, **330**, **350**, **690**, and/or any other devices or systems, such as any of those discussed herein.

(104) The system **600** includes physical hardware devices and software components capable of providing and/or accessing content and/or services to/from the remote system **655**. The system **600** and/or the remote system **655** can be implemented as any suitable computing system or other data processing apparatus usable to access and/or provide content/services from/to one another. As examples, the system **600** and/or the remote system **655** may comprise desktop computers, a work stations, laptop computers, mobile cellular phones (e.g., “smartphones”), tablet computers, portable media players, wearable computing devices, server computer systems, an aggregation of computing resources (e.g., in a cloud-based environment), or some other computing devices capable of interfacing directly or indirectly with network **650** or other network. The system **600** communicates with remote systems **655**, and vice versa, to obtain/serve content/services using any suitable communication protocol, such as any of those discussed herein.

(105) The compute node **600** includes one or more processors **601** (also referred to as “processor circuitry **601**”). The processor circuitry **601** includes circuitry capable of sequentially and/or automatically carrying out a sequence of arithmetic or logical operations, and recording, storing, and/or transferring digital data. Additionally or alternatively, the processor circuitry **601** includes any device capable of executing or otherwise operating computer-executable instructions, such as

program code, software modules, and/or functional processes. The processor circuitry **601** includes various hardware elements or components such as, for example, a set of processor cores and one or more of on-chip or on-die memory or registers, cache and/or scratchpad memory, low drop-out voltage regulators (LDOs), interrupt controllers, serial interfaces such as SPI, I2C or universal programmable serial interface circuit, real time clock (RTC), timer-counters including interval and watchdog timers, general purpose I/O, memory card controllers such as secure digital/multi-media card (SD/MMC) or similar, interfaces, mobile industry processor interface (MIPI) interfaces and Joint Test Access Group (JTAG) test access ports. Some of these components, such as the on-chip or on-die memory or registers, cache and/or scratchpad memory, may be implemented using the same or similar devices as the memory circuitry **603** discussed infra. The processor circuitry **601** is also coupled with memory circuitry **603** and storage circuitry **604**, and is configured to execute instructions stored in the memory/storage to enable various apps, OSs, or other software elements to run on the platform **600**. In particular, the processor circuitry **601** is configured to operate app software (e.g., instructions **601x**, **603x**, **604x**) to provide one or more services to a user of the compute node **600** and/or user(s) of remote systems/devices.

(106) The processor circuitry **601** can be embodied as, or otherwise include one or multiple central processing units (CPUs), application processors, graphics processing units (GPUs), RISC processors, Acorn RISC Machine (ARM) processors, complex instruction set computer (CISC) processors, DSPs, FPGAs, programmable logic devices (PLDs), ASICs, baseband processors, radio-frequency integrated circuits (RFICs), microprocessors or controllers, multi-core processors, multithreaded processors, ultra-low voltage processors, embedded processors, a specialized x-processing units (xPUs) or a data processing unit (DPUs) (e.g., Infrastructure Processing Unit (IPU), network processing unit (NPU), and/or the like), and/or any other processing devices or elements, or any combination thereof. In some implementations, the processor circuitry **601** is embodied as one or more special-purpose processor(s)/controller(s) configured (or configurable) to operate according to the various implementations and other aspects discussed herein. Additionally or alternatively, the processor circuitry **601** includes one or more hardware accelerators (e.g., same or similar to acceleration circuitry **608**), which can include microprocessors, programmable processing devices (e.g., FPGAs, ASICs, PLDs, DSPs. and/or the like), and/or the like. As examples, the processor circuitry **602** may include Intel® Core™ based processor(s), MCU-class processor(s), Xeon® processor(s); Advanced Micro Devices (AMD) Zen® Core Architecture processor(s), such as Ryzen® or Epyc® processor(s), Accelerated Processing Units (APUs), MxGPUs, and/or the like; A, S, W, and T series processor(s) from Apple® Inc., Snapdragon™ or Centrig™ processor(s) from Qualcomm® Technologies, Inc., Texas Instruments, Inc.® Open Multimedia Applications Platform (OMAP)™ processor(s); Power Architecture processor(s) provided by the OpenPOWER® Foundation and/or IBM®, MIPS Warrior M-class, Warrior I-class, and Warrior P-class processor(s) provided by MIPS Technologies, Inc.; ARM Cortex-A, Cortex-R, and Cortex-M family of processor(s) as licensed from ARM Holdings, Ltd.; the ThunderX2® provided by Cavium™, Inc.; GeForce®, Tegra®, Titan X®, Tesla®, Shield®, and/or other like GPUs provided by Nvidia®; and/or the like. Other examples of the processor circuitry **602** may be mentioned elsewhere in the present disclosure.

(107) The compute node **600** also includes non-transitory or transitory machine-readable media **602** (also referred to as “computer readable medium **602**” or “CRM **602**”), which may be embodied as, or otherwise include system memory **603**, storage **604**, and/or memory devices/elements of the processor **601**. Additionally or alternatively, the CRM **602** can be embodied as any of the devices/technologies described for the memory **603** and/or storage **604**.

(108) The system memory **603** (also referred to as “memory circuitry **603**”) includes one or more hardware elements/devices for storing data and/or instructions **603x** (and/or instructions **601x**, **604x**). Any number of memory devices may be used to provide for a given amount of system memory **603**. As examples, the memory **603** can be embodied as processor cache or scratchpad memory, volatile memory, non-volatile memory (NVM), and/or any other machine readable media for storing data.

Examples of volatile memory include random access memory (RAM), static RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), thyristor RAM (T-RAM), content-addressable memory (CAM), and/or the like. Examples of NVM can include read-only memory (ROM) (e.g., including programmable ROM (PROM), erasable PROM (EPROM), electrically EPROM (EEPROM), flash memory (e.g., NAND flash memory, NOR flash memory, and/or the like), solid-state storage (SSS) or solid-state ROM, programmable metallization cell (PMC), and/or the like), non-volatile RAM (NVRAM), phase change memory (PCM) or phase change RAM (PRAM) (e.g., Intel® 3D XPoint™ memory, chalcogenide RAM (CRAM), Interfacial Phase-Change Memory (IPCM), and/or the like), memistor devices, resistive memory or resistive RAM (ReRAM) (e.g., memristor devices, metal oxide-based ReRAM, quantum dot resistive memory devices, and/or the like), conductive bridging RAM (or PMC), magnetoresistive RAM (MRAM), electrochemical RAM (ECRAM), ferroelectric RAM (FeRAM), anti-ferroelectric RAM (AFRAM), ferroelectric field-effect transistor (FeFET) memory, and/or the like. Additionally or alternatively, the memory circuitry **603** can include spintronic memory devices (e.g., domain wall memory (DWM), spin transfer torque (STT) memory (e.g., STT-RAM or STT-MRAM), magnetic tunneling junction memory devices, spin-orbit transfer memory devices, Spin-Hall memory devices, nanowire memory cells, and/or the like). In some implementations, the individual memory devices **603** may be formed into any number of different package types, such as single die package (SDP), dual die package (DDP), quad die package (Q17P), memory modules (e.g., dual inline memory modules (DIMMs), microDIMMs, and/or MiniDIMMs), and/or the like. Additionally or alternatively, the memory circuitry **603** is or includes block addressable memory device(s), such as those based on NAND or NOR flash memory technologies (e.g., single-level cell (“SLC”), multi-level cell (“MLC”), quad-level cell (“QLC”), tri-level cell (“TLC”), or some other NAND or NOR device). Additionally or alternatively, the memory circuitry **603** can include resistor-based and/or transistor-less memory architectures. In some examples, the memory circuitry **603** can refer to a die, chip, and/or a packaged memory product. In some implementations, the memory **603** can be or include the on-die memory or registers associated with the processor circuitry **601**. Additionally or alternatively, the memory **603** can include any of the devices/components discussed infra w.r.t the storage circuitry **604**.

(109) The storage **604** (also referred to as “storage circuitry **604**”) provides persistent storage of information, such as data, OSs, apps, instructions **604x**, and/or other software elements. As examples, the storage **604** may be embodied as a magnetic disk storage device, hard disk drive (HDD), microHDD, solid-state drive (SSD), optical storage device, flash memory devices, memory card (e.g., secure digital (SD) card, eXtreme Digital (XD) picture card, USB flash drives, SIM cards, and/or the like), and/or any combination thereof. The storage circuitry **604** can also include specific storage units, such as storage devices and/or storage disks that include optical disks (e.g., DVDs, CDs/CD-ROM, Blu-ray disks, and/or the like), flash drives, floppy disks, hard drives, and/or any number of other hardware devices in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or caching). Additionally or alternatively, the storage circuitry **604** can include resistor-based and/or transistor-less memory architectures. Further, any number of technologies may be used for the storage **604** in addition to, or instead of, the previously described technologies, such as, for example, resistance change memories, phase change memories, holographic memories, chemical memories, among many others. Additionally or alternatively, the storage circuitry **604** can include any of the devices or components discussed previously w.r.t the memory **603**.

(110) Instructions **601x**, **603x**, **604x** in the form of computer programs, computational logic/modules (e.g., including the various modules/logic discussed herein), source code, middleware, firmware, object code, machine code, microcode (pcode), or hardware commands/instructions, when executed, implement or otherwise carry out various functions, processes, methods, algorithms, operations, tasks, actions, techniques, and/or other aspects of the present disclosure. The instructions **601x**, **603x**, **604x** may be written in any combination of one or more programming languages, including object oriented programming languages, procedural programming languages, scripting languages, markup

languages, machine language, and/or some other suitable programming languages including proprietary programming languages and/or development tools, or any other suitable technologies. The instructions **601x**, **603x**, **604x** may execute entirely on the system **600**, partly on the system **600**, as a stand-alone software package, partly on the system **600** and partly on a remote system **690**, or entirely on the remote system **690**. In the latter scenario, the remote system **690** may be connected to the system **600** through any type of network **699**. Although the instructions **601x**, **603x**, **604x** are shown as code blocks included in the processor **601**, memory **604**, and/or storage **620**, any of the code blocks may be replaced with hardwired circuits, for example, built into memory blocks/cells of an ASIC, FPGA, and/or some other suitable IC.

(111) In some examples, the storage circuitry **604** stores computational logic/modules configured to implement the techniques described herein. The computational logic **604x** may be employed to store working copies and/or permanent copies of programming instructions, or data to create the programming instructions, for the operation of various components of compute node **600** (e.g., drivers, libraries, APIs, and/or the like), an OS of compute node **600**, one or more applications, and/or the like. The computational logic **604x** may be stored or loaded into memory circuitry **603** as instructions **603x**, or data to create the instructions **603x**, which are then accessed for execution by the processor circuitry **601** via the IX **606** to carry out the various functions, processes, methods, algorithms, operations, tasks, actions, techniques, and/or other aspects described herein (see e.g., FIGS. 1-5). The various elements may be implemented by assembler instructions supported by processor circuitry **601** or high-level languages that may be compiled into instructions **601x**, or data to create the instructions **601x**, to be executed by the processor circuitry **601**. The permanent copy of the programming instructions may be placed into persistent storage circuitry **604** at the factory/OEM or in the field through, for example, a distribution medium (e.g., a wired connection and/or over-the-air (OTA) interface) and a communication interface (e.g., communication circuitry **607**) from a distribution server (e.g., remote system **690**) and/or the like.

(112) Additionally or alternatively, the instructions **601x**, **603x**, **604x** can include one or more operating systems (OS) and/or other software to control various aspects of the compute node **600**. The OS can include drivers and/or APIs to control particular devices or components that are embedded in the compute node **600**, attached to the compute node **600**, communicatively coupled with the compute node **600**, and/or otherwise accessible by the compute node **600**. The OSs also include one or more libraries, drivers, APIs, firmware, middleware, software glue, and/or the like, which provide program code and/or software components for one or more apps to obtain and use the data from other apps operated by the compute node **600**, such as the various subsystems of the NFT/blockchain service **250** and/or any other device or system discussed herein. For example, the OS can include a display driver to control and allow access to a display device, a touchscreen driver to control and allow access to a touchscreen interface of the system **600**, sensor drivers to obtain sensor readings of sensor circuitry **621** and control and allow access to sensor circuitry **621**, actuator drivers to obtain actuator positions of the actuators **622** and/or control and allow access to the actuators **622**, a camera driver to control and allow access to an embedded image capture device, audio drivers to control and allow access to one or more audio devices. The OS can be a general purpose OS or an OS specifically written for and tailored to the computing platform **600**. Example OSs include consumer-based OS (e.g., Microsoft® Windows® 10, Google® Android®, Apple® macOS®, Apple® iOS®, KaiOS™ provided by KaiOS Technologies Inc., Unix or a Unix-like OS such as Linux, Ubuntu, and/or the like), industry-focused OSs such as real-time OS (RTOS) (e.g., Apache® Mynewt, Windows® IoT®, Android Things®, Micrium® Micro-Controller OSs (“MicroC/OS” or “pC/OS”), VxWorks®, FreeRTOS, and/or the like), hypervisors (e.g., Xen® Hypervisor, Real-Time Systems® RTS Hypervisor, Wind River Hypervisor, VMWare® vSphere® Hypervisor, and/or the like), and/or the like. For purposes of the present disclosure, can also include hypervisors, container orchestrators and/or container engines. The OS can invoke alternate software to facilitate one or more functions and/or operations that are not native to the OS, such as particular communication protocols and/or interpreters. Additionally or alternatively, the OS instantiates various functionalities that are not

native to the OS. In some examples, OSs include varying degrees of complexity and/or capabilities. In some examples, a first OS on a first compute node **600** may be the same or different than a second OS on a second compute node **600** (here, the first and second compute nodes **600** can be physical machines or VMs operating on the same or different physical compute nodes). In these examples, the first OS may be an RTOS having particular performance expectations of responsivity to dynamic input conditions, and the second OS can include GUI capabilities to facilitate end-user I/O and/or the like.

(113) The various components of the computing node **600** communicate with one another over an interconnect (IX) **606**. The IX **606** may include any number of IX (or similar) technologies including, for example, instruction set architecture (ISA), extended ISA (eISA), Inter-Integrated Circuit (I.sup.2C), serial peripheral interface (SPI), point-to-point interfaces, power management bus (PMBus), peripheral component interconnect (PCI), PCI express (PCIe), PCI extended (PCIx), Intel® Ultra Path Interconnect (UPI), Intel® Accelerator Link, Intel® QuickPath Interconnect (QPI), Intel® Omni-Path Architecture (OPA), Compute Express Link™ (CXL™) IX, RapidIO™ IX, Coherent Accelerator Processor Interface (CAPI), OpenCAPI, Advanced Microcontroller Bus Architecture (AMBA) IX, cache coherent interconnect for accelerators (CCIX), Gen-Z Consortium IXs, a HyperTransport IX, NVLink provided by NVIDIA®, ARM Advanced eXtensible Interface (AXI), a Time-Trigger Protocol (TTP) system, a FlexRay system, PROFIBUS, Ethernet, USB, On-Chip System Fabric (IOSF), Infinity Fabric (IF), and/or any number of other IX technologies. The IX **606** may be a proprietary bus, for example, used in a SoC based system.

(114) In some implementations (e.g., where the system **600** is a server computer system), the compute node **600** includes one or more hardware accelerators **608** (also referred to as “acceleration circuitry **608**”, “accelerator circuitry **608**”, and/or the like). The acceleration circuitry **608** can include various hardware elements such as, for example, one or more GPUs, FPGAs, DSPs, SoCs (including programmable SoCs and multi-processor SoCs), ASICs (including programmable ASICs), PLDs (including complex PLDs (CPLDs) and high capacity PLDs (HCPLDs), xPUs (e.g., DPUs, IPUs, and NPUs) and/or other forms of specialized circuitry designed to accomplish specialized tasks.

Additionally or alternatively, the acceleration circuitry **608** may be embodied as, or include, one or more of artificial intelligence (AI) accelerators (e.g., vision processing unit (VPU), neural compute sticks, neuromorphic hardware, deep learning processors (DLPs) or deep learning accelerators, tensor processing units (TPUs), physical neural network hardware, and/or the like), cryptographic accelerators (or secure cryptoprocessors), network processors, I/O accelerator (e.g., DMA engines and/or the like), and/or any other specialized hardware device/component. The offloaded tasks performed by the acceleration circuitry **608** can include, for example, AI/ML tasks (e.g., training, feature extraction, model execution for inference/prediction, classification, and so forth), visual data processing, graphics processing, digital and/or analog signal processing, network data processing, infrastructure function management, object detection, rule analysis, and/or the like. As examples, these processor(s) **601** and/or accelerators **608** may be a cluster of artificial intelligence (AI) GPUs, tensor processing units (TPUs) developed by Google® Inc., Real AI Processors (RAPs™) provided by AlphaICs®, Nervana™ Neural Network Processors (NNPs) provided by Intel® Corp., Intel® Movidius™ Myriad™ X Vision Processing Unit (VPU), NVIDIA® PX™ based GPUs, the NM500 chip provided by General Vision®, Hardware **3** provided by Tesla®, Inc., an Epiphany™ based processor provided by Adapteva®, and/or the like. In some implementations, the processor circuitry **602** and/or accelerator circuitry **608** may be implemented as AI accelerating co-processor(s), such as the Hexagon **685** DSP provided by Qualcomm®, the PowerVR 2NX Neural Net Accelerator (NNA) provided by Imagination Technologies Limited®, the Neural Engine core within the Apple® A11 or A12 Bionic SoC, the Neural Processing Unit (NPU) within the HiSilicon Kirin **970** provided by Huawei®, and/or the like.

(115) The acceleration circuitry **608** includes any suitable hardware device or collection of hardware elements that are designed to perform one or more specific functions more efficiently in comparison to general-purpose processing elements (e.g., those provided as part of the processor circuitry **601**).

For example, the acceleration circuitry **608** can include special-purpose processing device tailored to perform one or more specific tasks or workloads of the subsystems of the NFT/blockchain service **250**. In some examples, the specific tasks or workloads may be offloaded from one or more processors of the processor circuitry **602**. In some implementations, the processor circuitry **601** and/or acceleration circuitry **608** includes hardware elements specifically tailored for executing, operating, or otherwise providing AI and/or ML functionality, such as for operating various subsystems of the NFT/blockchain service **250** and/or any other device or system discussed herein, such as those discussed w.r.t FIGS. 1-5. In these implementations, the circuitry **601** and/or **608** is/are embodied as, or otherwise includes, one or more AI or ML chips that can run many different kinds of AI/ML instruction sets once loaded with the appropriate weightings, training data, AI/ML models, and/or the like. Additionally or alternatively, the processor circuitry **601** and/or accelerator circuitry **608** is/are embodied as, or otherwise includes, one or more custom-designed silicon cores specifically designed to operate corresponding subsystems of the NFT/blockchain service **250** and/or any other device or system discussed herein. These cores may be designed as synthesizable cores comprising hardware description language logic (e.g., register transfer logic, verilog, Very High Speed Integrated Circuit hardware description language (VHDL), and/or the like); netlist cores comprising gate-level description of electronic components and connections and/or process-specific very-large-scale integration (VLSI) layout; and/or analog or digital logic in transistor-layout format. In these implementations, one or more of the subsystems of the NFT/blockchain service **250** and/or any other device or system discussed herein may be operated, at least in part, on custom-designed silicon core(s). These “hardware-ized” subsystems may be integrated into a larger chipset but may be more efficient than using general purpose processor cores

(116) The TEE **609** operates as a protected area accessible to the processor circuitry **601** and/or other components to enable secure access to data and secure execution of instructions. The TEE **690** operates as a protected area accessible to the processor circuitry **602** to enable secure access to data and secure execution of instructions. In some implementations, the TEE **609** is embodied as one or more physical hardware devices that is/are separate from other components of the system **600**, such as a secure-embedded controller, a dedicated SoC, a TPM, a tamper-resistant chipset or microcontroller with embedded processing devices and memory devices, a smart card and/or universal integrated circuit card (UICC) (e.g., Subscriber Identity Module (SIM) card and/or the like), and/or the like. Examples of such implementations include a Desktop and mobile Architecture Hardware (DASH) compliant Network Interface Card (NIC), Intel® Management/Manageability Engine, Intel® Converged Security Engine (CSE) or a Converged Security Management/Manageability Engine (CSME), Trusted Execution Engine (TXE) provided by Intel® each of which may operate in conjunction with Intel® Active Management Technology (AMT) and/or Intel® vPro™ Technology; AMD® Platform Security coProcessor (PSP), AMD® PRO A-Series Accelerated Processing Unit (APU) with DASH manageability, Apple® Secure Enclave coprocessor; IBM® Crypto Express3®, IBM® 4807, 4808, 4809, and/or 4765 Cryptographic Coprocessors, IBM® Baseboard Management Controller (BMC) with Intelligent Platform Management Interface (IPMI), Dell™ Remote Assistant Card II (DRAC II), integrated Dell™ Remote Assistant Card (iDRAC), and/or the like.

(117) Additionally or alternatively, the TEE **609** is embodied as secure enclaves (or “enclaves”), which is/are isolated regions of code and/or data within the processor and/or memory/storage circuitry of the compute node **600**, where only code executed within a secure enclave may access data within the same secure enclave, and the secure enclave may only be accessible using the secure app (which may be implemented by an app processor or a tamper-resistant microcontroller). In some implementations, the memory circuitry **603** and/or storage circuitry **604** may be divided into one or more trusted memory regions for storing apps or software modules of the secure enclave(s) **609**. Example implementations of the TEE **690**, and an accompanying secure area in the processor circuitry **601** or the memory circuitry **603** and/or storage circuitry **604**, include Intel® Software Guard Extensions (SGX), ARM® TrustZone® hardware security extensions, Keystone Enclaves

provided by Oasis Labs™, and/or the like. Other aspects of security hardening, hardware roots-of-trust, and trusted or protected operations may be implemented in the device **600** through the TEE **690** and the processor circuitry **602**.

(118) Additionally or alternatively, the TEE **609** and/or processor circuitry **601**, acceleration circuitry **608**, memory circuitry **603**, and/or storage circuitry **604** may be divided into, or otherwise separated into isolated user-space instances and/or virtualized environments using a suitable virtualization technology, such as, for example, virtual machines (VMs), virtualization containers (e.g., Docker® containers, Kubernetes® containers, Solaris® containers and/or zones, OpenVZ® virtual private servers, DragonFly BSD® virtual kernels and/or jails, chroot jails, and/or the like), and/or other virtualization technologies. These virtualization technologies may be managed and/or controlled by a virtual machine monitor (VMM), hypervisor container engines, orchestrators, and/or the like. Such virtualization technologies provide execution environments/TEEs in which one or more apps and/or other software, code, or scripts may execute while being isolated from one or more other apps, software, code, or scripts.

(119) The communication circuitry **607** is a hardware element, or collection of hardware elements, used to communicate over one or more networks (e.g., network **699**) and/or with other devices. The communication circuitry **607** includes modem **607a** and transceiver circuitry (“TRx”) **607b**. The modem **607a** includes one or more processing devices (e.g., baseband processors) to carry out various protocol and radio control functions. Modem **607a** may interface with application circuitry of compute node **600** (e.g., a combination of processor circuitry **601**, memory circuitry **603**, and/or storage circuitry **604**) for generation and processing of baseband signals and for controlling operations of the TRx **607b**. The modem **607a** handles various radio control functions that enable communication with one or more radio networks via the TRx **607b** according to one or more wireless communication protocols. The modem **607a** may include circuitry such as, but not limited to, one or more single-core or multi-core processors (e.g., one or more baseband processors) or control logic to process baseband signals received from a receive signal path of the TRx **607b**, and to generate baseband signals to be provided to the TRx **607b** via a transmit signal path. In various implementations, the modem **607a** may implement a real-time OS (RTOS) to manage resources of the modem **607a**, schedule tasks, and/or the like.

(120) The communication circuitry **607** also includes TRx **607b** to enable communication with wireless networks using modulated electromagnetic radiation through a non-solid medium. The TRx **607b** may include one or more radios that are compatible with, and/or may operate according to any one or more of the radio communication technologies, radio access technologies (RATs), and/or communication protocols/standards including any combination of those discussed herein. TRx **607b** includes a receive signal path, which comprises circuitry to convert analog RF signals (e.g., an existing or received modulated waveform) into digital baseband signals to be provided to the modem **607a**. The TRx **607b** also includes a transmit signal path, which comprises circuitry configured to convert digital baseband signals provided by the modem **607a** to be converted into analog RF signals (e.g., modulated waveform) that will be amplified and transmitted via an antenna array including one or more antenna elements (not shown). The antenna array may be a plurality of microstrip antennas or printed antennas that are fabricated on the surface of one or more printed circuit boards. The antenna array may be formed in as a patch of metal foil (e.g., a patch antenna) in a variety of shapes, and may be coupled with the TRx **607b** using metal transmission lines and/or the like.

(121) The network interface circuitry/controller (NIC) **607c** provides wired communication to the network **699** and/or to other devices using a standard communication protocol such as, for example, Ethernet (e.g., [IEEE802.3]), Ethernet over GRE Tunnels, Ethernet over Multiprotocol Label Switching (MPLS), Ethernet over USB, Controller Area Network (CAN), Local Interconnect Network (LIN), DeviceNet, ControlNet, Data Highway+, PROFIBUS, or PROFINET, among many others. Network connectivity may be provided to/from the compute node **600** via the NIC **607c** using a physical connection, which may be electrical (e.g., a “copper interconnect”), fiber, and/or optical. The physical connection also includes suitable input connectors (e.g., ports, receptacles, sockets,

and/or the like) and output connectors (e.g., plugs, pins, and/or the like). The NIC **607c** may include one or more dedicated processors and/or FPGAs to communicate using one or more of the aforementioned network interface protocols. In some implementations, the NIC **607c** may include multiple controllers to provide connectivity to other networks using the same or different protocols. For example, the compute node **600** may include a first NIC **607c** providing communications to the network **699** over Ethernet and a second NIC **607c** providing communications to other devices over another type of network. As examples, the NIC **607c** is or includes one or more of an Ethernet controller (e.g., a Gigabit Ethernet Controller and/or the like), a high-speed serial interface (HSSI), a Peripheral Component Interconnect (PCI) controller, a USB controller, a SmartNIC, an Intelligent Fabric Processor (IFP), and/or other like device.

(122) The input/output (I/O) interface circuitry **608** (also referred to as “interface circuitry **608**”) is configured to connect or communicatively coupled the compute node **600** with one or more external (peripheral) components, devices, and/or subsystems. In some implementations, the interface circuitry **608** may be used to transfer data between the compute node **600** and another computer device (e.g., remote system **690**, client system **650**, and/or the like) via a wired and/or wireless connection. is used to connect additional devices or subsystems. The interface circuitry **608**, is part of, or includes circuitry that enables the exchange of information between two or more components or devices such as, for example, between the compute node **600** and one or more external devices. The external devices include sensor circuitry **641**, actuator circuitry **642**, positioning circuitry **643**, and other I/O devices **640**, but may also include other devices or subsystems not shown by FIG. **6**. Access to various such devices/components may be implementation specific, and may vary from implementation to implementation. As examples, the interface circuitry **608** can be embodied as, or otherwise include, one or more hardware interfaces such as, for example, buses (e.g., including an expansion buses, IXs, and/or the like), input/output (I/O) interfaces, peripheral component interfaces (e.g., peripheral cards and/or the like), network interface cards, host bus adapters, and/or mezzanines, and/or the like. In some implementations, the interface circuitry **608** includes one or more interface controllers and connectors that interconnect one or more of the processor circuitry **601**, memory circuitry **603**, storage circuitry **604**, communication circuitry **607**, and the other components of compute node **600** and/or to one or more external (peripheral) components, devices, and/or subsystems. Additionally or alternatively, the interface circuitry **608** includes a sensor hub or other like elements to obtain and process collected sensor data and/or actuator data before being passed to other components of the compute node **600**.

(123) Additionally or alternatively, the interface circuitry **608** and/or the IX **606** can be embodied as, or otherwise include memory controllers, storage controllers (e.g., redundant array of independent disk (RAID) controllers and/or the like), baseboard management controllers (BMCs), input/output (I/O) controllers, host controllers, and/or the like. Examples of I/O controllers include integrated memory controller (IMC), memory management unit (MMU), input-output MMU (IOMMU), sensor hub, General Purpose I/O (GPIO) controller, PCIe endpoint (EP) device, direct media interface (DMI) controller, Intel® Flexible Display Interface (FDI) controller(s), VGA interface controller(s), Peripheral Component Interconnect Express (PCIe) controller(s), universal serial bus (USB) controller(s), FireWire controller(s), Thunderbolt controller(s), FPGA Mezzanine Card (FMC), eXtensible Host Controller Interface (xHCI) controller(s), Enhanced Host Controller Interface (EHCI) controller(s), Serial Peripheral Interface (SPI) controller(s), Direct Memory Access (DMA) controller(s), hard drive controllers (e.g., Serial AT Attachment (SATA) host bus adapters/controllers, Intel® Rapid Storage Technology (RST), and/or the like), Advanced Host Controller Interface (AHCI), a Low Pin Count (LPC) interface (bridge function), Advanced Programmable Interrupt Controller(s) (APIC), audio controller(s), SMBus host interface controller(s), UART controller(s), and/or the like. Some of these controllers may be part of, or otherwise applicable to the memory circuitry **603**, storage circuitry **604**, and/or IX **606** as well. As examples, the connectors include electrical connectors, ports, slots, jumpers, receptacles, modular connectors, coaxial cable and/or BNC connectors, optical fiber connectors, PCB mount connectors, inline/cable connectors,

chassis/panels/controllers, peripheral component interfaces (e.g., non-volatile memory ports, USB ports, Ethernet ports, audio jacks, power supply interfaces, on-board diagnostic (OBD) ports, and so forth), and/or the like.

(124) The sensor(s) **641** (also referred to as “sensor circuitry **641**”) includes devices, modules, or subsystems whose purpose is to detect events or changes in its environment and send the information (sensor data) about the detected events to some other a device, module, subsystem, and/or the like. Individual sensors **641** may be exteroceptive sensors (e.g., sensors that capture and/or measure environmental phenomena and/external states), proprioceptive sensors (e.g., sensors that capture and/or measure internal states of the compute node **600** and/or individual components of the compute node **600**), and/or exproprioceptive sensors (e.g., sensors that capture, measure, or correlate internal states and external states). Examples of such sensors **641** include inertia measurement units (IMU), microelectromechanical systems (MEMS) or nanoelectromechanical systems (NEMS), level sensors, flow sensors, temperature sensors (e.g., thermistors, including sensors for measuring the temperature of internal components and sensors for measuring temperature external to the compute node **600**), pressure sensors, barometric pressure sensors, gravimeters, altimeters, image capture devices (e.g., visible light cameras, thermographic camera and/or thermal imaging camera (TIC) systems, forward-looking infrared (FLIR) camera systems, radiometric thermal camera systems, active infrared (IR) camera systems, ultraviolet (UV) camera systems, and/or the like), light detection and ranging (LiDAR) sensors, proximity sensors (e.g., IR radiation detector and/or the like), depth sensors, ambient light sensors, optical light sensors, ultrasonic transceivers, microphones, inductive loops, force and/or load sensors, remote charge converters (RCC), rotor speed and position sensor(s), fiber optic gyro (FOG) inertial sensors, Attitude & Heading Reference Unit (AHRU), fibre Bragg grating (FBG) sensors and interrogators, tachometers, engine temperature gauges, pressure gauges, transformer sensors, airspeed-measurement meters, speed indicators, and/or the like. The IMUs, MEMS, and/or NEMS can include, for example, one or more 3-axis accelerometers, one or more 3-axis gyroscopes, one or more magnetometers, one or more compasses, one or more barometers, and/or the like. Additionally or alternatively, the sensors **641** can include sensors of various compute components such as, for example, digital thermal sensors (DTS) of respective processors/cores, thermal sensor on-die (TSOD) of respective dual inline memory modules (DIMMs), baseboard thermal sensors, and/or any other sensor(s), such as any of those discussed herein.

(125) The actuators **642** allow the compute node **600** to change its state, position, and/or orientation, or move or control a mechanism or system. The actuators **642** comprise electrical and/or mechanical devices for moving or controlling a mechanism or system, and converts energy (e.g., electric current or moving air and/or liquid) into some kind of motion. The compute node **600** is configured to operate one or more actuators **642** based on one or more captured events, instructions, control signals, and/or configurations received from a service provider **690**, client device **650**, and/or other components of the compute node **600**. As examples, the actuators **642** can be or include any number and combination of the following: soft actuators (e.g., actuators that changes its shape in response to a stimuli such as, for example, mechanical, thermal, magnetic, and/or electrical stimuli), hydraulic actuators, pneumatic actuators, mechanical actuators, electromechanical actuators (EMAs), microelectromechanical actuators, electrohydraulic actuators, linear actuators, linear motors, rotary motors, DC motors, stepper motors, servomechanisms, electromechanical switches, electromechanical relays (EMRs), power switches, valve actuators, piezoelectric actuators and/or biomorphs, thermal biomorphs, solid state actuators, solid state relays (SSRs), shape-memory alloy-based actuators, electroactive polymer-based actuators, relay driver integrated circuits (ICs), solenoids, impactive actuators/mechanisms (e.g., jaws, claws, tweezers, clamps, hooks, mechanical fingers, humaniform dexterous robotic hands, and/or other gripper mechanisms that physically grasp by direct impact upon an object), propulsion actuators/mechanisms (e.g., wheels, axles, thrusters, propellers, engines, motors (e.g., those discussed previously), clutches, and/or the like), projectile actuators/mechanisms (e.g., mechanisms that shoot or propel objects or elements), controllers of the compute node **600** or components thereof (e.g., host controllers, cooling element controllers,

baseboard management controller (BMC), platform controller hub (PCH), uncore components (e.g., shared last level cache (LLC) cache, caching agent (Cbo), integrated memory controller (IMC), home agent (HA), power control unit (PCU), configuration agent (Ubox), integrated I/O controller (IIO), and interconnect (IX) link interfaces and/or controllers), and/or any other components such as any of those discussed herein), audible sound generators, visual warning devices, virtual instrumentation and/or virtualized actuator devices, and/or other like components or devices. In some examples, such as when the compute node **600** is part of a robot or drone, the actuator(s) **642** can be embodied as or otherwise represent one or more end effector tools, conveyor motors, and/or the like.

(126) The positioning circuitry **643** includes circuitry to receive and decode signals transmitted/broadcasted by a positioning network of a GNSS. Examples of such navigation satellite constellations include United States' GPS, Russia's Global Navigation System (GLONASS), the European Union's Galileo system, China's BeiDou Navigation Satellite System, a regional navigation system or GNSS augmentation system (e.g., Navigation with Indian Constellation (NAVIC), Japan's Quasi-Zenith Satellite System (QZSS), France's Doppler Orbitography and Radio-positioning Integrated by Satellite (DORIS), and/or the like), and/or the like. The positioning circuitry **643** comprises various hardware elements (e.g., including hardware devices such as switches, filters, amplifiers, antenna elements, and/or the like to facilitate OTA communications) to communicate with components of a positioning network, such as navigation satellite constellation nodes. In some implementations, the positioning circuitry **643** may include a Micro-Technology for Positioning, Navigation, and Timing (Micro-PNT) IC that uses a master timing clock to perform position tracking/estimation without GNSS assistance. The positioning circuitry **643** may also be part of, or interact with, the communication circuitry **607** to communicate with the nodes and components of the positioning network. The positioning circuitry **643** may also provide position data and/or time data to the application circuitry, which may use the data to synchronize operations with various infrastructure (e.g., radio base stations), for turn-by-turn navigation, and/or the like.

(127) NFC circuitry **646** comprises one or more hardware devices and software modules configurable or operable to read electronic tags and/or connect with another NFC-enabled device (also referred to as an “NFC touchpoint”). NFC is commonly used for contactless, short-range communications based on radio frequency identification (RFID) standards, where magnetic field induction is used to enable communication between NFC-enabled devices. The one or more hardware devices may include an NFC controller coupled with an antenna element and a processor coupled with the NFC controller. The NFC controller may be a chip providing NFC functionalities to the NFC circuitry **646**. The software modules may include NFC controller firmware and an NFC stack. The NFC stack may be executed by the processor to control the NFC controller, and the NFC controller firmware may be executed by the NFC controller to control the antenna element to emit an RF signal. The RF signal may power a passive NFC tag (e.g., a microchip embedded in a sticker or wristband) to transmit stored data to the NFC circuitry **646**, or initiate data transfer between the NFC circuitry **646** and another active NFC device (e.g., a smartphone or an NFC-enabled point-of-sale terminal) that is proximate to the computing system **600** (or the NFC circuitry **646** contained therein). The NFC circuitry **646** may include other elements, such as those discussed herein. Additionally, the NFC circuitry **646** may interface with a secure element (e.g., TEE **690**) to obtain payment credentials and/or other sensitive/secure data to be provided to the other active NFC device. Additionally or alternatively, the NFC circuitry **646** and/or some other element may provide Host Card Emulation (HCE), which emulates a physical secure element.

(128) The I/O device(s) **640** may be present within, or connected to, the compute node **600**. The I/O devices **640** include input device circuitry and output device circuitry including one or more user interfaces designed to enable user interaction with the compute node **600** and/or peripheral component interfaces designed to enable peripheral component interaction with the compute node **600**. The input device circuitry includes any physical or virtual means for accepting an input including, inter alia, one or more physical or virtual buttons, a physical or virtual keyboard, keypad, mouse, touchpad, touchscreen, microphones, scanner, headset, and/or the like. In implementations

where the input device circuitry includes a capacitive, resistive, or other like touch-surface, a touch signal may be obtained from circuitry of the touch-surface. The touch signal may include information regarding a location of the touch (e.g., one or more sets of (x,y) coordinates describing an area, shape, and/or movement of the touch), a pressure of the touch (e.g., as measured by area of contact between a user's finger or a deformable stylus and the touch-surface, or by a pressure sensor), a duration of contact, any other suitable information, or any combination of such information. In these implementations, one or more apps operated by the processor circuitry **601** may identify gesture(s) based on the information of the touch signal, and utilizing a gesture library that maps determined gestures with specified actions.

(129) The output device circuitry is used to show or convey information, such as sensor readings, actuator position(s), or other like information. Data and/or graphics may be displayed on one or more user interface components of the output device circuitry. The output device circuitry may include any number and/or combinations of audio or visual display, including, inter alia, one or more simple visual outputs/indicators (e.g., binary status indicators (e.g., light emitting diodes (LEDs)) and multi-character visual outputs, or more complex outputs such as display devices or touchscreens (e.g., Liquid Chrystal Displays (LCD), LED and/or OLED displays, quantum dot displays, projectors, and/or the like), with the output of characters, graphics, multimedia objects, and/or the like being generated or produced from operation of the compute node **600**. The output device circuitry may also include speakers or other audio emitting devices, printer(s), and/or the like. In some implementations, the sensor circuitry **641** may be used as the input device circuitry (e.g., an image capture device, motion capture device, and/or the like) and one or more actuators **642** may be used as the output device circuitry (e.g., an actuator to provide haptic feedback and/or the like). In another example, near-field communication (NFC) circuitry comprising an NFC controller coupled with an antenna element and a processing device may be included to read electronic tags and/or connect with another NFC-enabled device. Peripheral component interfaces may include, but are not limited to, a non-volatile memory port, a universal serial bus (USB) port, an audio jack, a power supply interface, and/or the like.

(130) A battery **624** may be coupled to the compute node **600** to power the compute node **600**, which may be used in implementations where the compute node **600** is not in a fixed location, such as when the compute node **600** is a mobile device or laptop. The battery **624** may be a lithium ion battery, a lead-acid automotive battery, or a metal-air battery, such as a zinc-air battery, an aluminum-air battery, a lithium-air battery, a lithium polymer battery, and/or the like. In implementations where the compute node **600** is mounted in a fixed location, such as when the system is implemented as a server computer system, the compute node **600** may have a power supply coupled to an electrical grid. In these implementations, the compute node **600** may include power tee circuitry to provide for electrical power drawn from a network cable to provide both power supply and data connectivity to the compute node **600** using a single cable.

(131) Power management integrated circuitry (PMIC) **622** may be included in the compute node **600** to track the state of charge (SoCh) of the battery **624**, and to control charging of the compute node **600**. The PMIC **622** may be used to monitor other parameters of the battery **624** to provide failure predictions, such as the state of health (SoH) and the state of function (SoF) of the battery **624**. The PMIC **622** may include voltage regulators, surge protectors, power alarm detection circuitry. The power alarm detection circuitry may detect one or more of brown out (under-voltage) and surge (over-voltage) conditions. The PMIC **622** may communicate the information on the battery **624** to the processor circuitry **601** over the IX **606**. The PMIC **622** may also include an analog-to-digital (ADC) convertor that allows the processor circuitry **601** to directly monitor the voltage of the battery **624** or the current flow from the battery **624**. The battery parameters may be used to determine actions that the compute node **600** may perform, such as transmission frequency, mesh network operation, sensing frequency, and/or the like.

(132) A power block **620**, or other power supply coupled to an electrical grid, may be coupled with the PMIC **622** to charge the battery **624**. In some examples, the power block **620** may be replaced

with a wireless power receiver to obtain the power wirelessly, for example, through a loop antenna in the compute node **600**. In these implementations, a wireless battery charging circuit may be included in the PMIC **622**. The specific charging circuits chosen depend on the size of the battery **624** and the current required.

(133) The compute node **600** may include any combinations of the components shown by FIG. 6; however, some of the components shown may be omitted, additional components may be present, and different arrangement of the components shown may occur in other implementations. In one example where the compute node **600** is or is part of a server computer system, the battery **624**, communication circuitry **607**, the sensors **641**, actuators **642**, and/or positioning circuitry **643**, and possibly some or all of the I/O devices **640**, may be omitted.

(134) As mentioned previously, the memory circuitry **603** and/or the storage circuitry **604** are embodied as transitory or non-transitory computer-readable media (e.g., CRM **602**). The CRM **602** is suitable for use to store instructions (or data that creates the instructions) that cause an apparatus (such as any of the devices/components/systems described w.r.t FIGS. 1-7), in response to execution of the instructions (e.g., instructions **601x**, **603x**, **604x**) by the compute node **600** (e.g., one or more processors **601**), to practice selected aspects of the present disclosure. The CRM **602** can include a number of programming instructions (e.g., instructions **601x**, **603x**, **604x**) (or data to create the programming instructions). The programming instructions are configured to enable a device (e.g., any of the devices/components/systems described w.r.t FIGS. 1-7), in response to execution of the programming instructions, to perform various programming operations associated with operating system functions, one or more apps, and/or aspects of the present disclosure (including various programming operations associated with FIGS. 1-7). The programming instructions may correspond to any of the computational logic **604x**, instructions **603x** and **601x** discussed previously.

(135) Additionally or alternatively, programming instructions (or data to create the instructions) may be disposed on multiple CRM **602**. In alternate implementations, programming instructions (or data to create the instructions) may be disposed on computer-readable transitory storage media, such as signals. The programming instructions embodied by a machine-readable medium **602** may be transmitted or received over a communications network using a transmission medium via a network interface device (e.g., communication circuitry **607** and/or NIC **607c** of FIG. 6) utilizing any one of a number of communication protocols and/or data transfer protocols such as any of those discussed herein.

(136) Any combination of one or more computer usable or CRM **602** may be utilized as or instead of the CRM **602**. The computer-usable or computer-readable medium **602** may be, for example, but not limited to one or more electronic, magnetic, optical, electromagnetic, infrared, or semiconductor systems, apparatuses, devices, or propagation media. For instance, the CRM **602** may be embodied by devices described for the storage circuitry **604** and/or memory circuitry **603** described previously and/or as discussed elsewhere in the present disclosure. In the context of the present disclosure, a computer-usable or computer-readable medium **602** may be any medium that can contain, store, communicate, propagate, or transport the program (or data to create the program) for use by or in connection with the instruction execution system, apparatus, or device. The computer-usable medium **602** may include a propagated data signal with the computer-usable program code (e.g., including programming instructions) or data to create the program code embodied therewith, either in baseband or as part of a carrier wave. The computer usable program code or data to create the program may be transmitted using any appropriate medium, including but not limited to wireless, wireline, optical fiber cable, RF, and/or the like.

(137) Additionally or alternatively, the program code (or data to create the program code) described herein may be stored in one or more of a compressed format, an encrypted format, a fragmented format, a packaged format, and/or the like. Program code (e.g., programming instructions) or data to create the program code as described herein may require one or more of installation, modification, adaptation, updating, combining, supplementing, configuring, decryption, decompression, unpacking, distribution, reassignment, and/or the like in order to make them directly readable and/or executable

by a computing device and/or other machine. For example, the program code or data to create the program code may be stored in multiple parts, which are individually compressed, encrypted, and stored on separate computing devices, wherein the parts when decrypted, decompressed, and combined form a set of executable instructions that implement the program code or the data to create the program code, such as those described herein. In another example, the program code or data to create the program code may be stored in a state in which they may be read by a computer, but require addition of a library (e.g., a dynamic link library), a software development kit (SDK), an API, and/or the like in order to execute the instructions on a particular computing device or other device. In another example, the program code or data to create the program code may need to be configured (e.g., settings stored, data input, network addresses recorded, and/or the like) before the program code or data to create the program code can be executed/used in whole or in part. In this example, the program code (or data to create the program code) may be unpacked, configured for proper execution, and stored in a first location with the configuration instructions located in a second location distinct from the first location. The configuration instructions can be initiated by an action, trigger, or instruction that is not co-located in storage or execution location with the instructions enabling the disclosed techniques. Accordingly, the disclosed program code or data to create the program code are intended to encompass such machine readable instructions and/or program(s) or data to create such machine readable instruction and/or programs regardless of the particular format or state of the machine readable instructions and/or program(s) when stored or otherwise at rest or in transit.

(138) The computer program code for carrying out operations of the present disclosure, including, for example, programming instructions, computational logic **604x**, instructions **603x**, and/or instructions **601x**, may be written in any combination of one or more programming languages, including an object oriented programming language (e.g., Python, PyTorch, Ruby, Scala, Smalltalk, Java™, Java Servlets, Kotlin, C++, C#, and/or the like), a procedural programming language (e.g., the “C” programming language, Go (or “Golang”), and/or the like), a scripting language (e.g., ECMAScript, JavaScript, Server-Side JavaScript (SSJS), PHP, Pearl, Python, PyTorch, Ruby, Lua, Torch/Lua with Just-In Time compiler (LuaJIT), Accelerated Mobile Pages Script (AMPscript), VBScript, and/or the like), a markup language (e.g., hypertext markup language (HTML), extensible markup language (XML), wiki markup or Wikitext, User Interface Markup Language (UIML), and/or the like), a data interchange format/definition (e.g., Java Script Object Notion (JSON), Apache® MessagePack™, and/or the like), a stylesheet language (e.g., Cascading Stylesheets (CSS), extensible stylesheet language (XSL), and/or the like), an interface definition language (IDL) (e.g., Apache® Thrift, Abstract Syntax Notation One (ASN.1), Google® Protocol Buffers (protobuf), efficient XML interchange (EXI), and/or the like), a web framework (e.g., Active Server Pages Network Enabled Technologies (ASP.NET), Apache® Wicket, Asynchronous JavaScript and XML (Ajax) frameworks, Django, Jakarta Server Faces (JSF; formerly JavaServer Faces), Jakarta Server Pages (JSP; formerly JavaServer Pages), Ruby on Rails, web toolkit, and/or the like), a template language (e.g., Apache® Velocity, Tea, Django template language, Mustache, Template Attribute Language (TAL), Extensible Stylesheet Language Transformations (XSLT), Thymeleaf, Facelet view, and/or the like), and/or some other suitable programming languages including proprietary programming languages and/or development tools, or any other languages or tools such as those discussed herein. It should be noted that some of the aforementioned languages, tools, and/or technologies may be classified as belonging to multiple types of languages/technologies or otherwise classified differently than described previously. The computer program code for carrying out operations of the present disclosure may also be written in any combination of the programming languages discussed herein. The program code may execute entirely on the compute node **600**, partly on the compute node **600** as a stand-alone software package, partly on the compute node **600** and partly on a remote computer, or entirely on the remote computer. In the latter scenario, the remote computer may be connected to the compute node **600** through any type of network (e.g., network **699**).

(139) The network **699** comprises a set of computers that share resources located on or otherwise

provided by a set of network nodes. The set of computers making up the network **699** can use one or more communication protocols and/or access technologies (such as any of those discussed herein) to communicate with one another and/or with other computers outside of the network **699** (e.g., compute node **600**, client device **650**, and/or remote system **690**), and may be connected with one another or otherwise arranged in a variety of network topologies.

(140) As examples, the network **699** can represent the Internet, one or more cellular networks, local area networks (LANs), wide area networks (WANs), wireless LANs (WLANs), Transfer Control Protocol (TCP)/Internet Protocol (IP)-based networks, Personal Area Networks (e.g., Bluetooth®, [IEEE802154], and/or the like), Digital Subscriber Line (DSL) and/or cable networks, data networks, cloud computing services, edge computing networks, proprietary and/or enterprise networks, and/or any combination thereof. In some implementations, the network **699** is associated with network operator who owns or controls equipment and other elements necessary to provide network-related services, such as one or more network access nodes (NANs) (e.g., base stations, access points, and/or the like), one or more servers for routing digital data or telephone calls (e.g., a core network or backbone network), and/or the like. Other networks can be used instead of or in addition to the Internet, such as an intranet, an extranet, a virtual private network (VPN), an enterprise network, a non-TCP/IP based network, any LAN, WLAN, WAN, and/or the like. In either implementation, the network **699** comprises computers, network connections among various computers (e.g., between the compute node **600**, client device(s) **650**, remote system **690**, and/or the like), and software routines to enable communication between the computers over respective network connections. Connections to the network **699** (and/or compute nodes therein) may be via a wired and/or a wireless connections using the various communication protocols such as any of those discussed herein. More than one network may be involved in a communication session between the illustrated devices. Connection to the network **699** may require that the computers execute software routines that enable, for example, the layers of the OSI model of computer networking or equivalent in a wireless (or cellular) phone network.

(141) The remote system **690** (also referred to as a “service provider”, “application server(s)”, “app server(s)”, “external platform”, and/or the like) comprises one or more physical and/or virtualized computing systems owned and/or operated by a company, enterprise, and/or individual that hosts, serves, and/or otherwise provides information objects to one or more users (e.g., compute node **600**). The physical and/or virtualized systems include one or more logically or physically connected servers and/or data storage devices distributed locally or across one or more geographic locations. Generally, the remote system **690** uses IP/network resources to provide InOb(s) such as electronic documents, webpages, forms, apps (e.g., native apps, web apps, mobile apps, and/or the like), data, services, web services, media, and/or content to different user/client devices **650**. As examples, the service provider **690** may provide mapping and/or navigation services; cloud computing services; search engine services; social networking, microblogging, and/or message board services; content (media) streaming services; e-commerce services; blockchain services; communication services such as Voice-over-Internet Protocol (VoIP) sessions, text messaging, group communication sessions, and/or the like; immersive gaming experiences; and/or other like services. In some examples, the remote system **690** corresponds to the NFT/blockchain service **250**, and the system **600** and/or client device **650** corresponds to user devices **310**, **360**, **650**. The user/client devices **310**, **360**, **650** that utilize services provided by remote system **690** may be referred to as “subscribers” and/or the like. Although FIG. **6** shows only a single remote system **690**, the remote system **690** may represent multiple remote system **690**, each of which may have their own subscribing users.

(142) Furthermore, various aspects of the present disclosure may take the form of a computer program product or data to create the computer program, with the computer program or data embodied in any tangible or non-transitory medium of expression having the computer-usable program code (or data to create the computer program) embodied in the medium.

3. Example Implementations

(143) FIG. **7** shows processes **700** and **710** for practicing aspects of the present disclosure. Process

700 is a process that can be used to provide NFT ID services, which may be performed by the NFT ID engine **350** discussed previously. Process **700** begins at operation **701** where the NFT ID engine **350** receives a set of inputs **401** from one or more data sources (e.g., user **310**, admin **360**, and/or one or more SPPs or third party platforms). At operation **702**, the NFT ID engine **350** stores or causes storage of the set of inputs **401** (e.g., ID info **513**) as metadata **413**. The NFT ID engine **350** may store the set of inputs **401** (e.g., ID info **513**) in file system **560** via API(s) **555**. At operation **703**, the NFT ID engine **350** executes a smart contract **411** to cause an NFT ID **402** to be minted based on the metadata **413** and according to a set of parameters defined by the smart contract **411**.

(144) Process **700** is a process that can be used to provide NFT ID services, which may be performed by the admin **360** discussed previously. Process **710** begins at operation **711** where the admin **360** provides a set of inputs **401** (e.g., ID info **513**) to an NFT ID service **250** (e.g., NFT ID engine **350**). At operation **712**, the admin **360** obtains a minted NFT ID **402** based on the set of inputs **401** (e.g., ID info **513**), and at operation **713**, the admin **360** issues the minted NFT ID **402** to a subject of the minted NFT ID **402** (e.g., user **310**).

(145) Additional examples of the presently described method, system, and device embodiments include the following, non-limiting implementations. Each of the following non-limiting examples may stand on its own or may be combined in any permutation or combination with any one or more of the other examples provided below or throughout the present disclosure.

(146) Example [0142] includes a method for providing non-fungible token (NFT) identity (ID) services, the method comprising: receiving a set of inputs from a set of data sources; causing storage of the set of inputs as metadata; and executing a smart contract to cause an NFT ID to be minted based on the metadata and according to a set of parameters defined by the smart contract.

(147) Example [0143] includes the method of example [0142] and/or some other examples herein, wherein causing storage of the set of inputs as metadata includes: sending the set of inputs to a distributed file system via an application programming interface (API).

(148) Example [0144] includes the method of examples [0142]-[0143] and/or some other examples herein, wherein the method includes: detecting a trigger to mint the NFT ID for a user, wherein the trigger includes transaction data to be used for executing the smart contract or the transaction data is generated in response to detection of the trigger; and executing the smart contract based on the detected trigger.

(149) Example [0145] includes the method of example [0144] and/or some other examples herein, wherein the transaction data includes one or more of a token ID for the NFT ID, ownership information of an owner of the NFT ID, a reference to a storage location of the metadata in a distributed file system, and supply information indicating a number and type of NFT IDs to be minted.

(150) Example [0146] includes the method of example [0145] and/or some other examples herein, wherein the transaction data includes a token name and a token symbol, and the method includes: generating the reference based on the token name and the token symbol.

(151) Example [0147] includes the method of example [0146] and/or some other examples herein, wherein the token name is a name of an entity for which the NFT ID is to be created, and the token symbol is a code representing the entity or a geographic region for which the NFT ID is to be created.

(152) Example [0148] includes the method of examples [0145]-[0147] and/or some other examples herein, wherein the method includes: sending the transaction data to an NFT framework to perform a minting process to mint the NFT ID.

(153) Example [0149] includes the method of example [0148] and/or some other examples herein, wherein the minting process is to cause the NFT framework to: store the reference to the storage location of the metadata in the NFT ID, not store the set of inputs or the metadata in a blockchain, and cause the NFT ID, when minted, to be recorded as a transaction in a block on a blockchain.

(154) Example [0150] includes the method of examples [0148]-[0149] and/or some other examples herein, wherein the method includes: receiving a minted NFT ID from the NFT framework; and issuing the minted NFT ID to an administrator (“admin”) or to a client associated with the user.

(155) Example [0151] includes the method of example [0150] and/or some other examples herein, wherein the issuance of the minted NFT ID is recorded as a transaction in a block on a blockchain.

(156) Example [0152] includes the method of example [0151] and/or some other examples herein, wherein issuance of the minted NFT ID from the admin to the user is recorded as another transaction in another block on the blockchain.

(157) Example [0153] includes the method of examples [0150]-[0152] and/or some other examples herein, wherein the set of data sources include one or more of the admin, the client, and one or more third party platforms.

(158) Example [0154] includes the method of example [0153] and/or some other examples herein, wherein the client is a standalone wallet device or a client application (app), a web app, or a digital wallet app operating on a client device; and the admin is another standalone wallet device or another client app, another web app, or another digital wallet app operating on another client device.

(159) Example [0155] includes the method of examples [0142]-[0154] and/or some other examples herein, wherein the method includes: generating the smart contract based on a configuration obtained from an admin.

(160) Example [0156] includes the method of examples [0142]-[0155] and/or some other examples herein, wherein the configuration includes one or more of a subset of inputs of the set of inputs to be provided by individual users, a subset of inputs of the set of inputs to be provided by individual admins, content types or formats of the set of inputs, a list of network addresses, address ranges, or domains that are permitted to access the NFT ID services, one or more types of apps that are permitted to access the NFT ID services, one or more device types that are permitted to be used to mint/create NFT IDs, cryptographic mechanisms to be used for storing the set of inputs, cryptographic mechanisms to be used for minting the NFT ID, content types or formats of minted NFT IDs, a location or range of locations for storing the metadata, a location or range of locations for storing minted NFT IDs, parameters or criteria for transferring NFT IDs, a list of verification nodes, and parameters or criteria for blockchain nodes to act as verification nodes.

(161) Example [0157] includes the method of examples [0142]-[0156] and/or some other examples herein, wherein the set of inputs include one or more of one or more ID documents, knowledge-based authentication (KBA) data or know your customer (KYC) data, one or more financial institution documents, one or more authentication credentials or digital certificates, biometric data, timestamp of when the NFT ID service is accessed, geolocation info associated with access of the NFT ID service, client app data, third party platforms data, device/system data, and network-related data.

(162) Example [0158] includes one or more computer readable media comprising instructions, wherein execution of the instructions by processor circuitry is to cause the processor circuitry to perform the method of examples [0142]-[0157] and/or some other example(s) herein.

(163) Example [0159] includes a computer program comprising the instructions of example [0158] and/or some other example(s) herein.

(164) Example [0160] includes an Application Programming Interface defining functions, methods, variables, data structures, and/or protocols for the computer program of example [0159] and/or some other example(s) herein.

(165) Example [0161] includes an apparatus comprising circuitry loaded with the instructions of example [0158] and/or some other example(s) herein.

(166) Example [0162] includes an apparatus comprising circuitry operable to run the instructions of example [0158] and/or some other example(s) herein.

(167) Example [0163] includes an integrated circuit comprising one or more of the processor circuitry and the one or more computer readable media of example [0158] and/or some other example(s) herein.

(168) Example [0164] includes a computing system comprising the one or more computer readable media and the processor circuitry of example [0158] and/or some other example(s) herein.

(169) Example [0165] includes an apparatus comprising means for executing the instructions of example [0158] and/or some other example(s) herein.

(170) Example [0166] includes a signal generated as a result of executing the instructions of example [0158] and/or some other example(s) herein.

(171) Example [0167] includes a data unit generated as a result of executing the instructions of example [0158] and/or some other example(s) herein.

(172) Example [0168] includes the data unit of example [0167] and/or some other example(s) herein, wherein the data unit is a datagram, packet, frame, subframe, segment, Protocol Data Unit (PDU), Service Data Unit (SDU), message, data block, data chunk, partition, fragment, and/or database object.

(173) Example [0169] includes a signal encoded with the data unit of examples [0167]-[0168] and/or some other example(s) herein.

(174) Example [0170] includes an electromagnetic signal carrying the instructions of example [0158] and/or some other example(s) herein.

(175) Example [0171] includes an apparatus comprising means for performing the method of examples [0142]-[0157] and/or some other example(s) herein.

4. Terminology

(176) As used herein, the singular forms “a,” “an” and “the” are intended to include plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specific the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operation, elements, components, and/or groups thereof. The phrase “A and/or B” means (A), (B), or (A and B). For the purposes of the present disclosure, the phrase “A, B, and/or C” means (A), (B), (C), (A and B), (A and C), (B and C), or (A, B and C). The phrase “X(s)” means one or more X or a set of X. The description may use the phrases “in an embodiment,” “In some embodiments,” “in one implementation,” “In some implementations,” “in some examples”, and/or the like, each of which may refer to one or more of the same or different embodiments, implementations, and/or examples. Furthermore, the terms “comprising,” “including,” “having,” and/or the like, as used w.r.t the present disclosure, are synonymous.

(177) The terms “coupled,” “communicatively coupled,” along with derivatives thereof are used herein. The term “coupled” may mean two or more elements are in direct physical or electrical contact with one another, may mean that two or more elements indirectly contact each other but still cooperate or interact with each other, and/or may mean that one or more other elements are coupled or connected between the elements that are said to be coupled with each other. The term “directly coupled” may mean that two or more elements are in direct contact with one another. The term “communicatively coupled” may mean that two or more elements may be in contact with one another by a means of communication including through a wire or other interconnect connection, through a wireless communication channel or link, and/or the like.

(178) The term “establish” or “establishment” at least in some examples refers to (partial or in full) acts, tasks, operations, and/or the like, related to bringing or the readying the bringing of something into existence either actively or passively (e.g., exposing a device identity or entity identity). Additionally or alternatively, the term “establish” or “establishment” at least in some examples refers to (partial or in full) acts, tasks, operations, and/or the like, related to initiating, starting, or warming communication or initiating, starting, or warming a relationship between two entities or elements (e.g., establish a session, establish a session, and/or the like). Additionally or alternatively, the term “establish” or “establishment” at least in some examples refers to initiating something to a state of working readiness. The term “established” at least in some examples refers to a state of being operational or ready for use (e.g., full establishment). Furthermore, any definition for the term “establish” or “establishment” defined in any specification or standard can be used for purposes of the present disclosure and such definitions are not disavowed by any of the aforementioned definitions.

(179) The term “obtain” at least in some examples refers to (partial or in full) acts, tasks, operations,

and/or the like, or intercepting, movement, copying, retrieval, or acquisition (e.g., from a memory, an interface, or a buffer), on the original packet stream or on a copy (e.g., a new instance) of the packet stream. Other aspects of obtaining or receiving may involving instantiating, enabling, or controlling the ability to obtain or receive a stream of packets (or the following parameters and templates or template values).

(180) The term “receipt” at least in some examples refers to any action (or set of actions) involved with receiving or obtaining an object, data, data unit, and/or the like, and/or the fact of the object, data, data unit, and/or the like being received. The term “receipt” at least in some examples refers to an object, data, data unit, and/or the like, being pushed to a device, system, element, and/or the like (e.g., often referred to as a push model), pulled by a device, system, element, and/or the like (e.g., often referred to as a pull model), and/or the like.

(181) The term “element” at least in some examples refers to a unit that is indivisible at a given level of abstraction and has a clearly defined boundary, wherein an element may be any type of entity including, for example, one or more devices, systems, controllers, network elements, modules, and so forth, or combinations thereof. The term “entity” at least in some examples refers to a distinct element of a component, architecture, platform, device, and/or system. Additionally or alternatively, the term “entity” at least in some examples refers to information transferred as a payload.

(182) The term “measurement” at least in some examples refers to the observation and/or quantification of attributes of an object, event, or phenomenon. Additionally or alternatively, the term “measurement” at least in some examples refers to a set of operations having the object of determining a measured value or measurement result, and/or the actual instance or execution of operations leading to a measured value. Additionally or alternatively, the term “measurement” at least in some examples refers to data recorded during testing.

(183) The term “metric” at least in some examples refers to a quantity produced in an assessment of a measured value. Additionally or alternatively, the term “metric” at least in some examples refers to data derived from a set of measurements. Additionally or alternatively, the term “metric” at least in some examples refers to set of events combined or otherwise grouped into one or more values. Additionally or alternatively, the term “metric” at least in some examples refers to a combination of measures or set of collected data points. Additionally or alternatively, the term “metric” at least in some examples refers to a standard definition of a quantity, produced in an assessment of performance and/or reliability of the network, which has an intended utility and is carefully specified to convey the exact meaning of a measured value.

(184) The term “signal” at least in some examples refers to an observable change in a quality and/or quantity. Additionally or alternatively, the term “signal” at least in some examples refers to a function that conveys information about of an object, event, or phenomenon. Additionally or alternatively, the term “signal” at least in some examples refers to any time varying voltage, current, or electromagnetic wave that may or may not carry information. The term “digital signal” at least in some examples refers to a signal that is constructed from a discrete set of waveforms of a physical quantity so as to represent a sequence of discrete values.

(185) The terms “ego” (as in, e.g., “ego device”) and “subject” (as in, e.g., “data subject”) at least in some examples refers to an entity, element, device, system, and/or the like, that is under consideration or being considered. The terms “neighbor” and “proximate” (as in, e.g., “proximate device”) at least in some examples refers to an entity, element, device, system, and/or the like, other than an ego device or subject device.

(186) The term “circuitry” at least in some examples refers to a circuit or system of multiple circuits configured to perform a particular function in an electronic device. The circuit or system of circuits may be part of, or include one or more hardware components, such as a logic circuit, a processor (shared, dedicated, or group) and/or memory (shared, dedicated, or group), an application-specific integrated circuit (ASIC), field-programmable gate array (FPGA), programmable logic controller (PLC), single-board computer (SBC), system on chip (SoC), system in package (SiP), multi-chip package (MCP), digital signal processor (DSP), and/or the like, that are configured to provide the

described functionality. In addition, the term “circuitry” may also refer to a combination of one or more hardware elements with the program code used to carry out the functionality of that program code. Some types of circuitry may execute one or more software or firmware programs to provide at least some of the described functionality. Such a combination of hardware elements and program code may be referred to as a particular type of circuitry.

(187) The term “compute node” or “compute device” at least in some examples refers to an identifiable entity implementing an aspect of computing operations, whether part of a larger system, distributed collection of systems, or a standalone apparatus. In some examples, a compute node may be referred to as a “computing device”, “computing system”, and/or the like, whether in operation as a client, server, or intermediate entity. Specific implementations of a compute node may be incorporated into a server, base station, gateway, road side unit, on-premise unit, user equipment, end consuming device, appliance, and/or the like.

(188) The term “computer system” at least in some examples refers to any type interconnected electronic devices, computer devices, or components thereof. Additionally, the terms “computer system” and/or “system” at least in some examples refer to various components of a computer that are communicatively coupled with one another. Furthermore, the term “computer system” and/or “system” at least in some examples refer to multiple computer devices and/or multiple computing systems that are communicatively coupled with one another and configured to share computing and/or networking resources. For purposes of the present disclosure, the terms “computer system”, “compute device”, “compute node”, and/or the like, may be considered synonymous to, and may be occasionally referred to, as a computing platform, platform, client device, client, mobile, mobile device, user device, user equipment (UE), mobile data terminal (MDT), terminal, receiver, transmitter, cellular phone, smartphones, feature phone, tablet personal computer, wearable device, laptop, desktop personal computers (or simply “desktop”), video game console, digital media players, handheld messaging devices, personal data assistant, electronic book reader (or simply “e-reader”), augmented reality (AR) device, virtual reality (VR) device, mixed reality (MR) device, in-vehicle infotainment (IVI) system, in-car entertainment (ICE) system, instrument cluster (IC), head-up display (HUD), on-board diagnostic (OBD) device, dashtop mobile equipment (DME), Electronic Engine Management System (EEMS), electronic control unit (ECU), electronic control module (ECM), embedded system, microcontroller, control module, engine management system (EMS), networked or “smart” appliance, machine-type communications (MTC) device, machine-to-machine (M2M) device, Internet of Things (IoT) device, autonomous sensor, server (e.g., stand-alone, rack-mounted, blade, and/or the like), cloud computing service, network element, network appliance, base station, access point, road side unit, gateway, router, switch, hub, on-premise unit, edge server, edge network device, aggregator, and/or any other like electronic devices.

(189) The term “server” at least in some examples refers to a computing device or system, including processing hardware and/or process space(s), an associated storage medium such as a memory device or database, and, in some instances, suitable application(s) as is known in the art. The terms “server system” and “server” may be used interchangeably herein, and these terms at least in some examples refers to one or more computing system(s) that provide access to a pool of physical and/or virtual resources. The various servers discussed herein include computer devices with rack computing architecture component(s), tower computing architecture component(s), blade computing architecture component(s), and/or the like. The servers may represent a cluster of servers, a server farm, a cloud computing service, or other grouping or pool of servers, which may be located in one or more datacenters. The servers may also be connected to, or otherwise associated with, one or more data storage devices (not shown). Moreover, the servers may include an operating system (OS) that provides executable program instructions for the general administration and operation of the individual server computer devices, and may include a computer-readable medium storing instructions that, when executed by a processor of the servers, may allow the servers to perform their intended functions. Suitable implementations for the OS and general functionality of servers are known or commercially available, and are readily implemented by persons having ordinary skill in

the art.

(190) The term “platform” at least in some examples refers to an environment in which instructions, program code, software elements, and/or the like can be executed or otherwise operate, and examples of such an environment include an architecture (e.g., a motherboard, a computing system, and/or the like), one or more hardware elements (e.g., embedded systems, and/or the like), a cluster of compute nodes, a set of distributed compute nodes or network, an operating system, a virtual machine (VM), a virtualization container, a software framework, a client application (e.g., web browser and/or the like) and associated application programming interfaces, a cloud computing service (e.g., platform as a service (PaaS)), or other underlying software executed with instructions, program code, software elements, and/or the like. The term “architecture” at least in some examples refers to a computer architecture or a network architecture. The term “computer architecture” at least in some examples refers to a physical and logical design or arrangement of software and/or hardware elements in a computing system or platform including technology standards for interacts therebetween. The term “network architecture” at least in some examples refers to a physical and logical design or arrangement of software and/or hardware elements in a network including communication protocols, interfaces, and media transmission.

(191) The term “appliance,” “computer appliance,” and/or the like, at least in some examples refers to a computer device or computer system with program code (e.g., software or firmware) that is specifically designed to provide a specific computing resource. The term “virtual appliance” at least in some examples refers to a virtual machine image to be implemented by a hypervisor-equipped device that virtualizes or emulates a computer appliance or otherwise is dedicated to provide a specific computing resource. The term “security appliance”, “firewall”, and/or the like at least in some examples refers to a computer appliance designed to protect computer networks from unwanted traffic and/or malicious attacks. The term “policy appliance” at least in some examples refers to technical control and logging mechanisms to enforce or reconcile policy rules (information use rules) and to ensure accountability in information systems. The term “gateway” at least in some examples refers to a network appliance that allows data to flow from one network to another network, or a computing system or application configured to perform such tasks. Examples of gateways include IP gateways, Internet-to-Orbit (I2O) gateways, IoT gateways, cloud storage gateways, and/or the like.

(192) The term “network element” at least in some examples refers to physical or virtualized equipment and/or infrastructure used to provide wired or wireless communication network services. Additionally or alternatively, the term “network element” at least in some examples refers to a physical or virtualized equipment and/or infrastructure of a wired or wireless communication network that provides network connectivity and/or radio baseband functions for data and/or voice services between one or more users and/or one or more compute nodes. The term “network element” may be considered synonymous to and/or referred to as a networked computer, networking hardware, network equipment, network node, router, switch, hub, bridge, radio network controller, network access node (NAN), base station, base transceiver station (BTS), access point (AP), Radio Access Network (RAN) node, roadside unit (RSU), gateway, server, network appliance, network function (NF), virtualized NF (VNF), and/or the like.

(193) The term “network access node” or “NAN” at least in some examples refers to a network element in a radio access network (RAN) responsible for the transmission and reception of radio signals in one or more cells or coverage areas to or from a UE or station. A “network access node” or “NAN” can have an integrated antenna or may be connected to an antenna array by feeder cables. Additionally or alternatively, a “network access node” or “NAN” may include specialized digital signal processing, network function hardware, and/or compute hardware to operate as a compute node. In some examples, a “network access node” or “NAN” may be split into multiple functional blocks operating in software for flexibility, cost, and performance. In some examples, a “network access node” or “NAN” may be a base station (e.g., an evolved Node B (eNB) or a next generation Node B (gNB)), an access point and/or wireless network access point, router, switch, hub, radio unit or remote radio head, Transmission Reception Point (TRxP), a gateway device (e.g., Residential

Gateway, Wireline 5G Cable Access Network, Wireline 5G Cable Access Network, Wireline BBF Access Network, and/or the like), network appliance, and/or some other network access hardware.

(194) The term “virtualization container”, “execution container”, or “container” at least in some examples refers to a partition of a compute node that provides an isolated virtualized computation environment. The term “OS container” at least in some examples refers to a virtualization container utilizing a shared Operating System (OS) kernel of its host, where the host providing the shared OS kernel can be a physical compute node or another virtualization container. Additionally or alternatively, the term “container” at least in some examples refers to a standard unit of software (or a package) including code and its relevant dependencies, and/or an abstraction at the application layer that packages code and dependencies together. Additionally or alternatively, the term “container” or “container image” at least in some examples refers to a lightweight, standalone, executable software package that includes everything needed to run an application such as, for example, code, runtime environment, system tools, system libraries, and settings.

(195) The term “virtual machine” or “VM” at least in some examples refers to a virtualized computation environment that behaves in a same or similar manner as a physical computer and/or a server. The term “hypervisor” at least in some examples refers to a software element that partitions the underlying physical resources of a compute node, creates VMs, manages resources for VMs, and isolates individual VMs from each other.

(196) The term “access technology” at least in some examples refers to the technology used for the underlying physical connection to a communication network. The term “radio technology” at least in some examples refers to technology for wireless transmission and/or reception of electromagnetic radiation for information transfer. The term “radio access technology” or “RAT” at least in some examples refers to the technology used for the underlying physical connection to a radio based communication network. Examples of access technologies include wireless access technologies/RATs, wireline, wireline-cable, wireline broadband forum (wireline-BBF), Ethernet (see e.g., *IEEE Standard for Ethernet*, IEEE Std 802.3-2018 (31 Aug. 2018) (“[IEEE802.3]”)) and variants thereof, fiber optics networks (e.g., ITU-T G.651, ITU-T G.652, Optical Transport Network (OTN), Synchronous optical networking (SONET) and synchronous digital hierarchy (SDH), and/or the like), digital subscriber line (DSL) and variants thereof, Data Over Cable Service Interface Specification (DOCSIS) technologies, hybrid fiber-coaxial (HFC) technologies, and/or the like. Examples of RATs (or RAT types) and/or communications protocols include Advanced Mobile Phone System (AMPS) technologies (e.g., Digital AMPS (D-AMPS), Total Access Communication System (TACS) and variants thereof, such as Extended TACS (ETACS), and/or the like); Global System for Mobile Communications (GSM) technologies (e.g., Circuit Switched Data (CSD), High-Speed CSD (HSCSD), General Packet Radio Service (GPRS), and Enhanced Data Rates for GSM Evolution (EDGE)); Third Generation Partnership Project (3GPP) technologies (e.g., Universal Mobile Telecommunications System (UMTS) and variants thereof (e.g., UMTS Terrestrial Radio Access (UTRA), Wideband Code Division Multiple Access (W-CDMA), Freedom of Multimedia Access (FOMA), Time Division-Code Division Multiple Access (TD-CDMA), Time Division-Synchronous Code Division Multiple Access (TD-SCDMA), and/or the like), Generic Access Network (GAN)/Unlicensed Mobile Access (UMA), High Speed Packet Access (HSPA) and variants thereof (e.g., HSPA Plus (HSPA+)), Long Term Evolution (LTE) and variants thereof (e.g., LTE-Advanced (LTE-A), Evolved UTRA (E-UTRA), LTE Extra, LTE-A Pro, LTE LAA, MuLTEfire, and/or the like), Fifth Generation (5G) or New Radio (NR), narrowband IoT (NB-IOT), 3GPP Proximity Services (ProSe), and/or the like); ETSI RATs (e.g., High Performance Radio Metropolitan Area Network (HiperMAN), Intelligent Transport Systems (ITS) (e.g., ITS-G5, ITS-G5B, ITS-G5C, and/or the like), and/or the like); Institute of Electrical and Electronics Engineers (IEEE) technologies and/or WiFi (e.g., *IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture*, IEEE Std 802-2014, pp. 1-74 (30 Jun. 2014) (“[IEEE802]”), *IEEE Standard for Information Technology—Telecommunications and Information Exchange between Systems—Local and Metropolitan Area Networks—Specific Requirements—Part 11: Wireless LAN Medium Access*

Control (MAC) and Physical Layer (PHY) Specifications, *IEEE Std 802.11-2020*, pp. 1-4379 (26 Feb. 2021) (“[IEEE80211]”), IEEE 802.15 technologies (e.g., *IEEE Standard for Low-Rate Wireless Networks*, IEEE Std 802.15.4-2020, pp. 1-800 (23 Jul. 2020) (“[IEEE802154]”) and variants thereof (e.g., ZigBee, WirelessHART, MiWi, ISA100.11a, Thread, IPv6 over Low power WPAN (6LoWPAN), and/or the like), *IEEE Standard for Local and metropolitan area networks—Part 15.6: Wireless Body Area Networks*, IEEE Std 802.15.6-2012, pp. 1-271 (29 Feb. 2012), and/or the like), WLAN V2X RATs (e.g., *IEEE Standard for Information technology—Local and metropolitan area networks—Specific requirements—Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications Amendment 6: Wireless Access in Vehicular Environments*, IEEE Std 802.11p-2010, pp. 1-51 (15 Jul. 2010) (“[IEEE80211p]”) (which is now part of [IEEE80211]), *IEEE Guide for Wireless Access in Vehicular Environments (WAVE) Architecture*, IEEE STANDARDS ASSOCIATION, IEEE 1609.0-2019 (10 Apr. 2019) (“[IEEE16090]”), IEEE 802.11bd, Dedicated Short Range Communications (DSRC), and/or the like), Worldwide Interoperability for Microwave Access (WiMAX) (e.g., *IEEE Standard for Air Interface for Broadband Wireless Access Systems*, IEEE Std 802.16-2017, pp. 1-2726 (2 Mar. 2018) (“[WiMAX]”)), Mobile Broadband Wireless Access (MBWA)/iBurst (e.g., IEEE 802.20 and variants thereof), Wireless Gigabit Alliance (WiGig) standards (e.g., IEEE 802.11ad, IEEE 802.11ay, and/or the like), and so forth); Integrated Digital Enhanced Network (iDEN) and variants thereof (e.g., Wideband Integrated Digital Enhanced Network (WiDEN)); millimeter wave (mmWave) technologies/standards (e.g., wireless systems operating at 10-300 GHz and above 3GPP 5G); short-range and/or wireless personal area network (WPAN) technologies/standards (e.g., IEEE 802.15 technologies (e.g., as mentioned previously); Bluetooth and variants thereof (e.g., Bluetooth 5.3, Bluetooth Low Energy (BLE), and/or the like), WiFi-direct, Miracast, ANT/ANT+, Z-Wave, Universal Plug and Play (UPnP), low power Wide Area Networks (LPWANs), Long Range Wide Area Network (LoRA or LoRaWAN™), and/or the like); optical and/or visible light communication (VLC) technologies/standards (e.g., *IEEE Standard for Local and metropolitan area networks—Part 15.7: Short-Range Optical Wireless Communications*, IEEE Std 802.15.7-2018, pp. 1-407 (23 Apr. 2019), and/or the like); Sigfox; Mobitex; 3GPP2 technologies (e.g., cdmaOne (2G), Code Division Multiple Access 2000 (CDMA 2000), and Evolution-Data Optimized or Evolution-Data Only (EV-DO); Push-to-talk (PTT), Mobile Telephone System (MTS) and variants thereof (e.g., Improved MTS (IMTS), Advanced MTS (AMTS), and/or the like); Personal Digital Cellular (PDC); Personal Handy-phone System (PHS), Cellular Digital Packet Data (CDPD); Cellular Digital Packet Data (CDPD); DataTAC; Digital Enhanced Cordless Telecommunications (DECT) and variants thereof (e.g., DECT Ultra Low Energy (DECT ULE), DECT-2020, DECT-5G, and/or the like); Ultra High Frequency (UHF) communication; Very High Frequency (VHF) communication; and/or any other suitable RAT or protocol. In addition to the aforementioned RATs/standards, any number of satellite uplink technologies may be used for purposes of the present disclosure including, for example, radios compliant with standards issued by the International Telecommunication Union (ITU), or the ETSI, among others. The examples provided herein are thus understood as being applicable to various other communication technologies, both existing and not yet formulated.

(197) The term “protocol” at least in some examples refers to a predefined procedure or method of performing one or more operations. Additionally or alternatively, the term “protocol” at least in some examples refers to a common means for unrelated objects to communicate with each other (sometimes also called interfaces). The term “communication protocol” at least in some examples refers to a set of standardized rules or instructions implemented by a communication device and/or system to communicate with other devices and/or systems, including instructions for packetizing/depacketizing data, modulating/demodulating signals, implementation of protocols stacks, and/or the like. In various implementations, a “protocol” and/or a “communication protocol” may be represented using a protocol stack, a finite state machine (FSM), and/or any other suitable data structure.

(198) The term “application layer” at least in some examples refers to an abstraction layer that

specifies shared communications protocols and interfaces used by hosts in a communications network. Additionally or alternatively, the term “application layer” at least in some examples refers to an abstraction layer that interacts with software applications that implement a communicating component, and may include identifying communication partners, determining resource availability, and synchronizing communication. Examples of application layer protocols include Hypertext Transfer Protocol (HTTP), HTTP secure (HTTPS), Andrew File System (AFS), File Transfer Protocol (FTP), Dynamic Host Configuration Protocol (DHCP), Internet Message Access Protocol (IMAP), Lightweight Directory Access Protocol (LDAP), MQTT (MQ Telemetry Transport), Remote Authentication Dial-In User Service (RADIUS), Diameter protocol, Extensible Authentication Protocol (EAP), RDMA over Converged Ethernet version 2 (RoCEv2), Real-time Transport Protocol (RTP), RTP Control Protocol (RTCP), Real Time Streaming Protocol (RTSP), Secure RTP (SRTP), SBMV Protocol, Skinny Client Control Protocol (SCCP), Session Initiation Protocol (SIP), Session Description Protocol (SDP), Simple Mail Transfer Protocol (SMTP), Simple Network Management Protocol (SNMP), Simple Service Discovery Protocol (SSDP), Small Computer System Interface (SCSI), Internet SCSI (iSCSI), iSCSI Extensions for RDMA (iSER), Transport Layer Security (TLS), voice over IP (VoIP), Virtual Private Network (VPN), Wireless Application Protocol (WAP), WebSockets, Web-based secure shell (SSH), Extensible Messaging and Presence Protocol (XMPP), and/or the like.

(199) The term “session layer” at least in some examples refers to an abstraction layer that controls dialogues and/or connections between entities or elements, and may include establishing, managing and terminating the connections between the entities or elements. The term “transport layer” at least in some examples refers to a protocol layer that provides end-to-end (e2e) communication services such as, for example, connection-oriented communication, reliability, flow control, and multiplexing. Examples of transport layer protocols include datagram congestion control protocol (DCCP), fibre channel protocol (FBC), Generic Routing Encapsulation (GRE), GPRS Tunneling (GTP), Micro Transport Protocol (pTP), Multipath TCP (MPTCP), MultiPath QUIC (MPQUIC), Multipath UDP (MPUDP), Quick UDP Internet Connections (QUIC), Remote Direct Memory Access (RDMA), Resource Reservation Protocol (RSVP), Stream Control Transmission Protocol (SCTP), transmission control protocol (TCP), user datagram protocol (UDP), and/or the like.

(200) The term “network layer” at least in some examples refers to a protocol layer that includes means for transferring network packets from a source to a destination via one or more networks. Additionally or alternatively, the term “network layer” at least in some examples refers to a protocol layer that is responsible for packet forwarding and/or routing through intermediary nodes. Additionally or alternatively, the term “network layer” or “internet layer” at least in some examples refers to a protocol layer that includes interworking methods, protocols, and specifications that are used to transport network packets across a network. As examples, the network layer protocols include internet protocol (IP), IP security (IPsec), Internet Control Message Protocol (ICMP), Internet Group Management Protocol (IGMP), Open Shortest Path First protocol (OSPF), Routing Information Protocol (RIP), RDMA over Converged Ethernet version 2 (RoCEv2), Subnetwork Access Protocol (SNAP), and/or some other internet or network protocol layer.

(201) The term “link layer” or “data link layer” at least in some examples refers to a protocol layer that transfers data between nodes on a network segment across a physical layer. Examples of link layer protocols include logical link control (LLC), medium access control (MAC), Ethernet, RDMA over Converged Ethernet version 1 (RoCEv1), and/or the like. The term “medium access control protocol”, “MAC protocol”, or “MAC” at least in some examples refers to a protocol that governs access to the transmission medium in a network, to enable the exchange of data between stations in a network. Additionally or alternatively, the term “medium access control layer”, “MAC layer”, or “MAC” at least in some examples refers to a protocol layer or sublayer that performs functions to provide frame-based, connectionless-mode (e.g., datagram style) data transfer between stations or devices. (see e.g., [IEEE802], 3GPP TS 38.321 v17.2.0 (2022 Oct. 1) and 3GPP TS 36.321 v17.2.0 (2022 Oct. 3)). The term “physical layer”, “PHY layer”, or “PHY” at least in some examples refers to

a protocol layer or sublayer that includes capabilities to transmit and receive modulated signals for communicating in a communications network (see e.g., [IEEE802], 3GPP TS 38.201 v17.0.0 (2022 Jan. 5) and 3GPP TS 36.201 v17.0.0 (2022 Mar. 31)).

(202) The term “channel” at least in some examples refers to any transmission medium, either tangible or intangible, which is used to communicate data or a data stream. The term “channel” may be synonymous with and/or equivalent to “communications channel,” “data communications channel,” “transmission channel,” “data transmission channel,” “access channel,” “data access channel,” “link,” “data link,” “carrier,” “radiofrequency carrier,” and/or any other like term denoting a pathway or medium through which data is communicated. Additionally, the term “link” at least in some examples refers to a connection between two devices through a RAT for the purpose of transmitting and receiving information.

(203) The term “local area network” or “LAN” at least in some examples refers to a network of devices, whether indoors or outdoors, covering a limited area or a relatively small geographic area (e.g., within a building or a campus). The term “wireless local area network”, “wireless LAN”, or “WLAN” at least in some examples refers to a LAN that involves wireless communications. The term “wide area network” or “WAN” at least in some examples refers to a network of devices that extends over a relatively large geographic area (e.g., a telecommunications network). Additionally or alternatively, the term “wide area network” or “WAN” at least in some examples refers to a computer network spanning regions, countries, or even an entire planet

(204) The term “compute resource” or simply “resource” at least in some examples refers to any physical or virtual component, or usage of such components, of limited availability within a computer system or network. Examples of computing resources include usage/access to, for a period of time, servers, processor(s), storage equipment, memory devices, memory areas, networks, electrical power, input/output (peripheral) devices, mechanical devices, network connections (e.g., channels/links, ports, network sockets, and/or the like), operating systems, virtual machines (VMs), software/applications, computer files, and/or the like. A “hardware resource” at least in some examples refers to compute, storage, and/or network resources provided by physical hardware element(s). A “virtualized resource” at least in some examples refers to compute, storage, and/or network resources provided by virtualization infrastructure to an application, device, system, and/or the like. The term “network resource” or “communication resource” at least in some examples refers to resources that are accessible by computer devices/systems via a communications network. The term “system resources” at least in some examples refers to any kind of shared entities to provide services, and may include computing and/or network resources. System resources may be considered as a set of coherent functions, network data objects or services, accessible through a server where such system resources reside on a single host or multiple hosts and are clearly identifiable.

(205) The term “service” at least in some examples refers to the provision of a discrete function within a system and/or environment. Additionally or alternatively, the term “service” at least in some examples refers to a functionality or a set of functionalities that can be reused. The term “microservice” at least in some examples refers to one or more processes that communicate over a network to fulfil a goal using technology-agnostic protocols (e.g., HTTP and/or the like). Additionally or alternatively, the term “microservice” at least in some examples refers to services that are relatively small in size, messaging-enabled, bounded by contexts, autonomously developed, independently deployable, decentralized, and/or built and released with automated processes. Additionally or alternatively, the term “microservice” at least in some examples refers to a self-contained piece of functionality with clear interfaces, and may implement a layered architecture through its own internal components. Additionally or alternatively, the term “microservice architecture” at least in some examples refers to a variant of the service-oriented architecture (SOA) structural style wherein applications are arranged as a collection of loosely-coupled services (e.g., fine-grained services) and may use lightweight protocols.

(206) The term “session” at least in some examples refers to a temporary and interactive information interchange between two or more communicating devices, two or more application instances,

by a computer and user, and/or between any two or more entities or elements. Additionally or alternatively, the term “session” at least in some examples refers to a connectivity service or other service that provides or enables the exchange of data between two entities or elements. The term “network session” at least in some examples refers to a session between two or more communicating devices over a network. The term “web session” at least in some examples refers to session between two or more communicating devices over the Internet or some other network. The term “session identifier,” “session ID,” or “session token” at least in some examples refers to a piece of data that is used in network communications to identify a session and/or a series of message exchanges.

(207) The term “identifier” at least in some examples refers to a value, or a set of values, that uniquely identify an identity in a certain scope. Additionally or alternatively, the term “identifier” at least in some examples refers to a sequence of characters that identifies or otherwise indicates the identity of a unique object, element, or entity, or a unique class of objects, elements, or entities. Additionally or alternatively, the term “identifier” at least in some examples refers to a sequence of characters used to identify or refer to an application, program, session, object, element, entity, variable, set of data, and/or the like. The “sequence of characters” mentioned previously at least in some examples refers to one or more names, labels, words, numbers, letters, symbols, and/or any combination thereof. Additionally or alternatively, the term “identifier” at least in some examples refers to a name, address, label, distinguishing index, and/or attribute. Additionally or alternatively, the term “identifier” at least in some examples refers to an instance of identification. The term “persistent identifier” at least in some examples refers to an identifier that is reused by a device or by another device associated with the same person or group of persons for an indefinite period. The term “application identifier”, “application ID”, or “app ID” at least in some examples refers to an identifier that can be mapped to a specific application, application instance, or application instance. In the context of 3GPP 5G/NR, an “application identifier” at least in some examples refers to an identifier that can be mapped to a specific application traffic detection rule. The term “endpoint address” at least in some examples refers to an address used to determine the host/authority part of a target URI, where the target URI is used to access an NF service (e.g., to invoke service operations) of an NF service producer or for notifications to an NF service consumer.

(208) The term “identification” at least in some examples refers to a process of recognizing an identity as distinct from other identities in a particular scope or context, which may involve processing identifiers to reference an identity in an identity database. The term “identity” at least in some examples refers to a set of characteristics, qualities, beliefs, behaviors, and/or other aspects of an entity. Identity can be applied to persons, things, and/or entities. An entity can have several identities (often known as personas). The term “digital identity” at least in some examples refers to a set of attributes and/or any information on an entity used by computer systems to represent an agent, a person, organization, application, device, and/or entity. Additionally or alternatively, the term “identity” or “digital identity” at least in some examples refers to a record or data representing an identity. For purposes of the present disclosure, the abbreviation “ID” may refer to the term “identity”, “identification”, and/or “identifier”.

(209) The term “network address” at least in some examples refers to an identifier for a node or host in a computer network, and may be a unique identifier across a network and/or may be unique to a locally administered portion of the network. The term “port” in the context of computer networks, at least in some examples refers to a communication endpoint, a virtual data connection between two or more entities, and/or a virtual point where network connections start and end. Additionally or alternatively, a “port” at least in some examples is associated with a specific process or service.

(210) Examples of identifiers and/or network addresses include an application identifier, Bluetooth hardware device address (BD_ADDR), a cellular network address (e.g., Access Point Name (APN), AMF identifier (ID), AF-Service-Identifier, Edge Application Server (EAS) ID, Data Network Access Identifier (DNAI), Data Network Name (DNN), EPS Bearer Identity (EBI), Equipment Identity Register (EIR) and/or 5G-EIR, Extended Unique Identifier (EUI), Group ID for Network Selection (GIN), Generic Public Subscription Identifier (GPSI), Globally Unique AMF Identifier (GUAMI),

Globally Unique Temporary Identifier (GUTI) and/or 5G-GUTI, Radio Network Temporary Identifier (RNTI) and variants thereof, International Mobile Equipment Identity (IMEI), IMEI Type Allocation Code (IMEA/TAC), International Mobile Subscriber Identity (IMSI), IMSI software version (IMSV), permanent equipment identifier (PEI), Local Area Data Network (LADN) DNN, Mobile Subscriber Identification Number (MSIN), Mobile Subscriber/Station ISDN Number (MSISDN), Network identifier (NID), Network Slice Instance (NSI) ID, Permanent Equipment Identifier (PEI), Public Land Mobile Network (PLMN) ID, QoS Flow ID (QFI) and/or 5G QoS Identifier (5QI), RAN ID, Routing Indicator, SMS Function (SMSF) ID, Stand-alone Non-Public Network (SNPN) ID, Subscription Concealed Identifier (SUCI), Subscription Permanent Identifier (SUPI), Temporary Mobile Subscriber Identity (TMSI) and variants thereof, UE Access Category and Identity, and/or other cellular network related identifiers), Closed Access Group Identifier (CAG-ID), driver's license number, Global Trade Item Number (GTIN) (e.g., Australian Product Number (APN), Electronic Produce Code (EPC), European Article Number (EAN), Universal Product Code (UPC), and/or the like), Digital Object Identifier (DOI),  custom character email address, Enterprise Application Server (EAS) ID, an endpoint address, an Electronic Product Code (EPC) as defined by the EPCglobal Tag Data Standard, Fully Qualified Domain Name (FQDN), flow ID and/or flow hash, hash value, index, integrated circuit card identification number (ICCID), international article number (IAN), internet protocol (IP) address in an IP network (e.g., IP version 4 (IPv4), IP version 6 (IPv6), and/or the like), an InterPlanetary File System (IPFS) content address, an internet packet exchange (IPX) address, LAN ID, a MAC address, personal area network (PAN) ID, personal identification number (PIN), personal unblocking key (PUK), port number (e.g., TCP port number, UDP port number, and/or the like), price lookup code (PLC), product key, QUIC connection ID, RFID tag, sequence number, service set identifier (SSID) and variants thereof, screen name, serial number, serial SIM number (SSN), stock keeping unit (SKU), socket address, social security number (SSN), subscriber identity module (SIM) ID, telephone number (e.g., in a public switched telephone network (PTSN)), unique identifier (UID) (e.g., including globally UID, universally unique identifier (UUID) (e.g., as specified in ISO/IEC 11578:1996), and/or the like), Universal Resource Identifier (URI), Universal Resource Locator (URL), Uniform Resource Name (URN), user name (e.g., ID for logging into a service provider platform, such as a social network and/or some other service), vehicle identification number (VIN), Virtual LAN (VLAN) ID, X.21 address, an X.25 address, Zigbee® ID, Zigbee® Device Network ID, and/or any other suitable network address and components thereof.

(211) The term “universally unique identifier” or “UUID” refers to a number used to identify information in computer systems. Usually, UUIDs are 128-bit numbers. UUIDs are generally represented as 32 hexadecimal digits displayed in five groups separated by hyphens in the following format: “xxxxxxxx-xxxx-Mxxx-Nxxx-xxxxxxxxxxxx” where the four-bit M and the 1 to 3 bit N fields code the format of the UUID itself. The term “universally unique identifier” or “UUID” may alternatively be referred to a “globally unique identifier” or “GUID”.

(212) The term “reference” at least in some examples refers to data useable to locate other data and may be implemented a variety of ways (e.g., a pointer, an index, a handle, a key, an identifier, a hyperlink, and/or the like).

(213) The term “configuration” at least in some examples refer to an information object, data structure(s), or other machine-readable element that contains instructions, conditions, parameters, options, settings, preferences, and/or criteria that is/are relevant to one or more software and/or hardware elements. Additionally or alternatively, the term “configuration” at least in some examples refers to the relative arrangement of components, functional units, and/or entities/elements according to some criteria and/or characteristics. For purposes of the present disclosure, the terms “configuration,” “policy,” “rules,” “rule set,” “template,” “definition,” “schema,” “operational parameters,” and “parameter set” may be used interchangeable throughout the present disclosure even those these terms may refer to different concepts.

(214) The terms “policy” and “ruleset” at least in some examples refer to an information object, data structure(s), or other machine-readable element that define a set of rules that govern the behavior of

one or more software and/or hardware elements.

(215) The term “application” or “app” at least in some examples refers to a computer program designed to carry out a specific task other than one relating to the operation of the computer itself. Additionally or alternatively, term “application” or “app” at least in some examples refers to a complete and deployable package, environment to achieve a certain function in an operational environment.

(216) The term “application programming interface” or “API” at least in some examples refers to a set of subroutine definitions, communication protocols, and tools for building software. Additionally or alternatively, the term “application programming interface” or “API” at least in some examples refers to a set of clearly defined methods of communication among various components. In some examples, an API may be defined or otherwise used for a web-based system, operating system, database system, computer hardware, software library, and/or the like. Examples of the APIs that may be used for purposes of the present disclosure include remote APIs and/or web APIs (e.g., Representational State Transfer (REST or RESTful) API, Simple Object Access Protocol (SOAP) API, salesforce.com Apex API, and/or the like), a web services (WS) (e.g., Apache® Axi2.4 or Axi3, Apache® CXF, a JSON-Remote Procedure Call (RPC) API (e.g., Ethereum JSON-RPC API implemented by a public or enterprise Ethereum® blockchain platform), JSON-Web Service Protocol (WSP), Web Services Description Language (WSDL), XML Interface for Network Services (XINS), Web Services Conversation Language (WSCL), Web Services Flow Language (WSFL), RESTful web services, Flow Wallet API, and/or the like), and/or some other suitable API and/or WS.

(217) The term “information object” or “InOb” at least in some examples refers to a data structure or piece of information, definition, or specification that includes a name to identify its use in an instance of communication. Additionally or alternatively, the term “information object” or “InOb” at least in some examples refers to a configuration item or other data structure that displays information in an organized form. Additionally or alternatively, the term “information object” or “InOb” at least in some examples refers to an abstraction of a real information entity and/or a representation and/or an occurrence of a real-world entity. Additionally or alternatively, the term “information object” or “InOb” at least in some examples refers to a data structure that contains and/or conveys information or data. Each of the data formats may also define the language, syntax, vocabulary, and/or protocols that govern information storage and/or exchange. Examples of the data formats that may be used for any of the InObs discussed herein may include Accelerated Mobile Pages Script (AMPscript), Abstract Syntax Notation One (ASN.1), Backus-Naur Form (BNF), extended BNF, Bencode, BSON, ColdFusion Markup Language (CFML), comma-separated values (CSV), Control Information Exchange Data Model (C2IEDM), Cascading Stylesheets (CSS), DARPA Agent Markup Language (DAML), Document Type Definition (DTD), Electronic Data Interchange (EDI), Extensible Data Notation (EDN), Extensible Markup Language (XML), Efficient XML Interchange (EXI), Extensible Stylesheet Language (XSL), Free Text (FT), Fixed Word Format (FWF), Cisco® Etch, Franca, Geography Markup Language (GML), Guide Template Language (GTL), Handlebars template language, Hypertext Markup Language (HTML), Interactive Financial Exchange (IFX), Keyhole Markup Language (KML), JAMscript, Java Script Object Notion (JSON), JSON Schema Language, Apache® MessagePack™, Mustache template language, Ontology Interchange Language (OIL), Open Service Interface Definition, Open Financial Exchange (OFX), Precision Graphics Markup Language (PGML), Google® Protocol Buffers (protobuf), Quicken® Financial Exchange (QFX), Regular Language for XML Next Generation (RelaxNG) schema language, regular expressions, Resource Description Framework (RDF) schema language, RESTful Service Description Language (RSDL), Scalable Vector Graphics (SVG), Schematron, Tactical Data Link (TDL) format (e.g., J-series message format for Link 16; JREAP messages; Multifunction Advanced Data Link (MADL), Integrated Broadcast Service/Common Message Format (IBS/CMF), Over-the-Horizon Targeting Gold (OTH-T Gold), Variable Message Format (VMF), United States Message Text Format (USMTF), and any future advanced TDL formats), VBScript, Web Application Description Language (WADL), Web Ontology Language (OWL), Web Services Description Language (WSDL), wiki

markup or Wikitext, Wireless Markup Language (WML), extensible HTML (XHTML), XPath, XQuery, XML DTD language, XML Schema Definition (XSD), XML Schema Language, XSL Transformations (XSLT), YAML (“Yet Another Markup Language” or “YANL Ain’t Markup Language”), Apache® Thrift, and/or any other data format and/or language discussed elsewhere herein. Additionally or alternatively, the data format for the InObs may be document and/or plain text, spreadsheet, graphics, and/or presentation formats including, for example, American National Standards Institute (ANSI) text, a Computer-Aided Design (CAD) application file format (e.g., “.c3d”, “.dwg”, “.dft”, “.iam”, “.iaw”, “.tct”, and/or other like file extensions), Google® Drive® formats (including associated formats for Google Docs®, Google Forms®, Google Sheets®, Google Slides®, and/or the like), Microsoft® Office® formats (e.g., “.doc”, “.ppt”, “.xls”, “.vsd”, and/or other like file extension), OpenDocument Format (including associated document, graphics, presentation, and spreadsheet formats), Open Office XML (OOXML) format (including associated document, graphics, presentation, and spreadsheet formats), Apple® Pages®, Portable Document Format (PDF), Question Object File Format (QUOX), Rich Text File (RTF), TeX and/or LaTeX (“.tex” file extension), text file (TXT), TurboTax® file (“.tax” file extension), You Need a Budget (YNAB) file, and/or any other like document or plain text file format. Additionally or alternatively, the data format for the InObs may be archive file formats that store metadata and concatenate files, and may or may not compress the files for storage. The term “archive file” refers to a file having a file format or data format that combines or concatenates one or more files into a single file or InOb. Archive files often store directory structures, error detection and correction information, arbitrary comments, and sometimes use built-in encryption. The term “archive format” refers to the data format or file format of an archive file, and may include, for example, archive-only formats that store metadata and concatenate files, for example, including directory or path information; compression-only formats that only compress a collection of files; software package formats that are used to create software packages (including self-installing files), disk image formats that are used to create disk images for mass storage, system recovery, and/or other like purposes; and multi-function archive formats that can store metadata, concatenate, compress, encrypt, create error detection and recovery information, and package the archive into self-extracting and self-expanding files. For the purposes of the present disclosure, the term “archive file” at least in some examples refers to an archive file having any of the aforementioned archive format types. Examples of archive file formats may include Android® Package (APK); Microsoft® Application Package (APPX); Genie Timeline Backup Index File (GBP); Graphics Interchange Format (GIF); gzip (.gz) provided by the GNU Project™; Java® Archive (JAR); Mike O'Brien Pack (MPQ) archives; Open Packaging Conventions (OPC) packages including OOXML files, OpenXPS files, and/or the like; Rar Archive (RAR); Red Hat® package/installer (RPM); Google® SketchUp backup File (SKB); TAR archive (“.tar”); XPIInstall or XPI installer modules; ZIP (.zip or .zipx); and/or the like. Additionally or alternatively, the archive file formats may be a suitable application package file format and/or the like.

(218) The term “identity document”, “piece of identification”, “ID”, (or colloquially referred to as “papers”) at least in some examples refers to any document that may be used to prove a person's identity. Many physical identity documents take the form of an identity card (or “photo ID”), which may be a passport card, driver's license, social security card, national identification card, and/or the like, and typically include a person's photograph, the bearer's name, birth date, address, gender and/or sex, an identification number (e.g., a unique national, state/provincial, or local identification number), card number, citizenship status, and/or other information.

(219) The term “authorization” at least in some examples refers to a prescription that a particular behavior shall not be prevented. The term “authentication” at least in some embodiments refers to a process of proving or verifying an identity. Additionally or alternatively, the term “authentication” at least in some embodiments refers to a mechanism by which a computer system checks or verifies that a user or entity is really the user or entity being claimed. Examples of the authentication and/or authorization techniques include using API keys, basic access authentication (“Basic Auth”), Open Authorization (OAuth), hash-based message authentication codes (HMAC), Kerberos protocol,

OpenID, WebID, and/or other authentication and/or authorization techniques.

(220) The term “biometric data”, “biometrics”, and/or “biometric identifier” at least in some examples refers to any body measurement(s) and/or calculation(s) related to human characteristics. Additionally or alternatively, the term “biometric data”, “biometrics”, and/or “biometric identifier” at least in some embodiments refers to one or more distinctive, measurable characteristics used to label and describe an individual. The term “physiological biometrics” at least in some embodiments refers to biometrics and/or other characteristics related to physical aspects of an individual; examples include fingerprints, face image, facial features (e.g., including relative arrangement of facial features), DNA, palm print, body part geometry (e.g., hand geometry and/or the like), vein patterns (e.g., palm vein patterns, finger vein pattern, or vein patterns of any other body part), eye features (e.g., retina and/or iris), odor/scent, voice features (e.g., pitch, tone, and other audio characteristics of an individual's voice), neural oscillations and/or brainwaves, pulse, electrocardiogram, pulse oximetry, and/or the like. The term “behavioral biometrics” or “behaviometrics” at least in some embodiments refers to biometrics and/or other characteristics related to an individual's behavioral pattern(s); examples include typing rhythm, gait, signature, behavioral profiling (e.g., including personality traits), and voice features.

(221) The term “certificate” or “digital certificate” at least in some examples refers to an information object (e.g., an electronic document or other data structure) used to prove the validity of a piece of data such as a public key in a public key infrastructure (PKI) system. Examples of the digital certificates include the X.509 format and/or some other suitable format, and may be signed using any suitable cryptographic mechanisms such as Elliptic Curve cryptography Digital Signature Algorithm (ECDSA) or some other suitable algorithm such as any of those discussed herein. Additionally or alternatively, the digital certificates discussed herein can include various certificates issued by the an issuer, a verification body, a notified body, certificate authority (CA) (e.g., a root CA and/or the like), an enrollment authority (EA), an authorization authority (AA), and/or other entity as delineated by relevant Certificate Authority Security Council (CASC) standards, Common Computing Security Standards Forum (CCSF) standards, CA/Browser Forum standards, GSMA standards, ETSI standards, GlobalPlatform standards, and/or some other suitable standard.

(222) The term “certificate revocation list” or “CRL” at least in some examples refers to a signed list indicating a set of certificates that are no longer considered valid by the certificate issuer

(223) The term “confidential data” at least in some examples refers to any form of information that a person or entity is obligated, by law or contract, to protect from unauthorized access, use, disclosure, modification, or destruction. Additionally or alternatively, “confidential data” at least in some examples refers to any data owned or licensed by a person or entity that is not intentionally shared with the general public or that is classified by the person or entity with a designation that precludes sharing with the general public.

(224) The term “consent” at least in some examples refers to any freely given, specific, informed and unambiguous indication of a data subject's wishes by which he or she, by a statement or by a clear affirmative action, signifies agreement to the processing of personal data relating to the data subject.

(225) The term “consistency check” at least in some examples refers to a test or assessment performed to determine if data has any internal conflicts, conflicts with other data, and/or whether any contradictions exist. In some examples, a “consistency check” may operate according to a “consistency model”, which at least in some examples refers to a set of operations for performing a consistency check and/or rules or policies used to determine if data is consistent (or predictable) or not.

(226) The term “cryptographic mechanism” at least in some examples refers to any cryptographic protocol and/or cryptographic algorithm. Examples of cryptographic mechanisms include a cryptographic hash algorithm, such as a function in the Secure Hash Algorithm (SHA) 2 set of cryptographic hash algorithms (e.g., SHA-226, SHA-256, SHA-512, and/or the like), SHA 3, and so forth, or any type of keyed or unkeyed cryptographic hash function and/or any other function

discussed herein; an elliptic curve cryptographic (ECC) algorithm (e.g., Elliptic Curve cryptography Key Agreement algorithm (ECKA) algorithm, Elliptic Curve cryptography Digital Signature Algorithm (ECDSA), Lenstra elliptic-curve factorization or elliptic-curve factorization method (ECM), Menezes-Qu-Vanstone (MQV) or elliptic curve MQV (ECMQV), Elliptic Curve Diffie-Hellman (ECDH) key agreement, Elliptic Curve Integrated Encryption Scheme (ECIES) or Elliptic Curve Augmented Encryption Scheme, Edwards-curve Digital Signature Algorithm (EdDSA), and/or the like); Rivest-Shamir-Adleman (RSA) cryptography; Merkle signature scheme, advanced encryption system (AES) algorithm; a triple data encryption algorithm (3DES); Quantum cryptography algorithms; and/or the like. Additionally or alternatively, the term “cryptographic protocol” at least in some examples refers to a sequence of steps precisely specifying the actions required of two or more entities to achieve specific security objectives (e.g., cryptographic protocol for key agreement). Additionally or alternatively, the term “cryptographic algorithm” at least in some examples refers to an algorithm specifying the steps followed by a single entity to achieve specific security objectives (e.g., cryptographic algorithm for symmetric key encryption).

(227) The term “cryptographic hash function”, “hash function”, or “hash”) at least in some examples refers to a mathematical algorithm that maps data of arbitrary size (sometimes referred to as a “message”) to a bit array of a fixed size (sometimes referred to as a “hash value”, “hash”, or “message digest”). A cryptographic hash function is usually a one-way function, which is a function that is practically infeasible to invert.

(228) The term “cryptographic key” or “key” in cryptography at least in some examples refers to a piece of information, usually a string of numbers or letters that are stored in a file, which, when processed through a cryptographic algorithm can encode or decode cryptographic data. The term “symmetric-key algorithm” at least in some examples refers to a cryptographic algorithm that uses the same cryptographic key for both the encryption of plaintext and the decryption of ciphertext; the keys may be identical, or there may be a simple transformation to go between the two keys.

(229) The term “encryption” at least in some examples refers to a process of encoding information wherein the original representation of information (referred to as “plaintext”) into an alternative form (referred to as “ciphertext”). In some examples, an encryption scheme includes use of a pseudo-random encryption key generated by a cryptographic mechanism or some other algorithm to generate an encryption key, which can be used to encrypt and/or decrypt the plaintext.

(230) The term “information security” or “InfoSec” at least in some examples refers to any practice, technique, and technology for protecting information by mitigating information risks and typically involves preventing or reducing the probability of unauthorized/inappropriate access to data, or the unlawful use, disclosure, disruption, deletion, corruption, modification, inspection, recording, or devaluation of information; and the information to be protected may take any form including electronic information, physical or tangible (e.g., computer-readable media storing information, paperwork, and/or the like), or intangible (e.g., knowledge, intellectual property assets, and/or the like).

(231) The term “integrity” at least in some examples refers to a mechanism that assures that data has not been altered in an unapproved way. Examples of cryptographic mechanisms that can be used for integrity protection include digital signatures, message authentication codes (MAC), and secure hashes.

(232) The term “know your client”, “know your customer”, or “KYC” at least in some examples refers to verification procedures, a set of standards and/or requirements used to ensure that an org has sufficient information about their clients, their risk profiles, and their financial position. In various examples, KYC includes three components, including customer identification program (CIP), imposed under the USA Patriot Act in 2001, customer due diligence (CDD), and ongoing monitoring or enhanced due diligence (EDD) of a customer's account once it is established. CIP requires that financial firms must obtain four pieces of identifying information about a client, including name, date of birth, address, and identification number. CDD is a process in which all of a customer's credentials are collected to verify their identity and evaluate their risk profile for suspicious account activity.

EDD is used for customers that are at a higher risk of infiltration, terrorism financing, or money laundering and additional information collection is often necessary. Account owners generally must provide a government-issued ID as proof of identity. Some institutions require two forms of ID, such as a driver's license, birth certificate, social security card, or passport. In addition to confirming identity, the address must be confirmed. This can be done with proof of ID or with an accompanying document confirming the address of the client.

(233) The term “knowledge-based assessment”, “knowledge-based authentication”, or “KBA” at least in some examples refers to verification and/or authentication processes or procedures, which requires the knowledge of private information (or personal data) to prove that the entity/element providing the identifying information is the actual owner of the corresponding identity. In some examples, KBA-generated questions are static KBAs or dynamic KBAs. The term “static KBAs” at least in some examples refers to a pre-agreed set of KBA data and/or shared secrets, such as place of birth, mother's maiden name, name of first pet, and/or the like. The term “dynamic KBAs” at least in some examples refers to KBA-questions generated from a wider base of personal information, such as account numbers, loan amounts, tax payment amounts, and/or the like. Additionally or alternatively, the term “dynamic KBAs” at least in some examples refers to KBA-questions that are generated based on changing parameters or conditions, such as previously supplied KBA questions, timing parameters, and/or the like.

(234) The term “personal data,” “personally identifiable information,” “PII,” at least in some examples refers to information that relates to an identified or identifiable individual (referred to as a “data subject”). Additionally or alternatively, “personal data,” “personally identifiable information,” “PII,” at least in some examples refers to information that can be used on its own or in combination with other information to identify, contact, or locate a data subject, or to identify a data subject in context.

(235) The term “plausibility check” at least in some examples refers to a test or assessment performed to determine whether data is, or can be, plausible. The term “plausible” at least in some examples refers to an amount or quality of being acceptable, reasonable, comprehensible, and/or probable.

(236) The term “Personal Identity Verification” or “PIV” at least in some examples refers to a common identification standard for Federal employees and contractors as specified in National Institute of Standards and Technology (NIST), “Personal Identity Verification (PIV) of Federal Employees and Contractors”, Federal Information Processing Standards (FIPS) 201-3 (January 2022), which is hereby incorporated by reference in its entirety and for all purposes. The term “Personal Identity Verification—Interoperable” or “PIV-I” at least in some examples refers to a credential standard for issuance to non-Federal entities to access U.S. Federal Government systems. Additionally or alternatively, the term “Personal Identity Verification—Interoperable” or “PIV-I” at least in some embodiments refers to a credential that is issued to non-Federal entities per the Chief Information Officers (CIO) Council, “Personal Identity Verification Interoperability for Issuers” v2.0.1 (27 Jul. 2017), which is hereby incorporated by reference in its entirety and for all purposes.

(237) The term “protected location” at least in some examples refers to a memory location outside of a hardware root of trust, protected against attacks on confidentiality, and in which from the perspective of the root of trust, integrity protection is limited to the detection of modifications.

(238) The term “pseudonymization” at least in some examples refers to any means of processing personal data or sensitive data in such a manner that the personal/sensitive data can no longer be attributed to a specific data subject (e.g., person or entity) without the use of additional information. The additional information may be kept separately from the personal/sensitive data and may be subject to technical and organizational measures to ensure that the personal/sensitive data are not attributed to an identified or identifiable natural person.

(239) The term “public-key cryptography” or “asymmetric cryptography” at least in some examples refers to a cryptographic system that use pairs of related keys including, for example, a public key used for generating ciphertext, and a corresponding private key to decrypt the ciphertext to obtain the original message (e.g., plaintext); in some examples, these key pairs are generated with cryptographic

algorithms based on one-way functions.

(240) The term “sensitive data” at least in some examples refers to data related to racial or ethnic origin, political opinions, religious or philosophical beliefs, or trade union membership, genetic data, biometric data, data concerning health, and/or data concerning a natural person's sex life or sexual orientation.

(241) The term “shielded location” at least in some examples refers to a memory location within the hardware root of trust, protected against attacks on confidentiality and manipulation attacks including deletion that impact the integrity of the memory, in which access is enforced by the hardware root of trust.

(242) The term “security threat” at least in some examples refers to a potential violation of security. Examples of security threats include loss or disclosure of information, modification of assets, destruction of assets, and/or the like. A security threat can be intentional like a deliberate attack or unintentional due to an internal failure or malfunctions. Alteration of data/assets may include insertion, deletion, and/or substitution breaches.

(243) The term “signature” or “digital signature” at least in some examples refers to a mathematical scheme, process, or method for verifying the authenticity of a digital message or information object (e.g., an electronic document or other data structure).

(244) The term “verification” at least in some examples refers to a process, method, function, or any other means of establishing the correctness of information or data.

(245) The term “electronic health record” or “EHR” at least in some examples refers to a systematized collection of patient and population electronically stored health information in a digital format. Additionally or alternatively, the term “electronic health record” or “EHR” at least in some examples refers to a health record and/or personal health record (PHR) in electronic form.

Additionally or alternatively, the term “electronic health record” or “EHR” at least in some examples refers to a collection of a patient's stored health information in a digital format. As examples, EHRs include a range of data, including demographics, medical history, progress notes, problems, medications, allergies, vital signs, immunization status, laboratory test results, radiology images, vital signs, personal statistics/data (e.g., age, weight, and/or the like), and billing information. For purposes of the present disclosure, the term “electronic health record” and “electronic medical record” may be used interchangeably, even though these terms may refer to different concepts in some cases or contexts. The term “personal health record” or “PHR” is a health record where health data and other information related to the care of a patient is maintained by the patient.

(246) The term “health care provider”, “healthcare provider”, or “HP” at least in some examples refers to an individual professional, facility, and/or organization licensed to provide healthcare diagnosis and treatment services including medication, surgery, medical devices, and/or the like. Examples of HPs include physicians, dentists, advanced practice providers (APPs) (e.g., physician assistants, nurses, pharmacists, midwives, chiropractors, social workers, psychologists, and/or the like), allied health professionals (e.g., technicians, therapists, hygienists, medical/dental assistants, nutritionists, scribes, counselors, physiologists, interpreters, radiation scientists, midwives, paramedics, pathologists, radiographers, sonographers, and/or the like), health professionals, individual hospitals, hospital networks, healthcare system, medical group, medical practice, clinics, and/or the like.

(247) The term “deployment script” at least in some examples refers to a script that automates the process of deploying software applications to a server, cloud, and/or other environment. In some examples, a “deployment script” includes a series of commands or instructions that are executed automatically to deploy an application, configure settings of the application and/or the environment, and/or start services and/or processes.

(248) The term “blockchain” at least in some examples refers to a list of records (referred to as “blocks”) that are linked together in some way, usually using cryptography. The term “block” as used in “blockchain” at least in some examples refers to a batch of transactions with a reference to a previous block (e.g., a hash of the previous block) in a blockchain thereby linking the block to the

previous block. In previous implementations, each block in a blockchain contains a cryptographic hash of a previous block, a timestamp, and transaction data (e.g., represented as a Merkle tree). Additionally or alternatively, the term “blockchain” at least in some examples refers to a digital database containing information, such as records of financial or other transactions, which can be simultaneously used and shared within a large decentralized, publicly accessible network. Additionally or alternatively, the term “blockchain” at least in some examples refers to a shared, immutable ledger that facilitates the process of recording transactions and tracking assets (tangible and intangible) in a network. In some examples, a blockchain includes a growing list of records, called blocks, that are linked together using cryptography. Each block contains a cryptographic hash of the previous block, a timestamp, and transaction data. The timestamp proves that the transaction data existed when the block was published in order to get into its hash. Each block contains information about the block previous to it, forming a chain, with each additional block reinforcing the ones before it. Therefore, blockchains are resistant to modification of their data because once recorded, the data in any given block cannot be altered retroactively without altering all subsequent blocks. Blockchains are typically managed by a peer-to-peer network for use as a publicly distributed ledger, where nodes collectively adhere to a protocol to communicate and validate new blocks. The term “blockchain mining” or “mining” at least in some examples refers to a process (e.g., computer computations) by which transactions are validated and verified for inclusion in a blockchain.

(249) The terms “consensus algorithm”, “consensus protocol”, “consensus mechanism”, and/or “consensus” at least in some examples refers to one or more coordinating processes that allows distributed computing applications and/or multi-agent systems to agree on a data value that is needed during computation. Examples of consensus algorithms include proof of work (PoW), reusable PoW, proof of useful work, proof of stake (PoS), proof of space, proof of authority, Specialized Proofs of Confidential Knowledge (SPoCKs), Delegated Proof of Stake (DPOS), Byzantine fault tolerance (BFT), BFT-DPOS, Transaction as Proof of Stake (TaPoS), Paxos, distributed lock services (e.g., Chubby provided by Google®), lockstep protocols, Byzantine agreement protocol (BAP), quantum BAP, and/or the like.

(250) The term “consortium blockchain” at least in some examples refers to a group of private blockchains, each owned by individual institutions that permit the sharing of information for various purposes, such as improving/streamlining workflows, transparency, and/or accountability. Additionally or alternatively, the term “consortium blockchain” at least in some examples refers to a hybrid blockchain networks that combines public and private blockchain network features. Additionally or alternatively, the term “consortium blockchain” at least in some examples refers to a permissioned blockchain networks governed by a group of organizations that have decided to share a ledger among themselves for transactions. Additionally or alternatively, the term “consortium blockchain” can also be referred to as a “federated blockchain”.

(251) The term “decentralized application”, “decentralized app”, “Dapp”, “Ðapp”, “dApp”, and/or the like, at least in some examples refers to an application that can operate autonomously, for example, through the use of smart contracts, that run on a decentralized computing platform, blockchain, or other distributed ledger system. Additionally or alternatively, the term “decentralized application”, “decentralized app”, “Dapp”, “Ðapp”, “dApp”, and/or the like, at least in some examples refers to an application configured to generate and distribute tokens according to a standard algorithm and/or set of criteria.

(252) The term “Ethereum” at least in some examples refers to a decentralized, open-source blockchain with smart contract functionality. The term “Ether”, “ETH”, or “E” at least in some examples refers to the native cryptocurrency of the Ethereum platform. The term “Ethereum Improvement Proposals” or “EIPs” at least in some examples refers to standards for the Ethereum platform, including core protocol specifications, client APIs, and contract standards. The term “Ethereum Virtual Machine” or “EVM” at least in some examples refers to a runtime environment for transaction execution in Ethereum. Additionally or alternatively, the term “Ethereum Virtual Machine” or “EVM” at least in some examples refers to a global virtual computer whose state every

participant on the Ethereum network stores and agrees on; where any participant can request the execution of arbitrary code on the EVM; code execution changes the state of the EVM. Additional aspects of Ethereum, Ether, and EVMs are discussed in *Ethereum Development Documentation*, ETHEREUM.ORG (18 Oct. 2018), <https://ethereum.org/en/developers/docs/> (“[EthereumDoc]”), *Ethereum Glossary*, ETHEREUM.ORG (23 Feb. 2022), <https://ethereum.org/en/glossary/>, Takenobu T., *Ethereum EVM illustrated: exploring some mental models and implementations*, rev. 0.01.1 (March 2018), http://takenobu-hs.github.io/downloads/ethereum_evm_illustrated.pdf, and Dr. Gavin Wood, *Ethereum: A secure Decentralised Generalised Transaction Ledger*, Berlin version b8ffc51 (21 Feb. 2022), <https://ethereum.github.io/yellowpaper/paper.pdf> (“[Ethereum-Yellow-Paper]”), the contents of each of which are hereby incorporated by reference in their entireties and for all purposes.

(253) The terms “flow blockchain”, “flow framework”, or simply “flow” at least in some examples refers to a node pipeline that may be used to verify blockchain transactions as discussed in Hentschel et al., *Flow: Separating Consensus and Compute*, arXiv:1909.05821v1 [cs.DC], 21 pages (12 Sep. 2019); Hentschel et al., *Flow: Separating Consensus and Compute—Execution Verification—*, arXiv:1909.05832v1 [cs.DC] (12 Sep. 2019); Hentschel et al., *Flow: Separating Consensus and Compute—Block Formation and Execution—*, arXiv:2002.07403v1 [cs.DC] (18 Feb. 2020); *Flow Primer*, FLOW BLOCKCHAIN (24 Sep. 2020), <https://flow.com/primer>; *FLOW Token Economics*, FLOW BLOCKCHAIN (23 Sep. 2020), <https://flow.com/flow-token-economics>; Mackenzie 10th floor, *How to Launch a Fungible Token on Flow*, FLOW DEVELOPERS (22 Sep. 2022), <https://developers.flow.com/flow/fungible-tokens>; [Flow-NFT]; Bastian Müller (“turbolent”), *The Cadence Programming Language*, FLOW DEVELOPERS (17 Mar. 2021), <https://developers.flow.com/cadence/language>; and Lafrance et al., *Incentives in a Multi-Role Blockchain*, 16 pages (21 Sep. 2020) (collectively referred to herein as “[Flow]”), the contents of each of which are hereby incorporated by reference in their entireties and for all purposes.

(254) The term “gas” at least in some examples refers to a unit that measures the amount of computational effort required to execute specific operations on the Ethereum network. Additionally or alternatively, the term “gas” at least in some examples refers to a limit on the amount of work that is needed to execute a transaction. The term “gas price” or “gas fee” at least in some examples refers to the fee required to conduct a transaction successfully in terms of computational resources, computational complexity, and/or currency.

(255) The term “housekeeping” at least in some examples refers to an entry or exit routine appended to a user-written block of code (such as a routine, subroutine, function, smart contract, and/or the like) at its entry and exit. Additionally or alternatively, the term “housekeeping” at least in some examples refers to any automated or manual process whereby a computer is cleaned up after usage (e.g., freeing resources such as virtual memory and/or the like, saving and/or restoring a program state or context, initializing local variables, garbage collection processes, data conversion, backing up data, disk maintenance processes, and/or the like).

(256) The term “InterPlanetary File System” or “IPFS” at least in some examples refers to a protocol and peer-to-peer network for storing and sharing data in a distributed file system. IPFS uses content-addressing to uniquely identify each file in a global namespace connecting all computing devices. Additional aspects of IPFS are discussed in Interplanetary File System (IPFS) Documentation, IPFS Docs (2018), <https://docs.ipfs.io/> (“[IPFS]”), the contents of which is hereby incorporated by reference in its entirety and for all purposes.

(257) The term “Merkle tree” or “hash tree” at least in some examples refers to a tree data structure in which every leaf node is labelled with the cryptographic hash of a data block, and every node that is not a leaf node (e.g., a branch node, inner node, or inode) is labelled with the cryptographic hash of the labels of its child nodes. Additionally or alternatively, “hash tree” at least in some examples is a generalization of a hash list and a hash chain.

(258) The term “minting” at least in some examples refers to a process of turning digital data into a digital asset such as a token or non-fungible token (NFT), and may involve adding the digital asset to a blockchain or other distributed ledger. In some examples, “minting” is performed according to

[EIP-721], [EIP-1155], Lockyer et al., *EIP-998: ERC-998 Composable Non-Fungible Token Standard [DRAFT]*, ETHEREUM IMPROVEMENT PROPOSALS, no. 998 (July 2018), <https://eips.ethereum.org/EIPS/eip-998> (“[EIP-998]”), Buterin et al., *EIP-1559: Fee market change for ETH 1.0 chain*, ETHEREUM IMPROVEMENT PROPOSALS, no. 1559 (April 2019), <https://eips.ethereum.org/EIPS/eip-1559> (“[EIP-1559]”), Marro et al., *EIP-5375: NFT Author Information and Consent*, ETHEREUM IMPROVEMENT PROPOSALS, no. 5375 (July 2022), <https://eips.ethereum.org/EIPS/eip-5375> (“[EIP-5375]”), and/or Zainan Victor Zhou, *EIP-5679: Token Minting and Burning*, ETHEREUM IMPROVEMENT PROPOSALS, no. 5679, (September 2022), <https://eips.ethereum.org/EIPS/eip-5679> (“[EIP-5679]”), the contents of each of which are hereby incorporated by reference in their entireties and for all purposes.

(259) The term “non-fungible token” or “NFT” at least in some examples refers to a non-interchangeable unit of data. Additionally or alternatively, the term “non-fungible token” or “NFT” at least in some examples refers to a non-interchangeable unit of data that provides or otherwise acts as a certificate of authenticity or proof of ownership of some physical or virtual item or object. NFTs may be stored on a blockchain or other form of digital ledger, and sold or traded. NFTs may be associated with digital files such as photos, videos, audio, virtual property or virtual assets, and/or the like. Moreover, because individual NFTs are uniquely identifiable, NFTs differ from blockchain cryptocurrencies, such as Bitcoin, Ether, and/or the like. Additional aspects of NFTs are discussed in Entriken et al., *EIP-721: Non-Fungible Token Standard*, ETHEREUM IMPROVEMENT PROPOSALS, no. 721 (24 Jan. 2018), <https://eips.ethereum.org/EIPS/eip-721> (“[EIP-721]”) and ReitwieBner et al., *EIP-165: Standard Interface Detection*, ETHEREUM IMPROVEMENT PROPOSALS, no. 165 (23 Jan. 2018), <https://eips.ethereum.org/EIPS/eip-165> (“[EIP-165]”), Burks et al., *EIP-2981: NFT Royalty Standard*, ETHEREUM IMPROVEMENT PROPOSALS, no. 2981 (September 2020), <https://eips.ethereum.org/EIPS/eip-2981> (“[EIP-2981]”), Anders et al., *EIP-4907: Rental NFT, an Extension of EIP-721*, ETHEREUM IMPROVEMENT PROPOSALS, no. 4907 (March 2022), <https://eips.ethereum.org/EIPS/eip-4907> (“[EIP-4907]”), Lance et al., *EIP-5006: Rental NFT, NFT User Extension [DRAFT]*, ETHEREUM IMPROVEMENT PROPOSALS, no. 5006 (April 2022), <https://eips.ethereum.org/EIPS/eip-5006> (“[EIP-5006]”), Anders et al., *EIP-5007: Time NFT, EIP-721 Time Extension [DRAFT]*, ETHEREUM IMPROVEMENT PROPOSALS, no. 5007 (April 2022), <https://eips.ethereum.org/EIPS/eip-5007> (“[EIP-5007]”), Siemens et al., *Flow Non-Fungible Token Standard*, FLOW BLOCKCHAIN (20 Dec. 2021) <https://github.com/onflow/flow-nft/blob/master/README.md> (“[Flow-NFT]”), and/or Karslen et al., *Non-Fingible Token Metadata*, FLOW IMPROVEMENT PROPOSAL, no. 636 (6 Dec. 2021) (“[FLIP-636]”), the contents of each of which are hereby incorporated by reference in their entireties and for all purposes.

(260) The term “on-chain transaction” at least in some examples refers to a transaction that occurs and is considered valid when the blockchain is modified. Additionally or alternatively, the term “on-chain transaction” at least in some examples refers to a transaction that is carried out on a blockchain or blockchain network. In some examples, the term “on-chain transaction” may be synonymous with the term “transaction”.

(261) The term “off-chain transaction” at least in some examples refers to a transaction that takes place or takes value outside of a blockchain. Additionally or alternatively, the term “off-chain transaction” at least in some examples refers to a transaction that is confirmed outside of a blockchain network. Additionally or alternatively, the term “off-chain transaction” at least in some examples refers to a transaction that involves some of the transaction-related work from a blockchain ecosystem, which can later be integrated back into a blockchain.

(262) The term “smart contract” at least in some examples refers to a set of self-executing code. Additionally or alternatively, the term “smart contract” at least in some examples refers to a program, application, set of trigger functions, or transaction protocol that is intended to automatically execute, control, or document relevant events and actions according to some predefined criteria or conditions such as those defined in a contract, agreement, or policy. Additional aspects of smart contracts are

discussed in Mudge et al., *EIP-173: Contract Ownership Standard*, ETHEREUM IMPROVEMENT PROPOSALS, no. 173 (7 Jun. 2018), <https://eips.ethereum.org/EIPS/eip-173> (“[EIP-173]”), Radomski et al., *EIP-1155: Multi Token Standard*, ETHEREUM IMPROVEMENT PROPOSALS, no. 1155 (17 Jun. 2018), <https://eips.ethereum.org/EIPS/eip-1155> (“[EIP-1155]”), Murray et al., *EIP-1167: Minimal Proxy Contract*, ETHEREUM IMPROVEMENT PROPOSALS, no. 1167 (June 2018), <https://eips.ethereum.org/EIPS/eip-1167> (“[EIP-1167]”), Giordano et al., *EIP-1271: Standard Signature Validation Method for Contracts*, ETHEREUM IMPROVEMENT PROPOSALS, no. 1271 (July 2018), <https://eips.ethereum.org/EIPS/eip-1271> (“[EIP-1271]”), *Enterprise Ethereum Alliance Client Specification v7*, EEA Editor's Draft, version 7 (10 Feb. 2022), <https://entethalliance.github.io/client-spec/spec.html> (“[EEA-CS7]”), *Solidity Documentation*, release 0.8.18, revision c1040815 (8 Sep. 2022) (“[Solidity]”), Vyper Team, *Vyper Documentation*, release v0.3.8, revision 1cd6f3db (15 Dec. 2022) (“[Vyper]”), FuelLaps™, Yul+, version 0.2.3 (10 Oct. 2020), <https://github.com/FuelLabs/yulp> (“[Yul+]”), *The Cadence Programming Language*, FLOW DEVELOPERS (17 Mar. 2021), <https://developers.flow.com/cadence/language/index> (“[Cadence]”), and *Contracts*, OPENZEPLIN |DOCS, version 4.x (2022), <https://docs.openzeppelin.com/contracts/4.x/> (“[OZContracts]”), the contents of each of which are hereby incorporated by reference in their entireties and for all purposes. In some examples, one or more smart contracts can be implemented as “diamonds” as discussed in Mudge, *EIP-2535: Diamonds, Multi-Facet Proxy*, ETHEREUM IMPROVEMENT PROPOSALS, no. 2535 (February 2020), <https://eips.ethereum.org/EIPS/eip-2535> (“[EIP-2535]”), the contents of which are hereby incorporated by reference in its entirety and for all purposes.

(263) The term “staking” at least in some examples refers to the process of holding or locking up a certain amount of cryptocurrency or tokens in order to participate in maintaining the operations and security of a blockchain network. Additionally or alternatively, the term “staking” at least in some examples refers to a consensus mechanism used in Proof-of-Stake (PoS) blockchain networks, where validators (also referred to as “validator nodes”, “staking nodes”, or “block producers”) are chosen to create new blocks based on the amount of cryptocurrency or tokens they have staked or locked up as collateral.

(264) The term “token” at least in some examples refers to a software and/or hardware object or element that represents the right or ability to perform an operation. Additionally or alternatively, the term “token” at least in some examples refers to a software and/or hardware object or element that references or maps to another data item, which may be done through a tokenization system. The term “security token”, “authentication token”, “cryptographic token”, and/or the like at least in some examples refers to a software object and/or a physical device used for computer authentication. The term “tokenization” at least in some examples refers to a process for substituting a data item with another equivalent data item (e.g., a “token”) that has no extrinsic or exploitable meaning or value, or at least a different meaning or value than the original data item. Additional aspects of tokens are discussed in Vogelsteller et al., *EIP-20: Token Standard*, ETHEREUM IMPROVEMENT PROPOSALS, no. 20 (19 Nov. 2015), <https://eips.ethereum.org/EIPS/eip-20> (“[EIP-20]”), Dafflon et al., *EIP-777: Token Standard*, ETHEREUM IMPROVEMENT PROPOSALS, no. 777 (20 Nov. 2017), <https://eips.ethereum.org/EIPS/eip-777> (“[EIP-777]”), StartfundInc, *EIP-5528: Refundable Fungible Token*, ETHEREUM IMPROVEMENT PROPOSALS, no. 5528 (August 2022), <https://eips.ethereum.org/EIPS/eip-5528> (“[EIP-5528]”), and/or Igualada et al., *Fingible Token Metadata*, FLOW IMPROVEMENT PROPOSAL, no. 1087 (16 Aug. 2022) (“[FLIP-1087]”), the contents of each of which are hereby incorporated by reference in their entireties and for all purposes. In some examples, the term “token” and/or “NFT” can include semi-fungible tokens as discussed in Wang et al., *EIP-3525: Semi-Fungible Token*, ETHEREUM IMPROVEMENT PROPOSALS, no. 3525 (December 2020), <https://eips.ethereum.org/EIPS/eip-3525> (“[EIP-3525]”) and/or Zhu et al., *EIP-5727: Semi-Fungible Soulbound Token [DRAFT]*, ETHEREUM IMPROVEMENT PROPOSALS, no. 5727 (September 2022), <https://eips.ethereum.org/EIPS/eip-5727> (“[EIP-5727]”), the contents of which is hereby incorporated by reference in its entirety and for all purposes.

(265) The term “transaction” at least in some examples refers to a unit of work performed within a computing system and/or a database management system. Additionally or alternatively, the term “transaction” at least in some examples refers to information processing that is divided into individual, indivisible operations. Additionally or alternatively, the term “transaction” at least in some examples refers to the physical and/or electronic exchange or transfer of assets or objects. Additionally or alternatively, the term “transaction” at least in some examples refers to a request to execute operations on a blockchain that change the state of one or more accounts. The term “private transaction” at least in some examples refers to a transaction where some information about the transaction, such as the payload data, or the sender or the recipient, is only available to the subset of parties privy to that transaction.

(266) The term “wallet” or “digital wallet” at least in some examples refers to an electronic device, online/web service, and/or software application that allows a party to make electronic transaction with another party. Additionally or alternatively, the term “wallet” or “digital wallet” at least in some examples refers to an electronic device, online/web service, and/or software application used to store credentials (e.g., cryptographic private keys) that are used to perform transactions and/or access an account. Additional aspects of wallets are discussed in [EEA-CS7].

(267) The term “translation” at least in some examples refers to the process of converting or otherwise changing data from a first form, shape, configuration, structure, description, and/or arrangement into a second form, shape, configuration, structure, description, and/or arrangement. In some examples, “translation” can include transcoding and/or transformation. The term “transcoding” at least in some examples refers to taking information/data in one format (e.g., a packed binary format) and translating the same information/data into another format in the same sequence. Additionally or alternatively, the term “transcoding” at least in some examples refers to taking the same information, in the same sequence, and packaging the information (e.g., bits or bytes) differently. The term “transformation” at least in some examples refers to changing data from one format and writing it in another format, keeping the same order, sequence, and/or nesting of data items. Additionally or alternatively, the term “transformation” at least in some examples involves the process of converting data from a first format or structure into a second format or structure, and involves reshaping the data into the second format to conform with a schema or other like specification. Transformation may include rearranging data items or data objects, which may involve changing the order, sequence, and/or nesting of the data items/objects. Additionally or alternatively, the term “transformation” at least in some examples refers to changing the schema of a data object to another schema.

(268) Aspects of the inventive subject matter may be referred to herein, individually and/or collectively, merely for convenience and without intending to voluntarily limit the scope of this application to any single aspect or inventive concept if more than one is in fact disclosed. Thus, although specific aspects have been illustrated and described herein, it should be appreciated that any arrangement calculated to achieve the same purpose may be substituted for the specific aspects shown. This disclosure is intended to cover any and all adaptations or variations of various aspects. Combinations of the above aspects and other aspects not specifically described herein will be apparent to those of skill in the art upon reviewing the above description.

Claims

1. A computing system, comprising: an interface circuitry; a processor circuitry connected to the interface circuitry; a non-transitory memory containing instructions, which when executed by the processor circuitry, causes the processor circuitry to perform the steps of: receiving, by the interface circuitry, from an online portal, identification (ID) data associated with a person, the ID data comprising one or more of a physical or electronic ID document, contact information, authentication credentials, and biometric data; forwarding, by the interface circuitry, the received ID data; verifying, by the processor circuitry, authenticity of the ID data against one or more authoritative sources;

storing, by the processor circuitry, the verified ID data as metadata in a distributed file system, detecting, by the processor circuitry, a trigger to mint an NFT ID for the person; executing, by a minting engine, in response to detection of the trigger, a smart contract to cause the NFT ID to be minted based on the metadata and according to a set of parameters defined by the smart contract, receiving, by the processor circuitry, from the minting engine, a minted NFT ID based on the execution of the smart contract, and issuing, by the processor circuitry, the minted NFT ID to an administrator (“admin”) or to a client associated with the person; and storing, by the processor circuitry, the minted NFT ID in one or more distributed ledgers or blockchains, wherein the NFT ID comprises a digitized form of a physical identity document.

2. The computing system of claim 1, wherein the instructions further cause the processor circuitry is to perform the steps of: generating transaction data to be used for executing the smart contract, wherein the transaction data includes one or more of a token ID for the NFT ID, ownership information of an owner of the NFT ID, a reference to a storage location of the metadata in the distributed file system, and supply information indicating a number and type of NFT IDs to be minted.

3. The computing system of claim 1, wherein the minted NFT ID includes a reference to a storage location of the metadata, and the minted NFT ID does not include the ID data and the metadata.

4. The computing system of claim 1, wherein the admin and the client associated with the person comprise a standalone wallet device or a client application (app), a web app, or a digital wallet app operating on a client device.
