

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250278775

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Blinn; Christopher et al.

Dynamic Data Object Distribution Based on Historical Performance

Abstract

Systems and method for dynamic data object distribution based on historical performance. The method includes accessing a centralized data structure with a number of order requests. Computing a shopping list including data objects for items and characteristic data for each item. Accessing data indicative of selection of the first shopping list by a first device, updating the order status of the first shopping list. Accessing data indicative of selection of the first shopping list by a second device. Computing a first subset of items and second subset of items for each respective computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective item of a plurality of items. Transmitting data to cause an interactive user interface of the first computing device to display the first subset of items.

Inventors: Blinn; Christopher (Mountain View, CA), Joshi; Pushkar Ravindra (Sunnyvale, CA), Rodríguez; Nolberto Castellanos (Medellín, Antioquia, CO), Shorser; Reuben Matthew (San Francisco, CA), Stein; Maxwell Dean (Jersey City, NJ), Xiong; Wei (Bothell, WA)

Applicant: Uber Technologies, Inc. (San Francisco, CA)

Family ID: 96880378

Appl. No.: 18/651077

Filed: April 30, 2024

Related U.S. Application Data

us-provisional-application US 63560260 20240301

Publication Classification

Int. Cl.: G06Q30/0601 (20230101)

Background/Summary

FIELD

[0001] The present disclosure generally relates to dynamic data object distribution based on historical performance associated with user profiles. More particularly, data from mobile client devices can be monitored in real-time to update data structures to intelligently split data objects associated with items in a list to optimize performance metrics moving forward.

BACKGROUND

[0002] Food delivery services allow a user to request a service that can be performed by a vehicle or courier. For instance, a user can request, through a delivery service application, a delivery service having a pick-up location, a drop-off location, and items for delivery. A courier and/or shopper can be assigned to perform the delivery service for the user. This can include selecting items from a pick-up location and transporting the items to a transition point and/or drop-off location.

SUMMARY

[0003] Aspects and advantages of embodiments of the present disclosure will be set forth in part in the following description, or can be learned from the description, or can be learned through practice of the embodiments.

[0004] One aspect of the present disclosure is directed to a computing system. The computing system includes one or more processors and one or more tangible, non-transitory, computer readable media that store instructions that are executable by the one or more processors to cause the computing system to perform operations. The operations include accessing data including a centralized data structure including a plurality of order requests, wherein each order request of a centralized list of order requests includes a plurality of data objects, each data object being indicative of an item. The operations include computing, based on a first order request of the centralized list of order requests and merchant location data, a shopping list including: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item. The operations include storing the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices. The operations include accessing data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices. The operations include automatically updating, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data. The operations include accessing data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices. The operations include based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, computing a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective item of a plurality of items. The operations include transmitting data including instructions, that, when executed by the first computing device, cause an interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.

[0005] Another Example aspect of the present disclosure is directed to a computer-implemented

method. The method includes accessing data including a centralized data structure including a plurality of order requests, wherein each order request of a centralized list of order requests includes a plurality of data objects, each data object being indicative of an item. The method includes computing, based on a first order request of the centralized list of order requests and merchant location data, a shopping list including: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item. The method includes storing the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices. The method includes accessing data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices. The method includes automatically updating, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data. The method includes accessing data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices. The method includes based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, computing a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective item of a plurality of items. The method includes transmitting data including instructions, that, when executed by the first computing device, cause an interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.

[0006] Yet another example aspect of the present disclosure is directed to one or more non-transitory computer readable media storing instructions that are executable by one or more processors to perform operations. The operations include accessing data including a centralized data structure including a plurality of order requests, wherein each order request of a centralized list of order requests includes a plurality of data objects, each data object being indicative of an item. The operations include computing, based on a first order request of the centralized list of order requests and merchant location data, a shopping list including: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item. The operations include storing the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices. The operations include accessing data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices. The operations include automatically updating, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data. The operations include accessing data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices. The operations include based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, computing a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective item of a plurality of items. The operations include transmitting data including instructions, that, when executed by the first computing device, cause an interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.

[0007] Other example aspects of the present disclosure are directed to other systems, methods, apparatuses, tangible non-transitory computer-readable media, and devices for performing functions described herein. These and other features, aspects and advantages of various implementations will become better understood with reference to the following description and

appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate implementations of the present disclosure and, together with the description, serve to explain the related principles.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Detailed discussion of embodiments directed to one of ordinary skill in the art are set forth in the specification, which makes reference to the appended figures, in which:

[0009] FIG. 1 depicts an example computing ecosystem according to example aspects of the present disclosure.

[0010] FIG. 2 depicts a block diagram of an example flowchart for dynamic order splitting according to aspects of the present disclosure.

[0011] FIG. 3 depicts an example flow chart method for dynamic order splitting according to aspects of the present disclosure.

[0012] FIG. 4 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0013] FIG. 5 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0014] FIG. 6 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0015] FIG. 7 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0016] FIG. 8 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0017] FIG. 9 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0018] FIG. 10 depicts a block diagram of an example data structures used for dynamic order splitting according to aspects of the present disclosure.

[0019] FIG. 11 depicts an example user interface for dynamic order splitting according to aspects of the present disclosure.

[0020] FIG. 12A to FIG. 12C depict example user interface for dynamic order splitting according to aspects of the present disclosure.

[0021] FIG. 13A to FIG. 13C depict example user interface for dynamic order splitting according to aspects of the present disclosure.

[0022] FIG. 14A to FIG. 14B depict example user interface for dynamic order splitting according to aspects of the present disclosure.

[0023] FIG. 15A to FIG. 15B depict example user interface for dynamic order splitting according to aspects of the present disclosure.

[0024] FIG. 16A to FIG. 16B depict example user interface for dynamic order splitting according to aspects of the present disclosure.

[0025] FIG. 17 depicts an example merchant location associated with dynamic order splitting according to aspects of the present disclosure.

[0026] FIG. 18 depicts an example computing system diagram of an example computing system for dynamic order splitting according to aspects of the present disclosure.

DETAILED DESCRIPTION

[0027] Generally, the present disclosure is directed to systems and methods for improving the efficiency of computing applications and computing resources associated with a distributed computing ecosystem including multiple client devices and one or more network computing

systems (e.g., cloud-based systems). For instance, the technology of the present disclosure can be utilized to dynamically distribute data payloads among a plurality of hardware devices associated with a merchant location that are connected to a cloud-based delivery platform. This can be implemented through, for example, real-time order splitting and shopper claiming based on shopper client device data and shopping list item feature data for merchant locations that have multiple shoppers and orders active at the same time.

[0028] More particularly, aspects of the present disclosure can be used to determine when to designate a shopping list as eligible for splitting as well as how and when to dynamically update interactive user interfaces (e.g., graphical user interfaces (GUIs)) associated with multiple shopper computing devices to facilitate splitting the lists and completing the orders accordingly. By doing so, the technology described herein can improve the computational efficiency of the network computing systems as well as the distributed client devices connected thereto, by avoiding the duplication of data across the client devices, allowing for more efficient completion of computational tasks, without resource-intensive re-work by the network and client computers.

[0029] Moreover, the computing system and methods of the present disclosure can intelligently determine opportunities for data payload distribution based on the status of computing devices in the network. For example, the network computing system can track (e.g., via digital checklists, GPS pings) the progress of a client device being used by a shopper to fill an order and/or the progress of a client device used by a courier that is driving to the merchant location. The network computing system can utilize this information in real-time to determine whether data indicative of an order should be split among client devices of multiple shoppers (e.g., to allow for quicker shopping). For instance, if a shopper is taking longer than usual or is predicted to complete shopping for an order after a courier is scheduled to arrive to pick up the order, the network computing system can determine that the order can be split and, in some instances, can encourage the order being split. This can occur by transmitting a real-time message to a first shopper indicating they can request the order to be split or transmitting a real-time message to a second shopper indicating that an active order is available to be split.

[0030] The network computing system can intelligently compute how to split data payloads among the plurality of client devices. For example, the data indicative of the shopping list can be intelligently divided among the shoppers' client devices based on the characteristics of the items to be shopped, the characteristics of the shoppers, the progress, etc. The network computing system can continuously monitor the shoppers' client devices to determine whether to reassign certain data (e.g., a shopping item) from one client device to another and generate updated UI instructions regarding the same. In this way, the technology of the present disclosure can continue to distribute the computational load among the client devices, to ensure efficient order completion while improving the computational load on respective client devices (saving valuable computing resources).

[0031] Existing methods provide for grouping items within lists and generating paths for shoppers, however, these methods fail to provide for centralized management of shopping for a single order across multiple devices and users while providing for real-time order progress and dynamically adjusting the interactive user interfaces of respective computing devices to present the subset of items for a user to shop.

[0032] Reference now will be made in detail to embodiments, one or more example(s) of which are illustrated in the drawings. Each example is provided by way of explanation of the embodiments, not limitation of the present disclosure. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made to the embodiments without departing from the scope of the present disclosure. For instance, features illustrated or described as part of one embodiment can be used with another embodiment to yield a still further embodiment. Thus, it is intended that aspects of the present disclosure cover such modifications and variations.

[0033] For example, the following describes the technology of this disclosure within the context of

a number of shopper client devices (e.g., mobile shopper devices) within a grocery store for example purposes only. As described herein, the technology described herein is not limited to shopper client devices in grocery stores and can be implemented for or within any location where items are available for purchase and other computing systems.

[0034] FIG. 1 depicts an example computing system **100** according to example aspects of the present disclosure. Example computing system **100** can include a network computing system **101**, one or more users **125** associated with one or more user devices **121**, one or more shoppers **135** associated with one or more shopper devices **131**, one or more couriers associated with one or more courier devices **151**, one or more merchants **145** associated with one or more merchant systems **146**, and one or more service providers **165** associated with one or more service provider systems **166**. In some examples, the one or more merchants **145** can be associated with shopper devices **131** (e.g., a designated shopper at a merchant location). Example computing system **100** can facilitate delivery services between users **125** and merchants **145** by utilizing shoppers **135** to retrieve requested items from merchant locations associated with merchants **145** and utilizing couriers **155** to retrieve the requested items from the merchant locations associated with merchants **145** to deliver the requested items to a drop-off location associated with an order request from one or more users **125**. In some instances, couriers **155** can be shoppers **135**. For instance, courier device **151** can include shopper device **131**. In some instances, couriers **151** can retrieve requested items from merchant locations associated with merchant **145**.

[0035] With respect to examples as described herein, the computing system **100** can be implemented on a server, on a combination of servers, or on a distributed set of computing devices which communicate over a network such as the Internet. For example, the computing system **100** can be distributed using one or more servers and/or client devices. In other examples, computing system **100** is implemented as part of, or in connection with a network computing system **101**, where, for example, operators (e.g., shoppers **135**, couriers **155**, etc.) use service vehicles to provide delivery services for requesting users **125**. In some examples, the computing system **100** can be implemented using client devices of users (e.g., user devices **121**, shopper devices **131**, courier devices **151**) associated with users **125**, shoppers **135**, couriers **155**, and merchants **145** with the individual devices executing a corresponding service application (e.g., application **122**, application **132**, application **152**, application **148**, application **168**) that causes the computing device to operate as an information inlet and/or outlet for network computing system **101**. In other examples, computing system **100** can be implemented using one or more merchant systems **146** associated with one or more merchants **145**. In other examples, computing system **100** can be implemented using one or more service provider systems **166**. Merchant system **146** or service provider systems **166** can operate as an information inlet and/or outlet for computing system **100** to exchange data with network computing system **101**.

[0036] In some instances, applications on the client devices (e.g., e.g., application **122**, application **132**, application **152**, application **148**, application **168**) can communicate with network computing system **101** via one or more application programming interfaces (APIs **170**). APIs can include infrastructure to allow for sharing of data across computing system **100** without the data being in a standardized form utilizing a set of protocol and procedures.

[0037] Network computing system **101** can include a number of subsystems and components for performing various operations. For example, network computing system **101** can include an operations computing system **103**, data repository **105**, and one or more machine-learned models **114**. Network computing system **101** can be any computing device that is capable of exchanging data and sharing resources. For example, network computing system **101** can include one or more networked devices configured to store or transmit data over physical or wireless technologies. In some examples, network computing system **101** can include hardware and software. In other examples, network computing system **101** can include physical equipment that is connected to a physical network.

[0038] Network computing system **101** can include an operations computing system **103**. In some examples, operations computing system **103** can be implemented by one or more computing devices. For example, operations computing system **103** can include one or more processors and one or more memory devices. The one or more memory devices can store instructions executable by the one or more processors to cause the one or more processors to perform operations or functions associated with other subsystems or components of network computing system **101**.

[0039] In some examples, operations computing system **103** can include an order request subsystem **104** configured to receive order requests from users **125** for delivery services. For example, a user **125** can submit a delivery service order request through an application **122** running on user device **121** associated with user **125**. In some examples, order request subsystem **104** can receive a single delivery service order request from a user **125**. In some examples, order request subsystem **104**, can receive multiple delivery service order requests from multiple users **125** concurrently. In some examples, order request subsystem **104** can coordinate multiple delivery service order requests from the same user **125** which require selection or delivery of grocery items from multiple merchant locations.

[0040] Order request subsystem **104** can perform actions to coordinate a completion time of an order request, with an estimated time of arrival (e.g., of a courier) for requested items. In some examples, where merchant **145** or an individual associated with merchant **145** is associated with shopper device **131**, order request subsystem **104** can coordinate actions to ensure a courier (e.g., individual delivering items to user **125**) does not have to wait an extended period of time at the merchant location for merchant **145** to prepare the order request. For instance, network computing system **101** can determine that there are multiple available shoppers **135** associated with respective shopper devices **131**. Network computing system **101** can dynamically distribute data objects associated with physical items (e.g., split an order request) among multiple shopper devices **131** based on data associated with the shoppers (e.g., shopper data **108**), data associated with the order request (e.g., order request data **106**), progress data associated with the order, and other relevant data (e.g., merchant data **110**). In some instances, shopper device **131** can be capable of transmitting location data to network computing system **101**. The location data can be indicative of a more granular location within a merchant location such that a store section, aisle, etc. can be identified.

[0041] In other examples, order request subsystem **104** can determine if there are insufficient resources to complete the delivery service order request. For example, insufficient resources can indicate there are no available couriers to deliver the requested grocery items. In some examples, order request subsystem **104** can reject a delivery service order request if there are insufficient resources (e.g., shoppers **135**, couriers, etc.) to complete the grocery delivery order request. In other examples, order request subsystem **104** can offer alternative solutions (e.g., a later time or day) if there are insufficient resources to complete the delivery order request.

[0042] In some examples, order request subsystem **104** can provide data indicative of the delivery service request to other subsystems and components of network computing system **101** for further processing or storage. For instance, order request subsystem **104** can provide the data indicative of the delivery service request to data repository **105**. Data repository **105** can include, for example, data stores such as relational databases, non-relational databases, key-value stores, full-text search engines, message queues, etc.

[0043] Data repository **105** can include order request data **106**, shopper data **108**, and merchant data **110**. Such data can be encrypted, stored in a secure manner, pseudonymized, or optionally collected (e.g., as selected by a user **125**). In some examples, data repository **105** can be replicated to ensure the data stored in data repository **105** is readily available for the plurality of user devices **121**, shopper devices **131**, courier devices **151**, service provider systems **166**, and merchant systems **146**.

[0044] Shopper data **108** can include historical performance data **108A**, location data **108B**, and

other shopper data. For instance, shopper data **108** can include data associated with shoppers **135** of the delivery service entity. In some examples, shopper data **108** can include user profile information (e.g., name, device type, shopper type (merchant versus courier) and user preferences (e.g., preferred items, categories, store locations).

[0045] Historical data **108A** can include historical information associated with users **125** or merchants **145**. For example, historical data can include a previous delivery service order requests that indicate items, merchant locations, and feedback from a user **125**. In some examples, historical data can include the history of specific grocery item availability at a merchant location, completion time to prepare an order, etc.

[0046] In some examples, data repository **105** can be updated by user devices **121**, shopper devices **131**, and merchant systems **146**. For example, as users **125** submits, via application **122** running on user device **121**, a delivery service order request, data repository **105** can be updated to reflect the delivery service request. In some examples, shopper device **131** can update, via application **132** running on shopper device **131**, data repository **105** by providing updates (e.g., item unavailable, shopping complete, etc.) associated with the delivery service order request. In other examples, merchant systems **146** can update data repository **105** to reflect changes such as inventory levels at merchant locations, operating hours of merchant locations, etc. In some examples, data repository **105** can be updated dynamically (e.g., as events occur) or can be updated on a scheduled reoccurring basis. For instance, the applications running on the respective devices can communicate with network computing system **101** via one or more API(s) **170** which can facilitate requests, data transmission, etc. between network computing system **101** and the respective applications on the respective devices. Data repository **105** can include order request data **106** which can be associated with the delivery service order request. For instance, the order request data **106** can include a number of items and associated feature data. For instance, the items can be individual items in a shopping list. Feature data can include characteristics associated with items such as selected quantity, item count, replacement indication, or other data associated with items. Additionally, or alternatively, order request data **106** can include a pick-up location, drop-off location, delivery instructions, promised delivery time, or other relevant data.

[0047] In some instances, order request data **106** can include item subset data **106A**. For instance, the system (e.g., models **114**) can determine that data objects (e.g., items) associated with an order request can be split across multiple shopper devices **131**. As such, the order request data **106** can be split into a number of item subset data structures **106A**. The item subset data structures **106A** can be updated during the completion of an order based on item fulfillment, shopper speed, shopper device location, expected courier arrival time, or other input data used to determine data object distribution.

[0048] Data repository **105** can include shopper data **108**. Shopper data **108** can include historical performance data **108A** and location data **108B**. Historical performance data **108A** can include number of completed orders, complex order fulfillment history, order completion rate, replacement item satisfaction metrics, shopper rating, or other metrics associated with historical performance of a particular shopper (e.g., associated with a shopper identifier). Location data **108B** can include location data obtained from location determining hardware of a shopper device **131**. For instance, location data **108B** can include near real-time location data which can provide insight into a location of a shopper device **131** within a merchant location such that the location data can be utilized by the system (e.g., and associated models) to determine allocation of the data objects associated with the respective shopping lists to the respective distributed shopper devices **131**.

[0049] Data repository **105** can include merchant data **110**. Merchant data **110** can include inventory data **110A** and item feature data **110B**. Inventory data **110A** can include data regarding available items, item identifiers (e.g., stock keeping unit (SKU), universal product code (UPC), European article number (EAN), global trade item number (GTIN), or other product identifier), number of items in stock, restock dates and times (e.g., most recent restock, next planned restock),

or other inventory related data.

[0050] Item feature data **110B** can include data such as category of an item, special designation of an item, location of an item, similar items, items often shopped together, or any other feature data. A category of an item can include frozen, perishable, non-perishable, non-edible, refrigerated, shelf stable, produce, canned goods, outside aisle, pharmacy, bakery, snacks, or beverages. A special designation of an item can include, for example, refrigerated, age restriction, fragile, or special packaging.

[0051] Data repository **105** can include user data which can include data associated with users **125** of the delivery service entity. In some examples, user data can include user profile information (e.g., name, address, payment information) and user preferences (e.g., replacement item indicators, preferred brands, ripeness level of produce grocery items) of users.

[0052] In some examples, one or more machine-learned models **114** can utilize the data stored in data repository **105**. By way of example, the one or more models **114** can be or can otherwise include various machine-learned models such as, for example, regression networks, generative adversarial networks, neural networks (e.g., deep neural networks), support vector machines, decision trees, ensemble models, k-nearest neighbors models, Bayesian networks, or other types of models including linear models or non-linear models. Example neural networks include feed-forward neural networks, recurrent neural networks (e.g., long short-term memory recurrent neural networks), convolutional neural networks, or other forms of neural networks.

[0053] For example, one or more models **114** can obtain user data including user preferences, shopper data **108** including historical performance data **108A** and location data **108B**, and merchant data **110** including inventory data **110A** and item feature data **110B**, to determine a dynamic allocation of data objects among shopper devices **131** for items of a current delivery service order request. In some examples, the one or more models **114** can include a data object allocation model trained to determine an allocation of data objects associated with items among shopper devices **131**.

[0054] As indicated, computing system **100** can include various users **125** and user devices **121**. Users **125** can include individuals, or a group of individuals associated with a user profile configured to interact with a delivery service entity. In some examples, users **125** can utilize a guest profile (e.g., one time use) to interact with the delivery service entity. User device **121** can include a mobile computing device, such as handheld point of sale device, a smartphone, tablet computer, laptop computer, VR or AR headset device, a device including a barcode scanner or other sensor, and the like. As such, user device **121** can include components such as a microphone, a camera, a satellite receiver, and a communication interface to communicate with external entities using any number of wireless communication protocols. In some examples, user device **121** can store a designated service application (e.g., application **122**) in a local memory. In some examples, the memory can store additional applications executable by one or more processors of user device **121**, enabling access and interaction with one or more host servers over one or more networks. In some examples, user devices **121** can communicate with network computing system **101** over one or more networks.

[0055] User devices **121** can be associated with users **125** and allow user **125** to interact with the delivery service entity (e.g., network computing system **101**). For example, in response to user input by a user **125**, application **122** can interact with user device **121** to display an application interface on a user interface of user device **121**. In some examples, user **125** can select items and submit a delivery service order request through application **122** running on user device **121**. In some examples, user **125** can view order updates (e.g., order in progress, complete, unavailable items, etc.) on the user interface of the user device. In some examples, user **125** can view an ETA (estimated time of arrival) for the order request.

[0056] In some examples, user device **121** can receive data from network computing system **101**. For example, application **122** can receive data stored in data repository **105** of network computing

system **101**. In some examples, application **122** can interact with user device **121** to display historical data (e.g., a user's order history). In some examples, application **122** can interact with user device **121** to display merchant data **110** (e.g., available grocery items available at a merchant location). In other examples, application **122** can interact with user device **121** to display suggestions for grocery items that are likely to be desired by user **125**.

[0057] For example, the one or more models **114** can include a user preference model trained to determine the preferences of a user **125**. For example, the user preference model can utilize user data containing user preference selections and historical data containing an order history of user **125** to determine the preferences of user **125** for a current order request. In some examples, application **122** can interact with user device **121** to display the suggested items determined by the one or more models **114** of network computing system **101**. For example, the one or more models can include a suggested item model trained to determine suggested items based on data stored in data repository **105**. In other examples, application **122** can interact with user device **121** to display suggested user preferences for currently selected items (e.g., items in the user's cart) prior to the user submitting the order request.

[0058] In some examples, user device **121** can transmit preference data to network computing system **101**. For example, application **122** can interact with the user interface of user device **121** to display selectable options for user **125**. For example, application **122** can interact with user device **121** to display user preference options. In some examples, user **125** can indicate a preference for replacement items. For instance, a preference for replacement items can include not replacing an item, requesting a recommendation for a replacement item, automatically selecting the best available alternative, or otherwise setting up rules relating to the replacement of various items (or item types). For instance, replacement preferences can vary based on associated merchant, type of item (e.g., produce versus trash bags), or other replacement options. Additionally, user preferences can include a preference that produce, or meat grocery items meet a preferred ripeness or fattiness level by interacting with (e.g., adjusting, sliding, swiping, typing, etc.) an interactive ripeness element (e.g., slider, menu) on the display of user device **121**. In some examples, user **125** can indicate (e.g., prior to submitting an order request) that user preferences should be used for all future order requests. For example, user **125** can indicate (e.g., prior to submitting an order request) that user preferences should only be used for a current order request. For instance, application **122** can interact with user device **121** to display user preference options and user **125** can select a user interface element to indicate that user preference selections are only for the current order request. In other examples, user **125** can opt to not save the user preference selections.

[0059] In other examples, user **125** can update previously saved user preferences. For example, application **122** can interact with the user interface of user device **121** to display saved user preference options. User **125** can indicate updated user preferences by updating an item preference user interface element. For example, user **125** can indicate an updated user preference relating to replacement indication or an updated user preference that produce, or meat grocery items meet a preferred ripeness or fattiness level by interacting with (e.g., adjusting, sliding, swiping, typing, etc.) an interactive ripeness element (e.g., slider, menu) on the display of user device **121**.

[0060] In some examples, user data can include user preferences. The user preference selections can be transmitted over one or more networks and stored in a data repository **105** of network computing system **101**. In some examples, the user preference selections can be used as input data to one or more models **114** of network computing system **101** to determine an allocation of data objects among shopper devices **131**.

[0061] In some examples, user device **121** can transmit feedback data to network computing system **101**. For example, application **122** can interact with user device **121** to display a feedback element on the user interface of user device **121**. User **125** can provide feedback indicating satisfaction or dissatisfaction with the delivery service. In some examples, user **125** can indicate feedback associated with user preferences, replacement items, or order fulfillment.

[0062] For example, application **122** can interact with the user interface of user device **121** to display a feedback user interface element. In some examples, the feedback user interface element can be displayed after user **125** has received the requested grocery items. For example, user **125** can indicate that a specified replacement preference (e.g., no replacement, best alternative, recommend a replacement) or specified item preference (e.g., a produce ripeness level) was satisfied by providing a rating (e.g., rating on a rating scale or text via a rich text editor, etc.). In some examples, user **125** can indicate that a specific item preference was not satisfied by providing a rating (e.g., rating on a rating scale or text via a rich text editor, etc.). In some examples user data can include feedback data captured by the feedback user interface element. In other examples, historical data can include feedback data captured by the feedback user interface element. The user feedback data can be captured by the feedback user interface element via the display of user device **121** and transmitted to network computing system **101** and stored in data repository **105**. In some examples, the user feedback data can be used to train models **114** of network computing system **101**. For instance, user feedback data can be associated with a merchant and/or shopper and can be utilized to update historical performance data **108A** and/or item feature data **110B**.

[0063] The computing system **100** can include shoppers **135** and shopper devices **131**. A shopper **135** can be used to retrieve requested items from a merchant location. In some examples, shopper **135** can include the courier (e.g., individual transporting requested grocery items), or an individual associated with a merchant **145** (e.g., a designated shopper at a merchant location). Shopper device **131** can include a mobile computing device, such as a smartphone, tablet computer, laptop computer, VR or AR headset device, and the like. As such, shopper device **131** can include features such as a microphone, a camera, a satellite receiver, and a communication interface to communicate with external entities using any number of wireless communication protocols.

[0064] In some implementations, shopper device **131** can be a courier device via which a courier receives data associated with the delivery service request. This can include instructions for traveling to a merchant location associated with one or more merchants **145**, items selected by a user **125**, instructions for shopping for one or more items associated with a delivery service request, etc.

[0065] In some implementations, shopper device **131** can be a mobile computing device associated with a merchant location. This can include a dedicated tablet, phone, etc. that is utilized by a shopper **135** within the merchant location. In some instances, shopper device **131** can include an authentication interface to associate a particular shopper **135** with shopper device **131** for fulfillment of a particular order, during a shift. Shopper device **131** can receive, for a merchant **145**, data that is associated with the delivery service order request such as order request data **106**. This can include items selected by a user **125**, pick-up times, etc. In some implementations, a shopper device **131** can be communicatively connected to a computing system of the merchant location (e.g., inventory systems, POS systems, etc.).

[0066] In some examples, shopper device **131** can store a designated service application (e.g., application **132**) in a local memory. In some examples, the memory can store additional applications executable by one or more processors of shopper device **131**, enabling access and interaction with one or more host servers over one or more networks. In some examples, shopper devices **131** can communicate with network computing system **101** over one or more networks. In some examples, shopper devices **131** can communicate with network computing system **101** via one or more API(s) **170**. In some instances, applications can include an aggregator application. For instance, an aggregator application can collect data indicative of a number of order requests from a number of different delivery service platforms (e.g., associated with one or more service providers **165** which are associated with one or more service provider systems **166**).

[0067] Shopper devices **131** can be associated with shoppers **135** and allow the shopper **135** to interact with the delivery service entity. For example, in response to user input by a shopper **135**, an application **132** can interact with shopper device **131** to display an application interface on a user

interface of shopper device **131**. Example user interfaces of a shopper device are further described with reference to FIG. **11A** to FIG. **16C**. Additionally, or alternatively, shopper devices **131** can include courier devices **151** and/or be associated with couriers **155**. For instance, couriers **155** can perform the item retrieval portion of a service within a merchant location.

[0068] In some examples, shopper device **131** can receive, over one or more networks, data from network computing system **101**. For example, application **132** can receive data stored in data repository **105**. In some examples, application **132** can interact with shopper device **131** to display merchant data **110** (e.g., merchant location, item locations within merchant location, etc.). In other examples, application **132** can interact with shopper device **131** to display user data (e.g., user preferences, essential items, etc.). In other examples, application **132** can interact with shopper device **131** to display shopper data **108** (e.g., historical performance data **108A** or location data **108B**).

[0069] In some implementations, application **132** running on shopper device **131** can make a call to merchant systems **146** via one or more API(s) **170** to hydrate application **132**. Hydrating application **132** can include filling one or more objects associated with the application with data. In some instances, an application can be partially hydrated to save on computing resources by only loading necessary information. Partial hydration can allow for reduction in bandwidth and computer processing unit cycles for data that is not actively being used. For instance, one or more API(s) **170** can include a claim order API. The merchant system **146** can obtain the request and determine an identifier associated with the device and/or an authenticated account associated with the shopper device **131** that is making the call. Utilizing the claim order API, shopper device **131** can claim one or more available orders as described herein. In some instances, the ability to claim certain orders can be dependent on a shopping mode associated with the shopper device **131**. For instance, a shopping mode can include a solo shopping mode or a co-shop shopping mode. When in solo shopping mode, a shopper device **131** can be prevented from joining a shopping order that is currently claimed by another shopper device. Alternatively, co-shop shopping mode can allow a shopper device **131** to join a shopping order that is currently claimed by another shopper device. In some instances, multiple shopper devices in solo shopping mode can attempt to claim a shopping order at the same time. The computing system can perform an optimization process to determine which shopper device to assign the order to. When an order is claimed or otherwise assigned, data repository **105** can be updated to reflect that the order has been assigned, and in some instances, the associated identifier that is assigned to the order (e.g., as depicted in FIG. **4**).

[0070] Application **132** can interact with shopper device **131** to display order request data **106** such as item subset data **106A**. In some instances, application **132** can interact with shopper device **131** to facilitate the recommendation or selection of distributing data objects associated with an order (e.g., splitting items) across multiple shopper devices. Distributing data objects associated with an order can be performed at designated times in an order request workflow. Additionally, or alternatively, distributing data objects associated with an order can be performed periodically throughout the fulfillment of an order request (e.g., as each shopper is making progress and moving around the merchant location to fulfill the order).

[0071] In some instances, application **132** can display a read-only interface for an unclaimed order. Responsive to obtaining user selection of “join order” or some other initiation, the application **132** can update to allow for interaction via the user interface of shopper device **131** with application **132** to view order details, mark items as shopped, or otherwise interact with the order (and thus updating the data repository **105** to update data associated with order).

[0072] In some instances, application **132** can include an authentication service. For instance, a shopper can utilize authentication service to identify themselves to the application **132** and associate themselves with shopper device **131** for a shopping session. Authentication can allow for the data repository **105** to be updated to reflect shopping metrics associated with the shopper identifier. For instance, a shopper can log-in using existing credentials. Additionally, or

alternatively, application **132** can include an interface flow for setting up an account. This can include providing a username, password, or other profile information.

[0073] Shopper device **131** can include one or more machine-learned models **130** configured to improve the data object distribution and/or item selections for the requested items. As examples, the one or more models **130** can be or can otherwise include various machine-learned models such as, for example, regression networks, generative adversarial networks, neural networks (e.g., deep neural networks), support vector machines, decision trees, ensemble models, k-nearest neighbors models, Bayesian networks, or other types of models including linear models or non-linear models. Example neural networks include feed-forward neural networks, recurrent neural networks (e.g., long short-term memory recurrent neural networks), convolutional neural networks, or other forms of neural networks. For example, the one or more models **130** can obtain order request data **106** including item subset data **106A**, shopper data **108** including historical performance data **108A** and location data **108B**, user data including user preferences, and merchant data **110**, to determine a distribution of data objects, user preference suggestion for items of a current delivery service order request, or a recommended route through a merchant location.

[0074] In some examples, one or more models **130** can include a data object distribution model trained to distribute data objects associated with various items in an order across multiple shopper devices. In some instances, one or more models **130** can be personalized to an account associated with a shopper device **131**, or a merchant. In some examples, the one or more models **130** can include an item detection model trained to detect grocery items available at a merchant location. In some examples, the one or more models **130** can include an item recommendation model trained to determine a recommended grocery item from the available grocery items at a merchant location. In some examples, the item detection and item recommendation models can be trained to utilize data from data repository **105**. For example, the historical data (e.g., previously requested grocery items) and user data (e.g., user preference data, user feedback, etc.) can be input to the one or more models **130** to improve the grocery item selections for the requested grocery items.

[0075] In some examples, shopper device **131** can transmit data to network computing system **101**. For example, application **132** can interact with the user interface of shopper device **131** to display the subset of items assigned to a respective shopper device **131**. For instance, the subset of items can include preferences associated with the items, replacement indications, location of the items within the store, count of the respective items, and a ready time associated with the items to be shopped. Additionally, application **132** can interact with the user interface of shopper device **131** to provide various interactive interface elements. The example interactive interface elements can be utilized to facilitate encouraging the splitting of orders, opting into splitting of orders, and/or providing messages associated with the splitting of orders. In some instances, the user interface of user device **121** can display the output indicative of the recommended replacement grocery item (e.g., image of the selected item including the available items) as an update to the order request that the item was selected (e.g., shopped) by the shopper **135**. In some examples, the user interface of user device **121** can display the output indicative of the recommended grocery item after the grocery items have been delivered to solicit feedback from user **125**. Examples of the one or more interactive interface elements are further described with reference to FIG. **11A** to FIG. **16D**.

[0076] In some examples, shopper device **131** can transmit data to network computing system **101**. For example, application **132** can interact with user device **121** to indicate updates associated with the order request. For example, the shopper **135** can provide updates indicating that a requested item has been completed (e.g., item was available and selected by the shopper). In some examples, the shopper **135** can provide updates indicating that a requested grocery item is unavailable (e.g., out of stock). In other examples, the shopper **135** can provide updates indicating one or more replacement suggestions. The updates associated with the order request can be transmitted over one or more networks and stored in a data repository **105** of network computing system **101**. In some examples, the updates can be used to train the models **114** of network computing system **101**.

[0077] Computing system **100** can include merchants **145** and merchant systems **146** that operate as an information inlet and/or outlet for the computing system **100** to exchange data with network computing system **101**. Merchants **145** can include any person or company involved in the trade or sale of items (e.g., grocery items). Merchants **145** can be associated with merchant locations (e.g., physical locations, grocery stores, etc.) where grocery items can be purchased. Example merchant locations include conventional supermarkets, limited assortment supermarkets, supercenters, warehouse clubs, or convenient stores. In some examples, merchants **145** can be associated with shopper devices **131**. For example, merchants **145** can offer merchant shopper services (e.g., a designated shopper at a merchant location) to select grocery items requested using the delivery service entity. In some examples, merchants **145** associated with a shopper device **131** can perform similar operations as a shopper **135** as described herein. In some instances, merchant systems **146** can interface with a number of service provider systems **166** to facilitate orders from a number of delivery service entities. In some instances, shopper devices **131** can be associated with a single delivery service (e.g., on service provider of a plurality of service provider systems **166**).

[0078] Merchant systems **146** can be associated with one or more merchants **145**. Merchant systems **146** can include a record for each merchant **145** subscribed to the delivery service entity (e.g., associated with service provider systems **166**) as well as associated merchant locations. By way of example, merchant systems **146** can aggregate inventory data for each respective merchant location to define grocery items that are available at each merchant location associated with the respective merchants **145**. In some examples, merchant systems **146** can include the location of grocery items that are available within each specific merchant location. Merchant systems **146** can be updated by merchant **145** to reflect the most up to date inventory levels at the respective merchant locations associated with the merchants **145**. In some examples, merchant systems **146** can synchronize within inventory management software, point-of-sale systems, etc. of one or more merchants **145** to maintain accurate levels of inventory at each respective merchant location.

[0079] In some examples, merchant systems **146** can transmit merchant data **110** to network computing system **101**. For example, a merchant system **146** can be updated (e.g., by an individual associated with the merchant **145**, automatically, via one or more API(s) **170**) etc.) to indicate that a particular item is no longer available at a merchant location associated with the merchant **145**. In some examples, a merchant system **146** can be updated to indicate that previously unavailable grocery items are now available at a merchant location associated with merchant **145**.

[0080] Merchant system **146** can transmit updated merchant data **110** indicating the change in inventory to network computing system **101**. In some examples, network computing system **101** can utilize the updated merchant data **110** for processing order requests from users **125** of the delivery service entity.

[0081] As described herein, network computing system **101** can include data flow to and from various devices and systems. An example dataflow diagram is described with reference to FIG. 2.

[0082] FIG. 2 depicts an example dataflow **200** diagram for dynamic data object distribution based on historical performance and/or real-time data according to example embodiments of the present disclosure. Dataflow **200** can include the shopping list being claimed by a first user at operation **205**. For instance, data indicative of user selection of a shopping list can be received via a user interface of a client device (e.g., shopper device). Responsive to the input indicative of user selection, a data object associated with the shopping list can be generated and/or updated to reflect that the shopping list has been claimed. For instance, the data object can be updated such that when an application interacts with a respective client device to display data associated with various orders stored within a data repository, the interface of the client device will include a visual indication associated with the claimed order being selected.

[0083] Rather than the order/shopping list being locked/prevented from being claimed by another shopper, the order/shopping list can be available for another shopper to claim.

[0084] At operation **210** the computing system can determine if the shopping list is eligible for

splitting. If the computing system determines that the shopping list is not available for splitting, at operation **215**, the computing system can update a graphical user interface of a second device to indicate that the shopping list is unavailable. For instance, the computing system can generate or update a data object associated with the shopping list that provides for displaying an indication that the shopping list is not available for splitting.

[0085] In some instances, the criteria for determining whether a shopping list is eligible for splitting can be determined based on a number of items, progress of the first user, types of items, or other order related data. Additionally, or alternatively, the criteria for determining whether a shopping list is eligible for splitting can be determined based on overall system activity. Overall system activity can include a number of active order requests and a number of active shopper devices. For instance, the number of active shopper devices can be determined based on utilization of system resources such as number of API calls, data usage, bandwidth usage, power usage, etc. The network traffic data being utilized by the shopper devices can be utilized to determine whether the devices are associated with active order requests. Based on the number of active order requests, and the number of active shopper devices, the system can determine whether to update a status associated with the shopping list as available or unavailable. For instance, if a number of shopper devices are active is greater than the number of active order requests, this can be a signal that could be utilized to denote the shopping list as eligible for splitting.

[0086] In some instances, the computing system can determine that the shopping list is available for splitting. Responsive to this determination, the computing system can, at operation **220**, generate or update a data object associated with the shopping list to indicate that the order is eligible to be split. For instance, the data object can include data such that an application associated with a shopper device causes a selectable user interface element depicting a message such as, “join this order” to be provided for display via a shopper device.

[0087] For instance, the second device can access a data repository of network computing system. The second device can make a call for one or more data objects associated with the shopping list. When accessed by the second computing device, the data objects can cause the GUI of the second computing device to provide the shopping list as eligible for splitting (e.g., including one or more selectable interactive user interface components associated with the shopping list) for display.

[0088] In some implementations, the second device can include a prompt for a user of the device to select a shopping mode. For instance, a shopping mode can include “solo” mode or “co-shopping” mode. A device associated with solo shopping mode can be prevented from joining an existing order. A device associated with co-shopping mode can be allowed to view and/or select an option to “join this order” and co-shop an order that is assigned to another shopper. For instance, the computing system can access a datastore including an indication of whether the order is assigned and/or information relating to an identifier that the order is assigned to. The identifier can include a device identifier, user identifier, or any other identifier.

[0089] At operation **225**, the computing system can obtain data indicative of the second user selecting the shopping list. For instance, the user can select the selectable user interface element depicting a message such as, “join this order.” Responsive to obtaining data indicative of the selection of the shopping list, the computing system can, at operation **230**, generate a first subset of items and a second subset of the items. The first subset of items and the second subset of items can be determined based on the progress of a client device associated with the first user (e.g., via a digital checklist, GPS ping), the progress of a client device associated with a courier, one or more item characteristics, and one or more historical performance metrics associated with the respective shopper.

[0090] At operation **235**, the computing system can transmit the first subset of items to the first device and the second subset of items to a second device.

[0091] At operation **240**, the computing system can dynamically update the first subset of items and the second subset of items to generate an updated first subset of items and second subset of

items. For instance, the computing system can loop back to operation **230** and re-generate the first subset of items and second subset of items. The dynamic updating of the first subset of items and second subset of items can be performed periodically while the order request associated with the shopping list is still pending. Additionally, or alternatively, the dynamic updating can be triggered by one or more progress updates. Progress updates can include physical location changes, a percentage or number of items being marked as completed, or some other progress indicator associated with the first shopper device and second shopper device.

[0092] At operation **245**, the computing system can determine completion of the first and second subset. For instance, operation **245** can include accessing a data structure (such as data structures depicted in FIG. **8**, FIG. **9**, and FIG. **10** to determine a status associated with the data object (e.g., in progress, completed, or unavailable). In some instances, the computing system can determine that each data object has either a completed or unavailable status indicator. As such, the system can determine that the order has been completed.

[0093] Upon completion of the order, the computing system can log data associated with each of the subsets and each of the shopper devices in order to update metrics associated with the shoppers, items, and merchant. For instance, the historical data associated with the shoppers (e.g., historical performance data **108A**) can be updated to include found rate, replacement rate, replacement approval, shopping speed, total orders, total items picked, fulfillment rate, average pick time, average basket size, fulfilled orders, missed orders, defected orders, or any other relevant metrics which can be utilized by the system to determine data object allocation and eligibility for split shopping lists for future order fulfillment. In some instances, relevant metrics can be broken down for different item types. For instance, a first shopper can perform better with picking items which require some subject judgment (e.g., ripeness of a fruit, cut of meat, size of produce) as such, their defect rate for that kind of item can be lower than another shopper associated with the same merchant.

[0094] FIG. **3** depicts a flowchart diagram of an example method **300** to perform dynamic data object distribution based on historical performance in accordance with some embodiments of the present disclosure. Method **300** can be performed by processing logic that can include hardware (e.g., computing devices, processing devices, circuitry, programmable logic, dedicated logic, hardware of a device, microcode, integrated circuit, etc.), software (e.g., instructions that are executable or can run on a processing device), or a combination thereof. In some implementations, method **300** can be performed by network computing system (e.g., network computing system **101**) which can be a distributed computing system (e.g., cloud-based systems). FIG. **3** depicts elements performed in a particular order for purposes of illustration and discussion. Those of ordinary skill in the art, using the disclosures provided herein, will understand that the elements of any of the methods discussed herein can be adapted, rearranged, expanded, omitted, combined, or modified in various ways without deviating from the scope of the present disclosure, and some processes can be performed in parallel. In some embodiments, one or more processes can be omitted. Thus, not all processes are required by every embodiment. Additional or alternative process flows are possible.

[0095] At operation **302**, processing logic can access data including a centralized data structure including a plurality of order requests. For instance, the centralized data structure can be one data structure of a number of hierarchical data structured stored or managed by the system. For instance, the hierarchical data structures can be organized such that updating data in one data structure can result in automatic adjustments to related data structures. For instance, a summary data structure including a number of orders and high level order details can be generated or updated based on a number of individual data structures associated with specific order requests.

[0096] At operation **304**, processing logic can compute, based on a first order request of the centralized list of order requests and merchant location data, a shopping list including: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item. For instance, the shopping list can be generated based on the shopping list

and merchant location data. The shopping list can include a number of data objects.

[0097] Each respective data object can be associated with an item of the delivery order request. The plurality of data objects for items to be retrieved for the first order can include, for example, a row in a table or some other discrete unit of a data structure with information associated with a particular item. Characteristic data for each respective item can include additional details relating to the item such as quantity, count, replacement indication which can be obtained as part of the order request. In some instances, the processing logic can access data structures associated with merchants and inventory to populate additional fields of the data object such as item location, item category, similar items, or other merchant related information associated with the respective item of the first order request.

[0098] At operation **306**, processing logic can store the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices. For instance, a number of other additional shopping lists can be computed and stored. The shopping lists can be accessible by the respective shopper computing devices (e.g., via the applications on the respective devices) can communicate with a network system to access the number of shopping lists. For instance, the shopping lists can include data that when executed by the application and the shopper device, causes the number of shopping lists to be provided for display via the user interface of the shopper device.

[0099] In some implementations, the shopping lists in the shopping list data store can include shopping lists associated with merchant shoppers and courier shoppers. In some instances, a courier shopper can be associated with traveling to a merchant location, retrieving items associated with the order, and delivering the items to a drop-off location. The present disclosure can provide for determining that a courier's estimated time of arrival is later than initially determined (e.g., due to traffic, etc.). Based on the delayed estimated time of arrival, processing logic can highlight the courier shopping list for claiming by a second user. For instance, processing logic can move the courier shopping list to the top of the list, sending a real-time notification to shopper devices indicative of an option to claim the order to co-shop. If the list is selected for co-shopping, processing logic can generate the sublists of items. In some instances, the sublist of items for each shopper can include items that are non-perishable to the merchant shopper whereas items which require refrigeration or special storage can be reserved for or otherwise assigned to the courier shopper's sublist. As such, the determination to distribute the data objects associated with the items of the order can be made based, at least in part, on the courier's estimated time of arrival at the merchant location.

[0100] In some implementations, sublists can be generated based on multiple orders. For instance, a first shopper can be assigned refrigeration items for two or more orders and a second shopper can be assigned non-perishable items for two or more orders. Additionally, or alternatively, a first portion of two orders can be assigned to a single first shopper while a second portion of the two orders can be distributed among different shoppers. As such, the system can determine multiple allocation of data objects associated with items across shopper devices to provide for better utilization of system resources and completion of the order request.

[0101] At operation **308**, processing logic can access data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices. In some instances, based on obtaining a request for the computed shopping list and the plurality of other additional shopping lists, processing logic can transmit data including instructions, that, when executed by a shopper computing device, cause presentation of the shopping list and the plurality of other additional shopping lists via an interactive user interface the shopper computing device. For instance, the first shopping list can be provided for display via a user interface of the shopper device. The user interface can include a selectable user interface element such as a button that can be "clicked" by a user to select or otherwise indicate that the user will proceed to fulfill the shopping portion of the order. The selection by a user can be any form of input such as touch,

voice, etc. that is obtained by a sensor of the shopper device.

[0102] At operation **310**, processing logic can automatically update, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data. The order status includes, for example: unclaimed, claimed and not begun, in progress, nearly done, or completed. For instance, an unclaimed order status can be indicative of an order which has not been claimed or otherwise selected by a shopper to perform. A claimed and not begun order status can be associated with an order that has been selected by a shopper device, but the system has since not received any updates regarding shopping progress or completion of items of the shopping list. In progress can include a claimed order where at least one item has been shopped or completed. Nearly done can include when a majority of a number of items have been shopped (e.g., 75% or greater completion, 4 or less items to go, or some other predetermined threshold). Completed can be associated with a shopping list where every item has a completed indicator or an unavailable indicator.

[0103] At operation **312**, processing logic can access data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices. In some instances, based on obtaining a request for the computed shopping list and the plurality of other additional shopping lists, processing logic can transmit data including instructions, that, when executed by a shopper computing device, cause presentation of the shopping list and the plurality of other additional shopping lists via an interactive user interface the shopper computing device. For instance, the first shopping list can be provided for display via a user interface of the shopper device. The user interface can include a selectable user interface element such as a button that can be “clicked” by a user to select or otherwise indicate that the user will proceed to fulfill the shopping portion of the order. The selection by a user can be any form of input such as touch, voice, etc. that is obtained by a sensor of the shopper device.

[0104] At operation **314**, processing logic can, based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, compute a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective item of the plurality of items.

[0105] Features associated with the first computing device can include a shopper profile associated with the device, location data associated with the device, historical shop data associated with the device or a shopper profile. Features associated with the second computing device can include a shopper profile associated with the device, location data associated with the device, historical shop data associated with the device or a shopper profile. By way of example, the first computing device and second computing device can be associated with two different shoppers. Each shopper can associate the device with themselves using a means of authentication. This can include, for example, signing into an account of the respective shopper.

[0106] The first computing device (e.g., first shopper) can have a historical shopping history of a much larger number of orders fulfilled than the second computing device (e.g., second shopper). As such, the processing logic can determine that items with characteristic data associated with being more complex or requiring more discretion (e.g., produce, meat) can be distributed to the first subset of items such that the first shopper associated with the first computing device will be responsible for shopping for that item.

[0107] As an additional, or alternative example, the first computing device can have a higher replacement approval rating than the second computing device. As such, the first computing device can be associated with a subset of items that includes items marked with “best replacement item” or “provide recommended alternative”.

[0108] Characteristic data of each respective item of the plurality of items can include a replacement indication, a category, or item type. A replacement indication can include an indication

of the proper means of adjusting the order if an item is out of stock or otherwise unavailable.

[0109] In some instances, computing first subset of items and the second subset of items is performed responsive to accessing data indicative of the first computing device indicating a need for assistance. In some instances, computing the first subset of items and the second subset of items is performed responsive to determining that a courier associated with picking up the first shopping list will arrive before the first computing device completes the shopping list.

[0110] The features associated with the first computing device and the features associated with the second computing device can include the historical performance of the operator (e.g., shopper, courier) associated with the respective device or experience level of the operator associated with the respective device. The historical performance of the operator can include an aggregation of metrics associated with past order fulfillment instance. The metrics can include at least one of: (i) an order replacement satisfaction rate, (ii) a shop time, or (ii) a wait time for a courier picking up the order. The experience level of the operator can be determined based on at least one of: (i) a number of previously completed orders or (ii) characteristics of previously completed orders.

[0111] The characteristic data of each respective item of the plurality of items can include at least one of: (i) an item type, (ii) an item location, or (iii) an item category. The item type can include at least one of: (i) frozen, (ii) perishable, (iii) non-perishable, (iv) non-edible, (v) refrigerated, or (vi) shelf stable. The item category can include at least one of: (i) an indication of produce, (ii) canned goods, (iii) outside aisle, (iv) pharmacy, (v) bakery, (vi) snacks, (vii) beverages, or (viii) frozen goods.

[0112] Computing a first subset of items for the first computing device and the second subset of items for the second computing device can include determining a percent completion of the first shopping list. Based on the percent completion of the first shopping list exceeding a predefined range, updating the order status data to indicate that the order cannot be selected by a second computing device. Additionally, or alternatively, based on the percent completion of the first shopping list being below a predefined range, the order status data can be updated to indicate that the order can be selected by a second computing device.

[0113] At operation **316**, processing logic can transmit data including instructions, that, when executed by the first computing device, cause the interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.

[0114] In some instances, processing logic can transmit data including instructions, that, when executed by the second computing device, cause the interactive user interface of the second computing device to provide the second subset of items for display via the interactive user interface of the second computing device. Processing logic can compute a first progress metric for the first computing device and a second progress metric for the second computing device. The first progress metric can be indicative of an amount of completion of the first subset of the first shopping list. The second progress metric can be indicative of an amount of completion of the second subset of the first shopping list. Based on the first progress metric and the second progress metric, the processing logic can periodically transmit instructions, that when executed, cause at least one of: (i) the interactive user interface of the first computing device or (ii) the interactive user interface of the second computing device to be updated.

[0115] For instance, processing logic can access current location data indicative of a real-time location of the first computing device and a real-time location of the second computing device within the merchant location. Based on (i) the current location data, (ii) the first progress metric, and (iii) the second progress metric, the processing logic can dynamically adjust a distribution of items between the first subset of items and the second subset of items. Based on dynamically adjusting the distribution of items, the processing logic can automatically transmit instructions which cause the interactive user interface associated with the first computing device to provide, for display, an updated first subset of items and the interactive user interface associated with the

second computing system to provide for display an updated second subset of items.

[0116] As described herein, dynamically adjusting the distribution of items between the first subset of items and the second subset of items can include removing one or more items from the first subset of items and adding the one or more removed items to the second subset of items.

[0117] As described herein, the processing logic can determine a replacement item is needed for a first item of the first subset of items. Based on a location of a recommended replacement item and the current location data, the processing logic can update the second subset of items to include the replacement item. The processing logic can transmit data including instructions that, when executed by the second computing device, cause the interactive user interface of the second computing device to provide the updated second subset of items for display via the interactive user interface of the second computing device. For instance, the location of the recommended replacement item and the real-time location of the second computing device can be within a predefined threshold.

[0118] The data flow described in FIG. 2 and method described in FIG. 3 can generate, access, and update various data structures. Examples of a data structures that can be stored in or associated with data repository **105** and with data flow **200** and method **300** are described with reference to FIG. 4 to FIG. 10.

[0119] FIG. 4 depicts an example data structure **400** of a memory according to example embodiments of the present disclosure. Example data can include Merchant A orders **405**. For instance, each respective merchant (e.g., associated with merchant systems **146**), can have associated data objects for the respective orders. The data objects can include an order identifier **410**, a number of items **415**, a number of units **420**, order assignment **425**, and ID(s) assigned **430**. The order identifier **410** can include a name, numerical identifier, or any other unique identifier to distinguish the respective data objects from one another in the data structure **400**. The number of items **415** can be indicative of the number of distinct items associated with the data object (e.g., total number of SKUs, etc.). The number of units **420** can include the total number of items including a count for any duplicates associated with a particular item type. Order assigned **425** can include an indication of whether the order has been assigned to an identifier (e.g., device identifier, shopper identifier). For instance, a true indication can be indicative of the order being assigned and a false indication can be indicative of the order not yet being assigned. ID(s) assigned **430** can include an indication of which identifier (e.g., device identifier, shopper identifier) has been assigned to the order. In some instances, this can include a single identifier, in some instances this can include multiple identifiers. In some instances, this can include a false designation if the order has not been assigned an identifier. Data structure **400** can include additional information associated with the respective data objects which can be used by the computing system (e.g., network computing system **101**) to dynamically adjust distribution of payload relating to the data objects.

[0120] FIG. 5 depicts an example data structure **500** of a memory according to example embodiments of the present disclosure. Example data can include data associated with a first data object from FIG. 4. For instance, data object associated with order “name A” can be associated with an additional data structure **500** which can include additional details associated with the Name A order **505**. For instance, the data structure **500** associated with Name A order **505** can include a number of items **510**, a number of units **515** of each respective item, the aisle **520** (e.g., location) of each respective item, a category **525** of each respective item, and a replacement indication **530** for each respective item.

[0121] As such, for each item, a data object (e.g., group of cells, concatenated string of identifiers) can be generated and stored in memory. The items **510** can include a plain language identification of an item including a brand name or description. The number of units **515** can indicate a number of units to be added. For instance, items can include brand A apple, oat milk, chocolate bar, brand B yogurt, turkey, provolone, chocolate ice cream, sprinkles, whipped cream, frozen pizza, cold brew

concentrate, and bananas. The number of units of each item can be included in the data object. For instance, two brand A apples, two brand B yogurts, three bananas, and one of each remaining item. [0122] Aisle **520** can include an aisle or other store identifier associated with an item location. The aisles for one merchant location can be distinct from other merchant locations. As such, items and associated aisles, categories, etc. can be tracked in real-time and utilized to populate or otherwise generate the various data objects of data structure **500**. For instance, data structure **500** can be generated by making calls (e.g., via an API) to an existing inventory or point of sale system to access and display or up-to-date information. In some instances, generation of the data structure **500** can be automatically performed by the computing system responsive to obtaining a respective order.

[0123] The category **525** can be a type or other designation which can be associated with the various items. For instance, the categories can include things such as produce, beverages, refrigerated items, deli, frozen items, baking, alcohol, bakery, cooking, household supplies, office supplies, candy, or any other designation.

[0124] Replacement indication **530** can be associated with acceptable replacement associated with each item. In some instances, the replacement indication **530** can be automatically generated. For instance, absent user input to the contrary, replacement can be set based on data associated with a user profile associated with the order (e.g., user profile associated with Name A **505**). If a user profile has historical data indicative of accepting brand B apples as a replacement to brand A apples, then the computing system can automatically indicate that the replacement indication **530** for the brand A apples is brand B apples. Alternatively historical data can be indicative of rejection of all or most replacement recommendations. As such, an item can be automatically flagged to not replace.

[0125] Additionally, or alternatively, user input can be obtained as part of an order request (e.g., received from a user device **121**) which can explicitly indicate a replacement indication **530**. In some instances, a replacement indication **530** can include “none,” “best alternative,” “provide recommended replacement,” one or more specific alternative items, or some other indication. “None” can be associated with providing for no replacement if an item is unavailable. “Best alternative” can allow for a shopper's discretion or use of a replacement recommendation engine for determining a recommended replacement item. “Provide recommended replacement” can allow for shopper's discretion or user of a replacement recommendation engine, however it can require a message to be sent and acknowledged by a user (e.g., via user device **121**) to accept the replacement suggestion. One or more specific alternatives can be one or more preselected or pre-approved replacement items, brands, etc. which can automatically replace the initial item with additional explicit approval.

[0126] The features associated with the respective data objects are provided for exemplary purposes only and are not meant to be limiting. Additional, or alternative features and associated data can be included or associated with respective data objects and utilized by the computing systems (e.g., network computing system **101**) to provide for dynamic order splitting according to example embodiments of the present disclosure.

[0127] As described herein, the computing system (e.g., network computing system **101**) can dynamically generate and update data structures to facilitate the dynamic adjustment of payload associated with data objects representing orders such that the orders can be fulfilled by users associated with computing devices in a distributed computing system.

[0128] For instance, the computing system can generate a first subset **605** of items and a second subset **635** of items. The distribution of items can be determined based on data indicative of the characteristics of the items and/or data indicative of the characteristics of the available shoppers. For instance, FIG. 6 depicts generating a first subset **605** and a second subset **635** based on the aisle and category of the respective item. For instance, the first subset **605** can include items **610**. The items **610** can be associated with a number of units **615** and aisles **620** which can include aisle 3,

aisle 5, and aisle 6. The items **610** can be associated with category **625** of refrigerated items, banking, and candy. As can be seen, the replacement indication **630** can be any type of replacement option.

[0129] Second subset **635** of items can include items **640**. Items **640** can be associated with a number of units **645** and aisles **650**. The aisles can include aisle 8, aisle 9, deli, and produce. The items **640** can be associated with category **655** of frozen, deli, and/or produce. As depicts in FIG. 6, the replacement indication **660** can be any type of replacement option.

[0130] Additionally, or alternatively, the items can be determined, at least based in part on replacement indication **730**. For instance, FIG. 7 depicts an example data structure of a memory according to example embodiments of the present disclosure. Example data can include a first subset **705** and a second subset **735**. The first subset **705** can include items **710**. The items **710** can include, for example, sprinkles, chocolate ice cream, oat milk, whipped cream, cold brew concentrate, and yogurt brand B. Each of the items can be associated with a number of units **715** and an aisle **720**. For instance, sprinkles can be associated with aisle 5 and a category **725** of baking. Chocolate ice cream can be associated with aisle 9 and category **725** of frozen. Oat milk, whipped cream, cold brew concentrate, and yogurt brand B can be associated with aisle 3 and a category **725** of refrigerated. Replacement indication **730** for the several of the items can include best alternative, provide recommended replacement, and a specific item (e.g., yogurt brand C).

[0131] Second subset **735** of items can be associated with items **740**. Items **740** can include, for instance, turkey, provolone, apple brand A, chocolate bar, frozen pizza, and bananas. Each of the items can be associated with a number of units **745** and an aisle **750**. Turkey and provolone can be associated with aisle **750** of deli and category **755** of deli. Additionally, in this example, turkey, provolone, and Apple Brand A can be associated with replacement indication of “none” such that the shopper assigned to second subset **735** of items will not need to determine or otherwise locate a replacement item if the items are unavailable. Items **740** chocolate bar and frozen pizza can be associated with “provide recommended replacement” replacement indication. The item **740** banana can include replacement indication of “best alternative”.

[0132] Based, at least in part, on the distribution of replacement indication **760**, the shoppers for the respective subsets can be selected. For instance, data associated with a found rate or replacement satisfaction or replacement rate for a shopper can be accessed. In some instances, the system can continually generate and update data structures including shopper historical data. For instance, shopper historical data can include shopping rate (e.g., number of items shopped per hour), found rate (percent of items which are located), replacement rate (percent of not-found items for which a replacement if found), and/or replacement satisfaction rate (data obtained from users regarding the substitute items). The system can continually update the information. In some instances, found rate or other metrics can be determined and/or updated after each order performed by a shopper. For instance, the system can log data associated with each order that is fulfilled. In some instances, the metrics can be divided based on aisle, category, replacement indication, or some other feature. Thus, the system can utilize the metrics of various shoppers and item features to individually adjust the allocation of data objects associated with each item to provide for the best utilization of system resources.

[0133] Existing methods would adjust or allocate data objects associated with items based solely on category or location within a merchant location. The present application provides for improvements by utilizing newly available data which is stored and updated by the system to allow for personalization and improved allocation of resources based on features of the items as well as features associated with the individual shoppers.

[0134] The features associated with the data objects as well as features associated with shoppers can be utilized during the initial distribution of items between the first subset and second subset (or additional subsets) as well as being used for dynamically updating the lists based on real-time data.

[0135] For instance, FIG. 8, FIG. 9, and FIG. 10 depict example subsets of items. For instance,

FIG. **8** depicts a first subset **805** and a second subset **810**. In the example, the items of first subset **805** can be associated with data indicative of the item being shipped. For instance, this can be depicted as a green check **815A-F**. Second subset **810** can include a number of items and associated status data. For instance, the status data can include a green check **815A** indicated that an item has been shipped, an in progress indication such as indicator **820B**, **820D**, **820E**, and/or **820F**, and a not found indicator **820D**.

[0136] Periodically, the system can determine an order progress status for the respective subsets of items. Based on the order progress status as well as real-time data associated with the shoppers, the system can determine that an item should be removed from a subset and that the data object should be added to a different subset.

[0137] For instance, FIG. **9** depicts an example reallocation of an item to a first subset **905** from a second subset **910**. For instance, based on the order progress of the first subset **905** including all items being shipped, and second subset **910** including several in progress items, the system can determine that one or more data objects associated with items should be removed **915** from the second subset and added **920** to the first subset.

[0138] The system can continue to periodically monitor the order progress status for both of the subsets until the order is completed. For instance, FIG. **10** depicts an example first subset **1005** and second subset **1010** with each item marked with a shipped or unavailable/unfulfilled indication. In some instances, second subset **1010** can include an indication **1015** that an item has been removed. In some instances, first subset **1005** can include a completed indicator **1020** for the item associated with the data object that was representative of the item. The indicator icons used in FIG. **8** to FIG. **10** are meant for illustrative purposes only and can be represented as any form of storable data. In some instances, the stored data can include instructions that when executed cause an interactive user interface of a client device to update and provide the items and/or indicators for display via the interactive user interface.

[0139] FIG. **11** depicts example order interfaces for various order statuses according to example embodiments of the present disclosure. Example order interfaces can include claimed order interfaces **1105**, **1120**, and **1130** and unclaimed order interfaces **1140**, **1155**, and **1170**.

[0140] The systems and methods provided herein include example user interface elements which can be used to communicate data indicative of order status. For instance, as depicted in FIG. **11**, there can be unclaimed orders associated with interface element **1105**, interface element **1120**, or interface element **1130**. Unclaimed order interface element **1105** can include a selectable component **1115**. The selectable component **1115** can be selected via the interactive user interface to select the new and not accepted order. The interface element **1105** can include a number of items/item count **1110A**.

[0141] Interface element **1120** can be associated with an order that has not been claimed but has an assigned courier. For instance, the courier can have an estimated time until arrival element **1125**. The interface element **1120** can include a number of items/item count **1110B**.

[0142] Interface element **1130** can be associated with an accepted order with no one actively shopping the order. For instance, interface element **1130** can include a finish in element **1135** which indicates an amount of time before the order must be completed. Interface element **1130** can include a number of items/item count **1110C**.

[0143] Additionally, or alternatively, there can be claimed orders associated with interface element **1140**, interface element **1155**, or interface element **1170**.

[0144] For instance, interface element **1140** can be associated with a claimed order where **8** out of **14** items have been shipped. Interface element **1140** can be associated with a finish in element **1150** which indicates an amount of time before the order must be completed. Interface element **1140** can include an indication of number of items left **1145**.

[0145] Interface element **1155** can be associated with an order that is nearly completed. For instance, the interface element **1155** can include an indication of number of items left **1160**.

Interface element **1155** can include a finish in element **1165** which indicates an amount of time before the order must be completed. For instance, interface element **1155** can be associated with an order where 11 items have been shopped and four items remain.

[0146] Interface element **1170** can be associated with an order that has had all items shopped. Interface element **1170** can include an indication of an estimated time until arrival element **1175** associated with an expected time for a courier to arrive. Interface element **1170** can include a number of items/item count **1110D**.

[0147] Interface elements depicted in FIG. **11** can be integrated into various interactive graphical user interfaces, such as those depicted in FIG. **12A** to FIG. **15D**.

[0148] FIG. **12A** to FIG. **12C** depict example interactive graphical user interfaces (GUIs) for a second computing device according to example embodiments of the present disclosure. FIG. **12A** depicts an example GUI **1200A** which includes a graphical depiction of a shopping list alongside an interactive interface element **1205** associated with initiating the process of determining the order is a split order and generating the subset of data objects associated with items to be distributed across the client devices. Interactive interface element **1215** can include an item left element **1210** which can provide an indication of a number of items left to be shopped. Selectable interface element **1215** can include a selectable interface element **1215**. For instance, the selectable interface element **1215** can be configured such that when the computing system obtains data indicative of the selection of selectable interface element **1215**, causes example GUI **1200A** to update to example GUI **1200B**.

[0149] Example GUI **1200B** can include interface element **1220** which can provide an additional visual indication and message associated with the split order. Interface element **1220** can include a selectable interface element **1225**, which can be configured such that when the computing system obtains data indicative of a selection of selectable interface element **1225**, causes example GUI **1200B** to update to example GUI **1200C**.

[0150] Example GUI **1200C** can include interface element **1230**. Interface element **1230** can include an indication that the order is now split and that items have been broken into subsets and distributed across the client devices associated with the respective shoppers or shopper profiles.

[0151] FIG. **13A** to FIG. **13C** depict example interactive GUIs for a first computing device according to example embodiments of the present disclosure. Example GUIs can include example GUI **1300A**. Example GUI **1300A** can include an initial shopping interface including a shopping list **1305** for an order which has been claimed and begun to shop. Responsive to the selection of an interface element on a second, separate client device, for a second user to join the shopping list **1305**. Responsive to the second client device indicating joining of the shopping list, example GUI **1300A** can update to example GUI **1300B**.

[0152] As depicted in FIG. **13B**, GUI **1300B** can include a shopping list **1310** and a message element **1315** which can include a message relating to splitting the order. For instance, message element **1315** can include language such as, “your colleague joined this order with you. Learn more.” A portion of message element **1315** can be selected, and responsive to the selection, example GUI **1300B** can update to example GUI **1300C**.

[0153] As depicted in FIG. **13C**, example GUI **1300C** can include a message element **1320** which can include a message providing additional context or details relating to a colleague joining the order as well as instructions regarding the system automatically determining the subsets of items and distributing the payload associated with the respective data objects. In some instances, message element **1320** can additionally, or alternatively, include a selectable user interface element which can be selected to return to the main user interface (e.g., as depicted in FIG. **13A**).

[0154] FIG. **14A** to FIG. **14B** depicts example interactive GUIs of a first device for interacting with an unclaimed order according to example embodiments of the present disclosure. For instance, FIG. **14A** depicts example GUI **1400A**. Example GUI **1400A** can include a shopping list **1405** and an interactive interface element **1410**. Interactive input element **1400** can include an indication

about the order status (e.g., noting that the order is not claimed and that “no one is shopping the order.” Interactive interface element **1410** can include selectable interface element **1415**. Upon selection of interactive interface element **1415**, example GUI **1400A** can be updated to example GUI **1400B**. Example GUI **1400B** can include message indication element **1420** stating that “shopping has started.” Example GUI **1400B** can include selectable user interface element **1425** for “cannot find order” and/or selectable user interface element **1430** for “found item.”

[0155] FIG. **15A** to FIG. **15B** depict example interactive GUIs of a second device for interacting with a claimed order according to example embodiments of the present disclosure. For instance, FIG. **15A** depicts example GUI **1500A**. Example GUI **1500A** can include shopping list **1505**, individual items **1510**, interactive input element **1515**, and selectable interface element **1520**. For instance, shopping list **1505** can include a plurality of individual items **1510** with associated descriptions, quantities, or instructions for locating. Interactive input element **1515** can include an indication about the order status. For instance, the order status can note that the order is claimed and that “Your colleague is shopping this order” and indication of the number of items left. Interactive input element **1515** can include selectable interface element **1520**. Upon selection of selectable interface element **1520**, example GUI **1500A** can update to example GUI **1500B**. Example GUI **1500B** can include an interactive user interface element **1525** which provides a message that selection of the join this order button will result in the remaining items of the shopping list being automatically allocated into subsets made up of data objects which will be distributed across the devices.

[0156] FIG. **16A** includes an updated example GUI **1600A** which includes a first subset **1605** of items for the shopper associated with the first user device to fulfill. FIG. **16B** depicts an updated example GUI **1600B** which includes a second subset **1610** of items for the shopper associated with the second user device to fulfill. As discussed herein, the initial split can be performed responsive to a second user selecting an already claimed shopping list. Additionally, or alternatively, the system can encourage selection of the shopping list by a second shopper. This can include providing messages to a second device to suggest that the second shopper claim the order/shopping list (e.g., a portion thereof).

[0157] In some instances, the system can continually monitor the progress of the respective shoppers (e.g., via the continually updated data structures) to determine that items should be removed or added to respective subsets associated with shoppers. The system can automatically adjust and provide updated GUIs including notifications highlighting the items which have been removed or added (E.g., as depicted in FIG. **8** to FIG. **10**).

[0158] FIG. **17** depicts an example merchant location **1700** including a number of shopper client devices **1701A-E**. For instance, the various client device locations. In some instances, a shopper to be paired as a second shopper can be based at least in part on the remaining items, the remaining item's locations within the store, and the shopper device location. For instance, if shopper device **1701A** is shopping a first order which has several not-yet-shopped deli or produce items, the shopper associated with shopper device **1701B** can be provided a real-time message (e.g., push notification) with an offer to join or otherwise split the order with the shopper associated with shopper device **1701A**.

[0159] In some instances, the computing system can select a shopper device of a number of shopper devices to provide a real-time message (e.g., push notification). For instance, the computing system can determine a plurality of shopper devices are active. In some instances, shopper devices can be associated with a logged-in or otherwise associated with a shopper profile. Shopper profile can include performance metric data. For instance, shopper profile performance metric data can include a shopper rating, shopper performance on categories of items (e.g., produce selection, replacement selection), or other shopper metrics. In some instances, computing system can determine near real-time location of the shopper device. The computing system can access shopper profile data or current location (e.g., near real-time location) data associated with the

shopper device. In some examples, the shopper profile data and/or current location data can be utilized to select the shopper device for receipt of the real-time message. Additionally, or alternatively, the shopper profile data or current location data can be utilized to determine how to allocate items and the associated data objects across the distributed computing system.

[0160] For instance, the number of shoppers and active shopper devices can include five shopper devices. A first shopper device can be associated with a user with a high satisfaction rating for produce. A second shopper device can be associated with an average satisfaction rate for produce. As such, an example implementation can include transmitting an offer for splitting an item including produce with the first shopper advise. Additionally, or alternatively, an example implementation can include generating the subset of items for the first shopper to include data objects representative of produce items such that the first shopper with a higher produce item rating can fulfill that portion of the distributed data objects representative of items of the order.

[0161] Additionally, or alternatively, as described herein, shopper A can indicate that a replacement item is needed. The replacement item can be located near shopper device **1701E**. As such, the system can transmit a real-time message (e.g., push notification) to shopper device **1701E** indicating an offer to join or otherwise split the order with the shopper associated with shopper device **1701A**.

[0162] FIG. **18** depicts a block diagram of an example computing system **1800** for implementing systems and methods according to example embodiments of the present disclosure. The computing system **1800** includes a computing system **1801** (e.g., a shopper device **131** corresponding to a shopper **135**), a server computing system **1811** (e.g., a network computing system **101**, cloud computing platform), and a training computing system **1819** communicatively coupled over one or more networks **1828**.

[0163] The computing system **1801** can include one or more computing devices **1802** or circuitry. For instance, the computing system **1801** can include a control circuit **1803** and a non-transitory computer-readable medium **1804**, also referred to herein as memory. In an embodiment, the control circuit **1803** can include one or more processors (e.g., microprocessors), one or more processing cores, a programmable logic circuit (PLC) or a programmable logic/gate array (PLA/PGA), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), or any other control circuit. In an embodiment, the control circuit **1803** can be programmed by one or more computer-readable or computer-executable instructions stored on the non-transitory computer-readable medium **1804**.

[0164] In an embodiment, the non-transitory computer-readable medium **1804** can be a memory device, also referred to as a data storage device, which can include an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination thereof. The non-transitory computer-readable medium **1804** can form, e.g., a hard disk drive (HDD), a solid state drive (SSD) or solid state integrated memory, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), a static random access memory (SRAM), dynamic random access memory (DRAM), a portable compact disc read-only memory (CD-ROM), a digital versatile disk (DVD), and/or a memory stick.

[0165] The non-transitory computer-readable medium **1804** can store information that can be accessed by the control circuit **1803**. For instance, the non-transitory computer-readable medium **1804** (e.g., memory devices) can store data **1805** that can be obtained, received, accessed, written, manipulated, created, and/or stored. The data **1805** can include, for instance, any of the data or information described herein. In some implementations, the computing system **1801** can obtain data from one or more memories that are remote from the computing system **1801**.

[0166] The non-transitory computer-readable medium **1804** can also store computer-readable instructions **1806** that can be executed by the control circuit **1803**. The instructions **1806** can be software written in any suitable programming language or can be implemented in hardware.

[0167] The instructions **1806** can be executed in logically and/or virtually separate threads on the control circuit **1803**. For example, the non-transitory computer-readable medium **1804** can store instructions **1806** that when executed by the control circuit **1803** cause the control circuit **1803** to perform any of the operations, methods and/or processes described herein. In some cases, the non-transitory computer-readable medium **1804** can store computer-executable instructions or computer-readable instructions, such as instructions to perform at least a portion of the method of FIG. 3.

[0168] In an embodiment, the computing system **1801** can store or include one or more machine-learned models **1807**. For example, the machine-learned models **1807** can be or can otherwise include various machine-learned models. In an embodiment, the machine-learned models **1807** can include neural networks (e.g., deep neural networks) or other types of machine-learned models, including non-linear models and/or linear models. Neural networks can include feed-forward neural networks, recurrent neural networks (e.g., long short-term memory recurrent neural networks), convolutional neural networks or other forms of neural networks. Some example machine-learned models can leverage an attention mechanism such as self-attention. For example, some example machine-learned models can include multi-headed self-attention models (e.g., transformer models).

[0169] In an embodiment, the one or more machine-learned models **1807** can be received from the server computing system **1811** over networks **1828**, stored in the computing system **1801** (e.g., non-transitory computer-readable medium **1804**), and then used or otherwise implemented by the control circuit **1803**. In an embodiment, the computing system **1801** can implement multiple parallel instances of a single model.

[0170] Additionally, or alternatively, one or more machine-learned models **1807** can be included in or otherwise stored and implemented by the server computing system **1811** that communicates with the computing system **1801** according to a client-server relationship. For example, the machine-learned models **1807** can be implemented by the server computing system **1811** as a portion of a web service. Thus, one or more models **1807** can be stored and implemented at the computing system **1801** and/or one or more models **1807** can be stored and implemented at the server computing system **1811**.

[0171] The computing system **1801** can include one or more communication interfaces **1808**. The communication interfaces **1808** can be used to communicate with one or more other systems. The communication interfaces **1808** can include any circuits, components, software, etc. for communicating via one or more networks (e.g., networks **1828**). In some implementations, the communication interfaces **1808** can include for example, one or more of a communications controller, receiver, transceiver, transmitter, port, conductors, software and/or hardware for communicating data/information.

[0172] The computing system **1801** can also include one or more user input components **1809** that receives user input. For example, the user input component **1809** can be a touch-sensitive component (e.g., a touch-sensitive user interface of a client device) that is sensitive to the touch of a user input object (e.g., a finger or a stylus). The touch-sensitive component can serve to implement a virtual keyboard. Other example user input components include a microphone, a traditional keyboard, cursor-device, joystick, or other devices by which a user can provide user input.

[0173] The computing system **1801** can include one or more output components **1810**. The output components **1810** can include hardware and/or software for audibly or visually producing content. For instance, the output components **1810** can include one or more speakers, earpieces, headsets, handsets, etc. The output components **1810** can include a display device, which can include hardware for displaying a user interface and/or messages for a user. By way of example, the output component **1810** can include a display screen, CRT, LCD, plasma screen, touch screen, TV, projector, tablet, and/or other suitable display components.

[0174] The server computing system **1811** can include one or more computing devices **1812**. In an

embodiment, the server computing system **1811** can include or is otherwise implemented by one or more server computing devices. In instances in which the server computing system **1811** includes plural server computing devices, such server computing devices can operate according to sequential computing architectures, parallel computing architectures, or some combination thereof. [0175] The server computing system **1811** can include a control circuit **1813** and a non-transitory computer-readable medium **1814**, also referred to herein as memory **1814**. In an embodiment, the control circuit **1813** can include one or more processors (e.g., microprocessors), one or more processing cores, a programmable logic circuit (PLC) or a programmable logic/gate array (PLA/PGA), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), or any other control circuit. In an embodiment, the control circuit **1813** can be programmed by one or more computer-readable or computer-executable instructions stored on the non-transitory computer-readable medium **1814**.

[0176] In an embodiment, the non-transitory computer-readable medium **1814** can be a memory device, also referred to as a data storage device, which can include an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination thereof. The non-transitory computer-readable medium can form, e.g., a hard disk drive (HDD), a solid state drive (SSD) or solid state integrated memory, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), a static random access memory (SRAM), dynamic random access memory (DRAM), a portable compact disc read-only memory (CD-ROM), a digital versatile disk (DVD), and/or a memory stick.

[0177] The non-transitory computer-readable medium **1814** can store information that can be accessed by the control circuit **1813**. For instance, the non-transitory computer-readable medium **1814** (e.g., memory devices) can store data **1815** that can be obtained, received, accessed, written, manipulated, created, and/or stored. The data **1815** can include, for instance, any of the data or information described herein. In some implementations, the server computing system **1811** can obtain data from one or more memories that are remote from the server computing system **1811**.

[0178] The non-transitory computer-readable medium **1814** can also store computer-readable instructions **1816** that can be executed by the control circuit **1813**. The instructions **1816** can be software written in any suitable programming language or can be implemented in hardware. The instructions can include computer-readable instructions, computer-executable instructions, etc.

[0179] The instructions **1816** can be executed in logically and/or virtually separate threads on the control circuit **1813**. For example, the non-transitory computer-readable medium **1814** can store instructions **1816** that when executed by the control circuit **1813** cause the control circuit **1813** to perform any of the operations, methods and/or processes described herein. In some cases, the non-transitory computer-readable medium **1814** can store computer-executable instructions or computer-readable instructions, such as instructions to perform at least a portion of the methods of FIG. 9.

[0180] The server computing system **1811** can store or otherwise include one or more machine-learned models **1817**. The machine-learned models **1817** can include or be the same as the models **1807** stored in computing system **1801**. In an embodiment, the machine-learned models **1817** can include an unsupervised learning model. In an embodiment, the machine-learned models **1817** can include neural networks (e.g., deep neural networks) or other types of machine-learned models, including non-linear models and/or linear models. Neural networks can include feed-forward neural networks, recurrent neural networks (e.g., long short-term memory recurrent neural networks), convolutional neural networks or other forms of neural networks. Some example machine-learned models can leverage an attention mechanism such as self-attention. For example, some example machine-learned models can include multi-headed self-attention models (e.g., transformer models).

[0181] The machine-learned models described in this specification can have various types of input data and/or combinations thereof, representing data available to sensors and/or other systems

onboard a vehicle. Input data can include, for example, latent encoding data (e.g., a latent space representation of an input, etc.), statistical data (e.g., data computed and/or calculated from some other data source), sensor data (e.g., raw and/or processed data captured by a sensor of the vehicle), or other types of data.

[0182] The server computing system **1811** can include one or more communication interfaces **1818**. The communication interfaces **1818** can be used to communicate with one or more other systems. The communication interfaces **1818** can include any circuits, components, software, etc. for communicating via one or more networks (e.g., networks **1828**). In some implementations, the communication interfaces **1818** can include for example, one or more of a communications controller, receiver, transceiver, transmitter, port, conductors, software and/or hardware for communicating data/information.

[0183] The computing system **1801** and/or the server computing system **1811** can train the models **1807** and **1817** via interaction with the training computing system **1819** that is communicatively coupled over the networks **1828**. The training computing system **1819** can be separate from the server computing system **1811** or can be a portion of the server computing system **1811**.

[0184] The training computing system **1819** can include one or more computing devices **1820**. In an embodiment, the training computing system **1819** can include or is otherwise implemented by one or more server computing devices. In instances in which the training computing system **1819** includes plural server computing devices, such server computing devices can operate according to sequential computing architectures, parallel computing architectures, or some combination thereof.

[0185] The training computing system **1819** can include a control circuit **1821** and a non-transitory computer-readable medium **1822**, also referred to herein as memory **1822**. In an embodiment, the control circuit **1821** can include one or more processors (e.g., microprocessors), one or more processing cores, a programmable logic circuit (PLC) or a programmable logic/gate array (PLA/PGA), a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), or any other control circuit. In an embodiment, the control circuit **1821** can be programmed by one or more computer-readable or computer-executable instructions stored on the non-transitory computer-readable medium **1822**.

[0186] In an embodiment, the non-transitory computer-readable medium **1822** can be a memory device, also referred to as a data storage device, which can include an electronic storage device, a magnetic storage device, an optical storage device, an electromagnetic storage device, a semiconductor storage device, or any suitable combination thereof. The non-transitory computer-readable medium can form, e.g., a hard disk drive (HDD), a solid state drive (SSD) or solid state integrated memory, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), a static random access memory (SRAM), dynamic random access memory (DRAM), a portable compact disc read-only memory (CD-ROM), a digital versatile disk (DVD), and/or a memory stick.

[0187] The non-transitory computer-readable medium **1822** can store information that can be accessed by the control circuit **1821**. For instance, the non-transitory computer-readable medium **1822** (e.g., memory devices) can store data **1823** that can be obtained, received, accessed, written, manipulated, created, and/or stored. The data **1823** can include, for instance, any of the data or information described herein. In some implementations, the training computing system **1819** can obtain data from one or more memories that are remote from the training computing system **1819**.

[0188] The non-transitory computer-readable medium **1822** can also store computer-readable instructions **1824** that can be executed by the control circuit **1821**. The instructions **1824** can be software written in any suitable programming language or can be implemented in hardware. The instructions can include computer-readable instructions, computer-executable instructions, etc.

[0189] The instructions **1824** can be executed in logically or virtually separate threads on the control circuit **1821**. For example, the non-transitory computer-readable medium **1822** can store instructions **1824** that when executed by the control circuit **1821** cause the control circuit **1821** to

perform any of the operations, methods and/or processes described herein. In some cases, the non-transitory computer-readable medium **1822** can store computer-executable instructions or computer-readable instructions, such as instructions to perform at least a portion of the methods of FIG. 9.

[0190] The training computing system **1819** can include a model trainer **1825** that trains the machine-learned models **1807**, **1817** stored at the computing system **1801** and/or the server computing system **1811** using various training or learning techniques. For example, the models **1807**, **1817** can be trained using a loss function. By way of example, for training a machine-learned segmentation or recommendation model, the model trainer **1825** can use a loss function. For example, a loss function can be backpropagated through the model(s) **1807**, **1817** to update one or more parameters of the model(s) **1807**, **1817** (e.g., based on a gradient of the loss function). Various loss functions can be used such as mean squared error, likelihood loss, cross entropy loss, hinge loss, and/or various other loss functions. Gradient descent techniques can be used to iteratively update the parameters over a number of training iterations.

[0191] The model trainer **1825** can train the models **1807**, **1817** (e.g., a machine-learned clustering model) in an unsupervised fashion. As such, the models **1807**, **1817** can be effectively trained using unlabeled data for particular applications or problem domains, which improves performance and adaptability of the models **1807**, **1817**.

[0192] The training computing system **1819** can modify parameters of the models **1807**, **1817** (e.g., the machine-learned models **114**, **120**, **130**, **150**) based on the loss function such that the models **1807**, **1817** can be effectively trained for specific applications in an unsupervised manner without labeled data.

[0193] The model trainer **1825** can utilize training techniques, such as backwards propagation of errors. For example, a loss function can be backpropagated through a model to update one or more parameters of the models (e.g., based on a gradient of the loss function). Various loss functions can be used such as mean squared error, likelihood loss, cross entropy loss, hinge loss, and/or various other loss functions. Gradient descent techniques can be used to iteratively update the parameters over a number of training iterations.

[0194] In an embodiment, performing backwards propagation of errors can include performing truncated backpropagation through time. The model trainer **1825** can perform a number of generalization techniques (e.g., weight decays, dropouts, etc.) to improve the generalization capability of a model being trained. In particular, the model trainer **1825** can train the machine-learned models **1807**, **1817** based on a set of training data **1826**.

[0195] The training data **1826** can include unlabeled training data for training in an unsupervised fashion. In an example, the training data **1826** can include unlabeled sets of data indicative of varying degrees of ripeness for produce grocery items and data indicative of confirmed ripeness (e.g., unripe, ripe, over ripe), for a produce grocery items. The training data **1826** can be specific to a grocery item to help focus the models **1807**, **1817** on the particular grocery item.

[0196] In an embodiment, training examples can be provided by the computing system **1801** (e.g., client device of the shopper). Thus, in such implementations, a model **1807** provided to the computing system **1801** can be trained by the training computing system **1819** in a manner to personalize the model **1807**.

[0197] The model trainer **1825** can include computer logic utilized to provide desired functionality. The model trainer **1825** can be implemented in hardware, firmware, and/or software controlling a general-purpose processor. For example, in an embodiment, the model trainer **1825** can include program files stored on a storage device, loaded into a memory and executed by one or more processors. In other implementations, the model trainer **1825** can include one or more sets of computer-executable instructions that are stored in a tangible computer-readable storage medium such as RAM, hard disk, or optical or magnetic media.

[0198] The training computing system **1819** can include one or more communication interfaces

1827. The communication interfaces **1827** can be used to communicate with one or more other systems. The communication interfaces **1827** can include any circuits, components, software, etc. for communicating via one or more networks (e.g., networks **1828**). In some implementations, the communication interfaces **1827** can include for example, one or more of a communications controller, receiver, transceiver, transmitter, port, conductors, software and/or hardware for communicating data/information.

[0199] The one or more networks **1828** can be any type of communications network, such as a local area network (e.g., intranet), wide area network (e.g., Internet), or some combination thereof and can include any number of wired or wireless links. In general, communication over a network **1828** can be carried via any type of wired and/or wireless connection, using a wide variety of communication protocols (e.g., TCP/IP, HTTP, SMTP, FTP), encodings or formats (e.g., HTML, XML), and/or protection schemes (e.g., VPN, secure HTTP, SSL).

[0200] FIG. **18** illustrates one example computing system that can be used to implement the present disclosure. Other computing systems can be used as well. For example, in an embodiment, the computing system **1801** can include the model trainer **1825** and the training data **1826**. In such implementations, the models **1807**, **1817** can be both trained and used locally at the computing system **1801**. In some of such implementations, the computing system **1801** can implement the model trainer **1825** to personalize the models **1807**, **1817**.

[0201] Computing tasks discussed herein as being performed at certain computing device(s)/systems can instead be performed at another computing device/system, or vice versa. Such configurations can be implemented without deviating from the scope of the present disclosure. The use of computer-based systems allows for a great variety of possible configurations, combinations, and divisions of tasks and functionality between and among components. Computer-implemented operations can be performed on a single component or across multiple components. Computer-implemented tasks or operations can be performed sequentially or in parallel. Data and instructions can be stored in a single memory device or across multiple memory devices.

[0202] The technology discussed herein makes reference to servers, databases, software applications, and other computer-based systems, as well as actions taken, and information sent to and from such systems. The inherent flexibility of computer-based systems allows for a great variety of possible configurations, combinations, and divisions of tasks and functionality between and among components. For instance, processes discussed herein can be implemented using a single device or component or multiple devices or components working in combination. Databases and applications can be implemented on a single system or distributed across multiple systems. Distributed components can operate sequentially or in parallel.

[0203] Aspects of the disclosure have been described in terms of illustrative implementations thereof. Numerous other implementations, modifications, or variations within the scope and spirit of the appended claims can occur to persons of ordinary skill in the art from a review of this disclosure. Any and all features in the following claims can be combined or rearranged in any way possible. Accordingly, the scope of the present disclosure is by way of example rather than by way of limitation, and the subject disclosure does not preclude inclusion of such modifications, variations or additions to the present subject matter as would be readily apparent to one of ordinary skill in the art. Moreover, terms are described herein using lists of example elements joined by conjunctions such as “and,” “or,” “but,” etc. It should be understood that such conjunctions are provided for explanatory purposes only. The term “or” and “and/or” can be used interchangeably herein. Lists joined by a particular conjunction such as “or,” for example, can refer to “at least one of” or “any combination of” example elements listed therein, with “or” being understood as “and/or” unless otherwise indicated. Also, terms such as “based on” should be understood as “based at least in part on.”

[0204] Those of ordinary skill in the art, using the disclosures provided herein, will understand that the elements of any of the claims discussed herein can be adapted, rearranged, expanded, omitted,

combined, or modified in various ways without deviating from the scope of the present disclosure. Some implementations are described with a reference numeral, for example illustrated purposes and are not meant to be limiting.

Claims

1. A computer-implemented method, including: accessing data comprising a centralized data structure comprising a plurality of order requests, wherein each order request of a centralized list of order requests comprises a plurality of data objects, each data object being indicative of an item; computing, based on a first order request of the centralized list of order requests and merchant location data, a shopping list comprising: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item; storing the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices; accessing data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices; automatically updating, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data; accessing data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices; based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, computing a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective item of a plurality of items; and transmitting data comprising instructions, that, when executed by the first computing device, cause an interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.

2. The computer-implemented method of claim 1, comprising: transmitting data comprising instructions, that, when executed by the second computing device, cause the interactive user interface of the second computing device to provide the second subset of items for display via the interactive user interface of the second computing device.

3. The computer-implemented method of claim 2, comprising: computing a first progress metric for the first computing device and a second progress metric for the second computing device, the first progress metric indicative of an amount of completion of the first subset of the first shopping list and the second progress metric indicative of an amount of completion of the second subset of the first shopping list; and based on the first progress metric and the second progress metric, periodically transmitting instructions, that when executed, cause at least one of: (i) the interactive user interface of the first computing device or (ii) the interactive user interface of the second computing device to be updated.

4. The computer-implemented method of claim 3, wherein periodically transmitting instructions, that when executed, cause the interactive user interface of the first computing device and the interactive user interface of the second computing device to be updated comprises: accessing current location data indicative of a real-time location of the first computing device and a real-time location of the second computing device within the merchant location; based on (i) the current location data, (ii) the first progress metric, and (iii) the second progress metric, dynamically adjusting a distribution of items between the first subset of items and the second subset of items; and based on dynamically adjusting the distribution of items, automatically transmitting instructions which cause the interactive user interface associated with the first computing device to provide for display an updated first subset of items and the interactive user interface associated with the second computing system to provide for display an updated second subset of items.

5. The computer-implemented method of claim 4, wherein dynamically adjusting the distribution of items between the first subset of items and the second subset of items comprises removing one or more items from the first subset of items and adding the one or more removed items to the second subset of items.

6. The computer-implemented method of claim 4, the method comprising: determining a replacement item is needed for a first item of the first subset of items; based on a location of a recommended replacement item and the current location data, updating the second subset of items to include the replacement item; and transmitting data comprising instructions that, when executed by the second computing device, cause the interactive user interface of the second computing device to provide the updated second subset of items for display via the interactive user interface of the second computing device.

7. The computer-implemented method of claim 6, wherein the location of the recommended replacement item and the real-time location of the second computing device are within a predefined threshold.

8. The computer-implemented method of claim 1, wherein computing the first subset of items for the first computing device and the second subset of items for the second computing device comprising: determining a percent completion of the first shopping list; and based on the percent completion of the first shopping list exceeding a predefined range, updating the order status data to indicate that the order cannot be selected by a second computing device.

9. The computer-implemented method of claim 1, wherein the features associated with the first computing device and the features associated with the second computing device comprise historical performance of an operator associated with the respective device or experience level of the operator associated with the respective device.

10. The computer-implemented method of claim 9, wherein the historical performance of the operator comprises an aggregation of metrics associated with past order fulfillment instance, the metrics comprising at least one of: (i) an order replacement satisfaction rate, (ii) a shop time, or (ii) a wait time for a courier picking up the order.

11. The computer-implemented method of claim 9, wherein the experience level of the operator is determined based on at least one of: (i) a number of previously completed orders or (ii) characteristics of previously completed orders.

12. A computing system one or more processors; and one or more non-transitory, computer-readable media storing instructions that are executable by the one or more processors to cause the computing system to perform operations, the operations comprising: accessing data comprising a centralized data structure comprising a plurality of order requests, wherein each order request of a centralized list of order requests comprises a plurality of data objects, each data object being indicative of an item; computing, based on a first order request of the centralized list of order requests and merchant location data, a shopping list comprising: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item; storing the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices; accessing data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices; automatically updating, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data; accessing data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices; based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, computing a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective data object of the plurality of data objects for items; and transmitting data comprising instructions,

that, when executed by the first computing device, cause an interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.

13. The computing system of claim 12, wherein the characteristic data of each respective data object of the plurality of data objects for items comprises at least one of: (i) an item type, (ii) an item location, or (iii) an item category.

14. The computing system of claim 13, wherein the item type comprises at least one of: (i) frozen, (ii) perishable, (iii) non-perishable, (iv) non-edible, (v) refrigerated, or (vi) shelf stable.

15. The computing system of claim 13, wherein the item category comprises an indication of at least one of: (i) produce, (ii) canned goods, (iii) outside aisle, (iv) pharmacy, (v) bakery, (vi) snacks, (vii) beverages, or (viii) frozen goods.

16. The computing system of claim 12, wherein computing first subset of items and the second subset of items is performed responsive to accessing data indicative of the first computing device indicating a need for assistance.

17. The computing system of claim 12, wherein the order status comprises unclaimed, claimed and not begun, in progress, nearly done, or completed.

18. The computing system of claim 12, wherein computing the first subset of items and the second subset of items is performed responsive to determining that a courier associated with picking up the first shopping list will arrive before the first computing device completes the shopping list.

19. The computing system of claim 12, comprising: based on obtaining a request for the computed shopping list and the plurality of other additional shopping lists, transmitting data comprising instructions, that, when executed by a shopper computing device, cause presentation of the shopping list and the plurality of other additional shopping lists via an interactive user interface the shopper computing device.

20. One or more non-transitory computer readable media storing instructions that are executable by one or more processors to perform operations, comprising: accessing data comprising a centralized data structure comprising a plurality of order requests, wherein each order request of the centralized data structure of order requests comprises a plurality of data objects, each data object being indicative of an item; computing, based on a first order request of the centralized data structure of order requests and merchant location data, a shopping list comprising: (i) the plurality of data objects for items to be retrieved for the first order and (ii) characteristic data for each respective item; storing the computed shopping list and a plurality of other additional shopping lists in a shopping list data store, the shopping list data store accessible to a plurality of shopper computing devices; accessing data indicative of selection of the first shopping list by a first computing device of the plurality of shopper computing devices; automatically updating, based on accessing the data indicative of the selection of the first shopping list, the shopping list data store to include order status data; accessing data indicative of selection of the first shopping list by a second computing device of the plurality of shopper computing devices; based on accessing data indicative of selection of the first shopping list by the first computing device and the second computing device, computing a first subset of items for the first computing device and a second subset of items for the second computing device based on (i) features associated with the first computing device, (ii) features associated with the second computing device, and (iii) the characteristic data of each respective data object of the plurality of data objects for items; and transmitting data comprising instructions, that, when executed by the first computing device, cause an interactive user interface of the first computing device to provide the first subset of items for display via the interactive user interface of the first computing device.
