

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279608

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

TSUSU; Koichi

ELECTRICAL CONNECTOR

Abstract

Side wall portions of a male connector that define a housing space includes first recesses having a shape of a groove extending along an insertion direction. A female connector includes a first protrusion that has a shape of a convexity extending along the insertion direction, and fitting in the first recess. The first recess of the male connector includes an inclined surface, the inclined surface being inclined relative to the insertion direction. The male connector and the female connector satisfy relation equations

[00001] $A > \times B$ (1) (where $1 \leq \leq 1.0641$) $25^\circ \leq Y \leq 45^\circ$ (2) provided that a dimension of the groove of the first recess is A, a dimension of a width of the first protrusion is B, and an inclination angle of the inclined surface relative to the insertion direction is Y.

Inventors: TSUSU; Koichi (Shizuoka-shi, JP)

Applicant: I-PEX Inc. (Kyoto-shi, JP)

Family ID: 96860880

Appl. No.: 19/047423

Filed: February 06, 2025

Foreign Application Priority Data

JP 2024-030969 Mar. 01, 2024

Publication Classification

Int. Cl.: H01R13/46 (20060101); H01R12/72 (20110101)

U.S. Cl.:

CPC H01R13/46 (20130101); H01R12/722 (20130101); H01R2201/26 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of Japanese Patent Application No. 2024-30969, filed on Mar. 1, 2024, the entire disclosure of which is incorporated by reference herein.

FIELD OF THE INVENTION

[0002] This application relates to an electrical connector.

BACKGROUND OF THE INVENTION

[0003] Japanese Unexamined Patent Application Publication No. 2002-289302 discloses an electrical connector including a plug connector and a socket connector. In the electrical connector disclosed in Japanese Unexamined Patent Application Publication No. 2002-289302, the plug connector is a male connector, and the socket connector is a female connector that is electrically connected by being inserted into an insertion port of the plug connector.

[0004] The electrical connector has a problem that, if the socket connector is inserted to the plug connector in a significantly inclined state, an insertion slot of the plug connector deforms in a direction that widens the insertion slot, causing damage to the plug connector.

[0005] The present disclosure has been made in consideration of the above-described circumstances, and an objective of the present disclosure is to provide an electrical connector including a pair of connectors that are fitted together and suppressing damage caused upon inserting one of the pair of connectors into the other of the pair of connectors.

SUMMARY OF THE INVENTION

[0006] In order to achieve the aforementioned objective, an electrical connector according to the present disclosure includes: [0007] a male connector in which a housing space and an opening leading from the housing space to an outside are formed; and [0008] a female connector to be inserted into the male connector from the opening of the housing space in an insertion direction, wherein [0009] the male connector includes surface portions that define the housing space, the surface portions including a first recess that has a shape of a groove extending along the insertion direction, [0010] the female connector includes a first protrusion that has a shape of a convexity extending along the insertion direction, and fits in the first recess, [0011] the first recess of the male connector includes an inclined surface, the inclined surface being inclined relative to the insertion direction, and [0012] the male connector and the female connector satisfy relation equations [00002] $A > \frac{1}{2} \times B$ (1) (where $1 \leq \frac{A}{B} \leq 1.0641$) $25^\circ \leq Y \leq 45^\circ$ (2) [0013] provided that a dimension of the groove of the first recess is A, a dimension of a width of the first protrusion is B, and an inclination angle of the inclined surface relative to the insertion direction is Y.

[0014] The present disclosure can suppress damage that may occur upon insertion of a female connector into a male connector.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] A more complete understanding of this application can be obtained when the following detailed description is considered in conjunction with the following drawings, in which:

[0016] FIG. 1 is a first exploded perspective view of an electrical connector according to Embodiment 1 of the present disclosure;

[0017] FIG. 2 is a second exploded perspective view of the electrical connector according to Embodiment 1;

[0018] FIG. 3 is a back view of the electrical connector according to Embodiment 1;

[0019] FIG. **4** is a plan view of the electrical connector according to Embodiment 1;
[0020] FIG. **5** is a first cross-sectional view for describing a method for manufacturing the electrical connector according to Embodiment 1;
[0021] FIG. **6** is a second cross-sectional view for describing the method for manufacturing the electrical connector according to Embodiment 1;
[0022] FIG. **7** is an exploded cross-sectional view of the electrical connector taken along an A-A cross-section of FIG. **4**;
[0023] FIG. **8** is a first cross-sectional view for describing a process of inserting a female connector into a male connector in Embodiment 1;
[0024] FIG. **9** is a second cross-sectional view for describing the process of inserting the female connector into the male connector in Embodiment 1;
[0025] FIG. **10** is an exploded cross-sectional view of the electrical connector according to a comparative example;
[0026] FIG. **11** is a first exploded perspective view of an electrical connector according to Embodiment 2;
[0027] FIG. **12** is a second exploded perspective view of the electrical connector according to Embodiment 2;
[0028] FIG. **13** is a first cross-sectional view for describing a process of inserting a female connector into a male connector in Embodiment 2;
[0029] FIG. **14** is a second cross-sectional view for describing the process of inserting the female connector into the male connector in Embodiment 2; and
[0030] FIG. **15** is an exploded perspective view of an electrical connector according to Embodiment 3.

DETAILED DESCRIPTION OF THE INVENTION

Embodiment 1

[0031] Hereinafter, an electrical connector **1** according to the embodiment of the present disclosure is described with reference to the drawings. In order to facilitate understanding, XYZ coordinates orthogonal to one another are set and are referred as appropriate. A-X direction of the XYZ coordinates is a direction same as an insertion direction D1 in which a female connector **20** is inserted into a male connector **10**, as illustrated in FIG. **1**. A Z-axis direction is a direction same as a height direction D2 of the electrical connector **1**. A Y-axis direction is a direction same as a width direction D3 of the electrical connector **1**.

[0032] The electrical connector **1** is, for example, an electronic circuit component equipped in an automobile component. As illustrated in FIGS. **1** and **2**, the electrical connector **1** includes a male connector **10** and a female connector **20**.

[0033] As illustrated in FIGS. **3** and **4**, the male connector **10** is a connector to which the female connector **20** is fitted, and is attached to a circuit board **90** that is a device to which the male connector **10** is installed. The male connector **10** includes a housing **10a**, retainers H, and male terminals **30**.

[0034] As illustrated in FIGS. **1** and **2**, the housing **10a** has a shape of a substantially rectangular parallelepiped, and includes a pair of side wall portions **13R** and **13L**, a ceiling portion **14**, a bottom portion **15**, and a rear-side wall portion **16**.

[0035] The side wall portions **13R** and **13L** form walls on both sides of the housing **10a** in the width direction D3 of the substantially rectangular parallelepiped. A first recess **11** is provided to an inner surface of each of the side wall portions **13R** and **13L**. The first recess **11** has a shape of a groove extending along the insertion direction D1 (X-axis direction). The first recess **11** according to the present embodiment is provided to each of the side wall portions **13R** and **13L**, but is not limited thereto. For example, the first recess **11** may be provided to one of the side wall portions **13R** and **13L**. The first recess **11** may be provided to the surface portions other than the side wall portions **13R** and **13L**. For example, the first recess **11** may be provided to one or both of the

ceiling portion **14** and bottom portion **15**. The first recess **11** is provided to the inner surface of each of the side wall portions **13R** and **13L**, but is not limited thereto. The first recess **11** may be provided to an outer surface of each of the side wall portions **13R** and **13L**. Furthermore, the first recess **11** may be provided to an outer face of the surface portions other than the side wall portions **13R** and **13L**.

[0036] The ceiling portion **14** forms a portion on a +Z side of the substantially rectangular parallelepiped of the housing **10a**.

[0037] The bottom portion **15** forms a surface portion on a -Z side of the substantially rectangular parallelepiped of the housing **10a**. The bottom portion **15** is a surface portion in contact with the circuit board **90**.

[0038] The rear-side wall portion **16** forms a wall portion on a -X side of the substantially rectangular parallelepiped of the housing **10a**.

[0039] The housing **10a** formed as described above has, inside the substantially rectangular parallelepiped, a housing space S and an opening S1 leading from the housing space S to the outside.

[0040] The opening S1 is formed in the housing **10a** to open in a +X direction. A part of the female connector **20** is fitted into the male connector **10** through the opening S1 and is accommodated in the housing space S provided inside the housing **10a**.

[0041] The housing **10a** according to Embodiment 1 is made of a material of solidified molten resin. Specifically, the housing **10a** is formed, for example, by pouring molten resin into injection molds **80A** and **80B** having two gates **81** and **82**, followed by solidification of the molten resin, as illustrated in FIGS. 5 and 6. In Embodiment 1, the housing **10a** is formed, for example, by pouring the molten resin into a portion **16a** through the two gates **81** and **82**. The portion **16a** is a portion where the rear-side wall portion **16** (see FIGS. 1 and 2) of the housing **10a** is formed. As a result, gate traces **17** are provided to the housing **10a** on the rear-side surface, that is, the surface on the -X side, of the rear-side wall portion **16**, as illustrated in FIG. 3. The gate traces **17** are inlets for inflow therethrough of the molten resin.

[0042] The gate traces **17** are provided at the center in the width direction D3. At least a pair of the gate traces **17** is provided along the height direction D2. The pair of gate traces **17** according to Embodiment 1 have different sizes.

[0043] Moreover, as the housing **10a** is formed using the injection molds **80A** and **80B** (see FIGS. 5 and 6) having the two gates **81** and **82**, weld lines L are formed on the side wall portions **13R** and **13L** of the housing **10a**, as illustrated in FIGS. 1 and 2. The weld line L is a molding defect area, that is, a portion where the molten resin merges, that occurs during molding of the molten resin. The weld line L according to Embodiment 1 is a slightly wavy line that extends along the insertion direction D1.

[0044] As illustrated in FIG. 7, the aforementioned first recesses **11** of the side wall portions **13R** and **13L** are provided on the +Z side (one side) in the height direction D2 of the male connector **10** than the positions where the weld lines L are located. Therefore, the first recess **11** is not provided at the same position as the weld line L in the height direction D2 of the male connector **10**, and is provided at a position shifted in the height direction D2, more specifically, a position closer to the top than the weld line L is. Furthermore, as illustrated in FIG. 2, an inclined surface **11a** is provided on a lower edge of an opening of the first recess **11**. The inclined surface **11a** is inclined at a predetermined angle relative to the insertion direction D1. The inclined surface **11a** is provided to facilitate the fitting of a first protrusion **21** into the first recess **11**, as well as to guide the insertion of the first protrusion **21** of the female connector **20**, upon insertion of the female connector **20** into the male connector **10**.

[0045] As illustrated in FIGS. 1 and 2, the retainer H is a member provided on the outer surface of each of the side wall portions **13R** and **13L** of the housing **10a**, and is fixed to the surface of the circuit board **90** that is a device to which the male connector **10** is installed. The retainer H is

formed, for example, by bending a plate-shaped metal member into an L-shape. The retainers H are used to firmly fix the housing **10a** to the circuit board **90**.

[0046] The male terminals **30** penetrate through and are arranged to the rear-side wall portion **16** of the housing **10a**, as illustrated in FIG. **4**. The male terminal **30** is prepared through, for example, press working a conductive board material such as copper, copper alloy, or the like. One end of the male terminal **30** protrudes into the housing space S of the housing **10a**. The other end of the male terminal **30**, that is, an end on the $-X$ side protrudes from the rear-side wall portion **16** of the housing **10a** on the $-X$ side, as illustrated in FIG. **4**. The end of the male terminal **30** on the $-X$ side is electrically connected to a conductive portion on the surface of the circuit board **90**, for example, by soldering.

[0047] As illustrated in FIGS. **1** and **2**, the female connector **20** includes a housing **20a**, the first protrusions **21**, locking arms **23**, engaging sections **24**, an operative tap **25**, and female terminals **40**.

[0048] The housing **20a** is formed to be accommodatable inside the housing space S of the housing **10a** of the male connector **10**. Specifically, the housing **20a** has a shape that corresponds to the internal shape of the housing space S of the male connector **10**, and also is capable allows fitting of the female connector **20** to the male connector **10** from the opening **S1**. The housing **20a** has terminal housing chambers for housing the respective female terminals **40**.

[0049] The first protrusion **21** is provided to each of the side surface on the $-Y$ side and the side surface on the $+Y$ side of the housing **20a**. The first protrusion **21** has a shape of a convexity elongating along the insertion direction **D1**, and fits in the first recess **11**.

[0050] Two locking arms **23** are provided on a top surface of the housing **20a**. The locking arm **23** is flexible in the height direction **D2**.

[0051] The engaging sections **24** are provided to each of the two locking arms **23**. The engaging sections **24** protrude in the $+Z$ direction from the respective locking arms **23**. The engaging sections **24** can engage with non-illustrated engaged sections provided inside the male connector **10**.

[0052] The operative tap **25** is used to disengage the engaging sections **24** from the engaged sections of the male connector **10** by a pressing operation by a user of the electrical connector **1**.

[0053] The female terminals **40** are accommodated in the respective terminal housing chambers of the housing **20a**, as illustrated in FIG. **2**. The female terminal **40** has, for example, a cylindrical portion capable of receiving the male terminal **30** (see FIG. **4**) to be connected, and a crimping portion where a cable **50** is crimped and connected. When the female terminal **40** is attached to the housing **20a**, the cable **50** connected to the female terminals **40** is in a state where the cable **50** is drawn from the housing **20a**.

[0054] As illustrated in FIGS. **8** and **9**, the electrical connector **1** with the configurations described above satisfies relation equations

[00003] $A > \alpha \times B$ (1) (where $1 \leq \alpha \leq 1.0641$) $25^\circ \leq Y \leq 45^\circ$ (2) [0055] provided that a dimension of the groove of the first recess **11** is A, a dimension of a width of the first protrusion **21** is B, and an inclination angle of the inclined surface **11a** relative to the insertion direction **D1** is Y.

[0056] Specifically, the electrical connector **1** according to Embodiment 1 satisfies a relation equation

[00004] $A / B = 1.0641$ ($\alpha = 1.0641$). (3)

[0057] In other words, the electrical connector **1** satisfies relation equations

[00005] $A > B / \cos X$ (4) $X \leq 20^\circ$ (5) $(X + Y) < 45^\circ$ (6) [0058] provided that an inclination angle of the female connector **20** relative to the insertion direction **D1** upon insertion of the female connector **20** into the male connector **10** is X. According to the relation equation (5), it indicates that the female connector **20** is inserted into the male connector **10** with an inclination angle X of 20° or less. In the aforementioned relation equation (1), “ α ” indicates “ $\sec X$ ”, that is a reciprocal of “ $\cos X$ ”, in other words, “ α ” indicates “ $1/\cos X$ ”. The upper limit of “ α ”, “1.0641”, is calculated

from " $1/\cos 20^\circ$ " ($1/\cos 20^\circ \approx 1/0.9397 \approx 1.0641$), based on the condition that the inclination angle X of the female connector **20** is 20° or less in the aforementioned relation equation (5).
[0059] As described above, in the electrical connector **1** according to Embodiment 1, the dimension A of the groove of the first recess **11**, the dimension B of the width of the first protrusion **21**, and the inclination angle Y of the inclined surface **11a** relative to the insertion direction **D1** satisfy the aforementioned relation equations. Therefore, upon insertion of the female connector **20** into the male connector **10** as illustrated in FIGS. **1** and **2**, the first protrusions **21** of the female connector **20** come in contact with the inclined surfaces **11a** of the first recesses **11** of the male connector **10** to guide the female connector **20** towards the housing space S of the male connector **10** and suppress the inclination angle X of the female connector **20** relative to the insertion direction **D1** to 20° or less. As such, as illustrated in FIG. **9**, this makes it easier for the first protrusions **21** to contact the inclined surfaces **11a** of the first recesses **11** before the first protrusions **21** contacting the upper edges **11b** of the first recesses **11**.

[0060] For example, in an electrical connector **1A** according to a comparative example, a female connector **20** is inserted into a male connector **10** at an inclination angle X greater than 20° ($X > 20^\circ$), as illustrated in FIG. **10**. As such, in some cases, first protrusions **21** come in contact with upper edges **11b** of first recesses **11** before the first protrusions **21** contacting inclined surfaces **11a** of the first recesses **11**. In this case, due to the contact, for example, a force F to open in a height direction **D2** is applied to the first recesses **11**. This may deform an opening of the male connector **10** in a direction that widens the opening, which may cause damage such as cracks in the male connector **10**. The force F may further cause splits in weld lines L.

[0061] However, in the electrical connector **1** according to Embodiment 1, the inclination angle X of the female connector **20** relative to the insertion direction **D1** upon insertion of the female connector **20** into the male connector **10** is suppressed to 20° or less, as illustrated in FIGS. **8** and **9**. Therefore, this makes it easier for the first protrusions **21** to contact the inclined surfaces **11a** of the first recesses **11** before the first protrusions **21** contacting the upper edges **11b** of the first recesses **11**. As such, for example, the force F to open in the height direction **D2** (see FIG. **10**) is less likely applied on the first recesses **11**, and thus, damage to the male connector **10** can be suppressed. As described above, in Embodiment 1, damage that may occur upon insertion of the female connector **20** into the male connector **10** can be suppressed.

[0062] In Embodiment 1, the first recesses **11** are arranged to the wall portions of the housing **10a** on the +Z side in the height direction **D2** compared to the position where the weld lines L are provided. That is, the first recesses **11** and the weld lines L are not provided at the same position in the height direction **D2**. Therefore, compared to a structure in which the first recesses **11** and the weld lines L are provided at the same position in the height direction **D2**, the aforementioned structure can suppress damage to the first recesses **11** and to the weld lines L. As a result, in Embodiment 1, damage that may occur upon insertion of the female connector **20** into the male connector **10** can be suppressed.

[0063] Furthermore, in Embodiment 1, the gate traces **17** are provided at the center in the width direction **D3**, and a pair of the gate traces **17** is provided along the height direction **D2**, as illustrated in FIG. **3**. This makes it easier to change or adjust the position of the weld lines L in the height direction **D2** in Embodiment 1.

Embodiment 2

[0064] In the electrical connector **1** according to Embodiment 1, the side wall portions **13R** and **13L** of the housing **10a** each include one first recess **11**, as illustrated in FIGS. **1** and **2**. However, the present disclosure is not limited thereto. As an electrical connector **2** according to Embodiment 2 illustrated in FIGS. **11** and **12**, side wall portions **13R** and **13L** of a housing **10a** of a male connector **10** may include, in addition to first recesses **11**, a second recess **12**. In this case, a female connector **20** includes, in addition to first protrusions **21**, a second protrusion **22** extending along an insertion direction **D1** with a space from the first protrusion **21**.

[0065] The second recess **12** is provided on one side wall portion **13L** of the side wall portions **13R** and **13L**. As illustrated in FIGS. **13** and **14**, the second recess **12** extends along the insertion direction **D1** with a space from the first recess **11**. In Embodiment 2, the second recess **12** is not provided to the other side wall portion **13R** of the side wall portions **13R** and **13L**. Furthermore, in Embodiment 2, weld lines **L** are provided between the second recess **12** and the first recess **11**. Furthermore, as illustrated in FIGS. **12** and **13**, an inclined surface **12a** is provided on an upper edge of an opening of the second recess **12**. The inclined surface **12a** is inclined at a predetermined angle relative to the insertion direction **D1**. The inclined surface **12a** is provided to facilitate the fitting of the second protrusion **22** into the second recess **12**, as well as to guide the insertion of the second protrusion **22** of the female connector **20**, upon insertion of the female connector **20** into the male connector **10**. In Embodiment 2, an inclination angle Y' of the inclined surface **12a** is the same as an inclination angle Y of the inclined surface **11a** ($Y=Y'$). However, the present disclosure is not limited thereto. The inclination angle Y' of the inclined surface **12a** is not necessarily the same as the inclination angle Y of the inclined surface **11a** ($Y+Y'$). The inclination angle Y' of the inclined surface **12a**, however, preferably approximates to the inclination angle Y of the inclined surface **11a**.

[0066] As illustrated in FIGS. **11** and **12**, the second protrusion **22** is provided to a side surface on the $-Y$ side of the side surface on the $-Y$ side and the side surface on the $+Y$ side of the housing **20a**. The second protrusion **22** has a shape of a convexity that elongates along the insertion direction **D1**, and fits in the second recess **12**. As illustrated in FIGS. **13** and **14**, the second protrusion **22** extends along the insertion direction **D1** with a space from the first protrusion **21**. In Embodiment 2, the second protrusion **22** is not provided to the other side surface on the $+Y$ side of the side surface on the $-Y$ side and the side surface on the $+Y$ side of the housing **20a**.

[0067] The electrical connector **2** with the configurations described above satisfies relation equations

$$[00006] A > \times B \quad (1) \quad C > \times D \quad (7) \quad (\text{where } 1 \leq \leq 1.0641) \quad 25^\circ \leq Y = Y' \leq 45^\circ \quad (8)$$

[0068] provided that a dimension of the groove of the first recess **11** is A , a dimension of a width of the first protrusion **21** is B , a dimension of the groove of the second recess **12** is C , a dimension of the width of the second protrusion **22** is D , and an inclination angle of the inclined surface **11a** relative to the insertion direction **D1** is Y .

[0069] Specifically, the electrical connector **2** according to Embodiment 2 satisfies relation equations

$$[00007] A / B = C / D = 1.0641 (= 1.0641) \quad (9) \quad 25^\circ \leq Y = Y' \leq 45^\circ . \quad (10)$$

[0070] As described above, in the electrical connector **2** according to Embodiment 2, the dimension A of the groove of the first recess **11**, the dimension B of the width of the first protrusion **21**, the dimension C of the groove of the second recess **12**, the dimension D of the width of the second protrusion **22**, and the inclination angles Y and Y' of the inclined surfaces **11a** and **12a** relative to the insertion direction **D1** satisfy the aforementioned relation equations. Therefore, it can suppress the angle of insertion of the female connector **20** into the male connector **10** from increasing. As a result, in Embodiment 2, damage that may occur upon insertion of the female connector **20** into the male connector **10** can be suppressed.

[0071] Furthermore, in Embodiment 2, the weld lines **L** are provided between the first recess **11** and the second recess **12**. That is, the second recess **12** and the weld lines **L** are not provided at the same position in the height direction **D2**. Therefore, compared to a structure in which the second recess **12** and the weld lines **L** are provided at the same position in the height direction **D2**, the aforementioned structure can suppress damage such as cracks in the second recess **12** and the weld lines **L**. As a result, in Embodiment 2, damage that may occur upon insertion of the female connector **20** into the male connector **10** can be suppressed.

[0072] The configuration in Embodiment 2 also produces the same advantageous effects as in

Embodiment 1.

[0073] Although embodiments of the present disclosure are described above, the present disclosure is not limited to the aforementioned embodiments.

[0074] For example, in Embodiment 1, the first recesses **11** of the side wall portions **13R** and **13L** are provided on the +Z side (one side) in the height direction D2 of the male connector **10** than the position where the weld lines L are provided, as illustrated in FIG. 7. However, the present disclosure is not limited thereto. The first recesses **11** may be arranged on the -Z side (the other side) in the height direction D2 than the position where the weld lines L are provided.

[0075] Furthermore, in Embodiment 2, the weld lines L are provided between the first recess **11** and the second recess **12**, as illustrated in FIGS. 13 and 14. However, the present disclosure is not limited thereto. The weld line L may not be provided between the first recess **11** and the second recess **12**.

[0076] Furthermore, in Embodiment 1, the gate traces **17** are provided at the center in the width direction D3, and at least a pair of the gate traces **17** is provided along the height direction D2, as illustrated in FIG. 3. However, the present disclosure is not limited thereto. Three or more gate traces **17** may be provided. In such a case, the three or more gate traces **17** may preferably be provided at the center in the width direction D3 and along the height direction D2.

[0077] As illustrated in FIG. 3, the pair of gate traces **17** according to Embodiment 1 have different sizes. However, the present disclosure is not limited thereto. The pair of gate traces **17** may have the same size.

Embodiment 3

[0078] In Embodiment 2, the second recess **12** is provided on the one side wall portion **13L** of the side wall portions **13R** and **13L**, as illustrated in FIG. 11. However, the present disclosure is not limited thereto. As an electrical connector **3** according to Embodiment 3 illustrated in FIG. 15, second recesses **12** may be provided to both side wall portions **13R** and **13L**. In this case, second protrusions **22** are provided to both of a side surface on the -Y side and a side surface on the +Y side of a housing **20a** of a female connector **20**.

[0079] The foregoing describes some example embodiments for explanatory purposes. Although the foregoing discussion has presented specific embodiments, persons skilled in the art will recognize that changes may be made in form and detail without departing from the broader spirit and scope of the invention. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense. This detailed description, therefore, is not to be taken in a limiting sense, and the scope of the invention is defined only by the included claims, along with the full range of equivalents to which such claims are entitled. [0080] **1, 1A, 2, 3** Electrical connector [0081] **10** Male connector [0082] **10a** Housing [0083] **11** First recess [0084] **11a** Inclined surface [0085] **11b** Upper edge [0086] **12** Second recess [0087] **12a** Inclined surface [0088] **13R, 13L** Side wall portion [0089] **14** Ceiling portion [0090] **15** Bottom portion [0091] **16** Rear-side wall portion [0092] **16a** Portion (Portion where rear-side wall portion is formed) [0093] **17** Gate trace [0094] **20** Female connector [0095] **20a** Housing [0096] **21** First protrusion [0097] **22** Second protrusion [0098] **23** Locking arm [0099] **24** Engaging section [0100] **25** Operative tap [0101] **30** Male terminal [0102] **40** Female terminal [0103] **50** Cable [0104] **80A, 80B** Injection mold [0105] **81, 82** Gate [0106] **90** Circuit board [0107] H Retainer [0108] L Weld line [0109] S Housing space [0110] S1 Opening [0111] A, C Dimension (of groove) [0112] B, D Dimension (of width) [0113] D1 Insertion direction [0114] D2 Height direction [0115] D3 Width direction [0116] X, Y, Y Inclination angle [0117] F Force (to open in height direction)

INDUSTRIAL APPLICABILITY

[0118] The present disclosure is suitable for use in an electrical connector as an automobile component.

Claims

1. An electrical connector, comprising: a male connector in which a housing space and an opening leading from the housing space to an outside are formed; and a female connector to be inserted into the male connector from the opening of the housing space in an insertion direction, wherein the male connector includes surface portions that define the housing space, the surface portions including a first recess that has a shape of a groove extending along the insertion direction, the female connector includes a first protrusion that has a shape of a convexity extending along the insertion direction, and fitting in the first recess, the first recess of the male connector includes an inclined surface, the inclined surface being inclined relative to the insertion direction, and the male connector and the female connector satisfy relation equations $A > \sqrt{2} \times B$ (1) (where $1 \leq \sqrt{2} \leq 1.0641$) $25^\circ \leq Y \leq 45^\circ$ (2) provided that a dimension of the groove of the first recess is A, a dimension of a width of the first protrusion is B, and an inclination angle of the inclined surface relative to the insertion direction is Y.
 2. The electrical connector according to claim 1, wherein a value A/B obtained by dividing the dimension A of the groove of the first recess by the dimension B of the width of the first protrusion satisfies a relation equation $A / B = 1.0641$. (3)
 3. The electrical connector according to claim 1, wherein the male connector is made of a material of solidified molten resin, the surface portions of the male connector that define the housing space include a pair of side wall portions, a ceiling portion, and a bottom portion, the ceiling portion and the bottom portion connecting the pair of side wall portions, in the pair of side wall portions, weld lines that are linearly occurred upon molding of molten resin are formed to extend long the insertion direction, and the first recesses are arranged to the pair of side wall portions on one side in a height direction of the male connector than a position where the weld lines are provided.
 4. The electrical connector according to claim 3, wherein at least one side wall portion of the pair of the side wall portions includes a second recess that extends along the insertion direction with a space from the first recess, and the weld line is provided between the first recess and the second recess.
 5. The electrical connector according to claim 4, wherein the female connector includes a second protrusion that has a shape of a convexity extending along the insertion direction, and fitting in the second recess.
 6. The electrical connector according to claim 3, wherein the male connector includes at least a pair of gate traces that are inlets for inflow therethrough of the molten resin, the at least the pair of gate traces being provided at a center in a width direction perpendicular to the insertion direction and the height direction of the male connector, and provided along the height direction of the male connector.
 7. The electrical connector according to claim 6, wherein the pair of gate traces have different sizes.
-