

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282007

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

WU; Kai et al.

PRESS PLATE MODULE, PRODUCTION LINE, AND CONTROL METHOD

Abstract

A press plate module, a production line, and a control method are provided. The press plate module includes a press plate assembly and a mounting seat assembly. One of the mounting seat assembly and the press plate assembly is provided with a stop element, and the other is provided with a stop surface. The stop element is selectively extendable and retractable, and the press plate module includes a locked state and an unlocked state. In the locked state, the stop element is in an extended state and abuts against the stop surface, such that the press plate assembly is fixed with the mounting seat assembly, and the mounting seat assembly drives the press plate assembly to move, such that the press plate assembly presses against or separates from a battery. In the unlocked state, the stop element is in a retracted state and separated from the stop surface.

Inventors: WU; Kai (Ningde, CN), CHEN; Shaolin (Ningde, CN), WU; Ying (Ningde, CN), WANG; Wenchong (Ningde, CN), XUE; Qiang (Ningde, CN)

Applicant: Contemporary Amperex Technology (Hong Kong) Limited (Hong Kong, CN)

Family ID: 88655798

Assignee: Contemporary Amperex Technology (Hong Kong) Limited (Hong Kong, CN)

Appl. No.: 19/211091

Filed: May 16, 2025

Foreign Application Priority Data

CN

202311310316.6

Oct. 11, 2023

Related U.S. Application Data

parent WO continuation PCT/CN2023/134497 20231127 PENDING child US 19211091

Publication Classification

Int. Cl.: **B23K37/04** (20060101); **B23K101/36** (20060101); **H01M10/04** (20060101);
H01M50/516 (20210101)

U.S. Cl.:

CPC **B23K37/0435** (20130101); **H01M10/0404** (20130101); **H01M50/516** (20210101);
B23K2101/36 (20180801)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of international Patent Application No. PCT/CN2023/134497, filed on Nov. 27, 2023, which claims priority to the Chinese Patent Application No. 202311310316.6, filed on Oct. 11, 2023. The aforementioned patent applications are incorporated herein by reference in their entirety.

TECHNICAL FIELD

[0002] Embodiments of this application relate to the technical field of battery production, and in particular, to a press plate module, a production line, and a control method.

BACKGROUND

[0003] In the process of battery production and manufacturing, busbar welding needs to be performed on different battery cells in series and parallel connection, so as to form battery modules.

[0004] In the process of busbar welding, it is necessary to attach busbar components to poles of the battery cells, so as to improve the welding yield. Therefore, in the process of busbar welding, an action force is applied to the busbar components through a press plate assembly, such that the busbar components and the poles are pressed tightly and attached.

[0005] Since the size specifications of different types of battery cells in different battery modules are different, it is often necessary to replace press plate assemblies with different sizes in the switching process of producing different types of battery modules on a production line. In the replacement process, it often takes a long time and high labor costs, which adversely affects production efficiency.

SUMMARY

[0006] In view of this, embodiments of this disclosure provide a press plate module, a production line, and a control method for improving the replacement efficiency of a press plate assembly.

[0007] To realize the above objective, the technical solutions of the embodiments of this disclosure are realized as follows:

[0008] An embodiment of this disclosure provides a press plate module for battery assembly operations. The press plate module includes a press plate assembly and a mounting seat assembly, where one of the mounting seat assembly and the press plate assembly is provided with a stop element and the other is provided with a stop surface, and the stop element is selectively extendable and retractable; [0009] the press plate module has a locked state and an unlocked state; [0010] in the locked state, the stop element is in an extended state and abuts against the stop surface, such that the press plate assembly is fixed with the mounting seat assembly, and the mounting seat assembly is able to drive the press plate assembly to move such that the press plate assembly presses against or is separated from a battery; and [0011] in the unlocked state, the stop element is in a retracted state and separated from the stop surface, such that the press plate assembly is separated from the mounting seat assembly.

[0012] According to the embodiment of this disclosure, the press plate module is provided with the stop element which is selectively extendable and retractable and the stop surface matched with the stop element, the press plate assembly can be fixed with or separated from the mounting seat assembly by abutting or not between the stop element and the stop surface, and the press plate module can switch between the locked state and the unlocked state only by controlling the stop element to extend and retract, thereby reducing the process steps of replacing the press plate assembly, being conducive to realizing the automatic operation of replacing the press plate assembly, further being conducive to reducing the time for replacing the press plate assembly, improving the working efficiency, and being conducive to improving the production efficiency of the battery.

[0013] In some embodiments, the stop element is arranged on the mounting seat assembly, and the stop surface is arranged on the press plate assembly. In this way, a related driving mechanism for driving the stop element to extend and retract is located on the mounting seat assembly, and only one set of stop element and related driving mechanism needs to be configured in the mounting seat assembly and a plurality of different types of press plate assemblies, while only the stop surface formed by a fixed surface needs to be arranged in different types of press plate assemblies, which is conducive to simplifying the structure of the press plate assemblies and reducing the manufacturing cost of the press plate assemblies.

[0014] In some embodiments, one of the mounting seat assembly and the press plate assembly is provided with a guide protrusion and the other is provided with a guide hole, and the guide protrusion is able to be inserted into or detached from the guide hole along a moving direction of the press plate assembly. In this way, the stop element can conveniently and smoothly reach the position to realize stop fit with the stop surface during the relative movement of the press plate assembly and the mounting seat assembly, and the probability that the mounting seat assembly cannot be fixed with the press plate assembly since the stop element does not abut against the stop surface after extending is reduced.

[0015] In some embodiments, for projections perpendicular to a vertical direction, in the locked state, a projection of the stop element and a projection of the stop surface at least partially overlap; and in the unlocked state, the projection of the stop element is separated from the projection of the stop surface, such that the press plate assembly is separated from the mounting seat assembly under action of gravity.

[0016] In this way, by using the self-gravity of the press plate assembly and the mounting seat assembly, on the one hand, in the locked state, the stop element is kept to abut against the stop surface, thereby reducing the probability of accidents caused by the separation between the stop element and the stop surface in the working process. On the other hand, in the unlocked state, the press plate assembly is directly separated from the mounting seat assembly under action of gravity without additional action force, thereby improving the convenience of separation.

[0017] In some embodiments, one of the mounting seat assembly and the press plate assembly includes a locking structure, and the other is provided with a fixing hole, where one end of the fixing hole is open for the locking structure to be inserted into the fixing hole, and of a circumferential surface of a part of the locking structure inserted into the fixing hole and a circumferential inner wall of the fixing hole, one is provided with the stop element and the other is provided with the stop surface.

[0018] On the one hand, due to the constraint between the surface of the locking structure and the inner wall of the fixing hole, the stop element can conveniently reach the position to realize stop fit with the stop surface, and the probability that the mounting seat assembly cannot be fixed with the press plate assembly since the stop element does not abut against the stop surface after extending is reduced. On the other hand, the surface of the locking structure and the inner wall of the fixing hole can share the load between the stop element and the stop surface, such that the probability of damage of a driving structure for driving the stop element to extend and retract due to excessive

load is reduced.

[0019] In some embodiments, the mounting seat assembly includes the locking structure and an adapter member, the locking structure is arranged at a side of the adapter member facing towards the press plate assembly, at least part of the locking structure protrudes from a surface of the adapter member at the side facing towards the press plate assembly, and the stop element is located at a protruding part of the locking structure. In this way, on the one hand, the adapter member can abut against the press plate assembly along the moving direction of the press plate assembly, thereby restricting the relative position between the press plate assembly and the mounting seat assembly along the moving direction of the press plate assembly, playing a limiting role, and reducing the probability that the locking structure cannot extend and retract due to collision along the moving direction of the press plate assembly. On the other hand, the stop element is exposed on the locking structure, such that an extendable and retractable state of the stop element is convenient to observe, which is conducive to directly judging whether the function of driving the stop element to extend and retract by the locking structure operates normally.

[0020] In some embodiments, the mounting seat assembly includes a mounting piece and a driving piece, the driving piece is arranged on the mounting piece, and a driving end of the driving piece is drivably connected to the adapter member to drive the adapter member to extend and retract. Therefore, on the one hand, in the unlocked state, the driving piece realizes the purpose of driving the locking structure to be inserted into or pulled out from the fixing hole. On the other hand, in the locked state, the press plate assembly is driven to move by the driving piece, so as to realize the purpose of pressing or separating the press plate assembly from the battery.

[0021] In some embodiments, the mounting seat assembly includes a guide protrusion, and the press plate assembly is provided with a guide hole, where the guide hole is open at a side facing towards the mounting seat assembly, the guide protrusion and the locking structure are located on a same side of the adapter member, the guide protrusion is able to be inserted into the guide hole along an insertion direction of the locking structure into the fixing hole, the locking structure protrudes from the surface of the adapter member at the side facing towards the press plate assembly by a height of $H1$, and the guide protrusion protrudes from the surface of the adapter member at the side facing towards the press plate assembly by a height of $H2$, where $H1 \leq H2$. In this way, the guide protrusion is inserted into the guide hole before the locking structure is inserted into the fixing hole, and the guide protrusion is first matched with the guide hole to realize the positioning between the mounting seat assembly and the press plate assembly, so as to reduce the probability that the locking structure is damaged on impact due to the dislocation between the locking structure and the fixing hole, and meanwhile, be conducive to improving the positioning accuracy of assembling and disassembling the press plate assembly.

[0022] In some embodiments, the locking structure is a pneumatic steel ball locking clamp, and steel balls of the pneumatic steel ball locking clamp form the stop element. In this way, by controlling pressure of gas conveyed to the pneumatic steel ball locking clamp, the steel balls can be driven to extend and retract, thereby facilitating the automatic control over the extendable and retractable movement of the stop element.

[0023] In some embodiments, the inner wall of the fixing hole is provided with a fixing protrusion, and a surface of the fixing protrusion at a side facing away from the mounting seat assembly forms the stop surface. In this way, the stop element can conveniently abut against the fixing protrusion in the extended state and be separated from the fixing protrusion in the retracted state.

[0024] In some embodiments, the press plate assembly includes a press plate body and a fixing shaft sleeve, where the press plate body is provided with a first mounting hole, at least one end of the first mounting hole is open, and the fixing shaft sleeve is provided with a through second mounting hole. The fixing shaft sleeve covers the opening of the first mounting hole and is detachably connected to the press plate body. The first mounting hole communicates with the second mounting hole to form the fixing hole. The fixing protrusion is arranged on an inner wall of

the second mounting hole. In this way, there is no need to directly process and manufacture the fixing protrusion on the press plate body, thereby reducing the production and manufacturing difficulty. After long-term use, the fixing protrusion is worn, only the fixing shaft sleeve needs to be replaced, and the whole press plate assembly does not need to be disassembled and maintained, such that the maintenance efficiency is improved, and the workload and maintenance cost are reduced.

[0025] An embodiment of this disclosure further provides a production line for battery assembly operations. The production line includes the press plate module according to any one of the foregoing embodiments, and the press plate module is configured to selectively press against a battery. In this way, the press plate module switches between a locked state and an unlocked state, such that the efficiency of replacing the press plate assembly is improved in the switching process of producing different types of batteries on a production line.

[0026] In some embodiments, the production line includes a driving module, and a driving end of the driving module is drivably connected to the mounting seat assembly to drive the press plate module to move between a working station and a replacement station. In this way, the driving module drives the press plate module to move between the working station and the replacement station, so as to avoid interference with battery assembly in the process of replacing the press plate assembly.

[0027] In some embodiments, the production line includes a temporary storage module, where the temporary storage module includes a plurality of trays and a driving assembly, where the trays are configured for placing the press plate assemblies, and the driving assembly is drivably connected to each of the trays, so as to selectively move one of the trays to a waiting station, enabling the tray to receive a press plate assembly separated from the mounting seat assembly, or enabling a press plate assembly placed on the tray to be fixed with the mounting seat assembly. In this way, the driving assembly is conducive to realizing the automatic control of moving the press plate assembly that needs to be replaced to the waiting station and cooperating with the press plate module.

[0028] In some embodiments, the mounting seat assembly is able to drive the press plate assembly to move along a vertical direction, and under a condition that the press plate module is located in the replacement station and one of the trays is located in the waiting station, the tray is located below the mounting seat assembly. In this way, the press plate assembly placed on the tray is constrained in position by the fit of a fixing boss and a guide hole, and the probability that the press plate assembly falls off the tray during the movement with the tray is reduced.

[0029] An embodiment of this disclosure further provides a control method for replacing a press plate assembly. The control method includes: [0030] controlling a first driving motor in a driving module to drive a press plate module to move from a working station to a replacement station; [0031] controlling a second driving motor in a driving assembly to drive an empty tray to move to a waiting station; [0032] controlling a first solenoid valve such that a cylinder in a mounting seat assembly drives a press plate assembly to move downwards to a lowest position; [0033] controlling a second solenoid valve to retract steel balls in a pneumatic steel ball locking clamp, thereby changing the press plate module from a locked state to an unlocked state, and dropping the press plate assembly onto the tray at the waiting station; [0034] controlling the first solenoid valve such that the cylinder in the mounting seat assembly drives an adapter member to move upwards to a highest position; [0035] controlling the second driving motor in the driving assembly to drive the tray currently located at the waiting station to move away from the waiting station; [0036] controlling the second driving motor in the driving assembly to drive the tray, on which the press plate assembly to be replaced is placed, to move to the waiting station; [0037] controlling the first solenoid valve such that the cylinder in the mounting seat assembly drives the adapter member to move downwards to the lowest position; [0038] controlling the second solenoid valve such that the steel balls in the pneumatic steel ball locking clamp extend out, thereby changing the press plate module from the unlocked state to the locked state; [0039] controlling the first solenoid valve such

that the cylinder in the mounting seat assembly drives the press plate assembly to move upwards to the highest position; and [0040] controlling the first driving motor in the driving module to drive the press plate module to move from the replacement station to the working station.

[0041] In this way, rapid and automatic replacement of the press plate assembly is realized conveniently, and the working efficiency of replacing the press plate assembly is improved.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0042] FIG. 1 is a schematic diagram of a press plate module from a first perspective according to an embodiment of this disclosure;

[0043] FIG. 2 is a schematic diagram of the embodiment in FIG. 1 from a second perspective;

[0044] FIG. 3 is a schematic diagram of the embodiment in FIG. 1 from a third perspective;

[0045] FIG. 4 is a schematic diagram of a mounting seat assembly according to an embodiment of this disclosure;

[0046] FIG. 5 is a schematic diagram of a locking structure and a fixing hole in a locked state according to an embodiment of this disclosure, where a dotted arrow indicates airflow entering the locking structure;

[0047] FIG. 6 is a schematic diagram of a press plate assembly according to an embodiment of this disclosure;

[0048] FIG. 7 is a schematic diagram of a production line according to an embodiment of this disclosure;

[0049] FIG. 8 is a partially enlarged schematic diagram of position A in FIG. 7;

[0050] FIG. 9 is a schematic diagram of a temporary storage module according to an embodiment of this disclosure;

[0051] FIG. 10 is a schematic diagram of a tray according to an embodiment of this disclosure; and

[0052] FIG. 11 is a schematic diagram of steps of a control method of a production line according to an embodiment of this disclosure.

LIST OF REFERENCE SIGNS

[0053] press plate module **10**; [0054] press plate assembly **11**; [0055] stop surface **11a**; [0056] guide hole **11b**; [0057] fixing hole **11c**; [0058] relief hole **11d**; [0059] fixing protrusion **111**; [0060] press plate body **112**; [0061] first mounting hole **112a**; [0062] fixing shaft sleeve **113**; [0063] second mounting hole **113a**; [0064] mounting seat assembly **12**; [0065] stop element **121**; [0066] guide protrusion **122**; [0067] locking structure **123**; [0068] steel ball **1231**; [0069] piston rod **1232**; [0070] accommodation slot **1232a**; [0071] elastic piece **1233**; [0072] housing **1234**; [0073] air inlet hole **1234a**; [0074] accommodating cavity **1234b**; [0075] adapter member **124**; [0076] mounting piece **125**; [0077] driving piece **126**; [0078] driving module **20**; [0079] temporary storage module **30**; [0080] tray **31**; [0081] tray body **311**; [0082] fixing boss **312**; [0083] driving assembly **32**; [0084] conveying module **40**; and [0085] battery **50**.

DETAILED DESCRIPTION

[0086] It should be noted that, in the case of no conflict, embodiments in this disclosure and the technical features in the embodiments can be combined with each other, and the detailed description in the specific embodiments should be understood as an explanation of the purpose of this disclosure and should not be regarded as an undue restriction on this disclosure.

[0087] Unless otherwise defined, all technical and scientific terms used herein have the same meanings as commonly understood by a person skilled in the technical field of this disclosure. The terms used herein are merely intended to describe the specific embodiments rather than to limit this disclosure. The terms “include” and “contain” and any variations thereof in the specification and detailed description of drawings of this disclosure are intended as non-exclusive inclusion.

[0088] In the description of the embodiments of this disclosure, the technical terms “first”, “second”, “third” and the like are merely intended to distinguish between different items but not intended to indicate or imply relative importance or implicitly specify the quantity of the indicated technical features, specific order, or order of precedence. In the description of the embodiments of this disclosure, unless otherwise expressly specified, “a plurality of” means two or more.

[0089] Reference to “embodiment” herein means that a specific feature, structure or characteristic described with reference to the embodiment may be included in at least one embodiment of this disclosure. The presence of the phrase in various places in the specification does not necessarily mean the same embodiment, nor is it a separate or alternative embodiment that is mutually exclusive with other embodiments. A person skilled in the art explicitly and implicitly understands that the embodiments described herein may be combined with other embodiments.

[0090] In the description of the embodiments of this disclosure, the term “and/or” merely indicates a relationship between related items, and represents three possible relationships. For example, “A and/or B” may represent the following three circumstances: A alone, both A and B, and B alone. In addition, the character “/” herein generally indicates an “or” relationship between contextually associated objects.

[0091] In the description of the embodiments of this disclosure, for ease of description, as shown by the arrow in FIG. 7, a direction where the arrow X is located is a first direction, a direction where the arrow Y is located is a second direction, a direction where the arrow Z is located is a vertical direction, and the direction indicated by the arrow Z along the vertical direction is called “up” and “top”, and the opposite direction is called “down”.

[0092] In the description of the embodiments of this disclosure, unless otherwise expressly specified and defined, the technical terms such as “mounting”, “concatenation”, “connection”, and “fixing” need to be understood in a broad sense, for example, understood as a fixed connection or a detachable connection or integrally formed; or understood as a mechanical connection or an electrical connection; understood as a direct connection, or an indirect connection implemented through an intermediate medium; or understood as internal communication between two components or interaction between two components. A person of ordinary skill in the art can understand specific meanings of these terms in the embodiments of this disclosure based on specific situations.

[0093] In the description of the embodiments of this disclosure, unless otherwise explicitly provided and defined, the technical term “contact” should be understood in a broad sense, which may be direct contact, contact through an intermediate medium layer, contact with no interaction force between the two in contact, or contact with interaction force between the two in contact.

[0094] The following makes a detailed description of the embodiments of this disclosure.

[0095] At present, batteries are increasingly widely used in life and industry. The batteries are not only used in energy storage power systems such as hydro, thermal, wind, and solar power stations, but also widely used in electric means of transport such as electric bicycles, electric motorcycles, and electric vehicles, and used in many other fields such as aerospace. The market demand for the batteries keeps soaring with the increase of the application fields of the batteries.

[0096] A plurality of battery cells are arranged in one battery, and the plurality of battery cells are electrically connected in series and parallel through busbar components.

[0097] The busbar components weld poles of the plurality of battery cells in a welding way. In the process of welding the poles and the busbar components, a press plate assembly needs to press against between the busbar components and the poles so as to attach the poles and the busbar components, thereby improving the welding yield.

[0098] In the process of producing different types of batteries, there are differences in parameters such as the size and shape of the poles of the battery cells with different sizes, and the sizes of the corresponding busbar components are also different. Therefore, sizes of press plate assemblies required to provide an abutting function in the production process of different types of batteries are

different, and different types of press plate assemblies need to be replaced in the process of changing to produce products on a production line.

[0099] An embodiment of this disclosure aims to provide a press plate module that can separate and fix a press plate assembly by switching between unlocking and locking, thereby facilitating rapid replacement of different types of press plate assemblies.

[0100] Specifically, an embodiment of this disclosure provides a press plate module **10**. Referring to FIGS. **1** to **4**, press plate module **10** is configured for assembly operations of a battery **50**. The press plate module **10** includes a press plate assembly **11** and a mounting seat assembly **12**. One of the mounting seat assembly **12** and the press plate assembly **11** is provided with a stop element **121** and the other is provided with a stop surface **11a**. The stop element **121** is selectively extendable and retractable, and the press plate module **10** has a locked state and an unlocked state. In the locked state, the stop element **121** is in an extended state and abuts against the stop surface **11a**, such that the press plate assembly **11** is fixed with the mounting seat assembly **12**, and the mounting seat assembly **12** is able to drive the press plate assembly **11** to move, such that the press plate assembly **11** presses against or is separated from the battery **50**. In the unlocked state, the stop element **121** is in a retracted state and separated from the stop surface **11a**, such that the press plate assembly **11** is separated from the mounting seat assembly **12**.

[0101] The press plate assembly **11** is configured to apply action force between the busbar components and the poles during the assembly of the battery **50**, such that the busbar components and the poles are attached to each other, thereby facilitating the welding between the poles and the busbar components.

[0102] The specific form of the press plate assembly **11** to apply the action force between the busbar components and the poles is not limited. For example, the press plate assembly **11** pushes the busbar components from a side of the busbar components facing away from cells of the battery **50**, such that the busbar components are sandwiched between the press plate assembly **11** and the cells of the battery **50**, and the busbar components are attached to the poles.

[0103] The mounting seat assembly **12** provides a mounting position for the press plate assembly **11**. In addition, in the locked state, a driving end of the mounting seat assembly **12** can drive the press plate assembly **11** to move, such that the press plate assembly **11** can push the busbar components and the poles to be attached. Alternatively, the press plate assembly **11** is separated from the battery **50**, so as to take out the battery **50** after the operation and replace the battery **50** with a new battery **50** to be operated.

[0104] The driving end of the mounting seat assembly **12** is detachably connected to the press plate assembly **11**, such that different types of press plate assemblies **11** can be respectively connected to the mounting seat assembly **12** through disassembly and assembly, so as to meet the requirements of different types of cells of the battery **50** and busbar components.

[0105] The stop surface **11a** is at least part of a surface of a solid structure on the mounting seat assembly **12** or the press plate assembly **11**.

[0106] The stop element **121** and the stop surface **11a** can selectively realize stop fit. Specifically, the stop element **121** can be selectively extendable or retractable. When the stop element **121** is in the extended state, the mounting seat assembly **12** and the press plate assembly **11** are constrained in their relative positions by the abutting action force between the stop element **121** and the stop surface **11a**, so as to realize the purpose of fixing the press plate assembly **11** and the mounting seat assembly **12**, such that the press plate module **10** is in the locked state, and the press plate assembly **11** can move under the driving of the mounting seat assembly **12**. When the stop element **121** is in the retracted state, the stop element **121** is separated from the stop surface **11a**, the abutting action force between the stop element **121** and the stop surface **11a** disappears, and the mounting seat assembly **12** and the press plate assembly **11** can move relatively, such that the press plate assembly **11** is separated from the mounting seat assembly **12**, and the replacement of different types of press plate assemblies **11** can be realized.

[0107] It can be understood that the time when the stop element **121** extends or retracts is selected according to the time when the press plate assembly **11** needs to be replaced.

[0108] According to the embodiment of this disclosure, the press plate module **10** is provided with the stop element **121** which is selectively extendable and retractable and the stop surface **11a** matched with the stop element, the press plate assembly **11** can be fixed with or separated from the mounting seat assembly **12** by abutting or not between the stop element **121** and the stop surface **11a**, and the press plate module **10** can switch between the locked state and the unlocked state only by controlling the stop element **121** to extend and retract, thereby reducing the process steps of replacing the press plate assembly **11**, being conducive to realizing the automatic operation of replacing the press plate assembly **11**, further being conducive to reducing the time for replacing the press plate assembly **11**, improving the working efficiency, and being conducive to improving the production efficiency of the battery **50**.

[0109] The battery **50** may be, but not limited to, used in energy storage power systems, vehicles, ships, aircraft and other electric apparatuses.

[0110] The battery **50** includes a plurality of battery cells. The battery cell may be a secondary battery, and the secondary battery is a battery cell that is reusable through activation of an active material by charging the battery cell that is discharged.

[0111] The battery cell may be a lithium-ion battery, a sodium-ion battery, a sodium-lithium-ion battery, a lithium metal battery, a sodium metal battery, a lithium-sulfur battery, a magnesium-ion battery, a nickel-hydrogen battery, a nickel-cadmium battery, a lead storage battery, or the like. The specific type of the battery cell is not limited by the embodiments of this disclosure.

[0112] As an example, the battery cell may be a cylindrical cell, a prismatic cell, a pouch cell, or a battery cell in another shape. The prismatic cell includes a square-shell battery cell, a blade battery cell, and a polygonal prism battery. An example of the polygonal prism battery is a hexagonal prism battery. The type of the battery cell is not particularly limited by the embodiments of this disclosure.

[0113] The following makes a detailed description of a press plate module **10** in some embodiments of this disclosure.

[0114] It can be understood that corresponding parts need to form a driving mechanism to realize the purpose of driving the stop element **121** to extend and retract, and the stop surface **11a** may be a fixed surface of the solid structure.

[0115] In some embodiments, referring to FIGS. **1** to **4**, the stop element **121** is arranged on the mounting seat assembly **12**, and the stop surface **11a** is arranged on the press plate assembly **11**. In this way, the related driving mechanism for driving the stop element **121** to extend and retract is located on the mounting seat assembly **12**, and only one set of stop element **121** and related driving mechanism needs to be configured in the mounting seat assembly **12** and a plurality of different types of press plate assemblies **11**, while only the stop surface **11a** formed by the fixed surface needs to be arranged in different types of press plate assemblies **11**, which is conducive to simplifying the structure of the press plate assemblies **11** and reducing the manufacturing cost of the press plate assemblies **11**.

[0116] It can be understood that only after the mounting seat assembly **12** and the press plate assembly **11** reach a preset locking position can the stop element **121** extend out to realize the stop fit with the stop surface **11a**.

[0117] In some embodiments, referring to FIG. **4**, one of the mounting seat assembly **12** and the press plate assembly **11** is provided with guide protrusions **122** and the other is provided with guide holes **11b**, and the guide protrusions **122** are able to be inserted into or detached from the guide holes **11b** along a moving direction of the press plate assembly **11**.

[0118] The guide protrusions **122** are arranged on one of the mounting seat assembly **12** and the press plate assembly **11** and extend towards the other.

[0119] After the guide protrusions **122** are inserted into the guide holes **11b**, projections of inner

walls of the guide holes **11b** and surfaces of the guide protrusions **122** in a direction perpendicular to the moving direction of the press plate assembly **11** at least partially overlap, such that the inner walls of the guide holes **11b** and the surfaces of the guide protrusions **122** form stop fit, thereby constraining the relative position between the press plate assembly **11** and the mounting seat assembly **12** in the moving process. In this way, the stop element **121** can conveniently and smoothly reach the position to realize stop fit with the stop surface **11a** during the relative movement of the press plate assembly **11** and the mounting seat assembly **12**, and the probability that the mounting seat assembly **12** cannot be fixed with the press plate assembly **11** since the stop element **121** does not abut against the stop surface **11a** after extending is reduced.

[0120] It can be understood that, referring to FIG. 4, the guide protrusions **122** extend along the moving direction of the press plate assembly **11**.

[0121] For the projections perpendicular to the moving direction of the press plate assembly **11**, the projections of the guide protrusions **122** are within the projections of the guide holes **11b**.

[0122] It can be understood that the relative position between the press plate assembly **11** and the mounting seat assembly **12** facilitates separation of the press plate assembly **11** and the mounting seat assembly **12** when the stop element **121** is in the retracted state.

[0123] In some embodiments, referring to FIGS. 2, 4, and 5, for the projections perpendicular to the vertical direction, in the locked state, a projection of the stop element **121** and a projection of the stop surface **11a** at least partially overlap; and in the unlocked state, the projection of the stop element **121** is separated from the projection of the stop surface **11a**, such that the press plate assembly **11** is separated from the mounting seat assembly **12** under action of gravity.

[0124] The vertical direction is a positive or negative direction along gravity.

[0125] In the locked state, one of the stop element **121** and the stop surface **11a** is located below the other, such that under action of gravity, parts with the projections overlapping of the stop element **121** and the stop surface **11a** can abut against each other along the vertical direction. In the unlocked state, the projection of the stop element **121** is separated from the projection of the stop surface **11a**, that is, the press plate assembly **11** and the mounting seat assembly **12** are not constrained along the vertical direction and can move relatively, such that one of the press plate assembly **11** and the mounting seat assembly **12** can fall off and be separated from the other under action of gravity.

[0126] In this way, the self-gravity of the press plate assembly **11** and the mounting seat assembly **12** is used, on the one hand, in the locked state, the stop element **121** is kept to abut against the stop surface **11a**, thereby reducing the probability of accidents caused by the separation between the stop element **121** and the stop surface **11a** in the working process. On the other hand, in the unlocked state, the press plate assembly **11** is directly separated from the mounting seat assembly **12** under action of gravity without additional action force, thereby improving the convenience of separation.

[0127] In some embodiments, the moving direction of the press plate assembly **11** is the vertical direction, such that the press plate assembly **11** presses against the battery **50** by means of own gravity, thereby improving the attachment effect between the poles and the busbar components.

[0128] In some embodiments, referring to FIG. 2, the press plate assembly **11** is located below the mounting seat assembly **12**, such that the press plate assembly **11** that needs to be replaced can directly fall off and be separated from the mounting seat assembly **12** under action of gravity in the unlocked state.

[0129] In some embodiments, an extendable and retractable direction of the stop element **121** is perpendicular to the vertical direction.

[0130] In some embodiments, referring to FIGS. 2 to 4, one of the mounting seat assembly **12** and the press plate assembly **11** includes locking structures **123**, and the other is provided with fixing holes **11c**, where one end of the fixing hole **11c** is open for the locking structure **123** to be inserted into the fixing hole **11c**, and of a circumferential surface of a part of the locking structure **123**

inserted into the fixing hole **11c** and a circumferential inner wall of the fixing hole **11c**, one is provided with the stop element **121** and the other is provided with the stop surface **11a**.

[0131] The fixing hole **11c** is configured to cooperate with the locking structure **123**, so as to realize the stop fit between the stop element **121** and the stop surface **11a**.

[0132] On the one hand, due to the constraint between the surface of the locking structure **123** and the inner wall of the fixing hole **11c**, the stop element **121** can conveniently reach the position to realize stop fit with the stop surface **11a**, and the probability that the mounting seat assembly **12** cannot be fixed with the press plate assembly **11** since the stop element **121** does not abut against the stop surface **11a** after extending is reduced. On the other hand, the surface of the locking structure **123** and the inner wall of the fixing hole **11c** can share the load between the stop element **121** and the stop surface **11a**, such that the probability of damage of a driving structure for driving the stop element **121** to extend and retract due to excessive load is reduced.

[0133] The fixing hole **11c** may be a through hole or a blind hole.

[0134] In some embodiments, referring to FIGS. **2** to **4**, the mounting seat assembly **12** includes the locking structures **123** and an adapter member **124**, the locking structures **123** are arranged at a side of the adapter member **124** facing towards the press plate assembly **11**, at least part of the locking structures **123** protrudes from a surface of the adapter member **124** at the side facing towards the press plate assembly **11**, and stop elements **121** are located at protruding parts of the locking structures **123**.

[0135] The adapter member **124** is configured to provide an installation position for the installation of the locking structures **123**.

[0136] The stop elements **121** are located on the locking structures **123**, that is, the locking structures **123** are provided with driving mechanisms for at least partially driving the stop elements **121** to extend and retract.

[0137] The locking structures **123** protrude from a side of the adapter member **124** facing towards the press plate assembly **11**. In this way, on the one hand, the adapter member **124** can abut against the press plate assembly **11** along the moving direction of the press plate assembly **11**, thereby constraining the relative position between the press plate assembly **11** and the mounting seat assembly **12** along the moving direction of the press plate assembly **11**, playing a limiting role, and reducing the probability that the locking structures **123** cannot extend and retract due to collision along the moving direction of the press plate assembly **11**. On the other hand, the stop elements **121** are exposed on the locking structures **123**, such that an extendable and retractable state of the stop elements **121** is convenient to observe, which is conducive to directly judging whether the function of driving the stop elements **121** to extend and retract by the locking structures **123** operates normally.

[0138] It can be understood that for the projections perpendicular to the moving direction of the press plate assembly **11**, a projection of the adapter member **124** and a projection of the press plate assembly **11** at least partially overlap, such that the adapter member **124** and the press plate assembly **11** can abut against each other along the moving direction of the press plate assembly **11**.

[0139] A specific way for the mounting seat assembly **12** to drive the press plate assembly **11** to move is not limited.

[0140] Exemplarily, referring to FIGS. **1** to **3**, the mounting seat assembly **12** includes a mounting piece **125** and a driving piece **126**, the driving piece **126** is arranged on the mounting piece **125**, and a driving end of the driving piece **126** is drivably connected to the adapter member **124** to drive the adapter member **124** to extend and retract. The driving end of the driving piece **126** can extend and retract relative to the mounting piece **125**, thereby driving the adapter member **124** and the locking structures **123** to move. Therefore, on the one hand, in the unlocked state, the driving piece **126** realizes the purpose of driving the locking structures **123** to be inserted into or pulled out from the fixing holes **11c**. On the other hand, in the locked state, the press plate assembly **11** is driven to move by the driving piece **126**, so as to realize the purpose of pressing or separating the press plate

assembly **11** from the battery **50**. The specific type of the driving piece **126** is not limited, such as an air cylinder and an electric cylinder. It can be understood that in the embodiment where the driving piece **126** is an air cylinder, a piston rod of the cylinder is connected to the adapter member **124**, and the piston rod need to be controlled to extend and retract by a first solenoid valve.

[0141] In some embodiments, referring to FIGS. **1** to **3**, the mounting piece **125** is a plate-like structure extending along the vertical direction, and the adapter member **124** includes a vertical portion and a horizontal portion, where the vertical portion extends along the vertical direction, the horizontal portion extends perpendicular to the vertical direction, and the driving end of the driving piece **126** is drivably connected to the vertical portion; and one of the mounting piece **125** and the vertical portion is provided with a sliding block and the other is provided with a guide rail, the guide rail extends along the vertical direction, the sliding block and the guide rail are in sliding fit, and the locking structures **123** are arranged on the horizontal portion. Through the fit between the sliding block and the guide rail, the resistance when the driving piece **126** drives the adapter member **124** to move is reduced.

[0142] In some embodiments, referring to FIGS. **4** and **6**, the mounting seat assembly **12** includes guide protrusions **122**, and the press plate assembly **11** is provided with guide holes **11b**, where the guide hole **11b** is open at a side facing towards the mounting seat assembly **12**, the guide protrusion **122** and the locking structure **123** are located on a same side of the adapter member **124**, the guide protrusion **122** is able to be inserted into the guide hole **11b** along an insertion direction of the locking structure **123** into the fixing hole **11c**, the locking structure **123** protrudes from the surface of the adapter member **124** at the side facing towards the press plate assembly **11** by a height of $H1$, and the guide protrusion **122** protrudes from the surface of the adapter member **124** at the side facing towards the press plate assembly **11** by a height of $H2$, where $H1 \leq H2$.

[0143] The height of the locking structure **123** protruding from the surface of the adapter member **124** at the side facing towards the press plate assembly **11** refers to a distance between an end surface of the locking structure **123** at an end facing away from the adapter member **124** and the surface of the adapter member **124** at the side facing towards the press plate assembly **11**.

[0144] The way to measure the specific value of $H1$ is not limited. For example, the vernier caliper is configured to respectively abut against the end surface of the locking structure **123** at the end facing away from the adapter member **124** and the surface of the adapter member **124** at the side facing towards the press plate assembly **11** so as to read the distance value therebetween.

[0145] The height of the guide protrusion **122** protruding from the surface of the adapter member **124** at the side facing towards the press plate assembly **11** refers to a distance between an end surface of the guide protrusion **122** at an end facing away from the adapter member **124** and the surface of the adapter member **124** at the side facing towards the press plate assembly **11**.

[0146] The way to measure the specific value of $H2$ is not limited. For example, the vernier caliper is configured to respectively abut against the end surface of the guide protrusion **122** at the end facing away from the adapter member **124** and the surface of the adapter member **124** at the side facing towards the press plate assembly **11** so as to read the distance value therebetween.

[0147] In this way, the guide protrusion **122** is inserted into the guide hole **11c** before the locking structure **123** is inserted into the fixing hole **11c**, and the guide protrusion **122** is first matched with the guide hole **11b** to realize the positioning between the mounting seat assembly **12** and the press plate assembly **11**, so as to reduce the probability that the locking structure **123** is damaged on impact due to the dislocation between the locking structure **123** and the fixing hole **11c**, and meanwhile, be conducive to improving the positioning accuracy of assembling and disassembling the press plate assembly **11**.

[0148] The locking structure **123** is not specifically limited.

[0149] Exemplarily, referring to FIG. **5**, the locking structure **123** is a pneumatic steel ball locking clamp, and steel balls **1231** of the pneumatic steel ball locking clamp form the stop element **121**. In this way, by controlling pressure of gas conveyed to the pneumatic steel ball locking clamp, the

steel balls **1231** can be driven to extend and retract, thereby facilitating the automatic control over the extendable and retractable movement of the stop element **121**.

[0150] The pneumatic steel ball locking clamp is a standard product, and its general structure and working principle are described as follows:

[0151] The pneumatic steel ball locking clamp includes steel balls **1231**, a piston rod **1232**, an elastic piece **1233** and a housing **1234**. The housing **1234** is provided with an accommodating cavity **1234b**, the piston rod **1232** penetrates into the accommodating cavity **1234b** and divides the accommodating cavity **1234b** into a rod sub-cavity and a rodless sub-cavity, the elastic piece **1233** is located in the rod sub-cavity and connects the piston rod **1232** to an inner wall of the rod sub-cavity so as to drive the piston rod **1232** to extend and retract, the housing **1234** is provided with an air inlet hole **1234a**, the air inlet hole **1234a** is communicated with the rodless sub-cavity to be configured to input compressed air into the rodless sub-cavity, the housing **1234** is provided with a mounting hole communicated with the rodless sub-cavity, the steel balls **1231** are arranged in the mounting hole, and a circumferential surface of the piston rod **1232** is provided with an accommodation slot **1232a**.

[0152] In the extended state, the input of compressed air into the rodless sub-cavity through the air inlet hole **1234a** is stopped, and the piston rod **1232** retracts under action of the elastic piece **1233**, such that an outer surface of the piston rod **1232** abuts against the steel balls **1231** and pushes the steel balls **1231** to move outwards to abut against the stop surface **11a**, and the steel balls **1231** are clamped and fixed by the stop surface **11a** and the outer surface of the piston rod **1232**, thereby keeping the steel balls **1231** to abut against the stop surface **11a**. In the retracted state, compressed air is input into the rodless sub-cavity through the air inlet hole **1234a**, and the compressed air pushes the piston rod **1232** to press the elastic piece **1233** so as to make the piston rod **1232** extend out until the steel balls **1231** are pushed back into the accommodation slot **1232a** under the abutting force of the stop surface **11a**, such that the steel balls **1231** can be embedded into the accommodation slot **1232a**.

[0153] It can be understood that the air inlet hole **1234a** can be selectively connected or disconnected to an air source via an air pipeline through a second solenoid valve. The air source may be an air compressor or a compressed air tank.

[0154] The specific way to form the stop surface **11a** is not limited.

[0155] Exemplarily, referring to FIG. 5, the inner wall of the fixing hole **11c** is provided with a fixing protrusion **111**, and a surface of the fixing protrusion **111** at a side facing away from the mounting seat assembly **12** forms the stop surface **11a**. In this way, the stop element **121** can conveniently abut against the fixing protrusion **111** in the extended state and be separated from the fixing protrusion **111** in the retracted state.

[0156] In some embodiments, referring to FIGS. 5 and 6, the press plate assembly **11** includes a press plate body **112** and fixing shaft sleeves **113**, where the press plate body **112** is provided with first mounting holes **112a**, at least one end of the first mounting hole **112a** is open, and the fixing shaft sleeve **113** is provided with a through second mounting hole **113a**; the fixing shaft sleeve **113** covers the opening of the first mounting hole **112a** and is detachably connected to the press plate body **112**; the first mounting hole **112a** communicates with the second mounting hole **113a** to form the fixing hole **11c**; and the fixing protrusion **111** is arranged on an inner wall of the second mounting hole **113a**.

[0157] In this way, there is no need to directly process and manufacture the fixing protrusion **111** on the press plate body **112**, thereby reducing the production and manufacturing difficulty. After long-term use, the fixing protrusion **111** is worn, only the fixing shaft sleeve **113** needs to be replaced, and the whole press plate assembly **11** does not need to be disassembled and maintained, such that the maintenance efficiency is improved, and the workload and maintenance cost are reduced.

[0158] In some embodiments, referring to FIG. 6, the press plate assembly **11** is provided with

relief holes **11d** configured to accommodate the poles of the battery **50** when the press plate assembly **11** presses against the battery **50**, so as to reduce the adverse impact on the battery **50** by the action force exerted by the press plate assembly **11** on the battery **50**.

[0159] Referring to FIGS. **1** to **6**, the press plate module **10** in an embodiment of this disclosure is described in detail as follows:

[0160] The press plate module **10** includes the press plate assembly **11** and the mounting seat assembly **12**, the press plate assembly **11** is located below the mounting seat assembly **12**, and the mounting seat assembly **12** includes the locking structures **123**, the adapter member **124**, the mounting piece **125**, the driving piece **126** and the guide protrusions **122**. The driving piece **126** is arranged on the mounting piece **125**, and the driving end of the driving piece **126** is drivably connected to the adapter member **124** to drive the adapter member **124** to extend and retract. The locking structure **123** is arranged at the side of the adapter member **124** facing towards the press plate assembly **11**, and is the pneumatic steel ball locking clamp. The steel balls **1231** in the pneumatic steel ball locking clamp can extend and retract. The press plate assembly **11** includes the press plate body **112** and the fixing shaft sleeves **113**, where the press plate body **112** is provided with first mounting holes **112a**, at least one end of the first mounting hole **112a** is open, and the fixing shaft sleeve **113** is provided with a through second mounting hole **113a**; the fixing shaft sleeve **113** covers the opening of the first mounting hole **112a** and is detachably connected to the press plate body **112**; the first mounting hole **112a** communicates with the second mounting hole **113a** to form the fixing hole **11c**; the fixing protrusion **111** is arranged on the inner wall of the second mounting hole **113a**; and the stop surface **11a** is formed on the surface of the fixing protrusion **111** at the side facing away from the mounting seat assembly **12**. The press plate module **10** includes the locked state and the unlocked state. In the locked state, the steel balls **1231** are in the extended state and abut against the stop surface **11a**, such that the press plate assembly **11** is fixed with the mounting seat assembly **12**, and the mounting seat assembly **12** can drive the press plate assembly **11** to move, such that the press plate assembly **11** presses against or is separated from the battery **50**. In the unlocked state, the steel balls **1231** are in the retracted state and separated from the stop surface **11a**, such that the press plate assembly **11** is separated from the mounting seat assembly **12**. The press plate assembly **11** is provided with the guide holes **11b**, where the guide hole **11b** is open at a side facing towards the mounting seat assembly **12**, and the guide protrusion **122** and the locking structure **123** are located on a same side of the adapter member **124**, and the guide protrusion **122** is able to be inserted into the guide hole **11b** along the insertion direction of the locking structure **123** into the fixing hole **11c**, and the locking structure **123** protrudes from the surface of the adapter member **124** at the side facing towards the press plate assembly **11** by a height of $H1$, and the guide protrusion **122** protrudes from the surface of the adapter member **124** at the side facing towards the press plate assembly **11** by a height of $H2$, where $H1 \leq H2$.

[0161] An embodiment of this disclosure further provides a production line, referring to FIG. **7**, configured for assembly operations of a battery **50**. The production line includes the press plate module **10** according to the foregoing embodiments, and the press plate module **10** is configured to selectively press against the battery **50**, such that attachment between busbar components and poles of cells of the battery **50** is facilitated, thereby facilitating welding.

[0162] In this way, the press plate module **10** switches between a locked state and an unlocked state, such that the efficiency of replacing the press plate assembly **11** is improved in the switching process of producing different types of batteries **50** on a production line.

[0163] In some embodiments, referring to FIGS. **7** and **8**, the production line includes a driving module **20**, and a driving end of the driving module **20** is drivably connected to the mounting seat assembly **12** to drive the press plate module **10** to move between a working station and a replacement station.

[0164] The working station means that when the press plate module **10** is located at this position,

the press plate module **10** is only in the locked state, and the mounting seat assembly **12** drives the press plate assembly **11** to move, such that the press plate assembly **11** presses against or is separated from the battery **50**.

[0165] The replacement station means that when the press plate module **10** is located at this position, the press plate module **10** may be between the locked state and the unlocked state, such that the press plate module **10** can replace different types of press plate assemblies **11**.

[0166] In this way, the driving module **20** drives the press plate module **10** to move between the working station and the replacement station, so as to avoid interference with assembly of the battery **50** in the process of replacing the press plate assembly **11**.

[0167] The specific type of the driving module **20** is not limited.

[0168] Exemplarily, the driving module **20** includes a first mounting frame, a first driving motor and a first driving rack. The first driving rack is arranged at a top of the first mounting frame. The mounting seat assembly **12** is fixedly connected to the first driving rack. An output end of the first driving motor is provided with a first driving gear. The top of the first mounting frame is provided with a first bearing guide rail extending along a first direction. The mounting seat assembly **12** is provided with a first bearing sliding block. The first bearing sliding block is in sliding fit with the first bearing guide rail. The first driving gear meshes with the first driving rack to drive the first driving rack to move along the first direction, so as to drive the mounting seat assembly **12** to move along the first direction. By controlling the number of rotation turns of the output end of the first driving motor, the specific position of the mounting seat assembly **12** on the first bearing guide rail along the first direction is controlled, so as to realize the movement of the press plate module **10** between the working station and the replacement station.

[0169] It can be understood that there are a plurality of different types of press plate assemblies **11** on the production line, and one of different types of press plate assemblies **11** needs to selectively be fixed with the mounting seat assembly **12** according to actual needs.

[0170] In some embodiments, referring to FIGS. 7 to 10, the production line includes a temporary storage module **30**. The temporary storage module **30** includes a plurality of trays **31** and a driving assembly **32**. The trays **31** are configured for placing the press plate assemblies **11**, and the driving assembly **32** is drivably connected to each of the trays **31** to drive each of the trays **31** to selectively move to a waiting station, enabling the tray **31** to receive a press plate assembly **11** separated from the mounting seat assembly **12**, or enabling a press plate assembly **11** placed on the tray **31** to be fixed with the mounting seat assembly **12**.

[0171] The trays **31** are configured to place different types of press plate assemblies **11**. One tray **31** may bear only one press plate assembly **11** or a plurality of press plate assemblies **11**.

[0172] Referring to FIG. 9, the driving assembly **32** is configured to drive the trays **31** to move, so as to move the press plate assembly **11** that needs to be replaced to the waiting station, or to move an empty tray **31** to the waiting station.

[0173] The waiting station refers to waiting for the press plate module **10** to reach the replacement station after the tray **31** moves to this position, such that the separated press plate assembly **11** can be placed on the empty tray **31**, or the mounting seat assembly **12** can be locked with the press plate assembly **11** on the tray **31**.

[0174] In this way, the driving assembly **32** is conducive to realizing the automatic control of moving the press plate assembly **11** that needs to be replaced to the waiting station and cooperating with the press plate module **10**.

[0175] The specific form of the driving assembly **32** is not limited. The driving assembly includes a second mounting frame, a second driving motor and a second driving rack. The second driving rack is arranged at a top of the second mounting frame. The tray **31** is fixedly connected to the second driving rack. An output end of the second driving motor is provided with a second driving gear. The top of the second mounting frame is provided with a second bearing guide rail extending along a second direction. The tray **31** is provided with a second bearing sliding block. The second bearing

sliding block is in sliding fit with the second bearing guide rail, and the second driving gear meshes with the second driving rack to drive the second driving rack to move along the second direction, so as to drive the tray **31** to move along the second direction. By controlling the number of rotation turns of the output end of the second driving motor, the specific position of the tray **31** on the second bearing guide rail along the second direction is controlled, so as to realize the purpose that the tray **31** reaches the waiting station.

[0176] In some embodiments, referring to FIG. 7, the first direction is orthogonal to the second direction to reduce the total floor space of the production line.

[0177] In some embodiments, referring to FIG. 7, the mounting seat assembly **12** is able to drive the press plate assembly **11** to move along the vertical direction. Under a condition that the press plate module **10** is located in the replacement station and one of the trays **31** is located in the waiting station, the tray **31** is located below the mounting seat assembly **12**. In this way, after the press plate module **10** switches from the locked state to the unlocked state, the press plate assembly **11** can directly fall onto the tray **31** under action of gravity.

[0178] In some embodiments, referring to FIG. 10, the tray **31** includes a tray body **311** and fixing bosses **312**. The fixing bosses **312** are located at one end of the tray body **311** facing towards the press plate assembly **11**, and the fixing bosses **312** are configured to be inserted into the guide holes **11b**, such that the press plate assembly **11** placed on the tray **31** is constrained in position by the fit of the fixing bosses **312** and the guide holes **11b**, and the probability that the press plate assembly **11** falls off the tray **31** during the movement with the tray **31** is reduced.

[0179] In some embodiments, the fixing protrusions **111** are located at the top end of the tray body **311**.

[0180] In some embodiments, the production line includes a conveying module **40**, and the conveying module **40** is configured to convey the battery **50** to a laminating station.

[0181] The laminating station means that after the battery **50** reaches this position, the press plate module **10** located at the working station drives the press plate assembly **11** to press against the battery **50**.

[0182] In this way, batteries **50** to be processed can be continuously conveyed to the laminating station and the processed batteries **50** are moved out of the laminating station.

[0183] Referring to FIGS. 7 to 10, the production line in an embodiment of this disclosure is described in detail as follows:

[0184] The production line includes the press plate module **10**, the driving module **20**, and the temporary storage module **30**, where [0185] the driving end of the driving module **20** is drivably connected to the mounting seat assembly **12** to drive the press plate module **10** to move between the working station and the replacement station.

[0186] The temporary storage module **30** includes the plurality of trays **31** and the driving assembly **32**, the trays **31** are configured for placing the press plate assemblies **11**, and the driving assembly **32** is drivably connected to each of the trays **31** to drive each of the trays **31** to selectively move to the waiting station, enabling the tray **31** to receive a press plate assembly **11** separated from the mounting seat assembly **12**. Alternatively, the press plate assembly **11** placed on the tray **31** can be fixed with the mounting seat assembly **12**, and under the condition that the press plate module **10** is located in the replacement station and one of the trays **31** is located in the waiting station, the tray **31** is located below the mounting seat assembly **12**.

[0187] An embodiment of this disclosure provides a control method for replacing a press plate assembly **11** on a production line. The control method is applied to a control device. For example, the control device may be a Programmable Logic Controller (PLC) device. As shown in FIG. 11, in an embodiment in which a first driving motor, a second driving motor, a first solenoid valve and a second solenoid valve are included, a driving piece **126** is an air cylinder, and steel balls **1231** in a pneumatic steel ball locking clamp forms a stop element **121**, the method includes: [0188] Step **S01**: Control a first driving motor in a driving module to drive a press plate module to move from a

working station to a replacement station. [0189] Step **S02**: Control a second driving motor in a driving assembly to drive an empty tray to move to a waiting station. [0190] It can be understood that Step **S01** and Step **S02** may be completed successively or simultaneously. [0191] Step **S03**: Control a first solenoid valve such that a cylinder in a mounting seat assembly drives a press plate assembly to move downwards to a lowest position. [0192] Step **S04**: Control a second solenoid valve to retract steel balls in a pneumatic steel ball locking clamp, thereby changing the press plate module from a locked state to an unlocked state, and dropping the press plate assembly onto the tray at the waiting station. [0193] Step **S05**: Control the first solenoid valve such that the cylinder in the mounting seat assembly drives an adapter member to move upwards to a highest position. [0194] Step **S06**: Control the second driving motor in the driving assembly to drive the tray currently located at the waiting station to move away from the waiting station. [0195] Step **S07**: Control the second driving motor in the driving assembly to drive the tray, on which the press plate assembly to be replaced is placed, to move to the waiting station. [0196] Step **S08**: Control the first solenoid valve such that the cylinder in the mounting seat assembly drives the adapter member to move downwards to the lowest position. [0197] Step **S09**: Control the second solenoid valve such that the steel balls in the pneumatic steel ball locking clamp extend out, thereby changing the press plate module from the unlocked state to the locked state. [0198] Step **S10**: Control the first solenoid valve such that the cylinder in the mounting seat assembly drives the press plate assembly to move upwards to the highest position. [0199] Step **S11**: Control the first driving motor in the driving module to drive the press plate module to move from the replacement station to the working station.

[0200] In this way, rapid and automatic replacement of the press plate assembly **11** is realized conveniently, and the working efficiency of replacing the press plate assembly **11** is improved.

[0201] Various embodiments/implementations provided in this disclosure may be combined with each other without contradiction.

[0202] The above embodiments are only preferred embodiments of this disclosure, but are not intended to limit this disclosure. For a person skilled in the art, this disclosure may have various modifications and variations. Any modification, equivalent replacement, improvement, and the like made within the spirit and principles of this disclosure shall fall within the scope of protection of this disclosure.

INDUSTRIAL PRACTICALITY

[0203] The embodiments of this disclosure are conducive to realizing rapid and automatic replacement of the press plate assembly, and the working efficiency of replacing the press plate assembly is improved.

Claims

1. A press plate module for battery assembly operations, wherein the press plate module comprises a press plate assembly and a mounting seat assembly, wherein one of the mounting seat assembly and the press plate assembly is provided with a stop element and the other is provided with a stop surface, and the stop element is selectively extendable and retractable; the press plate module has a locked state and an unlocked state; in the locked state, the stop element is in an extended state and abuts against the stop surface, such that the press plate assembly is fixed with the mounting seat assembly, and the mounting seat assembly is able to drive the press plate assembly to move such that the press plate assembly presses against or is separated from a battery; and in the unlocked state, the stop element is in a retracted state and separated from the stop surface, such that the press plate assembly is separated from the mounting seat assembly.
2. The press plate module according to claim 1, wherein the stop element is arranged on the mounting seat assembly, and the stop surface is arranged on the press plate assembly.
3. The press plate module according to claim 1, wherein one of the mounting seat assembly and the

press plate assembly is provided with a guide protrusion and the other is provided with a guide hole, and the guide protrusion is able to be inserted into or detached from the guide hole along a moving direction of the press plate assembly.

4. The press plate module according to claim 1, wherein for projections perpendicular to a vertical direction, in the locked state, a projection of the stop element and a projection of the stop surface at least partially overlap; and in the unlocked state, the projection of the stop element is separated from the projection of the stop surface, such that the press plate assembly is separated from the mounting seat assembly under action of gravity.

5. The press plate module according to claim 1, wherein one of the mounting seat assembly and the press plate assembly comprises a locking structure and the other is provided with a fixing hole, wherein one end of the fixing hole is open for the locking structure to be inserted into the fixing hole, and of a circumferential surface of a part of the locking structure inserted into the fixing hole and a circumferential inner wall of the fixing hole, one is provided with the stop element and the other is provided with the stop surface.

6. The press plate module according to claim 5, wherein the mounting seat assembly comprises the locking structure and an adapter member, the locking structure is arranged at a side of the adapter member facing towards the press plate assembly, at least part of the locking structure protrudes from a surface of the adapter member at the side facing towards the press plate assembly, and the stop element is located at a protruding part of the locking structure.

7. The press plate module according to claim 6, wherein the mounting seat assembly comprises a mounting piece and a driving piece, the driving piece is arranged on the mounting piece, and a driving end of the driving piece is drivably connected to the adapter member to drive the adapter member to extend and retract.

8. The press plate module according to claim 6, wherein the mounting seat assembly comprises a guide protrusion, and the press plate assembly is provided with a guide hole, wherein the guide hole is open at a side facing towards the mounting seat assembly, the guide protrusion and the locking structure are located on a same side of the adapter member, the guide protrusion is able to be inserted into the guide hole along an insertion direction of the locking structure into the fixing hole, the locking structure protrudes from the surface of the adapter member at the side facing towards the press plate assembly by a height of $H1$, and the guide protrusion protrudes from the surface of the adapter member at the side facing towards the press plate assembly by a height of $H2$, wherein $H1 \leq H2$.

9. The press plate module according to claim 5, wherein the locking structure is a pneumatic steel ball locking clamp, and steel balls of the pneumatic steel ball locking clamp form the stop element.

10. The press plate module according to claim 5, wherein the inner wall of the fixing hole is provided with a fixing protrusion, and a surface of the fixing protrusion at a side facing away from the mounting seat assembly forms the stop surface.

11. The press plate module according to claim 10, wherein the press plate assembly comprises a press plate body and a fixing shaft sleeve, wherein the press plate body is provided with a first mounting hole, at least one end of the first mounting hole is open, and the fixing shaft sleeve is provided with a through second mounting hole; the fixing shaft sleeve covers an opening of the first mounting hole and is detachably connected to the press plate body; the first mounting hole communicates with the second mounting hole to form the fixing hole; and the fixing protrusion is arranged on an inner wall of the second mounting hole.

12. A production line for battery assembly operations, wherein the production line comprises the press plate module according to any one of claims 1 to 11, and the press plate module is configured to selectively press against a battery.

13. The production line according to claim 12, wherein the production line comprises a driving module, and a driving end of the driving module is drivably connected to the mounting seat assembly to drive the press plate module to move between a working station and a replacement

station.

14. The production line according to claim 13, wherein the production line comprises a temporary storage module, and the temporary storage module comprises a plurality of trays and a driving assembly, wherein the trays are configured for placing the press plate assemblies, and the driving assembly is drivably connected to each of the trays so as to selectively move one of the trays to a waiting station, enabling the tray to receive a press plate assembly separated from the mounting seat assembly, or enabling a press plate assembly placed on the tray to be fixed with the mounting seat assembly.

15. The production line according to claim 14, wherein the mounting seat assembly is able to drive the press plate assembly to move along a vertical direction, and under a condition that the press plate module is located in the replacement station and one of the trays is located in the waiting station, the tray is located below the mounting seat assembly.

16. A control method for replacing a press plate assembly, wherein the control method comprises: controlling a first driving motor in a driving module to drive a press plate module to move from a working station to a replacement station; controlling a second driving motor in a driving assembly to drive an empty tray to move to a waiting station; controlling a first solenoid valve such that a cylinder in a mounting seat assembly drives a press plate assembly to move downwards to a lowest position; controlling a second solenoid valve to retract steel balls in a pneumatic steel ball locking clamp, thereby changing the press plate module from a locked state to an unlocked state, and dropping the press plate assembly onto the tray at the waiting station; controlling the first solenoid valve such that the cylinder in the mounting seat assembly drives an adapter member to move upwards to a highest position; controlling the second driving motor in the driving assembly to drive the tray currently located at the waiting station to move away from the waiting station; controlling the second driving motor in the driving assembly to drive the tray, on which the press plate assembly to be replaced is placed, to move to the waiting station; controlling the first solenoid valve such that the cylinder in the mounting seat assembly drives the adapter member to move downwards to the lowest position; controlling the second solenoid valve such that the steel balls in the pneumatic steel ball locking clamp extend out, thereby changing the press plate module from the unlocked state to the locked state; controlling the first solenoid valve such that the cylinder in the mounting seat assembly drives the press plate assembly to move upwards to the highest position; and controlling the first driving motor in the driving module to drive the press plate module to move from the replacement station to the working station.
