

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396820
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Hartley; Amanda et al.

Heat exchange and temperature sensing device and method of use

Abstract

A method and apparatus are disclosed for regulating a temperature of an esophagus when heat or cold is delivered to a left atrium, the method including altering a heat exchange device from an insertable configuration to a heat exchanging configuration which conforms and corresponds with a cross-section of an inside of the esophagus such that the esophagus is maintained in its natural shape and location. In some embodiments the heat exchange device has a heating/cooling balloon which is inflated to be in the heat exchanging configuration. Some alternative embodiments includes altering the configuration of the balloon to conform to or correspond with the cross section of an esophagus by means other than inflation.

Inventors:	Hartley; Amanda (Caledon, CA), Davies; Gareth (Toronto, CA), Centazzo-Colella; Amanda (Toronto, CA), Yang; Noah (Ottawa, CA), Al-Saffar; Yasir (Oakville, CA), Shah; Kishan (Etobicoke, CA), Herbert-Copley; Andrew (Toronto, CA), Wierzbicki; Ramunas (Toronto, CA), Gerber; Dmitry (Toronto, CA), Mok; Daniel Wing Fai (Mississauga, CA), Dell; Trevor James (Etobicoke, CA), Avari; Hamed (Oakville, CA)
Applicant:	Boston Scientific Medical Device Limited (Ballybrit, IE)
Family ID:	1000008782616
Assignee:	Boston Scientific Medical Device Limited (Galway, IE)
Appl. No.:	17/266663
Filed (or PCT Filed):	February 13, 2019
PCT No.:	PCT/IB2019/051168
PCT Pub. No.:	WO2020/030985
PCT Pub. Date:	February 13, 2020

Prior Publication Data

Document Identifier

US 20210298862 A1

Publication Date

Sep. 30, 2021

Foreign Application Priority Data

WO

PCT/IB2018/056059

Aug. 10, 2018

Related U.S. Application Data

continuation-in-part parent-doc WO PCT/IB2018/056059 20180810 PENDING child-doc US 17266663

us-provisional-application US 62543635 20170810

Publication Classification

Int. Cl.: **A61B5/01** (20060101); **A61B5/00** (20060101); **A61B18/02** (20060101); **A61B18/04** (20060101); **A61B90/00** (20160101); **A61F7/00** (20060101); **A61F7/12** (20060101); **A61B5/287** (20210101); **A61B17/00** (20060101); **A61B18/00** (20060101); **A61F7/10** (20060101); **A61M25/10** (20130101); **A61N1/05** (20060101); **A61N1/362** (20060101)

U.S. Cl.:

CPC **A61B90/04** (20160201); **A61B5/01** (20130101); **A61B5/6853** (20130101); **A61B18/02** (20130101); **A61B18/04** (20130101); **A61F7/0085** (20130101); **A61F7/12** (20130101); **A61F7/123** (20130101); **A61B5/287** (20210101); **A61B2017/00557** (20130101); **A61B2018/00023** (20130101); **A61B2018/00035** (20130101); **A61B2018/0022** (20130101); **A61B2018/00357** (20130101); **A61B2018/00488** (20130101); **A61B2018/00577** (20130101); **A61B2018/00791** (20130101); **A61B2018/00797** (20130101); **A61B2018/00839** (20130101); **A61B2018/0091** (20130101); **A61B2018/0212** (20130101); **A61B2090/0418** (20160201); **A61B2090/0463** (20160201); **A61B2090/061** (20160201); **A61B2090/374** (20160201); **A61B2090/3762** (20160201); **A61B2090/3966** (20160201); **A61B2090/3983** (20160201); **A61F2007/0054** (20130101); **A61F2007/0056** (20130101); **A61F2007/0075** (20130101); **A61F2007/0091** (20130101); **A61F2007/0096** (20130101); **A61F2007/101** (20130101); **A61F2007/126** (20130101); **A61M25/1002** (20130101); **A61M2025/1013** (20130101); **A61M2025/1043** (20130101); **A61M2025/1084** (20130101); **A61M2210/105** (20130101); **A61N1/0517** (20130101); **A61N1/362** (20130101)

Field of Classification Search

CPC: **A61B (90/04)**; **A61B (5/01)**; **A61B (5/6853)**; **A61B (5/287)**; **A61B (5/25)**; **A61B (5/28)**; **A61B (5/055)**; **A61B (5/4233)**; **A61B (18/02)**; **A61B (18/04)**; **A61B (18/1492)**; **A61B (2017/00557)**; **A61B (2018/00023)**; **A61B (2018/00035)**; **A61B (2018/0022)**; **A61B (2018/00357)**; **A61B (2018/00488)**; **A61B (2018/00577)**; **A61B (2018/00791)**; **A61B (2018/00797)**; **A61B (2018/00839)**; **A61B (2018/0091)**; **A61B (2018/0212)**; **A61B (2018/00005)**; **A61B (2018/00029)**; **A61B (2018/00285)**; **A61B (2018/00291)**; **A61B (2090/0418)**; **A61B (2090/0463)**; **A61B (2090/061)**; **A61B (2090/374)**; **A61B**

(2090/3762); A61B (2090/3966); A61B (2090/3983); A61B (2090/065); A61B (2034/2051); A61B (6/032); A61B (6/487); A61F (7/0085); A61F (7/12); A61F (7/123); A61F (2007/0054); A61F (2007/0056); A61F (2007/0075); A61F (2007/0091); A61F (2007/0096); A61F (2007/101); A61F (2007/126); A61F (2007/0059); A61F (2007/0086); A61M (25/1002); A61M (2025/1013); A61M (2025/1043); A61M (2025/1084); A61M (2210/105); A61N (1/0517); A61N (1/362)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
175254	12/1875	Oberly	N/A	N/A
827626	12/1905	Gillet	N/A	N/A
848711	12/1906	Daniel	N/A	N/A
1072954	12/1912	Junn	N/A	N/A
1279654	12/1917	Charlesworth	N/A	N/A
1918094	12/1932	Geekas	N/A	N/A
1996986	12/1934	Weinberg	N/A	N/A
2021989	12/1934	Matthew	N/A	N/A
2146636	12/1938	Lipchow	N/A	N/A
3429574	12/1968	Williams	N/A	N/A
3448739	12/1968	Stark et al.	N/A	N/A
3575415	12/1970	Fulp et al.	N/A	N/A
3595239	12/1970	Petersen	N/A	N/A
4129129	12/1977	Amrine	N/A	N/A
4244362	12/1980	Anderson	N/A	N/A
4401124	12/1982	Guess et al.	N/A	N/A
4639252	12/1986	Kelly et al.	N/A	N/A
4641649	12/1986	Walinsky et al.	N/A	N/A
4669467	12/1986	Willett et al.	N/A	N/A
4682596	12/1986	Bales et al.	N/A	N/A
4790311	12/1987	Ruiz	N/A	N/A
4790809	12/1987	Kuntz	N/A	N/A
4793350	12/1987	Mar et al.	N/A	N/A
4807620	12/1988	Strul et al.	N/A	N/A
4832048	12/1988	Cohen	N/A	N/A
4840622	12/1988	Hardy	N/A	N/A
4863441	12/1988	Lindsay et al.	N/A	N/A
4884567	12/1988	Elliott et al.	N/A	N/A
4892104	12/1989	Ito et al.	N/A	N/A
4896671	12/1989	Cunningham et al.	N/A	N/A
4928693	12/1989	Goodin et al.	N/A	N/A
4936281	12/1989	Stasz	N/A	N/A
4960410	12/1989	Pinchuk	N/A	N/A
4977897	12/1989	Hurwitz	N/A	N/A
4998933	12/1990	Eggers et al.	N/A	N/A
5006119	12/1990	Acker et al.	N/A	N/A
5019076	12/1990	Yamanashi et al.	N/A	N/A
5047026	12/1990	Rydell	N/A	N/A

5081997	12/1991	Bosley et al.	N/A	N/A
5098431	12/1991	Rydell	N/A	N/A
5112048	12/1991	Kienle	N/A	N/A
5154724	12/1991	Andrews	N/A	N/A
5196024	12/1992	Barath	N/A	N/A
5201756	12/1992	Horzewski et al.	N/A	N/A
5209741	12/1992	Spaeth	N/A	N/A
5211183	12/1992	Wilson	N/A	N/A
5221256	12/1992	Mahurkar	N/A	N/A
5230349	12/1992	Langberg	N/A	N/A
5281216	12/1993	Klicek	N/A	N/A
5300068	12/1993	Rosar et al.	N/A	N/A
5300069	12/1993	Hunsberger et al.	N/A	N/A
5314418	12/1993	Takano et al.	N/A	N/A
5318525	12/1993	West et al.	N/A	N/A
5327905	12/1993	Avitall	N/A	N/A
5364393	12/1993	Auth et al.	N/A	N/A
5372596	12/1993	Klicek et al.	N/A	N/A
5380304	12/1994	Parker	N/A	N/A
5397304	12/1994	Truckai	N/A	N/A
5403338	12/1994	Milo	N/A	N/A
5423809	12/1994	Klicek	N/A	N/A
5425382	12/1994	Golden et al.	N/A	N/A
5490859	12/1995	Mische et al.	N/A	N/A
5497774	12/1995	Swartz et al.	N/A	N/A
5501667	12/1995	Verduin, Jr.	N/A	N/A
5507751	12/1995	Goode et al.	N/A	N/A
5509411	12/1995	Littmann et al.	N/A	N/A
5540681	12/1995	Strul et al.	N/A	N/A
5545200	12/1995	West et al.	N/A	N/A
5555618	12/1995	Winkler	N/A	N/A
5571088	12/1995	Lennox et al.	N/A	N/A
5575766	12/1995	Swartz et al.	N/A	N/A
5575772	12/1995	Lennox	N/A	N/A
5599347	12/1996	Hart et al.	N/A	N/A
5605162	12/1996	Mirzaee et al.	N/A	N/A
5617878	12/1996	Taheri	N/A	N/A
5622169	12/1996	Golden et al.	N/A	N/A
5624430	12/1996	Eton et al.	N/A	N/A
5667488	12/1996	Lundquist et al.	N/A	N/A
5673695	12/1996	McGee et al.	N/A	N/A
5674208	12/1996	Berg et al.	N/A	N/A
5683366	12/1996	Eggers et al.	N/A	N/A
5720744	12/1997	Eggleston et al.	N/A	N/A
5741249	12/1997	Moss et al.	N/A	N/A
5766135	12/1997	Terwilliger	N/A	N/A
5779688	12/1997	Imran et al.	N/A	N/A
5810764	12/1997	Eggers et al.	N/A	N/A
5814028	12/1997	Swartz et al.	N/A	N/A
5830214	12/1997	Flom et al.	N/A	N/A

5836875	12/1997	Webster, Jr.	N/A	N/A
5849011	12/1997	Jones et al.	N/A	N/A
5851210	12/1997	Torossian	N/A	N/A
5885227	12/1998	Finlayson	N/A	N/A
5888201	12/1998	Stinson et al.	N/A	N/A
5893848	12/1998	Negus et al.	N/A	N/A
5893885	12/1998	Webster, Jr.	N/A	N/A
5904679	12/1998	Clayman	N/A	N/A
5916210	12/1998	Winston	N/A	N/A
5921957	12/1998	Killion et al.	N/A	N/A
5931818	12/1998	Werp et al.	N/A	N/A
5944023	12/1998	Johnson et al.	N/A	N/A
5951482	12/1998	Winston et al.	N/A	N/A
5957842	12/1998	Littmann et al.	N/A	N/A
5964757	12/1998	Ponzi	N/A	N/A
5967976	12/1998	Larsen et al.	N/A	N/A
5989276	12/1998	Houser et al.	N/A	N/A
6007555	12/1998	Devine	N/A	N/A
6009877	12/1999	Edwards	N/A	N/A
6013072	12/1999	Winston et al.	N/A	N/A
6017340	12/1999	Cassidy et al.	N/A	N/A
6018676	12/1999	Davis et al.	N/A	N/A
6030380	12/1999	Auth et al.	N/A	N/A
6032674	12/1999	Eggers et al.	N/A	N/A
6048349	12/1999	Winston et al.	N/A	N/A
6053870	12/1999	Fulton, III	N/A	N/A
6053904	12/1999	Scribner et al.	N/A	N/A
6056747	12/1999	Saadat et al.	N/A	N/A
6063093	12/1999	Winston et al.	N/A	N/A
6093185	12/1999	Ellis et al.	N/A	N/A
6106515	12/1999	Winston et al.	N/A	N/A
6106520	12/1999	Laufer et al.	N/A	N/A
6117131	12/1999	Taylor	N/A	N/A
6142992	12/1999	Cheng et al.	N/A	N/A
6146380	12/1999	Racz et al.	N/A	N/A
6155264	12/1999	Ressemann et al.	N/A	N/A
6156031	12/1999	Aita et al.	N/A	N/A
6171305	12/2000	Sherman	N/A	N/A
6179824	12/2000	Eggers et al.	N/A	N/A
6193676	12/2000	Winston et al.	N/A	N/A
6193715	12/2000	Wrublewski et al.	N/A	N/A
6210408	12/2000	Chandrasekaran et al.	N/A	N/A
6217575	12/2000	Devore et al.	N/A	N/A
6221061	12/2000	Engelson et al.	N/A	N/A
6228076	12/2000	Winston et al.	N/A	N/A
6245054	12/2000	Fuimaono et al.	N/A	N/A
6267758	12/2000	Daw et al.	N/A	N/A
6283983	12/2000	Makower et al.	N/A	N/A
6292678	12/2000	Hall et al.	N/A	N/A

6293945	12/2000	Parins et al.	N/A	N/A
6296615	12/2000	Brockway et al.	N/A	N/A
6296636	12/2000	Cheng et al.	N/A	N/A
6302898	12/2000	Edwards et al.	N/A	N/A
6304769	12/2000	Arenson et al.	N/A	N/A
6315777	12/2000	Comben	N/A	N/A
6328699	12/2000	Eigler et al.	N/A	N/A
6360128	12/2001	Kordis et al.	N/A	N/A
6364877	12/2001	Goble et al.	N/A	N/A
6385472	12/2001	Hall et al.	N/A	N/A
6394976	12/2001	Winston et al.	N/A	N/A
6395002	12/2001	Ellman et al.	N/A	N/A
6419674	12/2001	Bowser et al.	N/A	N/A
6428551	12/2001	Hall et al.	N/A	N/A
6450989	12/2001	Dubrul et al.	N/A	N/A
6475214	12/2001	Moaddeb	N/A	N/A
6485485	12/2001	Winston et al.	N/A	N/A
6508754	12/2002	Liprie et al.	N/A	N/A
6524303	12/2002	Garibaldi	N/A	N/A
6530923	12/2002	Dubrul et al.	N/A	N/A
6554827	12/2002	Chandrasekaran et al.	N/A	N/A
6562031	12/2002	Chandrasekaran et al.	N/A	N/A
6562049	12/2002	Norlander et al.	N/A	N/A
6565562	12/2002	Shah et al.	N/A	N/A
6592612	12/2002	Samson et al.	N/A	N/A
6607529	12/2002	Jones et al.	N/A	N/A
6632222	12/2002	Edwards et al.	N/A	N/A
6639999	12/2002	Cookingham et al.	N/A	N/A
6641603	12/2002	Walker et al.	N/A	N/A
6650923	12/2002	Lesh et al.	N/A	N/A
6651672	12/2002	Roth	N/A	N/A
6662034	12/2002	Segner et al.	N/A	N/A
6663621	12/2002	Winston et al.	N/A	N/A
6702811	12/2003	Stewart et al.	N/A	N/A
6709444	12/2003	Makower	N/A	N/A
6723052	12/2003	Mills	N/A	N/A
6733511	12/2003	Hall et al.	N/A	N/A
6740103	12/2003	Hall et al.	N/A	N/A
6752800	12/2003	Winston et al.	N/A	N/A
6755816	12/2003	Ritter et al.	N/A	N/A
6811544	12/2003	Schaer	N/A	N/A
6814733	12/2003	Schwartz et al.	N/A	N/A
6820614	12/2003	Bonutti	N/A	N/A
6834201	12/2003	Gillies et al.	N/A	N/A
6842639	12/2004	Winston et al.	N/A	N/A
6852109	12/2004	Winston et al.	N/A	N/A
6855143	12/2004	Davison et al.	N/A	N/A
6860856	12/2004	Ward et al.	N/A	N/A

6869431	12/2004	Maguire et al.	N/A	N/A
6911026	12/2004	Hall et al.	N/A	N/A
6944490	12/2004	Chow	N/A	N/A
6951554	12/2004	Johansen et al.	N/A	N/A
6951555	12/2004	Suresh et al.	N/A	N/A
6955675	12/2004	Jain	N/A	N/A
6970732	12/2004	Winston et al.	N/A	N/A
6980843	12/2004	Eng et al.	N/A	N/A
7029470	12/2005	Francischelli et al.	N/A	N/A
7056294	12/2005	Khairkhahan et al.	N/A	N/A
7083566	12/2005	Tornes et al.	N/A	N/A
7112197	12/2005	Hartley et al.	N/A	N/A
7335197	12/2007	Sage et al.	N/A	N/A
7618430	12/2008	Scheib	N/A	N/A
7651492	12/2009	Wham	N/A	N/A
7666203	12/2009	Chanduszko et al.	N/A	N/A
7678081	12/2009	Whiting et al.	N/A	N/A
7682360	12/2009	Guerra	N/A	N/A
7828796	12/2009	Wong et al.	N/A	N/A
7900928	12/2010	Held et al.	N/A	N/A
8192425	12/2011	Mirza et al.	N/A	N/A
8257323	12/2011	Joseph et al.	N/A	N/A
8388549	12/2012	Paul et al.	N/A	N/A
8500697	12/2012	Kurth et al.	N/A	N/A
9126035	12/2014	Valoir	N/A	N/A
10004550	12/2017	Ryba et al.	N/A	N/A
11339579	12/2021	Stearns	N/A	N/A
2001/0012934	12/2000	Chandrasekaran et al.	N/A	N/A
2001/0021867	12/2000	Kordis et al.	N/A	N/A
2002/0010460	12/2001	Joye	606/23	A61B 18/02
2002/0019644	12/2001	Hastings et al.	N/A	N/A
2002/0022781	12/2001	McLntire et al.	N/A	N/A
2002/0022836	12/2001	Goble et al.	N/A	N/A
2002/0035361	12/2001	Houser et al.	N/A	N/A
2002/0087153	12/2001	Roschak et al.	N/A	N/A
2002/0087156	12/2001	Maguire et al.	N/A	N/A
2002/0111618	12/2001	Stewart et al.	N/A	N/A
2002/0123749	12/2001	Jain	N/A	N/A
2002/0147485	12/2001	Mamo et al.	N/A	N/A
2002/0169377	12/2001	Khairkhahan et al.	N/A	N/A
2002/0188302	12/2001	Berg et al.	N/A	N/A
2002/0198521	12/2001	Maguire	N/A	N/A
2003/0032929	12/2002	McGuckin	N/A	N/A
2003/0040742	12/2002	Underwood et al.	N/A	N/A
2003/0040782	12/2002	Walker et al.	N/A	N/A
2003/0144658	12/2002	Schwartz et al.	N/A	N/A
2003/0158480	12/2002	Tornes et al.	N/A	N/A
2003/0163153	12/2002	Scheib	N/A	N/A
2003/0225392	12/2002	McMichael et al.	N/A	N/A

2004/0015162	12/2003	McGaffigan	N/A	N/A
2004/0024396	12/2003	Eggers	N/A	N/A
2004/0030328	12/2003	Eggers et al.	N/A	N/A
2004/0044350	12/2003	Martin et al.	N/A	N/A
2004/0073243	12/2003	Sepetka et al.	N/A	N/A
2004/0077948	12/2003	Molante et al.	N/A	N/A
2004/0116851	12/2003	Johansen et al.	N/A	N/A
2004/0127963	12/2003	Uchida et al.	N/A	N/A
2004/0133113	12/2003	Krishnan	N/A	N/A
2004/0133130	12/2003	Ferry et al.	N/A	N/A
2004/0143256	12/2003	Bednarek	N/A	N/A
2004/0143312	12/2003	Samson et al.	N/A	N/A
2004/0147950	12/2003	Mueller et al.	N/A	N/A
2004/0181213	12/2003	Gondo	N/A	N/A
2004/0210281	12/2003	Dzeng et al.	N/A	N/A
2004/0230188	12/2003	Cioanta et al.	N/A	N/A
2005/0004585	12/2004	Hall et al.	N/A	N/A
2005/0010208	12/2004	Winston et al.	N/A	N/A
2005/0049628	12/2004	Schweikert et al.	N/A	N/A
2005/0059966	12/2004	McClurken et al.	N/A	N/A
2005/0065507	12/2004	Hartley et al.	N/A	N/A
2005/0085806	12/2004	Auge et al.	N/A	N/A
2005/0096529	12/2004	Cooper et al.	N/A	N/A
2005/0101984	12/2004	Chanduszko et al.	N/A	N/A
2005/0119556	12/2004	Gillies et al.	N/A	N/A
2005/0123702	12/2004	Beckham	N/A	N/A
2005/0137527	12/2004	Kunin	N/A	N/A
2005/0149012	12/2004	Penny et al.	N/A	N/A
2005/0203504	12/2004	Wham et al.	N/A	N/A
2005/0203507	12/2004	Truckai et al.	N/A	N/A
2005/0261607	12/2004	Johansen et al.	N/A	N/A
2005/0288631	12/2004	Lewis et al.	N/A	N/A
2006/0041253	12/2005	Newton et al.	N/A	N/A
2006/0074398	12/2005	Whiting et al.	N/A	N/A
2006/0079769	12/2005	Whiting et al.	N/A	N/A
2006/0079787	12/2005	Whiting et al.	N/A	N/A
2006/0079884	12/2005	Manzo et al.	N/A	N/A
2006/0085054	12/2005	Zikorus et al.	N/A	N/A
2006/0089638	12/2005	Carmel et al.	N/A	N/A
2006/0106375	12/2005	Werneth et al.	N/A	N/A
2006/0135962	12/2005	Kick et al.	N/A	N/A
2006/0142756	12/2005	Davies et al.	N/A	N/A
2006/0149166	12/2005	Zvuloni	N/A	N/A
2006/0189972	12/2005	Grossman	N/A	N/A
2006/0241586	12/2005	Wilk	N/A	N/A
2006/0247672	12/2005	Vidlund et al.	N/A	N/A
2006/0264927	12/2005	Ryan	N/A	N/A
2006/0276552	12/2005	Barbut et al.	N/A	N/A
2006/0276710	12/2005	Krishnan	N/A	N/A
2007/0038277	12/2006	Dae et al.	N/A	N/A

2007/0055328	12/2006	Mayse et al.	N/A	N/A
2007/0060879	12/2006	Weitzner et al.	N/A	N/A
2007/0066975	12/2006	Wong et al.	N/A	N/A
2007/0118099	12/2006	Trout, III	N/A	N/A
2007/0123964	12/2006	Davies et al.	N/A	N/A
2007/0167775	12/2006	Kochavi et al.	N/A	N/A
2007/0208256	12/2006	Marilla	N/A	N/A
2007/0225681	12/2006	House	N/A	N/A
2007/0270791	12/2006	Wang et al.	N/A	N/A
2008/0039865	12/2007	Shaher et al.	N/A	N/A
2008/0042360	12/2007	Veikley	N/A	N/A
2008/0086120	12/2007	Mirza et al.	N/A	N/A
2008/0097213	12/2007	Carlson et al.	N/A	N/A
2008/0108987	12/2007	Bruszewski et al.	N/A	N/A
2008/0146918	12/2007	Magnin et al.	N/A	N/A
2008/0171934	12/2007	Greenan et al.	N/A	N/A
2008/0208121	12/2007	Youssef et al.	N/A	N/A
2008/0243112	12/2007	De Neve	N/A	N/A
2008/0275439	12/2007	Francischelli et al.	N/A	N/A
2008/0312644	12/2007	Fourkas et al.	N/A	N/A
2009/0105742	12/2008	Kurth et al.	N/A	N/A
2009/0138009	12/2008	Mswanathan et al.	N/A	N/A
2009/0163850	12/2008	Betts et al.	N/A	N/A
2009/0177114	12/2008	Chin et al.	N/A	N/A
2009/0264977	12/2008	Bruszewski et al.	N/A	N/A
2010/0087789	12/2009	Leeflang et al.	N/A	N/A
2010/0125282	12/2009	Machek et al.	N/A	N/A
2010/0168624	12/2009	Sliwa	N/A	N/A
2010/0168684	12/2009	Ryan	N/A	N/A
2010/0179632	12/2009	Bruszewski et al.	N/A	N/A
2010/0191142	12/2009	Paul et al.	N/A	N/A
2010/0194047	12/2009	Sauerwine	N/A	N/A
2011/0046619	12/2010	Ducharme	N/A	N/A
2011/0082452	12/2010	Melsky	606/15	A61B 18/1492
2011/0082488	12/2010	Niazi	N/A	N/A
2011/0152716	12/2010	Chudzik et al.	N/A	N/A
2011/0160592	12/2010	Mitchell	N/A	N/A
2011/0166633	12/2010	Stull	N/A	N/A
2011/0190763	12/2010	Urban et al.	N/A	N/A
2012/0232546	12/2011	Mirza et al.	N/A	N/A
2012/0265055	12/2011	Melsheimer et al.	N/A	N/A
2012/0330156	12/2011	Brown et al.	N/A	N/A
2013/0006139	12/2012	Tiano	N/A	N/A
2013/0110098	12/2012	Lalonde	N/A	N/A
2013/0184551	12/2012	Paganelli et al.	N/A	N/A
2013/0184735	12/2012	Fischell et al.	N/A	N/A
2013/0190796	12/2012	Tilson et al.	N/A	N/A
2013/0211283	12/2012	Bunch	600/549	A61B 5/6853
2013/0282084	12/2012	Mathur et al.	N/A	N/A

2014/0206987	12/2013	Urbanski et al.	N/A	N/A
2014/0228636	12/2013	Nimkar et al.	N/A	N/A
2014/0277304	12/2013	Stull	N/A	N/A
2014/0296769	12/2013	Hyde et al.	N/A	N/A
2014/0364928	12/2013	Machold	607/106	A61F 7/123
2015/0165170	12/2014	Beasley et al.	N/A	N/A
2016/0199224	12/2015	Keller et al.	N/A	N/A
2016/0220741	12/2015	Garrison et al.	N/A	N/A
2016/0262823	12/2015	Aklog	N/A	A61B 18/04
2017/0105871	12/2016	Nierich	N/A	N/A
2018/0055687	12/2017	Keller et al.	N/A	N/A
2018/0303663	12/2017	Cattaneo et al.	N/A	N/A
2018/0360651	12/2017	Brian, III et al.	N/A	N/A
2019/0021763	12/2018	Zhou et al.	N/A	N/A
2019/0247035	12/2018	Gittard et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2952162	12/2014	EP	N/A
2006/055286	12/2005	WO	N/A
2017/064134	12/2016	WO	N/A
2020/030985	12/2019	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT Patent Application No. PCT/IB2018/056059, mailed on Mar. 21, 2019, 31 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/IB2019/051168, mailed on Jun. 3, 2019, 13 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/IB2020/051156, mailed on May 20, 2020, 15 pages. cited by applicant

Primary Examiner: Tejani; Ankit D

Assistant Examiner: Solomon; Joshua Brendon

Attorney, Agent or Firm: Nelson Mullins Riley & Scarborough LLP

Background/Summary

TECHNICAL FIELD

(1) The disclosure relates to the field of heating and cooling tissue, in particular the temperature management of tissue using a heat exchange and temperature sensing device.

SUMMARY OF THE DISCLOSURE

(2) The problem of preventing injury to an esophagus caused by heat or cold being delivered to the heart or other nearby tissue may be solved by regulating the temperature of the esophagus using a heat exchange device having a heat exchanger which has a cross section substantially corresponding with the collapsed/relaxed/natural cross section of the inside of the esophagus. In some embodiments, the heat exchanger is a balloon, and inflation of the balloon substantially

maintains the esophagus in its natural shape and location (i.e., the esophagus is not displaced towards the left atrium). Some alternative embodiments includes providing a heat exchanger that substantially conforms to or corresponds with the cross section of an esophagus by means other than inflation while substantially maintaining the natural shape and location of the esophagus.

(3) In a first broad aspect, embodiments of the present invention are for a heat exchanging device for regulating a temperature of an esophagus when heat or cold is delivered to a left atrium of a heart, the heat exchanging device comprising: an elongated shaft comprising a distal end and a proximal end; a heat exchanger attached to the distal end of the elongated shaft, the heat exchanger comprising an insertable configuration and a heat exchanging configuration; wherein a cross-section of the heat exchanger in the insertable configuration is smaller than a cross-section of the heat exchanger in the heat exchanging configuration, and wherein said cross-section of the heat exchanger in the heat exchanging configuration substantially conforms to and corresponds with a cross-section of an inside surface of the esophagus such that the esophagus is substantially maintained in its natural shape and location when the heat exchanger is in its heat exchanging configuration.

(4) In some embodiments of the first broad aspect, the heat exchanger comprises a distal end, a proximal end, and a cavity therebetween. In some such embodiments, the elongated shaft defines at least a first lumen and a second lumen, and at least a portion of said cavity is in fluid communication with the first lumen and the second lumen of the elongated shaft.

(5) In some embodiments of the first broad aspect, the shape of the heat exchanger is constrained by a weld pattern, wherein the weld pattern comprises at least one weld, wherein said at least one weld attaches at least part of an anterior surface of the heat exchanger and a posterior surface of the heat exchanger. In some such embodiments, the at least one weld comprises a plurality of welds which are oriented as a series of consecutive chevrons along the length of the heat exchanger. In some examples, at least one chevron of the series of consecutive chevrons is comprised of a pair of dumbbell-shaped welds.

(6) In some examples, at least one chevron of the series of consecutive chevrons is comprised of a pair of welds which are generally curved in shape with hook-shaped ends. In some examples including a plurality of welds, the heat exchanging device further comprises an alternative pair of welds which have an alternative shape selected from the group consisting of C-shaped welds, generally V-shaped welds, and welds which have a generally triangular-shaped portion and a circular portion.

(7) In some embodiments of the first broad aspect, the elongated shaft is a multi-lumen tube which defines an inlet lumen and a first outlet lumen. In some such embodiments, the inlet lumen comprises a fluid inlet port to allow heat exchange fluid to flow into said heat exchanger. In some embodiments having the multi-lumen tube, the first outlet lumen comprises a fluid outlet port to allow heat exchange fluid to flow out of said heat exchanger. Some embodiments having the multi-lumen tube further comprise a second outlet lumen. Some embodiments further comprise the first outlet lumen having a larger diameter than the inlet lumen. Some embodiments further comprise a utility lumen.

(8) Some embodiments of the first broad aspect further comprise a radiopaque material positioned on the heat exchanger. In some embodiments, the radiopaque material defines at least one circular shaped marker. In some embodiments, the radiopaque material defines a bordering frame on a side of the heat exchanger wherein the bordering frame borders at least a portion of the surface of the side. In some embodiments comprising a radiopaque material positioned on the heat exchanger, the radiopaque material is configured to indicate which side of the balloon is facing a heart of a patient. Some embodiments further comprise at least one temperature sensor on a side of the heat exchanger and the radiopaque material being configured to indicate which direction the at least one temperature sensor is facing.

(9) In some embodiments of the first broad aspect, the first lumen is a fluid inlet tube and an inner

layer of the fluid inlet tube defines an inlet fluid pathway, and the elongated shaft defines a series of air pockets surrounding the inlet fluid pathway to thereby thermally insulate the fluid inlet tube. In some such embodiments, an outer layer of the fluid inlet tube and the inner layer of the fluid inlet tube define the series of air pockets therebetween.

(10) In some embodiments of the first broad aspect, the second lumen is a fluid outlet tube and an inner layer of the fluid outlet tube defines an outlet fluid pathway, and the elongated shaft defines a series of air pockets surrounding the outlet fluid pathway to thereby thermally insulate the fluid outlet tube. In some such embodiments, an outer layer of the fluid outlet tube and the inner layer of the fluid outlet tube define the series of air pockets therebetween.

(11) In some embodiments of the first broad aspect, the heat exchanger comprises a first zone and a second zone which can be identified under imaging. In some such embodiments, the first zone has a first temperature sensor and the second zone has a second temperature sensor, whereby the heat exchanging device is operable to be moved such that a selected zone with a preferred temperature is adjacent to a heart of a patient.

(12) In some embodiments of the first broad aspect, the heat exchanger is comprised of at least one balloon.

(13) In some embodiments of the first broad aspect, the heat exchanger is comprised of at least one balloon, and the heat exchanging device further comprises an outer balloon surrounding the heat exchanger. In some such embodiments, the elongated shaft comprises an inner lumen which is in fluid communication with the at least one balloon of the heat exchanger and an outer lumen which is in fluid communication the outer balloon. In some embodiments having an outer balloon surrounding the heat exchanger, the elongated shaft contains a tubing wherein an inner surface of the tubing defines the inner lumen, and an outer surface of the tubing and an inner surface of the shaft define the outer lumen.

(14) In a second broad aspect, embodiments of the present invention are for a method of regulating a temperature of an esophagus when heat or cold is delivered to a left atrium. The method comprises the steps of: (1) delivering a heat exchange device to a target site within an esophagus; (2) confirming a desired location of the heat exchange device; and (3) exchanging heat with the esophagus; wherein step (2) comprises a user (a) identifying a first zone and a second zone of the heat exchanger under imaging, (b) measuring a first zone temperature and a second zone temperature, (c) comparing the first zone temperature against the second zone temperature and selecting a preferred temperature, and (d) positioning the heat exchanger such that a selected zone having the preferred temperature is adjacent to a heart of a patient.

(15) In a third broad aspect, embodiments of the present invention are for a heat exchanging device for regulating a temperature of an esophagus when heat or cold is delivered to a left atrium of a heart, the heat exchanging device comprising: a heat exchanger which is elongate, the heat exchanger comprising a distal end, a proximal end, a cavity therebetween; the heat exchanging device further comprising a fluid inlet port and a fluid outlet port in fluid communication with the cavity, and a temperature sensor for measuring a temperature.

(16) In some embodiments of the third broad aspect, the temperature sensor is attached to the heat exchanger. In some such embodiments, the temperature sensor is attached to the distal end of the heat exchanger.

(17) In some embodiments of the third broad aspect, the heat exchanging device comprises a heat exchanging configuration wherein a side of the heat exchanger faces a heart of a patient and the temperature sensor is on the side of the heat exchanger which faces the heart. Some such embodiments further comprise an imaging marker for positioning the heat exchanging device in the heat exchanging configuration.

(18) In some embodiments of the third broad aspect, the temperature sensor is spaced apart from the heat exchanger such that the temperature sensed by the temperature sensor is of an esophagus of a patient. In some embodiments, the temperature sensor is spaced apart from the heat exchanger

such that the temperature sensed by the temperature sensor is of a stomach of a patient.

(19) In some embodiments of the third broad aspect, the temperature sensor is mounted on a part of a structural frame that is external to the heat exchanger. Some embodiments further comprise an elongated shaft wherein the elongated shaft comprises at least two struts and the temperature sensor is mounted on a strut. In some embodiments, the temperature sensor is affixed to or woven into a textile which surrounds the heat exchanger. In some embodiments, the temperature sensor is affixed to a strand connected to an end of the heat exchanger. In some embodiments, an array of temperature sensors are operable to be used to measure a plurality of temperatures.

(20) In some embodiments of the third broad aspect, the heat exchanger is a balloon. In some such embodiments, the temperature sensor is attached to the balloon, and in some further embodiments, the temperature sensor comprises conductive ink on the surface of the balloon.

(21) In a fourth broad aspect, embodiments of the present invention are for method of installing a heat exchanging device in an esophagus wherein the heat exchanging device comprises an elongated shaft having a distal end, a heat exchanger with an inner balloon attached to the distal end of the elongated shaft, an outer balloon surrounding the inner balloon, and the elongated shaft having an inner lumen in fluid communication with the inner balloon and an outer lumen in fluid communication with the outer balloon; the method comprising the steps of: (a) extending the heat exchanger with the inner balloon and the outer balloon out of a sheath to a location inside of an esophagus; (b) inflating the outer balloon with a first fluid which flows through the outer lumen to thereby expand the esophagus; (c) inflating the inner balloon with a second fluid which flows through the inner lumen; and (d) withdrawing the first fluid in the outer balloon through the outer lumen to thereby create a vacuum which collapses the outer balloon.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order that the invention may be readily understood, embodiments of the invention are illustrated by way of examples in the accompanying drawings, in which:

(2) FIG. 1 is an illustration of a heat exchange device;

(3) FIG. 2 is an illustration of a cross section of an esophagus;

(4) FIG. 3 is an illustration of a cross section of a balloon heat exchanger;

(5) FIG. 4 is an illustration of a balloon heat exchanger expanded in an esophagus;

(6) FIG. 5 is an illustration of three balloons side-by-side;

(7) FIG. 6 is an illustration of balloons with centered necks;

(8) FIG. 7 is an illustration of balloons with offset necks;

(9) FIG. 8 is an illustration of a serpentine welded balloon;

(10) FIG. 9 is an illustration of a welded balloons with ties;

(11) FIG. 10 is an illustration of a welded balloon with fins;

(12) FIG. 11 is an illustration of a welded balloon with pockets;

(13) FIG. 12 is an illustration of a coiled tube heat exchanger;

(14) FIG. 13 is an illustration of a multiple-tube heat exchanger;

(15) FIG. 14 is an illustration of a helical-tube heat exchanger;

(16) FIG. 15 is an illustration of a serpentine-tube heat exchanger;

(17) FIG. 16 is an illustration of an inlet port with a single hole;

(18) FIG. 17 is an illustration of an inlet port with multiple holes;

(19) FIG. 18 is an illustration of temperature sensors affixed to balloon surface;

(20) FIG. 19 is an illustration of temperature sensors mounted on the embodiments depicted in FIGS. 13 and 14;

(21) FIG. 20 is an illustration of temperature sensors mounted on struts made from a catheter shaft

(22) FIG. 21 is an illustration of temperature sensors affixed to textile;
(23) FIG. 22 is an illustration of temperature sensors affixed to strands;
(24) FIG. 23 is an illustration of a heat exchanger with an insulating air balloon inside;
(25) FIG. 24 is an illustration of a heat exchanger with an insulating air balloon outside;
(26) FIG. 25 is an illustration of open irrigation of a fluid with suction;
(27) FIG. 26 is a flowchart of a method;
(28) FIG. 27 is an illustration of a balloon with a weld line;
(29) FIG. 28 is an illustration of a balloon with tack welds;
(30) FIG. 29 is another embodiment of a heat exchange device which includes an outer sheath;
(31) FIG. 30 is an exploded view of a balloon;
(32) FIG. 31 is an illustration of a coiled tube heat exchanger with an oblong cross-sectional profile;
(33) FIG. 32 is an illustration of a multiple-tube heat exchanger with an oblong cross-sectional profile;
(34) FIG. 33 is an illustration of a helical-tube heat exchanger with an oblong cross-sectional profile;
(35) FIG. 34 is an illustration of a heat exchanger with an insulating portion;
(36) FIG. 35 is an illustration of a heat exchanger with a shaping lumen and a heat exchanging lumen;
(37) FIG. 36 is an illustration of temperature sensors mounted on the embodiment depicted in FIG. 32;
(38) FIG. 37 is an illustration of temperature sensors mounted on the embodiment depicted in FIG. 33;
(39) FIG. 38 is an illustration of a balloon with a pair of wavy weld lines;
(40) FIG. 39 is an illustration of a further embodiment of a balloon with a pair of wavy weld lines;
(41) FIG. 40 is an illustration of a balloon with a pair of wavy weld lines and multiple tack welds;
(42) FIG. 41 is an illustration of a balloon with a pair of curved weld lines;
(43) FIG. 42 is an illustration of a further embodiment of a balloon with tack welds;
(44) FIG. 43 is an illustration of a balloon with a pair of broken weld lines;
(45) FIG. 44 is an illustration of a further embodiment of a balloon with a pair of broken weld lines;
(46) FIG. 45 is an illustration of yet another embodiment of a balloon with a pair of broken weld lines;
(47) FIG. 46 is an illustration of a balloon with a pair of broken weld lines and a pair of tack welds;
(48) FIG. 47 is an illustration of a balloon with chevron pattern welds;
(49) FIG. 48 is an illustration of a further embodiment of a balloon with chevron pattern welds;
(50) FIG. 49 is an illustration of yet another embodiment of a balloon with chevron pattern welds;
(51) FIG. 50 is an illustration of a welded balloon with an outer balloon;
(52) FIG. 51 is an illustration of an irrigation heat exchanger;
(53) FIG. 52 is an illustration of the embodiment of FIG. 51 disposed in a body lumen;
(54) FIG. 53 is a side view of the embodiment depicted in FIG. 52;
(55) FIG. 54 is an exploded view of a an embodiment;
(56) FIG. 55 is an illustration of a heat exchanger comprising a pocket;
(57) FIG. 56 is a cross-sectional plan view of a heat exchanger attached to a shaft and an inlet tube;
(58) FIG. 57 is a cross-sectional plan view of a heat exchanger attached to a shaft, an inlet tube, and an outlet tube;
(59) FIG. 58 is an illustration of another embodiment of a balloon with chevron pattern welds and a pair of alternatively shaped welds;
(60) FIG. 59 is an illustration of a further embodiment of a balloon with chevron pattern welds and a pair of C-shaped welds;

- (61) FIG. 60 is an illustration of a yet further embodiment of a balloon with chevron pattern welds and a pair of V-shaped welds;
- (62) FIG. 61 is a cross-section of a multi-lumen shaft;
- (63) FIG. 62 is an illustration of an embodiment of a balloon with radiopaque material;
- (64) FIG. 63 is an illustration of another embodiment of a balloon with radiopaque material;
- (65) FIG. 64 is an illustration of an embodiment of a shaft with air pockets;
- (66) FIG. 65 is an illustration of an embodiment of a balloon with zones;
- (67) FIGS. 66A to 66D are illustrations of an embodiment of a heat exchange device with inner and outer balloons; and
- (68) FIGS. 67A to 67C are illustrations of shaft embodiments which could be used in the heat exchange device of FIGS. 66A to 66D.

DETAILED DESCRIPTION

- (69) Inadvertent thermal injury to the esophagus is a dangerous complication of left atrial ablation due to the close proximity of the esophagus to the posterior aspect of the human heart. These thermal injuries can include esophageal mucosal changes, tissue necrosis, ulcer formation, and atrial-esophageal fistula formation.
- (70) Current preventative options include reducing the power or duration of ablation when targeting the posterior wall of the left atrium, and monitoring luminal esophageal temperature during ablation so that the ablation can be stopped if there is an unacceptable temperature change in the esophagus. These options may reduce the effectiveness of an ablation treatment.
- (71) Attempts have been made in the past to protect the esophagus using cooling balloons. One of the limitations of such balloons is that the balloons typically expand and/or displace the esophagus. Sometimes, a balloon expands and displaces an esophagus to a position closer to the posterior wall of the heart which is the location of heating by delivery of energy for ablation. In such cases, the cooling by the balloon may not be sufficient to protect the esophagus from thermal injury.
- (72) The present inventors have conceived of and reduced to practice embodiments of a heat exchange and temperature sensing device and a method of use of said device which is able to prevent injury to an esophagus caused by heat or cold being delivered to the left atrium of the heart. The device regulates the temperature of the esophagus by providing a heat exchanger which can be placed in the esophagus. The heating/cooling balloon has an inflatable cross section corresponding with the collapsed/relaxed/natural cross section of the inside of the esophagus. Inflation of the balloon maintains the esophagus in its natural shape and location such that the esophagus is not displaced towards the left atrium.
- (73) In its collapsed or insertable state, the balloon is low in profile and flexible so that it can be inserted into the nose or mouth and advanced to the esophagus. Once positioned in the esophagus, it is expandable to take on a shape with a profile and dimensions corresponding to the collapsed/relaxed/natural cross section of the internal lumen defined by a human esophagus. When fully expanded, the heat exchange balloon makes contact with the endoluminal surface of the esophagus without substantially displacing it from its natural location.
- (74) The outer surface of the balloon is in intimate contact with the mucosal layer of the esophagus. It supplies or removes thermal energy in order to keep the esophagus at a desired temperature throughout an ablation procedure. This includes cooling the esophagus during heat-based ablation procedures, (such as radio frequency/RF or high intensity focused ultrasound ablation/HIFU), or warming the esophagus during cold-based ablation procedures (such as cryoablation).
- (75) This method and device may be used during left atrial ablation procedures, which are procedures for treating atrial fibrillation in humans. These procedures may include RF/HIFU ablations and cryoablations. In these types of procedures, ablations are performed to create lesions around the ostia of the pulmonary veins, some of which are typically very close to the esophagus. Before the veins are ablated, the balloon portion of the device is positioned in the esophageal lumen and posterior to the left atrium. Once activated, the device either removes thermal energy

from the esophagus, or delivers thermal energy to the esophagus to keep it in a desired temperature range throughout the procedure.

(76) The invention can also be used in other cardiac procedures where the temperatures in the heart reach undesired levels. It can also be used in other areas of the body where temperature management is required to protect sensitive structures, for example ablation of the prostate to treat cancer. Additionally, the invention can be used to control patient temperature, for example to induce and maintain hypothermia in critically ill patients, or to warm patients with body temperatures below normal, such as when they are under general anesthesia and undergoing surgery.

(77) With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of certain embodiments of the present invention only. Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

(78) Heat Exchanging Fluid Device

(79) An example of a heat exchange and temperature sensing device **100** for use in the method described herein is illustrated in FIG. **1**. Heat exchanging fluid device **100** comprises a main shaft **103** which has balloon heat exchanger **101** at one end, with temperature sensor **104** being associated with balloon heat exchanger **101**. Handle **105** is at the other end of main shaft **103**. The end of heat exchange device **100** having handle **105** also includes fluid inflow **106**, fluid outflow **107**, and temperature sensor connector **108**. Another embodiment of heat exchange and temperature sensing device **100** is shown in FIG. **29**. As will be described in more detail below, heat is exchanged by allowing fluid to be circulated through the balloon **101** via fluid inflow **106** and fluid outflow **107**.

(80) In one embodiment, the fluid is made substantially of water. For example, the fluid may be distilled water or saline. Alternately, the fluid may be a substance that is not substantially water, such as an oil based or petroleum product. In addition, the fluid may contain additives, for example a disinfectant, or stabilizer. The temperature, flow rate, and pressure of the fluid is managed through an external controller which includes a pump. The heat exchanging fluid device of the present invention is described in greater detail below.

(81) The heat exchanging fluid device comprises inlet port(s) and outlet port(s). The inlet port(s) is the location where the fluid enters the heat exchanger (e.g. a balloon). There may be one or multiple inlet ports which service different locations in the heat exchanger. In one embodiment, the inlet port **116** is a hole on tube **127** located inside the heat exchanger **101** (e.g. FIG. **16**. Inlet port with single hole). The fluid advances through fluid inflow **106** and tube **127** until it reaches the hole **116** and enters the heat exchanger **101**. Fluid inflow **106** and tube **127** are in fluid communication to allow fluid to be supplied to the heat exchanger via fluid inflow **106**. In some embodiments the tube **127** is made of plastic, possibly reinforced with materials such as a metal coil or braid within the tube wall. The hole **116** may be at the distal end of the heat exchanger **101**, or the proximal end of the heat exchanger **101**, or at any location in between. In the embodiments depicted in FIGS. **1** and **29**, inlet port(s) are in fluid communication with fluid inflow **106**. In some embodiments, inlet port(s) are part of fluid inflow **106**.

(82) In some embodiments, heat exchange fluid is circulated in a closed loop. After heat exchange fluid leaves the heat exchange device via fluid outflow, the heat exchange fluid is re-heated/re-cooled then introduced back into the heat exchange device via fluid inflow. Heat exchange fluid may thus be continuously recirculated.

(83) In other embodiments, heat exchange fluid is circulated in an open loop. Heat exchange fluid

leaving the heat exchange device is discarded or disposed of.

(84) In an alternate embodiment, the tube has multiple holes spaced along the tube (e.g. FIG. 17. Tube 127 with multiple inlet ports 116). The fluid advances through the tube until it reaches one of the multiple holes, and enters the heat exchanger in multiple locations simultaneously. The holes may be spaced linearly at regular intervals, or in a helical pattern around the tube, or in any other type of pattern along the tube. Typically, the holes are located to optimize one of the features of the heat exchange. For example, the holes may be located to maximize the thermal performance of the heat exchanger, or to control pressure inside the heat exchanger.

(85) The outlet port is the location where the fluid exits the heat exchanger. There may be one or multiple outlet ports which service different locations in the heat exchanger. In one embodiment, the outlet port is a tube with a single hole located inside the heat exchanger. The fluid enters the heat exchanger at the inlet port(s), travels through the heat exchanger, and exits at the outlet port. In some embodiments, the tube is made of plastic, possibly reinforced with materials such as a metal coil or braid within the tube wall. The hole may be at the distal end of the heat exchanger, or the proximal end of the heat exchanger, or at any location in between. In the embodiment depicted in FIGS. 1 and 29, outlet port(s) are in fluid communication with fluid outflow 107. In some embodiments, outlet port(s) are part of fluid outflow 107.

(86) In another embodiment, the tube 127 has multiple holes spaced along its length. The fluid in the heat exchanger exits through one of the multiple holes simultaneously. The holes may be spaced linearly at regular intervals, or in a helical pattern around the tube, or in any other type of pattern along the tube. Typically, the holes are located to optimize one of the features of the heat exchange. For example, the holes may be located to maximize the thermal performance of the heat exchanger, or to control pressure inside the heat exchanger.

(87) The heat exchange device 100 may comprise a sheath or sleeve. A sheath 152 is depicted in FIG. 29. As will be discussed in greater detail below, a heat exchanger 101 may be collapsed/wrapped/deflated around a shaft 103 such that the heat exchanger 101 may be received into a sheath 152. Accordingly, sheath 152 is dimensioned to receive heat exchanger 101 when it is in a collapsed/wrapped/deflated configuration. This feature may be provided to avoid damage to the body lumen when the heat exchanger is being advanced therethrough. Heat exchanger 101 may be provided with radiopaque (RO) markers or electroanatomic mapping (EAM) 153 for using imaging techniques to determine the location of the heat exchanger 101 relative to known anatomical markers. The embodiment depicted in FIG. 29 is provided with a body temperature sensor 155. Body temperature sensor 155 is spaced apart from heat exchanger 101 such that the temperature sensed by sensor 155 is of the body lumen (e.g. the esophagus) and not of the heat exchanger 101. Items 154 are additional electrodes for either pacing or detecting electric signals. For pacing, pacing electrodes would be provided. For detecting electric signals, electrocardiogram electrodes would be provided. The various sensors and electrodes may be connected to one or more external devices through connector 108.

(88) FIGS. 62 and 63 illustrate embodiments of the heat exchanger 101 in which, radiopaque material has been placed on the balloon to aid in visualization for positioning and verifying the correct position of the device. Examples of radiopaque materials which may be used for visualizing the balloon under fluoroscopy include films or extrusions with additives, radiopaque ink or paint, metal foil, and other materials known to those skilled in the art. The radiopaque material 220 can be implemented in different configurations, for example, as a bordering frame (FIG. 63), dots or circular markers (FIG. 62), lines, patterns, and other known configurations. Radiopaque material which has been placed on a balloon may be used to verify the balloon is: (1) positioned behind the left atrium, (2) fully deployed such that the balloon is flat and not folded or twisted, and (3) positioned such that temperature sensors are facing the heart. For the balloon to be positioned such that one side of the balloon is facing the heart, the radiopaque material 220 should be placed on the balloon in an asymmetrical manner, for example, the radiopaque material being placed in the four

corners of the balloon, with a different configuration from the others, as shown in FIG. 62.

(89) FIG. 56 illustrates an embodiment of heat exchanger **101** with inlet and outlet ports. The heat exchanger **101** comprises proximal neck portion **146** and distal neck portion **134**. In this embodiment, inlet ports **116** are positioned proximate the distal end of heat exchanger **101**. Fluid travels through tube **127** along the arrows shown in the figure. When the fluid reaches the outlet ports **116**, fluid exits tube **127** and enters the heat exchanger **101**. The fluid then follows a return path towards a proximal end of the heat exchanger **101** (i.e., towards proximal neck portion **146**) and leaves the heat exchanger **101** via outlet ports **150**. In this embodiment, outlet ports **150** are formed by providing a circumferential gap between the proximal neck portion **146** of the heat exchanger **101** and the tube **127**. The diameter of tube **127** is somewhat narrower than the inner diameter of shaft **103** to permit fluid to flow there between and back towards the fluid outflow **107**. Tube **127** is attached via welding or other means to distal neck portion **146** such that fluid is prevented from escaping the heat exchanger **101** out from the distal neck portion **146**. Proximal neck portion **146** is attached via welding or other means to shaft **103** such that fluid is prevented from escaping the heat exchanger **101** and shaft **103**.

(90) FIG. 57 illustrates a further embodiment of a heat exchanger **101** with inlet and outlet ports. In this embodiment, an inner inlet tube **152** and an outer outlet tube **153** are provided. Fluid flows into the heat exchanger **101** via ports **116**. Both the inner inlet tube **152** and the outer outlet tube **153** comprise ports **116** to allow fluid to pass therethrough. Means are provided to prevent fluid from flowing into the space between inner inlet tube **152** and outer outlet tube **153**. In this embodiment, O-rings **151** are placed on either side of ports **116**. The O-rings **151** prevent fluid from flowing into the space between the inner inlet tube **152** and the outer outlet tube **153**. Outer outlet tube **153** comprise outlet ports **150**. Fluid leaving the heat exchanger **101** flows into the outlet ports **150** and towards a fluid outflow.

(91) FIG. 61 is a cross section of an embodiment of the shaft of a heat exchanger wherein the shaft is a multi-lumen tube **251**. Multi-lumen tube **251** includes an inlet lumen **252**, at least one outlet lumen **253**, and a utility lumen **254**. Utility lumen **254** may be used to provide for balloon pressure measurement, temperatures sensors, conductor wires, and other uses known to one skilled in the art. The multi-lumen design of the shaft allows for ease of assembly, provides thermal insulation between the lumens, the ability to achieve lower balloon pressures than some other designs.

(92) (b) A heat exchanger (a cavity for circulation of fluid). In one embodiment, the cavity is a balloon—this embodiment will be described in greater detail below. Some embodiments of balloons are made of a non-compliant material such as Nylon 12 or PET. Alternative balloon embodiments are made of a compliant material such as Pebax® or urethane.

(93) (c) Features augmenting contact. To ensure appropriate heat exchange is occurring at the esophagus, the heat exchanger must maintain adequate contact with the tissue. The heat exchanger having contact with the esophagus also ensures any heat sensors on the heat exchanger are contacting the inner surface of the esophagus. The following optional features may be included for augmenting the contact between the heat exchanger and the tissue:

(94) (c.1) Controllable heat exchanger size. This feature includes the heat exchanger being expandable or contractable to fit the size of the esophagus and promote contact with the tissue. The change in size may be controlled with pressure, such as the internal pressure in a balloon, or external pressure exerted by the anatomy on the device. Alternately, the size may be controlled with a mechanical expansion/contraction mechanism, which may further comprise a feedback loop from the forces exerted on the device (detected via force sensors) to achieve the optimal contact force.

(95) (c.2) Conformable heat exchanger shape. This feature includes the expansion of the heat exchanger being constrained in one or more axes, using the balloon designs outlined above and through the use of compliant and non-compliant materials, thin films with ties or welds, and shape memory materials. In alternative embodiments, the heat exchanger is moldable to the esophagus shape through the use of compliant materials that respond to forces exerted by the tissue.

(96) (c.3) Anchoring feature. The heat exchange device may have an anchoring feature or features such as notches, necks, collars, or hooks that allow the device to engage internally with anatomical features to hold it in place. In alternative embodiments, the device has an anchoring feature such as tape, Velcro, and straps that allow it to engage externally with other devices such as an endotracheal tube or a nasal bridle to hold it in place.

(97) (c.4) Suction feature. The heat exchange device may incorporate suction to hold the tissue against the surface of the device to ensure appropriate tissue contact. Tissue suction may also be used to ensure that tissue is pulled away from the area where heat is being applied. For example, when esophagus tissue is pulled towards the heat exchanger, it may be consequently pulled away from the left atrium of the heart where ablation is taking place.

(98) Also, force may be applied to the esophagus or the device to maintain adequate tissue contact. This may be a force external to the patient, or applied from within the patient from the heat exchange device, or from another device (for example, by suction feature as described above).

(99) An additional technique to ensure proper heat exchange is to assess the amount of tissue contact between the heat exchanger and the tissue at the target site. The heat exchange device may comprise force sensors to measure the amount of force between the tissue and the heat exchanger. This force may be used in a feedback loop in communication with the device to maintain optimal force between the heat exchanger and the tissue.

(100) Yet another technique to ensure proper heat exchange is to use heat flux sensors to measure the heat flux at any given part of the tissue at the target site. A greater heat flux measurement represents greater heat transfer between the tissue and the heat exchanger.

(101) Balloon Heat Exchanger

(102) Some embodiments of the heat exchanging fluid device described herein comprise a balloon heat exchanger **101** (FIG. 1). The balloon **101** comprises a cavity for circulation of fluid. Embodiments of such heat exchange balloons are illustrated in FIGS. 2, 5-15, 18-24, 26-30, 34-35, and 38-50.

(103) The inflated cross-sectional shape of such a balloon mimics the natural shape of the inside of a human esophagus. In its collapsed shape, a human esophagus **109** typically has a cross-section of around 1.5-3 cm wide and around 0-0.5 cm high (e.g. FIG. 2. cross section of esophagus). The balloon of the invention (e.g. FIG. 3. cross section of balloon heat exchanger **101**) maintains a cross-section of similar dimensions in order to make intimate contact with the mucosal layer of the esophagus without displacing it, i.e., the balloon is expandable but is restrained in one or more axes to reduce forces exerted on the abutting surfaces of the esophagus (e.g. FIG. 4. balloon heat exchanger **101** expanded in esophagus **109**).

(104) The desired shape of the balloon heat exchanger **101** can be realized in a number of ways. In one embodiment (see FIGS. 5-7), at least two cylindrical balloons are abutted and held side-by-side. For example, if 3 balloons (see FIG. 5) with an inflated diameter of 5 mm are placed side-by-side, the overall dimensions of the cross-section of the heat exchanger (when expanded) is approximately 15 mm wide and 5 mm tall. Thus, both the number of cylindrical balloons and the inflated diameter of the balloons can be varied to vary the overall dimensions of the cross-section of the heat exchanger.

(105) This approach may be used with any number of cylindrical balloons abutted side-by-side. In some embodiments, these balloons are cylindrical with balloon necks **110** in the middle of the balloon (FIG. 6. balloons with centered necks), or in some other embodiments, with offset balloon necks **110** located away from the center of the balloon (FIG. 7. balloons with offset necks). Balloon necks **110** may be in fluid communication with the main body of balloon **128**. Balloon necks **110** may be connected with input ports or output ports to allow fluid flow through the balloon.

(106) In another embodiment, the desired shape of the balloon is achieved by welding thin films together. The films may be plastic such as urethane, or another material that is formable in thin film. In one embodiment, the films are welded in a serpentine shape. FIG. 8 illustrates a serpentine

welded balloon having top and bottom films (when in the orientation of FIG. 8) welded together along weld lines **111**. The top and bottom films, when welded, result in a lumen **149** through which fluid may be circulated to perform the heat exchange.

(107) In some embodiments the welding technique is used to add singular or multiple ties inside a balloon to prevent it from expanding in undesired axes. FIG. 9 shows two examples of welded balloons with ties with the balloon on the left having a single tie **112** and the balloon on the right of the figure having two ties. Weld lines **111** weld the ties in place.

(108) In other embodiments a balloon shape is constrained with welds. FIGS. 27-28, 30, and 38-50 feature balloon heat exchangers with a variety of weld patterns. Varying the weld patterns impact the lengthwise and widthwise inflatability and rigidity of the balloon as well as the flow of fluid through the balloon.

(109) FIGS. 28 and 42 illustrate balloons with tack welds **126** (or spot welds). The weld pattern in this embodiment results in multiple fluid flow channels that extend along the length and the width of the balloon. These channels are “open” such that fluid flowing within one channel may flow to another channel. This allows fluid to flow into any particular area of the balloon, even if the balloon is bent, folded, or otherwise restricted from freely inflating in that area. These fluid channels allow the balloon to be more easily inflated and deployed in applications where the balloon is introduced into the esophagus deflated and wrapped around a central shaft (such as shown in FIG. 29) along the balloon's lengthwise axis. Also, these embodiments allow the mixing of flow amongst the various fluid channels, which promotes heat exchange across the entire surface of the balloon.

(110) The balloon heat exchanger **101** of FIG. 27 includes a balloon with a weld line **111** creating two fluid flow channels. FIGS. 38, 39, and 40 includes a balloon **101** with two wavy welds creating three fluid flow channels—the wavy welds in these embodiments creates multiple hinge axis, and each axis resists hinge-like behavior giving the balloon added widthwise rigidity when the balloon is inflated, which may be desirable in certain applications. FIG. 41 includes a balloon **101** with two weld lines which are curved at their end. The curved ends correspond with an outer contour of the balloon. By providing these curves, the cross-sectional area at the ends of the balloon **101** are somewhat reduced, thereby reducing the stress on the material when inflated. The embodiments in FIGS. 27, 38, 39, 40, and 41 each create multiple fluid channels along the length of the balloon such that fluid which is introduced at one end (e.g., the distal end) may naturally flow through the channels towards the other end (e.g., the proximal end). Continuous fluid flow through the length of the balloon enables more efficient heat exchange as the target area is continuously provided with heated or cooled fluids.

(111) FIGS. 43, 44, 45, and 46 illustrate balloons with broken line welds. This design enables the mixing of fluid flow between the lengthwise fluid channels, which may be desirable in applications where the fluid in a particular channel is being cooled or heated more than the fluid in the other lumens. These fluid channels are “open” such that fluid from one lengthwise channel may flow to a different lengthwise channel, the balloon may provide more even heat exchange to an area of the esophagus that is experiencing the most extreme temperatures. It also allows the balloon to be more easily inflated within the esophagus because there are multiple pathways for fluid to flow into a given area of the balloon.

(112) FIGS. 47, 48, 49, 58, 59, and 60 illustrate balloons with a chevron pattern of internal welds. This pattern allows fluid flow mixing across the fluid flow channels. The diagonal alignment of the welds increases widthwise rigidity which allows the balloon to be more easily deployed and inflated after being introduced into the esophagus in applications where the balloon is introduced into the esophagus deflated and wrapped around a central shaft along the balloon's lengthwise axis. FIG. 58 includes short welds **211** which define a plurality of chevron portions which are dumbbell shaped (or round ended). FIGS. 59 and 60 include short welds **211** which define a plurality of chevron portions which are curved with hook-shaped ends. All of FIGS. 58, 59 and 60 include a

pair of short welds **211** (shown at the top of the drawings) which have alternative shapes. The alternative pair of the short welds **211** of FIG. **58** are generally triangular-shaped with each triangle having an extended circular corner portion (and could alternatively be described as being generally megaphone-shaped). The alternative pair of short welds **211** at the top of FIG. **59** are C-shaped and the alternative pair of short welds **211** at the top of FIG. **60** are generally V-shaped. In alternative embodiments of FIGS. **58**, **59**, and **60**, the alternative pair of short welds **211** are at different locations along the balloon **101**.

(113) FIG. **30** is an exploded view of a balloon **101** before welding. In this embodiment, a pocket **144** is welded in between an anterior balloon surface **147** and a posterior balloon surface **148**. This embodiment of balloon **101** further comprises a distal neck portion **145** and a proximal neck portion **146**. Pocket **144** may comprise temperature sensors, heat flux sensors, force sensors, or other sensors (not shown). FIG. **54** is an exploded view of a further embodiment of balloon **101** before welding. In this embodiment, three pockets **144** are welded to the outer surface of the anterior balloon surface **147** (i.e., the surface closest to the target area), allowing various sensors to be spread across the width of the balloon. Weld lines **111** are provided creating three fluid flow channels. Pockets **144** are positioned along the fluid flow channels. Positioning pockets **144** on the outer surface of the balloon also allows the sensors to be closer to the target area. Other orientations and combinations of pockets may also be provided. In yet a further embodiment, FIG. **55** depicts a heat exchanger **101** comprising a pocket **144**. Pocket **144** may be formed by attaching a piece of material on the outside of the heat exchanger **101**, thereby creating a pocket **144** adjacent to lumen **149**.

(114) Some alternative embodiments of the heat exchanger **101** have fins or fingers that expand to the desired shape once inflated. The example of FIG. **10** includes a welded balloon with fins **113**.

(115) In other embodiments, multiple pockets are welded along the balloon and brought together with ties to hold the balloon in the desired shape. The FIG. **11** embodiment of balloon heat exchanger **101** comprises an inner film **131**, an outer film **132**, and a tie **112**. The inner film **131** and outer film **132** are welded together to form a series of longitudinal pockets **114** (that is, along the length of the balloon). Fluid flows through the longitudinal pockets in order to perform heat exchange. Tie **112** is attached between two sides of an inner diameter of the balloon heat exchanger **101** to produce a desired cross-sectional shape. In FIG. **11**, the cross-sectional shape of the balloon heat exchanger is circular. As previously mentioned, the balloon heat exchanger is more preferably oblong to better conform to the cross-sectional area of the collapsed esophagus and reduce the resulting displacement of the esophagus. The length and position of tie **112** may be adjusted to change the shape of the balloon heat exchanger when it is in its inflated or expanded configuration.

(116) In addition to using welding to construct balloon heat exchangers, other means known to those skilled in the art may also be used. For example, other adhesive techniques or blow molding techniques may be employed.

(117) In the embodiments where the outer edges of the balloon are welded, sometimes the outer edges may become sharp. In such cases, an outer balloon **135** without any sharp edges may be provided and covers the inner welded balloon **101** (see FIG. **50**). To avoid air or other fluids to be trapped between the inner balloon and the outer balloon **135**, the outer balloon may be perforated or may be vacuum sealed against the inner balloon. The outer balloon may be constructed by flipping a welded balloon inside-out, blow molding, or other techniques known to those skilled in the art. A blunt tip **156** may be provided to prevent damage to the body lumen. In the embodiment shown in FIG. **50**, a sheath **152** is also provided for receiving the heat exchanger **101**.

(118) Use of outer balloon **135** may also provide other advantages. Outer balloon **135** can provide a layer of protection for any electronics placed on the inner balloon (heat exchanger **101**). The outer balloon **135** can be inflated to keep the esophagus open and allow the inner balloon to open without being obstructed by the esophagus. As to be explained below, when the outer lumen **242** is used to pull (i.e. create) a vacuum which collapses the outer balloon **135** around the inner balloon, a

vacuum is also created in outer lumen **242** whereby the outer lumen functions to insulate the fluid flowing in inner lumen **240** and reduce heat exchange between the shaft and surrounding tissue. (119) The steps of FIGS. **66A** to **66D** are explained below with respect to the embodiment of shaft **251** illustrated in FIG. **67A**. Shaft **251** of FIG. **67A** contains tubing **127** whereby inner lumen **240** is defined inside of tubing **127** and outer lumen **242** is defined between tubing **127** and shaft **251**. Inner lumen **240** is in fluid communication with inner balloon **101** and provides for the flow of fluid into and out of the inner balloon. Outer lumen **242** is in fluid communication with outer balloon **135** and provides for the flow of fluid into and out of the outer balloon. FIGS. **66A** to **66D** illustrate how the outer balloon **135** can keep the esophagus **109** open and allow the inner balloon to unfold without being obstructed by esophagus. FIG. **66A** shows heat exchanger **101**, outer balloon **135**, and shaft **251** after being extended out of a sheath. The outer balloon **135** is not expanded and heat exchanger **101** is unfolded. Outer balloon **135** is inflated with fluid (possibly air) injected through outer lumen **242** to arrive at the configuration of FIG. **66B**. FIG. **66B** shows an expanded outer balloon **135** which is opening and expanding esophagus **109** to provide space around folded heat exchanger **101**. Fluid (typically water but other fluids can be used) is injected through inner lumen **240** to expand heat exchanger **101** resulting in the situation of FIG. **66C** wherein heat exchanger **101** has been expanded and unfolded. The fluid in outer balloon **135** is removed using a vacuum to thereby deflate outer balloon **135** so that it fits tightly around heat exchanger **101** (FIG. **66D**). Creating a vacuum to collapse outer balloon **135** also creates a vacuum inside outer lumen **242** (FIG. **67A**) whereby outer lumen **242** functions to insulate the flow of cooling fluid inside inner lumen **240** from surrounding tissue and thereby increase cooling (or heating for heating procedures) at the balloon esophagus interface. A heat exchanger **101** in the configuration of FIG. **66D** could be rotated if needed so that a desired side faces the patient's heart. (120) FIG. **67B** shows an alternative embodiment of shaft **251** which includes an inner inlet lumen **240a**, an inner outlet lumen **240b**, an outer inlet lumen **242a**, and an outer outlet lumen **242b**. FIG. **67C** illustrates a multi-lumen extruded alternative embodiment of shaft **251** which comprises a single inner lumen **240** and a plurality of outer lumens **242** wherein all of the outer lumens **242** could be used for both inflow and outflow, or alternatively, some of the outer lumens **242** could be dedicated inflow lumens and other outer lumens **242** dedicated outflow lumens.

(121) In another embodiment, the outer edges of the welded balloon may comprise small cuts along the outer edge. By introducing small cuts along the outer edge, the rigid outer edge is rendered soft, and reduces the likelihood of damage to the esophagus while the balloon is being introduced through the esophagus. Other techniques may be used to blunt or soften the outer edge, including: The outer edge may be widened such that the welded outer edge is softened. The outer edge may be folded over and welded, glued, or bonded to create a rounded outer edge. The outer edge may be melted to blunt the outer edge. Other materials (sprays or dips) may be added to blunt the outer edge.

(122) FIG. **35** illustrates a further embodiment of a balloon heat exchanger **101**. In this embodiment, the balloon **101** comprises a shaping lumen **132** and a heat exchanging lumen **133**. The shaping lumen **132** and heat exchanging lumen **133** are isolated from one another such that fluid in one lumen does not flow to or from the other. In operation, fluid flows through the heat exchanging lumen **133**. The temperature and flow rate of the fluid may be varied to change the rate at which heat is being exchanged between the heat exchanger **101** and the surrounding environment (i.e., the tissue in the esophagus when the heat exchanger **101** is inserted therein). In this embodiment, balloon **101** further comprises a shaping lumen **132**. Shaping lumen **132** may be supplied with a separate fluid (e.g., air or water) which inflates the shaping lumen **132** to its inflated form. Unlike the heat exchanging lumen **133**, fluid need not flow through the shaping lumen **132** in order for the shaping lumen **132** to perform its function. Once inflated, it is possible to maintain the shape of the shaping lumen **132** without providing any fluid flow. Thus, the shape of balloon **101** may be controlled independently from the fluid flow rate and pressure inside the

heat exchanging lumen **133**. Those skilled in the art will appreciate that this allows greater flexibility in varying the parameters to arrive at an appropriate rate of heat exchange.

(123) Tubular Heat Exchanger

(124) In another embodiment of the heat exchanger, the cavity for circulation of fluid is an arrangement of thermally conductive tubes. The tubes are preferably arranged to fill a cross-sectional area with outside dimensions similar to the collapsed state of a human esophagus.

(125) In some embodiments, the tubes are arranged in coils. FIG. **12** illustrates a tubular heat exchanger **102** having coils **115**. The profile of the tubular heat exchanger **102** of FIG. **12** is circular.

(126) In some embodiments, the tubes are arranged in parallel and in a circular orientation, such as in the example of tubular heat exchanger **102** FIG. **13**. The tubular heat exchanger **102** of FIG. **12** includes a number of exposed tubes **129** while alternative embodiments may include separate lumens in a single tube (not shown).

(127) In some embodiments, the tubes **129** are arranged in a helix (e.g. FIG. **14**. Helical-tube heat exchanger). In FIG. **14**, each tube **129** is spiral-shaped and is helically arranged adjacent to other spiral-shaped tubes. In the embodiments shown in FIGS. **13** and **14**, heat exchanger **102** further comprise a pair of end portions **130**. Each of the tubes **129** are fixed between the two end portions **130** to maintain the relative orientation between the tubes.

(128) Each of the embodiments illustrated in FIGS. **12**, **13**, and **14** comprise a circular cross-sectional profile. More preferably, the cross-sectional profile of the heat exchanger **102** is oblong to better conform to the cross-sectional area of the inside of a collapsed human esophagus. Examples of such embodiments are illustrated in FIGS. **31**, **32**, and **33**.

(129) Some alternative embodiments have a serpentine-shaped tube, such as shown in FIG. **15**.

(130) Typically, the surface of the heat exchanger is thermally conductive to facilitate the transfer of heat at the desired treatment zone. In some examples, the surface is a film substantially thin enough to allow transfer of thermal energy, e.g. with a thickness between around 0.001" to around 0.003". In some alternate embodiments, the surface is made of a thermally conductive material, such as metal foil.

(131) To further promote heat exchange, a thermally conductive gel or coating may be applied to the heat exchanger, or to the target tissue site. This may fill any gaps that might exist between the tissue and the heat exchanger.

(132) Method of Using the Heat Exchanging Fluid Device

(133) A method of regulating a temperature of an esophagus when heat or cold is delivered to a left atrium (FIG. **26**) includes the steps of: (1) measuring the esophagus and selecting a size of a heat exchange device which fits the esophagus; (2) delivering the heat exchange device to a target site; (3) confirming a desired location of the heat exchange device; (4) exchanging heat with the esophagus; (5) confirming that the target site is protected; and (6) retrieving the heat exchange device.

(134) The steps of the method are described in more detail herein below.

(135) Step 1: Measuring the Esophagus and Selecting a Size of a Heat Exchange Device which Fits the Esophagus

(136) The esophagus is measured in order to select the appropriate device size for the patient. Ways of doing this include: (a) Using an internal measurement device. One example is a device that expands until optimal force, impedance, or another parameter indicative of size is measured by the device. Another technique is inserting a series of devices of different sizes into the esophagus until adequate force, impedance, or other parameter is measured by the device. (b) Using imaging, such as fluoroscopy, CT, MRI, EAM, etc. Measurements of the anatomy can be taken using methods known to those skilled in these areas of imaging. (c) Using a combination of internal measurement devices and imaging. For example, inserting devices of different sizes into the esophagus and viewing them with an imaging modality to determine proper fit. Another technique is inserting an

internal ruler device into the esophagus and taking measurements with the imaging system. (d)

Estimating the size of the esophagus based on external anatomical features.

(137) Once the esophagus size is known, the heat exchange device of best fit can be chosen from a selection of devices that cover the range of most anatomical variations.

(138) Step 2: Delivering the Heat Exchange Device to a Target Site

(139) Delivering the heat exchange device to the target site in the esophagus includes inserting it through a small orifice such as the mouth or nostril, and then advancing the heat exchange device through tortuous path defined by the esophagus until the heat exchange device is positioned at the posterior aspect of the left atrium. A number of features enable the heat exchange device to enter a small orifice.

(140) The heat exchanger may be collapsible, foldable, and wrappable such that it can be delivered through a substantially round hole with a diameter of about 0.2 cm to about 0.6 cm. In one embodiment, the heat exchanger is a balloon that can be deflated and wrapped or folded around a main shaft such that it can be delivered to the desired treatment area through a small orifice. Some embodiments of the heat exchange device **100** have an outer diameter equal to or less than 18F.

(141) In an alternate embodiment, the heat exchanger is made of tubes that can be twisted, pulled, or otherwise re-arranged such that they maintain an outer diameter in the desired range and be delivered through a small orifice. Alternately, the tubes themselves may collapse when they are evacuated.

(142) Alternately, the heat exchange device could have a folding or collapsing metal structure such as a stent-like configuration (see FIG. 20).

(143) The delivery orifice may be an access point on the patient, such as the nasal or oral passageway. Alternately, the delivery orifice may be a delivery tube. Once collapsed, the heat exchanger can be loaded inside the delivery tube, and the delivery tube delivered through an access point on the patient. Typical embodiments of the heat exchange balloon may be tapered at the ends to promote gradual dilation of the small orifice. Once in the desired treatment area, the heat exchanger (the balloon) can then be advanced to exit the tube. Alternately, instead of advancing the heat exchanger (the balloon) out of the delivery tube, the delivery tube could be retracted to expose the heat exchanger.

(144) In addition to the above features, the delivery of the heat exchange device may be augmented by the addition of a lubricious coating on the outside surface of the heat exchange device or on the inner surface of the small orifice.

(145) In order to advance the heat exchange device along a tortuous path, the flexibility of the device may be modifiable with a selection of features: (a) varying stiffness along the body of the device, and (b) bend points built into the device. For example, instead of a singular heat exchange balloon there may be a number of heat exchange balloon in series along the body of the device, with bend points between them. Alternately, there may be spring-like joints or bendy-straw style joints at desired bend points along the body of the device.

(146) To overcome the difficulty of navigating a flexible device along a tortuous path, the heat exchange and temperature sensing device may have a selection of features: (a) steerable portions, (b) weighted portions, and/or (c) a stylet that may be removable. The stylet may be super-elastic, have a shape-set memory, may be steerable, or may change the shape of the heat exchange device as it is advanced and retracted within.

(147) To avoid mechanical injury to tissue, the heat exchange device may have features to promote atraumatic delivery. These features may include floppy portions, tapered ends, soft portions, steerable portions, and a soft covering sheath.

(148) If the heat exchange device is collapsed/folded/wrapped, it must be expanded once it reaches the target location of the esophagus. The heat exchange device may be expanded in a number of ways: (a) Expanded with pressure, such as with a balloon or tubes inflated with heat exchange fluid. In some embodiments, the device may operate at more than one pressure. For example, fluid

provided at a first higher pressure may be used to expand or inflate the balloon or tube. Once the balloon or tubes have been expanded, the heat exchange device may operate at a lower pressure so that the balloon or tubes are less rigid. A balloon or tubes which are less rigid are more likely to make good contact with the esophagus while minimizing displacement of the esophagus. (b) Expanded with shape memory. The heat exchange device may employ shape memory metals or polymers that may be expanded into the desired shape through thermal or electrical activation. (c) Expanded with a mechanical mechanism, such as with a stent-like configuration. (d) With any of these expansion methods, the heat exchange device may expand to perforate a delivery sheath that was holding the folded/collapsed/wrapped portions within.

Step 3: Confirming a Desired Location of the Heat Exchange Device

(149) Once the heat exchange device has been delivered to the target site and expanded (if required) the user confirms that the device is in the correct location. This may be achieved by a number of means: (a) Device visualization relative to known anatomical markers. This can be achieved by having markers on the device, such as a ruler on the device body, orientation markers on the device body or handle, electrodes visible on an EAM system, or radiopaque markers on the device body (see item **153** in FIG. **29**), handle or stylet visible on fluoroscopy. Visualization of markers can be used to confirm the position and orientation of heat exchange device **100**. Markers are located on the heat exchange device such that they do not interfere with the desired use of the device, for example, located on the posterior aspect of the heat exchanger.

(150) FIG. **65** illustrates apparatus for a method of confirming the location of the heat exchange device. In a balloon **101** with cooled water flowing in it, there is a temperature gradient from the inlet to the outlet. This gradient is due to the heating added to the fluid from the tissue touching the balloon. In the example of FIG. **65**, the cooling fluid flows from left (the inlet end) to right (the outlet end) whereby the fluid flow **235** is cooler on the left and warmer on the right. FIG. **65** further illustrates radiopaque markers **221** which under imaging allow a user to identify the regions of Zone **1**, Zone **2**, and Zone **3**, wherein Zone **1** is the coolest zone and Zone **3** is the warmest zone. Typically each zone has a temperature sensor associated with it. Such temperature sensors could be attached to balloon **101** within the zones; or temperatures could be determined by other means. The temperature sensors for the different zones are typically independent of each other. Depending on the case, the user may wish to adjust the cooling at a particular site (e.g. the zone closest to ablation does not have the desired temperature) by moving the balloon. The different cooling zones can be identified with radiopaque markers **221** and viewed under imaging. The user may then utilize the cooling zones by adjusting the position of the balloon (if needed) to achieve the desired cooling. The above example relates to heat ablation procedures. In the case of a cryoablation procedure, the gradient would be reversed, but the same method could be applied. Alternative embodiments have two, four, or more zones. (b) Measurement of a physiological parameter. Some embodiments of the heat exchange device are capable of measuring a physiological parameter indicative of location in the body through the use of sensors or electrodes. Examples of the parameter which may be measured include ECG, tissue impedance, temperature, blood perfusion rate, oxygen saturation, and others.

Step 4: Exchanging Heat with the Esophagus

Option 1: Using a Heat Exchanging Fluid Device

(151) As discussed above, heat may be exchanged within the esophagus using a heat exchange fluid device, such as those embodiments described above in the section titled “Heat Exchange Fluid Device”. In one embodiment, the fluid used in the device is comprised substantially of water. For example, the fluid may be distilled water or saline. Alternatively, the fluid may be a substance that is not substantially water, such as an oil based or petroleum product. In addition, the fluid may contain additives, for example a disinfectant, or stabilizer. The temperature, flow rate, and pressure of the fluid is managed through an external controller which includes a pump.

(152) In operation, fluid flows through an inlet port into the heat exchanger of the heat exchanging

fluid device and circulates through the body of the heat exchanger. An outlet port is also provided to allow fluid to flow out of the heat exchanger. Fluid may continuously flow through the heat exchanger so that there is continuous heat exchange with the esophagus.

(153) Option 2 for Exchanging Heat: Open Irrigation

(154) In an alternate embodiment (e.g. FIG. 25 open irrigation of fluid with suction), the heat exchange fluid **125** is delivered directly to the desired treatment zone in an open-irrigated system. In one embodiment, the heat exchange device **100** is connected to an external controller that provides the heat exchange fluid **125**. The fluid is delivered through a fluid spray tube **122** and sprayed circumferentially toward the endoluminal surface of the esophagus. Fluid is removed using fluid suction tube **123**. In typical embodiments, the tube has multiple holes along its length and around its circumference in order to deliver an even spray of fluid to the desired treatment zone. In one embodiment, the fluid is allowed to travel through the esophagus to the stomach. Alternately, in some embodiments, the esophagus is blocked by an esophageal blocking balloon **124**, and the fluid is collected cranial to the blocking balloon **124** and suctioned from the esophagus.

(155) A further alternative embodiment is depicted in FIGS. 51-53. Similar to the embodiment depicted in FIG. 25, heat exchange fluid **125** is delivered directly to the desired treatment zone. The irrigation heat exchanger **136** delivers heat exchange fluid through an irrigation surface **137** with a series of irrigation ports **138** from which heat exchange fluid is sprayed. The heat exchanger **136** may further comprise a proximal blocking balloon **142** and a distal blocking balloon **143** which prevents fluid from escaping into the stomach or the larynx respectively. The heat exchanger **136** may further comprise a distal suction component **140** and a proximal suction **141** component which captures fluid after it has been sprayed from the irrigation ports **138**. The heat exchanger **136** may be connected to or integral with a tube **139**. Tube **139** may comprise an inlet tube and outlet tube (not depicted) for supplying fluid to and removing fluid from the desired treatment zone. The other end of tube **139** may be connected with an external controller that provides heat exchange fluid **125**.

(156) Option 3 for Exchanging Heat: Using a Thermoelectric Heat Exchange Device

(157) In some embodiments, the heat exchanger is a Peltier device which may heat or cool the esophagus with thermoelectric heat exchange. The heat exchange device is connected to an external controller that powers the Peltier device.

(158) Option 4 for Exchanging Heat: Using an Evaporative Cooling Device

(159) An alternate method of cooling the esophagus is to deliver a coolant directly to the endoluminal surface of the esophagus. In one embodiment, the heat exchange device is connected to an external controller that provides the coolant. The coolant is sprayed in a mist mixed with a gas such as air or oxygen to the surface of the esophagus. The coolant rapidly evaporates due to the gas flow. The esophageal surface is cooled as a result of the evaporation.

(160) Option 5 for Exchanging Heat: Using a Vortex Tube Heat Exchange

(161) Some embodiments of the heat exchanger make use of a vortex tube, a mechanical device that separates a compressed gas into a hot stream and a cold stream. Either stream could be used for heat exchange, so this type of heat exchanger could be used to either warm or cool the esophagus.

(162) Option 6 for Exchanging Heat: Endothermic/Exothermic Chemical Reaction.

(163) Step 5: confirming that the target site is protected

(164) Once the heat exchanger is positioned at the target site and adequate heat exchange is occurring between the esophagus and the heat exchanger, the user confirms that the tissue is protected. There are a number of options to make this confirmation: (a) Imaging modalities such as MRI or ultrasound may be used to monitor tissue changes in the esophagus. An absence of lesion growth or tissue changes supports the lack of tissue damage. (b) Monitoring a physiological parameter indicative of tissue viability/health. Examples of physiological parameters may include temperature, tissue impedance, blood perfusion rate, oxygen saturation, or nerve function (for example vagus or phrenic nerve). Some embodiments of the heat exchange device comprise a

means to measure these parameters. The heat exchange device may be connected to an external controller that interprets/displays/analyses the signals produced from the heat exchange device. The measured physiological parameters may be used in a control loop to alert the user of unsafe levels. The control loop may be connected to the ablation therapy device to stop ablation before a critical level is reached. The control loop may include a mathematical model of changes in the physiological parameter that can predict when irreversible damage may occur, and stop the ablation energy before the dangerous levels are reached.

(165) There are a number of options for measuring temperature. The temperature measured may be one of a number of temperatures, including the temperature of the desired treatment area, or the patient's core body temperature. Temperature may be measured by any of a number of sensors, including thermocouples, thermistors, fiber optics, or by another method such as ultrasound, MRI, infrared, or microwave radiometry.

(166) In one embodiment, the means of measuring temperature is affixed to the heat exchange surface. For example, individual thermocouple pairs, or a flexible circuit containing thermocouples and/or thermistors, or a fiber optic cable may be affixed to the surface of the heat exchanger with adhesives. Alternately, the temperature sensors may be spray or dip coated onto the surface of the heat exchanger with a flexible material such as urethane. Alternately, the temperature sensors may be laminated onto the surface of the heat exchange surface with a thin film, or they may be laminated between two thin film layers, which may then be used to create the heat exchanger. Alternately, the temperature sensors may be positioned inside pockets welded to the surface of the heat exchanger. When positioned on the surface of the heat exchanger, the temperature sensors measure the temperature of the desired treatment area once the heat exchanger makes contact with the desired treatment area (e.g. FIG. 18. Temperature sensors **104** affixed to balloon surface of balloon heat exchanger **101**).

(167) In another embodiment, the temperature sensors are drawn onto the surface of the balloon with conductive ink. For example, the temperature sensors of some embodiments are thermocouples made by crossing a line of conductive silver ink with a line of conductive nickel ink.

(168) In another embodiment, the temperature sensors are affixed to the shaft with adhesives, thermal welding, or another means. For example, a temperature sensor may be added to the distal end of the shaft, which is positioned in the patient's stomach to monitor core body temperature.

(169) In another embodiment, the temperature sensors **104** are mounted on a structural frame **117** that is separate from the heat exchanger. For example, the structural frame **117** may be made of expandable and collapsible struts that can be deployed around the heat exchanger to measure the temperature of the desired treatment area (e.g. FIG. 19 temperature sensors mounted on structural frame separate from heat exchanger). The struts may be in one of a number of configurations, such as linear (top of FIG. 19), helical (bottom of FIG. 19), intersecting, or asymmetrical. The struts may be expanded and collapsed with the use of a mechanical mechanism such as a pull wire. The struts may be made of a number of materials, for example, a flexible metal such as Nitinol, or a plastic such as Pebax, or a shape memory alloy or shape memory polymer. The shape memory polymer may be activated to take on the desired shape by thermal or electrical inputs.

(170) In another embodiment, the struts may be part of the shaft. The embodiment of FIG. 20 includes temperature sensors **104** mounted on struts **118** made from main shaft **103**.

(171) As previously mentioned, the balloon heat exchanger is more preferably oblong to better conform to the cross-sectional area of the collapsed esophagus and reduce the resulting displacement of the esophagus. Accordingly, the embodiments illustrated in FIGS. 19 and 20 may be provided with a more oblong cross-sectional shape. For example, FIGS. 36 and 37 illustrate further embodiments comprising tubes **129** and temperature sensors **104** which feature a more oblong cross-sectional profile.

(172) In another embodiment, the temperature sensors **104** are affixed to or woven into a textile

119 (i.e. a fabric material) that surrounds the heat exchanger (e.g. FIG. **21** temperature sensors affixed to textile). When the heat exchanger is expanded into its desired shape, the fabric may expand around it, allowing the temperature sensors to make contact with and measure the temperature of the desired treatment area.

(173) In another embodiment, the temperature sensors **104** are affixed to strands **120** connected at one end of the heat exchanger so that they hang freely about the other end of the heat exchanger. The example of FIG. **22** includes temperature sensors **104** affixed to strands **120** which are attached to main shaft **103**. Strands **120** are flexible and atraumatic such that as they are advanced through the esophagus, the esophagus is not damaged.

(174) In order to obtain meaningful temperature data, an array of temperature sensors may be used to measure a plurality of temperatures. The sensors may be positioned in such a way that an algorithm may be used to interpolate the temperatures between the sensors in order to produce a temperature map of the esophageal surface. Alternately, a temperature map may be produced using IR or microwave temperature measuring modalities.

(175) One concern some users may have with respect to the sensors is what is known as the antenna effect. There is some published literature indicating that metal electrodes in the esophagus may promote thermal injury as a result of electrical or thermal interactions with the ablation catheter. To eliminate this risk, the electrodes on some embodiments of the heat exchange device are insulated, or made of a non-conductive material. Alternately, the electrodes may be positioned such that the electrical or thermal interactions will not affect them, for example, the electrodes may be located on the posterior wall of the heat exchanger so that the heat exchanger insulates the electrodes from the interactions. In addition, filters may be built into the external device where the signals are interpreted and displayed to eliminate these interactions.

(176) Step 6: Retrieving the Heat Exchange Device

(177) After treatment, the heat exchanger is typically collapsed for removal from the patient. In one embodiment, the heat exchanger is evacuated by pulling a vacuum at the outlet port or the inlet port. Once evacuated, the heat exchanger can be pulled back through the delivery orifice and removed from the patient. In alternative embodiments, the heat exchanger is collapsed using a sleeve around the heat exchanger. This sleeve may comprise a fabric mesh structure, a metal structure, such as a structure similar to a stent, or a polymer cage. In some embodiments the sleeve is a sheath. In one embodiment, the sleeve is collapsed using a mechanical mechanism. In another embodiment, the sleeve is collapsed using shape memory material properties.

(178) Once the heat exchanger is collapsed, the heat exchange device may be pulled into the delivery orifice, or the delivery orifice may be advanced over the heat exchange device. The heat exchange device may be inverted (inside-out) as it is pulled into the delivery orifice. In some embodiments of the method, the delivery orifice is the patient's nose or mouth. In another embodiment, the delivery orifice is a sheath separate from the device. The sheath may have a telescoping feature. The sheath may be integrated with the heat exchange device. For example, it may comprise expanding and contracting struts that are part of the body of the heat exchange device, or it may be a translating portion of the heat exchange device body.

(179) Once inside the delivery orifice, the heat exchange device is removed from the patient.

(180) Patient's Body Core Temperature

(181) The user may be concerned about affecting the patient's core body temperature as a result of exchanging heat in the esophagus. There are a number of optional features and surgical techniques to mitigate this risk. (a) Focus heat exchange at areas of highest risk. This may be achieved by monitoring a physiological parameter at different locations on the esophagus and using a control loop in the external controller to determine the high-risk areas and focus heat exchange in those areas. (b) Counteract heat exchange at esophagus with opposite and optionally equal heat exchange at another body location. This may be achieved by measuring the amount of heat exchanged by the heat exchange device in the esophagus and using a separate device (such as a warming or cooling

blanket) to exchange an equal and opposite amount of heat at a location distinct from the esophagus. A control loop may be used to automatically balance the heat exchanged. Alternatively, the heat exchange device may be used to supply opposite and optionally equal heat exchange while the ablation therapy is not being applied. (c) Only exchange heat at the esophagus while an ablation is being performed. This may be achieved by a communication link between the ablation therapy device and the heat exchange device. The heat exchange device is activated only when the ablation therapy is applied. (d) Some embodiments of the device may comprise the following insulative features at the non-therapy areas to minimize overall heat exchange and focus heat exchange only in the target area: (i) a coating of insulative material, (ii) an insulating lubricant or gel, (iii) an air filled lumen or space, or (iv) an air filled balloon inside (or outside) of the heat exchanger. FIG. 23 illustrates a balloon heat exchanger **101** with an insulating balloon **121** on the inside. FIGS. 24 and 34 illustrates a balloon heat exchanger **101** with an insulating balloon **121** on the outside.

In an ablation procedure, the “non-therapy area” is the side of the esophagus farthest away from the heart. By insulating the side of the esophagus farthest away from the heart, the heat exchange directed away from the “non-therapy area” and focused on the target area, which is the side of the esophagus closest to the heart. FIG. 34 illustrates another embodiment of a heat exchanger **101** which comprises an insulating portion **131**. The insulating portion **131** may comprise one or more of an insulating lubricant or gel, a coating of insulating material, or air.

FIG. 64 illustrates the example of air pockets around the shaft tubing of the balloon catheter minimizing heat loss at a non-therapy area. The outer layer **232** of tubing **230** insulates the shaft by creating air pockets **233** between the outer layer **232** and the inner layer **231** (which surrounds fluid pathway **235**). The air pockets **233** reduce the cooling of the mouth and the part of the esophagus which is not in the ablation area, thereby increasing the thermal efficiency of the design. (e)

Monitoring core body temperature. The heat exchange device may have a temperature sensor at a location away from the heat exchange area to monitor core body temperature. For example, in some embodiments the temperature sensor is at the distal end of the device and is positioned in the patient's stomach. A control loop may be used to feedback the patient's core temperature to the user and alert the user of dangerous temperatures. Alternately, the control loop could be used to control the amount of heat being exchanged in the patient. (f) Determining a safe heat exchange operating range based on patient characteristics, the bio-heat equation, and other pertinent information. Some embodiments of the method include monitoring the amount of heat exchanged by the heat exchange device and confirming that it does not exceed the calculated safe amount.

(182) These techniques can be performed during step 4 (FIG. 26) of the above described method.

(183) Ablation Therapy

(184) It is also important that an ablation therapy is not adversely affected by the heat exchange at the esophagus. To eliminate this risk, the user may monitor lesion growth or a physiological parameter at the therapy site using methodologies described above. A feedback loop may also be used to maximize the therapeutic energy delivered while the esophagus is not in danger. This may be achieved by monitoring a physiological parameter indicative of tissue health/viability as described above, and using that data in a control loop to stop or decrease ablative therapy when the esophageal tissue is in danger, and increase/optimize ablative therapy when the esophageal tissue is not affected. The data may also be used to focus the heat exchange at high risk areas in the esophagus to minimize the impact on the therapeutic energy delivery. The data may also be used to decrease or stop the heat exchange during ablations when the esophagus is not at risk. These techniques can be performed during step 4 (FIG. 26) of the above described method.

(185) Other Steps

(186) Other additional steps in the method may include pacing the heart and performing a cardiac EP exam using the heat exchange device. To facilitate these steps, some embodiments of the heat exchange device comprise pacing and ECG electrodes on the body of heat exchange device. This technique can be performed during step 3 (FIG. 26) of the above described method.

(187) Injury to an esophagus caused by heat or cold being delivered to the left atrium is prevented by regulating the temperature of the esophagus using embodiments of a heat exchange device having a heating/cooling balloon (or sac) which has an inflated cross section corresponding with the collapsed/relaxed/natural cross section of the inside of the esophagus whereby inflation of the balloon maintains the esophagus in its natural shape and location and avoids not displacing the esophagus towards the left atrium. Some alternative embodiments includes altering a configuration of the balloon to conform to or correspond with the cross section of an esophagus by means other than inflation.

(188) The embodiments of the invention described above are intended to be exemplary only. The scope of the invention is therefore intended to be limited solely by the scope of the appended claims.

(189) It is appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable subcombination.

(190) Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the broad scope of the appended claims. All publications, patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual publication, patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present invention.

EXAMPLES

(191) Example 1. A method of regulating a temperature of an esophagus when heat or cold is delivered to a left atrium comprises altering a heat exchange device from an insertable configuration to a heat exchanging configuration which substantially conforms and corresponds with a cross-section of an inside of the esophagus such that the esophagus is substantially maintained in its natural shape and location whereby the esophagus is substantially not displaced towards the left atrium.

(192) Example 2. A method of regulating a temperature of an esophagus when heat or cold is delivered to a left atrium comprises (a) inflating a heat exchange device from an collapsed configuration to an inflated configuration which substantially conforms and corresponds with a cross-section of an inside of the esophagus such that the esophagus is substantially maintained in its natural shape and location whereby the esophagus is substantially not displaced towards the left atrium and (b) regulating the temperature of the esophagus using the heat exchange device.

(193) Example 3. A method of regulating a temperature of an esophagus when heat or cold is delivered to a left atrium includes the steps of: (1) measuring the esophagus and selecting a size a heat exchange device which fits the esophagus; (2) delivering the heat exchange device to a target site; (3) confirming a desired location of the heat exchange device; (4) exchanging heat with the esophagus; (5) confirming that the target site is protected; and (6) retrieving the heat exchange device.

(194) Example 4. The method of example 3, wherein step (1) comprises using imaging such as fluoroscopy, CT, MRI, or EAM.

(195) Example 5. The method of example 3, wherein the heat exchange device comprises a balloon and a main shaft, and the method includes, before step (2), the step of deflating or collapsing the balloon and wrapping or folding the balloon around the main shaft.

(196) Example 6. The method of example 3, wherein the heat exchange device comprises a balloon, and the method includes, before step (2), the step of priming the heat exchange device to

replace air with fluid.

(197) Example 7. The method of example 3, wherein step (2) comprises advancing the heat exchange device through a nostril.

(198) Example 8. The method of example 3, wherein the heat exchange device further comprises imaging markers and step (2) includes using an imaging system to position the heat exchange device.

(199) Example 9. The method of example 3, wherein step (2) comprises advancing an outer sheath with the heat exchange device and pulling back on the outer sheath when the heat exchange device is positioned to expose the heat exchange device.

(200) Example 10. The method of example 3, wherein step (3) comprises confirming an orientation of the heat exchange device relative to a known anatomical marker by imaging of imaging markers on the heat exchange device.

(201) Example 11. The method of example 10, wherein the known anatomical marker is the left atrium.

(202) Example 12. The method of example 3, wherein step (4) includes begin circulating a heat exchange fluid through the heat exchange device before heat or cold is delivered to the left atrium.

(203) Example 13. The method of example 12, wherein step (4) includes stop circulating the heat exchange fluid through the heat exchange device after heat or cold is delivered to the left atrium.

(204) Example 14. The method of example 3, wherein step (5) comprises imaging of a tissue of the esophagus to determine if the tissue has been changed.

(205) Example 15. The method of example 3, wherein step (5) comprises monitoring a physiological parameter which indicates a health factor of a tissue of the esophagus.

(206) Example 16. The method of example 13, wherein prior to step (6), the method includes vacuuming the heat exchange fluid from the heat exchange device.

(207) Example 17. The method of example 9, wherein prior to step (6), the method includes advancing the outer sheath to cover the heat exchange device, thereby reducing a diameter of the heat exchange device.

(208) Example 18. The method of example 3, wherein step (6) includes removing the heat exchange device from a patient.

(209) Example 19. A method of monitoring a temperature of a tissue of an esophagus includes (a) inflating a device from an collapsed configuration to an inflated configuration which conforms and corresponds with a cross-section of an inside of the esophagus such that the esophagus is maintained in its natural shape and location whereby the esophagus is not displaced towards a left atrium and (b) monitoring the temperature of the tissue using sensors on an outside of the device.

(210) Example 20. The method of example 19, wherein step (b) comprises using sensors on one side of the device.

Claims

1. A heat exchanging device for regulating a temperature of an esophagus when heat or cold is delivered to a left atrium of a heart, comprising: an elongated shaft comprising a distal end and a proximal end, the elongated shaft defining at least a first lumen and a second lumen; a heat exchanger attached to the distal end of the elongated shaft, the heat exchanger comprising an insertable configuration, a heat exchanging configuration, a distal end, a proximal end, and a cavity therebetween, at least a portion of said cavity being in fluid communication with the first lumen and the second lumen of the elongated shaft; wherein a cross-section of the heat exchanger in the insertable configuration is smaller than a cross-section of the heat exchanger in the heat exchanging configuration, wherein said cross-section of the heat exchanger in the heat exchanging configuration substantially conforms to and corresponds with a cross-section of an inside surface of the esophagus such that the esophagus is substantially maintained in its natural shape and location

when the heat exchanger is in its heat exchanging configuration, and wherein said shape of the heat exchanger is constrained by a weld pattern, wherein the weld pattern comprises at least one weld, and wherein said at least one weld attaches at least part of an anterior surface of the heat exchanger and a posterior surface of the heat exchanger.

2. The heat exchanging device of claim 1, wherein the at least one weld comprises a plurality of welds which are oriented as a series of consecutive chevrons along a length of the heat exchanger.

3. The heat exchanging device of claim 2, wherein at least one chevron of the series of consecutive chevrons is comprised of a pair of welds which are generally curved in shape with hook-shaped ends.

4. The heat exchanging device of claim 1, wherein the elongated shaft is a multi-lumen tube which defines an inlet lumen and a first outlet lumen, said inlet lumen comprises a fluid inlet port to allow heat exchange fluid to flow into said heat exchanger and said first outlet lumen comprises a fluid outlet port to allow heat exchange fluid to flow out of said heat exchanger.

5. The heat exchanging device of claim 4, further comprising a second outlet lumen.

6. The heat exchanging device of claim 4, wherein the first outlet lumen has a larger diameter than the inlet lumen.

7. The heat exchanging device of claim 1 further comprising a radiopaque material positioned on the heat exchanger.

8. The heat exchanging device of claim 7, wherein the heat exchanger is comprised of at least one balloon.

9. The heat exchanging device of claim 8, wherein the radiopaque material defines a bordering frame on a side of the heat exchanger, wherein the bordering frame borders at least a portion of a surface of the side of the heat exchanger.

10. The heat exchanging device of claim 8, wherein the radiopaque material is configured to indicate which side of the balloon is facing a heart of a patient.

11. The heat exchanging device of claim 7, further comprising at least one temperature sensor on a side of the heat exchanger and the radiopaque material being configured to indicate which direction the at least one temperature sensor is facing.

12. The heat exchanging device of claim 1, wherein the first lumen is a fluid inlet tube and an inner layer of the fluid inlet tube defines an inlet fluid pathway, and the elongated shaft defines a series of air pockets surrounding the inlet fluid pathway to thereby thermally insulate the fluid inlet tube.

13. The heat exchanging device of claim 12, wherein an outer layer of the fluid inlet tube and the inner layer of the fluid inlet tube define the series of air pockets therebetween.

14. The heat exchanging device of claim 1, wherein the second lumen is a fluid outlet tube and an inner layer of the fluid outlet tube defines an outlet fluid pathway, and the elongated shaft defines a series of air pockets surrounding the outlet fluid pathway to thereby thermally insulate the fluid outlet tube.

15. The heat exchanging device of claim 14, wherein an outer layer of the fluid outlet tube and the inner layer of the fluid outlet tube define the series of air pockets therebetween.

16. The heat exchanging device of claim 1, wherein the heat exchanging device further comprises an outer balloon surrounding the heat exchanger.

17. The heat exchanging device of claim 16, wherein the elongated shaft comprises an inner lumen which is in fluid communication with the outer balloon of the heat exchanger and an outer lumen which is in fluid communication the outer balloon.

18. A heat exchanging device for regulating a temperature of an esophagus when heat or cold is delivered to a left atrium of a heart, comprising: an elongated shaft comprising a distal end and a proximal end, the elongated shaft defining at least a first lumen and a second lumen; a heat exchanger attached to the distal end of the elongated shaft, the heat exchanger comprising an insertable configuration, a heat exchanging configuration, a distal end, a proximal end, and a cavity therebetween, at least a portion of said cavity being in fluid communication with the first lumen

and the second lumen of the elongated shaft; wherein a cross-section of the heat exchanger in the insertable configuration is smaller than a cross-section of the heat exchanger in the heat exchanging configuration, wherein said cross-section of the heat exchanger in the heat exchanging configuration substantially conforms to and corresponds with a cross-section of an inside surface of the esophagus such that the esophagus is substantially maintained in its natural shape and location when the heat exchanger is in its heat exchanging configuration, and wherein said shape of the heat exchanger is constrained by a weld pattern, wherein the weld pattern comprises at least one weld, and wherein said at least one weld attaches at least part of an anterior surface of the heat exchanger and a posterior surface of the heat exchanger; wherein the heat exchanger comprises a first zone and a second zone which can be identified under imaging, the first zone having a first temperature sensor and the second zone having a second temperature sensor, whereby the heat exchanging device is operable to be moved such that a selected zone with a preferred temperature is adjacent to a heart of a patient.

19. A heat exchanging device for regulating a temperature of an esophagus when heat or cold is delivered to a left atrium of a heart, comprising: an elongated shaft comprising a distal end and a proximal end, the elongated shaft defining at least a first lumen and a second lumen; a heat exchanger attached to the distal end of the elongated shaft, the heat exchanger comprising an insertable configuration, an expanded heat exchanging configuration, a distal end, a proximal end, and a cavity therebetween, at least a portion of said cavity being in fluid communication with the first lumen and the second lumen of the elongated shaft; wherein a cross-section of the heat exchanger in the insertable configuration is smaller than a cross-section of the heat exchanger in the heat exchanging configuration, wherein said cross-section of the heat exchanger in the heat exchanging configuration substantially conforms to and corresponds with a cross-section of an inside surface of the esophagus such that the esophagus is substantially maintained in its natural shape and location when the heat exchanger is in its heat exchanging configuration, wherein the heat exchanger moves from the insertable configuration to the heat exchanging configuration by inflating the cavity with heat exchange fluid, and wherein said shape of the heat exchanger is constrained by a weld pattern.

20. The heat exchanging device of claim 19, wherein the weld pattern comprises a plurality of welds that attach at least part of an anterior surface of the heat exchanger and a posterior surface of the heat exchanger to create multiple flow channels that extend along a length and width of the heat exchanger.
