

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399695
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Ishikawa; Tomoyasu et al.

Vehicle control device, program update method, and program update system

Abstract

A vehicle control device includes a memory having a first storage area for storing a program related to vehicle control and a second storage area for storing an update program for updating the program, and a controller configured to determine whether a vehicle is in a stop state and start an update process of updating the program stored in the first storage area with the update program stored in the second storage area when the controller determines that the vehicle is in the stop state.

Inventors:	Ishikawa; Tomoyasu (Nagoya, JP), Ariga; Takanori (Nagoya, JP)
Applicant:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Family ID:	1000008782541
Assignee:	TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)
Appl. No.:	17/071086
Filed:	October 15, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210132937 A1	May. 06, 2021

Foreign Application Priority Data

JP	2019-198783	Oct. 31, 2019
----	-------------	---------------

Publication Classification

Int. Cl.: G06F8/65 (20180101); H04W4/44 (20180101)

U.S. Cl.:

CPC **G06F8/65** (20130101); **H04W4/44** (20180201);

Field of Classification Search

CPC: G06F (8/65); H04W (4/44); B60R (16/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10394548	12/2018	Fox	N/A	G06F 12/0646
10884902	12/2020	Kislovskiy	N/A	G06F 11/0706
10913451	12/2020	Li	N/A	B60W 50/0225
11204750	12/2020	Tatourian	N/A	H04W 4/44
12045551	12/2023	Fox	N/A	G06F 11/3692
2008/0204358	12/2007	Sato	348/E5.002	H04N 21/654
2017/0134164	12/2016	Haga	N/A	B60R 16/023
2017/0262277	12/2016	Endo	N/A	H04L 67/04
2018/0074811	12/2017	Kiyama	N/A	H04L 67/12
2018/0152341	12/2017	Maeda	N/A	H04L 41/082
2019/0193653	12/2018	Nakamura	N/A	G06F 9/4893
2019/0212732	12/2018	Takanashi	N/A	G05D 1/0061
2019/0250902	12/2018	Tateishi	N/A	G06F 8/654
2019/0286454	12/2018	Sano	N/A	B60R 16/0231
2019/0324458	12/2018	Sadeghi	N/A	G05D 1/0276
2019/0332371	12/2018	Kobayashi	N/A	G07C 5/008
2020/0114927	12/2019	Yokota	N/A	B60W 50/00
2020/0387368	12/2019	Jeong	N/A	G06F 8/65
2021/0011711	12/2020	Ogawa	N/A	G06F 8/62
2021/0165649	12/2020	Harata	N/A	G06F 3/0679
2021/0309237	12/2020	Sekiguchi	N/A	G06F 11/1433
2021/0349709	12/2020	Nakatsukasa	N/A	G06F 8/656

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107533491	12/2017	CN	N/A
108701065	12/2017	CN	B60R 16/02
109643254	12/2018	CN	N/A
2011-148398	12/2010	JP	N/A
2015-101229	12/2014	JP	N/A
2017-097620	12/2016	JP	N/A
2017-134506	12/2016	JP	N/A
2018-037059	12/2017	JP	N/A
2018-045515	12/2017	JP	N/A
2018-086894	12/2017	JP	N/A
2018-100002	12/2017	JP	N/A
2019-020866	12/2018	JP	N/A
WO 2018/230314	12/2017	WO	N/A

Primary Examiner: Wu; Daxin

Attorney, Agent or Firm: Oblon, McClelland, Maier & Neustadt, L.L.P.

Background/Summary

INCORPORATION BY REFERENCE

(1) The disclosure of Japanese Patent Application No. 2019-198783 filed on Oct. 31, 2019 including the specification, drawings and abstract is incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

(2) The present disclosure relates to a vehicle control device, a program update method, and a program update system.

2. Description of Related Art

(3) A vehicle is equipped with a plurality of control devices called electronic control units (ECUs). Each of the control devices such as the ECUs includes a memory in which one or more programs executed by one or more controllers such as central processing units (CPUs) are stored, and executes respective functions. To improve the functions of the control devices, it has been proposed to rewrite and update the programs stored in the memories to a newer version. In particular, it has been proposed that the vehicle receives data for updating the programs from an external server via wireless communication so that the programs can be updated without the need to visit a maintenance shop or the like.

(4) Japanese Unexamined Patent Application Publication No. 2011-148398 (JP 2011-148398 A) discloses a program update system for updating a program installed in an ECU mounted on a vehicle. In the system, a management device manages version information and an update file for each vehicle ID. Based on the vehicle ID transmitted from the ECU, the management device transmits the update file to the ECU only when the program installed in the ECU is not the latest version, thereby improving the distribution efficiency.

SUMMARY

(5) When the need to execute a current program arises while updating the current program using the data for updating the program, an update process that is being executed may be required to be interrupted temporarily. When such an interruption in the update process occurs, a time from the start of a program update process to the completion of the program update process becomes long.

(6) The present disclosure provides a vehicle control device, a program update method, and a program update system that can suppress occurrence of an interruption in a program update process.

(7) A first aspect of the present disclosure relates to a vehicle control device. The vehicle control device includes a memory having a first storage area for storing a program related to vehicle control and a second storage area for storing an update program for updating the program, and a controller configured to determine whether a vehicle is in a stop state and start an update process of updating the program stored in the first storage area with the update program stored in the second storage area when the controller determines that the vehicle is in the stop state.

(8) According to the first aspect of the present disclosure, the controller may be configured to derive, after the update program is downloaded from a management server that manages the update program to the second storage area, an update time that is a time estimated to be required from a start of the update process to a completion of the update process. The update time is derived based

on the update program that has been downloaded. The controller may be configured to allow an information terminal that is communicable with the vehicle to display at least the update time when the controller determines that the vehicle is in the stop state after deriving the update time.

(9) According to the first aspect of the present disclosure, the controller may be further configured to allow, when the controller determines that the vehicle is in the stop state after deriving the update time, the information terminal to display a permission request for activating the update process. The controller may be configured to start the update process when the controller receives via the information terminal a permission for activating the update process.

(10) According to the first aspect of the present disclosure, the controller may be configured to acquire at least a state of a power supply of the vehicle as vehicle information and determine that the vehicle is in the stop state when the power supply of the vehicle is off.

(11) According to the first aspect of the present disclosure, the controller may be configured to acquire at least a state of a parking brake as vehicle information and determine that the vehicle is in the stop state when the parking brake is activated.

(12) According to the first aspect of the present disclosure, the controller may be configured to acquire at least a vehicle speed as vehicle information and determine that the vehicle is in the stop state when the vehicle speed is zero.

(13) A second aspect of the present disclosure relates to a program update method. The program update method is performed by a vehicle control device including a memory having a first storage area for storing a program related to vehicle control and a second storage area for storing an update program for updating the program, and a controller. The program update method includes determining, by the controller, whether a vehicle is in a stop state and starting, by the controller, an update process of updating the program stored in the first storage area with the update program stored in the second storage area when the controller determines that the vehicle is in the stop state.

(14) A third aspect of the present disclosure relates to a program update system. The program update system includes a vehicle control device mounted on a vehicle and including a memory having a first storage area for storing a program related to vehicle control and a second storage area for storing an update program for updating the program, and a management server that manages the update program and that communicates with the vehicle so as to allow the update program to be downloaded and stored in the second storage area of the vehicle control device. The vehicle control device is configured to acquire information on the vehicle, determine whether the vehicle is in a stop state based on the information that has been acquired, and start an update process of updating the program stored in the first storage area with the update program stored in the second storage area when the vehicle control device determines that the vehicle is in the stop state.

(15) According to the vehicle control device, the program update method, and the program update system of the present disclosure described above, the program update process is started at a timing when the vehicle is in the stop state so that it is assumed that there is enough time until the execution of the current program is requested. Thus, it is possible to suppress the occurrence of an interruption in the program update process.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Features, advantages, and technical and industrial significance of exemplary embodiments of the present disclosure will be described below with reference to the accompanying drawings, in which like signs denote like elements, and wherein:
- (2) FIG. 1 is a diagram illustrating a configuration example of a program update system to which a control device according to an embodiment of the present disclosure is applied;
- (3) FIG. 2 is a diagram illustrating a configuration example of the control device;

- (4) FIG. 3 is a flowchart of a program update process executed by the control device according to a first example;
- (5) FIG. 4A is an example of a transition in a vehicle state and a start timing of the update process in the first example;
- (6) FIG. 4B is an example of the transition in the vehicle state and the start timing of the update process in the first example;
- (7) FIG. 5A is a flowchart of a program update process executed by a control device according to a second example;
- (8) FIG. 5B is a flowchart of the program update process executed by the control device according to the second example;
- (9) FIG. 6A is an example of a transition in a vehicle state and a start timing of the update process in the second example; and
- (10) FIG. 6B is an example of the transition in the vehicle state and the start timing of the update process in the second example.

DETAILED DESCRIPTION OF EMBODIMENTS

(11) A control device of the present disclosure stores an update program in a storage area that is different from a storage area in which a current program executed during vehicle control is stored, and starts a process of updating the current program with the update program at a timing while a vehicle is in stop state. Thus, it can be expected that there is enough time until the execution of the current program is subsequently requested and it is possible to suppress the occurrence of an interruption in the program update process.

Embodiment

(12) Hereinafter, an embodiment of the present disclosure will be described in detail with reference to the drawings.

(13) Configurations

(14) FIG. 1 is a diagram illustrating a configuration example of a program update system to which a control device according to the embodiment of the present disclosure is applied. A program update system **10** illustrated in FIG. 1 includes a vehicle **100**, a vehicle management server **200**, and a mobile device **300**. The vehicle **100** includes a communication device **110**, a plurality of control devices **120**, and a display device **130**. The communication device **110**, the control devices **120**, and the display device **130** are communicably connected to each other via an in-vehicle network such as a controller area network (CAN). The number of the control devices **120** is not limited.

(15) The communication device **110** is a data communication module (DCM) or the like and is communicably connected to an external device such as the vehicle management server **200** and the mobile device **300** via a wireless network such as the 4th generation mobile system (4G) or Wi-Fi.

(16) The control devices **120** are devices that perform various controls of the vehicle **100**, which are called ECUs, for example. As illustrated in FIG. 2, each of the control devices **120** includes a communicator **121**, a controller **122**, and a memory **123**.

(17) The communicator **121** communicates with the vehicle management server **200** via the communication device **110** of the vehicle **100**, and inquires the vehicle management server **200** on updates and downloads an update program from the vehicle management server **200**. The controller **122** controls processes of the control device **120** including each process (described later) of determination of a vehicle state, program update, update time derivation, and display of update status. The memory **123** stores one or more programs to be executed by the controller **122**. The memory **123** individually has a first storage area **1231** for storing a program (current program) related to vehicle control and a second storage area **1232** for storing an update program which is data necessary for updating the current program.

(18) The first storage area **1231** and the second storage area **1232** of the memory **123** are not limited to the configuration shown in FIG. 2, and may be provided as two physically separate

memories. Not all the control devices **120** of the vehicle **100** need to be program-updatable devices provided with the first storage area **1231** and the second storage area **1232**.

(19) The vehicle management server **200** is a server that manages the update program that is the data used to update the current program of the control devices **120** mounted on the vehicle **100**. The vehicle management server **200** stores the update program for the current program of the control devices **120** in a memory (not shown) and performs wireless communication with the communication device **110** of the vehicle **100** to receive inquiries on the updates from the vehicle **100** and allows the vehicle **100** to download the update programs from the vehicle management server **200**.

(20) The display device **130** is an information terminal having a display screen for displaying information (update status information) on the status of the program update process in the control device **120**. The display device **130** displays a predetermined notification or a permission request on its screen based on an instruction to display the update status information transmitted from the control device **120** via the in-vehicle network, or based on an instruction to display the update status information transmitted from the vehicle management server **200** via the wireless network. Examples of the display device **130** include a multi-information display and a vehicle navigation device mounted on the vehicle **100**.

(21) The mobile device **300** is an information terminal having a display screen for receiving the update status information regarding the status of the program update process in the control device **120** via the communication device **110** and displaying the received update status information. The mobile device **300** displays a predetermined notification or a permission request on its screen based on an instruction to display the update status information transmitted from the control device **120** via the wireless network, or based on an instruction to display the update status information transmitted from the vehicle management server **200** via the wireless network. Examples of the mobile device **300** include a general-purpose device owned by a user of the vehicle **100** such as a smartphone, a tablet device, or a personal computer.

(22) In the program update system **10** in FIG. **1**, the display device **130** and the mobile device **300** are included in the configuration of the information terminal for displaying the update status information regarding the status of the program update process in the control device **120**.

Alternatively, only one of the display device **130** and the mobile device **300** may be used. Further, a configuration other than the display device **130** and the mobile device **300** may be included as the information terminal as long as the update status information can be displayed and can be presented to the user of the vehicle **100**. The control device **120** that is performing the update may perform the instruction to display the update status information to the display device **130** and the mobile device **300**. Alternatively, the vehicle management server **200** may appropriately receive the update status from the control device **120** that is performing the update to perform the instruction to display the update status information to the display device **130** and the mobile device **300**.

First Example

(23) FIG. **3** is a flowchart illustrating a procedure of a program update process according to a first example, which can be executed by the control device **120**. FIGS. **4A** and **4B** are timing charts illustrating examples of the program update process according to the first example.

(24) The process illustrated in FIG. **3** is started, for example, when a power supply of the vehicle **100** is turned on.

(25) Step **S301**

(26) The controller **122** of the control device **120** inquires the vehicle management server **200** via the communicator **121** whether the update is available for the current program stored in the first storage area **1231** of the memory **123**.

(27) Step **S302**

(28) The controller **122** of the control device **120** receives a response from the vehicle management server **200** via the communicator **121** on the inquiry. When the controller **122** receives from the

vehicle management server **200** a response indicating that the update is available (step **S302**: YES), the process proceeds to step **S303**. When the controller **122** receives a response indicating that the update is not available (step **S302**: NO), this process ends.

(29) Step **S303**

(30) The controller **122** of the control device **120** downloads the update program from the vehicle management server **200** via the communicator **121**. The downloaded update program is stored in the second storage area **1232** of the memory **123**. The download of the update program does not affect the vehicle control, and is performed in the background without limiting the vehicle control.

(31) Step **S304**

(32) The controller **122** of the control device **120** determines whether the vehicle **100** is in a stop state. Examples of the stop state include a state in which a power supply of the vehicle **100** is off (for example, an ignition switch is off), a state in which a shift position is in a parking (P) position, and a state in which a speed of the vehicle **100** is zero. These states can be easily determined based on various pieces of vehicle information that can be obtained from various devices mounted on the vehicle **100**. When the vehicle **100** is in the stop state (step **S304**: YES), the process proceeds to step **S305**.

(33) Step **S305**

(34) The controller **122** of the control device **120** starts a process of updating the current program stored in the first storage area **1231** of the memory **123** with the update program stored in the second storage area **1232** of the memory **123**.

(35) Step **S306**

(36) The controller **122** of the control device **120** determines whether the program update process has been completed. When the update process has been completed (step **S306**: YES), this process ends.

(37) FIG. **4A** illustrates a case in which the download of the update program is completed during a period in which the vehicle **100** is in a non-stop state, and thereafter, the vehicle **100** transitions to the stop state. In this case, the program update process is not started until the vehicle **100** transitions to the stop state. By starting the update process at this timing, it can be expected that there is enough time until the execution of the current program is requested. Thus, it is possible to suppress the occurrence of the interruption in the program update process.

(38) FIG. **4B** illustrates a case in which the download of the update program is started during a period in which the vehicle **100** is in the non-stop state, and the vehicle **100** transitions to the stop state before the download is completed. In this case, the program update process is started subsequent to the completion of the download of the update program. Also when the update process is started at this timing, it can be expected that there is enough time until the execution of the current program is requested, and thus it is possible to suppress the occurrence of the interruption in the program update process.

(39) To restrain the update process from being interrupted after the program update process is started, the vehicle control related to the program that is being updated is desirably subjected to a predetermined measure until the update is completed. The predetermined measure is, for example, when the program is an engine control program, a process that limits an increase in an engine speed. With such a measure, even when the vehicle **100** transitions to the non-stop state during the program update process, the update can be completed without interruption in the update process. Therefore, it is possible to suppress an increase in the time of the update process.

Second Example

(40) FIGS. **5A** and **5B** are flowcharts illustrating a procedure of a program update process according to a second example, which can be executed by the control device **120**. Processes in FIG. **5A** and processes in FIG. **5B** are connected by connectors X and Y. FIGS. **6A** and **6B** are timing charts illustrating examples of the program update process according to the second example.

(41) In the second example, a process of displaying the update status information on a screen of the

display device **130** or the mobile device **300** is added to the process of the first example.

(42) Examples of the update status information include an update notification indicating that the update program is available, a download (DL) permission request for asking the user of the vehicle **100** for permission to download the update program from the vehicle management server **200** to the control device **120**, a DL completion notification indicating that the download of the update program from the vehicle management server **200** to the control device **120** has been completed, an update activation preparation completion notification indicating that the preparation for activating the update process of the current program with the update program has been completed, an update activation permission request for asking the user of the vehicle **100** for permission to activate the update process of the current program using the update program (that is, permission to switch controls), and an update completion notification indicating that the update process of the current program using the update program has been completed. Examples of the update status information also include the time required for an over-the-air (OTA) update process, which is a notification requirement in the regulations of the World Forum for Harmonization of Vehicle Regulations (WP29).

(43) The process shown in FIG. 5A is started, for example, when the power supply of the vehicle is turned on.

(44) Step S501

(45) The controller **122** of the control device **120** inquires the vehicle management server **200** via the communicator **121** whether the update is available for the current program stored in the first storage area **1231** of the memory **123**.

(46) Step S502

(47) The controller **122** of the control device **120** receives a response from the vehicle management server **200** via the communicator **121** on the inquiry. When the controller **122** receives from the vehicle management server **200** a response indicating that the update is available (step S502: YES), the process proceeds to step S503. When the controller **122** receives a response indicating that the update is not available (step S502: NO), this process ends.

(48) Step S503

(49) The controller **122** of the control device **120** causes the display device **130** or the mobile device **300** to display the update notification via the communicator **121**, the communication device **110**, and the vehicle management server **200**.

(50) Step S504

(51) The controller **122** of the control device **120** causes the display device **130** or the mobile device **300** to display the DL permission request on its screen via the communicator **121**, the communication device **110**, and the vehicle management server **200**.

(52) Step S505

(53) The controller **122** of the control device **120** determines whether the controller **122** has received a response, from the display device **130** or the mobile device **300**, indicating a permission to download the update program. When the permission has been received (step S505: YES), the process proceeds to step S506, and when no permission has been received (step S505: NO), this process ends.

(54) Step S506

(55) The controller **122** of the control device **120** downloads the update program from the vehicle management server **200** via the communicator **121**. The downloaded update program is stored in the second storage area **1232** of the memory **123**. The download of the update program does not affect the vehicle control, and is performed in the background without limiting the vehicle control.

(56) Step S507

(57) The controller **122** of the control device **120** derives an update time that is a time that is estimated to be required from the start of the update process to the completion of the update process. The update time typically represents a time from the start of the update process to the

completion of the update process without interruption therebetween, assuming that the vehicle control related to the program that is being updated is subjected to the predetermined measure. The update time is derived based on a size of the update program.

(58) Step S508

(59) The controller **122** of the control device **120** causes the display device **130** or the mobile device **300** to display the DL completion notification on its screen via the communicator **121**, the communication device **110**, and the vehicle management server **200**.

(60) Step S509

(61) The controller **122** of the control device **120** causes the display device **130** or the mobile device **300** to display the update activation preparation completion notification on its screen via the communicator **121**, the communication device **110**, and the vehicle management server **200**.

(62) Step S510

(63) The controller **122** of the control device **120** determines whether the vehicle **100** is in the stop state. Examples of the stop state include the state in which the ignition switch of the vehicle **100** is off (IG-OFF), the state in which the shift position is in the parking (P) position, and the state in which the speed of the vehicle **100** is zero. These states can be easily determined based on various pieces of the vehicle information that can be obtained from various devices mounted on the vehicle **100**. When the vehicle **100** is in the stop state (step S510: YES), the process proceeds to step S511.

(64) Step S511

(65) The controller **122** of the control device **120** causes the display device **130** or the mobile device **300** to display the update activation permission request and the update time on its screen via the communicator **121**, the communication device **110**, and the vehicle management server **200**.

(66) Step S512

(67) The controller **122** of the control device **120** determines whether the controller **122** has received a response, from the display device **130** or the mobile device **300**, indicating a permission to activate the update program. When the permission has been received (step S512: YES), the process proceeds to step S513, and when no permission has been received (step S512: NO), this process ends.

(68) Step S513

(69) The controller **122** of the control device **120** starts the process of updating the current program stored in the first storage area **1231** of the memory **123** with the update program stored in the second storage area **1232** of the memory **123**.

(70) Step S514

(71) The controller **122** of the control device **120** determines whether the program update process has been completed. When the update process has been completed (step S514: YES), the process proceeds to step S515.

(72) Step S515

(73) The controller **122** of the control device **120** causes the display device **130** or the mobile device **300** to display the update completion notification via the communicator **121**, the communication device **110**, and the vehicle management server **200**. When the update completion notification has been displayed, this process ends.

(74) FIG. 6A illustrates a case in which the download of the update program is completed during a period in which the vehicle **100** is in the non-stop state, and thereafter, the vehicle **100** does not transition to the stop state even after the DL completion notification and the update activation preparation completion notification is displayed. In this case, the update activation permission request and the update time are not displayed until the vehicle **100** transitions to the stop state. After the update activation is permitted, the program update process is started. By starting the update process at this timing, it can be expected that there is enough time until the execution of the current program is requested, and thus it is possible to suppress the occurrence of the interruption in the program update process.

(75) FIG. 6B illustrates a case in which the download of the update program is completed during a period in which the vehicle **100** is in the non-stop state, and the vehicle **100** transitions to the stop state during the update activation preparation completion notification subsequent to the completion of the download of the update program. In this case, the update activation permission request and the update time are displayed subsequent to the update activation preparation completion notification. After the update activation is permitted, the program update process is started. Also when the update process is started at this timing, it can be expected that there is enough time until the execution of the current program is requested, and thus it is possible to suppress the occurrence of the interruption in the program update process. The example in FIG. 6B illustrates a case in which the vehicle **100** transitions to the non-stop state before the program update process is completed. In this case, the vehicle control related to the program that is being updated is subjected to the predetermined measure from the time the vehicle **100** transitions to the non-stop state to the time the update process is completed (the time the update completion notification is displayed).

(76) The second example describes the case in which the update notification, the DL permission request, the DL completion notification, the update activation preparation completion notification, the update time, the update activation permission request, and the update completion notification are all displayed. Alternatively, with at least the update time displayed, other notifications and requests may be partially or entirely omitted.

Operations and Effects

(77) As described above, in the vehicle control device, the program update method, and the program update system according to the embodiment of the present disclosure, the memory has the first storage area for storing the program related to the vehicle control and the second storage area for storing the update program for updating the program, and the update program is downloaded from the vehicle management server to the second storage area without affecting the vehicle control. When it is determined that the vehicle is in the stop state (the power supply of the vehicle is off, the parking brake is activated, the vehicle speed is zero, etc.), the update process for updating the program stored in the first storage area with the update program stored in the second storage area is started.

(78) As described above, the program update process is started at the timing at which the vehicle is in the stop state and at which it is assumed that there is enough time until the execution of the current program is requested. Thus, it is possible to suppress the occurrence of the interruption in the program update process.

(79) Further, in the vehicle control device, the program update method, and the program update system according to the embodiment of the present disclosure, after the update program is downloaded from the vehicle management server to the second storage area, the update time that is the time estimated to be required from the start of the update process to the completion of the update process is derived based on the update program and displayed on the information terminal. Thus, it is possible to present a highly accurate update time to the user of the vehicle.

(80) With the highly accurate update time presented in this way, for example, when the update time has been presented to the user of the vehicle at a parking lot located away from the user's home, the user of the vehicle can return to the vehicle after the update time has elapsed. In this case, the update process has been completed, so the user can operate the vehicle immediately after returning to the vehicle. Thus, it is possible to reduce the trouble of having to wait in the vehicle without knowing the exact time required for the update to be completed.

(81) Further, in the vehicle control device, the program update method, and the program update system according to the embodiment of the present disclosure, when the permission request for activating the update process is displayed on the information terminal, it is possible to present a highly accurate update time together with the permission request. Thus, the user of the vehicle can permit the update of the program knowing the time required for the update of the program.

(82) Although the embodiment of the present disclosure has been described above, the applicable

embodiment is not limited to the vehicle control device and the program update system, and can also be applied to a program update method, a control program for the program update method, a computer-readable non-transitory storage medium storing the control program, and a vehicle including the program update system.

(83) The present disclosure can be used for a control device mounted on a vehicle or the like.

Claims

1. A control device configured to notify a user of update of a program related to vehicle control, the control device comprising at least one processor configured to: in a condition that a vehicle that is controlled in accordance with the program related to the vehicle control is in a stop state, display (i) information to request the user for an approval of the vehicle control in accordance with an update program, and (ii) update time that is required from reception of the approval to completion of the update, the update time being derived based on a size of the update program, wherein the information to request and the update time are displayed simultaneously; determine whether the at least one processor receives the approval from the user; and in response to receiving the approval from the user, execute a measure to limit execution of engine control of the vehicle and then perform a process to enable the vehicle to execute the vehicle control in accordance with the update program while the vehicle control is restricted by the measure, wherein the measure is executed continuously until the update is completed, regardless of whether the vehicle transitions from the stop state to the non-stop state before the completion of the update.
2. The control device according to claim 1, wherein the at least one processor is further configured to: download the update program from a management server that manages the update program; derive, when the update program is downloaded, an estimated time required for a process to enable the vehicle to control in accordance with the update program; and notify an information terminal that is communicable with the vehicle of at least the estimated time when the vehicle is in the stop state after deriving the estimated time.
3. The control device according to claim 2, wherein the at least one processor is further configured to: allow, when the vehicle is in the stop state after deriving the estimated time, the information terminal to notify the request for asking the user for the approval; and start an update process when the information terminal receives the approval.
4. The control device according to claim 1, wherein the stop state is at least a state in which a power supply of the vehicle is off.
5. The control device according to claim 1, wherein the stop state is at least a state in which a parking brake is activated.
6. The control device according to claim 1, wherein the stop state is at least a state in which a vehicle speed is zero.
7. The control device according to claim 1, wherein the at least one processor is further configured to: when the vehicle is in the stop state, control the notification unit to notify an estimated time required for a process to enable the vehicle to control in accordance with the update program.
8. The control device according to claim 1, wherein the notification unit is an information display and is configured to display the request for asking the user for the approval.
9. The control device according to claim 1, wherein the vehicle control controls a speed of the vehicle, and the measure limits the speed of the vehicle.
10. The control device according to claim 1, wherein the at least one processor is further configured to: display an update activation preparation completion notification prior to simultaneously displaying the information to request and the update time.
11. A program update method for notifying a user of update of a program related to vehicle control, the method being performed by at least one processor, the method comprising: in a condition that a vehicle that is controlled in accordance with the program related to the vehicle control is in a stop

state, displaying (i) information to request the user for an approval of the vehicle control in accordance with an update program, and (ii) update time that is required from reception of the approval to completion of the update, the update time being derived based on a size of the update program, wherein the information to request and the update time are displayed simultaneously; determining whether the at least one processor receives the approval from the user; and in response to receiving the approval from the user, executing a measure to limit execution of engine control of the vehicle and then performing a process to enable the vehicle to execute the vehicle control in accordance with the update program while the vehicle control is restricted by the measure, wherein the measure is executed continuously until the update is completed, regardless of whether the vehicle transitions from the stop state to the non-stop state before the completion of the update.

12. A program update system configured to notify a user of update of a program related to vehicle control, the program update system comprising at least one processor configured to: in a condition that a vehicle that is controlled in accordance with the program related to the vehicle control is in a stop state, display (i) information to request the user for an approval of the vehicle control in accordance with an update program, and (ii) update time that is required from reception of the approval to completion of the update, the update time being derived based on a size of the update program, wherein the information to request and the update time are displayed simultaneously; determine whether the at least one processor receives the approval from the user; and in response to receiving the approval from the user, execute a measure to limit execution of engine control of the vehicle and then perform a process to enable the vehicle to execute the vehicle control in accordance with the update program while the vehicle control is restricted by the measure, wherein the measure is executed continuously until the update is completed, regardless of whether the vehicle transitions from the stop state to the non-stop state before the completion of the update.
