

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400809
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Adams; Jason O. et al.

Laser-cut button veneer for a control device having a backlit keypad

Abstract

A veneer configured to be secured to a backlit button of a control device may include a plate portion. The plate portion may have one or more laser-cut indicia defined therethrough, may have laser-cut rounded corners, and may have angularly offset outer edges that may be defined during an embossing process. The laser-cut indicia may be representative of a command for controlling an electrical load. The indicia may include an alphanumeric character, an icon, or the like, may define one or more substantially zero-radius corners, and may define respective inner surfaces that are substantially perpendicular to an outer surface of the plate portion. A laser-cut alphanumeric character may have variable (e.g., continuously variable) line width. The plate portion may define a rib that suspends a floating portion of the alphanumeric character relative to an open portion. The rib may define a thickness that does not exceed 0.003 inches.

Inventors: Adams; Jason O. (Emmaus, PA), Destremps; Rich (Allentown, PA), Drizos; George M. (Macungie, PA), Kleppinger; Scott A (Macungie, PA), Kreschollek; Brad Michael (Bethlehem, PA), McDonald; Matthew Philip (Phoenixville, PA), Strange; Shawn A. (Blandon, PA)

Applicant: Lutron Technology Company LLC (Coopersburg, PA)

Family ID: 1000008782559

Assignee: Lutron Technology Company LLC (Coopersburg, PA)

Appl. No.: 17/135362

Filed: December 28, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210118631 A1	Apr. 22, 2021

Related U.S. Application Data

continuation parent-doc US 16362677 20190324 US 10892115 child-doc US 17135362
continuation parent-doc US 15242205 20160819 US 10276322 20190430 child-doc US 16362677
us-provisional-application US 62269498 20151218
us-provisional-application US 62207767 20150820

Publication Classification

Int. Cl.: **H01H13/02** (20060101); **B23K26/38** (20140101); **B32B7/12** (20060101); **B32B15/082** (20060101); **B41M5/24** (20060101); **H01H11/00** (20060101); **H01H13/14** (20060101); **H01H13/83** (20060101); H01H9/18 (20060101)

U.S. Cl.:

CPC **H01H13/023** (20130101); **B23K26/38** (20130101); **B32B7/12** (20130101); **B32B15/082** (20130101); **B41M5/24** (20130101); **H01H11/00** (20130101); **H01H13/14** (20130101); **H01H13/83** (20130101); B32B2457/00 (20130101); H01H2009/187 (20130101); H01H2219/028 (20130101); H01H2219/036 (20130101); H01H2229/02 (20130101); H01H2231/052 (20130101)

Field of Classification Search

CPC: H01H (13/023); H01H (11/00); H01H (13/14); H01H (13/83); H01H (2219/028); H01H (2219/036); H01H (2009/187); H01H (2229/02); H01H (2231/052); H01H (13/02); H01H (9/18); B23K (26/38); B32B (7/12); B32B (15/082); B32B (2457/00); B41M (5/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1464515	12/1922	Thomas	N/A	N/A
1761868	12/1929	Burke	N/A	N/A
1977261	12/1933	Brown	N/A	N/A
2109054	12/1937	Soreng et al.	N/A	N/A
4131777	12/1977	Bailey et al.	N/A	N/A
4667073	12/1986	Osika	N/A	N/A
5036440	12/1990	Takii et al.	N/A	N/A
5120920	12/1991	Moriike	N/A	N/A
5456955	12/1994	Muggli	N/A	N/A
5911317	12/1998	Tsai	N/A	N/A
6180048	12/2000	Katori	N/A	N/A
6803728	12/2003	Balasubramaniam et al.	N/A	N/A
7119296	12/2005	Liu et al.	N/A	N/A
7134205	12/2005	Bruennel	29/17.2	B29C 45/1418
7534500	12/2008	Kobayashi	428/458	B32B 27/36
8870477	12/2013	Merminod et al.	N/A	N/A

9349309	12/2015	Eloyan et al.	N/A	N/A
9443676	12/2015	Na	N/A	N/A
9640347	12/2016	Kwan et al.	N/A	N/A
9763302	12/2016	Mcdonald et al.	N/A	N/A
9911372	12/2017	Dimberg et al.	N/A	N/A
10276322	12/2018	Adams	N/A	B41M 5/24
10892115	12/2020	Adams	N/A	H01H 11/00
2010/0282580	12/2009	Maatta	N/A	N/A
2011/0018161	12/2010	Yang	N/A	N/A
2012/0111704	12/2011	Stohr et al.	N/A	N/A
2014/0001977	12/2013	Zacharchuk et al.	N/A	N/A
2015/0083561	12/2014	Han	200/314	H01H 13/83
2015/0090570	12/2014	Kwan et al.	N/A	N/A
2016/0049266	12/2015	Stringer	200/344	H01H 13/83
2016/0069537	12/2015	Dimberg et al.	N/A	N/A
2016/0307714	12/2015	Bhate et al.	N/A	N/A
2017/0053753	12/2016	Adams et al.	N/A	N/A
2017/0347420	12/2016	McDonald et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1808880	12/2006	EP	N/A

OTHER PUBLICATIONS

International Search Report, International Application No. PCT/US2016/047890, International Filing date Aug. 19, 2016, date of mailing Jul. 11, 2016. cited by applicant

Primary Examiner: Caroc; Lheiren Mae A

Attorney, Agent or Firm: Condo Roccia Koptiw LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/362,677, filed Mar. 24, 2019, now U.S. Pat. No. 10,892,115, which is a continuation of U.S. patent application Ser. No. 15/242,205, filed Aug. 19, 2016, now U.S. Pat. No. 10,276,322, which claims priority to U.S. Provisional Patent Application No. 62/207,767, filed Aug. 20, 2015, and to U.S. Provisional Patent Application No. 62/269,498, filed Dec. 18, 2015, all of which are incorporated herein by reference in their entireties.

BACKGROUND

(1) Load control devices may be used to control the amount of power delivered from a power source, such as an alternating-current (AC) power source, to one or more electrical loads. An example of such a load control device is a wall-mounted dimmer switch. Load control devices may be integrated into home automation systems.

(2) Home automation systems, which have become increasing popular, may be used by homeowners to integrate and/or control multiple electrical and/or electronic devices in their homes. For example, a homeowner may connect devices such as appliances, lights, blinds, thermostats, cable or satellite boxes, security systems, telecommunication systems, and the like to each other via

a wireless network.

(3) The homeowner may control such devices using a central (e.g., automated) controller, a dedicated remote control device (e.g., a wall-mounted keypad), a user interface provided via a phone, tablet, computer, or other device that is directly connected to a home network or remotely connected via the Internet, and so on. These devices may communicate with each other and/or with a control device, for example to improve efficiency, convenience, and/or usability of the devices.

(4) Dedicated remote control devices, such as wall-mounted keypads, may be manufactured to be aesthetically pleasing. For example, wall-mounted keypads may include faceplates and buttons made of metal, glass, or other materials to lend the keypads a luxury aesthetic when compared to traditional plastic keypads. However, the manufacture of such keypads may be problematic. For instance, in the case of metallic buttons, indicia are typically formed in the buttons using machining processes. However, such machining processes have limitations. For instance, small scale machining processes may be incapable of very fine detail, which may lead to undesirable aesthetics in the indicia, and/or may introduce inaccuracies or inconsistencies into the manufacturing process that reduce yield. Additionally, such machining processes are typically time intensive, which may impact manufacturing costs and capacity.

SUMMARY

(5) As described herein, a veneer may be configured to be secured to a backlit button of a control device, such as a wall-mounted keypad. The control device may be configured for use with a load control device, such as a dimmer switch.

(6) The veneer may include a plate portion that has one or more laser-cut indicia defined therethrough. The plate portion may further include laser-cut rounded corners. The veneer may further include a filler material that is disposed in the one or more indicia.

(7) The laser-cut indicia may be representative of a command for controlling an electrical load. The indicia may include an alphanumeric character, an icon, or the like. The indicia may define a substantially zero-radius corner. The indicia may define respective inner surfaces that are substantially perpendicular to an outer surface of the plate portion of the veneer.

(8) At least a section of a laser-cut alphanumeric character may define a variable (e.g., continuously variable) line width. If the alphanumeric character includes a floating portion, such as the letter “o” for example, the plate portion of the veneer may define one or more ribs that suspend the floating portion relative to an open portion of the alphanumeric character. Each rib may define a thickness that does not exceed 0.003 inches, for instance such that the ribs are virtually invisible to the naked eye of a user of the control device.

(9) An example method of producing a button that is configured for installation in a control device having a backlit keypad may include laser cutting one or more indicia into a veneer that is configured to be attached to an outer surface of the button. The indicia may be representative of a command for controlling an electrical load. The method may include adhering the veneer to the outer surface of the button.

(10) Another example method of producing a button that is configured for installation in a control device having a backlit keypad may include embossing a metal blank with an array of button veneers. The method may include laser cutting one or more indicia into at least one of the button veneers. The indicia may be representative of a command for controlling an electrical load. The method may include disposing a filler material into the indicia. The method may include separating the veneers from the blank. For example, the method may include laser cutting slots along respective perimeters of the button veneers. The slots may enable separating the veneers from the blank. Laser cutting the slots may include rounding the corners of each of the veneers. The method may include securing each veneer to a corresponding button of the keypad.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of an example control device, configured as a wall-mounted keypad, for use in a load control system for controlling the amount of power delivered to one or more electrical loads.
- (2) FIG. 2 is a perspective view of an example button that may be implemented in a control device, the button including a button body and a veneer with laser-cut indicia that is attached to the button body.
- (3) FIG. 3 depicts an example indicia that may be laser cut into a veneer secured to the button of a control device.
- (4) FIG. 4 depicts an example process for producing a button for use in a control device, the button including a veneer having one or more laser-cut indicia.
- (5) FIG. 5 is a perspective view of a metal blank, stamped to form an array of control device button veneers.
- (6) FIG. 6 is a perspective view of the metal blank illustrated in FIG. 5, after a laser cutting process has been performed on the blank.
- (7) FIG. 7 is a zoomed-in view of a portion of the metal blank illustrated in FIG. 6, illustrating a laser-cut tab that suspends a veneer relative to the blank.
- (8) FIG. 8A depicts the button of a control device, and a laser-cut button veneer, before the veneer is secured to the button.
- (9) FIG. 8B depicts the button illustrated in FIG. 8A, with the veneer secured to the button.
- (10) FIG. 9 is a perspective view of another example control device, configured as a wall-mounted keypad, for use in a load control system for controlling the amount of power delivered to one or more electrical loads.

DETAILED DESCRIPTION

- (11) FIG. 1 depicts an example control device that may be configured for use in a load control system for controlling one or more load control devices and/or electrical loads, such as lighting loads, motorized window treatments, or the like. As shown, the example control device is configured as a wall-mounted keypad **100**. The keypad **100** may include a faceplate **102**, one or more buttons **110**, and a housing **120** that is configured to be mounted to a structure, such as an interior wall of a building. The illustrated keypad **100** may be configured to control a load control device, such as a load control device configured to control an amount of power delivered to one or more electrical loads (e.g., one or more lighting loads) from a power source, such as an alternating-current (AC) power source or a direct current (DC) power source.
- (12) The faceplate **102** may define an opening **104** that extends therethrough and that is configured to at least partially receive the buttons **110**. For example, in accordance with the illustrated keypad **100**, the opening **104** may be sized to receive the buttons **110** such that a gap **106** is defined between inner edges of the opening **104** and corresponding outer peripheral surfaces of the buttons **110**. The keypad **100** may be configured such that the gap **106** remains uniform around the perimeter of the opening **104**. The keypad **100** may further be configured such that facing edges of adjacent buttons **110** are spaced apart from each other by a gap **108** that is substantially the same as (e.g., equal to) the gap **106** between the buttons **110** and the opening **104** of the faceplate **102**. The faceplate **102** may be made of the same material, or using the same mix of materials, as the buttons **110**. Alternatively, the faceplate **102** and the buttons **110** may be made of different materials. In accordance with an example implementation, the buttons **110** may be made of plastic and may have metal veneers that are attached thereto, and the faceplate **102** may be made of the same metal as the button veneers. The faceplate **102** may be configured to be attached to (e.g., removably attached to) the housing **120**.
- (13) The illustrated keypad **100** includes four buttons **110** that are rectangular in shape and are of the same size. However, it should be appreciated that the keypad **100** is not limited to buttons

having the illustrated button geometries. For example, the keypad **100** may alternatively include more or fewer buttons having the same or different geometries and/or sizes. The buttons **110** may be made of a mix of materials. For example, each illustrated button **110** may include a button body that is made of a first material (e.g., plastic), and may include a veneer **130** that is made of a different material (e.g., metal) and that is attached to the button body of the button **110**.

(14) Each veneer **130** may have one or more indicia **140** formed therein, such as cut therethrough. The indicia **140** may be representative of a function that the keypad **100** is configured to execute or that the keypad is configured to cause to be executed. For example, the indicia **140** may be representative of a command for controlling an electrical load. In accordance with an example implementation of the keypad **100**, the indicia **140** may be representative of a message that the keypad **100** is configured to transmit, for instance a message that includes a command for execution by a load control device that is associated with the keypad **100**. In accordance with an alternative example implementation, the keypad **100** may include an integral load control circuit (e.g., a dimming circuit), and the command may cause the integral load control circuit to control an electrical load that is electrically connected thereto. The indicia **140** of a particular button **110** may include one or more visual representations of a function associated the button **110**, such as, for example, one or more alphanumeric characters, icons, etc. in any combination.

(15) In accordance with the buttons **110** of the illustrated keypad **100**, the indicia **140** may be words that are indicative of respective functions that are invoked by depressing the buttons **110**. The indicia **140** may be laser cut through the veneers **130** of the buttons **110**, or may otherwise be formed on the buttons **110**. The keypad **100** may include one or more lighting elements (not shown) that are configured to illuminate respective interiors of the buttons **110**, such that the indicia **140** are backlit from within an interior of the keypad **100**. For example, the keypad **100** may include a plurality of lighting elements, such as light emitting diodes (LEDs), that are disposed within the housing **120** of the keypad **100**, behind the buttons **110**, and that are configured to backlight the buttons **110**. In this regard, the illustrated keypad **100** may be referred to as a backlit keypad or control device.

(16) Examples of button indicia and button backlighting systems are described in greater detail in commonly-assigned U.S. Provisional Patent Application No. 62/048,652, titled “Control Device Having Buttons With Metallic Surfaces And Backlit Indicia,” and U.S. Provisional Patent Application No. 62/048,658, titled “Control Device Having Buttons With Multiple-Level Backlighting,” the entire disclosures of which are incorporated herein by reference.

(17) The keypad **100** may be configured to transmit one or more digital messages to one or more external load control devices (e.g., dimmer switches) and/or electrical loads via a communication link, for example in response to one or more buttons **110** being depressed. The one or more digital messages may include, for example, one or more commands for execution by the one or more external load control devices to control respective electrical loads (e.g., lighting loads). The communication link may comprise a wired communication link or a wireless communication link, such as a radio-frequency (RF) communication link. In accordance with an alternative configuration, the keypad **100** may further include an internal load control circuit (not shown) for controlling the power delivered to one or more electrical loads (e.g., lighting loads). Examples of load control systems having remote control devices, such as the keypad **100**, are described in greater detail in commonly-assigned U.S. Provisional Patent Application No. 62/150,227, titled “Control Devices Having Independently Suspended Buttons For Controlled Actuation,” U.S. Pat. No. 6,803,728, issued Oct. 12, 2004, entitled “System For Control Of Devices,” and U.S. Patent Application Publication No. 2014/0001977, published Jan. 2, 2014, entitled “Load Control System Having Independently-Controlled Units Responsive To A Broadcast Controller,” the entire disclosures of which are incorporated herein by reference.

(18) FIG. 2 depicts an example button **210** that may be a component of a control device. For example, the button **210** may be implemented as one or more of the buttons **110** of the keypad **100**.

As shown, the button **210** includes a button body **220** and a veneer **230** that is attached to a front surface of the button body **220**. The button body **220** may be referred to as a carrier portion, such as a carrier portion of the button **210** or more generally as a carrier portion of a control device in which the button **210** is installed, such as the keypad **100**.

(19) The veneer **230** may include a plate portion **232** and may define peripheral walls **234** that extend rearward from the plate portion **232**. The plate portion **232** may define a front surface **233** of the veneer **230**. As shown, the plate portion **232** may define a flat, substantially planar front surface **233**. The plate portion **232** and the peripheral walls **234** may define four corners **231** of the veneer **230**. The veneer **230** may define outer edges **236** that extend along an outer perimeter of the plate portion **232**, between the corners **231**, along an interface between the plate portion **232** and the peripheral walls **234**. As shown, the outer edges **236** of the veneer **230** may be angularly offset relative to the front surface **233**. However, it should be appreciated that the veneer **230** is not limited to the illustrated outer edges **236**. For example, the veneer **230** may be alternatively formed, with outer edges **236** that may be rounded, may be square, or may define other geometries relative to the front surface **233**.

(20) In an example implementation, the veneer **230** may be formed from a sheet of metal, for example by an embossing process, a progressive stamping process, or the like. The formation process of the veneer **230** may define, for example, one or more of the plate portion **232**, the peripheral walls **234**, and the outer edges **236**. The corners **231** of the veneer **230** may be rounded, for example during a laser cutting process that separates the formed veneer **230** from a blank after the forming process is performed.

(21) The button body **220** may be configured such that the plate portion **232** and the peripheral walls **234** of the veneer **230** at least partially enclose a front portion of the button body **220** when the veneer **230** is attached to the button body **220**. The button body **220** may be made of any suitable material, such as plastic.

(22) The veneer **230** may include one or more indicia, such as indicia **240** that are defined in the plate portion **232** of the veneer **230**. For example, the indicia **240** may be formed during a laser cutting process. As shown, the indicia **240** extend into the front surface **233** of the veneer **230** and through the plate portion **232**. The front surface **233** of the veneer **230** may alternatively be referred to as an outer surface of the veneer **230**. The veneer **230** may be made of any suitable material, such as metal. The button body **220** may be made of a translucent material, for instance white or clear plastic, such that when the button body **220** is backlit, light may pass through the button body **220** and reach an inner surface of the veneer **230**, for example an inner surface of the plate portion **232**. Such light may be emitted, for example, from the interior of a control device in which the button **210** is installed, such as the keypad **100**. In accordance with such an implementation, the indicia **240** of the veneer **230** may expose corresponding underlying surfaces of the button body **220**, such that the indicia **240** may be illuminated when the button body **220** is backlit. In this regard, the veneer **230** may be configured to be secured to a backlit button of a control device.

(23) The illustrated indicia **240** include letters that form a word. However, the indicia **240** are not limited to letters, and may include any combination of alphanumeric characters, icons (e.g., symbols), or the like. The indicia **240** may be representative of a command for controlling an electrical load. For example, the indicia **240** may be representative of: a command message that may be transmitted by a control device in which the button **210** is operatively installed; of a command that is executed internally by such a control device; of a result of the performance of a command; or the like. To illustrate, one or more command messages may be transmitted by such a control device in response to one or more actuations of the button **210**. The veneer **230** may include a filler material (not shown) that is disposed into the indicia **240**. The filler material may prevent the accumulation of debris (e.g., dirt, skin, or the like) in the indicia **240**. The filler material may, for example, be backfilled into the indicia **240** such that the filler material is coplanar with the front surface **233** of the veneer **230**. The filler material may further function to improve the optical

performance of the indicia **240** when one or more of the buttons **210** are backlit, for instance to improve the readability of the indicia **240** when viewed from off angle.

(24) Forming the indicia **240** of the veneer **230** via a laser cutting process may enable the indicia **240** to exhibit one or more characteristics that are not typically achievable in indicia defined via known processes of button veneer manufacture, such as machining. Examples of such characteristics are illustrated in FIGS. **2** and **3**.

(25) For example, as shown in FIG. **2**, in accordance with a characteristic of laser-cut indicia **240**, the indicia **240** have corresponding inner surfaces **242** that may be substantially perpendicular to the front surface **233** of the veneer **230**, for example approximately 89°-91° from the front surface. This is in contrast to indicia formed by known techniques of machining into material having a planar surface, which indicia may exhibit tapered inner surfaces that are not perpendicular with respect to the planar surface. Perpendicular inner surfaces, such as inner surfaces **242**, may enable more light to be emitted from the indicia **240**, which may improve the aesthetic characteristics of the indicia **240**, and thus of the button **210**, for instance when the button **210** is backlit.

(26) FIG. **3** depicts a portion of the example indicia **240**, in particular the letter “R.” As shown, the plate portion **232**, once laser cut with the indicia **240**, defines one or more open portions **235** that extend through the plate portion **232**, and may define one or more floating portions **237**, such as that defined by the hoop of the “R.” The open portions **235** and floating portions **237** may be referred to as being defined by the corresponding indicia **240**.

(27) In accordance with another characteristic of laser-cut indicia **240**, the indicia **240** may define one or more corners **244** that have very small minimum radii. For example, the corners **244** of the illustrated “R” of the indicia **240** may have a minimum radius of approximately 0.0004 inches or smaller. The corners **244** may be referred to as inside corners of the indicia **240**. The corners **244** may appear, for instance to the naked eye of a user of a control device in which the button **210** is installed, as sharp corners having no radii at all. In this regard, the corners **244** of the illustrated indicia may be referred to as substantially zero-radius corners, or more generally as zero-radius corners. In contrast, the corners of indicia (e.g., alphanumeric characters) that may be formed using known machining techniques may have minimum radii of approximately 0.0035”. The presence of substantially zero-radius corners, such as the corners **244** of the illustrated indicia **240**, may enhance the aesthetic characteristics of the indicia **240**, and thus of the button **210**, for instance when the button **210** is backlit.

(28) The plate portion **232** may further define one or more ribs **238** that suspend one or more corresponding floating portions **237** relative to one or more open portions **235**. For example, in accordance with the illustrated “R,” the plate portion **232** defines three ribs **238** that suspend the floating portion **237** relative to the three open portions **235**. The ribs **238** within a portion of an indicia **240**, for instance within a particular alphanumeric character, may be configured to enable the control of one or more aspects of the separation of one or more scrap pieces (not shown) from the plate portion **232** during the laser cutting process. The one or more scrap pieces may correspond, for example, to the open portions **235** of the indicia **240**. Such aspects may include, for example, how one or more scrap pieces release from the plate portion **232** (e.g., twisting, bending, and the like) and/or when one or more scrap pieces release from plate portion **232** during the laser cutting process. One or both of the number of ribs **238** that are defined by an indicia **240** and the corresponding locations of the ribs **238** may influence the aspects of scrap piece separation. Control of the separation of scrap pieces from the plate portion **232** may assist with successful completion of the process of laser cutting the indicia **240**. In this regard, an indicia **240** (e.g., a font) may be designed to enhance performance of laser cutting the indicia **240** into the plate portion **232** of a veneer **230**.

(29) In accordance with still another characteristic of laser-cut indicia **240**, the laser-cutting process may be performed such that the ribs **238** are thinner than the thickness of ribs achievable with known machining processes. For example, the illustrated ribs **238** may be defined with a thickness

TH1 that may be, for example, between 0.002 inches and 0.004 inches, such as about 0.003 inches. In this regard, the ribs **238** may define respective thicknesses that do not exceed 0.003 inches. At a thickness of approximately 0.003 inches or narrower, the ribs **238** may be virtually invisible to the naked eye of a user of the keypad **100**. It should be appreciated that rib thickness narrower than 0.002 inches may be achievable with laser cutting. It should further be appreciated that the ribs **238** of a particular portion of the indicia **240**, such as the letter “R,” may have the same thickness (e.g., TH1). Alternatively, one or more of the ribs **238** may have different thicknesses. Reducing the thickness of the ribs **238** may cause the ribs **238** to be less visible, for example by a user of a control device in which the button is installed **210**. Such ribs **238** may improve the aesthetic characteristics of the indicia **240**, and thus of the button **210**, for instance when the button **210** is backlit.

(30) By contrast, to achieve rib thicknesses similar to those of the illustrated ribs **238** via machining processes may be undesirably time consuming, and may be accompanied by high failure rates which may in turn reduce manufacturing yield. Additionally, the illustrated ribs **238** may be formed with substantially zero-radius corners **244**, while ribs created via machining or via other processes, such as chemical photo etching, electrical discharge machining, or the like, may exhibit rounded corners that are visible to the naked eye and/or that may be aesthetically degraded by one or more heat affected zones.

(31) In accordance with still another characteristic of laser-cut indicia **240**, such an alphanumeric character may exhibit variable (e.g., continuously variable) line width. For example, a first section of the illustrated portion of the indicia **240** may exhibit a first line width LW1. A second section of the portion of the indicia **240** may exhibit a second line width LW2 that is narrower than the first line width LW1, and a third section of the portion of the indicia **240** may exhibit a third line width LW3 that is wider than the first line width LW1 and the second line width LW2. Such continuously varying line widths are typically difficult to implement using known machining techniques, for instance requiring multiple machining passes, z-axis translation during machining pass, or the like. The presence of varying line width, such as that exhibited by the “R” of the illustrated indicia **240**, may enhance the aesthetic characteristics of the indicia **240**, and thus of the button **210**, for instance when the button **210** is backlit.

(32) It should be appreciated that respective portions of a laser-cut indicia, such as the example indicia **240**, may exhibit one or more of the above-described characteristics, such as all of the above-described characteristics, in any combination.

(33) FIG. 4 depicts an example process **400** for producing a button **510** (e.g., as shown in FIGS. 5-7B) for use in a control device. For example, the button **510** may be implemented as one or more of the buttons **110** of the keypad **100**. At **402**, a formation process may be performed on a blank **500** to define one or more button veneers **530**, as shown in FIG. 5. The blank **500** may be, for example, a sheet of metal. As shown, the blank **500** may be a rectangular sheet of stainless steel. The blank **500** may define a planar front surface **502** and an opposed rear surface **504**, and may be flat prior to the embossing process. The formation process may be, for example, a sheet metal embossing process, a progressive stamping process, or another process. In accordance with the illustrated process **400**, the veneers **530** may be formed by embossing the veneers **530** into the blank **500**.

(34) During the embossing process, each of the one or more veneers **530** may be defined by forming a plate portion **532** and peripheral walls **534** that extend around a perimeter of each veneer **530** into the blank **500**. The plate portions **532** may define respective front surfaces **533** of the veneers **530**. As shown, the plate portion **532** may define respective flat, substantially planar front surfaces **533**. The plate portion **532** and the peripheral walls **534** of each veneer **530** may define four corners **531** of the veneer **530**. Each veneer **530** may define outer edges **536** that extend along an outer perimeter of the plate portion **532**, between the corners **531**, along an interface between the plate portion **532** and the peripheral walls **434**. As shown, the outer edges **536** of each veneer **530** may be angularly offset relative to the front surface **533**. However, it should be appreciated that the

veneers **530** are not limited to the illustrated outer edges **536**. For example, the veneers **530** may be alternatively formed, with outer edges **536** that may be rounded, may be square, or may define other geometries relative to the front surfaces **533**.

(35) As shown, the veneers **530** may be embossed into the rear surface **504** of the blank **500**, such that the plate portions **532** of the veneers **530** may be spaced from the front surface **502** of the blank **500**. In accordance with the example process **400**, the plate portion **532** of each veneer **530** may be spaced from the front surface **502** of the blank by approximately 0.01 inches. The illustrated blank **500** is embossed to define a vertical array of four veneers **530**. However, it should be appreciated that more or fewer veneers **530** may be embossed, and that the veneers **530** may be embossed in any alignment relative to each other.

(36) Optionally, during the embossing process, one or more alignment features may be defined in the blank **500**. The alignment features may be used to register the blank **500** in position relative to respective machines during one or more portions of the process **400**. For example, as shown, the blank **500** may be embossed with a plurality of alignment features that include apertures **506** and **508** that may be spaced from the veneers **530**. The apertures **506** and **508** may be configured as optical alignment fiducials, for example. To illustrate, the blank **500** may be positioned within a laser cutting apparatus, via the apertures **506** and **508**, prior to performing the laser cutting process.

(37) At **404**, a surface finish may be applied to the embossed blank **500**. The surface finish may be applied, for example, to one or both of the front surface **502** of the blank **500** and the rear surface **504** of the blank **500**. In this regard, one or both of a front surface **533** and a rear surface **535** of each veneer **530** may be treated. The front surface **533** of each veneer **530** may be referred to as an outward-facing surface, and the rear surface **535** of each veneer **530** may be referred to as inward-facing surface.

(38) One or more laser cutting processes may be performed on the blank **500**. For example, at **406**, a laser cutting apparatus may be configured to perform a first laser cutting process to define indicia **540** in one or more of the veneers **530**. As shown, respective indicia **540** may be laser cut through the plate portion **532** of each of the veneers **530**. That is, the indicia **540** may be defined into the front surface **533**, and through the rear surface **535**, of the plate portion **532** of each veneer **530**. The illustrated indicia **540** include letters that form words. However, the indicia **540** are not limited to letters, and may include any combination of alphanumeric characters, icons (e.g., symbols), or the like. The indicia **540** may be representative of a command for controlling an electrical load. For example, the indicia **540** may be representative of: a command message that may be transmitted by a control device in which the button **510** is operatively installed; of a command that is executed internally by such a control device; of a result of the performance of a command; or the like.

(39) At **408**, during a second laser cutting process, the veneers **530** may be partially cut out from the blank **500**. For example, one or more slots **507** may be laser cut through the blank **500** (e.g., into the front surface **502** and through the rear surface **504**) along the respective perimeter of each veneer **530**. In this regard, respective outer dimensions of the plate portions **532** of the veneers **530** may be defined by the second laser cutting process **408**. The laser cutting apparatus may be configured to round the corners **531** of the veneer **530**, for example while cutting the slots **507**. For example, the corners **531** of the illustrated veneers **530** may be rounded with a radius of approximately 0.005 inches during the laser-cutting process.

(40) To cut the slots **507**, the laser cutting apparatus may be configured to adjust the focal point of the laser from a first z-axis position wherein the focal point of the laser is positioned relative to the front surfaces **533** of the veneers **530**, to a second, lower z-axis position wherein the focal point of the laser is positioned relative to the front surface **502** of the blank **500**. In this regard, the laser apparatus may be configured to adjust the focal point of the laser along a vertical direction relative to the blank **500** during the laser cutting process.

(41) During performance of the second laser cutting process **408**, one or more portions of material of the blank **500** within the slots **507** may be left in place, to suspend each veneer **530** relative to

the blank **500**. For example, as shown, the slots **507** around each veneer **530** may be defined such that four tabs **509** remain that retain the veneer **530** in position relative to the blank **500** (e.g., as shown in FIG. 7). The illustrated tabs **509** are approximately 60 microns wide (relative to opposed sides of the blank **500**) and are approximately 20 microns high (relative to opposed upper and lower ends of the blank **500**). It should be appreciated, however, that the tabs **509** are not limited to the illustrated arrangement (e.g., number and respective locations of the tabs **509**) or the illustrated tab dimensions.

(42) It should be appreciated that the first laser cutting process at **406** and the second laser cutting process at **408** may be performed discretely from each other. Alternatively, the first and second laser cutting processes **406**, **408** may be performed as portions of a single laser cutting process (e.g., combining **406** and **408**) that is performed on the blank **500**. At the conclusion of the laser cutting process and/or processes, the veneers **530** may be suspended relative to the blank **500** via the tabs **509**. In this regard, the blank **500**, including the veneers **530**, may be removed from the laser cutting apparatus as a single piece.

(43) At **410**, a filler material (not shown) may be disposed into the indicia **540** of the respective veneers **530**. The filler material may at least partially fill the indicia **540**. For example, the filler material may fill the indicia **540** such that the filler material defines a filler surface that may be subsurface or convex relative to the front surfaces **533** of veneers **530**. In such an example, the filler surface may define one or more fillets along edges of the inner surfaces of the indicia **540**, which may reduce the effective depth of the indicia **540**. Alternatively, the filler material may fill the indicia **540** such that at least a portion of a filler surface defined by the filler material is substantially flush with (e.g., coplanar with) the front surfaces **533** of veneers **530**. The filler material may function to reduce the generation of debris (e.g., dirt, skin, or the like) in the indicia **540**, for example by reducing (e.g., eliminating) one or more abrasive edges defined by the indicia **540** that may, for example, scrape material from the finger of a user pressing the button **510** to which the veneer **530** is attached. The filler material may function to prevent the accumulation of such debris in the indicia **540**. The filler material may further function to improve the optical performance of the indicia **540** when one or more of the buttons **510** are backlit, for instance to improve the readability of the indicia **540** when viewed from off angle.

(44) The filler material may be any suitable material, such as a laminating film that, upon being heated, may flow and/or be mechanically disposed (e.g., pressed) into the indicia **540** of the veneers **530**. In an example, a commercial laminating film may be used. The laminating film may, for example, include a first layer comprising polyester base material and a second layer comprising ethylene-vinyl acetate (EVA) adhesive. It should be appreciated that the constitution (e.g., material and layers) of the laminating film is not limited to the example described herein. Nor is the filler material limited to laminating film. For example, the filler material may comprise any other material that may flow to fill the indicia **540** of the veneers **530** and/or bond to corresponding surfaces of the veneers **530**, such as the inner surfaces of the indicia **540** or the rear surfaces **535** of the veneers **530**.

(45) A portion of laminating film may be pre-configured to define a filler blank for use in an example process for filling the indicia **540** of one or more veneers **530**. For example, a sheet of laminating film may be cut such that a number of tabs are defined that correspond to respective veneers **530**. In accordance with an example process for filling the indicia **540** of the veneers **530** of the blank **500** (e.g., as shown in FIG. 6), a portion of laminating film may be cut to define a filler blank that includes a support strip and four tabs that extend outward from the support strip and that are spaced apart from each other along a length of the support strip. In accordance with an example filler blank, each tab may be sized to cover an area of the plate portion **532** of a corresponding one of the veneers **530**, for instance where indicia **540** may be defined in the veneer **530**.

(46) The filler blank may define one or more alignment features that may allow the filler blank to be properly located during an example indicia filling process. For example, the support strip of the

filler blank may define one or more apertures that extend therethrough, the apertures configured to receive complementary alignment features (e.g., posts) of a laminating apparatus, such that the filler blank is properly oriented relative to the blank **500**, and such that each tab is properly oriented relative to a corresponding one of the veneers **530**. One or more portions of the filler blank, such as the support strip, may be configured (e.g., shaped) to ease removal of one or more remaining portions of the filler blank at the conclusion of an indicia filling process, and such that removal may be achieved without degrading properties of the laminating film, such as adhesion to the indicia **540** and/or veneers **530**, or a thickness of the laminating film.

(47) An example process for filling the indicia **540** of one or more veneers **530** using a laminating film filler blank may include the use of one or more portions of adhesive release material. The adhesive release material may be any material that, during heating of the laminating film, may not adhere to and/or modify surfaces of the veneers **530** and/or the blank **500** to which adhesion of the laminating film is not desired. In accordance with an example process for filling the indicia **540** of one or more veneers **530** using a laminating film, the adhesive release material may be paper or another material suitable to prevent the laminating film from bonding to the veneers **530** during an indicia filling process. The adhesive release material may be configured (e.g., cut) to mask areas of the blank **500**, such as the veneers **530**, to which adhesion of the laminating film is not desired. In an example, the adhesive release material may define a shape that is substantially the same as that of the support strip of the filler blank.

(48) The adhesive release material may define one or more alignment features that may allow the adhesive release material to be properly located during an example indicia filling process. For example, the adhesive release material may define one or more apertures that extend therethrough, the apertures configured to receive complementary alignment features (e.g., posts) of a laminating apparatus. The respective apertures may be defined to align with one or more apertures defined by the filler blank, such that the adhesive release material may be properly oriented relative to the filler blank and the blank **500**. The adhesive release material may be configured (e.g., shaped) to ease removal of one or more remaining portions of the filler blank at the conclusion of an indicia filling process. The adhesive release material may be configured to exhibit one or more properties, such as material thickness, that may enable the adhesive release material to promote a consistent finished lamination thickness within the filled indicia **540** of a veneer **530**.

(49) A laminating apparatus may be provided in an implementation of an example indicia filling process. An example laminating apparatus may, for example, comprise a laminating press that includes a locating nest and a pressure plate. The laminating apparatus may be configured to apply one or both of heat and pressure to material (e.g., directly or indirectly) that is disposed between the pressure plate and the locating nest, such as the laminating film, at particular times during an example indicia filling process.

(50) The locating nest and pressure plate may be configured to cooperate to apply compression forces to material that is disposed therebetween. For example, the laminating apparatus may be configured such that one or both of the pressure plate and the locating nest move toward each other during an example indicia filling process. For example, the pressure plate and the locating nest may both be configured to move toward one another during an example indicia filling process, or alternatively one of the pressure plate or the locating nest may be fixed relative to the other during the indicia filling process. The laminating apparatus may be configured to evenly distribute compressive force to the laminating film (e.g., via the locating nest and/or via the pressure plate) during an example indicia filling process, for example in accordance with a particular time sequence and/or duration of the process.

(51) The laminating apparatus may be configured to generate and apply heat to material that is disposed between the pressure plate and the locating nest. For example, one or both of the locating nest and the pressure plate may be configured to generate and evenly distribute heat to the laminating film throughout a controlled range of temperatures during an indicia filling process. In

an example, the laminating apparatus may generate heat across a controlled range of temperatures in accordance with a particular time sequence and/or duration of the process. The laminating apparatus may be configured to transfer heat to the laminating film (e.g., directly or indirectly) from the locating nest, from the pressure plate, or from a combination of the locating nest and the pressure plate. The laminating apparatus may be configured to generate repeatable temperature and/or heat distribution over consecutive cycles of an example indicia filling process.

(52) In accordance with an example implementation of a laminating apparatus, the locating nest may include a substantially plate-shaped body that defines a rectangular outer perimeter and an upward-facing inner surface. The body may define a recess that extends into the inner surface. The locating nest may include a resiliently deformable pad that is configured to be received in the recess. The pad may be sized such that when a blank **500** is positioned on the pad during an example indicia filling process, the outer perimeter of the blank **500** does not extend beyond corresponding sides of the pad. For example, the pad may define a rectangular shape, and may be elongate between first and second ends such that the pad defines a length that is longer than a height of the blank **500**, and may define first and second sides that are spaced apart from each other by a distance that is substantially equal to a width of the blank **500**.

(53) The pad may be configured to promote conformance of the laminating film into the respective indicia **540** of one or more veneers **530** during an indicia filling process. For example, during an example indicia filling process, the filler blank may be compressed between a blank **500** and the pad. The pad may deform resiliently under compressive forces generated by the laminating apparatus, such that corresponding portions of the pad bias the tabs of the filler blank into corresponding veneers **530** of the blank **500**, which may cause the laminating film to flow into the indicia **540** of the veneers **530**. The locating nest may be configured to generate and/or transfer heat at one or more locations along the inner surface.

(54) The locating nest may define one or more alignment features that may allow the filler blank, the adhesive release layer, and/or the blank **500** to be properly located during an example indicia filling process. For example, the locating nest may define one or more posts that extend upward from the inner surface of the body along a direction that is perpendicular to the inner surface. Each post may be configured to receive one or more of a corresponding aperture in the support strip of the filler blank, a corresponding aperture in the adhesive release layer, or an aperture **506** or **508** of a blank **500**. The posts may be configured to facilitate proper orientation and alignment of the filler blank, the adhesive release layer, and a blank **500** relative to each other, and relative to the pad, during an indicia filling process.

(55) The locating nest may define a groove that extends into the body along a portion of the outer perimeter of the body. The groove may be configured to facilitate removal of the filler blank, the adhesive release layer, and a blank **500** at the conclusion of an indicia filling process. The filler blank, the adhesive release layer, and the blank **500** may be referred to as a laminating assembly, for instance when disposed in the laminating apparatus. The groove may be configured such that a portion of the filler blank and/or adhesive release layer extends into the groove when the laminating assembly is properly oriented in the locating nest. In an example, the groove may be sized to accommodate a finger and/or thumb of an individual.

(56) In accordance with an example implementation of a laminating apparatus, the pressure plate may include a substantially plate-shaped body that defines a downward-facing inner surface. The body of the pressure plate may define a rectangular outer perimeter that is substantially the same as that of the locating nest. Stated differently, the inner surface of the pressure plate may define an area that is substantially the same as an area defined by the inner surface of the locating nest. The pressure plate may define one or more openings that extend into the inner surface. The openings may be configured to receive respective ones of the posts of the locating nest as the pressure plate and the locating nest move toward each other during an indicia filling process. The pressure plate may be configured to generate and/or transfer heat at one or more locations along the inner surface.

(57) One or both of the locating nest and the pressure plate may be configured such that laminating film of the filler blank that comes into contact with respective surfaces of the locating nest and/or the pressure plate during an indicia filling process will not adhere to and/or accumulate on those surfaces. One or both of the locating nest and the pressure plate may be configured such that portions of the blank **500** (e.g., the veneers **530**) that come into contact with respective surfaces of the locating nest and/or the pressure plate during an indicia filling process will not adhere to those surfaces. It should be appreciated that the laminating apparatus is not limited to the laminating press as described herein. For example, an alternative implementation of an indicia filling process may utilize a locating “sandwich” and a heated roller laminator.

(58) In an example indicia filling process using laminating film, the laminating apparatus may be prepared before the process is initiated. For example, preparation of the laminating apparatus may include placing a first release film on the pad in the locating nest and a second release film on the inner surface of the pressure plate. The first release film may be dimensioned such that an outer perimeter of the first release film conforms to an outer perimeter of the pad, or may be otherwise dimensioned. The second release film may be dimensioned such that an outer perimeter of the second release film conforms to an outer perimeter of the inner surface of the pressure plate, or may be otherwise dimensioned.

(59) In a first step of the example indicia process, the filler blank, the adhesive release layer, and the blank **500** may be positioned on the locating nest, so as to define a laminating assembly. The filler blank, the adhesive release layer, and the blank **500** may be disposed onto the locating nest such that one or more posts of the locating nest are received in corresponding apertures of the filler blank, the adhesive release layer, and the blank **500**, which may ensure proper orientation of the filler blank, the adhesive release layer, and the blank **500** relative to each other. The filler blank may be disposed onto the locating nest such that the polyester side faces the inner surface of the locating nest, and rests against the first release film and the pad, with the EVA side facing upward toward the inner surface of the pressure plate. In this regard, the polyester side of the filler blank may be referred to as a back side relative to the veneers **530**, and the EVA side of the filler blank may be referred to as a front side relative to the veneers **530**. The adhesive release layer may be placed on the filler blank, such that it rests on the EVA side of the filler blank. The blank **500** may then be disposed onto the adhesive release layer and filler blank, with the rear surface **504** of the blank **500** facing the inner surface of the locating nest and the front surface **502** of the blank facing the inner surface of the pressure plate. It should be appreciated that the orientation of the laminating assembly relative to the laminating apparatus is not limited to the example orientation described herein. For instance, the laminating assembly may be alternatively oriented in the laminating apparatus, such as in an inverted or rotated orientation relative to the orientation described herein.

(60) In a second step of the example indicia filling process, with the laminating assembly positioned on the locating nest, a heat and pressure cycle of the laminating apparatus may be initiated. The heat and pressure cycle may be performed for a predetermined amount of time. In accordance with an example heat and pressure cycle, the pressure plate may be configured to apply a controlled sequence of pressure and heat to the laminating assembly. As heat and pressure are applied to the filler blank, the adhesive release layer, and the blank **500**, the laminating film of the filler blank may flow into the respective indicia **540** of the veneers **530**. The laminating film may bond with one or more surfaces of the veneers **530**. For example, the laminating film may adhere to the inner surfaces of the indicia **540** and/or to the rear surfaces **535** of the veneers **530**. The pressure plate may be configured to, at the end of the controlled sequence, back off and/or remove heat and pressure from the laminating assembly such that the bond between the laminating film and the veneers **530** is maintained. It should be appreciated that the example indicia filling process is not limited to the heat and pressure cycle as described herein. For instance, the laminating apparatus may alternatively be configured such that heat may be applied to the laminating assembly

by the pressure plate but not by the locating nest, or may be applied to the laminating assembly by both the pressure plate and the locating nest.

(61) In a third step of the example indicia filling process, the finished laminating assembly may be removed from the laminating apparatus. The finished laminating assembly may be cooled, for instance actively and/or passively, to allow the laminating film to cure before the laminating assembly is removed from the laminating apparatus. The finished laminating assembly may be actively cooled, for example, during a timed cooling cycle performed using a solenoid-controlled air jet. Alternatively, the finished laminating assembly may be allowed to passively cool for a period of time before removal from the laminating apparatus. In an example of removing the laminating assembly, an individual may insert a finger and thumb into the groove, may pinch exposed portions of the filler blank and/or the adhesive release layer, and may remove the finished laminating assembly from the laminating apparatus, for example by lifting the finished laminating assembly away from the inner surface of the locating nest.

(62) In a fourth step, with the finished laminating assembly removed from the laminating apparatus, excess laminating film and/or adhesive release material may be removed from the finished laminating assembly. For example, excess laminating film and/or adhesive release material may be pulled from the veneers **530**. The excess material may be removed while the veneers **530** are attached to the blank **500** or after the veneers **530** have been detached from the blank **500**.

(63) In another example implementation, the filler material may backfilled into the indicia **540** without the application of heat. The filler material may be any suitable material, such as ultraviolet (UV) curable acrylic adhesive. In accordance with an example of backfilling the indicia **540**, the blank **500** may be placed, front surface **502** facing downward, on a flat surface. The filler material may then be disposed into the indicia **540** along the rear surfaces **535** of the veneers **530**. For example, the acrylic adhesive may be mechanically disposed (e.g., pressed) into the indicia **540**.

(64) The filler material may at least partially fill the indicia **540**. For example, the filler material may fill the indicia **540** such that the filler material defines a filler surface that may be subsurface or convex relative to the front surfaces **533** of veneers **530**. In such an example, the filler surface may define one or more fillets along edges of the inner surfaces of the indicia **540**, which may reduce the effective depth of the indicia **540**. Alternatively, the filler material may fill the indicia **540** such that at least a portion of a filler surface defined by the filler material is substantially flush with (e.g., coplanar with) the front surfaces **533** of veneers **530**.

(65) Once disposed into the indicia **540**, the acrylic adhesive may be cured, which may cause the acrylic adhesive to bond to the veneers **530**, for instance to inner surfaces of the indicia **540** and/or to the rear surfaces **535** of the veneers **530**. Optionally, the rear surface **535** of each veneer **530** may be wiped, for instance to remove excess filler material. It should be appreciated that disposing the filler material into the indicia **540** is not limited to a backfilling process as described herein, and that the filler material may otherwise be disposed into the indicia **540**. For example, the filler material may alternatively be disposed into the indicia **540** along the front surfaces **533** of the veneers **530**. Such a front surface **533** application may be performed without wiping filler material from the veneers **530**.

(66) Returning now to the example process **400**, at **412**, the veneers **530** may be separated from the blank **500**. For example, each veneer **530** may be freed by causing the tabs **509** to break, thereby releasing the veneer **530** from the blank **500**. It should be appreciated that any portions of the tabs **509** that remain attached to the veneers **530** after separation of the veneers **530** from the blank **500** may be too small to see with the naked eye or to feel, such that a secondary cleaning process may not be performed on the veneers **530** after separation from the blank **500**.

(67) At **414**, assembly of the buttons **510** may be completed by securing each veneer **530** to a corresponding button body **520** (e.g., as shown in FIGS. **8A-8B**). The button body **520** of each button **510** may be referred to as a carrier portion, such as a carrier portion of the button **510** or more generally as a carrier portion of a control device in which the button **510** is installed, such as

the keypad **100**. Each button body **520** may have a front wall **522** that defines a front surface **523** and an opposed rear surface **525** of the of the button body **520**. The front wall **522** of each button body **520** may be referred to as an outer surface of the button **510**. Each button body **520** may further include perimeter walls **524** that extend rearward from the front wall **522**. The perimeter walls **524** may define an outer perimeter that is slightly longer than that of the front wall **522**, such that each button body **520** defines a shallow shelf **526** that extends around the perimeter of the front wall **522**, such that the front wall **522** defines a projection relative to the perimeter walls **524**.

(68) The plate portion **532** and peripheral walls **534** of each veneer **530** may define a cavity **538** that extends into a rear of the veneer **530**. The front wall **522** of each button body **520** may be configured to be received in the cavity **538** of a corresponding one of the veneers **530**, for instance such that the peripheral walls **534** of the veneer **530** extend to the perimeter walls **524** of the button body **520**. In this regard, each button body **520** may be configured such that the plate portion **532** and the peripheral walls **534** of a corresponding veneer **530** at least partially enclose the front wall **522** of the button body **520** when the veneer **530** is attached to the button body **520**. When each veneer **530** is secured in place relative to a corresponding button body **520**, the rear surface **535** of the plate portion **532** may abut the front surface **523** of the button body **520**. The veneers **530** may be secured to corresponding button bodies **520** using an adhesive, for example. It should be appreciated that the veneers **530** may be otherwise secured to the corresponding button bodies **520**, for example via mechanical attachment, such as tabs, snap locks, fasteners, or the like.

(69) The button bodies **520** may be made of a translucent material, for instance white or clear plastic, such that when the button bodies **520** are backlit, light may pass through the button bodies **520** and reach the rear surfaces **535** of the plate portions **532** of the veneers **530**. Such light may be emitted, for example, from the interior of a control device in which the buttons **510** are installed. In accordance with such an implementation, the indicia **540** of the veneers **530** may expose corresponding underlying surfaces of the button bodies **520**, such that the indicia **540** may be illuminated when the button bodies **520** are backlit. In this regard, the veneers **530** may be configured to be secured to the backlit buttons of a control device.

(70) It should be appreciated that the example process **400** is not limited to the illustrated operations **402-414**. For example, one or more operations of the example process **400** may be omitted. To illustrate, in an alternative example process the formation of the blank **500**, at **402**, may be omitted. However, the remaining portions of the process **400** may be performed on the unformed blank **500**. It should further be appreciated that the example process **400** is not limited to the illustrated order of performing the operations. For example, the veneers **530** may be separated from the blank **500** before the filler material is disposed into the indicia **540**, such that **412** may alternatively be performed before **410**.

(71) It should be appreciated that the example processes and manufacturing techniques illustrated and described herein are not limited to the production of laser-cut veneers for application to the buttons of backlit keypads, and that those example processes and manufacturing techniques may be otherwise applied, for instance to laser cutting other components of a control device.

(72) For example, FIG. **9** depicts an example control device that may be configured to operate in a load control system for controlling one or more load control devices and/or electrical loads, such as lighting loads, motorized window treatments, or the like. As shown, the example load control device is configured as a wall-mounted keypad **600**. The keypad **600** may include a faceplate **602**, one or more buttons **610**, and a housing **620** that is configured to be mounted to a structure, such as within a wallbox that is installed in an interior wall of a building. The faceplate **602** may define an opening **604** that extends therethrough and that is configured to at least partially receive the buttons **610** and a bezel **614** that carries the buttons **610**. The illustrated keypad **600** may be configured to control a load control device, such as a load control device configured to control an amount of power delivered to one or more electrical loads (e.g., one or more lighting loads) from a power source, such as an alternating-current (AC) power source or a direct current (DC) power source.

(73) The faceplate **602** may include a faceplate body (not shown) and a veneer **630** that is attached to a front surface of the faceplate body. The faceplate body may be referred to as a carrier portion, such as a carrier portion of the faceplate **602** or more generally as a carrier portion of the keypad **600**. The veneer **630** of the faceplate **602** may include a plate portion **632** and peripheral walls **634** that extend around a perimeter of the veneer **630**. The plate portion **632** may define a front surface **633** of the veneer **630**, and more generally a front surface of the faceplate **602**. As shown, the plate portion **632** may define a flat, substantially planar front surface **633**. The veneer **630** may be made of any suitable material, such as metal. The veneer **630** may be made of sheet metal, for example, and the plate portion **632** and the peripheral walls **634** may be defined, for example by an embossing process, a progressive stamping process, or the like.

(74) The plate portion **632** and peripheral walls **634** of the veneer **630** may define a cavity **638** that extends into a rear of the veneer **630**. The faceplate body may be configured to be received in the cavity **638** of the veneers **630**. The veneer **630** may be secured to the faceplate body using an adhesive, for example. It should be appreciated that the veneer **630** may be otherwise secured to the faceplate body, for example via mechanical attachment, such as tabs, snap locks, fasteners, or the like.

(75) The veneer **630** may include one or more indicia, such as indicia **640** that are defined in the plate portion **632** of the veneer **630**. In accordance with the faceplate **602** of the illustrated keypad **600**, the indicia **640** may be words that are indicative of respective functions that may be performed by the keypad **600**, and that may be invoked by depressing the buttons **610**. The indicia **640** may be laser cut through the veneer **630**. For example, the indicia **640** may be formed during a laser cutting process. Forming the indicia **640** of the veneer **630** via a laser cutting process may enable the indicia **640** to exhibit one or more characteristics that are not typically achievable in indicia defined via known processes of button veneer manufacture, such as machining. Examples of such characteristics are illustrated in FIGS. 2 and 3 and described herein.

(76) The keypad **600** may include one or more lighting elements (not shown) that are configured to illuminate the indicia **640** from within the interior of the keypad **600**, such that the indicia **640** are backlit. For example, the keypad **600** may include a plurality of lighting elements, such as light emitting diodes (LEDs), that are disposed within the housing **620** of the keypad **600**, behind the faceplate **602**, and that are configured to backlight the faceplate **602**. In this regard, the illustrated keypad **600** may be referred to as a backlit keypad or control device.

(77) As shown, the indicia **640** extend into the front surface **633** of the veneer **630** and through the plate portion **632**. The front surface **633** of the veneer **230** may alternatively be referred to as an outer surface of the veneer **630**, and more generally as an outer surface of the faceplate **602**. The faceplate body may be made of a translucent material, for instance white or clear plastic, such that when the faceplate body is backlit, light may pass through the faceplate body and reach an inner surface of the veneer **630**, for example an inner surface of the plate portion **632**. Such light may be emitted, for example, from the interior of the keypad **600**. In accordance with such an implementation, the indicia **640** of the veneer **630** may expose corresponding underlying surfaces of the faceplate body, such that the indicia **640** may be illuminated when the faceplate body is backlit. In this regard, the veneer **630** may be configured to be secured to a backlit faceplate of a control device.

(78) The illustrated indicia **640** include letters that form respective words. However, the indicia **640** are not limited to letters, and may include any combination of alphanumeric characters, icons (e.g., symbols), or the like. The indicia **640** may be representative of a command for controlling an electrical load. For example, the indicia **640** may be representative of: a command message that may be transmitted by the keypad **600**; of a command that is executed internally by the keypad **600**; of a result of the performance of a command; or the like. To illustrate, the indicia **640** may be representative of predetermined scenes that correspond to respective lighting intensities of one or more lighting loads that are controlled by the keypad **600**. One or more command messages to

invoke a corresponding scene may be transmitted by the keypad **600** in response to one or more actuations of the buttons **610**, for example.

(79) The veneer **630** may include a filler material (not shown) that is disposed into the indicia **640**. The filler material may, for example, be backfilled into the indicia **640** such that the filler material is coplanar with the front surface **633** of the veneer **630**. The filler material may, for example, function to improve the optical performance of the indicia **640** when one or more of the buttons **610** are backlit, for instance to improve the readability of the indicia **640** when viewed from off angle.

Claims

1. A veneer that is configured to be secured to a control device that backlights the veneer, the veneer comprising: a metal plate portion that includes two or more openings defined therethrough by a laser cutting process, wherein the openings cooperate to define a backlit indicia and wherein at least one of the openings has a variable width; a filler material disposed in the two or more openings, wherein the filler material is at least one of subsurface or convex relative to a front surface of the veneer, and the filler material improves at least one of an optical performance of the backlit indicia or a readability of the backlit indicia when viewed from off angle; and a rib that extends between the two or more openings and suspends a floating portion of the backlit indicia, wherein the floating portion is at least partially surrounded by the two or more openings.
2. The veneer of claim 1, wherein the backlit indicia is at least one of text comprising an alphanumeric character or an icon.
3. The veneer of claim 1, wherein the veneer is affixed to, or located adjacent to, a button of the control device, wherein the button, when actuated, is associated with a command for controlling an electrical load comprising a lighting load or a motorized window treatment load, and wherein the backlit indicia is representative of the command.
4. The veneer of claim 1, wherein the filler material is pressed into a rear surface of the veneer.
5. The veneer of claim 1, wherein the rib has a thickness selected to be optically difficult to perceive.
6. A control device, comprising: a translucent carrier portion configured to be backlit by one or more light emitting diodes; a button associated with a command communicated by the control device for controlling an external electrical load when the button is actuated; a metal veneer disposed on the carrier portion, wherein the veneer includes at least two openings defined therethrough by a laser cutting process, wherein at least one of the openings has a variable width, and wherein the openings define a backlit indicia; and a filler material disposed in the openings, wherein the filler material is at least one of subsurface or convex relative to a front surface of the veneer, and the filler material improves at least one of an optical performance of the backlit indicia or a readability of the backlit indicia when viewed from off angle.
7. The control device of claim 6, wherein the control device has a plurality of buttons, each button associated with a unique command for controlling the electrical load using the control device.
8. The control device of claim 7, wherein the control device has a plurality of backlit indicia, wherein each backlit indicia is at least one of text or an icon, each backlit indicia indicating a function of a respective button.
9. The control device of claim 6, wherein the filler material comprises a curable acrylic adhesive.
10. The control device of claim 6, wherein the filler material comprises a laminating film.
11. A method, comprising: embossing a metal sheet blank to outline a veneer; laser cutting two or more openings through the veneer to define an indicia, wherein at least one of the openings has a variable width; laser cutting another set of openings around a portion of the outline so that the veneer is partially cut out from the blank; placing filler material into the two or more openings that define the indicia from a rear surface of the veneer; and attaching the veneer to a translucent carrier

portion of a control device, wherein the carrier portion is configured to be backlit by one or more light emitting diodes.

12. The method of claim 11, further comprising applying a surface finish to a front surface of the veneer.

13. The method of claim 11, further comprising leaving a rib that extends between the two or more openings to suspend a floating portion of the indicia.

14. The method of claim 13, wherein the rib has a thickness selected to be optically difficult to perceive.

15. The method of claim 11, wherein the filler material is coplanar with a front surface of the veneer.

16. The method of claim 11, wherein the filler material is at least one of subsurface or convex relative to a front surface of the veneer.

17. The method of claim 11, wherein the filler material comprises a curable acrylic adhesive.

18. The method of claim 11, wherein the filler material comprises a laminating film.
