

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402427
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Otsuji; Hironari et al.

Imaging device having a plurality of in-layer lenses with corresponding on-chip lenses

Abstract

The deterioration of the image quality of an imaging element is to be prevented. The imaging element includes an on-chip lens, a photoelectric conversion unit, and a plurality of in-layer lenses. The on-chip lens collects incident light from a subject. The photoelectric conversion unit performs photoelectric conversion on the collected incident light. The plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens. Furthermore, the plurality of in-layer lenses allows the incident light that has passed through any one of the plurality of in-layer lenses to be incident on the photoelectric conversion unit.

Inventors:	Otsuji; Hironari (Kanagawa, JP), Kawano; Hiroyuki (Kanagawa, JP)
Applicant:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Family ID:	1000008782643
Assignee:	Sony Semiconductor Solutions Corporation (Kanagawa, JP)
Appl. No.:	17/299901
Filed (or PCT Filed):	November 12, 2019
PCT No.:	PCT/JP2019/044250
PCT Pub. No.:	WO2020/137203
PCT Pub. Date:	July 02, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220028912 A1	Jan. 27, 2022

Foreign Application Priority Data

JP 2018-242282 Dec. 26, 2018

Publication Classification

Int. Cl.: H10F39/00 (20250101); G02B3/00 (20060101); G02B5/20 (20060101); H10F39/12 (20250101); H10F39/18 (20250101)

U.S. Cl.:

CPC H10F39/8063 (20250101); G02B3/0037 (20130101); G02B5/208 (20130101); H10F39/024 (20250101); H10F39/182 (20250101); H10F39/199 (20250101); H10F39/8053 (20250101); H10F39/8057 (20250101);

Field of Classification Search

CPC: H01L (27/14627); H01L (27/14621); H01L (27/14645); G02B (3/0037); G02B (5/208)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7948555	12/2010	Kwon	N/A	N/A
2007/0210345	12/2006	Oda	257/E27.133	H01L 27/14643
2009/0122178	12/2008	Kwon	N/A	N/A
2013/0037698	12/2012	Maeda	257/E31.127	H10F 39/8053
2014/0071244	12/2013	Hirota	348/46	H04N 13/257
2015/0070532	12/2014	Masuda	438/70	H10F 39/024
2015/0281538	12/2014	Boettiger	348/262	H04N 23/90
2016/0013233	12/2015	Noudo	438/69	H10F 39/199
2019/0081098	12/2018	Lenchenkov	N/A	G02B 13/0085

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1574377	12/2004	CN	N/A
101069107	12/2006	CN	N/A
101292177	12/2007	CN	N/A
101853868	12/2009	CN	N/A
102693997	12/2011	CN	N/A
103000646	12/2012	CN	N/A

104900664	12/2014	CN	N/A
105009288	12/2014	CN	N/A
2001094086	12/2000	JP	N/A
2004356269	12/2003	JP	N/A
2005011969	12/2004	JP	N/A
2007158109	12/2006	JP	N/A
2007242857	12/2006	JP	N/A
2010239003	12/2009	JP	N/A
2010283082	12/2009	JP	H01L 27/14627
2010283082	12/2009	JP	H01L 27/14627
2011146608	12/2010	JP	N/A
2012204354	12/2011	JP	N/A
2013004635	12/2012	JP	N/A
2014075445	12/2013	JP	H10F 39/8063
2015167219	12/2014	JP	N/A
2015170620	12/2014	JP	N/A
2016-201397	12/2015	JP	N/A
2017034280	12/2016	JP	N/A
2017041474	12/2016	JP	N/A
2018046145	12/2017	JP	N/A
2018-201601	12/2017	JP	N/A
2018201061	12/2017	JP	N/A
100731094	12/2006	KR	N/A
201724484	12/2016	TW	N/A
WO-2014156704	12/2013	WO	N/A
WO-2016114154	12/2015	WO	N/A
WO-2018051604	12/2017	WO	H01L 27/14605
WO2018/173872	12/2017	WO	N/A
WO-2018211813	12/2017	WO	G02B 5/201

OTHER PUBLICATIONS

International Search Report issued in International Patent Application No. PCT/JP2019/044250 on Feb. 10, 2020 and English translation of same. 7 pages. cited by applicant

Written Opinion issued in International Patent Application No. PCT/JP2019/044250 on Feb. 10, 2020. 5 pages. cited by applicant

Primary Examiner: Assouman; Herve-Louis Y

Attorney, Agent or Firm: K&L Gates LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to an imaging element and an imaging apparatus. Specifically, the present disclosure relates to an imaging element that includes an on-chip lens and an in-layer lens, and an imaging apparatus that includes the imaging element.

BACKGROUND ART

(2) As an imaging element in which pixels that convert incident light to image signals are arranged

in a two-dimensional grid, a rear surface irradiation type imaging element has been conventionally used. This rear surface irradiation type imaging element is an imaging element in which a semiconductor substrate is irradiated with incident light from its rear surface side, the rear surface being different from a surface (front surface) of the semiconductor substrate in which a wiring region is formed. This can improve sensitivity in comparison with an imaging element that is irradiated with incident light from its front surface side. In the rear surface irradiation type imaging element, there is a case where incident light passes through the semiconductor substrate without being absorbed in the semiconductor substrate, and is reflected by a wiring layer of the wiring region. Especially, light having a long wavelength such as red light easily passes through the semiconductor substrate, so that an amount of light reflected by the wiring layer increases. When this reflected light is reflected outside the imaging element and incident on another pixel again, color mixture or the like occurs and image quality is degraded.

(3) In addition, if a light amount of this reflected light changes in accordance with an incident angle of the incident light, the image quality is further degraded. This is because the light amount of the reflected light that is incident on another pixel changes in accordance with the incident angle, and then sensitivity of the pixel fluctuates. To reduce the degradation of the image quality, proposed is an imaging element in which wiring in a wiring layer is configured in a symmetric form about the center of a pixel (for example, refer to Patent Literature 1). In this imaging element, the symmetrically configured wiring can make the light amount of the reflected light from the pixel constant regardless of the incident angle.

CITATION LIST

Patent Document

(4) Patent Document 1: Japanese Patent Application Laid-Open No. 2016-201397

SUMMARY OF THE INVENTION

Problems to be Solved by the Invention

(5) The conventional technology described above has an issue of being incapable of reducing reflection of incident light from the wiring layer and of preventing the degradation of the image quality.

(6) The present disclosure has been made in view of the above issue, and is directed to prevention of the deterioration of the image quality.

Solutions to Problems

(7) The present disclosure is provided to solve the above problem, and a first aspect of the present disclosure is an imaging element, including an on-chip lens configured to collect incident light from a subject, a photoelectric conversion unit configured to perform photoelectric conversion on the collected incident light, and a plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens, in which the plurality of in-layer lenses is configured to allow the incident light that has passed through any one of the plurality of in-layer lenses to be incident on the photoelectric conversion unit.

(8) Furthermore, in this first aspect, the plurality of in-layer lenses may be arranged in substantially an identical layer.

(9) Furthermore, in this first aspect, the plurality of in-layer lenses may be simultaneously formed.

(10) Furthermore, in this first aspect, a color filter configured to allow light having a predetermined wavelength, out of the incident light that has passed through the on-chip lens, to transmit through the color filter, may further be included.

(11) Furthermore, in this first aspect, the color filter may be configured to allow red light to transmit through the color filter.

(12) Furthermore, in this first aspect, the color filter may be configured to cause infrared light to transmit through the color filter.

(13) Furthermore, in this first aspect, one of the plurality of in-layer lenses may be arranged on an

optical axis of the on-chip lens.

(14) Furthermore, in this first aspect, the plurality of in-layer lenses may have mutually different shapes

(15) Furthermore, in this first aspect, a plurality of pixels each including the on-chip lens, the photoelectric conversion unit, and the plurality of in-layer lenses may further be included.

(16) Furthermore, in this first aspect, the plurality of in-layer lenses may be arranged asymmetrically about a center of each pixel.

(17) Furthermore, in this first aspect, a phase difference pixel that includes the on-chip lens and the photoelectric conversion unit, and that is configured to detect a phase difference by performing pupil division on the incident light from the subject may further be included.

(18) Furthermore, a second aspect of the present disclosure is an imaging apparatus, including an on-chip lens configured to collect incident light from a subject, a photoelectric conversion unit configured to perform photoelectric conversion on the collected incident light, a plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens, and a processing circuit configured to process an image signal on the basis of the photoelectric conversion in the photoelectric conversion unit, in which the plurality of in-layer lenses is configured to allow the incident light that has passed through any one of the plurality of in-layer lenses to be incident on the photoelectric conversion unit.

(19) Employing such aspects provides effects that incident light, which has passed through the on-chip lens, is individually collected by the plurality of in-layer lenses. A supposed case is that incident light is collected at different positions in the photoelectric conversion unit.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating a configuration example of an imaging element according to embodiments of the present disclosure.

(2) FIG. 2 is a diagram illustrating a configuration example of a pixel according to the embodiments of the present disclosure.

(3) FIG. 3 is a plan view illustrating a configuration example of pixels according to a first embodiment of the present disclosure.

(4) FIG. 4 is a sectional view illustrating a configuration example of a pixel according to the embodiments of the present disclosure.

(5) FIG. 5 is a diagram illustrating a light path of incident light in a conventional pixel.

(6) FIG. 6 is a diagram illustrating an example of a light path of incident light in the pixel according to the first embodiment of the present disclosure.

(7) FIG. 7 is a diagram illustrating an example of a manufacturing method of the imaging element according to the embodiments of the present disclosure.

(8) FIG. 8 is a diagram illustrating the example of the manufacturing method of the imaging element according to the embodiments of the present disclosure.

(9) FIG. 9 is a plan view illustrating a configuration example of a pixel according to a second embodiment of the present disclosure.

(10) FIG. 10 is a plan view illustrating a first configuration example of a pixel according to a third embodiment of the present disclosure.

(11) FIG. 11 is a plan view illustrating a second configuration example of the pixel according to the third embodiment of the present disclosure.

(12) FIG. 12 is a plan view illustrating a third configuration example of the pixel according to the third embodiment of the present disclosure.

- (13) FIG. 13 is a plan view illustrating a fourth configuration example of the pixel according to the third embodiment of the present disclosure.
- (14) FIG. 14 is a plan view illustrating a configuration example of a pixel according to a fourth embodiment of the present disclosure.
- (15) FIG. 15 is a diagram illustrating an example of a light path of incident light in the pixel according to the fourth embodiment.
- (16) FIG. 16 is a plan view illustrating a configuration example of a pixel according to a fifth embodiment of the present disclosure.
- (17) FIG. 17 is a plan view illustrating another configuration example of the pixel according to the fifth embodiment of the present disclosure.
- (18) FIG. 18 is a plan view illustrating a configuration example of a pixel array unit according to a sixth embodiment of the present disclosure.
- (19) FIG. 19 is a block diagram illustrating a schematic configuration example of a camera as an example of an imaging apparatus to which the present technology can be applied.
- (20) FIG. 20 is a view depicting an example of a schematic configuration of an endoscopic surgery system.
- (21) FIG. 21 is a block diagram depicting an example of a functional configuration of the camera head and the CCU.
- (22) FIG. 22 is a block diagram depicting an example of schematic configuration of a vehicle control system.
- (23) FIG. 23 is a diagram of assistance in explaining an example of installation positions of an outside-vehicle information detecting section and an imaging unit.

MODE FOR CARRYING OUT THE INVENTION

(24) Subsequently, modes for carrying out the present disclosure (hereinafter referred to as embodiments) will be described with reference to the drawings. In the following drawings, an identical or similar part is denoted by an identical or similar reference sign. In addition, the embodiments will be described in the following order. 1. First Embodiment 2. Second Embodiment 3. Third Embodiment 4. Fourth Embodiment 5. Fifth Embodiment 6. Sixth Embodiment 7. Examples of practical use for camera 8. Examples of practical use for endoscopic surgery system 9. Examples of practical use for mobile objects

1. First Embodiment

(25) [Configuration of Imaging Element]

(26) FIG. 1 is a diagram illustrating a configuration example of an imaging element according to embodiments of the present disclosure. An imaging element 1 illustrated in FIG. 1 includes a pixel array unit 10, a vertical drive unit 20, a column signal processing unit 30, and a control unit 40.

(27) The pixel array unit 10 is configured by arranging pixels 100 in a two-dimensional grid. The pixel 100 mentioned herein generates an image signal in accordance with irradiated light. This pixel 100 includes a photoelectric conversion unit that generates a charge in accordance with irradiated light. In addition, the pixel 100 further includes a pixel circuit. This pixel circuit generates an image signal based on the charge generated by the photoelectric conversion unit. The generation of the image signal is controlled by a control signal generated by the vertical drive unit 20, which will be described later. In the pixel array unit 10, signal lines 11 and 12 are arranged in a XY matrix. The signal line 11 is a signal line that transmits a control signal for a pixel circuit in the pixel 100, is arranged on a row-by-row basis in the pixel array unit 10, and is wired in common to pixels 100 arranged in each row. The signal line 12 is a signal line that transmits an image signal generated by the pixel circuit in the pixel 100, is arranged on a column-by-column basis in the pixel array unit 10, and is wired in common to pixels 100 arranged in each column. The photoelectric conversion unit and the pixel circuit are formed on a semiconductor substrate.

(28) The vertical drive unit 20 generates a control signal for the pixel circuit in the pixel 100. This vertical drive unit 20 transmits the generated control signal to the pixel 100 via the signal line 11

illustrated in FIG. 1. The column signal processing unit **30** performs processing on an image signal generated by the pixel **100**. This column signal processing unit **30** performs the processing on the image signal transmitted from the pixel **100** via the signal line **12** illustrated in FIG. 1. The processing in the column signal processing unit **30** corresponds to, for example, analog-to-digital conversion to convert an analog image signal generated in the pixel **100** to a digital image signal. The image signal generated by the column signal processing unit **30** is output as an image signal of the imaging element **1**. The control unit **40** controls the whole of the imaging element **1**. This control unit **40** controls the imaging element **1** by generating and outputting a control signal that controls the vertical drive unit **20** and the column signal processing unit **30**. The control signal generated by the control unit **40** is transmitted to the vertical drive unit **20** by a signal line **41** and transmitted to the column signal processing unit **30** by a signal line **42**. Note that the column signal processing unit **30** is an example of a processing circuit described in the claims.

(29) [Circuit Configuration of Pixel]

(30) FIG. 2 is a diagram illustrating a configuration example of a pixel according to the embodiments of the present disclosure. FIG. 2 is a circuit diagram illustrating a configuration example of the pixel **100**. The pixel **100** illustrated in FIG. 2 includes a photoelectric conversion unit **101**, a charge holding unit **102**, and metal oxide semiconductor (MOS) transistors **103** to **106**.

(31) The anode of the photoelectric conversion unit **101** is grounded, and the cathode thereof is connected to the source of the MOS transistor **103**. The drain of the MOS transistor **103** is connected to the source of the MOS transistor **104**, the gate of the MOS transistor **105**, and one end of the charge holding unit **102**. The other end of the charge holding unit **102** is grounded. The drains of the MOS transistors **104** and **105** are connected in common to a power supply line Vdd, and the source of the MOS transistor **105** is connected to the drain of the MOS transistor **106**. The source of the MOS transistor **106** is connected to the signal line **12**. The gates of the MOS transistors **103**, **104**, and **106** are connected to a transfer signal line TR, a reset signal line RST, and a selection signal line SEL, respectively. Note that the transfer signal line TR, the reset signal line RST, and the selection signal line SEL constitute the signal line **11**.

(32) The photoelectric conversion unit **101** generates a charge in accordance with irradiated light as described above. A photodiode can be used for this photoelectric conversion unit **101**. In addition, the charge holding unit **102** and the MOS transistors **103** to **106** constitute the pixel circuit.

(33) The MOS transistor **103** is a transistor that transfers a charge generated by photoelectric conversion performed by the photoelectric conversion unit **101** to the charge holding unit **102**. The transfer of the charge by the MOS transistor **103** is controlled by a signal transmitted by the transfer signal line TR. The charge holding unit **102** is a capacitor that holds the charge transferred by the MOS transistor **103**. The MOS transistor **105** is a transistor that generates a signal based on the charge held by the charge holding unit **102**. The MOS transistor **106** is a transistor that outputs the signal generated by the MOS transistor **105** to the signal line **12** as an image signal. This MOS transistor **106** is controlled by a signal transmitted by the selection signal line SEL.

(34) The MOS transistor **104** is a transistor that resets the charge holding unit **102** by discharging the charge held by the charge holding unit **102** to the power supply line Vdd. The resetting by this MOS transistor **104** is controlled by a signal transmitted by the reset signal line RST, and executed before the charge is transferred by the MOS transistor **103**. Note that at the time of the resetting, it is possible to also reset the photoelectric conversion unit **101** by bringing the MOS transistor **103** into conduction. In this manner, the pixel circuit converts the charge generated by the photoelectric conversion unit **101** to the image signal.

(35) [Configuration of Pixel]

(36) FIG. 3 is a plan view illustrating a configuration example of pixels according to a first embodiment of the present disclosure. FIG. 3 is a diagram illustrating a configuration example of the pixels **100** arranged in the pixel array unit **10**. In FIG. 3, a rectangle in a solid line represents the pixel **100**; a rectangle in a dotted line represents an n-type semiconductor region **111**.

constituting the photoelectric conversion unit **101**; a circle in an alternate long and two short dashes line represents an on-chip lens **180**; and a circle in a solid line represents an in-layer lens **160**.

(37) The on-chip lens **180** is a lens that is arranged in an outermost layer of the pixel **100** and that collects incident light from a subject on the photoelectric conversion unit **101**.

(38) The in-layer lens **160** is a lens that is arranged between the on-chip lens **180** and the photoelectric conversion unit **101** and that further collects the incident light collected by the on-chip lens **180**. A plurality of the in-layer lenses **160** is arranged in each pixel **100**. The pixel **100** illustrated in FIG. 3 represents an example in which nine in-layer lenses **160** are arranged in a grid. Note that a gap **169** is formed in the arranged plurality of in-layer lenses **160**. Incident light that passes through the gap **169** is emitted to the photoelectric conversion unit **101** without passing through the in-layer lens **160**. Details of the configuration of the pixel **100** will be described later.

(39) Note that a color filter **172** (not illustrated) is arranged in the pixel **100**. This color filter **172** is an optical filter that allows light having a predetermined wavelength, out of incident light, to pass therethrough. As the color filter **172**, for example, color filters that allow red light, green light, and blue light to pass therethrough can be arranged in the respective pixels **100**. Texts illustrated in FIG. 3 represent types of color filters **172** arranged in the pixels **100**. Specifically, “R”, “G”, and “B” represent that the color filters **172** corresponding to red light, green light, and blue light, respectively, are arranged. These color filters **172** can be arranged, for example, in a Bayer array. The Bayer array mentioned herein is an array method of arranging the color filters **172** corresponding to green light in a checkered form, and arranging the color filters **172** corresponding to red light and blue light between the color filters **172** corresponding to green light. Four pixels **100** in two rows and two columns illustrated in FIG. 3 are consecutively arranged lengthwise and breadthwise to constitute the pixel array unit **10**.

(40) [Sectional Configuration of Pixel]

(41) FIG. 4 is a sectional view illustrating a configuration example of a pixel according to the embodiments of the present disclosure. FIG. 4 is a sectional view illustrating a configuration example of the pixel **100** arranged in the pixel array unit **10**. In addition, FIG. 4 is a sectional view of the imaging element **1** (the pixel array unit **10**) along a line A-A' illustrated in FIG. 3. The pixel **100** illustrated in FIG. 4 includes a semiconductor substrate **110**, a wiring region **130**, a support substrate **140**, an insulating film **120**, a light-shielding film **150**, the in-layer lens **160**, a planarizing film **171**, the color filter **172**, and the on-chip lens **180**.

(42) The semiconductor substrate **110** is a semiconductor substrate in which a semiconductor region for the elements constituting the pixel circuit described with reference to FIG. 2 is formed. FIG. 4 illustrates the photoelectric conversion unit **101** and the MOS transistor **103** among these elements. The semiconductor substrate **110** illustrated in FIG. 4 includes a p-type semiconductor region **112** constituting a well region and an n-type semiconductor region **111** formed inside the p-type semiconductor region **112**. This n-type semiconductor region **111** constitutes the photoelectric conversion unit **101**. Specifically, a p-n junction including the n-type semiconductor region **111** and the p-type semiconductor region **112** surrounding the n-type semiconductor region **111** operates as a photodiode. When this p-n junction is irradiated with incident light, a charge is generated by photoelectric conversion and accumulates in the n-type semiconductor region **111**.

(43) As described above, the charge that has accumulated in the n-type semiconductor region **111** is transferred by the MOS transistor **103**. The MOS transistor **103** illustrated in FIG. 4 is a MOS transistor that uses the n-type semiconductor region **111** as a source region and the p-type semiconductor region **112** as a channel region. This MOS transistor **103** includes a gate electrode **133**. The semiconductor substrate **110** can include, for example, silicon (Si). In addition, the vertical drive unit **20** or the like described with reference to FIG. 1 can be arranged on the semiconductor substrate **110**.

(44) The wiring region **130** is a region in which wiring that is formed on a front surface of the semiconductor substrate **110** and that electrically joins a semiconductor element formed on the

semiconductor substrate **110** is formed. A wiring layer **132** and an insulating layer **131** are arranged in the wiring region **130**. The wiring layer **132** constitutes the wiring described above. This wiring layer **132** can include, for example, copper (Cu) and tungsten (W). The insulating layer **131** insulates the wiring layer **132**. This insulation layer **131** can include, for example, silicon oxide (SiO₂) or silicon nitride (SiN). In addition, the gate electrode **133** described above is further arranged in the wiring region **130**.

(45) The support substrate **140** is a substrate that supports the imaging element **1**. This support substrate **140** is a substrate that includes a silicon wafer or the like and that increases strength of the imaging element **1** mainly at the time of manufacturing the imaging element **1**.

(46) The insulating film **120** is a film that insulates and protects a rear surface side of the semiconductor substrate **110**. This insulating film **120** can include, for example, an oxide such as SiO₂.

(47) The light-shielding film **150** is arranged in proximity to a boundary between pixels **100**, and blocks incident light coming obliquely from adjacent pixels **100**. The color filters **172** corresponding to different light are arranged in the adjacent pixels **100** as described with reference to FIG. 3. When incident light, which has passed through the different types of color filters **172** in the adjacent pixels **100**, is emitted to the photoelectric conversion unit **101**, color mixture occurs, and thus image quality is degraded. Arranging the light-shielding film **150** and blocking incident light from the adjacent pixels **100** can prevent the color mixture. An opening portion **151** is arranged in the light-shielding film **150** at a central portion of the pixel **100**. Incident light is emitted to the photoelectric conversion unit **101** via this opening portion **151**. For example, a film including W can be used for the light-shielding film **150**.

(48) The in-layer lens **160** is a lens that is formed in an inner layer of the pixel **100** and that collects incident light. A convex portion in a hemisphere shape illustrated in FIG. 4 corresponds to one in-layer lens **160**. As described above, the plurality of in-layer lenses **160** is arranged in the pixel **100**. These in-layer lenses **160** are arranged in parallel to a light path of incident light in the pixel **100**. Specifically, the plurality of in-layer lenses **160** is arranged in a configuration that incident light, which has passed through one of these in-layer lenses **160**, reaches the photoelectric conversion unit **101**. The incident light reaches the photoelectric conversion unit **101** without passing through the plurality of in-layer lenses **160**. In FIG. 4, the plurality of in-layer lenses **160** is arranged in substantially the same layer. In a case where the in-layer lenses **160** are arranged in the same layer just as described, these in-layer lenses **160** can also be formed simultaneously. Note that the configuration only needs to allow incident light, which has passed through one of the plurality of in-layer lenses **160**, to reach the photoelectric conversion unit **101**, and the plurality of in-layer lenses **160** can also be formed in different layers.

(49) The in-layer lens **160** can include an inorganic material or a resin having a high refractive index. For example, the in-layer lens **160** can include SiN or silicon oxynitride (SiON). In addition, each of the in-layer lenses **160** can have a size of 0.8 μm to 1.0 μm in diameter, for example. The in-layer lenses **160** illustrated in FIG. 4 represent an example in which lower layer portions of the in-layer lenses **160** are formed with a common film. The lower layer portions of the in-layer lenses **160** planarize a rear surface of the imaging element **1** on which the light-shielding film **150** is formed.

(50) The planarizing film **171** planarizes the rear surface of the imaging element **1** on which the in-layer lenses **160** are formed. This planarizing film **171** can include, for example, a resin. The color filter **172** and the on-chip lens **180** are laminated in an upper layer of the planarizing film **171**.

(51) The imaging element **1** illustrated in FIG. 4 corresponds to a rear surface irradiation type imaging element that is irradiated with incident light from the rear surface side of the semiconductor substrate **110**. An arrow in a solid line illustrated in FIG. 4 represents incident light with which the rear surface is irradiated. In this manner, incident light, which has passed through the on-chip lens **180** and the in-layer lens **160**, reaches the n-type semiconductor region **111** of the

semiconductor substrate **110**, and photoelectric conversion is performed. However, part of light incident on the semiconductor substrate **110** passes through the semiconductor substrate **110** without contributing to photoelectric conversion, and reaches the wiring region **130**. An arrow in a broken line illustrated in FIG. **4** represents a state in which incident light passes through the semiconductor substrate **110**. When this light that has passed therethrough is reflected by the wiring layer **132** and emitted to the outside of the pixel **100**, it becomes stray light. When this stray light is reflected by a housing or the like outside the imaging element **1**, incident on another pixel **100** again, and subjected to photoelectric conversion, noise occurs in image signals and image quality is degraded. For this reason, arranging the plurality of in-layer lenses **160** in the pixel **100** illustrated in FIG. **4** reduces reflected light from the wiring layer **132**.

(52) [Light Path of Incident Light]

(53) FIG. **5** is a diagram illustrating a light path of incident light in a pixel according to a conventional technology. FIG. **5** is a diagram illustrating, as a comparative example, the light path of incident light in the pixel in which one in-layer lens **160** is arranged, and schematically illustrating the on-chip lens **180**, the in-layer lens **160**, the n-type semiconductor region **111**, and the wiring layer **132**. An arrow in a solid line illustrated in FIG. **5** represents incident light having a relatively long wavelength such as red light, and an arrow in a dotted line represents incident light having a relatively short wavelength such as blue light. The incident light is collected by the on-chip lens **180** and the in-layer lens **160** and reaches the photoelectric conversion unit **101** (n-type semiconductor region **111**). The incident light being collected by the two lenses shortens a focal length, and thus can decrease a height of the imaging element **1**. However, in a case where incident light is not absorbed in the n-type semiconductor region **111**, i.e., not subjected to photoelectric conversion, it passes through the n-type semiconductor region **111**, reaches the wiring layer **132** in the wiring region **130**, and is reflected.

(54) The incident light having the relatively short wavelength comes into focus at a shallow position of the n-type semiconductor region **111**. In a case where the incident light is not absorbed in the n-type semiconductor region **111**, it scatters and then reaches the wiring layer **132** of the wiring region **130**. In contrast, the incident light having the relatively long wavelength comes into focus at a deep position of the n-type semiconductor region **111**. For this reason, in a case where the incident light having the relatively long wavelength is not absorbed in the n-type semiconductor region **111**, it reaches the wiring layer **132** while being concentrated in a relatively narrow range as illustrated by arrows in broken lines and is reflected. Consequently, incident light having a longer wavelength causes reflection with higher intensity.

(55) FIG. **6** is a diagram illustrating an example of a light path of incident light in the pixel according to the first embodiment of the present disclosure. The incident light, which has passed thorough the on-chip lens **180** illustrated in FIG. **6**, is collected by a plurality of (three in FIG. **6**) in-layer lenses **160a**, **160b**, and **160c**, and emitted to the n-type semiconductor region **111**. In addition, incident light, which has been emitted to a region in contact with two in-layer lenses **160**, is repeatedly reflected between the two in-layer lenses **160**, and thereafter emitted to the n-type semiconductor region **111**. In this manner, the incident light is scattered by the in-layer lenses **160** and emitted to the n-type semiconductor region **111**. In a case where the incident light is not absorbed in the n-type semiconductor region **111**, it reaches the wiring layer **132** in a widely scattered state. As a result, an amount of reflected light can be reduced. In addition, because the incident light is scattered, it is possible to have a higher degree of flexibility in laying out the wiring layer **132**. For example, the wiring layer **132** can be arranged immediately below a central portion of the photoelectric conversion unit **101**.

(56) In addition, it is preferable to employ a configuration in which one of the plurality of in-layer lenses **160** is arranged at the central portion of the pixel **100** like the in-layer lens **160b** illustrated in FIG. **6**. Specifically, one of the plurality of in-layer lenses **160** is arranged on an optical axis of the on-chip lens **180**. Since incident light that has passed through the on-chip lens **180** is collected

on the central portion of the pixel **100**, a large amount of incident light that has passed through the on-chip lens **180** can be made pass through the in-layer lens **160**. In comparison with to a case where the gap **169** is arranged on the optical axis of the on-chip lens **180**, it is possible to scatter a larger amount of incident light.

(57) [Manufacturing Method of Imaging Element]

(58) FIGS. **7** and **8** are diagrams illustrating the example of the manufacturing method of the imaging element according to the embodiments of the present disclosure. FIG. **7** is a diagram illustrating an example of a manufacturing process of the imaging element **1**. In FIG. **7**, illustration of the configuration of the pixel **100** is simplified.

(59) First, the wiring region **130** is formed on the semiconductor substrate **110** in which the p-type semiconductor region **112** and the n-type semiconductor region **111** are formed. Subsequently, the support substrate **140** is bonded to the semiconductor substrate **110**, the semiconductor substrate **110** is turned upside down, and the rear surface of the semiconductor substrate **110** is ground to decrease its wall thickness. Subsequently, the insulating film **120** and the light-shielding film **150** are arranged on the rear surface of the semiconductor substrate **110** (A in FIG. **7**).

(60) Subsequently, a lens material **401**, which is a material of the in-layer lens **160**, is arranged on the rear surface of the semiconductor substrate **110**. Formation of the lens material **401** can be performed, for example, by film formation of a lens material such as SiN using chemical vapor deposition (CVD) (B in FIG. **7**).

(61) Subsequently, a resist **402** is laminated on the lens material **401**. For example, a photoresist is employed for this resist **402**, and the resist **402** can be formed by applying the photoresist on the lens material **401** (C in FIG. **7**).

(62) Subsequently, a resist **403** having a shape similar to that of the in-layer lens **160** is formed. The formation is performed, for example, by patterning the resist **402** in a cylindrical shape or a cube shape by a lithography technology. Thereafter, the resist **403** can be formed by dissolving the patterned resist **402** using a reflow furnace or the like (D in FIG. **8**).

(63) Subsequently, dry etching is performed using the resist **403** as a mask. With this processing, the shape of the resist **403** is transferred to the lens material **401**, and the in-layer lens **160** in a hemisphere shape is formed (E in FIG. **8**). Note that FIGS. **7** and **8** each illustrate an example of forming the plurality of in-layer lenses **160** simultaneously.

(64) As described above, in the imaging element **1** according to the first embodiment of the present disclosure, arranging the plurality of in-layer lenses **160** allows incident light that has passed through the on-chip lens **180** to scatter, and allows the scattered light to be emitted to the photoelectric conversion unit **101**. This reduces reflected light from the wiring layer **132**, thereby preventing degradation of image quality.

2. Second Embodiment

(65) The nine in-layer lenses **160** are arranged in the imaging element **1** according to the first embodiment described above. In contrast, an imaging element **1** according to a second embodiment of the present disclosure is different from the first embodiment in that different numbers of in-layer lenses **160** are arranged.

(66) [Configuration of Pixel]

(67) FIG. **9** is a plan view illustrating a configuration example of a pixel according to a second embodiment of the present disclosure. FIG. **9** is a diagram illustrating a configuration example of the pixel **100** similarly to FIG. **3**. In the following description, reference signs of the same constituent elements as those illustrated in FIG. **3** are omitted.

(68) A in FIG. **9** illustrates an example of arranging four in-layer lenses **160**. In addition, B in FIG. **9** illustrates an example of arranging 16 in-layer lenses **160**. In this manner, a freely-selected number of two or more in-layer lenses **160** can be arranged in the pixel **100**. Arranging more in-layer lenses **160** can make the gap **169** between the in-layer lenses **160** smaller and scatter a larger amount of incident light. It is possible to arrange in-layer lenses **160**, the number of which is in

accordance with processing accuracy of the in-layer lenses **160** in the manufacturing process of the imaging element **1**.

(69) In addition, C in FIG. **9** illustrates an example of a case of arranging nine in-layer lenses **160** each having a relatively small diameter in proximity to the central portion of the pixel **100**. Even in this case, it is possible to make the gap **169** small.

(70) Since a configuration of the imaging element **1** other than the above is similar to the configuration of the imaging element **1** described in the first embodiment of the present disclosure, a description thereof is omitted.

(71) As described above, in the imaging element **1** according to the second embodiment of the present disclosure, a freely-selected number of two or more in-layer lenses **160** can be arranged in accordance with processing accuracy.

3. Third Embodiment

(72) In the imaging element **1** according to the first embodiment, the in-layer lens **160** having a circular shape in a plan view is arranged. In contrast, an imaging element **1** according to a third embodiment of the present disclosure is different from the first embodiment in that in-layer lenses in different shapes are arranged.

(73) [Configuration of Pixel **1**]

(74) FIG. **10** is a plan view illustrating a first configuration example of a pixel according to a third embodiment of the present disclosure. FIG. **10** is a diagram illustrating a configuration example of a pixel **100** similarly to FIG. **3**. This pixel **100** is different from the pixel **100** described with reference to FIG. **3** in that an in-layer lens having a shape other than a circular shape is arranged. A in FIG. **10** illustrates an example of arranging an in-layer lens **161** having an elliptical shape in a plan view, besides the in-layer lens **160**. In addition, B in FIG. **10** illustrates another arrangement example of the in-layer lenses **160** and **161**. In this manner, it is possible to arrange the in-layer lenses **160** and **161** having mutually different shapes in the pixel **100**.

(75) [Configuration of Pixel **2**]

(76) FIG. **11** is a plan view illustrating a second configuration example of the pixel according to the third embodiment of the present disclosure. FIG. **11** illustrates an example of arranging the in-layer lenses **161**, or the in-layer lenses **160** and **161**, while optimizing their sizes to make the gap **169** small. A in FIG. **11** illustrates an example of arranging two in-layer lenses **161**. In addition, B and C in FIG. **11** each illustrate an example of arranging the in-layer lenses **160** and **161**. Any of the arrangements in FIG. **11** can make the gap **169** smaller than the gap **169** by the arrangements of the in-layer lenses **160** and **161** in FIG. **10**.

(77) [Configuration of Pixel **3**]

(78) FIG. **12** is a plan view illustrating a third configuration example of the pixel according to the third embodiment of the present disclosure. FIG. **12** illustrates an example of arranging an in-layer lens **162** having a rectangular shape in a plan view. In addition, B in FIG. **12** illustrates an example of a case of arranging in-layer lenses **162** respectively having a square shape and an oblong shape in a plan view in combination. In this manner, arranging the in-layer lens **162** having the rectangular shape can make the gap **169** smaller than the gap **169** in the case of arranging the in-layer lens **160** having the circular shape.

(79) [Configuration of Pixel **4**]

(80) FIG. **13** is a plan view illustrating a fourth configuration example of the pixel according to the third embodiment of the present disclosure. A in FIG. **13** illustrates an example of arranging an in-layer lens **163** and the in-layer lens **160**, and B in FIG. **13** illustrates a diagram illustrating a shape of a section of the in-layer lenses. The in-layer lens **163** is an in-layer lens that has an opening portion in its central portion in a plan view and that has a shape obtained by halving a torus in a thickness direction. The in-layer lens **160** illustrated in FIG. **13** is arranged in the opening portion of the in-layer lens **163**. In this manner, arranging the in-layer lenses **160** and **163** in combination can make the gap **169** smaller.

(81) Since a configuration of the imaging element **1** other than the above is similar to the configuration of the imaging element **1** described in the first embodiment of the present disclosure, a description thereof is omitted.

(82) As described above, in the imaging element **1** according to the third embodiment of the present disclosure, arranging the in-layer lenses **160** to **163** having different shapes can make the gap **169** smaller, and thus can scatter a larger amount of incident light.

4. Fourth Embodiment

(83) In the imaging element **1** according to the first embodiment described above, the in-layer lenses **160** arranged symmetrically about the center of the pixel **100** are used. In contrast, an imaging element **1** according to a fourth embodiment of the present disclosure is different from the first embodiment described above in that in-layer lenses arranged asymmetrically about the center of the pixel **100** are used.

(84) [Configuration of Pixel]

(85) FIG. **14** is a plan view illustrating a configuration example of a pixel according to a fourth embodiment of the present disclosure. FIG. **14** is a diagram illustrating a configuration example of a pixel **100** similarly to FIG. **3**. The pixel illustrated in FIG. **14** is different from the pixel **100** described with reference to FIG. **3** in that the in-layer lenses are arranged asymmetrically about the center of the pixel. Pixels (pixels **201** and **202**) in FIG. **14** are illustrated as an example of arranging four in-layer lenses **161** having different shapes. Specifically, as the pixels illustrated in FIG. **14**, two in-layer lenses **161a** each having a relatively large size, and two in-layer lenses **161b** each having a relatively small size are arranged. As a result, the in-layer lenses **161** are arranged asymmetrically about the center of the pixel **100**, and incident light can be scattered asymmetrically. The pixel **201** illustrated in A in FIG. **14** and the pixel **202** illustrated in B in FIG. **14** are configured by changing the arrangement of the in-layer lenses **161a** and **161b** by 180 degrees from each other. The pixels **201** and **202** are arranged in an end portion of the pixel array unit **10** described with reference to FIG. **1**. Specifically, the pixel **201** illustrated in A in FIG. **14** is arranged at a right end of the pixel array unit **10**, and the pixel **202** illustrated in B in FIG. **14** is arranged at a left end of the pixel array unit **10**. Incident light is emitted obliquely to the pixels at an end portion of the pixel array unit **10** in accordance with an image height of the subject. Thus, arranging the in-layer lenses **161** asymmetrically can reduce an influence by the image height.

(86) [Light Path of Incident Light]

(87) FIG. **15** is a diagram illustrating an example of a light path of incident light in the pixel according to the fourth embodiment of the present disclosure. FIG. **15** is a diagram illustrating the light path of incident light in the pixel **201**. As described above, the pixel **201** is arranged at the right end of the pixel array unit **10**. For this reason, incident light is incident on the pixel **201** obliquely from the upper left of the drawing. Thus, the plurality of in-layer lenses **161** is arranged by being shifted to the right side of the drawing in the pixel **201** and the in-layer lens **161** on the left side is horizontally long. This arrangement can collect obliquely incident light on a central portion of the pixel **201** and also scatter the obliquely incident light.

(88) Since a configuration of the imaging element **1** other than the above is similar to the configuration of the imaging element **1** described in the first embodiment of the present disclosure, a description thereof is omitted.

(89) As described above, the imaging element **1** according to the fourth embodiment of the present disclosure includes the in-layer lenses arranged asymmetrically about the center of the pixel, thereby enabling obliquely incident light to be collected on the central portion and also scattered in the pixel.

5. Fifth Embodiment

(90) In the imaging element **1** according to the first embodiment, the in-layer lens **160** is arranged in all the pixels **100** in the pixel array unit **10**. In contrast, an imaging element **1** according to a fifth embodiment of the present disclosure is different from the first embodiment in that the in-layer lens

160 is arranged in the pixel **100** in which the color filter **172** corresponding to incident light having a long wavelength is arranged.

(91) [Configuration of Pixel]

(92) FIG. **16** is a plan view illustrating a configuration example of a pixel according to a fifth embodiment of the present disclosure. The pixel **100** illustrated in FIG. **16** is different from the pixel **100** described with reference to FIG. **3** in that the in-layer lens **160** is arranged in the pixel **100** in which the color filter **172** corresponding to red light is arranged. Since red light has a long wavelength as described above, it reaches a deep portion of the semiconductor substrate **110**. Accordingly, an amount of light reflected by the wiring layer **132** increases. In contrast, green light or blue light having a short wavelength is collected on a region at a relatively shallow position of the semiconductor substrate **110**. For this reason, an amount of light reflected by the wiring layer **132** becomes relatively small. Thus, the in-layer lens **160** is arranged in the pixel **100** in which the color filter **172** corresponding to red light is arranged, and the in-layer lens **160** is not arranged in the pixel **100** in which the color filter **172** corresponding to green light or blue light is arranged. This can simplify the configuration of the imaging element **1**.

(93) [Another Configuration of Pixel]

(94) FIG. **17** is a plan view illustrating another configuration example of the pixel according to the fifth embodiment of the present disclosure. FIG. **17** is different from the pixel **100** described with reference to FIG. **3** in that the pixel **100** in which a color filter **172** corresponding to infrared light is arranged is further included. The color filter **172** corresponding to infrared light is a color filter **172** that allows infrared light to pass therethrough. In FIG. **17**, the pixel **100** denoted by “IR” indicates the color filter **172** corresponding to infrared light. The pixel **100** in which the color filter **172** corresponding to infrared light is arranged can be allocated to one of pixels **100** in which two color filters **172** corresponding to green light in the Bayer array are arranged. Arranging the in-layer lens **160** also in the pixel **100** in which the color filter **172** corresponding to infrared light having the long wavelength is arranged can scatter incident light.

(95) Since a configuration of the imaging element **1** other than the above is similar to the configuration of the imaging element **1** described in the first embodiment of the present disclosure, a description thereof is omitted.

(96) As described above, in the imaging element **1** according to the fifth embodiment of the present disclosure, arranging the in-layer lens **160** in the pixel in accordance with a wavelength of incident light can simplify the configuration of the imaging element **1**.

6. Sixth Embodiment

(97) In the imaging element **1** according to the first embodiment, only the pixel **100** is arranged in the pixel array unit **10**. In contrast, an imaging element **1** according to a sixth embodiment of the present disclosure is different from the first embodiment in that a phase difference pixel to detect an image plane phase difference of the subject is further arranged.

(98) [Configuration of Pixel Array Unit]

(99) FIG. **18** is a plan view illustrating a configuration example of a pixel array unit according to a sixth embodiment of the present disclosure. A pixel array unit **10** illustrated in FIG. **18** is different from the pixel array unit **10** described with reference to FIG. **3** in that a phase difference pixel **300**, besides the pixel **100**, is arranged. The phase difference pixel **300** mentioned herein is a pixel to detect the image plane phase difference of the subject. The imaging element **1** is used together with an image taking lens arranged outside, and an image of the subject is formed by the image taking lens on the pixel array unit **10** of the imaging element **1**. Detecting a phase difference of the subject whose image is formed enables detection of a focal position of the subject, thereby enabling autofocus to adjust a position of the image taking lens.

(100) FIG. **18** illustrates an arrangement of the light-shielding film **150**. As illustrated in FIG. **18**, the light-shielding film **150** having an opening portion **152**, instead of the opening portion **151**, is arranged in the phase difference pixel **300**. With this arrangement, the light-shielding film **150** is

arranged to cover a left half or right half of the photoelectric conversion unit **101** in the phase difference pixel **300**. In FIG. **18**, the light-shielding film **150** shields the left half and right half of the photoelectric conversion unit **101** from light in the phase difference pixels **300a** and **300b**, respectively. With this arrangement, incident light, which has passed through the left side and right side of the image taking lens in the phase difference pixels **300a** and **300b**, respectively, reaches the photoelectric conversion unit **101**, and respective image signals are generated. Such processing is called pupil division. A plurality of phase difference pixels **300a** and a plurality of **300b** are arranged in the pixel array unit **10**. Two images are generated on the basis of respective image signals generated by the plurality of phase difference pixels **300a** and the plurality of phase difference pixels **300b**. Subsequently, detecting a phase difference between the two images enables detection of the focal position of the image taking lens.

(101) In these phase difference pixels **300**, omitting the in-layer lens **160** can increase accuracy in pupil division. This is because incident light subjected to pupil division is not scattered by the in-layer lens **160**. This can reduce an error in detection of a phase difference.

(102) Since a configuration of the imaging element **1** other than the above is similar to the configuration of the imaging element **1** described in the first embodiment of the present disclosure, a description thereof is omitted.

(103) As described above, in the case of detecting the image plane phase difference, the imaging element **1** according to the sixth embodiment of the present disclosure scatters incident light in the pixel **100**, and also can reduce an error in detection of a phase difference by the phase difference pixel **300**.

7. Examples of Practical Use for Camera

(104) The technology according to the present disclosure (the present technology) can be applied to various products. For example, the present technology may be implemented as an imaging element mounted on an imaging apparatus such as a camera.

(105) FIG. **19** is a block diagram illustrating a schematic configuration example of a camera as an example of an imaging apparatus to which the present technology can be applied. A camera **1000** illustrated in FIG. **19** includes a lens **1001**, an imaging element **1002**, an imaging control unit **1003**, a lens drive unit **1004**, an image processing unit **1005**, an operation input unit **1006**, a frame memory **1007**, a display unit **1008**, and a recording unit **1009**.

(106) The lens **1001** is an image taking lens of the camera **1000**. This lens **1001** collects light from the subject and allows the light to be incident on the imaging element **1002**, which will be described later, to form an image of the subject.

(107) The imaging element **1002** is a semiconductor element that images light reflected from the subject and collected by the lens **1001**. This imaging element **1002** generates an analog image signal in accordance with irradiated light, converts the analog image signal to a digital image signal, and outputs the digital image signal.

(108) The imaging control unit **1003** controls imaging in the imaging element **1002**. This imaging control unit **1003** controls the imaging element **1002** by generating a control signal and outputting the control signal to the imaging element **1002**. In addition, the imaging control unit **1003** can perform autofocus in the camera **1000** on the basis of the image signal output from the imaging element **1002**. The autofocus mentioned herein is a system to detect and automatically adjust a focal position of the lens **1001**. As this autofocus, it is possible to use a method of detecting the focal position by causing a phase difference pixel arranged in the imaging element **1002** to detect an image plane phase difference (image plane phase difference autofocus). In addition, it is also possible to apply a method of detecting a position that allows an image to have the highest contrast (contrast autofocus) as the focal position. The imaging control unit **1003** adjusts the position of the lens **1001** via the lens drive unit **1004** on the basis of the detected focal position, and performs the autofocus. Note that the imaging control unit **1003** can be configured by, for example, a digital signal processor (DSP) that comes with firmware.

(109) The lens drive unit **1004** drives the lens **1001** on the basis of control by the imaging control unit **1003**. This lens drive unit **1004** can drive the lens **1001** by changing the position of the lens **1001** using a built-in motor.

(110) The image processing unit **1005** performs processing on an image signal generated by the imaging element **1002**. This processing corresponds to, for example, demosaicing to generate an image signal of a lacking color among image signals corresponding to red, green, and blue on a pixel-by-pixel basis, noise reduction to remove noise in the image signal, and encoding of the image signal. The image processing unit **1005** can be configured by, for example, a microcomputer that comes with firmware.

(111) The operation input unit **1006** accepts input of an operation from a user of the camera **1000**. For example, a push button or a touch panel can be used for this operation input unit **1006**. The input of the operation accepted by the operation input unit **1006** is transmitted to the imaging control unit **1003** and the image processing unit **1005**. Thereafter, processing in accordance with the input of the operation, for example, processing such as imaging of the subject is activated.

(112) The frame memory **1007** is a memory that stores a frame, which is an image signal for one screen. This frame memory **1007** is controlled by the image processing unit **1005**, and holds the frame in the course of the image processing.

(113) The display unit **1008** displays an image processed by the image processing unit **1005**. For example, a liquid crystal panel can be used for this display unit **1008**.

(114) The recording unit **1009** records an image processed by the image processing unit **1005**. For example, a memory card or a hard disk can be used for this recording unit **1009**.

(115) The description has been given of the camera to which the present disclosure can be applied. The present technology can be applied to the imaging element **1002** among the configurations described above. Specifically, the imaging element **1** described with reference to FIG. **1** can be applied to the imaging element **1002**. Applying the imaging element **1** to the imaging element **1002** reduces occurrence of color mixture, and thus can prevent degradation of image quality of an image generated by the camera **1000**. Note that the image processing unit **1005** is one example of a processing circuit described in the claims. The camera **1000** is one example of an imaging apparatus described in the claims.

(116) Note that the description has been given of the camera as one example, but the technology according to the present disclosure may be applied to another apparatus, for example, a monitoring apparatus.

8. Examples of Practical Use for Endoscopic Surgery System

(117) The technology (present technology) according to an embodiment of the present disclosure is applicable to a variety of products. For example, the technology according to the present disclosure may be applied to an endoscopic surgery system.

(118) FIG. **20** is a view depicting an example of a schematic configuration of an endoscopic surgery system to which the technology according to the present disclosure (present technology) can be applied.

(119) In FIG. **20**, a state is illustrated in which a surgeon (medical doctor) **11131** is using an endoscopic surgery system **11000** to perform surgery for a patient **11132** on a patient bed **11133**. As depicted, the endoscopic surgery system **11000** includes an endoscope **11100**, other surgical tools **11110** such as a pneumoperitoneum tube **11111** and an energy device **11112**, a supporting arm apparatus **11120** which supports the endoscope **11100** thereon, and a cart **11200** on which various apparatus for endoscopic surgery are mounted.

(120) The endoscope **11100** includes a lens barrel **11101** having a region of a predetermined length from a distal end thereof to be inserted into a body cavity of the patient **11132**, and a camera head **11102** connected to a proximal end of the lens barrel **11101**. In the example depicted, the endoscope **11100** is depicted which is included as a rigid endoscope having the lens barrel **11101** of the hard type. However, the endoscope **11100** may otherwise be included as a flexible endoscope having the

lens barrel of the flexible type.

(121) The lens barrel **11101** has, at a distal end thereof, an opening in which an objective lens is fitted. A light source apparatus **11203** is connected to the endoscope **11100** such that light generated by the light source apparatus **11203** is introduced to a distal end of the lens barrel **11101** and is irradiated toward an observation target in a body cavity of the patient **11132** through the objective lens. It is to be noted that the endoscope **11100** may be a forward-viewing endoscope or may be an oblique-viewing endoscope or a side-viewing endoscope.

(122) An optical system and an imaging element are provided in the inside of the camera head **11102** such that reflected light (observation light) from the observation target is condensed on the imaging element by the optical system. The observation light is photo-electrically converted by the imaging element to generate an electric signal corresponding to the observation light, namely, an image signal corresponding to an observation image. The image signal is transmitted as RAW data to a camera control unit (CCU) **11201**.

(123) The CCU **11201** includes a central processing unit (CPU), a graphics processing unit (GPU) or the like and integrally controls operation of the endoscope **11100** and a display apparatus **11202**. Further, the CCU **11201** receives an image signal from the camera head **11102** and performs, for the image signal, various image processes for displaying an image based on the image signal such as, for example, a development process (demosaic process).

(124) The display apparatus **11202** displays thereon an image based on an image signal, for which the image processes have been performed by the CCU **11201**, under the control of the CCU **11201**.

(125) The light source apparatus **11203** includes a light source such as, for example, a light emitting diode (LED) and supplies irradiation light upon imaging of a surgical region and the like to the endoscope **11100**.

(126) An input apparatus **11204** is an input interface for the endoscopic surgery system **11000**. A user can perform input of various kinds of information or instruction inputting to the endoscopic surgery system **11000** through the input apparatus **11204**. For example, the user would input an instruction or the like to change an image pickup condition (type of irradiation light, magnification, focal distance or the like) by the endoscope **11100**.

(127) A treatment tool controlling apparatus **11205** controls driving of the energy device **11112** for cautery or incision of a tissue, sealing of a blood vessel or the like. A pneumoperitoneum apparatus **11206** feeds gas into a body cavity of the patient **11132** through the pneumoperitoneum tube **11111** to inflate the body cavity in order to secure the field of view of the endoscope **11100** and secure the working space for the surgeon. A recorder **11207** is an apparatus capable of recording various kinds of information relating to surgery. A printer **11208** is an apparatus capable of printing various kinds of information relating to surgery in various forms such as a text, an image or a graph.

(128) It is to be noted that the light source apparatus **11203** which supplies irradiation light when a surgical region is to be imaged to the endoscope **11100** may include a white light source which includes, for example, an LED, a laser light source or a combination of them. In a case where a white light source includes a combination of red, green, and blue (RGB) laser light sources, since the output intensity and the output timing can be controlled with a high degree of accuracy for each color (each wavelength), adjustment of the white balance of a picked up image can be performed by the light source apparatus **11203**. Further, in this case, if laser beams from the respective RGB laser light sources are irradiated time-divisionally on an observation target and driving of the imaging elements of the camera head **11102** are controlled in synchronism with the irradiation timings, it is also possible to time-divisionally capture images corresponding to respective R, G and B. According to the method just described, a color image can be obtained even if a color filter is not provided for the imaging element.

(129) Further, the light source apparatus **11203** may be controlled such that the intensity of light to be outputted is changed for each predetermined time. By controlling driving of the imaging

element of the camera head **11102** in synchronism with the timing of the change of the intensity of light to acquire images time-divisionally and synthesizing the images, an image of a high dynamic range free from underexposed blocked up shadows and overexposed highlights can be created.

(130) Further, the light source apparatus **11203** may be configured to supply light of a predetermined wavelength band ready for special light observation. In special light observation, for example, by utilizing the wavelength dependency of absorption of light of a body tissue, narrow band light observation (narrow band imaging) of imaging a certain tissue such as a blood vessel of a superficial portion of the mucous membrane or the like in a high contrast is performed by applying light of a narrower wavelength band in comparison with irradiation light upon ordinary observation (namely, white light). Alternatively, in special light observation, fluorescent observation for obtaining an image from fluorescent light generated by irradiation of excitation light may also be performed. In fluorescent observation, it is possible to perform observation of fluorescent light from a body tissue by irradiating excitation light on the body tissue (autofluorescence observation) or to obtain a fluorescent light image by locally injecting a reagent such as indocyanine green (ICG) into a body tissue and irradiating excitation light corresponding to a fluorescent light wavelength of the reagent upon the body tissue, for example. The light source apparatus **11203** can be configured to supply such narrow-band light and/or excitation light suitable for special light observation as described above.

(131) FIG. **21** is a block diagram depicting an example of a functional configuration of the camera head **11102** and the CCU **11201** depicted in FIG. **20**.

(132) The camera head **11102** includes a lens unit **11401**, an imaging unit **11402**, a driving unit **11403**, a communication unit **11404** and a camera head controlling unit **11405**. The CCU **11201** includes a communication unit **11411**, an image processing unit **11412** and a control unit **11413**. The camera head **11102** and the CCU **11201** are connected for communication to each other by a transmission cable **11400**.

(133) The lens unit **11401** is an optical system, provided at a connecting location to the lens barrel **11101**. Observation light taken in from a distal end of the lens barrel **11101** is guided to the camera head **11102** and introduced into the lens unit **11401**. The lens unit **11401** includes a combination of a plurality of lenses including a zoom lens and a focusing lens.

(134) The imaging unit **11402** includes imaging elements. The number of imaging elements which is included by the imaging unit **11402** may be one (so-called single-plate type) or a plural number (so-called multi-plate type). In a case where the imaging unit **11402** is configured as that of the multi-plate type, for example, image signals corresponding to respective R, G, and B are generated by the imaging elements, and the image signals may be synthesized to obtain a color image. The imaging unit **11402** may also be configured so as to have a pair of imaging elements for acquiring respective image signals for the right eye and the left eye ready for three dimensional (3D) display. If 3D display is performed, then the depth of a living body tissue in a surgical region can be comprehended more accurately by the surgeon **11131**. It is to be noted that, in a case where the imaging unit **11402** is configured as that of multi-plate type, a plurality of systems of lens units **11401** is provided corresponding to the individual imaging elements.

(135) Further, the imaging unit **11402** may not necessarily be provided on the camera head **11102**. For example, the imaging unit **11402** may be provided immediately behind the objective lens in the inside of the lens barrel **11101**.

(136) The driving unit **11403** includes an actuator and moves the zoom lens and the focusing lens of the lens unit **11401** by a predetermined distance along an optical axis under the control of the camera head controlling unit **11405**. Consequently, the magnification and the focal point of a picked up image by the imaging unit **11402** can be adjusted suitably.

(137) The communication unit **11404** includes a communication apparatus for transmitting and receiving various kinds of information to and from the CCU **11201**. The communication unit **11404** transmits an image signal acquired from the imaging unit **11402** as RAW data to the CCU **11201**

through the transmission cable **11400**.

(138) In addition, the communication unit **11404** receives a control signal for controlling driving of the camera head **11102** from the CCU **11201** and supplies the control signal to the camera head controlling unit **11405**. The control signal includes information regarding imaging conditions such as, for example, information that a frame rate of a picked up image is designated, information that an exposure value upon image picking up is designated and/or information that a magnification and a focal point of a picked up image are designated.

(139) It is to be noted that the image pickup conditions such as the frame rate, exposure value, magnification or focal point may be appropriately designated by the user or may be set automatically by the control unit **11413** of the CCU **11201** on the basis of an acquired image signal. In the latter case, an auto exposure (AE) function, an auto focus (AF) function and an auto white balance (AWB) function are incorporated in the endoscope **11100**.

(140) The camera head controlling unit **11405** controls driving of the camera head **11102** on the basis of a control signal from the CCU **11201** received through the communication unit **11404**.

(141) The communication unit **11411** includes a communication apparatus for transmitting and receiving various kinds of information to and from the camera head **11102**. The communication unit **11411** receives an image signal transmitted thereto from the camera head **11102** through the transmission cable **11400**.

(142) Further, the communication unit **11411** transmits a control signal for controlling driving of the camera head **11102** to the camera head **11102**. The image signal and the control signal can be transmitted by electrical communication, optical communication or the like.

(143) The image processing unit **11412** performs various image processes for an image signal in the form of RAW data transmitted thereto from the camera head **11102**.

(144) The control unit **11413** performs various kinds of control relating to image picking up of a surgical region or the like by the endoscope **11100** and display of a picked up image obtained by image picking up of the surgical region or the like. For example, the control unit **11413** creates a control signal for controlling driving of the camera head **11102**.

(145) Further, the control unit **11413** controls, on the basis of an image signal for which image processes have been performed by the image processing unit **11412**, the display apparatus **11202** to display a picked up image in which the surgical region or the like is imaged. Thereupon, the control unit **11413** may recognize various objects in the picked up image using various image recognition technologies. For example, the control unit **11413** can recognize a surgical tool such as forceps, a particular living body region, bleeding, mist when the energy device **11112** is used and so forth by detecting the shape, color and so forth of edges of objects included in a picked up image. The control unit **11413** may cause, when it controls the display apparatus **11202** to display a picked up image, various kinds of surgery supporting information to be displayed in an overlapping manner with an image of the surgical region using a result of the recognition. Where surgery supporting information is displayed in an overlapping manner and presented to the surgeon **11131**, the burden on the surgeon **11131** can be reduced and the surgeon **11131** can proceed with the surgery with certainty.

(146) The transmission cable **11400** which connects the camera head **11102** and the CCU **11201** to each other is an electric signal cable ready for communication of an electric signal, an optical fiber ready for optical communication or a composite cable ready for both of electrical and optical communications.

(147) Here, while, in the example depicted, communication is performed by wired communication using the transmission cable **11400**, the communication between the camera head **11102** and the CCU **11201** may be performed by wireless communication.

(148) The description above is given of an example of the endoscopic surgery system to which the technology according to the present disclosure is applicable. The technology according to the present disclosure can be applied to the imaging unit **11402** among the configurations described

above. Specifically, the imaging element **1** illustrated in FIG. **1** can be applied to the imaging unit **10402**. Applying the present technology according to the present disclosure to the imaging unit **10402** enables acquisition of an image of the operated part with high image quality, thereby enabling the operator to unfailingly check the operated part.

(149) Note that the description has been given of the endoscopic surgery system as an example, but the technology according to the present disclosure may be applied to another system, for example, a micrographic surgery system.

9. Examples of Practical Use for Mobile Objects

(150) The technology (present technology) according to an embodiment of the present disclosure is applicable to a variety of products. For example, the technology according to an embodiment of the present disclosure is implemented as devices mounted on any type of mobile objects such as automobiles, electric vehicles, hybrid electric vehicles, motorcycles, bicycles, personal mobilities, airplanes, drones, ships, and robots.

(151) FIG. **22** is a block diagram depicting an example of schematic configuration of a vehicle control system as an example of a mobile object control system to which the technology according to the present disclosure can be applied.

(152) The vehicle control system **12000** includes a plurality of electronic control units connected to each other via a communication network **12001**. In the example depicted in FIG. **22**, the vehicle control system **12000** includes a driving system control unit **12010**, a body system control unit **12020**, an outside-vehicle information detecting unit **12030**, an in-vehicle information detecting unit **12040**, and an integrated control unit **12050**. In addition, as functional configurations of the integrated control unit **12050**, a microcomputer **12051**, a sound/image output section **12052**, a vehicle-mounted network interface (I/F) **12053** are shown.

(153) The driving system control unit **12010** controls the operation of devices related to the driving system of the vehicle in accordance with various kinds of programs. For example, the driving system control unit **12010** functions as a control device for a driving force generating device for generating the driving force of the vehicle, such as an internal combustion engine, a driving motor, or the like, a driving force transmitting mechanism for transmitting the driving force to wheels, a steering mechanism for adjusting the steering angle of the vehicle, a braking device for generating the braking force of the vehicle, and the like.

(154) The body system control unit **12020** controls the operation of various kinds of devices provided to a vehicle body in accordance with various kinds of programs. For example, the body system control unit **12020** functions as a control device for a keyless entry system, a smart key system, a power window device, or various kinds of lamps such as a headlamp, a backup lamp, a brake lamp, a turn signal, a fog lamp, or the like. In this case, radio waves transmitted from a mobile device as an alternative to a key or signals of various kinds of switches can be input to the body system control unit **12020**. The body system control unit **12020** receives these input radio waves or signals, and controls a door lock device, the power window device, the lamps, or the like of the vehicle.

(155) The outside-vehicle information detecting unit **12030** detects information about the outside of the vehicle including the vehicle control system **12000**. For example, the outside-vehicle information detecting unit **12030** is connected with an imaging unit **12031**. The outside-vehicle information detecting unit **12030** makes the imaging unit **12031** image an image of the outside of the vehicle, and receives the imaged image. On the basis of the received image, the outside-vehicle information detecting unit **12030** may perform processing of detecting an object such as a human, a vehicle, an obstacle, a sign, a character on a road surface, or the like, or processing of detecting a distance thereto.

(156) The imaging unit **12031** is an optical sensor that receives light, and which outputs an electrical signal corresponding to a received light amount of the light. The imaging unit **12031** can output the electrical signal as an image, or can output the electrical signal as information about a

measured distance. In addition, the light received by the imaging unit **12031** may be visible light, or may be invisible light such as infrared rays or the like.

(157) The in-vehicle information detecting unit **12040** detects information about the inside of the vehicle. The in-vehicle information detecting unit **12040** is, for example, connected with a driver state detecting section **12041** that detects the state of a driver. The driver state detecting section **12041**, for example, includes a camera that images the driver. On the basis of detection information input from the driver state detecting section **12041**, the in-vehicle information detecting unit **12040** may calculate a degree of fatigue of the driver or a degree of concentration of the driver, or may determine whether or not the driver is dozing.

(158) The microcomputer **12051** can calculate a control target value for the driving force generating device, the steering mechanism, or the braking device on the basis of the information about the inside or outside of the vehicle which information is obtained by the outside-vehicle information detecting unit **12030** or the in-vehicle information detecting unit **12040**, and output a control command to the driving system control unit **12010**. For example, the microcomputer **12051** can perform cooperative control intended to implement functions of an advanced driver assistance system (ADAS) which functions include collision avoidance or shock mitigation for the vehicle, following driving based on a following distance, vehicle speed maintaining driving, a warning of collision of the vehicle, a warning of deviation of the vehicle from a lane, or the like.

(159) In addition, the microcomputer **12051** can perform cooperative control intended for automatic driving, which makes the vehicle to travel autonomously without depending on the operation of the driver, or the like, by controlling the driving force generating device, the steering mechanism, the braking device, or the like on the basis of the information about the outside or inside of the vehicle which information is obtained by the outside-vehicle information detecting unit **12030** or the in-vehicle information detecting unit **12040**.

(160) In addition, the microcomputer **12051** can output a control command to the body system control unit **12020** on the basis of the information about the outside of the vehicle which information is obtained by the outside-vehicle information detecting unit **12030**. For example, the microcomputer **12051** can perform cooperative control intended to prevent a glare by controlling the headlamp so as to change from a high beam to a low beam, for example, in accordance with the position of a preceding vehicle or an oncoming vehicle detected by the outside-vehicle information detecting unit **12030**.

(161) The sound/image output section **12052** transmits an output signal of at least one of a sound and an image to an output device capable of visually or auditorily notifying an occupant of the vehicle or the outside of the vehicle of information. In the example of FIG. 22, an audio speaker **12061**, a display unit **12062**, and an instrument panel **12063** are illustrated as the output device. The display unit **12062** may, for example, include at least one of an on-board display and a head-up display.

(162) FIG. 23 is a diagram depicting an example of the installation position of the imaging unit **12031**.

(163) In FIG. 23, the vehicle **12100** includes imaging units **12101**, **12102**, **12103**, **12104**, and **12105** as the imaging unit **12031**.

(164) imaging units **12101**, **12102**, **12103**, **12104**, and **12105** are positioned, for example, at the front nose, a side mirror, the rear bumper, the back door, and the upper part, or the like, of the windshield in the vehicle compartment of the vehicle **12100**. The imaging unit **12101** provided to the front nose and the imaging unit **12105** provided to the upper portion of the windshield within the interior of the vehicle obtain mainly an image of the front of the vehicle **12100**. The imaging units **12102** and **12103** attached to the side mirrors chiefly acquire images of the areas on the sides of the vehicle **12100**. The imaging unit **12104** provided to the rear bumper or the back door obtains mainly an image of the rear of the vehicle **12100**. The image of the front of the vehicle obtained by the imaging units **12101** and **12105** is used mainly to detect a preceding vehicle, a pedestrian, an

obstacle, a signal, a traffic sign, a lane, or the like.

(165) Incidentally, FIG. 23 depicts an example of imaging ranges of the imaging units **12101** to **12104**. An imaging range **12111** represents the imaging range of the imaging unit **12101** provided to the front nose. Imaging ranges **12112** and **12113** respectively represent the imaging ranges of the imaging units **12102** and **12103** provided to the side view mirrors. An imaging range **12114** represents the imaging range of the imaging unit **12104** provided to the rear bumper or the back door. A bird's-eye image of the vehicle **12100** as viewed from above is obtained by superimposing image data imaged by the imaging units **12101** to **12104**, for example.

(166) At least one of the imaging units **12101** to **12104** may have a function of obtaining distance information. For example, at least one of the imaging units **12101** to **12104** may be a stereo camera constituted of a plurality of imaging elements, or may be an imaging element having pixels for phase difference detection.

(167) For example, the microcomputer **12051** can determine a distance to each three-dimensional object within the imaging ranges **12111** to **12114** and a temporal change in the distance (relative speed with respect to the vehicle **12100**) on the basis of the distance information obtained from the imaging units **12101** to **12104**, and thereby extract, as a preceding vehicle, a nearest three-dimensional object in particular that is present on a traveling path of the vehicle **12100** and which travels in substantially the same direction as the vehicle **12100** at a predetermined speed (for example, equal to or more than 0 km/h). Further, the microcomputer **12051** can set a following distance to be maintained in front of a preceding vehicle in advance, and perform automatic brake control (including following stop control), automatic acceleration control (including following start control), or the like. It is thus possible to perform cooperative control intended for automatic driving that makes the vehicle travel autonomously without depending on the operation of the driver or the like.

(168) For example, the microcomputer **12051** can classify three-dimensional object data on three-dimensional objects into three-dimensional object data of a two-wheeled vehicle, a standard-sized vehicle, a large-sized vehicle, a pedestrian, and other three-dimensional objects such as a utility pole on the basis of the distance information obtained from the imaging units **12101** to **12104**, extract the classified three-dimensional object data, and use the extracted three-dimensional object data for automatic avoidance of an obstacle. For example, the microcomputer **12051** identifies obstacles around the vehicle **12100** as obstacles that the driver of the vehicle **12100** can recognize visually and obstacles that are difficult for the driver of the vehicle **12100** to recognize visually. Then, the microcomputer **12051** determines a collision risk indicating a risk of collision with each obstacle. In a situation in which the collision risk is equal to or higher than a set value and there is thus a possibility of collision, the microcomputer **12051** outputs a warning to the driver via the audio speaker **12061** or the display unit **12062**, and performs forced deceleration or avoidance steering via the driving system control unit **12010**. The microcomputer **12051** can thereby assist in driving to avoid collision.

(169) At least one of the imaging units **12101** to **12104** may be an infrared camera that detects infrared rays. The microcomputer **12051** can, for example, recognize a pedestrian by determining whether or not there is a pedestrian in imaged images of the imaging units **12101** to **12104**. Such recognition of a pedestrian is, for example, performed by a procedure of extracting characteristic points in the imaged images of the imaging units **12101** to **12104** as infrared cameras and a procedure of determining whether or not it is the pedestrian by performing pattern matching processing on a series of characteristic points representing the contour of the object. When the microcomputer **12051** determines that there is a pedestrian in the imaged images of the imaging units **12101** to **12104**, and thus recognizes the pedestrian, the sound/image output section **12052** controls the display unit **12062** so that a square contour line for emphasis is displayed so as to be superimposed on the recognized pedestrian. Further, the sound/image output section **12052** may also control the display unit **12062** so that an icon or the like representing the pedestrian is

displayed at a desired position.

(170) The description has been given of the example of the vehicle control system to which the technology according to the present disclosure can be applied. The technology according to the present disclosure can be applied to the imaging unit **12031** or the like among the configurations described above. Specifically, the imaging element **1** illustrated in FIG. **1** can be applied to the imaging unit **12031**. Applying the technology according to the present disclosure to the imaging unit **12031** enables acquisition of a taken image with high image quality, thereby enabling reduction of fatigue of the driver.

(171) Finally, the above description of each of the embodiments is one example of the present disclosure, and the present disclosure is not limited to the embodiments described above. Thus, it is a matter of course that even if an embodiment is other than the embodiments described above, various modifications can be made in accordance with design or the like without departing from the technical idea of the present disclosure.

(172) In addition, the drawings of the embodiments described above are schematic drawings, and a dimensional ratio of each unit or the like does not necessarily match with the actual one.

Furthermore, it is a matter of course that a part having a different dimensional relationship or a different dimensional ratio between the drawings is included.

(173) Additionally, the present technology may also be configured as below.

(174) (1) An imaging element including: an on-chip lens configured to collect incident light from a subject; a photoelectric conversion unit configured to perform photoelectric conversion on the collected incident light; and a plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens, in which the plurality of in-layer lenses is configured to allow the incident light that has passed through any one of the plurality of in-layer lenses to be incident on the photoelectric conversion unit.

(175) (2) The imaging element according to (1), in which the plurality of in-layer lenses is arranged in substantially an identical layer.

(176) (3) The imaging element according to (2), in which the plurality of in-layer lenses is simultaneously formed.

(177) (4) The imaging element according to any one of (1) to (3), further including a color filter configured to allow light having a predetermined wavelength, out of the incident light that has passed through the on-chip lens, to transmit through the color filter.

(178) (5) The imaging element according to (4), in which the color filter is configured to allow red light to transmit through the color filter.

(179) (6) The imaging element according to (4), in which the color filter is configured to cause infrared light to transmit through the color filter.

(180) (7) The imaging element according to any one of (1) to (6), in which one of the plurality of in-layer lenses is arranged on an optical axis of the on-chip lens.

(181) (8) The imaging element according to any one of (1) to (7), in which the plurality of in-layer lenses has mutually different shapes.

(182) (9) The imaging element according to any one of (1) to (8), further including a plurality of pixels each including the on-chip lens, the photoelectric conversion unit, and the plurality of in-layer lenses.

(183) (10) The imaging element according to (9), in which the plurality of in-layer lenses is arranged asymmetrically about a center of the pixel.

(184) (11) The imaging element according to (9), further including a phase difference pixel that includes the on-chip lens and the photoelectric conversion unit, and that is configured to detect a phase difference by performing pupil division on the incident light from the subject.

(185) (12) An imaging apparatus including: an on-chip lens configured to collect incident light from a subject; a photoelectric conversion unit configured to perform photoelectric conversion on

the collected incident light; a plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens; and a processing circuit configured to process an image signal on the basis of the photoelectric conversion in the photoelectric conversion unit, in which the plurality of in-layer lenses is configured to allow the incident light that has passed through any one of the plurality of in-layer lenses to be incident on the photoelectric conversion unit.

REFERENCE SIGNS LIST

(186) **1** Imaging element **10** Pixel array unit **30** Column signal processing unit **100**, **201**, **202** Pixel **101** Photoelectric conversion unit **111** n-type semiconductor region **132** Wiring layer **150** Light-shielding film **160**, **160a**, **160b**, **161**, **161a**, **161b**, **162**, **163** In-layer lens **172** Color filter **180** On-chip lens **300**, **300a**, **300b** Phase difference pixel **1000** Camera **1002** Imaging element **10402**, **12031**, **12101** to **12105** Imaging unit

Claims

1. An imaging element comprising: an on-chip lens configured to collect incident light from a subject, the on-chip lens having an edge in a plan view; a photoelectric conversion unit configured to perform photoelectric conversion on the collected incident light; a plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens, the plurality of in-layer lenses including an array of three in-layer lenses arranged in first and second directions; and a plurality of gaps arranged, in the plan view, between the in-layer lenses and within the edge of the on-chip lens, such that each of the plurality of gaps overlaps only a single photoelectric conversion unit, wherein a one-to-many relationship exists between the on-chip lens and the in-layer lenses in the plurality of in-layer lenses which correspond to the on-chip lens, the plurality of in-layer lenses and the plurality of gaps are configured to allow the incident light that has passed through either any one of the plurality of in-layer lenses or any one of the plurality of gaps to be incident on the photoelectric conversion unit, each in-layer lens in the plurality of in-layer lenses is in direct contact with at least two adjacent in-layer lenses, and a space exists, in the plan view, between an edge of the photoelectric conversion unit and the plurality of in layer lenses, and each of the plurality of gaps has an irregular shape.
2. The imaging element according to claim 1, wherein the plurality of in-layer lenses is arranged in substantially an identical layer.
3. The imaging element according to claim 2, wherein the plurality of in-layer lenses is simultaneously formed.
4. The imaging element according to claim 1, further comprising a color filter configured to allow light having a predetermined wavelength, out of the incident light that has passed through the on-chip lens, to transmit through the color filter.
5. The imaging element according to claim 4, wherein the color filter is configured to allow red light to transmit through the color filter.
6. The imaging element according to claim 4, wherein the color filter is configured to cause infrared light to transmit through the color filter.
7. The imaging element according to claim 1, wherein one of the plurality of in-layer lenses is arranged on an optical axis of the on-chip lens.
8. The imaging element according to claim 1, wherein the plurality of in-layer lenses has mutually different shapes.
9. The imaging element according to claim 1, further comprising a plurality of pixels each including the on-chip lens, the photoelectric conversion unit, and the plurality of in-layer lenses.
10. The imaging element according to claim 9, wherein the plurality of in-layer lenses is arranged asymmetrically about a center of the pixel.

11. The imaging element according to claim 9, further comprising a phase difference pixel that includes the on-chip lens and the photoelectric conversion unit, and that is configured to detect a phase difference by performing pupil division on the incident light from the subject.

12. An imaging apparatus comprising: an on-chip lens configured to collect incident light from a subject, the on-chip lens having an edge in a plan view; a photoelectric conversion unit configured to perform photoelectric conversion on the collected incident light; a plurality of in-layer lenses that is arranged between the on-chip lens and the photoelectric conversion unit and that is configured to further collect the incident light that has passed through the on-chip lens, the plurality of in-layer lenses including an array of three in-layer lenses arranged in first and second directions; a plurality of gaps arranged, in the plan view, between the in-layer lenses and within the edge of the on-chip lens, such that each of the plurality of gaps overlaps only a single photoelectric conversion unit; and a processing circuit configured to process an image signal on a basis of the photoelectric conversion in the photoelectric conversion unit, wherein a one-to-many relationship exists between the on-chip lens and the in-layer lenses in the plurality of in-layer lenses which correspond to the on-chip lens, the plurality of in-layer lenses and the plurality of gaps are configured to allow the incident light that has passed through either any one of the plurality of in-layer lenses or any one of the plurality of gaps to be incident on the photoelectric conversion unit, each in-layer lens in the plurality of in-layer lenses is in direct contact with at least two adjacent in-layer lenses, and a space exists, in the plan view, between an edge of the photoelectric conversion unit and the plurality of in layer lenses, and each of the plurality of gaps has an irregular shape.

13. The imaging element according to claim 1, wherein a ratio of a quantity of in-layer lenses to the on-chip lens is 9 to 1, and the in-layer lenses are located overlapping the on-chip lens and between the in-layer lenses are 4 gaps.

14. The imaging element according to claim 13, wherein the plurality of in-layer lenses is arranged symmetrically about a center of the on-chip lens.
