

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402505
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kim; Hyunyoung et al.

Organic light-emitting display apparatus

Abstract

An organic light-emitting display apparatus includes a thin-film transistor on a substrate, a planarization layer on the thin-film transistor, and a pixel-defining spacer on the planarization layer. The pixel-defining spacer defines a pixel area between two pixels that are adjacent in a first direction.

Inventors:	Kim; Hyunyoung (Yongin-si, KR), Kim; Dohoon (Yongin-si, KR)
Applicant:	SAMSUNG DISPLAY CO., LTD. (Yongin-si, KR)
Family ID:	1000008782661
Assignee:	SAMSUNG DISPLAY CO., LTD. (Yongin-si, KR)
Appl. No.:	17/317229
Filed:	May 11, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210265435 A1	Aug. 26, 2021

Foreign Application Priority Data

KR	10-2015-0015577	Jan. 30, 2015
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 16373102 20190402 US 11004919 child-doc US 17317229
continuation parent-doc US 14969251 20151215 US 10263054 20190416 child-doc US 16373102

Publication Classification

Int. Cl.: H10K59/35 (20230101); H10K50/842 (20230101); H10K59/121 (20230101);
H10K59/122 (20230101); H10K59/124 (20230101); H10K59/80 (20230101)

U.S. Cl.:

CPC H10K59/353 (20230201); H10K50/8428 (20230201); H10K59/121 (20230201);
H10K59/122 (20230201); H10K59/124 (20230201); H10K59/352 (20230201);
H10K59/8723 (20230201);

Field of Classification Search

CPC: H10K (59/8723); H10K (50/8428); H10K (59/30-38); H10K (59/12-1315); H01L
(27/3246); H01L (27/326); H01L (27/3258); H01L (27/3262); H01L (27/3216); H01L
(27/3218); H01L (51/525)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9349957	12/2015	Shin et al.	N/A	N/A
9627457	12/2016	Lee	N/A	N/A
10263054	12/2018	Kim et al.	N/A	N/A
2002/0149720	12/2001	Janssen et al.	N/A	N/A
2007/0200488	12/2006	Ito	N/A	N/A
2009/0058271	12/2008	Koo et al.	N/A	N/A
2009/0121983	12/2008	Sung et al.	N/A	N/A
2010/0033084	12/2009	Ko et al.	N/A	N/A
2011/0260952	12/2010	Hwang et al.	N/A	N/A
2012/0056531	12/2011	Park	313/506	H10K 50/125
2013/0021566	12/2012	Akitomo et al.	N/A	N/A
2014/0111757	12/2013	Komatsu et al.	N/A	N/A
2014/0197396	12/2013	Madigan	N/A	N/A
2014/0252321	12/2013	Pyon et al.	N/A	N/A
2014/0319479	12/2013	Park et al.	N/A	N/A
2015/0008397	12/2014	Kim et al.	N/A	N/A
2015/0311265	12/2014	Matsueda et al.	N/A	N/A
2016/0148981	12/2015	Matsueda	N/A	N/A
2016/0225833	12/2015	Kim	N/A	N/A
2016/0225834	12/2015	Kim et al.	N/A	N/A
2017/0061849	12/2016	Matsueda	N/A	G09G 3/3233
2019/0229166	12/2018	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102832353	12/2011	CN	N/A
2003-007960	12/2002	KR	N/A
10-2009-0021714	12/2008	KR	N/A
10-2009-0049515	12/2008	KR	N/A
10-2010-0003243	12/2009	KR	N/A
10-2010-0095986	12/2009	KR	N/A

10-2013-0002344	12/2012	KR	N/A
10-2014-0 50846	12/2013	KR	N/A
10-2014-0050548	12/2013	KR	N/A
10-1427593	12/2013	KR	N/A
10-2015-0005264	12/2014	KR	N/A

OTHER PUBLICATIONS

CN Office Action Dated Dec. 26, 2019 Corresponding to Chinese Patent Application No. 201610069610.6. cited by applicant

Primary Examiner: Purvis; Sue A

Assistant Examiner: Cieslewicz; Aneta B

Attorney, Agent or Firm: F. CHAU & ASSOCIATES, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/373,102 filed on Apr. 2, 2019, which is a continuation of U.S. application Ser. No. 14/969,251, filed on Dec. 15, 2015, now U.S. Pat. No. 10,263,054 issued on Apr. 16, 2019, which claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2015-0015577, filed on Jan. 30, 2015, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) One or more embodiments relate to organic light-emitting display apparatuses.

Description of the Related Technology

(2) Organic light-emitting display apparatuses are self-emission display apparatuses which have an organic light-emitting device including a hole injection electrode, an electron injection electrode, and an organic emission layer formed between the hole injection electrode and the electron injection electrode, and emit light when excitons generated by combining holes injected from the hole injection electrode and electrons injected from the electron injection electrode inside the organic emission layer drop from an excited state to a ground state.

(3) As organic light-emitting display apparatuses have self-emitting characteristics, they do not require a separate light source. Thus, the organic light-emitting display apparatuses may be driven at a low voltage, be formed to be lightweight and thin, and have high-quality characteristics such as wide view angles, good contrast, and quick response times. Accordingly, such apparatuses have drawn attention as next-generation display apparatuses.

SUMMARY OF CERTAIN INVENTIVE ASPECTS

(4) One or more embodiments include an organic light-emitting display apparatus.

(5) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(6) According to one or more embodiments, an organic light-emitting display apparatus includes: a thin-film transistor on a substrate; a planarization layer on the thin-film transistor; and a pixel-defining spacer on the planarization layer, wherein the pixel-defining spacer defines a pixel area and is between two pixels adjacent in a first direction.

(7) The two adjacent pixels may be blue.

- (8) Among the blue pixels in the pixel area, a first gap between first two neighboring blue pixels and a second gap between second two neighboring blue pixels may be alternately and regularly formed, the first gap may be different from the second gap, and the pixel-defining spacer may be formed in a region in which a gap between two neighboring blue pixels is wide.
- (9) The pixel-defining spacer may be between two green pixels adjacent in a second direction and between two red pixels adjacent in the second direction, wherein the second direction is perpendicular to the first direction.
- (10) The pixel-defining spacer may be rectangular shaped.
- (11) The pixel-defining spacer may be lozenge shaped.
- (12) The pixel-defining spacer may be spaced apart from the blue pixels by at least about 8 μm .
- (13) The pixel-defining spacer may be spaced apart from green pixels or red pixels by at least about 9.2 μm .
- (14) The pixel-defining spacer may be hexagonal shaped.
- (15) The pixel-defining spacer may be spaced apart from the blue pixels by at least 9 μm .
- (16) The pixel-defining spacer may be spaced apart from green pixels or red pixels by at least about 9.6 μm .
- (17) Blue pixels in the pixel area may be formed such that two different gaps, each gap between two neighboring blue pixels, are alternately and regularly formed, and the pixel-defining spacer may be formed in different shapes in a region in which a gap between a first two neighboring blue pixels is narrow and in a region in which a gap between a second two neighboring blue pixels is wide.
- (18) The pixel-defining spacer may be trapezoidal shaped in the region in which a gap between two neighboring blue pixels is narrow.
- (19) The top of the trapezoidal shaped pixel-defining spacer may be located between the two blue pixels, and the bottom of the trapezoidal shaped pixel-defining spacer may be located between adjacent green and red pixels.
- (20) The pixel-defining spacer may be quadrilateral shaped in the region in which a gap between two neighboring blue pixels is wide.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and/or other aspects will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings in which:
- (2) FIG. 1 illustrates a cross-sectional view of an organic light-emitting display apparatus according to an embodiment;
- (3) FIG. 2 illustrates a top view of an organic light-emitting display apparatus according to an embodiment;
- (4) FIG. 3 illustrates a top view of an organic light-emitting display apparatus according to another embodiment;
- (5) FIG. 4 illustrates a top view of an organic light-emitting display apparatus according to another embodiment;
- (6) FIG. 5 illustrates a top view of an organic light-emitting display apparatus according to another embodiment.

DETAILED DESCRIPTION OF CERTAIN INVENTIVE EMBODIMENTS

- (7) Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings, wherein like reference numerals generally refer to like elements throughout. In this regard, the embodiments may have different forms and should not be construed

as being limited to the descriptions set forth herein. Accordingly, the embodiments are merely described below, by referring to the figures, to explain aspects of the present description.

(8) It will be understood that although the terms “first”, “second”, and the like may be used herein to describe various components, these components should not be limited by these terms. These components are only used to distinguish one component from another.

(9) As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

(10) It will be further understood that the terms “comprises” and/or “comprising” used herein specify the presence of stated features or components, but do not preclude the presence or addition of one or more other features or components.

(11) It will be understood that when a layer, region, or component is referred to as being “formed on,” another layer, region, or component, it can be directly or indirectly formed on the other layer, region, or component. For example, intervening layers, regions, or components may also be present.

(12) Sizes of elements in the drawings may be exaggerated for convenience of explanation. In other words, since sizes and thicknesses of components in the drawings are arbitrarily illustrated for convenience of explanation, the embodiments are not limited thereto.

(13) When a certain embodiment may be implemented differently, a specific process order may be performed differently from the described order. For example, two consecutively described processes may be performed substantially at the same time or performed in an order opposite to the described order.

(14) As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

(15) FIG. 1 illustrates a cross-sectional view of one pixel circuit of a thin film transistor array substrate included in an organic light-emitting display apparatus according to an embodiment.

(16) The thin-film transistor array substrate includes at least one thin-film transistor. The thin film transistor array substrate may include a plurality of regularly arranged thin-film transistors TFT, a plurality of irregularly arranged thin-film transistors TFT, or one thin-film transistor TFT.

(17) As shown in FIG. 1, the one pixel circuit may include a substrate **110**, a thin-film transistor TFT on the substrate **110**, and a planarization layer PL on the thin film transistor TFT.

(18) Referring to FIG. 1, a buffer layer **111** may be formed on the substrate **110**. The buffer layer **111** may act as a barrier layer and/or a blocking layer for preventing the spread of impurity ions, preventing the infiltration of humidity or external air, and for planarizing the surface of the substrate **110**.

(19) A semiconductor layer A of the thin-film transistor TFT is formed on the buffer layer **111**. The semiconductor layer A may include polysilicon and may include a channel region undoped with impurities, and source and drain regions doped with the impurities and respectively located at both sides of the channel region. The impurities may vary depending on a type of the thin-film transistor TFT, and may be N- or P-type impurities.

(20) A gate insulating layer **120** may be stacked on the entire surface of the substrate **110** to cover the semiconductor layer A. The gate insulating layer **120** may include an inorganic material, such as, for example, silicon oxide, silicon nitride, or the like, and in a multi-layer or a single layer. The gate insulating layer **120** insulates between the semiconductor layer A and a gate electrode G of the thin-film transistor TFT.

(21) A material of the gate electrode G may include one or more of molybdenum (Mo), aluminum (Al), platinum (Pt), palladium (Pd), silver (Ag), magnesium (Mg), gold (Au), nickel (Ni), neodymium (Nd), iridium (Ir), chromium (Cr), lithium (Li), calcium (Ca), titanium (Ti), tungsten (W), or copper (Cu).

(22) An interlayer insulating layer **130** is formed on the entire surface of the substrate **110** to cover

the gate electrode G.

(23) The interlayer insulating layer **130** may include an inorganic material or an organic material. According to one or more embodiments, the interlayer insulating layer **130** may include an inorganic material. For example, the interlayer insulating layer **130** may include metal oxide or metal nitride, and the inorganic material may include silicon oxide (SiO₂), silicon nitride (SiN_x), silicon oxynitride (SION), aluminum oxide (Al₂O₃), titanium oxide (TiO₂), tantalum oxide (Ta₂O₅), hafnium oxide (HfO₂), zinc oxide (ZnO₂), or the like.

(24) The interlayer insulating layer **130** may include an inorganic material of silicon oxide (SiO_x) and/or silicon nitride (SiN_x), or the like and in a multi-layer or a single layer. According to one or more embodiments, the interlayer insulating layer **130** may be formed in a double structure of SiO_x/SiN_y or SiN_x/SiO_y.

(25) The interlayer insulating layer **130** insulates the gate electrode G from wirings formed on the interlayer insulating layer **130**.

(26) A source electrode S and a drain electrode D of the thin-film transistor TFT respectively connected to the source region and the drain region doped with the impurities in the semiconductor layer A may be formed on the interlayer insulating layer **130**. In other embodiments, the source electrode S and the drain electrode D may be in the same layer as the semiconductor layer A. That is, the source electrode S and the drain electrode D of the thin-film transistor TFT may include polysilicon selectively doped with a doping material.

(27) The planarization layer PL is formed on the entire surface of the substrate **110** to cover a plurality of wirings, the source electrode S, and the drain electrode D formed on the interlayer insulating layer **130**. A pixel electrode **141** may be formed on the planarization layer PL. The pixel electrode **141** is connected to the drain electrode D or the source electrode S of the thin-film transistor TFT through a via hole VIA.

(28) The planarization layer PL may include an insulating material. For example, the planarization layer PL may include an inorganic material, an organic material, or an organic/inorganic compound, in a single- or multi-layer structure, and by various deposition methods. According to one or more embodiments, the planarization layer PL may include one or more materials of polyacrylates resin, epoxy resin, phenolic resin, polyamides resin, polyimides resin, unsaturated polyesters resin, poly phenylenethers resin, poly phenylenesulfides resin, and benzocyclobutene (BCB).

(29) An intermediate layer **143**, which includes an organic emission layer, and an opposite electrode **145** may be formed on the pixel electrode **141**, and the pixel electrode **141**, the intermediate layer **143**, and the opposite electrode **145** are components of an organic light-emitting diode (OLED).

(30) The pixel electrode **141** may fill the via hole VIA in the planarization layer PL and may be electrically connected to the source electrode S or the drain electrode D of the thin-film transistor TFT. The pixel electrode **141** and/or the opposite electrode **145** may be a transparent electrode or a reflective electrode. For the transparent electrode, the pixel electrode **141** and/or the opposite electrode **145** may include indium tin oxide (ITO), indium zinc oxide (IZO), zinc oxide (ZnO), or indium oxide (In₂O₃). For the reflective electrode, the pixel electrode **141** and/or the opposite electrode **145** may include a reflective layer including Ag, Mg, Al, Pt, Pd, Au, Ni, Nd, Ir, Cr, a compound thereof, or the like, and a transparent layer including ITO, IZO, ZnO, or In₂O₃. According to one or more embodiments, the pixel electrode **141** or the opposite electrode **145** may have an ITO/Ag/ITO structure.

(31) As described above, the pixel electrode **141**, the intermediate layer **143**, and the opposite electrode **145** form the OLED. Holes and electrons injected from the pixel electrode **141** and the opposite electrode **145** of the OLED may be combined in the organic emission layer of the intermediate layer **143**, thereby emitting light.

(32) The intermediate layer **143** may include an organic emission layer. As another example, the intermediate layer **143** may include the organic emission layer and may further include at least one of a hole injection layer (HIL), a hole transport layer (HTL), an electron transport layer (ETL), and an electron injection layer (EIL). In other embodiments, the intermediate layer **143** may include the organic emission layer and may further include other various function layers. The opposite electrode **145** is formed on the intermediate layer **143**. The opposite electrode **145** forms an electric field together with the pixel electrode **141** so that the intermediate layer **143** emits light. The pixel electrode **141** may be patterned for each pixel, and the opposite electrode **145** may be formed over all pixels such that a common voltage is applied to all the pixels.

(33) Each of the pixel electrode **141** and the opposite electrode **145** may be a transparent electrode or a reflective electrode. The pixel electrode **141** may function as an anode electrode, and the opposite electrode **145** may function as a cathode electrode. In other embodiments, the pixel electrode **141** may function as a cathode electrode, and the opposite electrode **145** may function as an anode electrode.

(34) Although only one OLED is shown in FIG. **1**, a display panel may include a plurality of OLEDs. One pixel may be formed for each OLED, and a red, green, blue, or white color may be realized for each pixel, as an example.

(35) In other embodiments, the intermediate layer **143** may be commonly formed for the whole pixel electrodes **141** regardless of a position of each pixel. In this case, the organic emission layer may be formed such that layers respectively including emission materials emitting red, green, and blue lights are vertically stacked or are mixed. Alternatively, other colors may be combined if white light is emitted. In addition, a color conversion layer or a color filter for converting the emitted white light into a predetermined color may be further included.

(36) In addition, the organic light-emitting display apparatus may further include a pixel-defining spacer HPDL on the planarization layer PL.

(37) The pixel-defining spacer HPDL in one embodiment indicates a component which performs both the role of a pixel-defining layer for defining a pixel area and a non-pixel area, and the role of a spacer for maintaining a gap between the substrate **110** and a sealing substrate (not shown).

(38) Therefore, the organic light-emitting display apparatus according to embodiments herein includes the pixel-defining spacer HPDL capable of performing both roles, and thus time and costs are saved in terms of a process.

(39) The pixel-defining spacer HPDL may include an opening through which the pixel electrode **141** is exposed and may be formed to cover all over the substrate **110**. As shown in FIG. **1**, the intermediate layer **143** may be formed in the opening such that the opening substantially becomes a pixel area.

(40) The pixel-defining spacer HPDL may be disposed between pixel areas to define a pixel area and a non-pixel area, and may protrude towards the top as shown in FIG. **1**. Since the pixel-defining spacer HPDL performs both the role of a pixel-defining layer and the role of a spacer, the pixel-defining spacer HPDL may protrude towards the top to have a sufficient height. Accordingly, the pixel-defining spacer HPDL may maintain the gap between the substrate **110** and the sealing substrate (not shown) on the substrate **110**, and may also prevent a decrease in a display characteristic due to an external shock.

(41) Although FIG. **1** shows a shape of the pixel-defining spacer HPDL according to one embodiment, the shape of the pixel-defining spacer HPDL is not limited thereto, and any shape may be applied thereto if the shape sufficiently performs both the role of a pixel-defining layer and the role of a spacer.

(42) The pixel-defining spacer HPDL may be formed by stacking an insulating material which may include an organic material or an inorganic material. The organic material may include one of BCB, an acrylic photoresist, a phenolic photoresist, a polyimides photoresist, or other photosensitive resins. However, embodiments are not limited thereto.

(43) FIG. 2 illustrates a top view of an organic light-emitting display apparatus according to an embodiment. FIG. 2 shows only a plurality of color pixels R, G, and B and pixel-defining spacers HPDL for convenience of description.

(44) As shown in FIG. 2, in one example, each pixel-defining spacer HPDL may be formed between two neighboring blue pixels B.

(45) When it is defined, as in FIG. 2, that a vertical direction is a first direction and a horizontal direction that is perpendicular to the first direction is a second direction, each pixel-defining spacer HPDL may be formed between two blue pixels B neighboring in the first direction.

(46) A thin-film transistor array substrate may be formed such that blue pixels B in a pixel area have different gaps therebetween, while gaps between red pixels R and green pixels G remain constant.

(47) That is, unlike the arrangement of the red pixels R and the green pixels G with a constant gap therebetween, the blue pixels B may be regularly arranged such that gaps between two neighboring blue pixels B maintain two gaps, W and N.

(48) Referring to FIG. 2, the blue pixels B may be alternately arranged such that gaps between two neighboring blue pixels B maintain a relatively wide gap W, and a relatively narrow gap N.

(49) In this case, as described above, the pixel-defining spacer HPDL may be formed between two neighboring blue pixels B. The pixel-defining spacer HPDL may be formed between two blue pixels B maintaining the relatively wide gap W therebetween.

(50) Commonly, in the existing organic light-emitting display apparatus, a spacer is formed between a red pixel R and a green pixel G. However, in this case, since a gap between the spacer and each pixel cannot be sufficiently secured, a dark spot may be generated due to a stabbing effect.

(51) Accordingly, in the organic light-emitting display apparatus according to embodiments herein described, the pixel-defining spacer HPDL is formed between two neighboring blue pixels B located to sufficiently secure a gap therebetween to solve the dark spot problem.

(52) The relatively wide gap W of the gaps between two neighboring blue pixels B may be about $67.5\text{ }\mu\text{m}$, and the relatively narrow gap N may be about $12.5\text{ }\mu\text{m}$. The gap between neighboring red and green pixels R and G may be about $27.5\text{ }\mu\text{m}$.

(53) Of course, the above-described numeric values of the gaps between the pixels R, G, and B are only illustrative, and embodiments are not limited thereto.

(54) By forming the pixel-defining spacer HPDL between two blue pixels B having a maximum gap W therebetween, a space is well used, and by maximizing a distance between the pixel-defining spacer HPDL and an opening region, a damage of a pixel due to an external shock may be prevented when a partial shock is applied.

(55) Referring to FIG. 2, in one embodiment of the organic light-emitting display apparatus, the pixel-defining spacer HPDL may be formed between two neighboring blue pixels B such that a region between a green pixel G and a red pixel R, and a region between another green pixel G and another red pixel R are respectively located to the left and right of the pixel-defining spacer HPDL.

(56) The pixel-defining spacer HPDL may be formed between two neighboring green pixels G and between two neighboring red pixels R in the second direction that is perpendicular to the first direction. In particular, the pixel-defining spacer HPDL may be formed in a space between neighboring green pixels G and red pixels R.

(57) The pixel-defining spacer HPDL may be formed between blue pixels B spaced apart by the gap W which is relatively wide with respect to gaps between blue pixels B adjacent to one another in the first direction that is the vertical direction in FIG. 2. The pixel-defining spacer HPDL may be formed at the same location as a location between neighboring red and green pixels R and G. In addition, the pixel-defining spacer HPDL may be formed in a region between two neighboring green pixels G and between two neighboring red pixels R in the second direction that is perpendicular to the first direction.

(58) Therefore, the pixel-defining spacer HPDL may be located in a vacant space around pixels R, G, and B without pixels R, G, and B in the left and right regions of the pixel-defining spacer HPDL in the second direction.

(59) Accordingly, a predetermined gap is maintained in the vertical direction of the pixel-defining spacer HPDL, and a vacant space without pixels is formed to the left and right of the pixel-defining spacer HPDL, and thus, even if the pixel-defining spacer HPDL moves due to an external shock, the pixel-defining spacer HPDL does not move to an opening region, and accordingly, a deposited object may be prevented from being stabbed.

(60) As shown in FIG. 2, the pixel-defining spacer HPDL may be formed in a rectangular shape, but is not limited thereto.

(61) In addition, distances from the pixel-defining spacer HPDL to a blue pixel B, to a red pixel R, and to a green pixel G may be variously adjusted.

(62) As described above, compared with the existing thin film transistor array substrate, distances from the pixel-defining spacer HPDL to nearby pixels may be maximized, and thus a slip distance of the pixel-defining spacer HPDL may be secured to thereby prevent a partial shock, and even when the pixel-defining spacer HPDL moves, the pixel-defining spacer HPDL does not move to an opening region, and thus a deposited object may be prevented from being stabbed.

(63) FIG. 3 illustrates a top view of a thin-film transistor array substrate according to another embodiment. In FIG. 3, like reference numerals in FIGS. 1 and 2 refer to like elements, and the description thereof is not repeated for conciseness of the description.

(64) In one embodiment of an organic light-emitting display apparatus, the pixel-defining spacer HPDL may be formed in a lozenge shape. Accordingly, the pixel-defining spacer HPDL may be formed by maximally using a vacant space between pixels while maintaining a minimum distance to a pixel as a predetermined gap.

(65) As shown in FIG. 3, when the pixel-defining spacer HPDL is formed in a lozenge shape, a vacant space between pixels may be maximally used, and thus a size of the pixel-defining spacer HPDL may be relatively large.

(66) By forming the pixel-defining spacer HPDL in a lozenge shape on the thin-film transistor array substrate, a minimum distance to blue pixels B in the vertical direction may be maintained as about 8 μm , and a minimum distance to red and green pixels R and G in the horizontal direction may be maintained as about 9.6 μm .

(67) The above-described numeric values as the distances to the blue, red, and green pixels B, R, and G are only illustrative, and embodiments are not limited thereto. In addition, the numeric values may be variously adjusted if the pixel-defining spacer HPDL is formed at the location described above.

(68) FIG. 4 illustrates a top view of an organic light-emitting display apparatus according to another embodiment. In FIG. 4, like reference numerals in FIGS. 1 and 2 refer to like elements, and the description thereof is not repeated for conciseness of the description.

(69) As shown in FIG. 4, in the organic light-emitting display apparatus, the pixel-defining spacer HPDL may be formed in a hexagonal shape.

(70) By forming the pixel-defining spacer HPDL in a hexagonal shape, a vacant space between pixels may be maximally used while maintaining a distance to a pixel as a predetermined gap, and thus a size of the pixel-defining spacer HPDL may be relatively large.

(71) By forming the pixel-defining spacer HPDL in a hexagonal shape in the organic light-emitting display apparatus, a minimum distance to blue pixels B in the vertical direction may be maintained as about 9 μm , and a minimum distance to red and green pixels R and G in the horizontal direction may be maintained as about 9.6 μm .

(72) The above-described numeric values as the distances to the blue, red, and green pixels B, R, and G are only illustrative, and embodiments are not limited thereto. In addition, the numeric values may be variously adjusted if the pixel-defining spacer HPDL is formed at the location

described above.

(73) FIG. 5 illustrates a top view of an organic light-emitting display apparatus according to another embodiment. In FIG. 5, like reference numerals in FIGS. 1 and 2 refer to like elements, and the description thereof is not repeated for conciseness of the description.

(74) Unlike the pixel-defining spacers HPDL described above, a thin-film transistor array substrate according to one embodiment may include pixel-defining spacers HPDL having different shapes.

(75) As shown in FIG. 5, the thin-film transistor array substrate may include pixel-defining spacers HPDL having two shapes in consideration of gaps between red, green, and blue pixels R, G, and B.

(76) As described above, gaps between two neighboring blue pixels B maintain the relatively wide gap W and the relatively narrow gap N. In this case, pixel-defining spacers HPDL of a quadrilateral shape may be formed between two blue pixels B maintaining the relatively wide gap W, and pixel-defining spacers HPDL of a trapezoidal shape may be formed between two blue pixels B maintaining the relatively narrow gap N.

(77) Accordingly, sizes and the number of pixel-defining spacers HPDL may be maximally formed while maintaining a maximum distance between the pixel-defining spacers HPDL and neighboring pixels.

(78) The pixel-defining spacers HPDL formed between two neighboring blue pixels B maintaining the relatively narrow gap N may be formed in a trapezoidal shape, and as shown in FIG. 5, the pixel-defining spacers HPDL may be formed such that the topside “s” that is a short side is located between two blue pixels B and the bottom side “I” that is a long side is located between a green pixel G and a red pixel R.

(79) The pixel-defining spacers HPDL are formed by considering that a gap between two blue pixels B is relatively narrow, whereas a gap between a green pixel G and a red pixel R is relatively wide.

(80) The pixel-defining spacers HPDL may be formed in a trapezoidal shape such that the topside s that is a short side of each pixel-defining spacer HPDL is located between two blue pixels B to maximally maintain a gap between the pixel-defining spacers HPDL and the two blue pixels B and the bottom side I that is a long side of each pixel-defining spacer HPDL is located between a green pixel G and a red pixel R.

(81) The pixel-defining spacer HPDL may be formed of a trapezoidal shape even between two blue pixels B maintaining the relatively narrow gap N in consideration of a location where the pixel-defining spacer HPDL moves vertically or horizontally while maximally using gaps between red, green, and blue pixels R, G, and B.

(82) Referring to FIG. 5, a pixel-defining spacer HPDL of a quadrilateral shape may be formed between two blue pixels B maintaining the relatively wide gap W. The quadrilateral shape of the pixel-defining spacer HPDL is not limited, and any quadrilateral shape may be applied.

(83) In addition, as shown in FIG. 5, the pixel-defining spacer HPDL may be divided into two pixel-defining spacers HPDL of a quadrilateral shape.

(84) Accordingly, on the thin-film transistor array substrate, a size of each pixel-defining spacer HPDL may be maximally formed within a range of maintaining a gap, and the number of pixel-defining spacers HPDL may also be maximized.

(85) As described above, according to the one or more embodiments, by forming a pixel-defining spacer using a space between pixels, a deposited object stabbing problem and a partial shock problem may be prevented.

(86) It should be understood that the embodiments described herein should be considered in a descriptive sense only and not for purposes of limitation. Descriptions of features or aspects within each embodiment should typically be considered as available for other similar features or aspects in other embodiments.

(87) While certain embodiments have been described with reference to the figures, it will be

understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope as defined by the following claims.

Claims

1. A display device comprising: a thin-film transistor on a substrate; a planarization layer on the thin-film transistor; a plurality of insulating structures on the planarization layer; and a plurality of first light-emitting areas emitting a first color, a plurality of second light-emitting areas emitting a second color, and a plurality of third light-emitting areas emitting a third color on the planarization layer, wherein each of the plurality of first light-emitting areas, the plurality of second light-emitting areas and the plurality of third light-emitting areas includes an organic emission layer, wherein the plurality of first light-emitting areas are arranged in a first row in a first direction, wherein the organic emission layer of adjacent first light-emitting areas are disconnected from each other, wherein the plurality of second light-emitting areas and the plurality of third light-emitting areas are alternately arranged in a second row in the first direction, wherein a size of each of the plurality of first light-emitting areas is greater than a size of each of the plurality of second light-emitting areas and a size of each of the plurality of third light-emitting areas, a first gap between first two adjacent first light-emitting areas and a second gap between second two adjacent first light-emitting areas are alternately formed, a width of the first gap being greater than a width of the second gap, and the plurality of insulating structures are disposed in the first gap and not in the second gap.
2. The display device of claim 1, wherein a third gap is formed between a second light-emitting area and a third light-emitting area that are adjacent to each other, a width of the third gap being less than the width of the first gap and greater than the width of the second gap.
3. The display device of claim 1, wherein a width of each of the plurality of first light-emitting areas in the first direction is greater than a width of each of the plurality of second light-emitting areas in a second direction and a width of each of the plurality of third light-emitting areas in the second direction, the second direction being perpendicular to the first direction.
4. The display device of claim 1, wherein the first color, the second color, and the third color generate a white color when mixed with each other.
5. The display device of claim 1, wherein the first color is a blue color, the second color is a red color, and the third color is a green color.
6. The display device of claim 1, wherein the width of each of the plurality of first light-emitting areas in the first direction is greater than a width thereof in the second direction.
7. The display device of claim 6, wherein the width of each of the plurality of first light-emitting areas in the first direction is greater than a width of each of the plurality of second light-emitting areas in the first direction.
8. The display device of claim 6, wherein the width of each of the plurality of first light-emitting areas in the first direction is greater than a width of each of the plurality of third light-emitting areas in the first direction.
9. The display device of claim 6, wherein the width of each of the plurality of first light-emitting areas in a second direction is less than the width of each of the plurality of second light-emitting areas in the second direction, the second direction being perpendicular to the first direction.
10. The display device of claim 6, wherein the width of each of the plurality of first light-emitting areas in a second direction is less than the width of each of the plurality of third light-emitting areas in the second direction, the second direction being perpendicular to the first direction.
11. The display device of claim 6, wherein a width of each of the plurality of second light-emitting areas in a second direction is equal to a width of each of the plurality of third light-emitting areas in the second direction, the second direction being perpendicular to the first direction.
12. The display device of claim 6, wherein the width of each of the plurality of first light-emitting

areas in a first direction is greater than a sum of a width of each of the plurality of second light-emitting areas in the first direction and a width of each of the plurality of third light-emitting areas in the first direction.

13. A display device comprising: a thin-film transistor on a substrate; a planarization layer on the thin-film transistor; a plurality of insulating structures on the planarization layer; and a plurality of first light-emitting areas emitting a first color, a plurality of second light-emitting areas emitting a second color, and a plurality of third light-emitting areas emitting a third color on the planarization layer, wherein each of the plurality of first light-emitting areas, the plurality of second light-emitting areas and the plurality of third light-emitting areas includes an organic emission layer, wherein the plurality of first light-emitting areas are arranged in a first row in a first direction, wherein the organic emission layer of adjacent first light-emitting areas are disconnected from each other, wherein the plurality of second light-emitting areas and the plurality of third light-emitting areas are alternately arranged in a second row in the first direction, wherein the shape of a second light-emitting area is symmetrical to the shape of a third light-emitting area about an axis passing through an intermediate point between the second light-emitting area and the third light-emitting area in a second direction that is perpendicular to the first direction, the second light-emitting area being adjacent to the third light-emitting area, a first gap between first two adjacent first light-emitting areas and a second gap between second two adjacent first light-emitting areas are alternately formed, a width of the first gap being greater than a width of the second gap, wherein the plurality of insulating structures are disposed in the first gap and not in the second gap.

14. The display device of claim 13, wherein the shape of each second light-emitting area is the same as the shape of each third light-emitting area.

15. The display device of claim 13, wherein a length of each first light-emitting area in the first direction is greater than a length in the first direction of each second light-emitting area and of each third light-emitting area, and a width in the second direction of each first light-emitting area is less than a width in the second direction of each second light-emitting area and of each third light-emitting area.
