

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                          |
|----------------------|--------------------------|
| United States Patent | 12387752                 |
| Kind Code            | B2                       |
| Date of Patent       | August 12, 2025          |
| Inventor(s)          | Pankaew; Ekaratch et al. |

---

### Suspension damping

---

#### Abstract

A dielectric layer configured to overlay a spring metal layer in a suspension assembly is described. The dielectric layer includes a tongue portion including a proximate end and a distal end, trace portions extending from the tongue portion, and an aperture aligned with the void and defined by the tongue portion. The aperture includes an elongated opening with opposing ends partially aligning with the central opening of the void. The aperture further includes slits extending from the opposing ends of the elongated opening and at least partially aligned with slits of the void in the spring metal layer.

---

**Inventors:** Pankaew; Ekaratch (Wangnoi, TH), Ee; Kuen Chee (Chino, CA), Sudachun; Preecha (Wangnoi, TH), Glaess; David (Bangkok, TH), Angsutanasombat; Chanatkarn (Wangnoi, TH)

**Applicant:** Magnecomp Corporation (Murrieta, CA)

**Family ID:** 77061449

**Assignee:** Magnecomp Corporation (Murrieta, CA)

**Appl. No.:** 18/658688

**Filed:** May 08, 2024

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20240290347 A1   | Aug. 29, 2024    |

#### Related U.S. Application Data

continuation parent-doc US 17158955 20210126 US 12002497 child-doc US 18658688  
us-provisional-application US 62968859 20200131

---

## Publication Classification

**Int. Cl.:** G11B5/48 (20060101)

**U.S. Cl.:**

**CPC** G11B5/4833 (20130101); G11B5/486 (20130101);

## Field of Classification Search

**USPC:** None

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name             | U.S. Cl.  | CPC            |
|------------|-------------|---------------------------|-----------|----------------|
| 5883758    | 12/1998     | Bennin et al.             | N/A       | N/A            |
| 5959807    | 12/1998     | Jurgenson                 | 360/245.7 | G11B<br>5/4806 |
| 5982584    | 12/1998     | Bennin et al.             | N/A       | N/A            |
| 6515832    | 12/2002     | Girard                    | N/A       | G11B<br>5/4826 |
| 6612016    | 12/2002     | Bennin et al.             | N/A       | N/A            |
| 6965499    | 12/2004     | Zhang et al.              | N/A       | N/A            |
| 7113372    | 12/2005     | Segar et al.              | N/A       | N/A            |
| 7384531    | 12/2007     | Peltoma                   | 360/235.1 | C25D 5/12      |
| 7489493    | 12/2008     | Thaveeprungsriporn et al. | N/A       | N/A            |
| 7518830    | 12/2008     | Panchal et al.            | N/A       | N/A            |
| 7567410    | 12/2008     | Zhang et al.              | N/A       | N/A            |
| 7595963    | 12/2008     | Chen                      | 360/245.9 | G11B<br>5/4853 |
| 7663843    | 12/2009     | Yao                       | N/A       | N/A            |
| 7697237    | 12/2009     | Danielson                 | N/A       | N/A            |
| 8027128    | 12/2010     | Muraki et al.             | N/A       | N/A            |
| 8085506    | 12/2010     | Ee et al.                 | N/A       | N/A            |
| 8085508    | 12/2010     | Hatch                     | N/A       | N/A            |
| 8446695    | 12/2012     | Ee                        | 360/245.9 | G11B<br>5/4826 |
| 8605389    | 12/2012     | Pan                       | 360/245.9 | G11B<br>5/486  |
| 8702998    | 12/2013     | Guerini                   | N/A       | N/A            |
| 8792212    | 12/2013     | Pan et al.                | N/A       | N/A            |
| 8792213    | 12/2013     | Vijay et al.              | N/A       | N/A            |
| 8947831    | 12/2014     | Ee                        | 360/245.3 | G11B<br>5/4873 |
| 8976491    | 12/2014     | Chen et al.               | N/A       | N/A            |
| 9025282    | 12/2014     | Miller                    | N/A       | N/A            |

|              |         |                    |           |                |
|--------------|---------|--------------------|-----------|----------------|
| 9025283      | 12/2014 | Puttichaem         | 360/245.9 | G11B<br>5/4853 |
| 9646638      | 12/2016 | Bjorstrom et al.   | N/A       | N/A            |
| 10002628     | 12/2017 | Bjorstrom          | N/A       | N/A            |
| 10373634     | 12/2018 | Pokornowski et al. | N/A       | N/A            |
| 10566016     | 12/2019 | Yamada et al.      | N/A       | N/A            |
| 12002497     | 12/2023 | Pankaew            | N/A       | G11B<br>5/486  |
| 2004/0226164 | 12/2003 | Girard             | N/A       | N/A            |
| 2005/0254175 | 12/2004 | Swanson            | 360/245.9 | G11B 5/48      |
| 2008/0180850 | 12/2007 | Rice et al.        | N/A       | N/A            |
| 2011/0096438 | 12/2010 | Takada et al.      | N/A       | N/A            |
| 2011/0228426 | 12/2010 | Zhou et al.        | N/A       | N/A            |
| 2013/0248231 | 12/2012 | Tobias             | 29/829    | H05K<br>1/05   |
| 2014/0168821 | 12/2013 | Miller             | N/A       | N/A            |
| 2014/0347765 | 12/2013 | Miller et al.      | N/A       | N/A            |
| 2015/0062758 | 12/2014 | Miller et al.      | N/A       | N/A            |
| 2015/0213818 | 12/2014 | Imai et al.        | N/A       | N/A            |
| 2016/0171995 | 12/2015 | Bjorstrom          | N/A       | N/A            |
| 2017/0330589 | 12/2016 | Bjorstrom et al.   | N/A       | N/A            |

## FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 2007-287296 | 12/2006          | JP      | N/A |
| 2009-187650 | 12/2008          | JP      | N/A |
| 2010-146631 | 12/2009          | JP      | N/A |
| 2014-238895 | 12/2013          | JP      | N/A |
| 2016-519387 | 12/2015          | JP      | N/A |
| 2019-515410 | 12/2018          | JP      | N/A |
| 2017/197030 | 12/2016          | WO      | N/A |

## OTHER PUBLICATIONS

Notification of Reasons for Rejection in Japanese Application No. 2022-546067, dated Aug. 6, 2024. cited by applicant

International Search Report and Written Opinion in International Application No. PCT/US2021/015301, mailed Apr. 21, 2021. cited by applicant

International Preliminary Report on Patentability in International Application No. PCT/US2021/015301, mailed Aug. 11, 2022. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed May 10, 2021. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Aug. 18, 2021. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Nov. 29, 2021. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Jun. 30, 2022. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Oct. 12, 2022. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Mar. 30, 2023. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Jul. 14, 2023. cited by applicant

Office Action in U.S. Appl. No. 17/158,955, mailed Oct. 23, 2023. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/158,955, mailed Feb. 1, 2024. cited by applicant

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/158,955 filed Jan. 26, 2021, which claims the benefit of U.S. Provisional Application No. 62/968,859 filed on Jan. 31, 2020, which is hereby incorporated by reference in its entirety.

### FIELD

(1) Embodiments of the disclosure relate to the field of suspensions for disk drives. More particularly, this disclosure relates to the field of flexures that are configured to be included in disk drive suspensions and provide for improved suspension damping.

### BACKGROUND

(2) Magnetic recording heads typically comprise a transducer and a slider. These are supported in proximity to a magnetic recording medium, usually a spinning disk with a magnetic coating, by a suspension assembly. The suspension includes a load beam that attaches to the slider with a read/write transducer assembly via a flexible gimbal device at one end and a flexible section of the suspension, namely the formed area, at the other end. The formed area in turn is connected to a suspension support arm. The suspension support arm connects to an actuator. It is desirable for the transducer suspension to be flexible in a direction perpendicular to the plane of the disk so that the suspension is able to follow any movement of the head due to disk run out or wobbling of the disk normal to its plane. If the transducer does not follow the out of plane motion of the disk, head to disk spacing variations will result. Additionally, the suspension should be extremely rigid in a plane parallel to that of the disk so the transducer can be accurately placed over a data track. The slider and the magnetic element are positioned over the proper track of data by a voice-coil powered actuator in order to read, write, and erase data.

(3) Data is transferred to a magnetic recording medium in the form of magnetic flux reversals from a gap in the transducer. Recently, advances have been made that allow very high densities of data to be stored on a single disk. For accurate and dense data encoding, the read/write gap in the transducer must be maintained as close to the disk as possible at a constant height; typically, a few nanometers above the disk. The storage capacity of the disk is a strong function of the height of the read/write gap above the disk, i.e., the flying height. Storage capacity is also a function of the track density, i.e., the number of recording tracks available radially. This is determined by the accuracy with which the actuator motor can locate the transducer over a previously written track of data and follow that track as the disk spins. Therefore, the storage capacity of the disk is measured by the number of flux reversals per square inch. More precisely, the area density is calculated by the linear bit density, or the number of flux reversals per inch along a track, times the radial track density, or the number of tracks available radially. Typically, the linear bit density is an order of magnitude greater than the radial track density. The number of flux reversals per inch is extremely sensitive to the head to disk interface spacing; flying height variation significantly reduces the number of flux reversals per inch. Hence, it is very important to keep the head to disk spacing as constant as possible.

(4) Suspension resonances are generally excited in the suspension during data seek and track following operations. However, there are also other sources that can cause the suspension to resonate, including external disturbances. In order to maximize the capacity of disk drives, it is necessary to control the resonant behavior of the suspension such that the suspension can have

better track following performance when the actuator is active.

## SUMMARY

(5) A suspension is provided. The suspension includes a flexure, which includes a gimbal, a proximal end, and a distal end. The flexure having a longitudinal axis extending from the proximal end to the distal end. The gimbal includes a spring metal layer including a base portion, a tongue, and a pair of spring arms extending from the base portion to the tongue. The gimbal also includes a dielectric layer overlaying the spring metal layer and a conductive metal layer overlying the dielectric layer.

(6) The conductive metal layer includes a first plurality of traces extending from the base portion to the tongue and a second plurality of traces extending from the base portion to the tongue. The suspension also includes a void formed in the spring metal layer and partially surrounding the tongue. A portion of the dielectric layer overlays a section of the void formed in the spring metal layer.

(7) In some embodiments of the suspension, a portion of the first plurality of traces and a portion of the second plurality of traces are coupled over the void and extend towards the tongue. The void includes a central opening with opposing ends, and first and second channels extending from the opposing ends of the central opening. The dielectric layer can include a tongue portion, trace portions, and an aperture aligned with the void and defined by the tongue portion and the trace portions. The tongue portion includes a proximate end and a distal end. The trace portions extending from the distal end of the tongue portion. The aperture includes an elongated opening with opposing ends partially aligning with the central opening of the void, and slits extending from the opposing ends of the elongated opening and at least partially exposing the first and second channels of the void.

(8) In some embodiments of the suspension, the slits of the aperture extend from the opposing ends of the elongated opening up to 40% of a length between the proximate end and the distal end of the tongue portion. Specifically, the slits of the aperture extend from the opposing ends of the elongated opening up to 25% of a length between the proximate end and the distal end of the tongue portion. In other embodiments, the slits of the aperture extend from the opposing ends of the elongated opening up to 80% of a length between the proximate end and the distal end of the tongue portion. Specifically, the slits of the aperture extend from the opposing ends of the elongated opening up to 50% of a length between the proximate end and the distal end of the tongue portion.

(9) A dielectric layer is also provided. The dielectric layer includes a tongue portion, trace portions, and an aperture aligned with the void and defined by the tongue portion. The tongue portion includes a proximate end and a distal end. The trace portions extending from the proximate end of the tongue portion. The aperture includes an elongated opening with opposing ends partially aligning with the central opening of the void.

(10) In some embodiments, the aperture further includes slits extending from the opposing ends of the elongated opening and at least partially exposing the first and second channels of the void. The slits of the aperture can extend from the opposing ends of the elongated opening up to 40% of a length between the proximate end and the distal end of the tongue portion. Specifically, the slits of the aperture extend from the opposing ends of the elongated opening up to 25% of a length between the proximate end and the distal end of the tongue portion. Alternatively, the slits of the aperture extend from the opposing ends of the elongated opening up to 80% of a length between the proximate end and the distal end of the tongue portion. Specifically, the slits of the aperture extend from the opposing ends of the elongated opening up to 50% of a length between the proximate end and the distal end of the tongue portion.

(11) A flexure is also provided. The flexure includes a gimbal, a proximal end, and a distal end. The flexure having a longitudinal axis extending from the proximal end to the distal end. The gimbal includes a spring metal layer including a base portion, a tongue, and a pair of spring arms

extending from the base portion to the tongue. The gimbal also includes a dielectric layer overlaying the spring metal layer and a conductive metal layer overlying the dielectric layer.

(12) The conductive metal layer includes a first plurality of traces extending from the base portion to the tongue and a second plurality of traces extending from the base portion to the tongue. The flexure also includes a void formed in the spring metal layer and partially surrounding the tongue. A portion of the dielectric layer overlays a section of the void formed in the spring metal layer.

(13) In some embodiments of the flexure, a portion of the first plurality of traces and a portion of the second plurality of traces are coupled over the void and extend towards the tongue. The void includes a central opening with opposing ends, and first and second channels extending from the opposing ends of the central opening. The dielectric layer can include a tongue portion, trace portions, and an aperture aligned with the void and defined by the tongue portion and the trace portions. The tongue portion includes a proximate end and a distal end. The trace portions extend from the distal end of the tongue portion. The aperture includes an elongated opening with opposing ends partially aligning with the central opening of the void, and slits extending from the opposing ends of the elongated opening and at least partially exposing the first and second channels of the void.

(14) In some embodiments of the flexure, the slits of the aperture extend from the opposing ends of the elongated opening up to 40% of a length between the proximate end and the distal end of the tongue portion. Specifically, the slits of the aperture extend from the opposing ends of the elongated opening up to 25% of a length between the proximate end and the distal end of the tongue portion. In other embodiments of the flexure, the slits of the aperture extend from the opposing ends of the elongated opening up to 80% of a length between the proximate end and the distal end of the tongue portion. Specifically, the slits of the aperture extend from the opposing ends of the elongated opening up to 50% of a length between the proximate end and the distal end of the tongue portion.

(15) Other features and advantages of embodiments of the present disclosure will be apparent from the accompanying drawings and from the detailed description that follows.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Embodiments of the present disclosure are illustrated by way of example and not limitation in the figures of the accompanying drawings, in which like references indicate similar elements and in which:
- (2) FIG. 1 is an isometric view of a suspension having a flexure, in accordance with an embodiment of the disclosure;
- (3) FIG. 2 is a perspective view of an underside of the suspension, in accordance with an embodiment of the disclosure;
- (4) FIG. 3 illustrates the flexure of the suspension, in accordance with embodiments of the disclosure;
- (5) FIG. 4 illustrates the dielectric layer of the flexure, in accordance with embodiments of the disclosure;
- (6) FIG. 5 illustrates the dielectric layer of the flexure, in accordance with embodiments of the disclosure;
- (7) FIG. 6 illustrates the dielectric layer of the flexure, in accordance with embodiments of the disclosure;
- (8) FIG. 7 illustrates the dielectric layer of the flexure, in accordance with embodiments of the disclosure; and
- (9) FIG. 8 illustrates a flexure **112**, in accordance with embodiments of the disclosure.

## DETAILED DESCRIPTION

(10) A suspension and components thereof are described herein. Such a suspension can included, but is not limited, to a dual-stage actuation (DSA) suspension and a tri-stage actuation suspension. The suspension, according to some embodiments, includes a flexure, which includes a gimbal, a proximal end, and a distal end. The flexure having a longitudinal axis extending from the proximal end to the distal end. The gimbal includes a spring metal layer including a base portion, a tongue, and a pair of spring arms extending from the base portion to the tongue. The gimbal also includes a dielectric layer overlaying the spring metal layer and a conductive metal layer overlying the dielectric layer.

(11) The conductive metal layer includes a first plurality of traces extending from the base portion to the tongue and a second plurality of traces extending from the base portion to the tongue. The suspension also includes a void formed in the spring metal layer and partially surrounding the tongue. A portion of the first plurality of traces and a portion of the second plurality of traces are coupled over the void and extend towards the tongue. A portion of the dielectric layer overlays a section of the void formed in the spring metal layer. The disclosed flexure provides additional stiffness, which improves the mechanical properties of the suspension.

(12) FIG. 1 is an isometric view of a suspension **10** having a flexure **12** with a co-located or gimbal-based actuation structure **14**, in accordance with an embodiment of the disclosure. As shown in FIG. 1, the suspension **10** includes a baseplate **16** as a proximal mounting structure. The suspension **10** also includes a load beam **18** having a rigid or beam region **20** coupled to the baseplate **16** along a spring or hinge region **22**. The load beam **18** can be formed from stainless steel. The flexure **12** includes a gimbal **24** at the distal end of the flexure **12**. A co-located or gimbal-based actuation structure **14** is located on the gimbal **24**, adjacent the distal end of the load beam **18**.

(13) FIG. 2 is a perspective view of an underside of the suspension **10**, in accordance with an embodiment of the disclosure. A head slider **32** is mounted to a tongue **33** of the gimbal **24**, on the side of the suspension **10** that is opposite the load beam **18**. The co-located or gimbal-based actuation structure **14** includes a motor **34**, which is a PZT or other piezoelectric actuator in the illustrated embodiment, mounted to the gimbal **24** of the flexure **12** between the load beam **18** and the head slider **32**. In response to electrical drive signals applied to the motor **34**, the motor drives portions of the gimbal **24**, including the tongue **33** and slider **32**, about a generally transverse tracking axis. Proximal and distal, as used herein, refers to the relative direction along the longitudinal axis of the suspension while lateral refers to the left and/or right directions orthogonal to the longitudinal axis of the suspension. For example, the baseplate **16** is proximal of the load beam **18** while opposite ends of the motor **34** extend laterally.

(14) FIG. 3 illustrates the flexure **12** of the suspension **10**, in accordance with embodiments of the disclosure. The flexure **12** is formed from overlaying spring metal such as stainless-steel layer **40**, polyimide or other dielectric layer **42**, copper or other conductive material layer **44** and coverlay, such as a polyimide layer. It will be understood that the stainless-steel layer **40** could alternatively be formed from another metal or rigid material. The dielectric layer **42** generally electrically isolates structures formed in the conductive material layer **44** from adjacent portions of the stainless-steel layer **40**.

(15) The coverlay generally covers and protects the structures formed in the conductive material layer **44**. The gimbal **24** includes the spring arms **52** and the tongue **33**. The spring arms **52** extend from a base portion **50** of the stainless-steel layer **40**. A mounting region **54**, which is part of the tongue **33**, is supported between the spring arms **52** by a pair of struts **56** that extend from support regions **58**, extending from the spring arms **52**. In some embodiments, the pair of struts **56** is the only part of the stainless-steel layer **40** that connects or otherwise supports the tongue **33** between the spring arms **52**.

(16) Specifically, the struts **56** can be the only structural linkage between the spring arms **52** and

the tongue 33. Also, the struts 56, in connecting with the tongue 33, can be the only part of the stainless-steel layer 40 that connects between the spring arms 52 distal of the base portion 50. As shown, the struts 56 are offset from one another with respect to the longitudinal axis of the flexure 12 or otherwise configured to enable rotational movement of the mounting region 54 about the tracking axis with respect to the spring arms 52. The struts 56 can each be the narrowest part of the stainless-steel layer 40 in, for example, an X-Y plane while the thickness of the stainless-steel layer 40 can be consistent along the flexure 12.

(17) A plurality of traces 60 formed in the conductive material layer 44 extend between the base portion 50 and the tongue 33 along a flexible circuit formed in the dielectric layer 42. A number of the traces 60 terminate at locations on a distal region on the tongue 33 and are configured to be electrically attached to terminals of the read/write head on the slider. Other traces 60 terminate at a contact such as a copper pad 64 on the tongue 33, below the motor 34. Portions of the dielectric layer 42 extend underneath the conductive material layer 44 onto the mounting region 54 and across a portion of the support regions 58. The tongue 33 projects longitudinally toward the base portion 50 and is surrounded on three sides by a void 65 or aperture through the flexure 12.

(18) The tongue 33 projects longitudinally toward the base portion 50 and is surrounded on three sides by a void 65 or aperture through the flexure 12. The void 65 includes a central opening 66, a first channel 69A and a second channel 69B. The first channel 69A can be defined by the spring arm 52, the strut 56, the support region 58 and the mounting region 54. A first portion of the trace 60A formed in the conductive material layer 44 extends from the mounting region 54 over the first channel 69A, where it is suspended from the stainless-steel layer 40. The first portion of the trace 60A is suspended over the void 65 and mounted on the base portion 50.

(19) The second channel 69B can be defined by the spring arm 52, the strut 56, the support region 58 and the mounting region 54. A second portion of the trace 60B formed in the conductive material layer 44 extends from the mounting region 54 over the second channel 69B, where it is suspended from the stainless-steel layer 40. The second portion of the trace 60B is suspended over the void 65 and mounted on the base portion 50.

(20) The dielectric layer 42 has an aperture 70 corresponding with the central opening 66, the first channel 69A, and the second channel 69B. Some embodiments of the dielectric layer are illustrated in further detail with respect to FIGS. 4-7.

(21) FIG. 4 illustrates a dielectric layer 42 of the flexure, in accordance with embodiments of the disclosure. The dielectric layer 42 includes a tongue portion 54A, lower trace portions 60A, upper trace portions 60B, and an aperture 70. The aperture 70 is defined by the tongue portion 54A, the lower trace portions 60A, and the upper trace portions 60B. The upper trace portions 60B extend from the tongue portion 54A. The tongue portion 54A can include a proximate end 54B and a distal end 54C. The aperture 70 of the dielectric layer 42 includes an elongated opening 71 with opposing ends. The elongated opening 71 is defined by the lower trace portions 60A and the proximate end 54B of the tongue portion 54A. The aperture 70 also includes slits 72 extending from the opposing ends of the elongated opening 71. The slits 72 are defined by the tongue portion 54A and the upper trace portions 60B. The elongated opening 71 at least partially aligns with the central opening of the void (65 shown in FIG. 3), and the slits 72 at least partially expose the first and second channels (69A, 69B of the void 65 shown in FIG. 3). The slits 72 extend a full-length 73 between the proximate end 54B of the tongue portion 54A and the upper trace portions 60B that extend from the tongue portion 54A. For some embodiments, the full length 73 is in a range including 0.6 millimeters (mm) to 0.9 mm. According to some embodiments, the upper trace portions 60B is defined by the width of the plurality of traces 60 in the conductive material layer and configured to be disposed on the dielectric layer 42. The width of the upper trace portions 60B, according to some embodiments, is in a range including 0.2 mm to 0.25 mm. For some embodiments, the illustrated dielectric layer 42 is formed separately from the suspension 10 and applied to the suspension 10.

(22) FIG. 5 illustrates a dielectric layer 42A of the flexure, in accordance with embodiments of the disclosure. As discussed above, the dielectric layer 42A includes a tongue portion 54A, lower trace portions 60A, upper trace portions 60B, and an aperture 70. The aperture 70 is defined by the tongue portion 54A, the lower trace portions 60A, and the upper trace portions 60B. The upper trace portions 60B extend from the distal end 54C of the tongue portion 54A. The elongated opening 71 is defined by the lower trace portions 60A and the proximate end 54B of the tongue portion 54A. The slits 72 are defined by the tongue portion 54A and the upper trace portions 60B, reduced by a reduction length 74. The slits 72 extend less than the full-length 73, described above, by the reduction length 74. For some embodiments, the reduction length 74 is the distance from the distal end of the slits 72 to a proximal end of the plurality of traces 60 in the conductive material layer that are disposed on or will be disposed on the upper trace portion 60B of the dielectric layer 42A. The reduction 74 is between 1 and 40 percent reduction of the full-length 73. Specifically, the reduction length is 25% of the slit 72 length between the proximate end 54B of the tongue portion 54A towards the distal end 54C of the tongue portion 54A. The reduction of the slit 72 increases the size of the dielectric layer 42A, by increasing dielectric material at the upper trace portions 60B.

(23) FIG. 6 illustrates a dielectric layer 42B of the flexure, in accordance with embodiments of the disclosure. The dielectric layer 42B includes a tongue portion 54A, lower trace portions 60A, upper trace portions 60B, and an aperture 70. The aperture 70 is defined by the tongue portion 54A, the lower trace portions 60A, and the upper trace portions 60B. The upper trace portions 60B extend from the distal end 54C of the tongue portion 54A. The elongated opening 71 is defined by the lower trace portions 60A and the proximate end 54B of the tongue portion 54A. The slits 72 are defined by the tongue portion 54A and the upper trace portions 60B, reduced by a reduction length 75. The slits 72 extend less than the full-length 73, described above, by the reduction length 75. For some embodiments, the reduction length 75 is the distance from the distal end of the slits 72 to a proximal end of the plurality of traces 60 in the conductive material layer that are disposed on or will be disposed on the upper trace portion 60B of the dielectric layer 42B. The reduction length 75 is between 41 and 99 percent length reduction of the full-length 73. Specifically, the reduction length is 50% of the slit 72 length between the proximate end 54B of the tongue portion 54A towards the distal end 54C of the tongue portion 54A. The reduction of the slit 72 increases the size of the dielectric layer 42B, by increasing dielectric material at the upper trace portions 60B.

(24) FIG. 7 illustrates a dielectric layer 42C of the flexure, in accordance with embodiments of the disclosure. The dielectric layer 42C includes a tongue portion 54A, lower trace portions 60A, and an aperture 70. The aperture 70 is defined by the tongue portion 54A and the lower trace portions 60A. The aperture 70 does not include slits extending from the opposing ends of the elongated opening 71 towards the upper trace portions 60B. Instead, the tongue portion 54A is extended in width to include and couple with the trace portions 60A. There may be a full fill-in of polyimide in place of the previous slits. The full fill-in of polyimide further increases the size of the dielectric layer 42C. Referring momentarily back to FIG. 3, the increased dielectric layer 42C provides even more coverage on the mounting 54 and across a larger portion of the support regions 58, in comparison to the dielectric layer 42B (described above).

(25) The dielectric layer 42C, such as the embodiment illustrated in FIG. 7, incorporates the full fill-in. This configuration has a very low to non-existent trace mode frequency. A suspension incorporating the dielectric layer 42, with the slits 72 that extend the full-length 73, such as the embodiment illustrated in FIG. 4 also exemplifies very low to non-existent trace mode frequency. The suspension incorporating the partial fill-in configurations of the dielectric layers 42A and 42B, such as embodiments illustrated in FIG. 5 and FIG. 6, respectively, exhibited increased trace mode frequency, increased gimbal pitch and roll stiffness ( $K_p$ ,  $K_r$ ), and a decreased T1-FX phase range from that of a suspension including slits that extend the full-length. The term “z-height” or Z-ht as used herein refers to the distance from the baseplate flange to the data disk surface. As the

polyimide material increases to 50% (dielectric layer **42B**), the trace mode frequency increases from that of a suspension including slits that extend the full-length.

(26) A suspension incorporating a reduced slit exhibited an increased stroke, increase in gimbal pitch, and an increase in roll stiffness over an embodiment with a full-length slit. The increased material, and subsequent reduction of the slit increases the rigidity of the suspension, particularly where the suspension is laterally bent.

(27) The increased rigidity of the suspension in the direction in which it is laterally bent causes a resonance peak **P** to appear at a relatively high frequency. For example, the suspension incorporating the dielectric layer without a polyimide slit exhibits little to no trace mode resonance. The trace mode resonance appears at a higher frequency as the slits in the dielectric layer are decreased. For example, the trace mode resonance of the suspension incorporating the dielectric layer **42** is 8.3 kHz. In comparison, the trace mode of the suspension incorporating the dielectric layer **42B** is 11.9 kHz. As the slits in the dielectric layer are decreased the T1-FX phase range is reduced. However, as the slit is reduced by 25%(25% fill) the T1-FX phase range increased seemingly due to less separation of frequency of trace mode and T1-FX mode.

(28) FIG. **8** illustrates a flexure **112**, in accordance with embodiments of the disclosure. The flexure **112** includes a plurality of traces **60** formed in the conductive material layer **44**. The traces **60** extend between the base portion **50** and the tongue **33** along a flexible circuit formed in the dielectric layer **42**. As indicated above, the tongue **33** projects longitudinally toward the base portion **50** and is surrounded on three sides by a void **65** or aperture through the flexure. As the traces **60** extend from the base portion **50**, a first plurality **62** of the traces **60** converge towards a second plurality **63** of the traces **60** over the void **65**. The first plurality **62** and the second plurality **63** of the traces **60** may be coupled via bridge **61**. The bridge **61** includes a portion of the conductive material layer **44**, supported by a portion of the dielectric layer **42**.

(29) Embodiments of the suspension that incorporated the bridge **61** exhibited a trace mode frequency shift. The suspension that incorporated the bridge **61** also exhibited a yaw frequency increase over those without a bridge. The suspension that incorporated the bridge **61** also exhibited a stroke increase and an increase of roll stiffness ( $K_r$ ) over those without a bridge. A suspension incorporating the bridge **61** coupling the first and second plurality (**62**, **63**) of traces **60** exhibited an increase in the stroke, and an increase in roll stiffness.

(30) The increased rigidity of the suspension in the direction in which it is laterally bent causes a resonance peak **P** to appear at a relatively high frequency. For example, the suspension incorporating the bridge **61** coupling the first plurality **62** of traces **60** and the second plurality **63** of traces **60** exhibit a yaw frequency increase over a suspension without a bridge.

(31) While various embodiments have been described above, it should be understood that they have been presented by way of example and not limitation. It will be apparent to persons skilled in the relevant art(s) that various changes in form and detail can be made therein without departing from the spirit and scope. For example, the bridge **61** configuration and the dielectric layers **42A-42C** were discussed separately; however, it should be appreciated that the bridge configuration **61** can be implemented in either dielectric layers **42A-42C**. Thus, embodiments include a bridge and split used independently or together to tune a suspension to have characteristics for a desired performance.

(32) In fact, after reading the above description, it will be apparent to one skilled in the relevant art(s) how to implement alternative embodiments. For example, other steps may be provided, or steps may be eliminated, from the described flows, and other components may be added to, or removed from, the described systems. Accordingly, other implementations are within the scope of the following claims.

(33) In addition, it should be understood that any figures which highlight the functionality and advantages are presented for example purposes only. The disclosed methodology and system are each sufficiently flexible and configurable such that they may be utilized in ways other than that

shown.

(34) Although the term “at least one” may often be used in the specification, claims and drawings, the terms “a”, “an”, “the”, “said”, etc. also signify “at least one” or “the at least one” in the specification, claims and drawings.

(35) Finally, it is the applicant's intent that only claims that include the express language “means for” or “step for” be interpreted under 35 U.S.C. 112(f). Claims that do not expressly include the phrase “means for” or “step for” are not to be interpreted under 35 U.S.C. 112(f).

## Claims

1. A suspension comprising: a flexure including a gimbal, a proximal end, and a distal end, the gimbal including a spring metal layer having a base portion, a tongue, and a pair of spring arms, a dielectric layer overlaying the spring metal layer, and a conductive metal layer including a first plurality of traces and a second plurality of traces extending from the base portion to the tongue; a void formed in the spring metal layer between the tongue and the base portion and partially surrounding the tongue, wherein an aperture is formed in the dielectric layer with the aperture defined by a tongue portion and trace portions of the dielectric layer, the aperture includes an elongated opening with opposing ends partially aligning with an opening of the void, a first slit and a second slit extending from the opposing ends of the elongated opening toward the tongue, wherein the slits extend toward the tongue at less than a full-length position that extends to the first plurality of traces and the second plurality of traces.
2. The suspension of claim 1, wherein the slits extend about half way between the elongated opening and the full-length position to the first plurality of traces and the second plurality of traces.
3. The suspension of claim 1, wherein the slits extend less than half way between the elongated opening and the full-length position to the first plurality of traces and the second plurality of traces.
4. The suspension of claim 1, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 40% of a length between a proximate end and a distal end of the tongue portion.
5. The suspension of claim 1, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 25% of a length between a proximate end and a distal end of the tongue portion.
6. The suspension of claim 1, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 80% of a length between a proximate end and a distal end of the tongue portion.
7. The suspension of claim 1, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 50% of a length between a proximate end and a distal end of the tongue portion.
8. A dielectric layer configured to overlay a spring metal layer in a suspension assembly, the dielectric layer part of a flexure including a gimbal, a proximal end, and a distal end, the dielectric layer comprising: a tongue portion including a proximate end and a distal end; trace portions extending from the distal end of the tongue portion, the trace portions comprising a first plurality of traces and a second plurality of traces; and an aperture configured to be aligned with a void of the spring metal layer, the aperture includes an elongated opening with opposing ends and at least a first slit and second slit each extending less than a full-length from the aperture to the trace portions, the void formed in the spring metal layer between the tongue portion and a base portion and partially surrounding the tongue portion.
9. The dielectric layer of claim 8, wherein the first slit and the second slit extend from the opposing ends of the elongated opening and are at least partially aligned with channels of the void of the spring metal layer.
10. The dielectric layer of claim 9, wherein the first slit and the second slit of the aperture extend

from the opposing ends of the elongated opening up to 40% of a length between the proximate end and the distal end of the tongue portion.

11. The dielectric layer of claim 9, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 25% of a length between the proximate end and the distal end of the tongue portion.

12. The dielectric layer of claim 9, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 80% of a length between the proximate end and the distal end of the tongue portion.

13. The dielectric layer of claim 9, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 50% of a length between the proximate end and the distal end of the tongue portion.

14. The dielectric layer of claim 9, wherein a portion of the trace portions is configured to couple over the void of the spring metal layer.

15. A flexure comprising: a gimbal, a proximal end, and a distal end, the gimbal includes a spring metal layer including a base portion, a tongue, and a pair of spring arms extending from the base portion to the tongue, a dielectric layer overlaying the spring metal layer and a conductive metal layer overlying the dielectric layer, the conductive metal layer including a first plurality of traces and a second plurality of traces extending from the base portion to the tongue; a void formed in the spring metal layer between the tongue and the base portion and partially surrounding the tongue, wherein an aperture is formed in the dielectric layer the aperture aligned with the void and defined by a tongue portion and trace portions of the dielectric layer, the aperture includes an elongated opening with opposing ends partially aligning with the central opening of the void, and a first slit and a second slit extending from the opposing ends of the elongated opening, wherein the slits extend toward the tongue at less than a full-length position that extends to the first plurality of traces and the second plurality of traces.

16. The flexure of claim 15, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 40% of a length between a proximate end and a distal end of the tongue portion.

17. The flexure of claim 15, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 25% of a length between a proximate end and a distal end of the tongue portion.

18. The flexure of claim 15, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 80% of a length between a proximate end and a distal end of the tongue portion.

19. The flexure of claim 15, wherein the first slit and the second slit of the aperture extend from the opposing ends of the elongated opening up to 50% of a length between a proximate end and a distal end of the tongue portion.

---