

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Design Patent

D1092791

Kind Code

S

Date of Patent

September 09, 2025

Inventor(s)

Joy; Brian

### Safety post

**Inventors:** Joy; Brian (Bensenville, IL)

**Applicant:** FRANK P. FREY AND COMPANY (Bensenville, IL)

**(\*\*) Term:** 15 Years      **Appl. No.:**

D/863933

**Filed:**

December 23, 2022

### Publication Classification

**LOC Cl.:** 2501

**U.S. Cl.:**

USPC      D25/133

### Field of Classification Search

**CPC:** A63B (9/00); A63B (21/1681); A63B (2210/50); A63B (2244/225); A47B (61/003); A47B (96/1483); A47B (96/1425); A47F (5/10); A47G (25/0692); A47K (3/38); B60P (7/15); B61D (45/00); B65G (69/30); B65G (69/2811); B65G (69/2876); B66F (3/00); B66F (3/247); B66F (3/24); E04B (2/821); E04B (2/7435); E04B (2/7845); E04B (2/7455); E04B (9/18); E04B (2002/7494); E04B (2002/7492); E04B (2009/186); E04C (3/005); E04C (3/32); E04F (11/1865); E04F (11/181); E04F (21/00); E04F (21/1833); E04G (3/26); E04G (3/265); E04G (5/14); E04G (5/045); E04G (5/142); E04G (5/041); E04G (5/145); E04G (5/043); E04G (7/28); E04G (11/486); E04G (11/483); E04G (11/38); E04G (11/48); E04G (13/062); E04G (21/3233); E04G (21/32); E04G (21/243); E04G (21/24); E04G (21/30); E04G (21/3261); E04G (21/3214); E04G (21/3223); E04G (21/3276); E04G (21/3295); E04G (21/26); E04G (21/3242); E04G (21/3219); E04G (21/3204); E04G (21/328); E04G (21/3238); E04G (23/0218); E04G (23/0237); E04G (25/065); E04G (25/06); E04G (25/061); E04G (25/063); E04G (25/04); E04G (25/00); E04G (25/08); E04G (2005/148); E04G (2025/042); E04G (2025/045); E04G (2025/047); E04H (12/2215); E04H (17/20); E04H (17/009); E04H (17/1413); E04H (17/22); E04H (17/1465); E04H (17/146); E21D (15/18); E21D (15/40); E21D

(15/325); E21D (15/22); E21D (15/38); E21D (15/42); E21D (15/55); E21D (15/24); E21D (15/52); E21D (15/502); E21D (15/566); F16B (2/246); F16B (12/02); F16B (7/105); F16B (7/1463); F16B (7/149); F16B (7/14); F16B (7/16); F16M (11/28); F16M (11/046); F16M (13/02)

**USPC:** D25/38; D25/38.1; D25/119; D25/123-136; D25/61; D25/157; D25/39; D25/42; D25/43; D25/48; D25/35; D25/11; D25/46; D25/31; D25/143; D25/68; D34/31; D14/253; D14/238; D16/243; D16/244; D8/388; D8/380; D8/381; D8/382; D8/400; D8/402; D8/409; D8/355; D8/356; D8/363; D8/374; D8/354; D8/394-396; D8/383; D8/74; D8/349; D8/371; D8/70; D8/72; D8/377; D8/398; D8/43; D8/73; D8/16; D8/19; D8/350; D8/353; D8/364; D8/366; D8/373; D8/499; D8/376; D12/55; D12/182; D12/183; D12/223; D12/162; D12/414; D11/183; D11/182; D21/840; D21/799; D21/705; D21/699; D21/484; D21/500; D21/504

---

## Description

- (1) FIG. 1 is a perspective view of a safety post of the present invention, according to some embodiments.
- (2) FIG. 2 is a front elevation view thereof.
- (3) FIG. 3 is a rear elevation view thereof.
- (4) FIG. 4 is a left-side elevation view thereof.
- (5) FIG. 5 is a right-side elevation view thereof.
- (6) FIG. 6 is a top plan view thereof; and,
- (7) FIG. 7 is a bottom plan view thereof.
- (8) Broken lines form no part of the claim.
- (9) Shading forms no part of the claim.

## Claims

The ornamental design for a safety post as shown and described.

---