

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396508
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Molina; Domingo Llanos

Suspension assembly and method of manufacture

Abstract

Methods, assemblies, and/or the like are provided. In accordance with various embodiments of the present disclosure there is provided a suspension assembly including a suspension frame having a lower band including one or more band holes configured to provide ventilation to a wearer of the suspension frame; and an upper band having one or more slots; and a pad overmolded onto the suspension frame, wherein the pad has one or more pad holes, wherein the one or more pad holes are configured to be aligned with the one or more slots such that the one or more pad holes are configured to provide ventilation to the wearer of the suspension frame. In some embodiments, the pad is overmolded onto the upper band of the suspension frame. In some embodiments, the suspension frame is a single piece including the lower band and the upper band.

Inventors:	Molina; Domingo Llanos (Mexico City, MX)
Applicant:	Honeywell Safety Products USA, Inc. (Charlotte, NC)
Family ID:	1000008778380
Appl. No.:	18/319924
Filed:	May 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240381967 A1	Nov. 21, 2024

Publication Classification

Int. Cl.: A42B3/14 (20060101); A42B3/12 (20060101); B29C45/00 (20060101); B29L31/48 (20060101)

U.S. Cl.:

CPC **A42B3/14** (20130101); **A42B3/125** (20130101); **B29C45/0001** (20130101);
B29K2995/0068 (20130101); B29L2031/4821 (20130101)

Field of Classification Search

CPC: A42B (3/14); A42B (3/142); A42B (3/145); A42B (3/147); A42B (3/08); A42B (3/085);
A42B (3/324); A42B (3/125)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3354468	12/1966	Bowers, Jr.	2/421	A42B 3/142
3430260	12/1968	Stropkay	2/416	A42B 3/14
5121508	12/1991	Grilliot	2/5	A42B 3/08
5608917	12/1996	Landis et al.	N/A	N/A
7213271	12/2006	Bielefeld	N/A	N/A
10549502	12/2019	Berrang	N/A	N/A
2005/0138719	12/2004	Huh	N/A	N/A
2006/0048285	12/2005	Bielefeld et al.	N/A	N/A
2015/0000370	12/2014	Crossman et al.	N/A	N/A
2015/0059057	12/2014	Pfanner et al.	N/A	N/A
2016/0016342	12/2015	Al-Dahhan et al.	N/A	N/A
2016/0262484	12/2015	Huh	N/A	N/A
2017/0150770	12/2016	Huh	N/A	A42B 3/085
2017/0245577	12/2016	Zhang et al.	N/A	N/A
2020/0390182	12/2019	Huh	N/A	A42B 3/142
2022/0210560	12/2021	Lin et al.	N/A	N/A

OTHER PUBLICATIONS

F & F Industrial, “MSA 454231 Skullgard Cap or Hat Replacement Suspension, Staz-On”,
retrieved from the Internet at URL: <<https://fandfind.com/product/msa-454231-skullgard-cap-or-hat-replacement-suspension-staz-on/>> on Nov. 6, 2013, 1 page. cited by applicant
Extended European Search Report Mailed on Oct. 18, 2024 for EP Application No. 24173655, 8
page(s). cited by applicant

Primary Examiner: Huynh; Khoa D

Assistant Examiner: Lopez; Erick I

Attorney, Agent or Firm: Fredrikson & Byron, P.A.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to suspension assemblies. In particular, it relates to suspension assemblies with an overmolded pad for use with hard hats of helmets.

BACKGROUND

(2) Suspension assemblies may be inserted or otherwise attached to the inside of hard hats and helmets to create a better and more comfortable fit when worn by a user. Suspension assemblies often require multiple parts, including the frame itself and a pad or other “soft” material to make the assembly comfortable for the user and wearable for longer periods of time. The requirement of multiple parts leads to more expensive design and development, though, for suspension assemblies.

(3) Through applied effort, ingenuity, and innovation, Applicant has solved problems relating to suspension assemblies by developing solutions embodied in the present disclosure, which are described in detail below.

SUMMARY

- (4) In general, embodiments of the present disclosure provide assemblies, methods of manufacture, and/or the like.
- (5) In accordance with various embodiments of the present disclosure there is provided a suspension assembly including a suspension frame having a lower band including one or more band holes configured to provide ventilation to a wearer of the suspension frame; and an upper band having one or more slots; and a pad overmolded onto the suspension frame, wherein the pad has one or more pad holes, wherein the one or more pad holes are configured to be aligned with the one or more slots such that the one or more pad holes are configured to provide ventilation to the wearer of the suspension frame.
- (6) In some embodiments, the pad is overmolded onto the upper band of the suspension frame.
- (7) In some embodiments, the suspension frame is a single piece including the lower band and the upper band.
- (8) In some embodiments, the suspension frame includes one or more flanges having one or more flange connection slots, wherein the one or more flange connection slots are configured to receive one or more fasteners to attach the suspension assembly to a helmet.
- (9) In some embodiments, the suspension frame is composed of high-density polyethylene or polyamide 6.
- (10) In some embodiments, the pad is a sweatband having moisture-wicking properties and composed of a thermoplastic elastomer (TPE), thermoplastic vulcanizates (TPV), or Thermoplastic Poly Urethane (TPU).
- (11) In some embodiments, the suspension assembly includes a helmet fixedly attached to the suspension frame.
- (12) In some embodiments, the helmet is a hardhat.
- (13) According to various embodiments, there is provided a method of manufacturing a suspension assembly, the method including injecting, by a first injection unit, a first material onto a mold defining a suspension frame, wherein the suspension frame includes: a lower band having one or more band holes configured to provide ventilation to a wearer of the suspension frame; and an upper band including one or more slots; rotating the mold; and injecting, by a second injection unit, a second material onto the suspension frame such that the second material forms a pad overmolded on the suspension frame.
- (14) In some embodiments, the pad is overmolded onto the upper band of the suspension frame.
- (15) In some embodiments, the suspension frame is a single piece having the lower band and the upper band.
- (16) In some embodiments, the suspension frame includes one or more flanges having one or more flange connection slots, wherein the one or more flange connection slots are configured to receive one or more fasteners to attach the suspension assembly to a helmet.
- (17) In some embodiments, the first material is composed of high-density polyethylene or polyamide 6.
- (18) In some embodiments, the pad is a sweatband having moisture-wicking properties.
- (19) In some embodiments, the second material is composed of thermoplastic elastomer (TPE),

thermoplastic vulcanizates (TPV), or Thermoplastic Poly Urethane (TPU).

(20) The above summary is provided merely for purposes of summarizing some example embodiments to provide a basic understanding of some embodiments of the disclosure.

Accordingly, it will be appreciated that the above-described embodiments are merely examples. It will be appreciated that the scope of the disclosure encompasses many potential embodiments in addition to those here summarized, some of which will be further described below.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

(1) Having thus described the disclosure in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

(2) FIG. 1 is an isometric view of an example suspension frame in accordance with various embodiments of the present disclosure;

(3) FIG. 2A is an isometric view of an example suspension frame with an overmolded pad in accordance with various embodiments of the present disclosure;

(4) FIG. 2B is an isometric view of an example suspension frame with overmolded pad in accordance with various embodiments of the present disclosure;

(5) FIG. 3 is a cross-sectional view of an example injection overmolding process in accordance with various embodiments of the present disclosure;

(6) FIG. 4A is a front isometric view of an example suspension assembly in accordance with various embodiments of the present disclosure;

(7) FIG. 4B is a rear isometric view of an example suspension assembly in accordance with various embodiments of the present disclosure;

(8) FIG. 5A is a detail view of an example suspension assembly in accordance with various embodiments of the present disclosure;

(9) FIG. 5B is a detail view of an example suspension assembly in accordance with various embodiments of the present disclosure; and

(10) FIG. 6 is a flow chart illustrating an example method of manufacturing an example suspension assembly in accordance with various embodiments of the present disclosure.

DETAILED DESCRIPTION OF SOME EXAMPLE EMBODIMENTS

(11) Various embodiments of the present disclosure now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the disclosure are shown. Indeed, this disclosure may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. The term “or” (also designated as “/”) is used herein in both the alternative and conjunctive sense, unless otherwise indicated. The terms “illustrative” and “exemplary” are used to be examples with no indication of quality level. Like numbers may refer to like elements throughout. The phrases “in one embodiment,” “according to one embodiment,” and/or the like generally mean that the particular feature, structure, or characteristic following the phrase may be included in at least one embodiment of the present disclosure and may be included in more than one embodiment of the present disclosure (importantly, such phrases do not necessarily may refer to the same embodiment).

Overview

(12) According to various embodiments, a suspension assembly includes a suspension frame and a pad. In some embodiments, the pad is a sweatband with dry fit properties. In some embodiments, the pad has holes and is composed In some embodiments, the pad is overmolded onto the suspension frame using a one step, “two shot” injection molding process. In some embodiments,

the suspension assembly may be configured to be inserted into or otherwise attached to a helmet or hardhat worn by an individual.

Example Suspension Assemblies

(13) FIG. 1 shows an isometric view of an example suspension frame **100**. In some embodiments, the suspension frame **100** may be a single piece frame configured to be fit around the head of an individual. In some embodiments, the suspension frame **100** may be a single piece when the suspension frame is coupled to a pin lock. In some embodiments, the suspension frame **100** may be multiple pieces when the suspension frame is coupled to a ratchet. In some embodiments, the suspension frame **100** may be configured to be fit inside (or otherwise attached to) a helmet or hard hat. In some embodiments, the suspension frame **100** may have a pad (e.g., a sweatband) **200** overmolded onto the suspension frame **100** to form a suspension assembly **400**, as will be describe later in this disclosure.

(14) In some embodiments, the suspension frame **100** may include a lower band **102** and an upper band **104**. In some embodiments, the lower band **102** and upper band **104** may be substantially semi-circular bands that form a substantially circular or oval-shaped frame. In some embodiments, the lower and upper bands **102**, **104** may be integrated portions of the suspension frame **100**, forming a single piece. In some embodiments, the front and upper bands **102**, **104** may be configured to conform ergonomically around an individual's head while allowing for breathability and ventilation (e.g., for sweat). In some embodiments, the lower band **102** may be coupled to a ratchet or pin lock.

(15) In some embodiments, the suspension frame **100** may be formed via injection molding. In some embodiments, the suspension frame **100** may be composed substantially of metal, plastic, composites, or some combination of these materials. In some embodiments, the suspension frame **100** may be composed of high-density polyethylene (HDPE) or polyamide 6 (PA6).

(16) In some embodiments, the lower band **102** may include a pair of parallel sloping portions **106A**, **106B**, which may slope “downward” relative to the upper band **104** such that the lower band **102** is in a “lower” plane than the upper band **104**. In some embodiments, the lower band **102** may be configured to fit around front or back of an individual's head when worn. In some embodiments, the lower band **102** may define one or more band holes **108A-D**. In some embodiments, the one or more band holes **108A-E** may be ventilation holes for a wearer of the suspension frame **100** (e.g., for sweat). In some embodiments, the one or more band holes **108A-E** may be substantially hexagonal, or a similar polygonal shape.

(17) In some embodiments, the upper band **104** may include one or more slots **110A-D**. In some embodiments, the one or more slots **110A-E** may be substantially rectangular shaped and curved to conform to the shape of the upper band **104**. In some embodiments, the upper band **104** may be in a “higher” plane than the lower band **102**. In some embodiments, the upper band **104** may be configured to fit around the front or the back of an individual's head when worn.

(18) In some embodiments, the suspension frame **100** may include one or more flanges **112A-B**. In some embodiments, the one or more flanges **112A-D** may be four parallel flanges **112A-D** disposed on opposed sides of the suspension frame **100**. In some embodiments, the one or more flanges **112A-D** may be integrated into the lower band **102** or upper band **104** of the suspension frame **100**, forming a single piece. In some embodiments, the one or more flanges **112A-D** may be disposed on the suspension frame **100** at the point where the lower band **102** meets the upper band **104**. In some embodiments, the one or more flanges **112A-D** may include one or more flange connection slots **114A-D**. In some embodiments, the one or more flanges **112A-B** and the one or more flange connection slots **114A-D** may be configured to attach the suspension frame **100** to a helmet or hard hat, as previously alluded to. In some embodiments, the one or more flange connection slots **114A-D** may be configured to receive one or more fastening devices or ribbons to attach the suspension frame **100** to a helmet or hardhat.

(19) FIG. 2A shows an isometric view of an example suspension frame **100** and a pad **200** in the

process of being overmolded onto the suspension frame **100**. FIG. 2B shows an isometric view of the suspension frame **100** and the pad **200** after the pad **200** has been overmolded onto the suspension frame **100**. In some embodiments, the pad **200** may be overmolded onto the upper band **104** of the suspension frame **100**. In some embodiments, the pad **200** may be overmolded onto the lower band **102** or both bands, as desired. In some embodiments, and as shown in at least FIG. 2B, the pad **200** may be overmolded to cover the one or more slots **110A-D** of the upper band **104**. In some embodiments, the pad **200** may be a sweatband with dry fit properties. In some embodiments, the pad **200** may be composed of a thermoplastic elastomer (TPE), thermoplastic vulcanizates (TPV), poly urethane (TPU), or a combination thereof. In some embodiments, the pad **200** may have a hardness ranging between 30 and 50 shore A. In some embodiments, the pad **200** may be overmolded onto the suspension frame **100** in a one step, “two shot” injection overmolding process.

(20) An example of an overmolding process **300** can be seen in at least FIG. 3, according to various embodiments. In some embodiments, the overmolding process **300** may be a one step, “two shot” injection overmolding process. In some embodiments, a first material **302** (e.g., a material of the suspension frame **100**) may be injected onto a mold **304**. In some embodiments, the first material **302** may be inserted via a first material injection unit **305**. In some embodiments, the mold **304** may then be rotated and a second material **306** (e.g., a material of the pad **200**) may be injected onto the first material **302**. In some embodiments, the second material **306** may be inserted via a second material injection unit **307**.

(21) FIGS. 4A and 4B show a front and rear isometric view of an example suspension assembly **400**. In some embodiments, the pad **200** of the suspension assembly may include a plurality of pad holes **202**. In some embodiments, the pad holes **202** may be created during the one step, “two shot” injection overmolding process, or the pad holes **202** may be created after the molding process. In some embodiments, the plurality of pad holes **202** may be arranged such that they are disposed over top of the slots **110A-D** of the upper band **104**. In some embodiments, the pad **200** may cover each slot **110A-D** on the upper band **104**. In some embodiments, the “hard” material of the upper band **104** may provide mechanical support to the suspension frame **100** (e.g., to hold a helmet or hard hat) while the “soft” material of the pad **200** may provide comfort to a user and allow sweat and other excretions from the user to exit the suspension assembly **400**.

(22) FIGS. 5A and 5B show detailed views of the suspension assembly **400**. In particular the detailed views of FIGS. 5A and 5B show “dry fit” properties of the pad **200** and the pad holes **202**. In some embodiments, and as shown in at least FIG. 5B, the material formulation and/or surface finishing of the pad **200** and/or the pad holes **202** may be configured to provide moisture-wicking properties for the suspension assembly **400** (e.g., removal of sweat **402A**, **402B**). In some embodiments, the pad **200** may be configured to have one or more channels **204A**, **204B** that may be in fluid communication with the pad holes **202**.

Example Methods of Manufacture

(23) FIG. 6 shows a flow chart illustrating an example method **500** for manufacturing a suspension assembly. In some embodiments, the method **500** may be used with respect to the suspension frame **100**, pad **200**, and suspension assembly **400**, and their various components, as previously described. In some embodiments, the method **500** may be used with other suitable systems, assemblies, and components, as desired. In some embodiments, one or more of the steps of the method **500** may be performed sequentially, and in some embodiments one or more of the steps of the method **500** may be performed simultaneously.

(24) In some embodiments, the method **500** may include a first step **502** of injecting, by a first injection unit, a first material onto a mold defining a suspension frame. In some embodiments, the method **500** may include a second step **504** of rotating the mold. In some embodiments, the method **500** may include a third step **506** of injecting, by a second injection unit, a second material onto the suspension frame such that the second material forms a pad overmolded on the suspension frame.

(25) Many modifications and other embodiments of the disclosure set forth herein will come to mind to one skilled in the art to which this disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the disclosure is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

Claims

1. A suspension assembly comprising: a suspension frame comprising: a lower band comprising one or more band holes configured to provide ventilation to a wearer of the suspension frame; and an upper band comprising one or more slots; and a pad overmolded onto the suspension frame, wherein the pad comprises one or more pad holes and one or more channels, wherein the one or more pad holes are configured to be aligned with the one or more slots such that the one or more pad holes are configured to provide ventilation to the wearer of the suspension frame, and wherein the one or more channels are in fluid communication with the one or more pad holes and the one or more pad holes are configured to provide moisture-wicking properties.
 2. The suspension assembly of claim 1, wherein the pad is overmolded onto the upper band of the suspension frame.
 3. The suspension assembly of claim 1, wherein the suspension frame is a single piece comprising the lower band and the upper band.
 4. The suspension assembly of claim 1, wherein the suspension frame comprises one or more flanges comprising one or more flange connection slots, wherein the one or more flange connection slots are configured to receive one or more fasteners to attach the suspension assembly to a helmet.
 5. The suspension assembly of claim 1, wherein the suspension frame is composed of high-density polyethylene or polyamide 6.
 6. The suspension assembly of claim 1, wherein the pad is a sweatband having moisture-wicking properties and composed of a thermoplastic elastomer (TPE), thermoplastic vulcanizates (TPV), or Thermoplastic Poly Urethane (TPU).
-