

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396872
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Poulsen; Andreas et al.

Multipurpose handle

Abstract

A multipurpose handle incorporated into a medical device delivery system. The multipurpose handle includes an elongate handle body, an actuation button, and a locking member. The elongate handle body has a proximal end extending to a distal end, which defines a longitudinal axis. The elongate body further includes a cutout that creates a movement space therein in which the actuation button is disposed and is connected to a medical device. The actuation button is movable within the cutout along the longitudinal axis and rotatable within the cutout. The locking member is connected to the elongate handle body and movable between a locked position and unlocked position. The locking member may be in contact with the actuation button and be configured to restrict the movement of the actuation button along the longitudinal axis when in the locked position.

Inventors: Poulsen; Andreas (Borup, DK), Marcussen; Mikkel (Broenshoej, DK), Klarskov; Lisbeth (Lejre, DK)

Applicant: Cook Medical Technologies LLC (Bloomington, IN)

Family ID: 1000008778408

Assignee: Cook Medical Technologies LLC (Bloomington, IN)

Appl. No.: 18/337733

Filed: June 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240277503 A1	Aug. 22, 2024

Related U.S. Application Data

continuation parent-doc US 16739497 20200110 US 11684501 child-doc US 18337733

Publication Classification

Int. Cl.: **A61F2/962** (20130101); **A61B17/00** (20060101); **A61B17/12** (20060101); **A61F2/01** (20060101); **A61F2/95** (20130101)

U.S. Cl.:

CPC **A61F2/962** (20130101); **A61B17/1214** (20130101); **A61F2/01** (20130101); A61B2017/00389 (20130101); A61B2017/1205 (20130101); A61F2/011 (20200501); A61F2/9517 (20200501); A61F2002/9528 (20130101)

Field of Classification Search

CPC: A61F (2/95); A61F (2/9517); A61F (2/954); A61F (2/958); A61F (2/962); A61F (2002/9528); A61F (2002/9534); A61F (2/01); A61F (2/011); A61F (2/24); A61F (2/2427); A61F (2/243); A61F (2/2433); A61F (2/2436); A61F (2/2439); A61B (17/00389); A61B (17/1214); A61B (17/221); A61B (2017/1205)

USPC: 623/1.11

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4799496	12/1988	Hargreaves	604/95.04	A61M 25/09041
5013300	12/1990	Williams	433/91	A61M 1/86
5066295	12/1990	Kozak	606/47	A61B 18/14
5613973	12/1996	Jackson	606/1	A61B 17/221
11684501	12/2022	Poulsen	623/1.11	A61F 2/00
2012/0123528	12/2011	Knippel	623/2.11	A61F 2/2436
2015/0335452	12/2014	Rao	623/23.66	A61F 2/966
2019/0029706	12/2018	Piraka	N/A	A61B 17/32

Primary Examiner: Rwego; Kankindi

Attorney, Agent or Firm: Woodard, Emhardt, Henry, Reeves & Wagner, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of Ser. No. 16/739,497, filed Jan. 10, 2020, now pending, which claims the benefit of priority of U.S. Provisional Application No. 62/791,948 filed Jan. 14, 2019, the entire contents of which are hereby incorporated herein by reference.

FIELD

(1) The disclosure relates generally to a medical device delivery system. More specifically, this disclosure relates to a multipurpose handle for use in a medical device delivery system that is

configured to control relative movements associated therewith, as well as a method of using the handle.

BACKGROUND

(2) The statements in this section merely provide background information related to the present disclosure and may not constitute prior art.

(3) In many medical procedures, an implant is inserted into a patient's body for treatment. For example, a vena cava filter may be deployed within a patient's vasculature in order to prevent a pulmonary embolism. In order to successfully deploy and retrieve the implant, the user (e.g., physician) needs to be able to control relative motion of various structures of a delivery and retrieval system. Many known systems require two-handed operation. However, such operation can be difficult for the user to move multiple structures in different directions while performing other functions, such as monitoring conditions at the surgery site in order to ensure patient safety.

(4) Conventional medical device delivery systems generally operate by moving the medical device within a catheter positioned in the body of a patient along a desired vascular path or other body passageway, until the medical device reaches a desired treatment site. The deployment operation requires some measure of skill by the user because he/she must monitor the relative position of the medical device and other components within the delivery system, as well as utilize both of his/her hands to operate the delivery system. More specifically, in many conventional systems the user must hold a proximal hub attached to an inner shaft member of the delivery system in a fixed position with one hand, while simultaneously withdrawing the proximal hub attached to the outer tubular sheath with the other hand.

(5) Accurate deployment and positioning of the device is important to ensuring patient safety. Thus, a system that provides accurate control of the movements of the medical device can improve the safety associated therewith. At the same time, it is also desirable to provide an integrated and ergonomic handle for easy and effective operation of the system. A handle that is capable of single-hand operation with a locking mechanism may provide such benefits. Accordingly, improvements can be made to a delivery and retrieval system with a handle configured for multipurpose operation.

SUMMARY

(6) The present disclosure generally provides a medical device delivery system. More specifically, the present disclosure provides a multipurpose handle for use in a medical device delivery system that is configured to control relative movements associated therewith.

(7) The multipurpose handle generally includes an elongate handle body, an actuation button, and a locking member. The elongate handle body has a proximal end extending to a distal end, which defines a longitudinal axis. The elongate body further includes a cutout that defines a movement space therein in which the actuation button is disposed and connected to a medical device. The actuation button is movable within the cutout along the longitudinal axis and rotatable within the cutout. The locking member is connected to the elongate handle body and movable between a locked position and unlocked position. The locking member is in contact with the actuation button in a configuration that restricts the movement of the actuation button along the longitudinal axis when in the locked position.

(8) According to another aspect of the present disclosure, a medical device delivery system is provided. This medical device delivery system comprises an outer sheath; a medical device located at least partially within the outer sheath in an initial configuration ready for deployment; and a multipurpose handle as described above and further defined herein. The multipurpose handle connected to the outer sheath and the medical device.

(9) According to yet another aspect of the present disclosure, the use of a medical device delivery system is described that incorporates a multipurpose handle to deliver or retrieve a medical device from a desired or targeted site within a vasculature of a patient's body. During such use, the multipurpose handle provides the user with control over longitudinal movement together with

scrolling rotation of the attached medical device. The user may utilize his/her thumb and index finger on a single hand to accomplish such longitudinal and rotational movements.

(10) Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

Description

DRAWINGS

- (1) In order that the disclosure may be well understood, there will now be described various forms thereof, given by way of example, reference being made to the accompanying drawings. The components in each of the drawings may not necessarily be drawn to scale, rather emphasis is placed upon illustrating the principles of the invention. Moreover, like referenced numerals in different drawings designate corresponding or similar components or elements.
- (2) FIG. 1 is a perspective view of a medical device delivery system having a multipurpose handle formed according to the teachings of the present disclosure.
- (3) FIG. 2 is a cross-sectional view of the multipurpose handle shown in the delivery system of FIG. 1.
- (4) FIG. 3 is a perspective view of another medical delivery system incorporating a multipurpose handle formed according to the teachings of the present disclosure.
- (5) FIG. 4 is a cross-sectional view of the multipurpose handle of FIG. 3 highlighting the ability for longitudinal and rotational motion.
- (6) FIG. 5 is a perspective view of an actuation button that may be used in the multipurpose handle.
- (7) FIG. 6 is a perspective view of an elongated handle body that may be used in the multipurpose handle.
- (8) FIG. 7 is a perspective view and a cross-sectional view of an elongated handle body that may be used in the multipurpose handle.
- (9) FIGS. 8A and 8B are perspective views of cutouts made in the elongated handle body according to the teachings of the present disclosure.
- (10) FIGS. 9A and 9B are perspective views of a multipurpose handle highlighting the use of a lock ring.
- (11) FIG. 9C is perspective view of the lock ring used in FIG. 9B.
- (12) FIG. 10 is a perspective view of a multipurpose handle with a locking member formed according to the teachings of the present disclosure.
- (13) FIG. 11 is a perspective view of another multipurpose handle with a locking member formed according to the teachings of the present disclosure.
- (14) FIG. 12A is a perspective view of multipurpose handle and an expanded view of a sliding locking button.
- (15) FIG. 12B is perspective view and a cross-sectional view of a multipurpose handle incorporating another locking button according to the teachings of the present disclosure.
- (16) FIG. 12C is a cross-sectional view of a multipurpose handle incorporating another locking button according to the teachings of the present disclosure.
- (17) FIG. 12D is a cross-sectional view of another multipurpose handle incorporating a different locking button according to the teachings of the present disclosure.
- (18) FIG. 12E is a cross-sectional view of a multipurpose handle incorporating an actuation button and locking member with a variable locking position.
- (19) FIGS. 13A and 13B are perspective views of medical device delivery systems that incorporate a multipurpose handle according to the teachings of the present disclosure.
- (20) FIG. 14 is a perspective view of a medical device delivery system that incorporates a

multipurpose handle with an expanded view of a locking button.

(21) FIG. 15 is a cross-sectional view of a medical device delivery system incorporating a multipurpose handle with an expanded view of another locking button.

(22) The drawings described herein are for illustration purposes only and are not intended to limit the scope of the present disclosure in any way.

DETAILED DESCRIPTION

(23) The following description is merely exemplary in nature and is in no way intended to limit the present disclosure or its application or uses. For example, the multipurpose handle made and used according to the teachings contained herein is described throughout the present disclosure in conjunction with deploying or retrieving a vena cava filter treating a pulmonary embolism in order to more fully illustrate the structural elements and the use thereof. The incorporation and use of such a multipurpose handle in other applications, including without limitation the deployment of a stent, is contemplated to be within the scope of the present disclosure. The multipurpose handle may be incorporated in any delivery system that includes an outer sheath that surrounds an inner shaft configured to carry a medical device therein for delivery to a desired target-site in a vasculature within the body. The multipurpose handle may be incorporated into a device of any type or size provided the mandrill size necessary to form the handle does not exceed the dimensions associated with manufacturing the handle to fit inside a human hand. It should be understood that throughout the description, corresponding reference numerals indicate like or corresponding parts and features.

(24) The present disclosure generally provides a medical device delivery system. More specifically, the present disclosure provides a multipurpose handle for use in a medical device delivery system configured to control relative movements associated therewith. As such, the medical device delivery system of the present disclosure is provided with an integrated and ergonomic handle that replaces the functions of separate proximal hubs in conventional systems, while providing a desirable dual mode of operation with a locking function.

(25) The handle design generally comprises a hollow tube with an inner moving part, capable of both sliding and rotating along with a locking member or mechanism that secures the inner part from longitudinal movement in the back-most position. The locking mechanism may have an audible and/or sensible confirmation of lock. The locking member or mechanism is configured to resist inadvertent or accidental movement or retraction of the various components within the medical device delivery system during packaging, sterilization, shipping, storage, handling, and preparation for use. The lock may be spring-loaded, or otherwise easily released as further described herein.

(26) The use of this multipurpose handle allows the user to have control over longitudinal movement together with scrolling rotation of the attached medical device. The medical device delivery system may be utilized in any procedure or other operation where a medical device is required to slide forwards/backwards and/or rotate in order to be successfully deployed. According to another aspect of the present disclosure, the multipurpose handle involves the use of a single actuator for multiple modes of operating the handle and delivery system.

(27) A medical device delivery system that incorporates the multipurpose handle of the present disclosure is capable of providing a variety of benefits and advantages. These benefits include, without limitation, one or more of the following: (i) single-handed operation of the medical device delivery system; (ii) a mechanism that provides leverage or mechanical advantage in adjusting or reducing the forces needed to operate the system; (iii) improved accuracy in positioning the medical device at the target-site; (iv) multiple modes of operation; (v) an integrated and ergonomic handle for operating the system; (vi) a locking mechanism capable of resisting inadvertent or accidental movement or retraction of the delivery system; and (vii) the ability to hold the delivery system components in a fixed relative position during an intermediate stage in the deployment of the medical device.

(28) For the purpose of this disclosure, the term “proximal” refers to a direction that is generally towards an user (e.g., physician) during a medical procedure, while the term “distal” refers to a direction that is generally towards a target site within a patient's anatomy during the medical procedure.

(29) For the purpose of this disclosure, the terms “about” and “substantially” are used herein with respect to measurable values and ranges due to expected variations known to those skilled in the art (e.g., limitations and variability in measurements).

(30) For the purpose of this disclosure, the terms “at least one” and “one or more of” an element are used interchangeably and may have the same meaning. These terms, which refer to the inclusion of a single element or a plurality of the elements, may also be represented by the suffix “(s)” at the end of the element. For example, “at least one metal”, “one or more metals”, and “metal(s)” may be used interchangeably and are intended to have the same meaning.

(31) The focus of the design of the multipurpose handle and the medical device delivery system is to enhance patient safety. In this respect, the multipurpose handle makes use of an ergonomic design and one-handed operation, which places more control on the user (e.g., physician) where conventional products rely on two hands to operate the device. The safety feature is also rooted in a thumb button for both longitudinal and scrolling movement, as well as adding precision to the user, which is not found in conventional products. The multipurpose handle also includes a locking mechanism triggered by the index finger, which ensures the device may be secured without compromising the control. Overall, the user can perform all of the relevant steps required in a medical procedure, while only moving the thumb and index fingers while simultaneously maintaining a firm grip on the delivery system. In comparison to conventional delivery systems, the medical device delivery system of the present disclosure may be manipulated by a user to easily perform all necessary steps with one hand, without having to look away from the typically used radio-imaging screen.

(32) Referring to FIGS. **1-15**, the medical device delivery system **1** includes a multipurpose handle **5** that comprises an elongate handle body **10**, an actuation button **15**, and a locking member **20**. The elongate handle body **10** has a proximal end **25** extending to a distal end **30**, which defines a longitudinal axis (A). The elongate body **10** further includes a cutout **35** that creates a movement space therein. The actuation button **15** is disposed within the cutout **35** and connected to a medical device **40**. The actuation button **15** may be movable within the cutout **35** along the longitudinal axis (A) and rotatable within the cutout **35**. The locking member **20** is connected to the elongate handle body **10** and movable between a locked position and unlocked position. The locking member **20** may be in contact with the actuation button **15** and be configured to restrict the movement of the actuation button **15** along the longitudinal axis (A) when in the locked position.

(33) As shown in FIGS. **1** and **2**, the actuation button **15** may include a sliding portion **15A** to control the longitudinal movement of the medical device **40** and a rotating portion **15B** to control rotational movement associated with the medical device **40**. The sliding portion **15A** and rotating portion **15B** may be manipulated by different fingers of the user's hand. For example, the sliding portion **15A** may be manipulated using the thumb finger, while the index finger of the user manipulates the rotating portion **15B**.

(34) Referring now to FIG. **2**, one or more of the sliding portion **15A** and the rotating portion **15B** of the actuation button **15** may include one or more slits **16** in order to provide for added sliding and/or scrolling control. The actuation button **15** may in communication or contact with a sliding component **45** configured to secure the medical device **40**. For example, this sliding component **45** may be, without limitation, a collet **46** that uses a fastener **46A** or other type of anchor to secure the medical device **40**.

(35) According to another aspect of the present disclosure as shown in FIGS. **3** and **4**, the longitudinal movement and rotational movement associated with the actuation button **15** may be incorporated such that one finger of the user is capable of controlling both the longitudinal and

rotational movement of the medical device by a sliding motion or a scrolling motion, respectively. For example, the actuation button **15** may be a thumb wheel capable of being manipulated solely by the thumb finger of the user (e.g., physician) in order to move the medical device **40** both longitudinally and rotationally through a sheath **50**. When desirable, the actuation button **15** as shown in FIG. **5** may include one or more fins **17** and/or an indented edge **18** configured to fit a thumb finger **3** to provide for additional gripping during rotational and longitudinal movements. When the actuation button **15** is a thumb wheel the fins **17** may be disposed around the circumference of the wheel.

(36) Referring now to FIG. **6**, the elongate handle body **10** may include one or more gripping knurls **55**, alternatively, a plurality of gripping knurls **55** for providing an user with a firm gripping surface. The elongate handle body **10** may represent a singular unified component or include a plurality of components, such as an upper body portion and a lower body portion, that are attached together by gluing, welding, melt bonding, or the like. The dimensions of the elongate handle body **10** may be customized in order to fit a specific predetermined hand size or be optimized such that various hand sizes are capable of obtaining a firm grip when using the multipurpose handle **1**. Additional ergonomic features may be included in the elongate handle body as well without exceeding the scope of the present disclosure.

(37) The multipurpose handle **5** including the elongate handle body **10**, as well as the various parts contained therein may be formed from polymeric or plastic materials, ceramic materials, metals or metal alloys, and/or combinations thereof. The materials for use in the multipurpose handle **5** are selected so that they exhibit desirable or required performance characteristics, such as biocompatibility, flexibility, and strength to name a few. The polymeric or plastic materials may include one or more thermoplastic materials or thermoset materials, individually or in combination. Several examples of suitable polymeric or plastic materials may include but not limited to polyamides (e.g., nylons), polyimides, polyethylenes, polyurethanes, polyethers, polyesters, acrylonitrile butadiene styrene (ABS), and mixtures or copolymers thereof. Alternatively, the elongate handle body **10** is formed from ABS. Any metal parts used within the multipurpose handle **5** may be formed from, without limitation, stainless steel, brass, Nitinol, or a combination thereof. Alternatively, the metal parts are formed from brass.

(38) Referring now to FIGS. **6**, **7**, and **8(A-B)**, the elongate handle body **10** may also include a cutout **35** in the form of a longitudinal slot that defines a channel **65** configured to accommodate the sliding action of the actuation button **15**. This cutout or longitudinal slot **35** is capable of limiting the extent of longitudinal movement within the multipurpose handle **5**. The actuation button **15** or thumb wheel that fits within the cavity **60** of the cutout **35** may include a tactile bump **65**, which can be seen in the cross-section of the actuation button **15** shown in the plane (A) view of FIG. **7**. This tactile bump **65** may assist the user in determining the orientation of the attached medical device **40**. When desirable this longitudinal slot may be in the shape of a droplet **35A** as shown in FIG. **8A**. The droplet shaped cutout **35A** may vary in size provided the actuation button **15** is secured and cannot slip out of the cavity **60** formed by the cutout **35A** (FIG. **8B**).

(39) Referring now to FIGS. **9(A-C)**, the locking mechanism **20** may include a locking ring **20A** configured to be either be in an unlocked position or a locked position. When the locking ring **20A** is unlocked, the actuation button **15** may be moved (FIG. **9A**). However, when the locking ring **20A** is in the locked position, the actuation button **15** is prevented from moving (FIG. **9B**). The locking ring **20A** may include at least one slit **67** that allows one portion of the locking ring **20A-1** to abut against the actuation button **15** when the locking ring **20A** is rotated into the locked position (FIG. **9C**). Another portion of the locking ring **20A-2** is located such that it grips or holds a portion of the elongated handle body **10** (FIG. **9B**). Such a locking mechanism **20** may resist inadvertent or accidental movement or retraction of the actuation button **15** or other components in the multipurpose handle **5** during packaging, sterilization, shipping, storage, handling, and preparation for use.

(40) Referring now to FIGS. **10** and **11**, the elongated handle body **10** may comprise a fin **11** aligned with the longitudinal axis (I) of the elongated handle body **10**. This fin **11** further comprise a hole **13** located in a position that is easily accessible by the index finger of the user during the operation of the medical device delivery system **1** (see FIG. **10**). The difference (A) between the longitudinal axis (I) of the elongated handle body **10** and the longitudinal axis (II) of the locking member **20** causes the locking member **30** to rotate into the elongated handle body **10** of the multipurpose handle **5** (see FIG. **11**). The locking member **20** may include one or more fins **21** to assist in gripping the mechanism in order to scroll or rotate the member between locked and unlocked positions.

(41) Referring now to FIGS. **12(A)-12(E)**, various other forms of the locking mechanism are described. In FIG. **12A**, a sliding locking button **23** is utilized. This locking button **23** slides against a portion of the actuation button **15** in order to prevent movement thereof when in the locked position. Alternatively, the locking button **23** abuts against a side and/or a face **15A** of the actuation button **15** or thumb wheel. Alternatively, the locking member **20** or button **23** makes contact with the distal face **15A** of the actuation button **15** or thumb wheel. The locking button **23** may slide in an opposite direction in order to unlock and allow the actuation button **15** to move. In this embodiment, the index finger **4** of the user may, together with the thumb finger provide greater control of the actuation button **15**.

(42) In FIG. **12B**, the locking button **23** is shown to abut against a face **15A** of the actuation button **15**. In this embodiment the fin **11** in contact with the user's middle or index finger **4** is capable of movement (m) causing the locking button **23** to engage the face **15A** of the actuation button **15** in order to establish a locked position. The locking button **23** may be held in place through the use of one or more fasteners **24** formed as part of the locking button **23**.

(43) In another configuration shown in FIG. **12C**, the actuation button **15** may slide over a projection **10B** arising from a wall of the elongate handle body **10** to create a locked position. In this locked position, the actuation button **15** is held in place by a spring **70**. The actuation button **15** may be released, thereby, creating an unlocked position through the use of the locking button **23**. The locking button **23** in this case is a push button that overcomes the spring **70** retention and moves the actuation button **15** past the projection **10B** in the wall of the elongate body handle **10**.

(44) Another form of the locking member **20** is shown in FIG. **12D** in which the locking button **23** is a spring-loaded lever capable of being pivoted near its fulcrum point **75**. A spring **71** is positioned such that the locking button **23** is held in a locked position by the spring **71** forcing the lever to contact a face **15A** of the actuation button **15**. The user is able to release the actuation button **15** by pushing on the locking button **23**, thereby overcoming the spring **71** retention and creating an unlocked position.

(45) In FIG. **12E**, the multipurpose handle **1** may include the capability of providing variable locking positions during the operation of the delivery system. Variable locking positions may be created, without limitation, through the use of a plurality of splines, ridges, or teeth **80A** located in the surface of the actuation button **15** that are appropriately mated or meshed with a plurality of grooves **80B** formed in the locking member **20** or vice versa. The alignment or meshing of the splines **80A** and the grooves **80B** creates a locked position that prevents movement of the actuation button **15**. The different number of splines **80A** and grooves **80B** that may be meshed or mated together establish variability in the position of the actuation button **15**. The locking member **20** may include a locking button **23** in which pushing upon the locking button **23** causes the splines **80A** and grooves **80B** to separate, thereby, creating an unlocked position allowing the actuation button **15** to move.

(46) Referring now to FIGS. **13A** and **13B**, the locking member **20** may be integrated with the fin **11** formed as part of the elongate handle body **10**. In this embodiment, the locking member **20** includes a pivot point **90** that allows the index finger of the user to apply pressure and push the locking member **20** into contact with the surface of a face **15A** of the actuation button **15**. The

locking member **20** acts similar to a lever that is typically in an unlocked position and upon the application of external force or pressure by the user is forced into a locked position.

(47) Another example of a medical device delivery system that incorporates the multipurpose handle of the present disclosure is described in FIG. **14**. In this configuration the locking button **23** comprises at least one protrusion **93** located on each side of the locking button **23** in order to hold the button **23** in place and prevent the button **23** from being removed (i.e., falling) through the opening present in the elongated handle body **10**. These protrusions **93** may also act as the pivot point **90A** with respect to axis (III) in order for the locking button to establish a locked position and unlocked position. When desirable, the locking button **23** may also be ergonomically curved **95** so that it more appropriately fits the index finger of the user.

(48) According to one aspect of the present disclosure, a locking button **23** is forced to abut against a face **15A** of the actuation button, thereby, creating a locked position. The locking button **23** may be spring-loaded in that a spring forces the multipurpose handle to be in an unlocked or locked state in the absence of pressure applied by the user to the locking button **23**. According to another aspect, the spring **72** as shown in FIG. **15**, may provide a sensible and/or audible click associated with locking/unlocking the button **23**. In the absence of pressure, the button **23** remains in the state in which it was left with subsequent locking or unlocking having to be done manually. In other words, an external force applied to the locking member that overcomes the force of the spring is able to cause the locking member to move from the unlocked position to the locked position or from the locked position to the unlocked position.

(49) According to another aspect of the present disclosure, a medical device delivery system is provided that incorporates the multipurpose handle described above and as further defined herein. As shown in FIGS. **1-15**, the medical device delivery system comprises an outer sheath, a medical device, and a multipurpose handle. The medical device is located at least partially within, alternatively, entirely within the outer sheath in an initial configuration ready for deployment. The outer sheath may be a catheter capable of holding and protecting the medical device while it is pushed endoluminally through a patient's vasculature to a remote treatment or targeted site. The outer sheath or catheter is advantageously as small in diameter as possible for a given application, in order to improve endovascular movement and hold the medical device properly in position until its deployment. The outer sheath may accommodate the use of a guide wire for tracking the delivery of the medical device to the desired or targeted position. The type of medical device is not restricted and may take the form of any known devices, including but not limited to, stents, embolic coils, and vena cava filters.

(50) According to another aspect of the present disclosure, the use of a medical device delivery system that incorporates a multipurpose handle as described herein to deliver or retrieve a medical device from a desired or targeted site within a vasculature of a patient's body is believed to be within the scope of the present invention. During such use, the multipurpose handle provides the user with control over longitudinal movement together with scrolling rotation of the attached medical device. The user may utilize his/her thumb and index finger on a single hand to accomplish such longitudinal and rotational movements.

(51) The specific examples provided in this disclosure are given to illustrate various embodiments of the invention and should not be construed to limit the scope of the disclosure. The embodiments have been described in a way which enables a clear and concise specification to be written, but it is intended and will be appreciated that embodiments may be variously combined or separated without parting from the invention. For example, it will be appreciated that all preferred features described herein are applicable to all aspects of the invention described herein.

(52) Those skilled-in-the-art, in light of the present disclosure, will appreciate that many changes can be made in the specific embodiments which are disclosed herein and still obtain alike or similar result without departing from or exceeding the spirit or scope of the disclosure. One skilled in the art will further understand that any properties reported herein represent properties that are routinely

measured and can be obtained by multiple different methods. The methods described herein represent one such method and other methods may be utilized without exceeding the scope of the present disclosure.

(53) The foregoing description of various forms of the invention has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Numerous modifications or variations are possible in light of the above teachings. The forms discussed were chosen and described to provide the best illustration of the principles of the invention and its practical application to thereby enable one of ordinary skill in the art to utilize the invention in various forms and with various modifications as are suited to the particular use contemplated. All such modifications and variations are within the scope of the invention as determined by the appended claims when interpreted in accordance with the breadth to which they are fairly, legally, and equitably entitled.

Claims

1. A multipurpose handle for delivery or retrieval of a medical device to or from a target site within a patient via a sheath connected to the multipurpose handle, the multipurpose handle comprising: an elongate handle body having a proximal end extending to a distal end defining a longitudinal axis, the elongate handle body having a cutout defining a movement space therein, the cutout including a longitudinal slot on the elongate handle body opening to a cavity in the elongate handle body; an actuation button disposed within the cutout of the elongate handle body and connected to the medical device, the actuation button being movable by sliding within the cutout along the longitudinal axis to move the medical device longitudinally and rotatable within the cutout to rotate the medical device, wherein an extent of sliding movement of the actuation button along the longitudinal axis is limited to within the cutout, and wherein the handle is configured to deliver the medical device to the target site within a patient from a position within the sheath by using a thumb of a hand of a user in a grip position gripping the handle to slide the actuation button along the longitudinal axis within said extent of sliding movement; a locking member connected to the elongate handle body and movable between a locked position and unlocked position, wherein the locking member is accessible to and movable between the locked position and the unlocked position by a finger of the hand of the user in said grip position and restricts movement of the actuation button along the longitudinal axis when in the locked position.
2. The multipurpose handle of claim 1 wherein the actuation button is a thumb wheel having a proximal face and a distal face.
3. The multipurpose handle of claim 2 wherein the thumb wheel includes fins disposed on the circumference of the thumb wheel.
4. The multipurpose handle of claim 2 wherein in the locking position, the locking member is in contact with the distal face of the thumb wheel.
5. The multipurpose handle of claim 2, wherein the locking member includes a locking ring.
6. The multipurpose handle of claim 2, wherein the thumb wheel includes a tactile bump.
7. The multipurpose handle of claim 1, wherein the actuation button is placed in the locked position by a sliding component.
8. The multipurpose handle of claim 1, wherein the longitudinal axis of the elongated body and a longitudinal axis of the locking member are located such that the locking mechanism rotates into the elongated body.
9. The multipurpose handle of claim 1, wherein the locking member includes a spring configured to hold the locking member in the locked position or unlocked position.
10. The multipurpose handle of claim 9, wherein the spring exhibits a force to hold the locking member in the locked position or the unlocked position, such that an external force applied to the locking member that overcomes the force of the spring is able to cause the locking member to

move from the unlocked position to the locked position or from the locked position to the unlocked position.

11. The multipurpose handle of claim 1, wherein the actuation button further comprises one or more protrusions configured to prevent the actuation button from being removed from the elongated body.

12. The multipurpose handle of claim 1 wherein the locking member includes a locking button configured to slide or be pushed in order to place the actuation button into the locked position.

13. The multipurpose handle of claim 1, wherein the locking member and the actuation button includes a plurality of splines located on one of the locking member or actuation button and a plurality of grooves located on the other one of the actuation button or locking member.

14. The multipurpose handle of claim 13, wherein the locking position is variable due to the different number of splines that are aligned or meshed with the grooves.

15. The use of the multipurpose handle of claim 1 in a medical device delivery system configured to deliver or retrieve a medical device from a targeted site in a vasculature of a patient.

16. A multipurpose handle for delivery or retrieval of a medical device, the multipurpose handle comprising: an elongate handle body having a proximal end extending to a distal end defining a longitudinal axis, the elongate handle body having a cutout defining a movement space therein, wherein the cutout is droplet shaped; an actuation button disposed within the cutout of the elongate handle body and connected to the medical device, the actuation button being movable within the cutout along the longitudinal axis and rotatable within the cutout; a locking member connected to the elongate handle body and movable between a locked position and unlocked position, the locking member being in contact with the actuation button and restricting movement of the actuation button along the longitudinal axis in the locked position.

17. A medical device delivery system for delivering a medical device to a target site within a patient, comprising: an outer sheath; a medical device located at a position within the outer sheath in an initial configuration ready for deployment, wherein the medical device is required to move longitudinally through the outer sheath for deployment to the target site; and a multipurpose handle connected to the outer sheath and the medical device, the handle comprising: an elongate handle body having a proximal end extending to a distal end defining a longitudinal axis, the elongate handle body having a cutout defining a movement space therein, the cutout including a longitudinal slot in the elongate handle body opening to a cavity in the elongate handle body; an actuation button disposed within the cutout of the elongate handle body and connected to the medical device, the actuation button being movable by sliding within the cutout along the longitudinal axis to move the medical device longitudinally and rotatable within the cutout to rotate the medical device, wherein an extent of sliding movement of the actuation button in the handle is limited to within the cutout, and wherein the medical device is deliverable to the target site from said position within the sheath by using a thumb of a hand of the user in a grip position gripping the handle to slide the actuation button longitudinally within said extent of sliding movement; a locking member connected to the elongate handle body and movable between a locked position and unlocked position, wherein the locking member is accessible to and movable between the locked position and unlocked position by a finger of the hand of the user in said grip position and restricts movement of the actuation button along the longitudinal axis when in the locked position.

18. The medical device delivery system of claim 17, wherein the medical device is a stent, an embolic coil, or a vena cava filter.

19. The medical device delivery system of claim 17, wherein the actuation button is placed in the locked position by a sliding component.

20. The use of the medical device delivery system of claim 17 for delivering or retrieving a medical device from a targeted site in a vasculature of a patient.
