

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397428
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kamon; Masayuki et al.

Robot system and method of controlling the robot system

Abstract

A robot system (**100**) includes a slave unit (**1**) including a slave arm (**11**) having a working end (**11a**), a slave arm actuator (**13**) configured to drive the slave arm, and a slave-side controller (**14**) configured to control the slave arm actuator based on a slave operating command for defining a target position of the working end, a master unit (**2**) including a master arm (**21**) having a manipulation end (**21a**) into which the content of manipulation is inputted by an operator, and a system controller (**3**) configured to generate the slave operating command based on the content of manipulation inputted into the manipulation end. When a command corresponding to the content of manipulation is a command corresponding to a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, the system controller performs processing to give perception to the operator.

Inventors: Kamon; Masayuki (Kobe, JP), Ryu; Hideyuki (Kobe, JP), Fujimori; Jun (Kobe, JP), Kinoshita; Hiroki (Kobe, JP), Takahashi; Hiroki (Kobe, JP), Shitaka; Takuya (Kobe, JP), Shimizu; Kai (Kobe, JP)

Applicant: KAWASAKI JUKOGYO KABUSHIKI KAISHA (Kobe, JP)

Family ID: 1000008778396

Assignee: KAWASAKI JUKOGYO KABUSHIKI KAISHA (Kobe, JP)

Appl. No.: 18/664497

Filed: May 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240300108 A1	Sep. 12, 2024

Foreign Application Priority Data

JP	2018240132	Dec. 21, 2018
JP	2018240133	Dec. 21, 2018

Related U.S. Application Data

continuation parent-doc US 17414979 US 12011834 20240618 WO PCT/JP2019/049916
20191219 child-doc US 18664497

Publication Classification

Int. Cl.: B25J13/02 (20060101); B25J3/00 (20060101); B25J3/04 (20060101); B25J9/16 (20060101); B25J13/08 (20060101)

U.S. Cl.:

CPC B25J9/1664 (20130101); B25J3/00 (20130101); B25J9/1633 (20130101); B25J9/1651 (20130101); B25J13/085 (20130101);

Field of Classification Search

CPC: B25J (9/1664); B25J (3/00); B25J (9/1633); B25J (9/1651); B25J (13/085); B25J (3/04); B25J (9/1689); B25J (13/025)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5949686	12/1998	Yoshinada	700/260	B25J 3/04
9492927	12/2015	Diolaiti	N/A	A61B 34/37
2007/0142825	12/2006	Prisco	606/1	A61B 34/70
2015/0366624	12/2014	Kostrzewski	606/130	A61B 34/76
2017/0001301	12/2016	Kamiya	N/A	B25J 9/1633
2018/0055577	12/2017	Barral	N/A	B25J 9/1633
2019/0201136	12/2018	Shelton, IV	N/A	G16H 50/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2015154172	12/2014	WO	B25J 3/04
WO-2018087123	12/2017	WO	B25J 13/025
WO-2018201240	12/2017	WO	B25J 13/006
WO-2018212265	12/2017	WO	B25J 13/085

Primary Examiner: Mott; Adam R

Assistant Examiner: Keniry; Heather J

Background/Summary

(1) This application is a continuation application of U.S. application Ser. No. 17/414,979, filed on Jun. 17, 2021, which is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2018-240132 and No. 2018-240133, both filed on Dec. 21, 2018, the entire contents of all of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present disclosure relates to a robot system and a method of controlling the robot system.

BACKGROUND ART

(2) Conventionally, a master-slave manipulator and a method of controlling the same are known.

(3) For example, Patent Document 1 discloses a master-slave manipulator which, when a reaction force measured by a force sensor exceeds a target force value set beforehand, inhibits operation of a slave arm so that the slave arm does not follow operation of a master arm in a force controlling direction set beforehand. The force controlling direction is a direction set substantially in agreement with a normal direction of a work object, and is a direction toward the work object and a direction away from the work object. The slave arm is operated by a force control so that the target force value set beforehand becomes equal to the reaction force measured by the force sensor.

(4) Moreover, Patent Document 2 discloses a master-slave manipulator having a slave arm which follows the shape of a master arm so that the shape of the slave arm becomes similar to the shape of the master arm, by operating the master arm. A contact is provided to the master arm, and this contact contacts a position regulating member to regulate an operating range of the master arm.

REFERENCE DOCUMENTS OF CONVENTIONAL ART

Patent Documents

(5) [Patent Document 1] JP 1996-281573A [Patent Document 2] JP 1995-124876A

DESCRIPTION OF THE DISCLOSURE

Problems to be Solved by the Disclosure

(6) However, according to the master-slave manipulator disclosed in Patent Document 1, for example, in a case where the slave arm is in contact with a hard work object, when an operator tries to forcibly move the master arm in a direction corresponding to a direction of the slave arm moving toward the work object, an excessive load is applied to the master arm, and therefore, the force sensor or the master arm may be damaged.

(7) Moreover, according to the master-slave manipulator disclosed in Patent Document 2, when the slave arm contacts a workpiece, it cannot notify the operator about the contact. It may be difficult for the operator to distinguish whether the slave arm contacts the workpiece and operation of the slave arm is regulated, or the contact contacts the position regulating member and the operating range of the master arm is regulated.

(8) One purpose of the present disclosure is to provide a robot system and a method of controlling the robot system, which enables the operator to perceive an operating limit of at least one of a master arm and a slave arm.

Summary of the Disclosure

(9) In order to achieve the purpose, a robot system according to one aspect of the present disclosure includes a slave unit including a slave arm having a working end, a slave arm actuator configured to drive the slave arm, and a slave-side controller configured to control the slave arm actuator based on a slave operating command for defining a target position of the working end, a master unit including a master arm having a manipulation end into which the content of manipulation is inputted by an operator, and a system controller including a slave operating command generating

module configured to generate the slave operating command based on the content of manipulation inputted into the manipulation end. When a command corresponding to the content of manipulation is a command corresponding to a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, the system controller performs processing to give perception to the operator.

Effect of the Disclosure

(10) According to the present disclosure, it is possible to enable the operator to perceive the limit of operation of at least one of the master arm and the slave arm.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a view schematically illustrating one example of a configuration of a robot system according to Embodiment 1.

(2) FIG. 2 is a block diagram schematically illustrating one example of a configuration of a control system of the robot system of FIG. 1.

(3) FIG. 3 is a flowchart illustrating one example of operation of the robot system of FIG. 1.

(4) FIG. 4 is a block diagram schematically illustrating one example of a configuration of a control system of a robot system according to Modification 1 of Embodiment 1.

(5) FIG. 5 is a block diagram schematically illustrating one example of a configuration of a control system of a robot system according to Embodiment 2.

(6) FIG. 6 is a view illustrating one example of setting of an operating range, an entering prohibited range, and a notifying range set by a notifying range setting module of the robot system according to Embodiment 2.

(7) FIG. 7 is a view illustrating one example of operation of the robot system according to Embodiment 2.

(8) FIG. 8 is a view illustrating one example of operation of the robot system according to Embodiment 2.

(9) FIG. 9 is a block diagram schematically illustrating one example of a configuration of a control system of a robot system according to Modification 2 of Embodiment 2.

MODES FOR CARRYING OUT THE DISCLOSURE

(10) First, one example of each aspect of the present disclosure is described. A robot system according to one aspect of the present disclosure includes a slave unit including a slave arm having a working end, a slave arm actuator configured to drive the slave arm, and a slave-side controller configured to control the slave arm actuator based on a slave operating command for defining a target position of the working end, a master unit including a master arm having a manipulation end into which the content of manipulation is inputted by an operator, and a system controller including a slave operating command generating module configured to generate the slave operating command based on the content of manipulation inputted into the manipulation end. When the command corresponding to the content of manipulation is a command corresponding to a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, the system controller performs processing to give perception to the operator.

(11) According to this aspect, the robot system can notify the operator, through the giving of perception, that the command corresponding to the content of manipulation is the command corresponding to the limit equivalent range. Thus, the robot system can enable the operator to perceive the limit of operation of at least one of the master arm and the slave arm.

(12) In the robot system according to one aspect of the present disclosure, the slave unit may further include a slave-side force detector configured to detect a direction and a magnitude of a reaction force acting on the working end or a workpiece held by the working end. The master unit

may further include a master-side force detector configured to detect a direction and a magnitude of an operating force applied by the operator to the manipulation end as the content of manipulation, a master arm actuator configured to drive the master arm, and a master-side controller configured to control the master arm actuator based on a master operating command for defining a target position of the manipulation end. The system controller may generate, based on the operating force and the reaction force, the slave operating command and the master operating command for moving the manipulation end in a moving direction corresponding to a moving direction of the working end of the slave operating command. When the system controller determines that the magnitude of the operating force is included in a range exceeding a first threshold as the limit equivalent range, the system controller may generate the master operating command for moving the manipulation end in the direction of the operating force.

(13) According to this aspect, the robot system can inform the operator, through the master arm, that the magnitude of the operating force exceeds the given first threshold, and can inform the operator that the master arm is overloaded. Moreover, the robot system can reduce the load on the master arm and the master-side force detector by moving the manipulation end in the direction in which the operator applied the force. Therefore, the damage to the master arm and the master-side force detector can be prevented. As a result, it can be prevented that the operator breaks the master arm.

(14) In the robot system according to one aspect of the present disclosure, the system controller may generate the master operating command for increasing a change in a moving velocity of the manipulation end as the operating force increases.

(15) According to this aspect, the robot system can guide the operator about how much the operating force is to be weakened, and thus, the operator can be guided so as to appropriately weaken the operating force. Moreover, as the magnitude of the operating force increases, the manipulation end moves more quickly in the direction in which the operator applied the force. Therefore, the load on the master arm and the master-side force detector can be reduced more appropriately, and the damages to the master arm and the master-side force detector can be prevented more appropriately.

(16) In the robot system according to one aspect of the present disclosure, the system controller may include an operating mode setting module configured to set an operating mode to one of a plurality of operating modes including a normal operating mode and an informing operating mode, a slave operating command generating module configured to generate the slave operating command based on the operating force and the reaction force, a first temporary master operating command generating module configured to generate a first temporary master operating command for moving the manipulation end in a moving direction corresponding to a moving direction of the working end of the slave operating command based on the operating force and the reaction force, a second temporary master operating command generating module configured to generate a second temporary master operating command based on the operating force, and a master operating command setting module configured to set the first temporary master operating command to the master operating command in the normal operating mode, and set the second temporary master operating command to the master operating command in the informing operating mode. When the operating mode setting module determines that the magnitude of the operating force is included in a range exceeding the first threshold, the operating mode setting module may set the operating mode to the informing operating mode.

(17) According to this aspect, the robot system can appropriately inform the operator through the master arm by changing the operating mode from the normal operating mode to the informing operating mode. Moreover, the robot system can stop the slave arm as well as appropriately change the operation of the slave arm based on the operating force and reaction force detected by the detector, regardless of the set operating mode. Therefore, the robot system can avoid that the operation of the master arm upon informing the operator affects the operation of the slave arm, and

as a result, it can appropriately inform the operator. In addition, since the robot system can change the operating mode automatically, an emergency stop for protecting the system can be avoided.

(18) In the robot system according to one aspect of the present disclosure, the plurality of operating modes may further include a resuming operating mode. The system controller may further include a third temporary master operating command generating module configured to generate a third temporary master operating command for moving the manipulation end toward the target position of the manipulation end defined by the first temporary master operating command. The master operating command setting module may further set the third temporary master operating command to the master operating command in the resuming operating mode. When the operating mode setting module determines that the magnitude of the operating force is included in a range of a given second threshold or below in a state where the operating mode is set to the informing operating mode, the operating mode setting module may set the operating mode to the resuming operating mode.

(19) According to this aspect, after informing the operator, the robot system can move the manipulation end so that the manipulation end and the working end have a given correlation.

(20) In the robot system according to one aspect of the present disclosure, when the operating mode setting module determines that the manipulation end is located at the target position of the first temporary master operating command in a state where the operating mode is set to the resuming operating mode, the operating mode setting module may set the operating mode to the normal operating mode.

(21) According to this aspect, the robot system can resume the manipulation end and the working end to the state where they operate synchronizably having the given correlation. Moreover, it can resume the mode to the normal operating mode automatically so that the interruption of the work can be avoided.

(22) In the robot system according to one aspect of the present disclosure, the system controller may include a converting module configured to calculate a target velocity vector based on the operating force and the reaction force, and a subconverting module configured to calculate a temporary target velocity vector based on the operating force. The slave operating command generating module may generate the slave operating command based on the target velocity vector. The first temporary master operating command generating module may generate the first temporary master operating command based on the target velocity vector. The second temporary master operating command generating module may generate the second temporary master operating command based on the temporary target velocity vector.

(23) According to this aspect, in the robot system of a bilateral control system, the informing the operator can be performed appropriately.

(24) The robot system according to one aspect of the present disclosure may further include an informing part configured to perform a notification by using sense information perceivable by the operator's perception. The master unit may further include a master-side force detector configured to detect a direction and a magnitude of an operating force applied by the operator to the manipulation end as the content of manipulation. When the system controller determines that the magnitude of the operating force is included in a range exceeding a third threshold as the limit equivalent range, the system controller may control the informing part to perform the notification to the operator.

(25) According to this aspect, the robot system can inform the operator that the magnitude of the operating force exceeds the first threshold, and can inform the operator that the master arm is overloaded. As a result, it can be prevented that the operator breaks the master arm.

(26) In the robot system according to one aspect of the present disclosure, the system controller may control the informing part so that an intensity of the sense information becomes stronger as the operating force becomes larger.

(27) According to this aspect, the robot system can guide the operator about how much the

operating force is to be weakened, and thus, the operator can be guided so as to appropriately weaken the operating force.

(28) The robot system according to one aspect of the present disclosure may further include an informing part configured to perform a notification by using sense information perceivable by the operator's perception. When the system controller determines that the target position of the working end of the slave operating command is located in a notifying range as the limit equivalent range, that is a range spreading from a limit of a given operating range to the operating range side, the system controller may control the informing part to perform the notification to the operator.

(29) According to this aspect, the robot system can notify the approaching of the working end to the limit of the operating range through the perception of the operator. Therefore, the operator can easily distinguish whether the working end contacts the workpiece, or whether the working end approaches the limit of the operating range or near the limit, and the work efficiency can be improved.

(30) In the robot system according to one aspect of the present disclosure, the system controller may control the informing part so that an intensity of the sense information becomes stronger as a distance between the target position of the working end of the slave operating command and the limit of the operating range becomes smaller.

(31) According to this aspect, the robot system can guide the operator about the distance to the limit of the operating range.

(32) In the robot system according to one aspect of the present disclosure, the slave unit may further include a slave-side force detector configured to detect a direction and a magnitude of a reaction force acting on the working end or a workpiece held by the working end. The master unit may further include a master-side force detector configured to detect a direction and a magnitude of an operating force applied by the operator to the manipulation end as the content of manipulation, a master arm actuator configured to drive the master arm, and a master-side controller configured to control the master arm actuator based on a master operating command. The system controller may generate, at every given control period, the slave operating command for defining the target position of the working end and the master operating command for defining a target position of the manipulation end so that the target position of the slave operating command and the target position of the master operating command have a given correlation. When the system controller determines that the target position of the working end of the slave operating command is located in a notifying range as the limit equivalent range, that is a range spreading from a limit of a given operating range to the operating range side, the system controller may generate the master operating command to change the operation of the manipulation end.

(33) According to this aspect, the robot system can notify the approaching of the working end to the limit of the operating range through an inner force sense of the operator. Therefore, the operator can easily distinguish whether the working end contacts the workpiece, or whether the working end approaches the limit of the operating range or near the limit, and the work efficiency can be improved.

(34) In the robot system according to one aspect of the present disclosure, when the system controller determines that the target position of the working end of the slave operating command is located in the notifying range, the system controller may set a repulsive force acting on the working end in a direction separating from the limit of the operating range, and generate the master operating command based on a resultant force of the operating force, the reaction force, and the repulsive force in a subsequent control period.

(35) According to this aspect, the robot system can notify the operator by the repulsive force about the approaching to the limit of the operating range. Moreover, based on the direction of the repulsive force, the robot system can appropriately guide the operator about the direction separating from the boundary.

(36) In the robot system according to one aspect of the present disclosure, the system controller

may set the repulsive force so that a magnitude of the repulsive force becomes larger as a distance between the target position of the working end of the slave operating command and the limit of the operating range becomes smaller.

(37) According to this aspect, the robot system can guide the operator about the distance to the limit of the operating range.

(38) In the robot system according to one aspect of the present disclosure, the system controller may further include a notifying range setting module configured to set the notifying range, a repulsive force setting module configured to set the repulsive force, when the repulsive force setting module determines that the target position of the working end of the slave operating command is located in the notifying range, a converting module configured to calculate a target velocity vector based on a resultant force of the operating force, the reaction force, and the repulsive force, a slave operating command generating module configured to generate the slave operating command based on the target velocity vector, and a master operating command generating module configured to generate the master operating command based on the target velocity vector.

(39) According to this aspect, in the robot system of a bilateral control system, the robot system can appropriately notify the operator about the approaching to the limit of the operating range.

(40) A method of controlling a robot system according to one aspect of the present disclosure is a method of controlling a robot system provided with a slave arm and a master arm. The method includes the step of outputting a slave operating command for defining a target position of a working end of the slave arm to a slave-side controller configured to control an actuator of the slave arm based on the slave operating command, based on the content of manipulation inputted into a manipulation end of the master arm. The method includes the step of, when the command generated corresponding to the content of manipulation is a command corresponding to a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, performing processing for giving perception to an operator who inputs the content of manipulation into the manipulation end. According to this aspect, the similar effect to the robot system according to one aspect of the present disclosure can be obtained.

(41) The method of controlling the robot system according to one aspect of the present disclosure may further include the steps of receiving a detected result of a direction and a magnitude of a reaction force acting on the working end or a workpiece held by the working end, receiving a detected result of a direction and a magnitude of an operating force applied by the operator to the manipulation end, as the content of manipulation, determining the target position of the working end based on the detected operating force and reaction force, determining a target position of the manipulation end based on the detected operating force and reaction force, and outputting a master operating command for defining the target position of the manipulation end to a master-side controller configured to control an actuator of the master arm based on the master operating command. When determined that the magnitude of the operating force is not included in a range exceeding a first threshold as the limit equivalent range, the target position of the manipulation end may be determined as a position corresponding to the position of the working end. When determined that the magnitude of the operating force is included in a range exceeding the first threshold, the target position of the manipulation end may be determined as a position moved in the direction of the operating force from a position corresponding to the position of the working end.

(42) In the method of controlling the robot system according to one aspect of the present disclosure, the master operating command for increasing a change in a moving velocity of the manipulation end as the operating force increases may be generated.

(43) The method of controlling the robot system according to one aspect of the present disclosure may further include the steps of setting an operating mode to one of a plurality of operating modes including a normal operating mode and an informing operating mode, generating the slave operating command based on the operating force and the reaction force, generating a first

temporary master operating command for moving the manipulation end in a moving direction corresponding to a moving direction of the working end of the slave operating command based on the operating force and the reaction force, generating a second temporary master operating command based on the operating force, and setting the first temporary master operating command to the master operating command in the normal operating mode, and setting the second temporary master operating command to the master operating command in the informing operating mode. The method may further include, when determined that the magnitude of the operating force is included in the range exceeding the first threshold, setting the operating mode to the informing operating mode.

(44) The method of controlling the robot system according to one aspect of the present disclosure may further include the steps of setting an operating mode to one of the plurality of operating modes including the normal operating mode, the informing operating mode, and a resuming operating mode, generating a third temporary master operating command for moving the manipulation end toward the target position of the manipulation end defined by the first temporary master operating command, setting the third temporary master operating command to the master operating command in the resuming operating mode, and when determined that the magnitude of the operating force is included in a range of a given second threshold or below in a state where the operating mode is set to the informing operating mode, setting the operating mode to the resuming operating mode.

(45) The method of controlling the robot system according to one aspect of the present disclosure may further include the step of, when determined that the manipulation end is located at the target position of the first temporary master operating command in a state where the operating mode is set to the resuming operating mode, setting the operating mode to the normal operating mode.

(46) The method of controlling the robot system according to one aspect of the present disclosure may further include the steps of calculating a target velocity vector based on the operating force and the reaction force, calculating a temporary target velocity vector based on the operating force, generating the slave operating command based on the target velocity vector, generating the first temporary master operating command based on the target velocity vector, and generating the second temporary master operating command based on the temporary target velocity vector.

(47) The method of controlling the robot system according to one aspect of the present disclosure may further include the step of receiving a detected result of a direction and a magnitude of an operating force applied by the operator to the manipulation end as the content of manipulation. When determined that the magnitude of the detected operating force is included in a range exceeding a third threshold as the limit equivalent range, a command for performing a notification using sense information perceivable by the operator's perception may be outputted.

(48) In the method of controlling the robot system according to one aspect of the present disclosure, a command for performing a notification such that an intensity of the sense information becomes stronger as the operating force becomes larger, may be outputted.

(49) The method of controlling the robot system according to one aspect of the present disclosure may further include the step of setting a notifying range spreading from a limit of a given operating range to the operating range side as the limit equivalent range. When determined that the target position of the working end of the slave operating command is located in the notifying range, a command for performing a notification using sense information perceivable by the operator's perception may be outputted.

(50) In the method of controlling the robot system according to one aspect of the present disclosure, a command for performing a notification such that an intensity of the sense information becomes stronger as a distance between the target position of the working end of the slave operating command and the limit of the operating range becomes smaller, may be outputted.

(51) The method of controlling the robot system according to one aspect of the present disclosure may further include the step of receiving a detected result of a direction and a magnitude of a

reaction force acting on the working end or a workpiece held by the working end, receiving a detected result of a direction and a magnitude of an operating force applied by the operator to the manipulation end, as the content of manipulation, determining the target position of the working end based on the detected operating force and reaction force, determining a target position of the manipulation end based on the detected operating force and reaction force, outputting a master operating command for defining the target position of the manipulation end to a master-side controller configured to control an actuator of the master arm based on the master operating command, and setting a notifying range spreading from a limit of a given operating range to the operating range side as the limit equivalent range. The target position of the working end is determined based on a resultant force of the operating force and the reaction force detected at every given control period. When determined that the target position of the working end is located in the notifying range, a repulsive force acting on the working end in a direction separating from the limit of the operating range may be set. A next target position of the manipulation end may be determined based on a resultant force of the operating force, the reaction force, and the repulsive force. The master operating command for causing the actuator of the master arm to locate the manipulation end at the next target position may be outputted in a subsequent control period.

(52) In the method of controlling the robot system according to one aspect of the present disclosure, when determined that the target position of the working end of the slave operating command is located in the notifying range, a repulsive force acting on the working end in a direction separating from the limit of the operating range may be set, and the master operating command may be generated based on a resultant force of the operating force, the reaction force, and the repulsive force in a subsequent control period.

(53) In the method of controlling the robot system according to one aspect of the present disclosure, the repulsive force may be set so that a magnitude of the repulsive force becomes larger as a distance between the target position of the working end of the slave operating command and the limit of the operating range becomes smaller.

(54) The method of controlling the robot system according to one aspect of the present disclosure may further include the steps of setting the notifying range, setting the repulsive force, when determined that the target position of the working end of the slave operating command is located in the notifying range, calculating a target velocity vector based on a resultant force of the operating force, the reaction force, and the repulsive force, generating the slave operating command based on the target velocity vector, and generating the master operating command based on the target velocity vector.

(55) Hereinafter, embodiments will be described with reference to the drawings. Note that the present disclosure is not limited by the embodiments. Moreover, below, throughout the drawings, the same reference characters are assigned to the same or corresponding elements to omit redundant description.

Embodiment 1

(56) FIG. 1 is a view schematically illustrating one example of a configuration of a robot system **100** according to Embodiment 1. FIG. 2 is a block diagram schematically illustrating one example of a configuration of a control system of the robot system **100**.

(57) As illustrated in FIGS. 1 and 2, the robot system **100** is a system including a master-slave robot which operates a slave arm **11** so that the slave arm **11** follows the motion of a master arm **21**. In the robot system **100**, when an operator P who is located at a position distant from a workspace of the slave arm **11** (outside of the workspace) moves the master arm **21** to input an operating command into the robot system **100**, the slave arm **11** performs operation corresponding to the operating command to perform a specific work, such as an assembly of component(s).

(58) Further, the robot system **100** is a bilateral-control robot system, in which a controller is configured to control the slave arm **11** and is further configured to control the operation of the master arm **21** while synchronizing the operation of the master arm **21** to the operation of the slave

arm **11** so as to present a force acting on the slave arm **11** to the operator P through the master arm **21**. The robot system **100** is provided with a slave unit **1** including the slave arm **11**, a master unit **2** including the master arm **21**, and a system controller **3**.

(59) [Example Configuration of Slave Unit]

(60) As illustrated in FIGS. **1** and **2**, the slave unit **1** is an industrial robot, for example. The slave unit **1** includes a base **10**, the slave arm **11**, a slave-side force detector **12**, a slave arm actuator **13**, and a slave-side controller **14**. The slave arm **11** is a vertical articulated robotic arm, for example.

(61) That is, the slave arm **11** is provided with a plurality of links connected sequentially in a direction from a base-end part to a tip-end part, and one or more joints which rotatably connects one of adjacent links to the other link. A tip-end part of the slave arm **11** is a working end **11a**, and a hand (also referred to as an “end effector”) **16** is provided to the working end **11a**. The base **10** is fixed to a floor, for example, and supports the slave arm **11**. The slave arm **11** has 6 degrees of freedom, for example, and can make the working end **11a** take an arbitrary posture at an arbitrary position within an operating range inside a three-dimensional space.

(62) For example, the hand **16** can perform a holding operation in which it holds the workpiece W and a releasing operation in which it releases or cancels the hold of the workpiece W, and perform the assembly of component(s). The hand **16** includes a hand actuator (not illustrated) for performing the holding operation and the releasing operation. Note that the structure of the hand **16** may be a structure according to the purpose of the work so that it is able to perform welding or painting.

(63) The slave-side force detector **12** is a sensor which detects magnitudes of forces acting in three axial directions which intersect perpendicularly to each other, and moments of the forces acting about the three axes, and is disposed at the working end **11a** of the slave arm **11**. The slave-side force detector **12** is comprised a 6-axis force sensor capable of detecting components of the forces which act in the three axial directions which intersect perpendicularly to each other, and act about the axes. Thus, when the workpiece W held by the working end **11a** of the slave arm **11** contacts an object T to which the workpiece W is assembled, the slave-side force detector **12** detects the direction and the magnitude of a reaction force f_s which acts on the working end **11a** or the workpiece W held by the working end **11a**. The detected reaction force f_s is outputted to the system controller **3**.

(64) The slave arm actuator **13** drives the slave arm **11**. That is, the slave arm actuator **13** includes an actuator provided to each joint of the slave arm **11**, and when it operates each joint by the drive of the actuator, a tip-end part (working end **11a**) of the slave arm **11** and the hand **16** are moved with respect to a base-end part within the given operating range. In this embodiment, for example, each joint of the slave arm **11** is a rotary joint, and the actuator is a servomotor provided with a speed reducer.

(65) The slave-side controller **14** controls the slave arm actuator **13** based on a slave operating command x_s which is a positional command for defining a target position of the working end **11a** to operate the slave arm **11**. The slave operating command x_s is a positional command in a slave coordinate system. The slave-side controller **14** calculates a rotation angle of the output shaft of the servomotor of each joint based on the slave operating command x_s , controls current supplied to the servomotor of each joint of the slave arm **11** to control operation of the servomotor so that it changes the posture of the slave arm **11** and locates the working end **11a** at the target position. The control of the posture of the slave arm **11** is performed by a feedback control based on a joint angle outputted from an encoder (not illustrated) provided to the slave arm **11**.

(66) [Example Configuration of Master Unit]

(67) As illustrated in FIGS. **1** and **2**, the master unit **2** is disposed outside the workspace and remotely controls operation of the slave arm **11**. The master unit **2** includes the master arm **21**, a master-side force detector **22**, a master arm actuator **23**, and a master-side controller **24**.

(68) The master arm **21** is a device for the operator P contacting and operating to input an operating

command to the slave arm **11** from the operator **P**. For example, the master arm **21** has 6 degrees of freedom, and can make a manipulation end **21a** take an arbitrary posture at an arbitrary position within an operating range in a three-dimensional space. The part which the operator **P** contacts and operates constitutes the manipulation end **21a**, and the operator **P** applies a force to the manipulation end **21a** to input the operating command to the slave arm **11**.

(69) The master-side force detector **22** is a sensor which detects the magnitudes of the forces acting in the three axial directions which intersect perpendicularly to each other, and the moments of the forces which act about the three axes, and is disposed at the manipulation end **21a** of the master arm **21**. The master-side force detector **22** is comprised of a 6-axis force sensor capable of detecting components of the forces which act in the three axial directions which intersect perpendicularly to each other, and act about the axes. Thus, the master-side force detector **22** detects the manipulation input of the operator **P** into the manipulation end **21a**, and detects the operating command **21a** from the operator **P** to the slave arm **11**, i.e., the direction and the magnitude of an operating force f_m which the operator **P** applied to the manipulation end of the master arm **21**. The detected operating force f_m is outputted to the system controller **3**.

(70) The master arm actuator **23** drives the master arm **21**. That is, the master arm actuator **23** includes an actuator provided to each joint of the master arm **21**, and operates each joint by the drive of the actuator to move the manipulation end **21a** of the master arm **21**. In this embodiment, for example, the actuator is a servomotor provided with a speed reducer.

(71) The master-side controller **24** controls the master arm actuator **23** based on a master operating command x_m which is a positional command for defining a target position of the manipulation end **21a** to operate the master arm **21**. The master operating command x_m is a positional command in a master coordinate system. The master coordinate system corresponds to the slave coordinate system, and therefore, based on one of position command values, the position command value of the other can be calculated by using a coordinate conversion. The master-side controller **24** calculates a rotation angle of the output shaft of the servomotor of each joint of the master arm **21** based on the master operating command x_m , controls current supplied to the servomotor of each joint of the master arm **21** to control operation of the servomotor of each joint so that it changes the posture of the master arm **21**, and therefore, locates the manipulation end **21a** at the target position. The control of the posture of the master arm **21** is performed by a feedback control based on the joint angle outputted from an encoder (not illustrated) provided to the master arm **21**.

(72) [Example Configuration of System Controller]

(73) The system controller **3** controls the slave unit **1** and the master unit **2** by a parallel bilateral control system. That is, the system controller **3** generates the slave operating command x_s which is a positional command and the master operating command x_m which is the positional command based on the operating force f_m detected by the master-side force detector **22** and the reaction force f_s detected by the slave-side force detector **12**.

(74) The system controller **3** includes a converting module **31**, a subconverting module **32**, a slave operating command generating module **51**, a first temporary master operating command generating module **52**, a second temporary master operating command generating module **53**, a third temporary master operating command generating module **54**, a master operating command setting module **36**, and an operating mode setting module **37**. The converting module **31**, the subconverting module **32**, the slave operating command generating module **51**, the first temporary master operating command generating module **52**, the second temporary master operating command generating module **53**, the third temporary master operating command generating module **54**, the master operating command setting module **36**, and the operating mode setting module **37** are functional blocks implemented by a processor (not illustrated) executing a given control program. Note that functions of the slave-side controller **14** and the master-side controller **24** are implemented by processor(s) (not illustrated) executing given control program(s).

(75) The above-described processor related to the slave-side controller **14**, the master-side

controller **24**, and the system controller **3** is comprised of a processor such as, a microcontroller, a CPU (Central Processing Unit), an ASIC (Application Specific Integrated Circuit), or a PLD (Programmable Logic Device) such as an FPGA (Field Programmable Gate Array). The processor may be comprised of a sole controller which carries out a centralized control, or may be comprised of a plurality of controllers which collaboratively carry out a distributed control. Note that some or all of the function of the processor may be implemented by a computer system comprised of a processor such as a CPU, a nonvolatile memory such as a RAM (Random Access Memory), and a volatile memory such as a ROM (Read-Only Memory), or may be implemented by dedicated hardware circuitry for an electronic circuit or an integrated circuit, or may be implemented by a combination of the computer system and the hardware circuitry.

(76) Moreover, the system controller **3** is provided with a storage device (not illustrated) which stores various programs and data. For example, the storage device includes a semiconductor memory, a hard disk drive, and an SSD (Solid State Drive), which are a volatile memory and a nonvolatile memory. Moreover, the system controller **3** may be comprised of a sole controller including the slave-side controller **14** and the master-side controller **24**, or may be comprised of a plurality of controllers which collaboratively carry out a distributed control.

(77) The converting module **31** calculates a target velocity vector v_d based on a resultant force of the operating force f_m detected by the master-side force detector **22** and the reaction force f_s detected by the slave-side force detector **12**. The target velocity vector v_d is used for calculating the moving directions and the magnitudes of the movement of the working end **11a** and the manipulation end **21a**, as will be described later. In more detail, the converting module **31** calculates the target velocity vector v_d defining the moving directions and moving velocities of the working end **11a** and the manipulation end **21a** based on a difference between the operating force f_m and the reaction force f_s by using the following Formula (1).

$$(78) \quad m \times \dot{v}_d + c_v \times v_d = f_m - f_s \quad (1)$$

Note that, “m” is a given mass value, and “c.sub.v” is a given coefficient of viscosity.

(79) As illustrated in Formula (1), by calculating the difference between the operating force f_m and the reaction force f_s , the converting module **31** associates the operating force f_m with the reaction force f_s , and treats the reaction force f_s as a reaction force against the operating force f_m . Then, the target velocity vector v_d is a value according to the difference between the operating force f_m and the reaction force f_s , and when the reaction force f_s is not zero due to the contact with the object T, the target velocity vector v_d normally becomes a vector which goes in a direction different from the direction of the operating force f_m .

(80) The subconverting module **32** calculates a temporary target velocity vector v_{dt} used for calculating the moving direction and the magnitude of the movement of the manipulation end **21a** based on the operating force f_m detected by the master-side force detector **22**. In more detail, the subconverting module **32** calculates the temporary target velocity vector v_{dt} defining the moving direction and the moving velocity of the manipulation end **21a** based on the operating force f_m by using the following Formula (2).

$$(81) \quad m \times \dot{v}_{dt} + c_v \times v_{dt} = f_m \quad (2)$$

(82) As illustrated in Formula (2), the temporary target velocity vector v_{dt} is a value according to the operating force f_m , and the temporary target velocity vector v_{dt} becomes a vector which goes substantially in the same direction as the operating force f_m . Moreover, the subconverting module **32** may multiply the reaction force f_s by a given coefficient and set a temporary reaction force smaller than the reaction force f_s , and may calculate the temporary target velocity vector v_{dt} based on the temporary reaction force and the operating force f_m .

(83) The slave operating command generating module **51** generates the slave operating command x_s based on the target velocity vector v_d so that the working end **11a** is moved at a speed according to the value of the target velocity vector v_d . The slave operating command x_s is a positional

command for defining the target position of the working end **11a**, as described above. The target position is normally set in the direction different from the direction of the operating force f_m , when the reaction force f_s is not substantially zero, as described regarding the target velocity vector v_d . The slave operating command x_s is outputted to the slave-side controller **14**, and the slave-side controller **14** controls the slave arm actuator **13** based on the slave operating command x_s so that the working end **11a** of the slave arm **11** is moved synchronously to follow the motion of the manipulation end **21a** of the master arm **21**.

(84) The first temporary master operating command generating module **52** generates a first temporary master operating command x_{mt1} based on the target velocity vector v_d so that the manipulation end **21a** is moved at a speed according to the value of the target velocity vector v_d . The first temporary master operating command x_{mt1} is an operating command for moving the manipulation end **21a** in a moving direction corresponding to the moving direction of the working end **11a** of the slave operating command x_s , and is a positional command for defining the target position of the manipulation end **21a**. Similarly to the slave operating command x_s , the target position is normally set in a direction different from the direction of the operating force f_m , when the reaction force f_s is not substantially zero.

(85) In this embodiment, in order to make the first temporary master operating command x_{mt1} as the operating command for moving the manipulation end **21a** in the moving direction corresponding to the moving direction of the working end **11a** of the slave operating command x_s , similar to the slave operating command x_s , the first temporary master operating command x_{mt1} is generated based on the target velocity vector v_d . Then, when seen from the operator P, the first temporary master operating command x_{mt1} is generated so that the moving direction of the working end **11a** of the slave operating command x_s becomes the same direction as the moving direction of the manipulation end **21a** of the first temporary master operating command x_{mt1} (in agreement with each other).

(86) The second temporary master operating command generating module **53** generates the second temporary master operating command x_{mt2} based on the temporary target velocity vector v_{dt} so that the manipulation end **21a** is moved at a speed according to the value of the temporary target velocity vector v_{dt} . The second temporary master operating command x_{mt2} is a positional command for defining the target position of the manipulation end **21a**. The target position is set in the same direction as the operating force f_m , as described regarding the temporary target velocity vector v_{dt} .

(87) The third temporary master operating command generating module **54** generates the third temporary master operating command x_{mt3} for moving the manipulation end **21a** toward the target position of the manipulation end **21a** defined by the first temporary master operating command x_{mt1} . The third temporary master operating command x_{mt3} is a positional command for defining the target position of the manipulation end **21a**. The target position is set in the same direction as the operating force f_m , as described regarding the temporary target velocity vector v_{dt} .

(88) The master operating command setting module **36** sets the first temporary master operating command x_{mt1} to the master operating command x_m in the normal operating mode, sets the second temporary master operating command x_{mt2} to the master operating command x_m in an informing operating mode, and sets the third temporary master operating command x_{mt3} to the master operating command x_m in a resuming operating mode. The master operating command x_m is outputted to the master-side controller **24**.

(89) The operating mode setting module **37** sets the mode to one of a plurality of operating modes including a normal operating mode, the informing operating mode, and the resuming operating mode.

(90) Therefore, the master operating command setting module **36** sets the first temporary master operating command x_{mt1} to the master operating command x_m in the normal operating mode. The master-side controller **24** controls the master arm actuator **23** based on the first temporary master

operating command $xmt1$ to operate the manipulation end $21a$ of the master arm **21** so that the manipulation end $21a$ resists the operating force f_m . Thus, the force acting on the working end $11a$ of the slave arm **11** is presented to the operator P through the manipulation end $21a$. Therefore, the operator P can perform the work while recognizing the inner force sense when the working end $11a$ contacts the environment.

(91) Moreover, the master operating command setting module **36** sets the second temporary master operating command $xmt2$ to the master operating command xm in the informing operating mode. The master-side controller **24** controls the master arm actuator **23** based on the second temporary master operating command $xmt2$ to move the manipulation end $21a$ in the direction of the operating force f_m applied by the operator P.

(92) Further, the master operating command setting module **36** sets the third temporary master operating command $xmt3$ to the master operating command xm in the resuming operating mode. The master-side controller **24** controls the master arm actuator **23** based on the third temporary master operating command $xmt3$ to move the manipulation end $21a$ so that the correlation with the working end $11a$ is resumed.

(93) Note that, the slave operating command generating module **51**, the first temporary master operating command generating module **52**, the second temporary master operating command generating module **53**, and the third temporary master operating command generating module **54** generate the operating command regardless of in which operating mode the operation is currently set.

(94) [Example Operation]

(95) Next, one example of operation of the robot system **100** is described. FIG. 3 is a flowchart illustrating one example of operation of the robot system **100**. As illustrated in FIG. 1, in this example operation, the operator P uses the robot system **100** to perform a work in which the workpiece W is assembled to the object T by fitting the workpiece W which is formed in a cylindrical shape and has a through-hole Wa onto the object T which is a cylindrical pin extending in the up-and-down direction and is formed fittable into the through-hole Wa . The workpiece W is gripped by the hand **16** of the slave arm **11**, and the object T is located, for example, over a production line.

(96) First, the operating mode setting module **37** determines whether the magnitude of the operating force f_m is included in a range exceeding a given first threshold $flim1$ (Step S1). The range exceeding the first threshold $flim1$ is one example of a limit equivalent range. The first threshold $flim1$ is a value set in advance based on a load permitted by the master arm **21**, and is a value set based on, for example, the maximum load which is detectable by the master-side force detector **22**, the load at which the master-side force detector **22** is not damaged, the load at which the joint of the master arm **21** is not damaged, and the load at which the link of the master arm **21** is not bent. In an initial state in which the operating force f_m is not applied to the master arm **21**, since the operating force f_m is zero, the operating mode setting module **37** determines that the magnitude of the operating force f_m is not included in the range exceeding the first threshold $flim1$, i.e., it does not exceed the first threshold $flim1$ (NO at Step S1), and sets the operating mode to the normal operating mode (Step S2).

(97) Then, in this initial state, if the slave arm **11** does not contact the environment, such as the object T, the reaction force f_s becomes zero and the difference between the operating force f_m and the reaction force f_s also becomes zero. Therefore, the target velocity vector vd calculated by the converting module **31** becomes a zero vector, and the position command value according to the slave operating command xs generated by the slave operating command generating module **51** based on the target velocity vector vd does not change. Therefore, the slave-side controller **14** maintains the current posture of the slave arm **11**. Moreover, the position command value according to the first temporary master operating command $xmt1$ does not change, and in the normal operating mode, the master-side controller **24** maintains the current posture of the master arm **21**

based on the first temporary master operating command x_{mt1} . Then, the operating mode setting module **37** again performs a determination according to Step **S1**.

(98) Next, when the operator **P** applies the operating force f_m in a direction in which the workpiece **W** is brought closer to the object **T**, i.e., applies the operating force f_m to the manipulation end **21a** of the master arm **21** downwardly, the converting module **31** calculates a downward target velocity vector v_d having the magnitude according to the operating force f_m by using Formula (1). Note that, in the state where the workpiece **W** does not contact the object **T**, the reaction force f_s is zero.

(99) Next, the slave operating command generating module **51** generates the slave operating command x_s based on the target velocity vector v_d , and sets the target position of the working end **11a** of the slave arm **11** below the current position. The slave-side controller **14** changes the posture of the slave arm **11** based on the slave operating command x_s so that the working end **11a** moves downwardly.

(100) Moreover, the first temporary master operating command generating module **52** generates the first temporary master operating command x_{mt1} based on the target velocity vector v_d , and updates the target position of the manipulation end **21a** of the master arm **21** to the position below the current position. When the magnitude of the operating force f_m is not included in the range exceeding the first threshold $flim1$, the state where the operating mode is set to the normal operating mode is maintained, and the master-side controller **24** changes the posture of the master arm **21** based on the first temporary master operating command x_{mt1} so that the manipulation end **21a** moves downwardly toward the target position.

(101) Thus, when the magnitude of the operating force f_m is not included in the range exceeding the given first threshold $flim1$, the working end **11a** of the slave arm **11** and the manipulation end **21a** of the master arm **21** move in the same direction simultaneously. Therefore, when the operator **P** moves the manipulation end **21a** of the master arm **21**, the operator **P** can acquire the sensation as if the working end **11a** of the slave arm **11** operates so as to follow the motion of the manipulation end **21a** of the master arm **21**.

(102) Then, when the working end **11a** of the slave arm **11** moves downwardly to cause the workpiece **W** to contact an upper end of the object **T** and push the workpiece **W** against the object **T**, the reaction force f_s according to the magnitude of the pushing force is detected by the slave-side force detector **12**. Then, from this state, even if the operator **P** applies the strong downward operating force f_m against the manipulation end **21a**, the reaction force f_s increases in proportion to the operating force f_m , the difference between the operating force f_m and the reaction force f_s becomes substantially zero, and the target velocity vector v_d calculated by the converting module **31** becomes the zero vector.

(103) At this time, the slave operating command generating module **51** generates the slave operating command x_s based on the target velocity vector v_d which is the zero vector regardless of the set operating mode, and sets the target position of the working end **11a** of the slave arm **11** to substantially the same position as the current position. The slave-side controller **14** maintains the current posture of the slave arm **11** based on the slave operating command x_s .

(104) Moreover, the first temporary master operating command generating module **52** also generates the first temporary master operating command x_{mt1} based on the target velocity vector v_d which is the zero vector, and sets the target position of the manipulation end **21a** of the master arm **21** to substantially the same position as the current position. Then, in the normal operating mode, the master-side controller **24** maintains the current posture of the master arm **21** based on the first temporary master operating command x_{mt1} , and operates the manipulation end **21a** of the master arm **21** so that the manipulation end **21a** resists the operating force f_m . Therefore, the reaction force f_s which acts on the working end **11a** of the slave arm **11** can be presented to the operator **P** through the manipulation end **21a**. Therefore, the operator **P** can perform the work while recognizing the reaction force f_s through the inner force sense of the operator **P**, when the working end **11a** contacts the environment. This work is, for example, to move the workpiece **W** in a

direction perpendicular to the reaction force while pushing the workpiece W against the object T to explore a position at which the through-hole Wa fits onto the object T. By recognizing the direction of the reaction force f_s , the operator P can recognize the direction of exploring the position at which the object T fits, i.e., the direction perpendicular to the reaction force f_s , and can perform the work efficiently.

(105) At this time, by the operation of the operator P, such as forcibly applying the downward operating force f_m to the manipulation end **21a** of the master arm **21**, if the operating mode setting module **37** determines that the magnitude of the operating force f_m is included in the range exceeding the first threshold f_{lim1} , i.e., the magnitude exceeds the first threshold f_{lim1} (YES at Step S1), it sets the operating mode to the informing operating mode (Step S3). Therefore, the master operating command setting module **36** sets the second temporary master operating command x_{mt2} to the master operating command x_m , and generates the master operating command x_m for moving the manipulation end **21a** in the direction of the operating force f_m .

(106) As described above, the second temporary master operating command generating module **53** generates the second temporary master operating command x_{mt2} based on the temporary target velocity vector v_{dt} calculated by the subconverting module **32**. Therefore, in the state where the operating mode is set to the informing operating mode, the master-side controller **24** changes the posture of the master arm **21** so that the manipulation end **21a** of the master arm **21** moves downwardly toward the target position based on the second temporary master operating command x_{mt2} .

(107) Moreover, as described above, the temporary target velocity vector v_{dt} is a velocity vector having the magnitude and the direction according to the operating force f_m detected by the master-side force detector **22**. Therefore, in the state where the operator P applies the strong downward operating force f_m against the manipulation end **21a**, the temporary target velocity vector v_{dt} becomes a downward vector with a large magnitude. Therefore, the target position of the second temporary master operating command x_{mt2} becomes a largely distant position below the current position. Therefore, the master-side controller **24** does not move the manipulation end **21a** until the magnitude of the operating force f_m exceeds the first threshold f_{lim1} , and then, when the magnitude of the operating force f_m is included in the range exceeding the first threshold f_{lim1} , it suddenly moves the manipulation end **21a** downwardly. That is, the operation of the manipulation end **21a** changes suddenly. Therefore, the operator P can be informed about the magnitude of the operating force f_m exceeding the first threshold f_{lim1} . Moreover, when the manipulation end **21a** moves in the direction in which the operator P applied the force, the load on the master arm **21** and the master-side force detector **22** can be reduced, and the damages to the master arm **21** and the master-side force detector **22** can be prevented.

(108) Further, since the manipulation end **21a** suddenly moves in the direction in which the operator P applied the force and the operation of the manipulation end **21a** changes suddenly, the operator P may be surprised, and, as a result, the operator P may be guided so that he/she weakens the operating force f_m .

(109) Moreover, the master operating command x_m is generated so that, as the magnitude of the operating force f_m (or an excess amount of the operating force f_m from the first threshold f_{lim1}) increases, the magnitude of the temporary target velocity vector v_{dt} becomes larger, and, as a result, the change in the moving velocity of the manipulation end **21a** increases. Therefore, the operator P can be guided about how much the operating force f_m is to be weakened. Moreover, the operator P can be surprised as much as the magnitude of the excessive operating force f_m . As a result, the operator P can be guided so as to appropriately weaken the operating force f_m .

Moreover, the manipulation end **21a** moves more quickly in the direction in which the operator P applied the force as the magnitude of the operating force f_m increases. Therefore, the load on the master arm **21** and the master-side force detector **22** can be reduced more appropriately, and the damages to the master arm **21** and the master-side force detector **22** can be prevented more

appropriately. Further, since the operating mode can be changed automatically from the normal operating mode to the informing operating mode, an emergency stop for protecting the robot system **100** can be avoided.

(110) Note that, in this embodiment, the master operating command x_m is generated so that the moving velocity of the manipulation end **21a** is increased as the magnitude of the operating force f_m increases. However, the present disclosure is not limited to this configuration. Alternatively, the master operating command x_m may be generated so that the moving velocity of the manipulation end **21a** is increased as an amount of change in the magnitude of the operating force per unit time increases.

(111) Note that the slave-side controller **14** controls the slave arm **11** based on the operating force f_m and the reaction force f_s , regardless of the set operating mode. For example, if the operator P weakens the operating force f_m , the target velocity vector v_d becomes an upward vector based on Formula (1), and the slave-side controller **14** controls the slave arm **11** to reduce the pushing force against the object T. Note that, when the operating mode is set to operating modes other than the normal operating mode, the slave-side controller **14** may suspend the operation of the slave arm **11**.

(112) Then, when the operating mode setting module **37** sets the informing operating mode at Step S3, it then determines whether the magnitude of the operating force f_m is included in an range of a second threshold $flim2$ or below (Step S4). The second threshold $flim2$ is a value of the first threshold $flim1$ or below, which is set in advance.

(113) Then, while the magnitude of the operating force f_m is not included in the range of the second threshold $flim2$ or below, i.e., while determining that it exceeds the second threshold $flim2$ (NO at Step S4), the operating mode setting module **37** repeatedly determines whether the magnitude of the operating force f_m is included in the range of the second threshold $flim2$ or below.

(114) Then, when the operator P weakens the operating force f_m and the magnitude of the operating force f_m becomes the second threshold $flim2$ or below, the operating mode setting module **37** determines that the magnitude of the operating force f_m is included in the range of the second threshold $flim2$ or below (YES at Step S4), and sets the operating mode to the resuming operating mode (Step S5).

(115) As described above, the third temporary master operating command generating module **54** generates the third temporary master operating command x_{mt3} based on the current position of the manipulation end **21a** and the first temporary master operating command x_{mt1} generated by the first temporary master operating command generating module **52**. Therefore, in the state where the operating mode is set to the resuming operating mode, the master-side controller **24** moves the manipulation end **21a** of the master arm **21** toward the target position of the first temporary master operating command x_{mt1} based on the third temporary master operating command x_{mt3} .

(116) Next, the operating mode setting module **37** determines whether the manipulation end **21a** is located at the target position according to the first temporary master operating command x_{mt1} generated by the first temporary master operating command generating module **52**, i.e., reaches the target position (Step S6). This determination is performed by determining whether the current position of the manipulation end **21a** is equal to the target position of the first temporary master operating command x_{mt1} . Then, if the operating mode setting module **37** determines that the manipulation end **21a** is not located at the target position according to the first temporary master operating command x_{mt1} (NO at Step S6), it again performs Step S5, where it maintains the state where the operating mode is set to the resuming operating mode.

(117) Then, if the operating mode setting module **37** determines that the manipulation end **21a** is located at the target position according to the first temporary master operating command x_{mt1} , it performs Step S2, where it sets and resumes the operating mode to the normal operating mode. Therefore, the working end **11a** of the slave arm **11** and the manipulation end **21a** of the master arm **21** are again configured to move in the same direction simultaneously. Moreover, the operating

mode can be automatically resumed to the normal operating mode, and an interruption of the work can be avoided.

(118) As described above, the robot system **100** sets the operating mode to the informing operating mode when the operating mode setting module **37** determines that the magnitude of the operating force f_m is included in the range exceeding the first threshold $flim1$, and it generates the master operating command x_m so that the manipulation end **21a** is moved in the direction of the operating force f_m . Therefore, the robot system **100** can inform the operator P that the master arm **21** is overloaded. Moreover, the robot system **100** can operate the master arm **21** so that the load slips off the master arm **21**. Therefore, the damage to the master arm **21** can be prevented.

Modification 1 of Embodiment 1

(119) Below, a configuration and operation of Modification 1 of the embodiment is described focusing on the difference from Embodiment 1. FIG. **4** is a block diagram schematically illustrating one example of a configuration of a control system of a robot system **200** according to Modification 1 of Embodiment 1.

(120) In this modification, the robot system **200** is further provided with an informing part **204** which performs a notification by using sense information perceivable by the perception of the operator P. For example, the perception of the operator P is at least any one of the senses, such as a tactile sense, an inner force sense, an acoustic sense, a sense of smell, and a visual sense. Moreover, the informing part **204** includes a vibrator, a speaker, a display, and a signaling lamp. Moreover, in this modification, the system controller **3** further includes an informing part controlling module **231**. The informing part controlling module **231** is a functional block implemented by a processor (not illustrated) executing a given control program. Note that, in FIG. **4**, although the subconverting module **32**, the second temporary master operating command generating module **53**, and the third temporary master operating command generating module **54** are not illustrated, these functional blocks may also be included.

(121) In the informing operating mode, the informing part controlling module **231** controls the informing part **204** to perform the notification to the operator P. Therefore, it can inform the operator P that the magnitude of the operating force f_m exceeds the first threshold $flim1$.

(122) Moreover, the informing part controlling module **231** controls the informing part **204** so that the intensity of the sense information becomes stronger as the operating force f_m increases. Controlling the informing part **204** so as to make the intensity of the sense information stronger is, for example, increasing the sound volume, changing the pitch of sound, changing the tone, increasing the vibration to the manipulation end **21a**, increasing the brightness, increasing a display area of the display unit. Thus, the operator P may be surprised as much as the magnitude of the excessive operating force f_m , and, as a result, the operator P may be guided so that he/she appropriately weakens the operating force f_m .

Embodiment 2

(123) A robot system **100A** according to Embodiment 2 is described. Below, Embodiment 2 is described focusing on the difference from Embodiment 1 and Modification 1, and description of the same matters as Embodiment 1 and Modification 1 is suitably omitted.

(124) FIG. **5** is a block diagram schematically illustrating one example of a configuration of a control system of the robot system **100A** according to Embodiment 2. As illustrated in FIG. **5**, the robot system **100A** includes the slave unit **1**, the master unit **2**, and a system controller **3A**.

(125) The system controller **3A** generates the slave operating command x_s and the master operating command x_m based on the operating force f_m detected by the master-side force detector **22**, and the reaction force f_s detected by the slave-side force detector **12**, at every given control period. Moreover, the system controller **3A** generates each command so that the target position of the slave operating command x_s and the target position of the master operating command x_m have a given correlation.

(126) The system controller **3** includes a converting module **310**, a slave operating command

generating module **320**, a master operating command generating module **330**, a notifying range setting module **340**, and a repulsive force setting module **350**. The converting module **310**, the slave operating command generating module **320**, the master operating command generating module **330**, the notifying range setting module **340**, and the repulsive force setting module **350** are functional blocks implemented by a processor (not illustrated) executing a given control program.

(127) The converting module **310** calculates a target velocity vector v_d based on a resultant force of the operating force f_m detected by the master-side force detector **22**, the reaction force f_s detected by the slave-side force detector **12**, and a repulsive force f_r set by the repulsive force setting module **350**. In more detail, the converting module **310** calculates the target velocity vector v_d defining the moving directions and the moving velocities of the working end **11a** and the manipulation end **21a** based on a resultant force obtained by adding the repulsive force f_r to a difference between the operating force f_m and the reaction force f_s , by using the following Formula (3).

$$(128) \quad m \times \dot{v}_d + c_v \times v_d = f_m - f_s + f_r \quad (3)$$

Note that, “m” is a given mass value, and “c.sub.v” is a given coefficient of viscosity.

(129) As illustrated in Formula (3), the converting module **310** associates the operating force f_m with the reaction force f_s by calculating the difference between the operating force f_m and the reaction force f_s , and treats the reaction force f_s as a reaction force against the operating force f_m .

(130) The function of the slave operating command generating module **320** is the same as the function of the slave operating command generating module **51** of Embodiment 1.

(131) The master operating command generating module **330** generates the master operating command x_m based on the target velocity vector v_d so that the manipulation end **21a** is moved at the speed according to the value of the target velocity vector v_d , and outputs it to the master-side controller **24**. The master-side controller **24** controls the master arm actuator **23** based on the master operating command x_m and operates the manipulation end **21a** of the master arm **21** so that the manipulation end **21a** resists the operating force f_m to present the operator P the reaction force f_s which acts on the working end **11a** of the slave arm **11** and the repulsive force f_r set by the repulsive force setting module **350**. Therefore, the operator P can perform the work while recognizing the reaction force f_s through the inner force sense of the operator P, when the working end **11a** contacts the environment. Moreover, the operator P can perform the work while recognizing the repulsive force f_r through the inner force sense of the operator P, when the working end **11a** enters into a notifying range A3. The notifying range A3 is one example of the limit equivalent range.

(132) FIG. **6** is a view illustrating one example of setting of an operating range A1, an entering prohibited range A2, and the notifying range A3 which are set by the notifying range setting module **340** of the robot system **100A** according to Embodiment 2.

(133) As illustrated in FIG. **6**, the notifying range setting module **340** sets the notifying range A3 which spreads toward the given operating range A1 from the limit of the operating range A1, i.e., a boundary B (illustrated by a one-dot chain line in FIG. **6**). That is, the notifying range A3 spreads inward of the operating range A1. In detail, the notifying range setting module **340** sets the given operating range A1, the entering prohibited range A2 other than operating range A1, and the notifying range A3 which spreads toward the operating range A1 from the limit of the given operating range A1, i.e., the boundary B between the operating range A1 and the entering prohibited range A2, by a given distance. That is, the notifying range A3 is a range included in the operating range A1, and is set so as to overlap with the operating range A1. The settings of the operating range A1, the entering prohibited range A2, and the notifying range A3 are stored in advance in a memory (not illustrated). The notifying range setting module **340** sets these ranges A1-A3 by reading the settings of the ranges A1-A3 from the memory. The function of the memory is implemented by the storage device described above. The operating range A1 is set so as to

exclude, for example, a space where the work is not performed, such as a space where an obstacle exists and a space distant from the object T.

(134) As illustrated in FIG. 5, when the repulsive force setting module **350** determines that the target position of the working end **11a** of the slave operating command **xs** is located in the notifying range **A3**, it sets the repulsive force **fr** which has a direction separating from the limit of the operating range **A1** and acts on the working end **11a**. In this embodiment, the repulsive force setting module **350** first calculates a distance **d** in the normal direction of the boundary **B** between the target position of the slave operating command **xs** and the boundary **B**. Then, the repulsive force setting module **350** calculates the repulsive force **fr** by using the following Formula (4).

$$(135) \quad f_r = (-kd + a)i \quad (4)$$

Note that, “**k**” is a given coefficient, “**a**” is a repulsive force which acts on the working end when the working end locates on the boundary, and “**i**” is a unit normal vector of the boundary **B** to the operating range side.

(136) As illustrated in this Formula (4), the repulsive force setting module **350** calculates the repulsive force **fr** so that the magnitude of the repulsive force **fr** becomes larger as the distance between the target position of the working end **11a** of the slave operating command **xs** and the limit of the operating range **A1** decreases. Note that a coefficient **k** in Formula (4) is a value set so as to be a repulsive force **fr** favorable for the operator **P**.

Example Operation

(137) Next, one example of operation of the robot system **100A** is described. FIGS. 7 and 8 are views illustrating one example of operation of the robot system **100A** according to Embodiment 2. For example, as illustrated in FIGS. 7 and 8, in this example operation, the operator **P** performs a work in which the workpiece **W** is assembled to the object **T** by using the robot system **100A**.

(138) First, as illustrated in FIG. 6, the notifying range setting module **340** sets the notifying range **A3**.

(139) Next, the converting module **310** calculates the target velocity vector **vd** at every given control period. In a state where the working end **11a** is located in the operating range **A1** other than the notifying range **A3**, the master arm **21** is not operated, and the slave arm **11** is not in contact with the environment, such as the object **T**, all of the operating force **fm**, the reaction force **fs**, and the repulsive force **fr** become zero, and the resultant force of the operating force **fm**, the reaction force **fs**, and the repulsive force **fr** becomes zero. Therefore, the target velocity vector **vd** calculated by the converting module **310** becomes the zero vector, and the slave operating command generating module **320** sets the next target position according to the slave operating command **xs** as the same position as the current position based on the target velocity vector **vd**. Then, in the subsequent control period, the slave-side controller **14** maintains the current posture of the slave arm **11** based on the slave operating command **xs**. Moreover, similarly to the slave operating command generating module **320**, the master operating command generating module **330** sets the next target position, and the master-side controller **24** maintains the current posture of the master arm **21** similarly to the slave-side controller **14**.

(140) Next, as illustrated in FIG. 7, when the operator **P** applies the operating force **fm** in the direction the workpiece **W** is brought closer to the object **T**, i.e., applies the downward operating force **fm** to the manipulation end **21a** of the master arm **21**, the converting module **310** calculates the downward target velocity vector **vd** having the magnitude according to the operating force **fm** by using Formula (3). Note that, in the state where the workpiece **W** does not contact the object **T**, the reaction force **fs** is zero. Then, the slave operating command generating module **320** sets the next target position of the working end **11a** of the slave operating command **xs** below the current position so that the working end **11a** is moved downwardly at the speed according to the downward target velocity vector **vd**. Then, in the subsequent control period, the slave-side controller **14** changes the posture of the slave arm **11** so that the working end **11a** is moved downwardly based

on the slave operating command x_s . Similarly, the master-side controller **24** changes the posture of the master arm **21** based on the master operating command x_m so that the manipulation end **21a** is moved downwardly.

(141) Thus, the working end **11a** of the slave arm **11** and the manipulation end **21a** of the master arm **21** move in the same direction simultaneously. Therefore, when the operator P moves the manipulation end **21a** of the master arm **21**, the operator P can feel as if the working end **11a** of the slave arm **11** operates so as to follow the motion of the manipulation end **21a** of the master arm **21**.

(142) Then, when the working end **11a** of the slave arm **11** moves downwardly, the workpiece W contacts the upper end of the object T, and when the workpiece W is pushed against the object T, the reaction force f_s according to the magnitude of the pushing force is detected by the slave-side force detector **12**. Then, from this state, even when the operator P applies the strong downward operating force f_m against the manipulation end **21a**, the reaction force f_s increases in proportion to the operating force f_m , and the difference between the operating force f_m and the reaction force f_s becomes substantially zero, and therefore, the target velocity vector v_d calculated by the converting module **310** becomes the zero vector. Therefore, the slave operating command generating module **320** sets the next target position according to the slave operating command x_s as the same position as the current position based on the target velocity vector v_d . Then, in the subsequent control period, the slave-side controller **14** maintains the current posture of the slave arm **11** based on the slave operating command x_s . Similarly to the slave operating command generating module **320**, the master operating command generating module **330** sets the next target position, and the master-side controller **24** maintains the current posture of the master arm **21** similarly to the slave-side controller **14**.

(143) Thus, when the workpiece W is pushed against the object T, the master-side controller **24** maintains the current posture of the master arm **21** based on the master operating command x_m , operates the manipulation end **21a** so that the manipulation end **21a** of the master arm **21** resists the operating force f_m , and changes the operation of the manipulation end **21a**. Therefore, the reaction force f_s which acts on the working end **11a** of the slave arm **11** can be presented to the operator P through the manipulation end **21a** of the master arm **21**. Therefore, the operator P can perform the work while recognizing the reaction force f_s through the inner force sense of the operator P, when the working end **11a** contacts the environment. This work is a work in which, for example, in the state illustrating in FIG. 7, the workpiece W is moved in the direction perpendicular to the reaction force while the workpiece W is pushed against the object T to explore the position at which the through-hole W_a and the object T fit. The operator P can perform the work efficiently because he/she can recognize the exploring direction of the fitting position of the object T (i.e., the direction which intersects perpendicular to the reaction force f_s) by recognizing the direction of the reaction force f_s .

(144) Meanwhile, as illustrated in FIG. 8, the operator P moves the working end **11a** of the slave arm **11** downwardly at the location where the object T does not exist in the plan view, and when the workpiece W enters into the notifying range A3 without being pushed against the object T, the repulsive force setting module **350** determines that the target position of the working end **11a** of the slave operating command x_s is located inside the notifying range A3, and calculates the repulsive force f_r by using Formula (4). Then, the converting module **310** calculates the target velocity vector v_d having the magnitude according to the resultant force of the operating force f_m and the repulsive force f_r by using Formula (3). Note that, in the state illustrated in FIG. 8 where the workpiece W does not contact the object T, the reaction force f_s is zero.

(145) At this time, in FIG. 8, as for normal direction components at the boundary B between the repulsive force f_r and the operating force f_m , the normal direction component of the repulsive force f_r is oriented to the opposite side of the normal direction component of the operating force f_m (opposite sign). Therefore, as for the resultant force acquired by synthesizing the repulsive force f_r with the operating force f_m , the component of the resultant force toward the boundary B becomes

smaller, and the component of the target velocity vector v_d toward the boundary B (the component of the target velocity vector v_d in the normal direction of the boundary B) also becomes smaller. (146) Then, the slave operating command generating module **320** sets the next target position of the working end **11a** of the slave operating command x_s as the position below the current position based on the target velocity vector v_d so that the working end **11a** is moved downwardly at a speed slower than the speed before entering into the notifying range A3. Then, in the subsequent control period, the slave-side controller **14** changes the posture of the slave arm **11** based on the slave operating command x_s so that the working end **11a** is moved downwardly. Similarly to the slave operating command generating module **320**, the master operating command generating module **330** sets the next target position, and similarly to the slave-side controller **14**, the master-side controller **24** changes the posture of the master arm **21** based on the master operating command x_m so that the manipulation end **21a** is moved downwardly. Therefore, the system controller **3A** can give the operator P such a sensation that the operation of the working end **11a** and the manipulation end **21a** became heavier, and can notify the operator P about an approach to the limit of the operating range A1.

(147) Note that, as the distance between the target position of the working end **11a** of the slave operating command x_s and the limit of the operating range A1 decreases, the magnitude of the repulsive force f_r set by the repulsive force setting module **350** becomes larger, the target velocity vector v_d becomes smaller, and the speeds of the working end **11a** and the manipulation end **21a** become slower. Further, when the repulsive force f_r exceeds the operating force f_m , the sign of the target velocity vector v_d is reversed, and the working end **11a** and the manipulation end **21a** are moved so that they are pushed back. Thus, since the direction of the repulsive force f_r turns to the direction separating from the limit of the operating range A1, and the magnitude of the repulsive force f_r becomes larger as the distance between the target position of the working end **11a** of the slave operating command x_s and the limit of the operating range A1 decreases, the operator P can be guided intelligibly about the direction separating from the boundary B.

(148) Then, the slave operating command generating module **320** regulates the entering of the working end **11a** into the entering prohibited range A2, when the next target position of the working end **11a** reaches the boundary B.

(149) Thus, when the workpiece W contacts the object T, the operator P becomes suddenly impossible to move the manipulation end **21a** in the direction corresponding to the direction of pushing the workpiece W against the object T. On the other hand, when the working end **11a** enters into the notifying range A3, the operator P perceives the operation of the manipulation end **21a** gradually heavier as it approaches the limit of the operating range A1. Therefore, the operator P can easily distinguish whether the working end **11a** contacts the workpiece W, or whether the working end **11a** approaches the limit of the operating range A1. Therefore, for example, the operator P can be prevented from erroneously recognizing that the working end **11a** is in contact with the workpiece W, in spite of being in the state where the working end **11a** reaches the limit of the operating range A1 and the operations of the working end **11a** and the manipulation end **21a** are regulated. Thus, a wrong work (assembly at a wrong location) can be prevented, and the work efficiency can be improved.

Modification 2 of Embodiment 2

(150) Below, a configuration and operation of Modification 2 of Embodiment 2 are described focusing on the difference from Embodiment 2. FIG. **9** is a block diagram schematically illustrating one example of a configuration of a control system of a robot system **200A** according to Modification 2 of Embodiment 2.

(151) In this modification, the robot system **200A** is also further provided with the informing part **204** similarly to Modification 1 of Embodiment 1. Moreover, in this modification, the system controller **3A** is also further provided with an informing part controlling module **2310** similarly to Modification 1 of Embodiment 1. Note that, in FIG. **9**, although the repulsive force setting module

350 is not illustrated, it may be included as a functional block.

(152) When the informing part controlling module **2310** determines that the target position of the working end **11a** of the slave operating command **xs** is located in the notifying range **A3**, it controls the informing part **204** to inform it to the operator **P**. Thus, it can inform the operator **P** about the approaching to the limit of the operating range **A1** (i.e., the boundary **B**).

(153) Moreover, the informing part controlling module **2310** controls the informing part **204** so that the intensity of the sense information becomes stronger as the distance between the target position of the working end **11a** of the slave operating command **xs** and the boundary **B** decreases. Therefore, the operator **P** can be guided intelligibly about the direction separating from the boundary **B**.

(154) Note that, in Embodiment 2 and Modification 2, the operating range **A1** is set for the working end **11a**, and is set as a range which permits operation of the working end **11a** in this range. The present disclosure is not limited to this configuration, but, alternatively, the operating range **A1** may be set for the manipulation end **21a** and may be set as a range which permits operation of the manipulation end **21a** in this range. In this case, the system controller **3A** controls the system to inform the operator **P** that the manipulation end **21a** approaches the limit of the operating range **A1**.

(155) Moreover, the operating range may be set for each of the working end **11a** and the manipulation end **21a**. In this case, the system controller **3A** may control the system to inform the operator **P** at least either one of that the working end **11a** approaches the limit of that operating range or that the manipulation end **21a** approaches the limit of the operating range.

(156) Moreover, in Embodiment 2 and Modification 2, the converting module **310** calculates the target velocity vector **vd** based on the resultant force of the operating force **fm**, the reaction force **fs**, and the repulsive force **fr**, by using Formula (3). The present disclosure is not limited to this configuration, but, alternatively, the converting module **310** may change the coefficient of viscosity **cv** of Formula (3) so that the magnitude of the coefficient of viscosity **cv** of Formula (3) becomes larger as the distance between the target position of the working end **11a** of the slave operating command **xs** and the limit of the operating range **A1** decreases, without including the repulsive force **fr** in the resultant force.

(157) It is apparent for the person skilled in the art that many improvements and other embodiments of the present disclosure are possible from the above description. Therefore, the above description is to be interpreted only as illustration, and it is provided in order to teach the person skilled in the art the best mode that implements the present disclosure. The details of the structures and/or the functions may be changed substantially, without departing from the present disclosure.

DESCRIPTION OF REFERENCE CHARACTERS

(158) **W** Workpiece **T** Object **P** Operator **1** Slave Unit **2** Master Unit **3, 3A** System Controller **11a** Working End **11** Slave Arm **12** Slave-side Force Detector **13** Slave Arm Actuator **14** Slave-side Controller **21** Master Arm **21a** Manipulation End **22** Master-side Force Detector **23** Master Arm Actuator **24** Master-side Controller **100, 100A, 200, 200A** Robot System

Claims

1. A robot system, comprising: a slave arm having a working end; a master arm having a manipulation end into which content of manipulation is inputted, the content of manipulation comprising a direction and an operating force input to the manipulation end; and a system controller configured to perform operations comprising generating a slave operating command for defining a target position of the working end based on the content of manipulation inputted into the manipulation end, wherein the slave operating command comprises a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, and the system controller performs operations further comprising determining that the operating force

exceeds a threshold of the limit equivalent range, and processing to give a perception through the manipulation end by applying a force to the manipulator end in the same direction as the operating force.

2. The robot system of claim 1, wherein the system controller is further configured to perform operations comprising generating the master operating command based on the content of manipulation inputted into the manipulation end the master arm and a master operating command for defining a target position of the manipulation end, and the master operating command is generated for increasing a change in a moving velocity of the manipulation end as the operating force increases.

3. The robot system of claim 1, wherein the system controller is configured to perform operations further comprising determining that a magnitude of the operating force applied to the manipulation end as the content of manipulation is included in a range exceeding a third threshold as the limit equivalent range, and performing control to provide the perception.

4. The robot system of claim 3, wherein the system controller is configured to perform operations further comprising performing control to provide the perception by controlling an intensity of the perception such that the perception becomes stronger as the operating force becomes larger.

5. The robot system of claim 1, wherein the system controller is configured to perform operations further comprising determining that the target position of the working end of the slave arm based on the slave operating command is located in a notifying range, and performing control to provide the perception.

6. The robot system of claim 5, wherein the system controller is configured to perform operations further comprising performing control to provide the perception by controlling an intensity of the perception such that the perception becomes stronger as a distance between the target position of the working end of the slave operating command and the limit of the operating range becomes smaller.

7. A method of controlling a robot system comprising a slave arm and a master arm, the method comprising: outputting a slave operating command for defining a target position of a working end of the slave arm to a slave-side controller configured to control an actuator of the slave arm based on the slave operating command, the slave operating command generated based on content of manipulation inputted into a manipulation end of the master arm, the content of manipulation comprising a direction and an operating force input to the manipulation end, wherein the slave operating command comprises a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, determining that the operating force exceeds a threshold of the limit equivalent range, and controlling the manipulation end of the master arm to give a perception through the manipulation end by applying a force to the manipulator end in the same direction as the operating force.

8. The method of claim 7, further comprising setting a notifying range that spreads from a limit of a given operating range to an area within the given operating range on the given operating range side as the limit equivalent range, wherein, based on determining that the target position of the working end of the slave operating command is located in the notifying range, performing a notification by outputting a command to control the manipulation end to provide the perception.

9. A robot system, comprising: a slave arm having a working end; a master arm having a manipulation end into which content of manipulation is inputted, the content of manipulation comprising a direction and an operating force input to the manipulation end; and a system controller configured to perform operations comprising generating a slave operating command for defining a target position of the working end based on the content of manipulation inputted into the manipulation end, wherein: the slave operating command comprises a limit equivalent range corresponding to a limit of operation of at least one of the slave arm and the master arm, the system controller performs operations further comprising: determining that the operating force exceeds a threshold of the limit equivalent range; processing to give a perception through the manipulation

end by applying a force to the manipulator end; generating, based on the operating force and a reaction force acting on the working end or a workpiece held by the working end, the slave operating command and the master operating command for moving the manipulation end in a moving direction corresponding to a moving direction of the working end of the slave operating command; based on determining that the magnitude of the operating force exceeding a first threshold as the limit equivalent range, generating the master operating command for providing the perception by applying the force and moving the manipulation end in the direction of the operating force; generating a first temporary master operating command for moving the manipulation end in a moving direction corresponding to a moving direction of the working end commanded by a slave operating command generated based on the operating force and the reaction force; generating a second temporary master operating command based on the operating force; and setting the first temporary master operating command to the master operating command in a normal operating mode, and setting the second temporary master operating command to the master operating command in an informing operating mode; and based on the magnitude of the operating force exceeding the first threshold, setting the operating mode to the informing operating mode.
