

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400788
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Diekhans; Tobias et al.

Device for inductive energy transmission in a human body and use of the device

Abstract

The invention relates to a device (10) for inductive energy transmission into a human body (1), having a transmitter coil (24) and/or a receiver coil (14) having a first magnetic core (26) and a resonance or choke coil (16, 34) having a second magnetic core (32), wherein the first magnetic core (26) forms a part of the second magnetic core (32).

Inventors: Diekhans; Tobias (Stuttgart, DE), Araujo; Samuel Vasconcelos (Esslingen, DE), Jiptner; Michael (Besigheim, DE)

Applicant: KARDION GMBH (Stuttgart, DE)

Family ID: 1000008778429

Assignee: Kardion GmbH (Stuttgart, DE)

Appl. No.: 18/349710

Filed: July 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230352236 A1	Nov. 02, 2023

Related U.S. Application Data

continuation parent-doc US 17090355 20201105 US 11699551 child-doc US 18349710

Publication Classification

Int. Cl.: H01F38/14 (20060101); A61M60/873 (20210101); A61M60/876 (20210101); H01F27/24 (20060101); H02J50/12 (20160101)

U.S. Cl.:

CPC H01F38/14 (20130101); A61M60/873 (20210101); A61M60/876 (20210101); H01F27/24 (20130101); H02J50/12 (20160201);

Field of Classification Search

CPC: H01F (38/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2254698	12/1940	Hansen, Jr.	N/A	N/A
3085407	12/1962	Tomlinson	N/A	N/A
3614181	12/1970	Meeks	N/A	N/A
3645268	12/1971	Capote	N/A	N/A
3747998	12/1972	Klein et al.	N/A	N/A
3790878	12/1973	Brokaw	N/A	N/A
3807813	12/1973	Milligan	N/A	N/A
4441210	12/1983	Hochmair et al.	N/A	N/A
4888009	12/1988	Lederman et al.	N/A	N/A
4888011	12/1988	Kung et al.	N/A	N/A
4896754	12/1989	Carlson et al.	N/A	N/A
5000177	12/1990	Hoffmann et al.	N/A	N/A
5195877	12/1992	Kletschka	N/A	N/A
5289821	12/1993	Swartz	N/A	N/A
5443503	12/1994	Yamane	N/A	N/A
5599173	12/1996	Chen et al.	N/A	N/A
5613935	12/1996	Jarvik	N/A	N/A
5629661	12/1996	Ooi et al.	N/A	N/A
5690674	12/1996	Diaz	N/A	N/A
5702430	12/1996	Larson, Jr. et al.	N/A	N/A
5713954	12/1997	Rosenberg et al.	N/A	N/A
5766207	12/1997	Potter et al.	N/A	N/A
5814900	12/1997	Esser	307/104	H04B 5/00
5843141	12/1997	Bischoff et al.	N/A	N/A
5888242	12/1998	Antaki et al.	N/A	N/A
6053873	12/1999	Govari et al.	N/A	N/A
6058958	12/1999	Benkowski et al.	N/A	N/A
6149405	12/1999	Abe et al.	N/A	N/A
6212430	12/2000	Kung et al.	N/A	N/A
6224540	12/2000	Lederman et al.	N/A	N/A
6254359	12/2000	Aber	N/A	N/A
6264601	12/2000	Jassawalla et al.	N/A	N/A
6324430	12/2000	Zarinetchi et al.	N/A	N/A

6324431	12/2000	Zarinetchi et al.	N/A	N/A
6361292	12/2001	Chang et al.	N/A	N/A
6366817	12/2001	Kung	N/A	N/A
6389318	12/2001	Zarinetchi et al.	N/A	N/A
6398734	12/2001	Cimochowski et al.	N/A	N/A
6400991	12/2001	Kung	N/A	N/A
6442434	12/2001	Zarinetchi et al.	N/A	N/A
6445956	12/2001	Laird et al.	N/A	N/A
6471713	12/2001	Vargas et al.	N/A	N/A
6496733	12/2001	Zarinetchi et al.	N/A	N/A
6508756	12/2002	Kung et al.	N/A	N/A
6516227	12/2002	Meadows et al.	N/A	N/A
6527698	12/2002	Kung et al.	N/A	N/A
6530876	12/2002	Spence	N/A	N/A
6540658	12/2002	Fasciano et al.	N/A	N/A
6553263	12/2002	Meadows et al.	N/A	N/A
6561975	12/2002	Pool et al.	N/A	N/A
6592620	12/2002	Lancisi et al.	N/A	N/A
6979338	12/2004	Loshakove et al.	N/A	N/A
7062331	12/2005	Zarinetchi et al.	N/A	N/A
7070398	12/2005	Olsen et al.	N/A	N/A
7155291	12/2005	Zarinetchi et al.	N/A	N/A
7160243	12/2006	Medvedev	N/A	N/A
7338521	12/2007	Antaki et al.	N/A	N/A
7513864	12/2008	Kantrowitz et al.	N/A	N/A
7520850	12/2008	Brockway	N/A	N/A
7762941	12/2009	Jarvik	N/A	N/A
7794384	12/2009	Sugiura et al.	N/A	N/A
7819916	12/2009	Yaegashi	N/A	N/A
7942805	12/2010	Shambaugh, Jr.	N/A	N/A
7959551	12/2010	Jarvik	N/A	N/A
8012079	12/2010	Delgado, III	N/A	N/A
8075472	12/2010	Zilbershlag et al.	N/A	N/A
8088059	12/2011	Jarvik	N/A	N/A
8231519	12/2011	Reichenbach et al.	N/A	N/A
8461817	12/2012	Martin et al.	N/A	N/A
8489200	12/2012	Zarinetchi et al.	N/A	N/A
8608635	12/2012	Yomtov et al.	N/A	N/A
8612002	12/2012	Faltys et al.	N/A	N/A
8620447	12/2012	D'Ambrosio et al.	N/A	N/A
8766788	12/2013	D'Ambrosio	N/A	N/A
8827890	12/2013	Lee et al.	N/A	N/A
8862232	12/2013	Zarinetchi et al.	N/A	N/A
8870739	12/2013	LaRose et al.	N/A	N/A
8900114	12/2013	Tansley et al.	N/A	N/A
8961389	12/2014	Zilbershlag	N/A	N/A
9002468	12/2014	Shea et al.	N/A	N/A
9002469	12/2014	D'Ambrosio	N/A	N/A
9071182	12/2014	Yoshida et al.	N/A	N/A
9220826	12/2014	D'Ambrosio	N/A	N/A

9283314	12/2015	Prasad et al.	N/A	N/A
9381286	12/2015	Spence et al.	N/A	N/A
9440013	12/2015	Dowling et al.	N/A	N/A
9456898	12/2015	Barnes et al.	N/A	N/A
9486566	12/2015	Siess	N/A	N/A
9492600	12/2015	Strueber et al.	N/A	N/A
9539094	12/2016	Dale et al.	N/A	N/A
9561362	12/2016	Malinowski	N/A	N/A
9569985	12/2016	Alkhatib et al.	N/A	N/A
9592397	12/2016	Hansen et al.	N/A	N/A
9603984	12/2016	Romero et al.	N/A	N/A
9616107	12/2016	VanAntwerp et al.	N/A	N/A
9713701	12/2016	Sarkar et al.	N/A	N/A
9717831	12/2016	Schuermann	N/A	N/A
9724083	12/2016	Quadri et al.	N/A	N/A
9800172	12/2016	Leabman	N/A	N/A
9833314	12/2016	Corbett	N/A	N/A
9833611	12/2016	Govea et al.	N/A	N/A
9848899	12/2016	Sliwa et al.	N/A	N/A
9974894	12/2017	Morello	N/A	N/A
10143571	12/2017	Spence et al.	N/A	N/A
10463508	12/2018	Spence et al.	N/A	N/A
10732583	12/2019	Rudser	N/A	N/A
10944293	12/2020	Nakao	N/A	N/A
11000282	12/2020	Schuelke et al.	N/A	N/A
11056878	12/2020	Gao et al.	N/A	N/A
11065437	12/2020	Aber et al.	N/A	N/A
11103715	12/2020	Fort	N/A	N/A
11110265	12/2020	Johnson	N/A	N/A
11179559	12/2020	Hansen	N/A	N/A
11224737	12/2021	Petersen et al.	N/A	N/A
11291826	12/2021	Tuval et al.	N/A	N/A
11316371	12/2021	Partovi et al.	N/A	N/A
11317988	12/2021	Hansen et al.	N/A	N/A
11344717	12/2021	Kallenbach et al.	N/A	N/A
11351359	12/2021	Clifton et al.	N/A	N/A
11351360	12/2021	Rudser et al.	N/A	N/A
11368081	12/2021	Vogt et al.	N/A	N/A
11369785	12/2021	Callaway et al.	N/A	N/A
11369786	12/2021	Menon et al.	N/A	N/A
11389641	12/2021	Nguyen et al.	N/A	N/A
11406483	12/2021	Wirbisky et al.	N/A	N/A
11406520	12/2021	Lam	N/A	N/A
11406802	12/2021	DeGraaf et al.	N/A	N/A
11413443	12/2021	Hodges et al.	N/A	N/A
11413444	12/2021	Nix et al.	N/A	N/A
11439806	12/2021	Kimball et al.	N/A	N/A
11471692	12/2021	Aghassian et al.	N/A	N/A
11497906	12/2021	Grace et al.	N/A	N/A
11517737	12/2021	Struthers et al.	N/A	N/A

11517738	12/2021	Wisniewski	N/A	N/A
11517740	12/2021	Agarwa et al.	N/A	N/A
11529508	12/2021	Jablonsk et al.	N/A	N/A
11583671	12/2022	Nguyen et al.	N/A	N/A
11596727	12/2022	Siess et al.	N/A	N/A
11602624	12/2022	Siess et al.	N/A	N/A
11682924	12/2022	Hansen et al.	N/A	N/A
11689057	12/2022	Hansen	N/A	N/A
11699551	12/2022	Diekhans et al.	N/A	N/A
11745005	12/2022	Delgado, III	N/A	N/A
11752354	12/2022	Stotz et al.	N/A	N/A
11804767	12/2022	Vogt et al.	N/A	N/A
11881721	12/2023	Araujo et al.	N/A	N/A
11996699	12/2023	Vasconcelos	N/A	N/A
		Araujo et al.		
12102835	12/2023	Stotz et al.	N/A	N/A
2001/0016686	12/2000	Okada et al.	N/A	N/A
2002/0177324	12/2001	Metzler	N/A	N/A
2003/0040765	12/2002	Breznock	N/A	N/A
2003/0125766	12/2002	Ding	N/A	N/A
2003/0130581	12/2002	Salo et al.	N/A	N/A
2004/0167410	12/2003	Hettrick	N/A	N/A
2005/0006083	12/2004	Chen et al.	N/A	N/A
2005/0107658	12/2004	Brockway	N/A	N/A
2005/0107847	12/2004	Gruber et al.	N/A	N/A
2006/0004423	12/2005	Boveja et al.	N/A	N/A
2006/0190036	12/2005	Wendel et al.	N/A	N/A
2006/0196277	12/2005	Allen et al.	N/A	N/A
2007/0129767	12/2006	Wahlstrand	N/A	N/A
2007/0282209	12/2006	Lui et al.	N/A	N/A
2008/0015481	12/2007	Bergin et al.	N/A	N/A
2008/0079392	12/2007	Baarman et al.	N/A	N/A
2008/0082005	12/2007	Stern et al.	N/A	N/A
2008/0211455	12/2007	Park et al.	N/A	N/A
2008/0266922	12/2007	Mumtaz et al.	N/A	N/A
2009/0010462	12/2008	Ekchian et al.	N/A	N/A
2009/0024042	12/2008	Nunez et al.	N/A	N/A
2009/0134711	12/2008	Issa et al.	N/A	N/A
2009/0198307	12/2008	Mi et al.	N/A	N/A
2009/0198312	12/2008	Barker	N/A	N/A
2009/0276016	12/2008	Phillips et al.	N/A	N/A
2009/0312650	12/2008	Maile et al.	N/A	N/A
2010/0010582	12/2009	Carbunaru	N/A	N/A
2010/0191035	12/2009	Kang et al.	N/A	N/A
2010/0219967	12/2009	Kaufmann	N/A	N/A
2010/0280568	12/2009	Bulkes et al.	N/A	N/A
2010/0312310	12/2009	Meskens	607/61	H02J 50/005
2010/0331918	12/2009	Digiore et al.	N/A	N/A
2010/0331920	12/2009	Digiore et al.	N/A	N/A

2011/0071336	12/2010	Yomtov	N/A	N/A
2011/0137394	12/2010	Lunsford et al.	N/A	N/A
2011/0224720	12/2010	Kassab et al.	N/A	N/A
2012/0019201	12/2011	Peterson	N/A	N/A
2012/0022645	12/2011	Burke	N/A	N/A
2012/0050931	12/2011	Terry et al.	N/A	N/A
2012/0112543	12/2011	van Wageningen et al.	N/A	N/A
2012/0158074	12/2011	Hall	N/A	N/A
2012/0212178	12/2011	Kim	N/A	N/A
2012/0235633	12/2011	Kesler et al.	N/A	N/A
2013/0069651	12/2012	Lumiani	N/A	N/A
2013/0099585	12/2012	Von Novak et al.	N/A	N/A
2013/0116575	12/2012	Mickle et al.	N/A	N/A
2013/0303970	12/2012	Keenan et al.	N/A	N/A
2014/0012282	12/2013	Fritsch	N/A	N/A
2014/0039587	12/2013	Romero	N/A	N/A
2014/0063666	12/2013	Kallal et al.	N/A	N/A
2014/0094645	12/2013	Lafontaine et al.	N/A	N/A
2014/0104898	12/2013	Yeo et al.	N/A	N/A
2014/0107754	12/2013	Fuhs et al.	N/A	N/A
2014/0135884	12/2013	Tockman et al.	N/A	N/A
2014/0194058	12/2013	Lee et al.	N/A	N/A
2014/0233184	12/2013	Thompson et al.	N/A	N/A
2014/0249603	12/2013	Yan et al.	N/A	N/A
2014/0265620	12/2013	Hoarau et al.	N/A	N/A
2015/0008755	12/2014	Sone	N/A	N/A
2015/0028805	12/2014	Dearden et al.	N/A	N/A
2015/0090372	12/2014	Branagan et al.	N/A	N/A
2015/0196076	12/2014	Billingslea	N/A	N/A
2015/0290372	12/2014	Muller et al.	N/A	N/A
2015/0290373	12/2014	Rudser et al.	N/A	N/A
2015/0333532	12/2014	Han et al.	N/A	N/A
2015/0380972	12/2014	Fort	N/A	N/A
2016/0022889	12/2015	Bluvshstein et al.	N/A	N/A
2016/0067395	12/2015	Jimenez et al.	N/A	N/A
2016/0081680	12/2015	Taylor	N/A	N/A
2016/0087558	12/2015	Yamamoto	N/A	N/A
2016/0095968	12/2015	Rudser	N/A	N/A
2016/0175501	12/2015	Schuermann	N/A	N/A
2016/0268846	12/2015	Akuzawa et al.	N/A	N/A
2016/0271309	12/2015	Throckmorton et al.	N/A	N/A
2016/0331980	12/2015	Strommer et al.	N/A	N/A
2016/0344302	12/2015	Inoue	N/A	N/A
2017/0047781	12/2016	Stanislawski et al.	N/A	N/A
2017/0070082	12/2016	Zheng et al.	N/A	N/A
2017/0136164	12/2016	Yeatts	N/A	N/A
2017/0143977	12/2016	Kaib et al.	N/A	N/A
2017/0202575	12/2016	Stanfield et al.	N/A	N/A

2017/0203104	12/2016	Nageri et al.	N/A	N/A
2017/0231717	12/2016	Forsell	N/A	N/A
2017/0271919	12/2016	Von Novak, III et al.	N/A	N/A
2017/0275799	12/2016	Chen	N/A	N/A
2017/0288448	12/2016	Kranz et al.	N/A	N/A
2017/0303375	12/2016	Woodhead	N/A	N/A
2017/0353053	12/2016	Muratov	N/A	N/A
2017/0354812	12/2016	Callaghan et al.	N/A	N/A
2018/0078329	12/2017	Hansen et al.	N/A	N/A
2018/0194236	12/2017	Elshaer et al.	N/A	N/A
2018/0207336	12/2017	Solem	N/A	N/A
2018/0256796	12/2017	Hansen	N/A	N/A
2018/0256800	12/2017	Conyers et al.	N/A	N/A
2018/0280708	12/2017	Escalona et al.	N/A	N/A
2018/0287405	12/2017	Govindaraj	N/A	N/A
2018/0316209	12/2017	Gliner	N/A	N/A
2019/0004037	12/2018	Zhang et al.	N/A	N/A
2019/0060543	12/2018	Khanal et al.	N/A	N/A
2019/0068004	12/2018	Louis	N/A	N/A
2019/0097447	12/2018	Partovi	N/A	N/A
2019/0175808	12/2018	Zilbershlag et al.	N/A	N/A
2019/0222064	12/2018	Du et al.	N/A	N/A
2019/0344000	12/2018	Kushwaha et al.	N/A	N/A
2019/0351120	12/2018	Kushwaha et al.	N/A	N/A
2019/0393735	12/2018	Lee et al.	N/A	N/A
2020/0054806	12/2019	Sun	N/A	N/A
2020/0139032	12/2019	Bryson et al.	N/A	N/A
2020/0227954	12/2019	Ding et al.	N/A	N/A
2020/0350812	12/2019	Vogt et al.	N/A	N/A
2021/0052793	12/2020	Struthers et al.	N/A	N/A
2021/0057804	12/2020	Wenning	N/A	N/A
2021/0143688	12/2020	Agrawal et al.	N/A	N/A
2021/0290931	12/2020	Baumbach	N/A	N/A
2021/0322011	12/2020	Schuelke et al.	N/A	N/A
2021/0336484	12/2020	Araujo et al.	N/A	N/A
2021/0339009	12/2020	Stotz et al.	N/A	N/A
2021/0351628	12/2020	Araujo et al.	N/A	N/A
2021/0379360	12/2020	Schellenberg	N/A	N/A
2021/0386990	12/2020	Stotz et al.	N/A	N/A
2021/0393944	12/2020	Wenning	N/A	N/A
2021/0399582	12/2020	Araujo et al.	N/A	N/A
2022/0080184	12/2021	Clifton et al.	N/A	N/A
2022/0080185	12/2021	Clifton et al.	N/A	N/A
2022/0320901	12/2021	Araujo et al.	N/A	N/A
2022/0407403	12/2021	Vogt et al.	N/A	N/A
2023/0191141	12/2022	Wenning et al.	N/A	N/A
2023/0381526	12/2022	Stotz et al.	N/A	N/A
2024/0269459	12/2023	Schellenberg et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3 000 581	12/2016	CA	N/A
103143072	12/2012	CN	N/A
103942511	12/2013	CN	N/A
104274873	12/2014	CN	N/A
104888293	12/2016	CN	N/A
106776441	12/2016	CN	N/A
103 02 550	12/2003	DE	N/A
10 2012 200 912	12/2012	DE	N/A
11 2012 005 944	12/2013	DE	N/A
10 2016 106 683	12/2015	DE	N/A
10 2016 225 862	12/2016	DE	N/A
10 2016 203 172	12/2016	DE	N/A
10 2017 213 475	12/2018	DE	N/A
10 2018 204 604	12/2018	DE	N/A
10 2018 204 610	12/2018	DE	N/A
10 2018 206 714	12/2018	DE	N/A
10 2018 206 724	12/2018	DE	N/A
10 2018 206 725	12/2018	DE	N/A
10 2018 206 727	12/2018	DE	N/A
10 2018 206 731	12/2018	DE	N/A
10 2018 206 750	12/2018	DE	N/A
10 2018 206 754	12/2018	DE	N/A
10 2018 206 758	12/2018	DE	N/A
10 2018 222 505	12/2019	DE	N/A
0 930 086	12/1998	EP	N/A
2 752 209	12/2013	EP	N/A
2 782 210	12/2013	EP	N/A
2 859 911	12/2014	EP	N/A
2 966 753	12/2015	EP	N/A
2 454 799	12/2015	EP	N/A
2 709 689	12/2016	EP	N/A
3 220 505	12/2016	EP	N/A
3 536 360	12/2018	EP	N/A
3 357 523	12/2020	EP	N/A
3 423 126	12/2020	EP	N/A
3 490 628	12/2020	EP	N/A
3 198 677	12/2020	EP	N/A
3 248 647	12/2020	EP	N/A
3 436 106	12/2020	EP	N/A
3 509 661	12/2020	EP	N/A
3 528 863	12/2020	EP	N/A
3 436 105	12/2020	EP	N/A
3 116 407	12/2020	EP	N/A
3 131 600	12/2020	EP	N/A
3 827 876	12/2020	EP	N/A
2 608 731	12/2020	EP	N/A

2 599 510	12/2020	EP	N/A
3 077 018	12/2020	EP	N/A
3 485 936	12/2020	EP	N/A
3 539 613	12/2021	EP	N/A
2 858 718	12/2021	EP	N/A
3 624 867	12/2021	EP	N/A
3 755 237	12/2021	EP	N/A
3 497 775	12/2021	EP	N/A
3 711 788	12/2021	EP	N/A
2 654 883	12/2021	EP	N/A
3 485 819	12/2021	EP	N/A
3 600 477	12/2021	EP	N/A
3 808 408	12/2021	EP	N/A
3 858 422	12/2021	EP	N/A
2 892 583	12/2022	EP	N/A
3 597 231	12/2022	EP	N/A
3 856 275	12/2022	EP	N/A
3 003 420	12/2022	EP	N/A
3 946 511	12/2022	EP	N/A
3 826 104	12/2022	EP	N/A
H11-178249	12/1998	JP	N/A
4706886	12/2010	JP	N/A
2013-013216	12/2012	JP	N/A
2018-046708	12/2017	JP	N/A
10-1185112	12/2011	KR	N/A
WO 2008/106103	12/2007	WO	N/A
WO 2009/023905	12/2008	WO	N/A
WO 2009/029977	12/2008	WO	N/A
WO 2010/042054	12/2009	WO	N/A
WO 2011/007300	12/2010	WO	N/A
WO 2012/147061	12/2011	WO	N/A
WO 2013/164831	12/2012	WO	N/A
WO 2015/152732	12/2014	WO	N/A
WO 2017/021846	12/2016	WO	N/A
WO 2017/060257	12/2016	WO	N/A
WO 2017/066257	12/2016	WO	N/A
WO 2017/089440	12/2016	WO	N/A
WO 2017/118738	12/2016	WO	N/A
WO 2017/165372	12/2016	WO	N/A
WO 2017/218349	12/2016	WO	N/A
WO 2018/033799	12/2017	WO	N/A
WO 2018/100192	12/2017	WO	N/A
WO 2019/025258	12/2018	WO	N/A
WO 2019/025259	12/2018	WO	N/A
WO 2019/025260	12/2018	WO	N/A
WO 2019/101786	12/2018	WO	N/A
WO 2019/145253	12/2018	WO	N/A
WO 2019/158996	12/2018	WO	N/A
WO 2019/183247	12/2018	WO	N/A
WO 2019/185511	12/2018	WO	N/A

WO 2019/185512	12/2018	WO	N/A
WO 2019/211400	12/2018	WO	N/A
WO 2019/211405	12/2018	WO	N/A
WO 2019/211410	12/2018	WO	N/A
WO 2019/211413	12/2018	WO	N/A
WO 2019/211414	12/2018	WO	N/A
WO 2019/211415	12/2018	WO	N/A
WO 2019/211416	12/2018	WO	N/A
WO 2019/229224	12/2018	WO	N/A
WO 2019/234151	12/2018	WO	N/A
WO 2019/241556	12/2018	WO	N/A
WO 2019/244031	12/2018	WO	N/A
WO 2020/089429	12/2019	WO	N/A
WO 2023/076869	12/2022	WO	N/A

OTHER PUBLICATIONS

Atkinson et al., “Pulse-Doppler Ultrasound and Its Clinical Application”, The Yale Journal of Biology and Medicine, 1977, vol. 50, pp. 367-373. cited by applicant

Leguy et al., “Assessment of Blood Volume Flow in Slightly Curved Arteries from a Single Velocity Profile”, Journal of Biomechanics, 2009, pp. 1664-1672. cited by applicant

Murali, Akila, “Design of Inductive Coils for Wireless Power Transfer to Pediatric Implants”, A graduate project submitted in partial fulfillment of the requirements for the degree of Master of Science in Electrical Engineering, California State University, Northridge, May 2018, pp. 37. cited by applicant

Sinha et al., “Effect of Mechanical Assistance of the Systemic Ventricle in Single Ventricle Circulation with Cavopulmonary Connection”, The Journal of Thoracic and Cardiovascular Surgery, Apr. 2014, vol. 147, No. 4, pp. 1271-1275. cited by applicant

Vieli, A., “Doppler Flow Determination”, BJA: British Journal of Anaesthesia, 1988, vol. 60, pp. 107S-112S. cited by applicant

Primary Examiner: Kessie; Daniel

Attorney, Agent or Firm: Knobbe, Martens Olson & Bear, LLP

Background/Summary

BACKGROUND

Field

- (1) The invention relates to a device for inductive energy transmission into a human body. The invention further relates to the use of a device according to the invention.
- (2) Medical technology uses devices for inductive energy transmission, in which a transmitter unit disposed outside a human body comprises a transmitter coil, the magnetic field of which induces energy in the receiver coil of a receiver unit disposed [in] the human body, which at least indirectly serves to charge a battery disposed in the human body. Such a system is known as a so-called VAD (ventricular assist device) system used to operate a pump that supports the heart of a patient (DE 10 2016 106 683 A1).
- (3) For such a device, and this applies to both the receiver unit and the transmitter unit, it is essential that it is configured in as compact a manner as possible. On the one hand, in terms of the

receiver unit, this minimizes the space required in the body for the receiver unit, while on the other hand, in terms of the transmitter unit, it increases the wearing comfort of such a transmitter unit under the patient's clothing. The transmitter unit or the receiver unit furthermore typically comprise a housing, in which the components of the respective unit are disposed. It is also known that, in addition to the transmitter coil or the receiver coil, an electronic circuit is required for the operation of said coils, which typically also comprises a so-called resonance or choke coil. Like the transmitter coil or the receiver coil, such a resonance or choke coil comprises a magnetic core and a wire winding that interacts with the magnetic core. In the case of the resonance or choke coil, this is typically a component of a resonance circuit and, in the state of the art, is always disposed discretely, i.e. separately from the transmitter coil or receiver coil, on a circuit carrier (circuit board) together with other electronic components. The separate arrangement and configuration of the magnetic cores for the transmitter coil or receiver coil and for the resonance or choke coil results in an increase of the overall height of the transmitter unit or receiver unit, in particular with regard to the respective magnetic cores, because the resonance or choke coil is disposed above or below the level of the transmitter coil or receiver coil and thus also affects the overall height of the housing of the transmitter unit or receiver unit.

DISCLOSURE OF THE INVENTION

Summary

(4) The device according to the invention for inductive energy transmission having the features of Claim 1 has the advantage that it enables a particularly compact arrangement of the transmitter coil or receiver coil and the resonance or choke coil in the transmitter unit or the receiver unit.

(5) The invention is based on the idea of using or configuring a part of the magnetic core of the transmitter coil or the receiver coil simultaneously as a part of the magnetic core of the resonance or choke coil or vice versa. This not only saves material for the magnetic cores, but also enables a particularly compact arrangement of the two magnetic cores relative to one another.

(6) Advantageous further developments of the device for inductive energy transmission into a human body according to the invention are presented in the subclaims.

(7) In a first structural configuration of the device, it is provided that the first magnetic core (of the transmitter or receiver coil) is disposed in direct contact with an end face of the second magnetic core (of the resonance or choke coil).

(8) In order to fulfill the intended functionality, it is furthermore provided in a preferred structural configuration that the transmitter coil or the receiver coil comprises wire windings which are disposed concentrically to one another and the resonance or choke coil comprises second wire windings which are disposed concentrically to one another, and that the first wire windings are disposed radially outside the second wire windings.

(9) The last-mentioned configuration in particular leads to a geometric arrangement, in which the resonance or choke coil is disposed concentrically to a longitudinal axis of the first magnetic core.

(10) A structural arrangement or configuration of the two coils (transmitter coil and receiver coil or resonance or choke coil) as described thus far in particular enables a desired decoupling of the transmitter and the receiver coil with the resonance or choke coil due to both the selected topology and the design of the transmitter or receiver coil itself. The transmitter coil and the receiver coil in particular have a very low coupling factor to the resonance or choke coil, because the (magnetic) fields of the transmitter coil or receiver coil are enclosed on one side by the ferrite core. The return of the magnetic fields on the other side then takes place via the air over a longer distance and thus leads to the aforementioned low coupling. The structural arrangement of the coils as described thus far typically has a very low coupling factor of typically up to about 0.05.

(11) Another preferred structural configuration provides that the first magnetic core is disc-shaped and has at least one groove-like recess which extends radially around the longitudinal axis for receiving first wire windings of the transmitter or receiver coil.

(12) In particular in the last-mentioned design, it is further provided that the resonance or choke

coil is disposed on the side of the at least one recess which faces away from the first wire windings. (13) To positively affect the saturation of the core material of the magnetic core of the resonance or choke coil and for the purpose of optimal guidance of the magnetic field lines, it is also advantageous if, in the region of contact with the second magnetic core, the first magnetic core has a wall thickness which corresponds to the wall thickness of a middle leg of the E-core of the second magnetic core.

(14) The invention further also includes the use of a device for energy transmission into a human body according to the invention as described thus far, in particular as a component of a VAD system.

(15) Further advantages, features and details of the invention emerge from the following description of preferred design examples and with reference to the drawing.

Description

BRIEF DESCRIPTION OF THE DRAWING

(1) The only FIGURE shows a schematic illustration of a device for inductive energy transmission into a human body.

DETAILED DESCRIPTION

(2) The device **10** shown in the only FIGURE is in particular configured as a component of a so-called VAD system **100**, wherein the VAD system **100** comprises a pump for supporting the heart function of a patient that is operated or supplied with energy via a not-depicted battery. This battery is charged by means of the device **10**.

(3) The device **10** comprises a receiver unit **12** that is disposed in a human body **1** and comprises a housing **13**, in which a receiver coil **14**, which is shown in the illustration of the FIGURE in a highly simplified manner, is disposed. The receiver coil **14** is used for at least indirect charging of said battery, for example via not-depicted wire connections to the battery and a not-depicted electronic circuit. In addition to the receiver coil **14**, the receiver unit **12** further comprises a choke coil **16**, which is likewise shown purely schematically and is not a component of a receiving oscillator circuit.

(4) The receiver unit **12** interacts with a transmitter unit **20** disposed outside the body **1**. As an example, the transmitter unit **20** comprises a housing **22** which, on the one hand, can be positioned in at least indirect contact with the skin **2** of the body **1** and in alignment with the receiver unit **12** and, on the other hand, comprises a transmitter coil **24** in its interior. The transmitter coil **24** consists of a disc-shaped first magnetic core **26**, which comprises a radially circumferential, groove-like recess **28** on the side facing the receiver unit **12**. First wire windings **30**, which are disposed concentrically to one another around a longitudinal axis **42** of the first magnetic core **26**, are disposed in the region of the recess **28** and serve to produce a not-depicted magnetic field in order to induce electrical energy in the receiver coil **12** which is used to charge said battery.

(5) As an example, the transmitter coil **24** has a height $h_{\text{sub.1}}$. On the side of the first magnetic core **26** facing away from the receiver unit **12**, a second magnetic core **32** is disposed as part of a resonance or choke coil **34**. The second magnetic core **32** is configured in the form of an E-magnetic core **32**. Second wire windings **40** of the resonance or choke coil **34** are concentrically wound around a (central) middle leg **38** of the second magnetic core **36**.

(6) As can be seen from the illustration of the FIGURE, the middle leg **38** is also disposed concentrically to the longitudinal axis **42** of the first magnetic core **26**. The second wire windings **40** furthermore extend radially inside the first wire windings **30** of the transmitter coil **24**.

(7) With its three legs **37** to **39**, the end face **44** of the second magnetic core **36** facing the first magnetic core **26** directly abuts the end face **46** of the first magnetic core **26**. The illustration of the FIGURE also shows that, in the region in which the second magnetic core **32** and the first magnetic

core **26** overlap, the thickness d of the middle leg **38** of the second magnetic core **32** corresponds to the wall thickness s of the first magnetic core **26**. The second magnetic core **32** has a height $h_{\text{sub}.2}$. The illustration of the FIGURE further shows that the total height H of the housing **22** of the transmitter unit **20** substantially depends on or is determined by the sum of the two heights $h_{\text{sub}.1}$ and $h_{\text{sub}.2}$ of the two magnetic cores **26** and **32**.

(8) The device **10** as described thus far can be changed or modified in many ways without departing from the idea of the invention. It is in particular noted that the specific configuration of the transmitter coil **24** and the resonance or choke coil **34**, or the magnetic cores **26**, **32** thereof, has been described on the basis of the transmitter unit **20**. It is just as possible for the described structure to be provided in the same way in the region of the receiver unit **12**. This likewise results in a minimization of the overall height of the housing **13** of the receiver unit **12**.

Claims

1. A device for inductively transmitting energy into or receiving energy within a human body, the device comprising: a first coil including a first magnetic core, wherein the first magnetic core has an end face and at least one leg extending away from a side opposite the end face and is configured to receive a plurality of wire windings opposite the end face and around the at least one leg, and a second coil including a second magnetic core, the second magnetic core comprising three legs abutting the end face of the first magnetic core, wherein the second coil includes at least one recess extending radially around a middle leg of the three legs, the at least one recess configured to receive a plurality of wire windings, wherein the first magnetic core and the second magnetic core have E-shaped cross-sections facing in a same direction, and wherein a width of the first magnetic core disposed in direct contact with the second magnetic core corresponds to a width of the middle leg of the second magnetic core.
2. The device according to claim 1, wherein the plurality of wire windings of the second coil wind concentrically around the middle leg of the second magnetic core.
3. The device according to claim 1, wherein the first coil comprises a plurality of first wire windings disposed concentrically relative to one another, wherein the second coil comprises a plurality of second wire windings disposed concentrically relative to one another, and wherein the plurality of first wire windings are disposed radially outside the plurality of second wire windings.
4. The device according to claim 1, wherein the second coil is disposed concentrically to a longitudinal axis of the first magnetic core.
5. The device according to claim 1, wherein the first magnetic core is disc-shaped.
6. The device according to claim 5, wherein the first magnetic core comprises a radially circumferential recess.
7. The device according to claim 1, further comprising a housing surrounding the first coil and the second coil, a height of the housing being equal to a height of the first coil and a height of the second coil.
8. A method for inductively transmitting energy, the method comprising: inductively transmitting energy using a transmitter device and a receiver device, wherein at least one of the transmitter device and the receiver device comprises: a first coil including a first magnetic core, wherein the first magnetic core has an end face and at least one leg extending away from a side opposite the end face and is configured to receive a plurality of wire windings opposite the end face and around the at least one leg, and a second coil including a second magnetic core, the second magnetic core comprising three legs abutting the end face of the first magnetic core, wherein the second coil includes at least one recess extending radially around a middle leg of the three legs, the at least one recess configured to receive a plurality of wire windings, wherein the first magnetic core and the second magnetic core have E-shaped cross-sections facing in a same direction, and wherein a width of the first magnetic core disposed in direct contact with the second magnetic core corresponds to a

width of the middle leg of the second magnetic core.

9. The method of claim 8, wherein at least one of the transmitter device and the receiver device further comprises a housing, wherein the housing is in at least indirect contact with skin of a human body.

10. The method of claim 8, wherein the transmitter device inductively transmits energy and the receiver device inductively receives energy.

11. The method of claim 10, wherein the energy received at the receiver device is used for charging a battery in communication with the receiver device.

12. A system for inductive energy transmission, the system comprising: a first device including a first coil and a second coil; and a second device, wherein the first coil includes a first magnetic core, wherein the first magnetic core has an end face and at least one leg extending away from a side opposite the end face and is configured to receive a plurality of wire windings opposite the end face and around the at least one leg and wherein the second coil includes a second magnetic core, wherein the second magnetic core comprises three legs abutting the end face of the first magnetic core, wherein the second coil includes at least one recess extending radially around a middle leg of the three legs, the at least one recess configured to receive a plurality of wire windings, wherein the first magnetic core and the second magnetic core have E-shaped cross-sections facing in a same direction and wherein the first and second devices are disposed in alignment on opposite sides of skin of a body to transfer energy into the body, and wherein a width of the first magnetic core disposed in direct contact with the second magnetic core corresponds to a width of the middle leg of the second magnetic core.

13. The system of claim 12, wherein the plurality of wire windings of the second coil wind concentrically around the middle leg of the second magnetic core.

14. The system of claim 12, wherein the first coil comprises a plurality of first wire windings disposed concentrically relative to one another, wherein the second coil comprises a plurality of second wire windings disposed concentrically relative to one another, and wherein the plurality of first wire windings are disposed radially outside the plurality of second wire windings.

15. The system of claim 12, wherein the second coil is disposed concentrically to a longitudinal axis of the first magnetic core.

16. The system according to claim 12, further comprising a housing surrounding the first coil and the second coil, a height of the housing equal to a height of the first coil and a height of the second coil.

17. The system according to claim 12, wherein the first magnetic core is disc shaped.

18. The system according to claim 17, wherein the first magnetic core comprises a radially circumferential recess.
