

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400819
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Guyot; Ludovic et al.

Electrical switching device having an auxiliary contact

Abstract

Electrical cut-off device including a fuse used to open a power line in which a direct current circulates, a movable drawer connected to the fuse and capable, once the fuse is broken, of moving in a fixed chamber under the action of a compression spring mounted between the fixed chamber and the movable drawer, and an auxiliary contact whose fixed contact part is secured to the fixed chamber and movable contact part is secured to the movable drawer whose movement will cause the opening of the normally closed auxiliary contact.

Inventors:	Guyot; Ludovic (Blagnac, FR), Valire; Jérôme (Blagnac, FR)
Applicant:	SAFRAN ELECTRICAL & POWER (Blagnac, FR)
Family ID:	1000008778410
Assignee:	SAFRAN ELECTRICAL & POWER (Blagnac, FR)
Appl. No.:	18/723217
Filed (or PCT Filed):	December 13, 2022
PCT No.:	PCT/FR2022/052332
PCT Pub. No.:	WO2023/118691
PCT Pub. Date:	June 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240420911 A1	Dec. 19, 2024

Foreign Application Priority Data

FR	2114269	Dec. 22, 2021
----	---------	---------------

Publication Classification

Int. Cl.: H01H85/30 (20060101); H01H39/00 (20060101); H01H85/042 (20060101); H01H85/36 (20060101)

U.S. Cl.:

CPC H01H85/306 (20130101); H01H39/006 (20130101); H01H85/042 (20130101); H01H85/36 (20130101);

Field of Classification Search

CPC: H01H (85/30-306); H01H (39/006); H01H (85/042); H01H (85/36)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4652067	12/1986	Lutzenberger	439/43	H01R 13/703
5097244	12/1991	Veverka et al.	N/A	N/A
10589635	12/2019	Solodovnik	N/A	B60L 50/13
2012/0194317	12/2011	Vranicar	337/401	H01H 37/761
2013/0200984	12/2012	Matthiesen	337/186	H01H 37/761
2014/0266561	12/2013	Horne	N/A	N/A
2017/0345602	12/2016	Yoon	N/A	H01H 85/17
2019/0252145	12/2018	Ehrhardt	N/A	H01H 37/765
2022/0013314	12/2021	Hierl	N/A	H01H 37/764

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102020104617	12/2019	DE	N/A

OTHER PUBLICATIONS

Search Report and Written Opinion issued in International Application No. PCT/FR2022/052332, mailed Mar. 28, 2023. cited by applicant

Search Report and Written Opinion issued in French Application No. 2114269, mailed Jul. 25, 2022. cited by applicant

Primary Examiner: Crum; Jacob R

Attorney, Agent or Firm: Bookoff McAndrews, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This is a National Stage Application under 35 U.S.C. § 371 of International Application No. PCT/FR2022/052332, filed Dec. 13, 2022, now published as WO 2023/118691 A1, which claims

TECHNICAL FIELD

(2) The present invention relates to the general field of electrical cut-off devices for direct current, preferably high-voltage direct current (HVDC), supply networks and more particularly aircraft propulsion systems.

PRIOR ART

(3) The electrical cut-off system known under the terms “pyrofuse” or “pyroswitch” is an assembly composed of a pyrotechnic actuator and of a fuse triggered by the actuator. It is used to open a power line in which a direct current circulates, in the event of a short circuit or excessive current. The pyrotechnic actuator then acts to help the fuse open the power line in extreme conditions by the combined action of the melting of the fuse element and mechanical action of stretching the fuse which contributes to breaking it. There are also electrical cut-off systems with mechanical actuator or others without any actuator.

(4) If such devices are generally satisfactory, it is however difficult to make sure of the melting of the fuse or of the proper triggering of the actuator when it exists, as well as of a possible dormant failure of the device that cannot be operational without a fuse in good operating state during the opening of the power line.

DISCLOSURE OF THE INVENTION

(5) The main aim of the present invention is therefore to ensure constant monitoring of the state of the fuse throughout its lifespan and whatever its mode of activation. Another aim is also to ensure that the auxiliary contact detecting this state has reached its limit.

(6) These aims are achieved by an electrical cut-off device including a fuse used to open a power line in which a direct current circulates, characterized in that it further includes a movable drawer connected to the fuse and capable, once the fuse is broken, of moving in a fixed chamber under the action of a compression spring mounted between the fixed chamber and the movable drawer, and an auxiliary contact whose fixed contact part is secured to the fixed chamber and movable contact part is secured to the movable drawer whose movement will cause the opening of the normally closed auxiliary contact.

(7) Advantageously, the auxiliary contact is galvanically isolated from the power line.

(8) The addition of this auxiliary breakage detection circuit galvanically isolated from the power circuit ensures the function of monitoring the state of the fuse, regardless of its activation mode, short circuit or pyrotechnic or mechanical activation.

(9) Preferably, the movable drawer is fixed to one end of the fuse by a first fixing screw.

(10) Advantageously, the movable drawer is made up of a slide sliding in the fixed chamber and of a stopper bearing against the fixed chamber and fixed to the slide by a second fixing screw.

(11) Preferably, the fixed and movable contact parts of the auxiliary contact are each constituted by a copper strip and a silver pad.

(12) Advantageously, the movable contact part is mounted on an isolation plate fixed to the stopper by third fixing screws.

(13) Preferably, the auxiliary contact is connected to a Sub-D connector in order to actuate an external signaling process.

(14) According to one embodiment, the cut-off device includes a limit switch contact with a copper strip and a silver pad.

(15) Preferably, the fuse is triggered by a pyrotechnic or mechanical actuator.

(16) The invention also relates to a high-voltage direct current (HVDC) supply network including a cut-off device as mentioned above and an aircraft propulsion system including such a high-voltage direct current supply network.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Other characteristics and advantages of the present invention will emerge from the description given below, with reference to the appended drawings which illustrate one exemplary embodiment devoid of any limitation and in which:

(2) FIG. 1 is a sectional view in a passive position of a cut-off device in accordance with the invention,

(3) FIG. 2 is a sectional view in an active position of a cut-off device in accordance with the invention, and

(4) FIG. 3 is an outer perspective view of the cut-off device of FIGS. 1 and 2 at the level of its auxiliary contact.

DESCRIPTION OF THE EMBODIMENTS

(5) The principle of the invention is based on the fact that as soon as an overcurrent passes through the fuse of the electrical cut-off device and melts it, a drawer provided with an auxiliary contact is no longer retained by this fuse and then moves into a chamber under the action of a pressurized compression spring and which thus returns to its free position, releasing the auxiliary contact, so as to signal the breakage of the fuse whose monitoring can thus be ensured.

(6) FIGS. 1 and 2 show by way of example, in two different positions, an electrical cut-off device **10** consisting of a pyrotechnic or mechanical actuator **12** and of a fuse **14** triggered by the actuator, and used to open a power line in which a high-voltage direct current circulates. The pyrotechnic or mechanical actuator known per se is not detailed.

(7) In the first position of FIG. 1, the cut-off device is at rest, the fuse **14** of the device is in perfect state and stretches between a first fixed end **14A** and a second movable end **14B** fixed to a movable drawer **16** by a first fixing screw **18**. The drawer can move in translation in a housing **20** of a fixed chamber **22** mounted in the body **10A** of the cut-off device. The movable drawer is advantageously made in two parts with a slide **16A** and a stopper **16B**. The slide **16A** is movably mounted in translation in the housing **20** and is in the form of a shouldered shaft, the shoulder **160** being permanently located in the housing **20**. The slide **16A** has a first end fixed to the fuse **14** via the first fixing screw **18** and a second end fixed in a blind hole **24** of the stopper **16B** via a second fixing screw **26**. The stopper **16B** fixed to the slide **16A** by the second fixing screw **26** places under stress a compression spring **28** (which then has a length in place L_p) until being pressed against the fixed chamber **22** via a connecting ring **30** mounted in the housing **20** and whose thickness corresponds to that of the shoulder **160**.

(8) An auxiliary contact **32** whose fixed contact part **32A** is secured to the fixed chamber **22** (more specifically to an offset part **22A** of this fixed chamber visible in FIG. 3) and movable contact part **32B** facing it is secured to the movable drawer **16** (more specifically directly to the stopper **16B** or via an isolation plate **34** fixed by third fixing screws **36** to the stopper (visible in FIG. 3) depending on the nature of the material constituting this stopper), is provided to ensure the function of detecting the tearing (the melting) of the fuse whose movement via the slide **16A** and the compression spring **28** will cause the opening of this normally closed auxiliary contact (NC) in the rest position of the cut-off device. Each fixed or movable contact part is made up of a copper strip **320A**, **320B** and of a silver pad **322A**, **322B**, the contacting of the two silver pads indicating the closure of the auxiliary contact. Note the galvanic isolation formed between this auxiliary contact and the power line due to the absence of a conductive connection therebetween.

(9) The two copper strips of the two fixed and movable contact parts are connected by wiring to a Sub-D type connector (not represented) which makes it possible to read the state of the auxiliary contact and thus monitor and know the state of the fuse of the electrical cut-off device.

(10) In the second position of FIG. 2, the fuse **14** has melted under the action of heat or broken for any other undesired reason and the slide **16A** sliding in the fixed chamber **22** has therefore translated under the action of the compression spring **28** which then returns to its free length L_0 .

(11) Indeed, this slide **16A** secured to one end of the fuse **14** is able to be driven in translation under the action of release of this compression spring when the cut-off device **10** moves from its rest, therefore passive, position to an active operating position, bringing its shoulder **160** against the connecting ring **30** held by the compression spring **28** against the fixed chamber **22**. The bearing face **162** of the stopper **16B** is now separated from the fixed chamber against which it was bearing via the connecting ring **30**, this separation setting in motion the normally closed auxiliary contact **32**. The movable contact part **32B** fixed to the stopper **16B** is then set in motion and separates from the opposite fixed contact part **32A** fixed to the fixed chamber **5**, the auxiliary contact is then in the open position.

(12) It will be noted that when the normally closed auxiliary contactor is, as illustrated, coupled with a normally open auxiliary contact (NO **38**), made up of another copper strip **380** and of a silver pad **382**, it is possible to ensure that the system has reached its limit under the action of the compression spring **28**.

Claims

1. An electrical cut-off device including a fuse used to open a power line in which a direct current circulates, wherein the electrical cut-off device further includes a movable drawer connected to the fuse and capable, once the fuse is broken, of moving in a fixed chamber under an action of a compression spring mounted between the fixed chamber and the movable drawer, and a normally closed auxiliary contact whose fixed contact part is secured to the fixed chamber and movable contact part is secured to the movable drawer whose movement will cause the opening of the normally closed auxiliary contact, wherein the normally closed auxiliary contact is galvanically isolated from the power line.
2. The cut-off device according to claim 1, wherein the movable drawer is fixed to one end of the fuse by a first fixing screw.
3. The cut-off device according to claim 1, wherein the normally closed auxiliary contact is connected to a Sub-D connector in order to actuate an external signaling process.
4. The cut-off device according to claim 1, wherein the fixed and movable contact parts of the normally closed auxiliary contact are each constituted by a copper strip and a silver pad.
5. The cut-off device according to claim 4, wherein the movable contact part is mounted on an isolation plate fixed to a stopper by third fixing screws.
6. The cut-off device according to claim 1, further including a limit switch contact with a copper strip and a silver pad.
7. The cut-off device according to claim 1, wherein the fuse is triggered by a pyrotechnic or mechanical actuator.
8. A high-voltage direct current (HVDC) supply network including a cut-off device according to claim 7.
9. An aircraft propulsion system including a high-voltage direct current supply network according to claim 8.
10. An electrical cut-off device including a fuse used to open a power line in which a direct current circulates, wherein the electrical cut-off device characterized in that it further includes a movable drawer connected to the fuse and capable, once the fuse is broken, of moving in a fixed chamber under an action of a compression spring mounted between the fixed chamber and the movable drawer, and a normally closed auxiliary contact whose fixed contact part is secured to the fixed chamber and movable contact part is secured to the movable drawer whose movement will cause the opening of the normally closed auxiliary contact, wherein the movable drawer is fixed to one end of the fuse by a first fixing screw.
11. An electrical cut-off device including a fuse used to open a power line in which a direct current circulates, wherein the electrical cut-off device characterized in that it further includes a movable

drawer connected to the fuse and capable, once the fuse is broken, of moving in a fixed chamber under an action of a compression spring mounted between the fixed chamber and the movable drawer, and a normally closed auxiliary contact whose fixed contact part is secured to the fixed chamber and movable contact part is secured to the movable drawer whose movement will cause the opening of the normally closed auxiliary contact, wherein the movable drawer is made up of a slide sliding in the fixed chamber and of a stopper bearing against the fixed chamber and fixed to the slide by a second fixing screw.
