

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401536
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Qiao; Weihua et al.

Ethernet type packet data unit session communications

Abstract

Systems, apparatuses, and methods are described for wireless communications. A network function device, such as a policy control function device, may send a policy and charging control rule that is based on one or more Ethernet medium access control (MAC) addresses. For example, the policy control function device may send the policy and charging control rule to a session management function device to provide a packet data unit (PDU) session for a wireless device.

Inventors: Qiao; Weihua (Herndon, VA), Dinan; Esmael Hejazi (McLean, VA), Park; Kyungmin (Vienna, VA), Talebi Fard; Peyman (Vienna, VA)

Applicant: Comcast Cable Communications, LLC (Philadelphia, PA)

Family ID: 1000008778424

Assignee: Comcast Cable Communications, LLC (Philadelphia, PA)

Appl. No.: 18/347676

Filed: July 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240039744 A1	Feb. 01, 2024

Related U.S. Application Data

continuation parent-doc US 16951875 20201118 US 11743061 child-doc US 18347676
continuation parent-doc US 16155378 20181009 US 10938583 20210302 child-doc US 16951875
us-provisional-application US 62569935 20171009
us-provisional-application US 62569927 20171009
us-provisional-application US 62569910 20171009

Publication Classification

Int. Cl.: **H04L12/14** (20240101); **H04L9/40** (20220101); **H04L41/0893** (20220101); **H04L41/50** (20220101); **H04L47/20** (20220101); **H04L47/24** (20220101); **H04M15/00** (20060101); **H04W4/24** (20180101); H04L41/0894 (20220101); H04L43/028 (20220101); H04W76/12 (20180101)

U.S. Cl.:

CPC **H04L12/1407** (20130101); **H04L12/1435** (20130101); **H04L12/1492** (20130101); **H04L41/0893** (20130101); **H04L41/50** (20130101); **H04L47/20** (20130101); **H04L47/24** (20130101); **H04L63/0245** (20130101); **H04L63/0254** (20130101); **H04L63/20** (20130101); **H04M15/00** (20130101); **H04M15/66** (20130101); **H04M15/8016** (20130101); **H04M15/8228** (20130101); **H04W4/24** (20130101); H04L41/0894 (20220501); H04L43/028 (20130101); H04W76/12 (20180201)

Field of Classification Search

CPC: H04L (12/1407); H04L (12/1435); H04L (12/1492); H04L (41/0893); H04L (41/50); H04L (47/20); H04L (47/24); H04L (63/0245); H04L (63/0254); H04L (63/20); H04L (43/028); H04L (41/0894); H04M (15/00); H04M (15/66); H04M (15/8016); H04M (15/8228); H04W (4/24); H04W (76/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10251147	12/2018	Park et al.	N/A	N/A
10264506	12/2018	Faccin et al.	N/A	N/A
10951427	12/2020	Qiao	N/A	H04L 63/0245
12095576	12/2023	Qiao	N/A	H04W 4/24
2013/0139221	12/2012	Gundavelli	726/4	H04W 12/068
2014/0204927	12/2013	Horn et al.	N/A	N/A
2014/0219267	12/2013	Eyuboglu et al.	N/A	N/A
2015/0063331	12/2014	Scahill	370/338	H04W 48/20
2016/0345170	12/2015	Mann	N/A	N/A
2016/0345178	12/2015	Bronowich	N/A	N/A
2017/0289019	12/2016	Faccin et al.	N/A	N/A
2017/0303189	12/2016	Hampel et al.	N/A	N/A
2018/0192390	12/2017	Li et al.	N/A	N/A
2018/0270782	12/2017	Park et al.	N/A	N/A
2018/0270888	12/2017	Faccin	N/A	N/A
2018/0332523	12/2017	Faccin et al.	N/A	N/A
2019/0116520	12/2018	Chaponniere et al.	N/A	N/A
2019/0150219	12/2018	Wang et al.	N/A	N/A
2019/0166647	12/2018	Velev et al.	N/A	N/A

2019/0182895	12/2018	Di Girolamo et al.	N/A	N/A
2019/0200264	12/2018	Kim et al.	N/A	N/A
2019/0261159	12/2018	Wang et al.	N/A	N/A
2019/0274178	12/2018	Salkintzis et al.	N/A	N/A
2019/0306758	12/2018	Ma et al.	N/A	N/A
2019/0313473	12/2018	Kim et al.	N/A	N/A
2019/0335366	12/2018	Jin et al.	N/A	N/A
2019/0364496	12/2018	Jin	N/A	N/A
2019/0364541	12/2018	Ryu	N/A	N/A
2019/0380104	12/2018	Vrzic et al.	N/A	N/A
2019/0387428	12/2018	Ahmad et al.	N/A	N/A
2020/0084657	12/2019	Lee et al.	N/A	N/A
2021/0075865	12/2020	Zhu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101414940	12/2010	CN	N/A
3094155	12/2015	EP	N/A
3337284	12/2017	EP	N/A
3425993	12/2018	EP	N/A
2009052749	12/2008	WO	N/A
2014011008	12/2013	WO	N/A
2014094287	12/2013	WO	N/A
WO-2016091298	12/2015	WO	N/A
2017030420	12/2016	WO	N/A
2017171514	12/2016	WO	N/A
2018006017	12/2017	WO	N/A
2018130968	12/2017	WO	N/A

OTHER PUBLICATIONS

R2-1710864 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Mediatek Inc., Title: Basic Framework for Bandwidth Part Operation. cited by applicant

R2-1710965 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: vivo, Title: Discussion on bandwidth part operation. cited by applicant

R2-1711065 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Nokia, Nokia Shanghai Bell, Title: Cell and BWP relation. cited by applicant

R2-1711187 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: Framework to support bandwidth parts in NR. cited by applicant

R2-1711188 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: Signaling to support bandwidth part. cited by applicant

R2-1711189 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: Activation/deactivation of bandwidth parts in NR. cited by applicant

R2-1711388 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: LG Electronics Inc., Title: RRC Procedures for BWP Configuration. cited by applicant

R2-1711595 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: The impact of bandwidth part on RAN2: Overview and Issues. cited by applicant

R2-1711607 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: Scenarios of Measurement Gap Considering Bandwidth Part. cited by

applicant

R2-1711640 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: ZTE Corporation, Sane Chips, Title: Initial discussion on the impacts of BWP on RAN2. cited by applicant

R2-1712101 3GPP TSG RAN WG2 Meeting #100, Reno, USA, Nov. 27-Dec. 1, 2017, Source: ETSI MCC, Title: Report of 3GPP Tsg Ran2 #99bis Meeting in Prague. cited by applicant
3GPP TS 23.501 V15.2.0 (Jun. 2018); Technical Specification; 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; System Architecture for the 5G System; Stage 2 (Release 15). cited by applicant

S2-183494 3GPP TSG RAN WG2 Meeting #127, Sanya, China, Apr. 16-20, 2018, Source: Nokia, Nokia Shanghai Bell, China Mobile, Title: Controlled Support of (AF) Session Binding for Ethernet PDU Session Type. cited by applicant

S2-173117 3GPP TSG RAN WG2 Meeting #121, Hangzhou, China, May 15-19, 2017, Source: Qualcomm Incorporated, Title: Options on Packet Filters Extension for PDU Sessions of Type Ethernet and Unstructured in 5GS. cited by applicant

S2-174838 3GPP SA WG2 Meeting #122, Cabo, Mexico, Jun. 26-30, 2017, Source: Nokia, Alcatel-Lucent Shanghai Bell, Title: Update on policy control for QoS control functionalities. cited by applicant

S2-174210 3GPP SA WG2 Meeting #122, Cabo, Mexico, Jun. 26-30, 2017, Source: Ericsson, Title: 5G System details for PCC. cited by applicant

Jun. 9, 2021—European Search Report—EP 21157697.0. cited by applicant

Jun. 24, 2022—European Office Action—EP App. No. 21157697.0. cited by applicant

Mar. 21, 2019—EP Extended Search Report—EP 18201708.7. cited by applicant

C1-174177 3GPP TSG-CT Wg1 Meeting #106, Kochi, India, Oct. 23-27, 2017, Source: LG Electronics, Ericsson, Title: Corrections on PDU session type and PDU type. cited by applicant

R3-161353 3GPP TSG RAN WG3 Meeting #92, Nanjing, China, May23-27, 2016, Source: Nokia, Alcatel-Lucent Shanghai Bell, Title: Proposal for RAN-CN Functional Split. cited by applicant

S2-177144 3GPP SA WG2 Meeting #123, Ljubljana, Slovenia, Oct. 23-27, 2017, Source: Huawei, HiSilicon, Title: Clarification on Ethernet PDU session. cited by applicant

C1-173155 3GPP TSG-CT WG1 Meeting #105, Krakow, Poland, Aug. 21-25, 2017, Source: Nokia, Alcatel-Lucent Shanghai Bell, Title: Pseudo-CR on support of 5GSM Pdu session types. cited by applicant

3GPP TS 36.323 V14.3.1 (Jun. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Packet Data Convergence Protocol (PDCP) specification (Release 14). cited by applicant

3GPP TS 36.331 V14.3.0 (Jun. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol Specification (Release 14). cited by applicant

3GPP TS 38.300 V1.0.1 (Oct. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; NR and NG-RAN Overall Description; Stage 2 (Release 15). cited by applicant

3GPP TS 38.323 V0.3.0 (Aug. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Packet Data Convergence Protocol (PDCP) specification (Release 15). cited by applicant

Cisco, Next-Generation Enterprise WAN: Cisco ISRs with 4G Lte Deployment Guide, May 2014. cited by applicant

Effnet Platform, Effnet EthHC™, 2017. cited by applicant

Wikipedia, “Ethernet frame”, last edited Sep. 24, 2017. cited by applicant

Wikipedia, “EtherType”, last edited Aug. 10, 2017. cited by applicant

Wikipedia, "IEEE 802.1Q", last edited Aug. 7, 2017. cited by applicant

S2-177974 3GPP SA WG2 Meeting #123, Ljubljana, Slovenia, Oct. 23-27, 2017, Source: Huawei, HiSilicon, Title: Classification on Ethernet PDU session. cited by applicant

S2-178029 3GPP SA WG2 Meeting #123, Ljubljana, Slovenia, Oct. 23-27, 2017, Source: Nokia, Nokia Shanghai Bell, Title: Corrections and Improvements for Ethernet PDU Session Type. cited by applicant

3GPP TS 36.211 V14.4.0 (Sep. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Channels and Modulation (Release 14). cited by applicant

3GPP TS 36.212 V14.4.0 (Sep. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and Channel Coding (Release 14). cited by applicant

3GPP TS 36.300 V14.4.0 (Sep. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall Description; Stage 2 (Release 14). cited by applicant

3GPP TS 36.321 V14.4.0 (Sep. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol Specification (Release 14). cited by applicant

3GPP TS 36.331 V14.4.0 (Sep. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) Protocol Specification (Release 14). cited by applicant

3GPP TS 36.213 V14.4.0 (Sep. 2017), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Physical Layer Procedures (Release 14). cited by applicant

S2-184514 3GPP TSG-SA WG2 Meeting #127, Sanya, China, Apr. 16-20, 2018, Source: Qualcomm Incorporated, Spreadtrum Communications, Ericsson, Title: Consolidation of UE Network Capabilities. cited by applicant

S2-183522 3GPP TSG-SA WG2 Meeting #127, Sanya, China, Apr. 16-20, 2018, Source: Qualcomm Incorporated, Title: Consolidation of UE Network Capabilities. cited by applicant

R1-1719301 3GPP TSG RAN WG1 Meeting #91, Reno, USA, Source: MCC Support, Title: Final Report of 3GPP TSG RAN WG1 #90bis v1.0.0 (Prague, Czech Republic, Oct. 9-13, 2017). cited by applicant

R1-1717057 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Huawei, HiSilicon, Title: On initial active bandwidth part. cited by applicant

R1-1717077 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Huawei, HiSilicon, Title: Remaining issues on bandwidth part. cited by applicant

R1-1717400 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Intel Corporation, Title: Remaining details for bandwidth parts. cited by applicant

R1-1717504 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: vivo, Title: Remaining details for bandwidth part operation. cited by applicant

R1-1717675 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: On Bandwidth Part Operation. cited by applicant

R1-1717839 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: CATT, Title: Remaining aspects of BWP operation. cited by applicant

R1-1717905 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Huawei, HiSilicon, Title: Bandwidth part activation and adaptation. cited by applicant

R1-1717972 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: LG Electronics, Title: Remaining issues on bandwidth parts. cited by applicant

R1-1718050 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017,

Source: OPPO, Title: Remaining issues on bandwidth part configuration and activation. cited by applicant
R1-1718223 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: NTT DOCOMO, Inc., Title: Remaining issues on bandwidth parts for NR. cited by applicant
R1-1718327 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: MediaTek Inc., Title: Remaining Details on Bandwidth Part Operation in NR. cited by applicant
R1-1718365 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: InterDigital, Inc., Title: Remaining details of BWP. cited by applicant
R1-1718404 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: AT&T, Title: Remaining details for bandwidth parts. cited by applicant
R1-1718523 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Ericsson, Title: On bandwidth parties. cited by applicant
R1-1718580 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Qualcomm Incorporated, Title: Open Issues on BWP. cited by applicant
R1-1718607 3GPP TSG RAN WG1 Meeting #90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Nokia, Nokia Shanghai Bell, Title: On remaining aspects of BWPs. cited by applicant
R1-1718901 3GPP TSG RAN WG1 Meeting 90bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: MediaTek Inc., Title: Summary of Bandwidth Part Operation. cited by applicant
R2-1710091 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Samsung, Title: Random Access in RRC Connected: Bandwidth Part Aspects. cited by applicant
R2-1710125 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: OPPO, Title: Impact of BWP on CA. cited by applicant
R2-1710126 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: OPPO, Title: Timer based BWP switching. cited by applicant
R2-1710217 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Huawei, HiSilicon, Title: User plane impacts for Bandwidth Parts. cited by applicant
R2-1710274 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: CATT, Title: Modeling Bandwidth Parts in MAC. cited by applicant
R2-1710275 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: CATT, Title: BWP model. cited by applicant
R2-1710457 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Huawei, HiSilicon, Title: Control plane impacts for Bandwidth Parts. cited by applicant
R2-1710592 3GPP TSG RAN WG2 Meeting #99bis, Prague, Czech Republic, Oct. 9-13, 2017, Source: Intel Corporation, Title: Overall impact in RAN2 for BWP. cited by applicant
Feb. 22, 2024—European Office Action—EP App. No. 21157697.0. cited by applicant

Primary Examiner: Phillips; Michael K

Attorney, Agent or Firm: Banner & Witcoff, Ltd.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of and claims priority to U.S. patent application Ser. No. 16/951,875, filed Nov. 18, 2020, which is a continuation of U.S. patent application Ser. No. 16/155,378, filed on Oct. 9, 2018 (now U.S. Pat.

No. 10,938,583), which claims the benefit of U.S. Provisional Application No. 62/569,910, filed Oct. 9, 2017; U.S. Provisional Application No. 62/569,927, filed Oct. 9, 2017; and U.S. Provisional Application No. 62/569,935, filed Oct. 9, 2017, each of which is hereby incorporated by reference in its entirety.

BACKGROUND

(1) A wireless communications system may not be able to provide an Ethernet over wireless communications for a wireless device due to insufficient information known by the system about the wireless device. For example, some network devices may not have wireless device specific information that may be necessary to serve Ethernet over wireless communications for a wireless device. As a result, difficulties may arise for a wireless device to obtain desired services using Ethernet over wireless communications.

SUMMARY

(2) The following summary presents a simplified summary of certain features. The summary is not an extensive overview and is not intended to identify key or critical elements.

(3) Systems, apparatuses, and methods are described for Ethernet packet data unit (PDU) session communications. A data network may provide one or more addresses to a session management function for an Ethernet PDU session. A wireless device may provide one or more Ethernet packet filter sets to the session management function to request an Ethernet PDU session. The session management function may provide to a user plane function one or more messages comprising the one or more Ethernet packet filter sets, the one or more addresses, and/or at least one policy rule. The user plane function may apply the at least one policy rule to a data flow to provide the requested Ethernet PDU session for the wireless device.

(4) These and other features and advantages are described in greater detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Some features are shown by way of example, and not by limitation, in the accompanying drawings. In the drawings, like numerals reference similar elements.

(2) FIG. 1 shows an example 5G system architecture.

(3) FIG. 2 shows an example 5G system architecture.

(4) FIG. 3 shows an example of a wireless device and a network node.

(5) FIGS. 4A and 4B show example elements of computing devices that may be used to implement any of the various devices described herein.

(6) FIG. 5 shows examples of registration management state models for a wireless device and an access and mobility management function (AMF).

(7) FIG. 6 shows examples of connection management state models for a wireless device and an AMF.

(8) FIG. 7 shows an example for classifying and marking traffic.

(9) FIGS. 8A-B shows examples of registration procedures.

(10) FIG. 9 shows an example of an Ethernet packet and frame structure.

(11) FIG. 10 shows an example of a PDU session establishment.

(12) FIG. 11 shows an example of a user plane protocol stack.

(13) FIG. 12 shows an example of a packet data convergence protocol (PDCP) data PDU.

(14) FIG. 13 shows an example of a PDCP control PDU.

(15) FIG. 14 shows an example layer 2 data flow.

(16) FIGS. 15A, 15B, 15C, and 15D show examples of registration procedures.

(17) FIGS. 16A and 16B show examples of PDU session creation procedures.

(18) FIGS. 17A and 17B show examples of PDU session modification procedures.

- (19) FIGS. **18A** and **18B** show examples of PDU session release procedures.
- (20) FIGS. **19A** and **19B** show examples of PDU session establishment procedures.
- (21) FIGS. **20A** and **20B** show examples of service request procedures.
- (22) FIG. **21** shows an example of an Ethernet over wireless communications procedure that may be performed by a computing device.
- (23) FIG. **22** shows an example of procedures involving a network exposure function.
- (24) FIG. **23** shows an example of procedures involving a session management function.
- (25) FIG. **24** shows an example of procedures involving an application function.
- (26) FIG. **25** shows an example of procedures involving a unified data management.
- (27) FIG. **26** shows an example of an Ethernet over wireless communications procedure that may be performed by a computing device.

DETAILED DESCRIPTION

- (28) The accompanying drawings, which form a part hereof, show examples of the disclosure. It is to be understood that the examples shown in the drawings and/or discussed herein are non-exclusive and that there are other examples of how the disclosure may be practiced.
- (29) Examples of enhanced features and functionalities in networks, such as 5G networks, or other systems are provided. The technology disclosed herein may be employed in the technical field of networks, such as 5G systems, and Ethernet type PDU sessions for communication systems. More particularly, the technology disclosed herein may relate to for Ethernet PDU type sessions in communication systems such as 5GC, 5G, or other systems. The communication systems may comprise any number and/or type of devices, such as, for example, computing devices, wireless devices, mobile devices, handsets, tablets, laptops, Internet of things (IoT) devices, hotspots, cellular repeaters, computing devices, and/or, more generally, user equipment (e.g., UE). Although one or more of the above types of devices may be referenced herein (e.g., UE, wireless device, computing device, etc.), it should be understood that any device herein may comprise any one or more of the above types of devices or similar devices.
- (30) The following acronyms are used throughout the present disclosure, provided below for convenience although other acronyms may be introduced in the detailed description. 5th generation mobile networks 5G Core Network 5G System 5G QoS Indicator AF Application Function AMF Access and Mobility Management Function AN Access Network ARP Allocation and Retention Priority AUSF Authentication Server Function CN Core Network DL Downlink DN Data Network DN-AAA Data Network Authentication Authorization and Accounting DNN Data Network Name eNB Evolved Node B ESP Encapsulating Security Protocol gNB Next Generation Node B or NR Node B IETF Internet Engineering Task Force IP Internet Protocol L2 Layer 2 (data link layer) L3 Layer 3 (network layer) LADN Local Area Data Network LI Lawful Intercept MICO Mobile Initiated Connection Only N3IWF Non-3GPP InterWorking Function NAS Non Access Stratum NEF Network Exposure Function NF Network Function NG-RAN NR Radio Access Network NR New Radio NRF Network Repository Function NSSAI Network Slice Selection Assistance Information PCC Policy and Charging Control PCF Policy Control Function PDCP Packet Data Convergence Protocol PDU Packet Data Unit PEI Permanent Equipment Identifier PLMN Public Land Mobile Network (R)AN (Radio) Access Network RAT Radio Access Technology RFC Request For Comments RLC Radio Link Control ROHC Robust Header Compression RRC Radio Resource Control QFI QoS Flow Identity QoS Quality of Service RM Registration Management SMF Session Management Function SN Sequence Number S-NSSAI Single Network Slice Selection Assistance information UDM Unified Data Management UE User Equipment UL Uplink UPF User Plane Function VPLMN Visited Public Land Mobile Network
- (31) FIG. **1** and FIG. **2** show examples 5G system architecture. A 5G access network may comprise an access network connecting to a 5GC. An access network may comprise an AN **105** (e.g., NG-RAN such as in FIG. **1**, or any access node as in FIG. **2**) and/or non-3GPP AN **165** which may be an untrusted AN. An example 5GC may connect to one or more 5G access networks (e.g., a 5G

AN) and/or NG-RANs. The 5GC may comprise functional elements or network functions as in example FIG. 1 and example FIG. 2, where interfaces may be employed for communication among the functional elements and/or network elements. A network function may be a processing function in a network that has a functional behavior and interfaces. A network function may be implemented as a network element on a dedicated hardware, a base station, and/or as a software instance running on a dedicated hardware, shared hardware, and/or as a virtualized function instantiated on an appropriate platform.

(32) The access and mobility management function AMF **155** may comprise one or more of the following functionalities: termination of (R)AN CP interface (N2), termination of NAS (N1), NAS ciphering and integrity protection, registration management, connection management, reachability management, mobility management, lawful intercept (for AMF events and interface to LI system), transport for session management, SM messages between a wireless device **100** and an SMF **160**, transparent proxy for routing SM messages, access authentication, access authorization, transport for short message service (SMS) messages between wireless device **100** and an SMS function (SMSF), security anchor function (SEA) interaction with the AUSF **150** and the wireless device **100**, receiving an intermediate key established as a result of the wireless device **100** authentication process, security context management (SCM), and/or receiving a key from the SEA to derive access network specific keys. A variety of these functionalities may be supported in a single instance of an AMF **155** and/or in multiple instances of AMF **155** as appropriate.

(33) The AMF **155** may support non-3GPP access networks via an N2 interface with N3IWF **170**, NAS signaling with a wireless device **100** over N3IWF **170**, authentication of wireless devices connected over N3IWF **170**, management of mobility, authentication, and separate security context state(s) of a wireless device **100** connected via non-3GPP access **165** or connected via 3GPP access **105** and non-3GPP accesses **165** simultaneously, support of a coordinated RM context valid over 3GPP access **105** and non-3GPP access **165**, and/or support of context management (CM) management contexts for the wireless device **100** for connectivity over non-3GPP access. Some functionalities described above may be supported in an instance of a network slice. An AMF **155** region may comprise of one or multiple AMF **155** sets. AMF **155** set may comprise of some AMFs **155** that serve a given area and/or network slice(s). Multiple AMF **155** sets may be per AMF **155** region and/or network slice(s). Application identifiers may be mapped to one or more specific application traffic detection rules. A configured NSSAI may be a NSSAI that has been provisioned in a wireless device **100**. DN **115** access identifier (DNAI), for a DNN, may be an identifier of a user plane access to a DN **115**. Initial registration may be related to a wireless device **100** registration in a RM-DEREGISTERED state. N2AP wireless device **100** association may be a logical per wireless device **100** association between a 5G AN node and an AMF **155**. Wireless device **100** may comprise a N2AP wireless device-TNLA-binding, which may be a binding between a N2AP wireless device **100** association and a specific transport network layer (TNL) association for a given wireless device **100**.

(34) The session management function (SMF) **160** may comprise one or more of the following functionalities: session management (e.g., session establishment, modify and release, comprising tunnel maintain between UPF **110** and AN **105** node), wireless device IP address allocation & management (comprising optional authorization), selection and control of user plane function(s), configuration of traffic steering at UPF **110** to route traffic to its proper destination, termination of interfaces towards policy control functions, control part of policy enforcement and QoS, lawful intercept (for SM events and interface to LI system), termination of SM parts of NAS messages, downlink data notification, initiation of AN specific SM information, sent via AMF **155** over N2 to (R)AN **105**, determination of SSC mode of a session, roaming functionality, handling local enforcement to apply QoS SLAs (VPLMN), charging data collection and charging interface (VPLMN), lawful intercept (in VPLMN for SM events and interface to LI system), and/or support for interaction with external DN **115** for transport of signaling for PDU session

authorization/authentication by external DN **115**. One or more of these functionalities may be supported in a single instance of a SMF **160**. One or more of the functionalities described above may be supported in an instance of a network slice.

(35) The user plane function (UPF) **110** may comprise one or more of the following functionalities: anchor point for Intra-/Inter-RAT mobility (if applicable), external PDU session point of interconnect to DN **115**, packet routing & forwarding, packet inspection and user plane part of policy rule enforcement, lawful intercept (UP collection), traffic usage reporting, uplink classifier to support routing traffic flows to a data network, branching point to support multi-homed PDU session(s), QoS handling for user plane, uplink traffic verification (SDF to QoS flow mapping), transport level packet marking in the uplink and downlink, downlink packet buffering, and/or downlink data notification triggering. One or more of these functionalities may be supported in a single instance of a UPF **110**. One or more of functionalities described above may be supported in an instance of a network slice. User plane function(s) (UPF(s) **110**) may handle the user plane path of PDU sessions. A UPF **110** that provides the interface to a data network supports the functionality of a PDU session anchor.

(36) IP address management may comprise allocation and release of the wireless device IP address as well as renewal of the allocated IP address. The wireless device **100** sets the requested PDU type during the PDU session establishment procedure based on its IP stack capabilities and configuration. The SMF **160** may select PDU type of a PDU session as follows: if the SMF **160** receives a request with PDU type set to IP, the SMF **160** may select either PDU type IPv4 or IPv6 based on DNN configuration and/or operator policies. The SMF **160** may also provide a cause value to the wireless device **100** to indicate whether the other IP version (e.g. IPv6 if IPv4 is selected and vice versa) may be supported on the DNN. If the other IP versions are supported, wireless device **100** may request another PDU session to the same DNN for the other IP version. If the SMF **160** receives a request for PDU type IPv4 or IPv6 and the requested IP version may be supported by the DNN, the SMF **160** selects the requested PDU type. The 5GC elements and wireless device **100** support the following mechanisms: during PDU session establishment procedure, the SMF **160** may send the IP address to the wireless device **100** via SM NAS signaling. The IPv4 address allocation and/or IPv4 parameter configuration via DHCPv4 may also be used if the PDU session may be established. IPv6 prefix allocation may be supported via IPv6 stateless auto configuration, if IPv6 may be supported. IPv6 parameter configuration via stateless DHCPv6 may also be supported. The 5GC may support the allocation of a static IPv4 address and/or a static IPv6 prefix based on subscription information in the UDM **140** or based on the configuration on a per-subscriber, per-DNN basis.

(37) The policy control function PCF **135** may support unified policy framework to govern network behavior, provide policy rules to control plane function(s) to enforce them, and/or implement a front end to access subscription information relevant for policy decisions in a user data repository (UDR). The unified data management UDM **140** may comprise an application front end (FE) that comprises the UDM-FE that may be in charge of processing credentials, location management, and/or subscription management. The PCF **135** may be in charge of policy control and the user data repository (UDR) that stores data required for functionalities provided by UDM-FE, plus policy profiles required by the PCF **135**. The data stored in the UDR may comprise at least user subscription data, comprising at least subscription identifiers, security credentials, access and mobility related subscription data, session related subscription data, and/or policy data.

(38) The network exposure function NEF **125** may provide a means to securely expose the services and capabilities provided by the 3GPP network functions, translate between information exchanged with the AF **145** and information exchanged with the internal network functions, and/or receive information from other network functions.

(39) The NF repository function NRF **130** may support a service discovery function that receives NF discovery requests from a NF instance, provides the information of the discovered NF instances

to the NF instance, and/or maintains the information of available NF instances and their supported services.

(40) The network slice selection function (NSSF) **120** may support selecting the set of network slice instances serving the wireless device **100**, determining the provided NSSAI, determining the AMF **155** set to be employed to serve the wireless device **100**, and/or, based on configuration, determining a list of candidate AMF(s) **155**, possibly by querying the NRF **130**.

(41) The functionality of non-3GPP interworking function N3IWF **170** for non-3GPP access **165** may comprise at least one or more of the following: supporting of IPsec tunnel establishment with the wireless device, terminating the IKEv2/IPsec protocols with the wireless device **100** over NWu, relaying over N2 the information needed to authenticate the wireless device **100** and authorize its access to the 5GC, terminating of N2 and N3 interfaces to 5GC for control-plane and user-plane respectively, relaying uplink and downlink control-plane NAS (N1) signaling between the wireless device **100** and AMF **155**, handling of N2 signaling from SMF **160** (which may be relayed by AMF **155**) related to PDU sessions and QoS, establishing of IPsec security association (IPsec SA) to support PDU session traffic, relaying uplink and downlink user-plane packets between the wireless device **100** and UPF **110**, enforcing QoS corresponding to N3 packet marking, considering QoS requirements associated to such marking received over N2, N3 user-plane packet marking in the uplink, local mobility anchor within untrusted non-3GPP access networks **165** using MOBIKE, and/or supporting AMF **155** selection.

(42) The application function AF **145** may interact with the 3GPP core network to provide a variety of services. Based on operator deployment, AF **145** may be trusted by the operator to interact directly with relevant network functions. Application functions not provided by the operator to access directly the network functions may use the external exposure framework (via the NEF **125**) to interact with relevant network functions.

(43) The control plane interface between the (R)AN **105** and the 5GC may support connection of multiple different kinds of ANs, such as 3GPP (R)AN **105** and/or N3IWF **170**, to the 5GC via a unique control plane protocol. A single N2 AP protocol may be employed for both the 3GPP access **105** and non-3GPP access **165** and/or for decoupling between AMF **155** and other functions such as SMF **160** that may need to control the services supported by AN(s) (e.g. control of the UP resources in the AN **105** for a PDU session). The 5GC may be able to provide policy information from the PCF **135** to the wireless device **100**. Such policy information may comprise the following: access network discovery & selection policy, wireless device route selection policy (URSP) that groups to or more of SSC mode selection policy (SSCMSP), network slice selection policy (NSSP), DNN selection policy, and/or non-seamless offload policy. The 5GC may support the connectivity of a wireless device **100** via non-3GPP access networks **165**. As shown in example FIG. 5, the registration management, RM may be employed to register or de-register a wireless device **100** with the network, and establish the user context in the network. Connection management may be employed to establish and release the signaling connection between the wireless device **100** and the AMF **155**.

(44) A wireless device **100** may need to register with the network to receive services that require registration. The wireless device **100** may update its registration with the network, e.g., periodically, after the wireless device is registered, to remain reachable (e.g. periodic registration update), on mobility (e.g. mobility registration update), and/or to update its capabilities or re-negotiate protocol parameters. An initial registration procedure, such as in the examples shown in FIG. 8A and FIG. 8B, may involve execution of network access control functions (e.g. user authentication and access authorization based on subscription profiles in UDM **140**). As result of the registration procedure, the identity of the serving AMF **155** may be registered in UDM **140**. The registration management (RM) procedures may be applicable over both 3GPP access **105** and non-3GPP access **165**.

(45) FIG. 3 shows hardware elements of a network node **320** (e.g., a base station) and a wireless

device **310**. A communication network may include at least one network node **320** and at least one wireless device **310**. The network node **320** may include one or more communication interface **322**, one or more processors **324**, and one or more sets of program code instructions **328** stored in non-transitory memory **326** and executable by the one or more processors **324**. The wireless device **310** may include one or more communication interface **312**, one or more processors **314**, and one or more sets of program code instructions **318** stored in non-transitory memory **316** and executable by the one or more processors **314**. A communication interface **322** in the network node **320** may be configured to engage in communication with a communication interface **312** in the wireless device **310**, such as via a communication path that includes at least one wireless link. The wireless link may be a bi-directional link. The communication interface **312** in the wireless device **310** may also be configured to engage in communication with the communication interface **322** in the network node **320**. The network node **320** and the wireless device **310** may be configured to send and receive data over the wireless link using multiple frequency carriers. Network nodes, base stations, wireless devices, and other communication devices may include structure and operations of transceiver(s). A transceiver is a device that includes both a transmitter and receiver. Transceivers may be employed in devices such as wireless devices, base stations, relay nodes, and/or the like. Examples for radio technology implemented in the communication interfaces **312**, **322** and the wireless link are shown in FIG. 3, FIGS. 4A, and 4B, and associated text. The communication network may comprise any number and/or type of devices, such as, for example, computing devices, wireless devices, mobile devices, handsets, tablets, laptops, internet of things (IoT) devices, hotspots, cellular repeaters, computing devices, and/or, more generally, user equipment (e.g., UE). Although one or more of the above types of devices may be referenced herein (e.g., UE, wireless device, computing device, etc.), it should be understood that any device herein may comprise any one or more of the above types of devices or similar devices. The communication network, and any other network referenced herein, may comprise an LTE network, a 5G network, or any other network for wireless communications. Apparatuses, systems, and/or methods described herein may generally be described as implemented on one or more devices (e.g., wireless device, base station, eNB, gNB, computing device, etc.), in one or more networks, but it will be understood that one or more features and steps may be implemented on any device and/or in any network. As used throughout, the term “base station” may comprise one or more of: a base station, a node, a Node B, a gNB, an eNB, an ng-eNB, a relay node (e.g., an integrated access and backhaul (IAB) node), a donor node (e.g., a donor eNB, a donor gNB, etc.), an access point (e.g., a Wi-Fi access point), a computing device, a device capable of wirelessly communicating, and/or any other device capable of sending and/or receiving signals. As used throughout, the term “wireless device” may comprise one or more of: a UE, a handset, a mobile device, a computing device, a node, a device capable of wirelessly communicating, and/or any other device capable of sending and/or receiving signals. Any reference to one or more of these terms/devices also considers use of any other term/device mentioned above.

(46) The communications network may comprise Radio Access Network (RAN) architecture. The RAN architecture may comprise one or more RAN nodes that may be a next generation Node B (gNB) (e.g., **320**) providing New Radio (NR) user plane and control plane protocol terminations towards a first wireless device (e.g. **310**). A RAN node may be a next generation evolved Node B (ng-eNB), providing Evolved UMTS Terrestrial Radio Access (E-UTRA) user plane and control plane protocol terminations towards a second wireless device. The first wireless device may communicate with a gNB over a Uu interface. The second wireless device may communicate with a ng-eNB over a Uu interface. The network node **320** may comprise one or more of a gNB, ng-eNB, and/or the like.

(47) A gNB or an ng-eNB may host functions such as: radio resource management and scheduling, IP header compression, encryption and integrity protection of data, selection of Access and Mobility Management Function (AMF) at User Equipment (UE) attachment, routing of user plane

and control plane data, connection setup and release, scheduling and transmission of paging messages (originated from the AMF), scheduling and transmission of system broadcast information (originated from the AMF or Operation and Maintenance (O&M)), measurement and measurement reporting configuration, transport level packet marking in the uplink, session management, support of network slicing, Quality of Service (QoS) flow management and mapping to data radio bearers, support of wireless devices in RRC_INACTIVE state, distribution function for Non-Access Stratum (NAS) messages, RAN sharing, and dual connectivity or tight interworking between NR and E-UTRA.

(48) One or more gNB s and/or one or more ng-eNB s may be interconnected with each other by means of Xn interface. A gNB or an ng-eNB may be connected by means of NG interfaces to 5G Core Network (5GC). 5GC may comprise one or more AMF/User Plane Function (UPF) functions. A gNB or an ng-eNB may be connected to a UPF by means of an NG-User plane (NG-U) interface. The NG-U interface may provide delivery (e.g., non-guaranteed delivery) of user plane Protocol Data Units (PDUs) between a RAN node and the UPF. A gNB or an ng-eNB may be connected to an AMF by means of an NG-Control plane (e.g., NG-C) interface. The NG-C interface may provide functions such as NG interface management, UE context management, UE mobility management, transport of NAS messages, paging, PDU session management, configuration transfer or warning message transmission.

(49) A UPF may host functions such as anchor point for intra-/inter-Radio Access Technology (RAT) mobility (if applicable), external PDU session point of interconnect to data network, packet routing and forwarding, packet inspection and user plane part of policy rule enforcement, traffic usage reporting, uplink classifier to support routing traffic flows to a data network, branching point to support multi-homed PDU session, QoS handling for user plane, for example, packet filtering, gating, Uplink (UL)/Downlink (DL) rate enforcement, uplink traffic verification (e.g. Service Data Flow (SDF) to QoS flow mapping), downlink packet buffering and/or downlink data notification triggering.

(50) An AMF may host functions such as NAS signaling termination, NAS signaling security, Access Stratum (AS) security control, inter Core Network (CN) node signaling for mobility between 3.sup.rd Generation Partnership Project (3GPP) access networks, idle mode UE reachability (e.g., control and execution of paging retransmission), registration area management, support of intra-system and inter-system mobility, access authentication, access authorization including check of roaming rights, mobility management control (subscription and policies), support of network slicing and/or Session Management Function (SMF) selection

(51) An interface may be a hardware interface, a firmware interface, a software interface, and/or a combination thereof. The hardware interface may include connectors, wires, electronic devices such as drivers, amplifiers, and/or the like. A software interface may include code stored in a memory device to implement protocol(s), protocol layers, communication drivers, device drivers, combinations thereof, and/or the like. A firmware interface may include a combination of embedded hardware and code stored in and/or in communication with a memory device to implement connections, electronic device operations, protocol(s), protocol layers, communication drivers, device drivers, hardware operations, combinations thereof, and/or the like.

(52) FIG. 4A shows general hardware elements that may be used to implement any of the various computing devices discussed herein, including any base station, wireless device, or computing device. The computing device **400** (e.g., wireless device) may include one or more processors **418**, which may execute instructions stored memory, such as non-removable memory **430**, removable memory **432** (such as a Universal Serial Bus (USB) drive, compact disk (CD) or digital versatile disk (DVD), or floppy disk drive), or any other desired storage medium. Instructions may also be stored in an attached (or internal) hard drive. The computing device **400** may also include a security processor (not shown), which may execute instructions of a one or more computer programs to monitor the processes executing on the processor **418** and any process that requests

access to any hardware and/or software components of the computing device **400** (e.g., the non-removable memory **430**, the removable memory **432**, the hard drive, a device controller (e.g., a keypad **426**, a display and/or touchpad **428**, a speaker and/or microphone **424**, and/or one or more peripherals **438**), a transceiver **420**, a network interface, a GPS **436** (e.g., a GPS chipset), a Bluetooth interface, a Wi-Fi interface, etc.). The computing device **400** may include one or more output devices, such as the display and/or touchpad **428** (e.g., a screen, a display device, a monitor, a television, etc.), and may include one or more output device controllers, such as a video processor. There may also be one or more user input devices, such as a remote control, keyboard, mouse, touch screen, microphone, etc., that may be configured, for example, as one or more of the peripherals **438**. The computing device **400** may also include one or more network interfaces, such as a network interface, the may be a wired interface, a wireless interface such as the transceiver **420**, or a combination of the two. The network interface may provide an interface for the computing device **400** to communicate (e.g., via communications **416**) with a network (e.g., a RAN, or any other network). The network interface may include a modem (e.g., a cable modem), and the external network may include communication links, an external network, an in-home network, a provider's wireless, coaxial, fiber, or hybrid fiber/coaxial distribution system (e.g., a DOCSIS network), or any other desired network. Additionally, the computing device **400** may include a location-detecting device, such as a global positioning system (GPS) chipset or microprocessor **436**, which may be configured to receive and process global positioning signals and determine, with possible assistance from an external server and antenna (e.g., antenna **422**), a geographic position of the computing device **400**.

(53) FIG. **4B** shows general hardware elements that may be used to implement any of the various computing devices discussed herein, including, e.g., the network node **320**, the wireless device **310**, or any other network node, base station, wireless device, or computing device described herein. The computing device **4000** may include one or more processors **4001**, which may execute instructions stored in the random access memory (RAM) **4003**, the removable media **4004** (such as a Universal Serial Bus (USB) drive, compact disk (CD) or digital versatile disk (DVD), or floppy disk drive), or any other desired storage medium. Instructions may also be stored in an attached (or internal) hard drive **4005**. The computing device **4000** may also include a security processor (not shown), which may execute instructions of one or more computer programs to monitor the processes executing on the processor **4001** and any process that requests access to any hardware and/or software components of the computing device **4000** (e.g., ROM **4002**, RAM **4003**, the removable media **4004**, the hard drive **4005**, the device controller **4007**, a network interface **4009**, a GPS **4011**, a Bluetooth interface **4012**, a Wi-Fi interface **4013**, etc.). The computing device **4000** may include one or more output devices, such as the display **4006** (e.g., a screen, a display device, a monitor, a television, etc.), and may include one or more output device controllers **4007**, such as a video processor. There may also be one or more user input devices **4008**, such as a remote control, keyboard, mouse, touch screen, microphone, etc. The computing device **4000** may also include one or more network interfaces, such as a network interface **4009**, which may be a wired interface, a wireless interface, or a combination of the two. The network interface **4009** may provide an interface for the computing device **4000** to communicate with a network **4010** (e.g., a RAN, or any other network). The network interface **4009** may include a modem (e.g., a cable modem), and the external network **4010** may include communication links, an external network, an in-home network, a provider's wireless, coaxial, fiber, or hybrid fiber/coaxial distribution system (e.g., a DOCSIS network), or any other desired network. Additionally, the computing device **4000** may include a location-detecting device, such as a global positioning system (GPS) microprocessor **4011**, which may be configured to receive and process global positioning signals and determine, with possible assistance from an external server and antenna, a geographic position of the computing device **4000**.

(54) The examples in FIGS. **4A** and **4B** are hardware configurations, although the components

shown may be implemented as software as well. For example, modifications may be made to add, remove, combine, divide, etc. components of the computing device **4000** as desired. Additionally, the components may be implemented using basic computing devices and components, and the same components (e.g., processor **4001**, ROM storage **4002**, display **4006**, etc.) may be used to implement any of the other computing devices and components described herein. For example, the various components described herein may be implemented using computing devices having components such as a processor executing computer-executable instructions stored on a computer-readable medium, as shown in FIGS. **4A** and **4B**. Some or all of the entities described herein may be software based, and may co-exist in a common physical platform (e.g., a requesting entity may be a separate software process and program from a dependent entity, both of which may be executed as software on a common computing device).

(55) Base stations, wireless devices, relay nodes, and other communication devices may comprise one or more transceivers. A transceiver may be a device that comprises both a transmitter and receiver. The communication network may comprise any number and/or type of devices, such as, for example, computing devices, wireless devices, mobile devices, handsets, tablets, laptops, internet of things (IoT) devices, hotspots, cellular repeaters, computing devices, and/or, more generally, user equipment. Although one or more of the above types of devices may be referenced herein (e.g., user equipment, wireless device, computing device, etc.), it should be understood that any device herein may comprise any one or more of the above types of devices or similar devices. The communication network, and any other network referenced herein, may comprise an LTE network, a 5G network, or any other network for wireless communications. Apparatuses, systems, and/or methods described herein may generally be described as implemented on one or more devices (e.g., a wireless device, base station, eNB, gNB, computing device, etc.), in one or more networks, but it will be understood that one or more features and/or steps may be implemented on any device and/or in any network. As used throughout, the term “base station” may comprise one or more of: a base station, a node, a Node B, a gNB, an eNB, an ng-eNB, a relay node (e.g., an integrated access and backhaul (IAB) node), a donor node (e.g., a donor eNB, a donor gNB, etc.), an access point (e.g., a Wi-Fi access point), a computing device, a device capable of wirelessly communicating, and/or any other device capable of sending and/or receiving signals. As used throughout, the term “wireless device” may comprise one or more of: a UE, a handset, a mobile device, a computing device, a node, a device capable of wirelessly communicating, or any other device capable of sending and/or receiving signals. Any reference to one or more of these terms/devices also considers use of any other term/device mentioned above.

(56) FIG. 5 depicts examples of the RM states of a wireless device, such as the wireless device **100**, as observed by the wireless device **100** and AMF **155**. The top half of FIG. 5 shows RM state transition in the wireless device. Two RM states may be used in a wireless device **100** (and possibly in the AMF **155**) that may reflect the registration status of the wireless device **100** in the selected PLMN. The registration status of the wireless device **100** in the selected PLMN may be RM-DEREGISTERED **500** or RM-REGISTERED **510**. In the RM DEREGISTERED state **500**, the wireless device **100** may not be registered with a network. The wireless device **100** context in AMF **155** may not hold valid location or routing information for the wireless device **100** so the wireless device **100** may be not reachable by the AMF **155**. Some wireless device context may still be stored in the wireless device **100** and the AMF **155**. In the RM REGISTERED state **510**, the wireless device **100** may be registered with the network. In the RM-REGISTERED **510** state, the wireless device **100** may receive services that require registration with the network.

(57) The bottom half of FIG. 5 shows RM state transitions in the AMF **155**. Two RM states may be used in the AMF **155** for the wireless device **100** that reflect the registration status of the wireless device **100** in the selected PLMN. The two RM states that may be used in the AMF **155** for the wireless device **100** in the selected PLMN may be RM-DEREGISTERED **520** or RM-REGISTERED **530**. The state of RM-DEREGISTERED **500** in the wireless device **100** may

correspond to the state of RM-DEREGISTERED 520 in the AMF 155. The state of RM-REGISTERED 510 in the wireless device 100 may correspond to the state of RM-REGISTERED 530 in the AMF 155.

(58) FIG. 6 depicts examples of CM state transitions as observed by the wireless device 100 and AMF 155. Connection management CM may comprise the functions of establishing and releasing a signaling connection between a wireless device 100 and the AMF 155 over N1. This signaling connection may be used to provide NAS signaling exchange between the wireless device 100 and a core network. The signaling connection may comprise both the AN signaling connection between the wireless device 100 and/or the (R)AN 105 (e.g. RRC connection over 3GPP access) and the N2 connection for this wireless device 100 between the AN and the AMF 155. The top half of FIG. 6 shows CM state transitions in the wireless device 100. Two CM states may be used for the NAS signaling connectivity of the wireless device 100 with the AMF 155: CM-IDLE 600 and CM-CONNECTED 610. A wireless device 100 in CM-IDLE 600 state may be in RM-REGISTERED 510 state that may have no NAS signaling connection established with the AMF 155 over N1. The wireless device 100 may perform cell selection, cell reselection, and PLMN selection. A wireless device 100 in CM-CONNECTED 610 state may have a NAS signaling connection with the AMF 155 over N1. RRC inactive state may apply to NG-RAN (e.g., it applies to NR and E-UTRA connected to 5G CN). The AMF 155 may provide (e.g., based on network configuration) assistance information to the NG (R)AN 105, for example, to assist the NG (R)AN's 105 decision as to whether the wireless device 100 may be sent to RRC inactive state. If a wireless device 100 may be CM-CONNECTED 610 with RRC inactive state, the wireless device 100 may resume the RRC connection (e.g., due to uplink data pending), may execute a mobile initiated signaling procedure (e.g., as a response to (R)AN 105 paging), and/or notify the network that it has left the (R)AN 105 notification area. NAS signaling connection management may comprise the functions of establishing and releasing a NAS signaling connection. NAS signaling connection establishment function may be provided by the wireless device 100 and the AMF 155 to establish a NAS signaling connection for a wireless device 100 in CM-IDLE 600 state. The procedure of releasing a NAS signaling connection may be initiated by the 5G (R)AN 105 node or the AMF 155.

(59) The bottom half of FIG. 6 shows CM state transitions in the AMF 155. Two CM states may be used for a wireless device 100 at the AMF 155: CM-IDLE 620 and CM-CONNECTED 630. The state of CM-IDLE 600 in the wireless device 100 may correspond to the state of CM-IDLE 620 in the AMF 155. The state of CM-CONNECTED 610 in the wireless device 100 may correspond to the state of CM-CONNECTED 630 in the AMF 155. Reachability management of the wireless device 100 may detect whether a wireless device 100 may be reachable and/or provide the wireless device location (e.g., the access node in communication with the wireless device) for the network to reach the wireless device 100. This may be done by paging wireless device 100 and wireless device location tracking. The wireless device location tracking may comprise both wireless device registration area tracking and wireless device reachability tracking. Such functionalities may be either located at a 5GC (e.g., for a CM-IDLE 620 state) or an NG-RAN 105 (e.g., for a CM-CONNECTED 630 state).

(60) The wireless device 100 and the AMF 155 may negotiate wireless device 100 reachability characteristics in CM-IDLE 600 and/or 620 states during registration and registration update procedures. A variety of wireless device reachability categories may be negotiated between a wireless device 100 and an AMF 155 for CM-IDLE 600 and/or 620 states, such as wireless device 100 reachability providing mobile device terminated data. The wireless device 100 may be CM-IDLE 600 mode and mobile initiated connection only (MICO) mode. The 5GC may support a PDU connectivity service that provides exchange of PDUs between a wireless device 100 and a data network identified by a DNN. The PDU connectivity service may be supported via PDU sessions that may be established, for example, after request from the wireless device 100.

(61) A PDU session may support one or more PDU session types. PDU sessions may be established

(e.g., after wireless device **100** request), modified (e.g., after wireless device **100** and 5GC request) and released (e.g., after wireless device **100** and 5GC request) using NAS SM signaling exchanged over N1 between the wireless device **100** and the SMF **160**. The 5GC may be able to trigger a specific application in the wireless device **100** (e.g., after a request from an application server). If receiving that trigger message, the wireless device **100** may pass it to the identified application in the wireless device **100**. The identified application in the wireless device **100** may establish a PDU session to a specific DNN.

(62) FIG. 7 shows an example of a QoS flow based framework. A QoS model (e.g., a 5G QoS model) may support the QoS flow based framework. The QoS model may support both QoS flows that require a guaranteed flow bit rate and QoS flows that may not require a guaranteed flow bit rate. The QoS model may also support reflective QoS. The QoS model may comprise flow mapping or packet marking at the CN_UP **720**, AN **710**, and/or wireless device **700**. Packets may arrive from and/or destined to the application/service layer **730** of wireless device **700**, CN_UP **720**, and/or an AF (e.g., the AF **145**). QoS flow may be granular of QoS differentiation in a PDU session. A QoS Flow IDQFI may be used to identify a QoS flow in a system. User plane traffic with the same QFI within a PDU session may receive the same traffic forwarding treatment. The QFI may be carried in an encapsulation header on N3 (and N9), for example, without any changes to an end-to-end packet header. The QFI may be used with PDUs having different types of payload. The QFI may be unique within a PDU session.

(63) The QoS parameters of a QoS flow may be provided to the (R)AN as a QoS profile over N2 at a PDU session or at a QoS flow establishment, and an NG-RAN may be used, for example, if the user plane may be activated. A default QoS rule may be utilized for every PDU session. An SMF (e.g., SMF **160**) may allocate the QFI for a QoS flow and may derive its QoS parameters from the information provided by the PCF. The SMF **160** may provide the QFI together with the QoS profile containing the QoS parameters of a QoS flow to the (R)AN **710**. QoS flow may be granular for QoS forwarding treatment in a system (e.g., a 5GS). Traffic mapped to the same QoS flow may receive the same forwarding treatment (e.g., scheduling policy, queue management policy, rate shaping policy, RLC configuration, and/or the like). Providing different QoS forwarding treatment may require separate QoS flow. A QoS indicator may be used as a reference to a specific QoS forwarding behavior (e.g., packet loss rate, and/or packet delay budget) to be provided to a QoS flow. This QoS indicator may be implemented in the access network by the 5QI referencing node specific parameters that control the QoS forwarding treatment (e.g., scheduling weights, admission thresholds, queue management thresholds, link layer protocol configuration, and/or the like).

(64) One or more devices (e.g., a 5GC) may support edge computing and may provide operators and/or third party services to be hosted close to the wireless device access point of attachment. The one or more devices (e.g., a 5GC) may select a UPF **110** close to the wireless device **100** and may execute the traffic steering from the UPF **110** to the LADN via a N6 interface. This selecting a UPF **110** close to the wireless device may be based on the wireless device subscription data, wireless device location, the information from application function AF **145**, policy, and/or other related traffic rules. The one or more devices (e.g., a 5GC) may expose network information and capabilities to an edge computing application function. The functionality support for edge computing may comprise local routing where the one or more devices (e.g., a 5GC) may select UPF **110** to route the user traffic to the LADN, traffic steering where the one or more devices (e.g., a 5GC) selects the traffic to be routed to the applications in the LADN, session and service continuity to provide wireless device **100** and application mobility, user plane selection and reselection (e.g., based on input from application function), network capability exposure where the one or more devices (e.g., a 5GC) and application function may provide information to each other via NEF, QoS and charging where PCF may provide rules for QoS control and charging for the traffic routed to the LADN, and/or support of local area data network where the one or more devices (e.g., a 5GC) may provide support to connect to the LADN in a certain area where the

applications are deployed.

(65) An example system (e.g., a 5GS) may be a 3GPP system comprising of 5G access network **105**, 5GC and a wireless device **100**, and/or the like. Provided NSSAI may be an NSSAI provided by a serving PLMN, for example, during a registration procedure, indicating the NSSAI provided by the network for the wireless device **100** in the serving PLMN for the current registration area. A periodic registration update may be wireless device **100** re-registration at expiry of a periodic registration timer. A requested NSSAI may be a NSSAI that the wireless device **100** may provide to the network. A service-based interface may represent how a set of services may be provided/exposed by a given NF.

(66) A PDU connectivity service may provide exchange of PDUs between a wireless device **100** and a data network. PDU session may be an association between a wireless device **100** and a data network, DN that provides a PDU connectivity service. The type of association may be IP, Ethernet, or unstructured. Service continuity may comprise an uninterrupted user experience of a service, for example, if the IP address and/or anchoring point change. Session continuity may comprise the continuity of a PDU session. For a PDU session of an IP type session, continuity may indicate that the IP address may be preserved for the lifetime of the PDU session. An uplink classifier may be a UPF functionality that aims at diverting uplink traffic, for example, based on filter rules provided by SMF, towards a data network.

(67) The system architecture may support data connectivity and services enabling deployments to use techniques such as, but not limited to, network function virtualization and/or software defined networking. The system architecture may leverage service-based interactions between control plane (CP) network functions where identified. In system architecture, separation of the user plane (UP) functions from the control plane functions may be considered. A system may provide a network function to interact with other NF(s) directly if required. A system may reduce dependencies between the access network (AN) and the core network (CN). The architecture may comprise a converged access-agnostic core network with a common AN-CN interface that integrates different 3GPP and non-3GPP access types. A system furthermore may support a unified authentication framework, stateless NFs (e.g., where the compute resource may be decoupled from the storage resource), capability exposure, and/or concurrent access to local and centralized services. UP functions may be deployed close to the access network, for example, to support low latency services and access to LADNs.

(68) A system may support roaming with both home routed traffic as well as local breakout traffic in the visited PLMN. An example architecture may be service-based and the interaction between network functions may be represented in a variety of ways. FIG. 1 shows an example service-based representation, where network functions within the control plane may provide other authorized network functions to access their services. This service-based representation shown in FIG. 1 may also comprise point-to-point reference points where necessary. FIG. 2 shows an example reference point representation, showing the interaction between the NF services in the network functions described by point-to-point reference point (e.g., N11) between any two network functions.

(69) Establishment of user plane connectivity to a data network via a network slice instance(s) may comprise performing an RM procedure, for example, to select an AMF **155** that supports the required network slices, and establishing one or more PDU session(s) to the required data network via the network slice instance(s). The set of network slices for a wireless device **100** may be changed, for example, if the wireless device **100** may be registered with a network. The set of network slices for the wireless device **100** may be initiated by the network or the wireless device **100**.

(70) Ethernet over wireless communications may provide advantages to wireless communications and a user. For example, wireless communications services may be enhanced, and/or additional services may be made available, by using Ethernet over wireless communications. Additional data and/or different types of data may be accommodated using Ethernet over wireless communications.

User specific services and/or device specific services may be provided by using Ethernet over wireless communications. Different priority, rates, and/or pricing may be implemented for services and/or applications by using Ethernet over wireless communications. Ethernet over wireless communications may comprise Ethernet over any wireless system, including but not limited to Ethernet over 5G or Ethernet over any legacy or future wireless communication system.

(71) A packet data unit (PDU) session may be supported. The PDU session may be supported, for example in 5G, using one or more protocols such as IPv4, IPv6, or Ethernet, or the PDU session may be unstructured (e.g., a non-IP PDU). Ethernet may comprise a variety of networking technologies, such as those that may be used in local area networks (LANs), metropolitan area networks (MANs), wide area networks (WAN), or other networks. A data packet on an Ethernet link may be referred to as an Ethernet packet. An Ethernet packet may transport an Ethernet frame as its payload. With Ethernet over wireless communications, an Ethernet packet may be transferred over a wireless communication system (e.g., a 5G system).

(72) Ethernet over wireless communications, such as Ethernet over 5G, may require information from outside of certain network devices (e.g., outside of a 5GC). For example, in some systems (e.g., in 5G) a control plane may not allocate medium access control (MAC) addresses and/or Ethertype to a wireless device for Ethernet over wireless communications. Certain network devices may not have source MAC addresses, destination MAC addresses, Ethertype, and/or other user specific and/or device specific information that may be necessary to serve Ethernet over wireless communications for a wireless device. A policy control device may require such information in order to provide policy information for servicing the wireless device using Ethernet over wireless communications. A session management device may require such user specific and/or device specific information to provide requested services for the wireless device and/or to implement any required policies for such services. A user plane function may require such information to detect Ethernet packet and/or to enforce policies. Additionally or alternatively, other devices in a network may require user specific and/or device specific information to provide Ethernet over wireless communications for the wireless device. A wireless device may provide, for example, an Ethernet packet filter that may comprise information necessary to serve an Ethernet over wireless communications for the wireless device. Additionally or alternatively, a data network outside of a core network (e.g., outside of a 5GC) may provide for example, an Ethernet packet filter that may comprise information necessary to serve an Ethernet over wireless communications for the wireless device.

(73) FIGS. 8A and 8B show connection, registration, and mobility management procedures. These procedures are described, for example, in “5G; Procedures for the 5G System,” ETSI TS 123 502 version 15.2.0, also 3GPP TS 23.502 version 15.2.0 Release 15, dated June 2018 and published by the European Telecommunications Standards Institute.

(74) At step **801** (in FIG. 8A), a wireless device (e.g., wireless device **100**) may send a message comprising a registration request to a (R)AN (e.g., (R)AN **105**). At step **802**, the (R)AN **105** may perform an AMF selection. At step **803**, the (R)AN **105** may send a message comprising the registration request to a new AMF (e.g., New AMF **155-1**). At step **804**, the New AMF **155-1** may send, to an old AMF (e.g., Old AMF **155-2**), a message comprising an indication of a context transfer (e.g., Namf_Communication_UEContextTransfer). At step **805**, the Old AMF **155-2** may send, to the New AMF **155-1**, a response message comprising a context transfer response (e.g., Namf_Communication_UEContextTransfer response). At step **806**, the New AMF **155-1** may send, to the wireless device **100**, a message comprising an identity request. At step **807**, the wireless device **100** may send, to the New AMF **155-1**, a message comprising an identity response. At step **908**, the New AMF **155-1** may perform an AUSF selection. At step **809**, authentication and/or security procedures may be performed between the wireless device **100** and the New AMF **155-1**, between the New AMF **155-1** and an AUSF (e.g., AUSF **150**), and/or between the AUSF **150** and a UDM (e.g., UDM **140**). At step **810**, the New AMF **155-1** may send, to the Old AMF **155-2**, a

message comprising a registration completion notification (e.g., Namf_Communication_RegistrationCompleteNotify). At step **811**, messages comprising identity requests and/or responses may be communicated between the wireless device **100** and the New AMF **155-1**.

(75) At step **812**, the New AMF **155-1** may send to an EIR, and/or the EIR may send to the AMF **155-1**, one or more messages associated with an identity check (e.g., N5g-eir_MEIdentityCheck_Get).

(76) At step **813** (in FIG. **8B**), the New AMF **155-1** may perform a UDM selection. At step **814a**, the New AMF **155-1** may send, to the UDM **140**, a message comprising a context management registration (e.g., Nudm_UEContextManagement_Registration). The UDM **140** may send, to the New AMF **155-1**, a message comprising a response to the context management registration. At step **814b**, the UDM **140** may send, to the New AMF **155-1**, a message comprising a notification for a subscription data update (e.g., Nudm_SubscriptionData_UpdateNotify). At step **814c**, the UDM **140** may send, to the Old AMF **155-2**, a message comprising a notification of a context management removal (e.g., Nudm_UEContextManagement_RemoveNotify). At step **815**, the New AMF **155-1** may perform a PCF selection. At step **816**, the New AMF **155-1** may send, to a PCF (e.g., PCF **135**), a message comprising policy control or policy creation (e.g., Npcf_PolicyControl_PolicyCreate). The PCF **135** may send a response to the New AMF **155-1**. At step **817**, the New AMF **155-1** may send, to an SMF (e.g., SMF **160**), a message comprising an event exposure notification (e.g., Namf_EventExposure_Notify(UE Reachability state with PDU status)). At step **818**, the New AMF **155-1** may send, to a N3IWF, a message comprising an N2 request. At step **819**, the N3IWF may send, to the New AMF **155-1**, a message comprising an N2 response. At step **820**, the Old AMF **155-2** may send, to the PCF **135**, a message comprising a policy control and/or policy deletion (e.g., Npcf_PolicyControl_PolicyDelete). The PCF **135** may send a response to the Old AMF **155-2**. At step **821**, the New AMF **155-1** may send, to the wireless device **100**, a message comprising a registration acceptance (e.g., Registration Accept). At step **822**, the wireless device **100** may send, to the New AMF **155-1**, a message comprising a registration completion (e.g., Registration Complete). Steps indicated by dashed lines (e.g., steps **806-813**, **815-820**, and **821**) may be optional.

(77) FIG. **9** shows an example of an Ethernet packet and frame structure. An Ethernet packet and frame structure may correspond with the Ethernet packet and frame structure for IEEE 802.3. An Ethernet frame may be preceded by a preamble (e.g., 7 octets) and a start frame delimiter (SFD) (e.g., 1 octet), both of which may be part of an Ethernet packet at a physical layer. The Ethernet frame may start with an Ethernet header, which may comprise destination and/or source MAC addresses as its first two fields (e.g., 6 octets of MAC destination and 6 octets of MAC source). An optional 802.1Q tag (e.g., 4 octets) may follow the MAC addresses. Next, may be an Ethertype (e.g., in Ethernet II) or length (e.g., in IEEE 802.3) (e.g., 2 octets). Thereafter, a middle section of the frame may comprise payload data (e.g., 46-1500 octets), which may include, for example, any headers for other protocols (e.g., Internet Protocol) that may be carried in the frame. The frame may end with a frame check sequence (FCS) (e.g., 4 octets), which may comprise a 32-bit cyclic redundancy check that may be used to detect any in-transit corruption of data. An inter-packet gap (IPG) (e.g., 12 octets) may be provided at the end of the Ethernet packet. A layer 2 Ethernet frame may comprise 64 to 1522 octets after the preamble and the SFD. A layer 1 Ethernet packet may comprise 64 to 1522 octets including the preamble and the SFD, followed by an IPG of 12 octets.

(78) A session management function (SMF) and/or a user plane function (UPF) may provide a PDU session anchor, for example, for a PDU session set up with an Ethernet PDU session type. The SMF and the UPF may support specific behaviors associated with a PDU session that may carry Ethernet frames. A MAC and/or an IP address may not be allocated, for example by a 5GC to a wireless device, for a PDU session. The UPF may store MAC addresses, for example, that may be received from a wireless device, and associate the MAC addresses with an appropriate PDU

session.

(79) A wireless device may operate in a bridge mode for connecting a LAN to a 5GS. Different MAC addresses may be used as source address of different frames that may be sent via an uplink over a single PDU session. Different destination MAC address of different frames that may be sent via a downlink, for example over the same PDU session as the uplink, may be used. Entities on the LAN that may be connected to a system (e.g., a 5GS) by the wireless device may be allocated an IP address by a data network. The data network may not be specified by 3GPP 5G specifications. A wireless device that may be connected to the system (e.g., a 5GS) may be the only wireless device that may be authenticated. For example, devices behind a wireless device that may be connected to the system (e.g., a 5GS) may not be authenticated.

(80) Different Frames exchanged via a PDU session, such as an Ethernet type PDU session, may be served with different quality of service (QoS) over the system (e.g., a 5GS). An SMF may provide, to a UPF, traffic filters based on the Ethernet frame structure. A packet filter set may support packet filtering (e.g., for an Ethernet PDU session type) based on one or more of: source MAC address and/or destination MAC address; Ethertype (e.g., such as set forth by IEEE 802.3); customer-virtual Local Area Network (VLAN) tag (C-TAG) and/or service-VLAN tag (S-TAG) VLAN identifier (VID) fields (e.g., such as set forth in IEEE 802.1Q); C-TAG and/or S-TAG priority code point (PCP) and/or drop eligibility indicator (DEI) fields (e.g., such as set forth in IEEE 802.1Q); and/or IP packet filter set. Additionally or alternatively, for example for Ethertype indicates IPv4/IPv6 payload, the packet filter set may support packet filtering comprising one or more of: a source and/or destination IP address and/or a IPv6 prefix, a source and/or destination port number, a protocol ID of a protocol above IP and/or a next header type, a type of service (TOS) (e.g., for IPv4), a traffic class (e.g., for IPv6), a mask, a flow label (e.g., for IPv6), and/or a security parameter index.

(81) FIG. 10 shows an example of a PDU session establishment. The PDU session establishment may originate with a wireless device (e.g., wireless device 100) requesting a PDU session establishment. At step 1001, the wireless device 100 may send, to the AMF 155, a NAS message. The NAS message may comprise one or more of: S-NSSAI, DNN, PDU Session ID, request type, and/or an N1 SM container (e.g., comprising a PDU session establishment request). The wireless device 100 may initiate the PDU session establishment procedure, for example, by the transmission of a NAS message containing a PDU session establishment request within the N1 SM container. The PDU session establishment request may include, for example, one or more of: a PDU type (e.g., Ethernet), an SSC mode, a protocol configuration option, and/or a PDU session ID (e.g., that may be generated by the wireless device 100).

(82) At step 1002, the AMF 155 may select an SMF (e.g., SMF 160) and send, to the selected SMF (e.g., SMF 160), a message. The message may comprise a PDU session create request (e.g., Nsmf_PDUSession_CreateSMRequest). The PDU session create request may comprise one or more of: SUPI, DNN, S-NSSAI, PDU session ID, AMF ID, request type, N1 SM container (e.g., comprising the PDU session establishment request), user location information, access type, and/or PEI.

(83) At step 1003, the SMF 160 may register with the UDM 140, for example, if the SMF 160 has not yet registered and/or if subscription data is not available. The SMF 160 may retrieve subscription data. Subscribers may be notified, for example, if subscription data is modified. The SMF 160 may select an UPF and trigger a PDU session establishment authentication and/or authorization, for example, if the SMF 160 determines it should perform secondary authorization and/or authentication during the establishment of the PDU session by a DN-AAA server.

(84) At step 1004, the SMF 160 may perform PCF selection (e.g., if dynamic PCC is deployed) and/or the SMF 160 may apply one or more local policies (e.g., if dynamic PCC is not deployed). The SMF 160 may invoke an operation (e.g., a Npcf_SMPolicyControl_Get operation), for example, to establish a PDU session with the PCF 135 and/or to obtain the default PCC rules for

the PDU session.

(85) At step **1005**, the PCF **135** may subscribe one or more events in the SMF **160**, for example, by invoking an operation (e.g., a Nsmf_EventExposure_Subscribe operation). At step **1006**, the SMF **160** may report one or more events to the PCF **135** that were previously subscribed, for example, by invoking a service operation (e.g., a Nsmf_EventExposure_Notify service operation). At step **1007**, the PCF **135** may provide updated policies to the SMF **160**, for example, by invoking a service operation (e.g., a Npcf_SMPolicyControl_UpdateNotify service operation). The PCF **135** may provide, to the SMF **160**, authorized Session-AMBR and/or the authorized 5QI/ARP.

(86) At step **1008**, the SMF **160** may initiate an N4 session establishment procedure with the selected UPF **110**, for example, if a request type indicates and initial request and/or if a PDU session establishment authentication and/or authorization was not performed. Additionally or alternatively, the SMF **160** may initiate an N4 session modification procedure with the selected UPF **110**, for example, by the SMF **160** sending an N4 session establishment and/or modification request to the UPF **110**, and/or by providing one or more packet detection, enforcement and/or reporting rules that may be installed on the UPF **110** for the PDU session. The CN tunnel info may be provided to UPF **110** at step **1008**, for example, if CN tunnel info is allocated by the SMF **160**.

(87) At step **1009**, the UPF **110** may acknowledge the SMF **160**, for example, by sending an N4 session establishment and/or modification response. The CN tunnel info may be provided to SMF **160** at step **1009**, for example, if CN tunnel info is allocated by the UPF **110**.

(88) At step **1010**, the SMF **160** may send, to the AMF **155**, one or more messages comprising a response message. The response message (e.g., Nsmf_PDUSession_CreateSM Response) may comprise one or more of: cause information, N2 SM information, and/or N1 SM container. The N2 SM information may comprise one or more of a PDU session ID, QoS profile, SN tunnel information, or S-NSSAI, session-AMBR. The N1 SM container may comprise a PDU session establishment accept. The PDU session establishment accept may comprise one or more of a: QoS rule, SSC mode, S-NSSAI, allocated IPv4 address, or session-AMBR. The N2 SM information may comprise information that the AMF **155** may forward to the (R)AN **105**. The CN tunnel information may correspond to the Core Network address of the N3 tunnel corresponding to the PDU Session. The QoS profile may provide the (R)AN **105** with the mapping between QoS parameters and QoS flow identifiers. Multiple QoS profiles may be provided to the (R)AN **105**. The PDU session ID may be used by AN signaling with the wireless device **100** to indicate to the wireless device **100** an association between AN resource and a PDU Session for the wireless device **100**.

(89) At step **1011**, the AMF **155** may send, to the (R)AN **105**, an N2 PDU session request. The N2 PDU session request may comprise one or more of N2 SM information or a NAS message. The NAS message may comprise one or more of: a PDU session ID and/or an N1 SM container (e.g., a PDU session establishment accept message). The AMF **155** may send the NAS message comprising a PDU session ID and a PDU session establishment accept messages (e.g., that may be targeted to the wireless device **100**), and N2 SM information that may be received from the SMF **160**, within the N2 PDU session request to the (R)AN **105**.

(90) At step **1012**, the (R)AN **105** may send, to the wireless device **100**, one or more messages for a resource setup. The wireless device **100** may send, to the (R)AN **105** one or more messages for the AN resource setup. The (R)AN **105** may issue an AN specific signaling exchange with the wireless device **100** that may be related to the information received from SMF **160**. For example, an RRC connection reconfiguration (e.g., for a 3GPP RAN) may take place with the wireless device **100** establishing the necessary RAN resources related to the QoS rules for the PDU session request received at step **1010**. The (R)AN **105** may allocate (R)AN N3 tunnel information for the PDU session. The (R)AN **105** may forward the NAS message (e.g., comprising one or more of a PDU session ID, or N1 SM container such as a PDU session establishment accept message) that may be provided at step **1010** to the wireless device **100**. The (R)AN **105** may provide the NAS message to

the wireless device **100**, for example, if the necessary RAN resources have been established and/or the allocation of (R)AN tunnel information has been successful.

(91) At step **1013**, the (R)AN **105** may send, to the AMF **155**, an N2 PDU session response. The N2 PDU session response may comprise one or more of: a PDU session ID, a cause message, and/or N2 SM information. N2 SM information may comprise one or more of: a PDU Session ID, (R)AN tunnel information, and/or a list of accepted and/or rejected QoS profile(s). The (R)AN tunnel info may correspond to the access network address of the N3 tunnel corresponding to the PDU session.

(92) At step **1014**, the AMF **155** may send, to the SMF **160**, an SM context request message (e.g., Nsmf_PDUSession_UpdateSMContext Request). The SM context request message may comprise, for example, N2 SM information. The AMF **155** may forward the N2 SM information, that may be received from the (R)AN **105**, to the SMF **160**.

(93) At step **1015**, the SMF **160** may initiate an N4 session establishment procedure with the UPF **110** (e.g., if the N4 session for the PDU session was not already established). Additionally or alternatively, the SMF **160** may initiate an N4 session modification procedure with the UPF **110**. The SMF **160** may provide AN tunnel information and CN tunnel information. The CN tunnel information may need to be provided, for example, if the SMF **160** selected CN tunnel info.

(94) At step **1016**, the UPF **110** may provide an N4 session establishment and/or modification response to the SMF **160**.

(95) At step **1017**, the SMF **160** may send, to the AMF **155**, an SM context response message (e.g., Nsmf_PDUSession_UpdateSMContext Response). The SM context response message may comprise a cause message. The AMF **155** may forward relevant events to the SMF **160**, for example, after step **1017** and/or for a handover where the (R)AN tunnel information may change and/or the AMF may be relocated.

(96) FIG. **11** shows an example of a user plane protocol stack. The user plane protocol stack between the wireless device **100** and the (R)AN **105** may comprise, for example, service data adaptation protocol (SDAP), PDCP, RLC, MAC, and PHY sublayers. The main services and functions of the PDCP sublayer for the user plane may comprise, for example one or more of: sequence numbering; header compression and decompression (e.g., ROHC); transfer of user data; reordering and duplicate detection; PDCP PDU routing (e.g., for split bearers); retransmission of PDCP SDUs; ciphering, deciphering, and integrity protection; PDCP SDU discard; PDCP re-establishment and data recovery for RLC AM; and/or duplication of PDCP PDUs.

(97) The main services and functions of the PDCP sublayer for the control plane may comprise, for example, one or more of: sequence numbering; ciphering, deciphering, and integrity protection; transfer of control plane data; duplicate detection; and/or duplication of PDCP PDUs. For the header compression and decompression function of the PDCP sublayer, the header compression protocol may be based on the Robust Header Compression (ROHC) framework (e.g., such as in IETF RFC 5795: “The RObust Header Compression (ROHC) Framework”). There may be multiple header compression algorithms, called profiles, defined for the ROHC framework. A profile may be specific to the particular network layer, transport layer, or upper layer protocol combination (e.g., TCP/IP and RTP/UDP/IP). The ROHC channel may be specified as part of the ROHC framework (e.g., such as in IETF RFC 5795). The ROHC framework may include how to multiplex different flows (e.g., header compressed or not) over the ROHC channel, and/or how to associate a specific IP flow with a specific context state (e.g., during initialization of the compression algorithm for that flow). The implementation of the functionality of the ROHC framework and/or of the functionality of the supported header compression profiles may not covered in the 3GPP specifications. The following profiles may be supported, for example, by 3GPP 5G specification TS 38.323:

(98) TABLE-US-00001 TABLE 1 Supported header compression protocols and profiles
Profile Identifier Usage Reference
0x0000 No compression RFC 5795
0x0001 RTP/UDP/IP RFC 3095, RFC 4815
0x0002 UDP/IP RFC 3095, RFC 4815
0x0003 ESP/IP RFC 3095, RFC 4815
0x0004 IP

RFC 3843, RFC 4815 0x0006 TCP/IP RFC 6846 0x0101 RTP/UDP/IP RFC 5225 0x0102 UDP/IP RFC 5225 0x0103 ESP/IP RFC 5225 0x0104 IP RFC 5225

(99) The PDCP Data PDU may be used to convey one or more of: a PDCP SDU SN; user plane data; control plane data; and/or a MAC-I.

(100) FIG. 12 shows an example of a PDCP data PDU. A PDCP data PDU with 12 bits in PDCP SN may be used for signaling radio bearers carrying control plane data (SRBs). A PDCP PDU may be a bit string that is byte aligned (e.g., arranged in multiple of 8 bits) in length. Bit strings may be represented by tables in which the most significant bit may be the leftmost bit of the first line of the table (e.g., in Table 1), the least significant bit may be the rightmost bit on the last line of the table, and more generally, the bit string may to be read from left to right and in the reading order of the lines. The bit order of a parameter field within a PDCP PDU may be represented with the first and most significant bit in the leftmost bit and the last and least significant bit in the rightmost bit.

PDCP SDUs may be bit strings that may be byte aligned in length. A compressed or uncompressed SDU may be included into a PDCP Data PDU from the first bit onward. The PDCP control PDU may be used to convey one or more of a PDCP status report or an interspersed ROHC feedback.

(101) FIG. 13 shows an example of a PDCP control PDU. The PDCP control PDU may carry one interspersed ROHC feedback that may be applicable for a data radio bearer which may utilize RLC UM (e.g., UM DRBs), and for a data radio bearer which may utilize RLC AM (e.g., AM DRBs). The PDU type may indicate the type of control information included in the corresponding PDCP control PDU, such as shown in Table 2 below.

(102) TABLE-US-00002 TABLE 2 PDU type Bit Description 000 PDCP status report 001 Interspersed ROHC feedback 010-111 Reserved

(103) FIG. 14 shows an example of a layer 2 data flow. A transport block may be generated at a MAC layer, for example, by concatenating two RLC PDUs from a radio bearer (RB). The two RLC PDUs from the RB may each correspond to one Ethernet frame and/or IP packet (e.g., n and/or n+1). Headers and subheaders may be represented by “H”.

(104) A system (e.g., a 5G system) may support an Ethernet type PDU session. For an Ethernet PDU session type, an Ethernet packet filter set may be used, for example in one or more QoS rules and/or SDF template, to identify a QoS flow. The packet filter set (e.g., for an Ethernet PDU session type) may support packet filtering based on any combination of one or more of: source MAC address and/or destination MAC address; Ethertype (e.g., such as set forth by IEEE 802.3); customer-VLAN tag (C-TAG) and/or service-VLAN tag (S-TAG) VID fields (e.g., such as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP/DEI fields (e.g., such as set forth in IEEE 802.1Q); and/or IP packet filter set (e.g., if Ethertype indicates IPv4 and/or IPv6 payload).

(105) Ethernet type PDU sessions may be difficult to implement. Some legacy technologies may not support and/or transfer traffic of Ethernet type PDUs. Enhanced signaling mechanisms may be provided, however, to support traffic of Ethernet type PDUs. For example, signaling mechanisms and/or network protocols may provide capability to transmit and/or receive a wireless device MAC profile and/or an IP profile among network nodes. The wireless device MAC profile and/or an IP profile may be provided to improve network performance, for example, by providing capability to establish an Ethernet type PDU session. One or more devices (e.g., in a 5GC) may not allocate to a wireless device a MAC address and/or an IP address for an Ethernet type PDU session. Network signaling and/or performance may be improved by providing information for an Ethernet type PDU session. A UPF may receive one or more of: a source MAC address, a destination MAC address, and/or an Ethernet packet filter set. The UPF may associate one or more MAC addresses with a PDU session. Information associated with a wireless device may be provided, such as MAC addresses, Ethertype, customer-VLAN tag (C-TAG) and/or service-VLAN tag (S-TAG) VID, C-TAG and/or S-TAG PCP and/or DEI, and/or an IP packet filter set (e.g., if Ethertype indicates an IPv4 and/or an IPv6 payload). An SMF and/or a PCF may create and/or determine a corresponding policy (e.g., QoS control, charging control, gating, etc.) that may require packet filter information,

for example, to detect a service data flow and/or a QoS flow. A UPF may receive one or more policies from an SMF, for example, to detect and/or process a service data flow and/or a QoS flow. A UPF may store one or more MAC addresses (e.g., that may be received from the wireless device). The UPF may associate one or more MAC addresses with a PDU session (e.g., an Ethernet PDU session).

(106) FIGS. **15A-15D** show examples of registration procedures. A wireless device (e.g., wireless device **100**) may perform a registration procedure, for example, in a CM-IDLE state. FIGS. **15A** and **15B** show registration procedures that may involve a PCF (e.g., PCF **135**). FIGS. **15C** and **15D** show registration procedures that may not involve a PCF (e.g., PCF **135**). Steps **1501-1512** in FIG. **15A** correspond to steps **1501-1512**, respectively, in FIG. **15C**, unless otherwise indicated. Steps **1513-1527** in FIG. **15B** correspond to steps **1513-1527**, respectively, in FIG. **15D**, unless otherwise indicated.

(107) At step **1501** (in FIGS. **15A** and **15C**), a wireless device (e.g., wireless device **100**) may send a registration request to a (R)AN **105**. The registration request may comprise an AN message. The AN message may comprise one or more of: an AN parameter or an RM-NAS registration request. An RM-NAS registration request may comprise one or more of: a registration type, a SUPI or 5G-GUTI, a security parameter, an NSSAI, a device capability (e.g., a 5GCN capability of a wireless device), a PDU session status, a PDU session to be re-activated, a follow on request, and/or a MICO mode preference. A wireless device (e.g., wireless device **100**) may include in the registration request one or more of Ethernet packet filter sets. An Ethernet packet filter set may be identified on a per device basis (e.g., per wireless device identified by a wireless device identifier), on a per data network basis (e.g., per APN, which may be indicated by a DNN), on a per network slice basis (e.g., indicated by an S-NSSAI); and/or on a per PDU session (e.g., indicated by a PDU session ID). An Ethernet packet filter set may comprise one or more of: a source MAC address, a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); a C-TAG and/or S-TAG VID field (e.g., as set forth in IEEE 802.1Q); a C-TAG and/or S-TAG PCP and/or DEI field (e.g., as set forth in IEEE 802.1Q); and/or an IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). An IP packet filter set may comprise one or more of: a source IP address, a destination IP address, and/or an IPv6 prefix; a source port number and/or a destination port number; a protocol ID of the protocol above IP and/or a next header type; a type of service (TOS) (e.g., for IPv4), a traffic class (e.g., for IPv6), and/or a mask; a flow label (e.g., for IPv6); and/or a security parameter index. A device identifier may indicate a user identity and/or an identifier of a wireless device. The device identifier may comprise a wireless device network access identifier, a SUPI, a 5G-GUTI, and/or other wireless device identifier(s).

(108) At step **1502** (in FIGS. **15A** and **15C**), the (R)AN **105** may perform an AMF selection. The (R)AN **105** may select an AMF (e.g., AMF **155-1**) based on a (R)AT and/or an NSSAI, if available. The (R)AN **105** may select an AMF, for example, if a SUPI is included and/or if a valid AMF is not indicated (e.g., such as by a 5G GUTI). The (R)AN **105** may select the new AMF **155-1**.

(109) At step **1503** (in FIGS. **15A** and **15C**), the (R)AN **105** may send, to the selected AMF (e.g., the new AMF **155-1**), a message comprising a registration request. The message may comprise one or more of: N2 parameters and/or an RM-NAS registration request. The registration request may comprise one or more of: a registration type, a subscriber permanent identifier (e.g., a 5G-GUTI), a security parameter, an NSSAI and/or a MICO mode preference, a PDU session status, and/or a PDU session(s) (e.g., that may be determined to be re-activated). The message comprising the registration request may comprise one or more Ethernet packet filter set(s) information that may have been received from the wireless device **100**.

(110) At step **1504** (in FIGS. **15A** and **15C**), the new AMF **155-1** may send, to the old AMF **155-2**, a context transfer message. The new AMF **155-1** may invoke, for example, the `Namf_Communication_UEContextTransfer` service operation on the old AMF **155-2**, for example, if an identifier (e.g., a 5G-GUTI of the wireless device **100**) was included in the registration request

and/or if the serving AMF **155-2** has changed since a last registration. The context transfer message may comprise a complete registration request information element, which may be integrity protected, to request the wireless device **100** SUPI and/or MM context information.

(111) At step **1505** (in FIGS. **15A** and **15C**), the old AMF **155-2** may send, to the new AMF **155-1**, a response message. The old AMF **155-2** may respond to the new AMF **155-1** with a response (e.g., a Namf_Communication_UEContextTransfer response) comprising the wireless device **100** SUPI and/or MM context information. If the old AMF **155-2** has information about active PDU sessions, the old AMF **155-2** may include in an existing PDU session(s) (e.g., which may have been established before the response message) one or more of: SMF information (e.g., SMF identities and/or SMF addresses); UPF information (e.g., UPF identities and/or UPF addresses); PDU session ID(s); wireless device address (e.g., for IPv4) and/or wireless device prefix (e.g., for IPv6) if available; and/or DNN if available.

(112) At step **1506** (in FIGS. **15A** and **15C**), the new AMF **155-1** may send, to the wireless device **100**, a message comprising an identity request. An identity request procedure may be initiated by the new AMF **155-1** sending an identity request message to the wireless device **100**, for example, if the SUPI is not provided by the wireless device **100** and/or if the SUPI is not retrieved from the old AMF **155-2**.

(113) At step **1507** (in FIGS. **15A** and **15C**), the wireless device **100** may send, to the new AMF **155-1**, a message comprising an identity response. The wireless device **100** may respond to the identity request from step **1506** with an identity response message, to the new AMF **155-1**, that comprises the SUPI.

(114) At step **1508** (in FIGS. **15A** and **15C**), the new AMF-1 may perform an AUSF selection. The new AMF **155-1** may decide to invoke an AUSF selection, for example, after receiving the identity response from step **1507**.

(115) At step **1509** (in FIGS. **15A** and **15C**), authentication and/or security processes may be performed. For example, the AUSF **150** may initiate authentication of the wireless device **100**, and/or the new AMF **155-1** may initiate NAS security functions.

(116) At step **1510** (in FIGS. **15A** and **15C**), the new AMF **155-1** may send, to the old AMF **155-2**, a message comprising a registration complete notification. The new AMF **155-1** may indicate to the old AMF **155-2** that a registration of the wireless device **100** in the New AMF **155-1** has been completed, for example, by invoking a Namf_Communication_RegistrationCompleteNotify service operation.

(117) At step **1511** (in FIGS. **15A** and **15C**), the new AMF **155-1** may send, to the wireless device **100**, a message comprising an identity request. The wireless device **100** may send, to the new AMF **155-1**, a response to an identity request (e.g., which may provide an indication of the identity of the wireless device **100**). The identity request procedure may be initiated by the AMF **155-1** sending an identity request message to the wireless device **100** to retrieve a PEI, for example, if the PEI was not provided by the wireless device **100** and/or if the PEI was not retrieved from the old AMF **155-2**.

(118) At step **1512** (in FIGS. **15A** and **15C**), the new AMF **155-1** may send, to the old AMF **155-2**, a message comprising an identity check. The old AMF **155-2** may send, to the new AMF **155-1**, a message comprising a response to the identity check (e.g., which may provide a confirmation of the identity of the wireless device **100**). The New AMF **155-1** may initiate an ME identity check, for example, by invoking an N5g-eir_MEIdentityCheck_Get service operation.

(119) At step **1513** (in FIGS. **15B** and **15D**), the new AMF **155-1** may perform a UDM selection. The new AMF **155-1** may select a UDM (e.g., the UDM **140**) based on the SUPI.

(120) At step **1514** (in FIGS. **15B** and **15D**), registration, update, and removal messages may be sent between the UDM **140** and the new AMF **155-1** and/or the old AMF **155-2**. At step **1514a**, the new AMF **155-1** may invoke a registration, for example, by sending a message (e.g., Nudm_UEContextManagement_Registration) to the UDM **140**. The new AMF **155-1** may invoke

the registration, for example, if the AMF has changed since a last registration, if the wireless device **100** provides a SUPI that does not refer to a valid context in the AMF **155-1**, and/or if the wireless device **100** registers to an AMF that it has already registered for other access (e.g., a non-3GPP access, such that the UE is registered over a non-3GPP access and initiates the registration procedure to add a 3GPP access). A subscription data retrieval indication may be included, for example, if there is no subscription context for the UE in the New AMF **155-1**. The new AMF **155-1** may provide the access type it serves for the wireless device **100** to the UDM **140**. The access type may be set to a particular access type, such as a 3GPP access. The UDM **140** and/or the AMF **155-1** may store the associated access type. At step **1514b**, the UDM **140** may invoke a service operation (e.g., the Nudm_SubscriptionData_UpdateNotification) to provide subscription data from the UDM **140** to the new AMF **155-1**, for example, if the subscription data retrieval indication was included in step **1514a**. If the UDM **140** stores the associated access type, it may cause the UDM **140** to initiate a removal procedure by sending a message (e.g., Nudm_UEContextManagement_RemoveNotification), to the old AMF **155-2** that may correspond to a particular access (e.g., 3GPP access). The old AMF **155-2** may remove the MM context of the wireless device **100**, for example, after or in response to receiving a message from the UDM **140**, for example, as part of the removal procedure.

(121) At step **1515** (in FIG. **15B**), the new AMF **155-1** may perform a PCF selection. The new AMF **155-1** may select a PCF, for example, based on one or more of: the SUPI; an Ethernet MAC address; a wireless device address (e.g., for IPv4); a prefix (e.g., for IPv6) of an Ethernet payload for an existing PDU session(s) (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload); and/or a DNN. The new AMF **155-1** may select the PCF **135**. While step **1515** is additionally shown in FIG. **15D** for reference, this step may not be performed in FIG. **15D**, for example, if the PCF **135** is not used for this step. For example, in FIG. **15D**, the new AMF **155-1** may send/receive one or more messages for policy control directly to/from the SMF **160** without selecting a PCF. Step **1515** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(122) At step **1516** (in FIG. **15B**), one or more messages for policy control(s) may be sent by the new AMF **155-1** to the PCF **135**, and/or by the PCF **135** to the new AMF **155-1**. The new AMF **155-1** may send a request, to the PCF **135**, to apply operator policies for the wireless device **100**, for example, if the new AMF **155-1** has not yet obtained an access and mobility policy for the wireless device **100** and/or if the access and mobility policy in the new AMF **155-1** may no longer be valid. The new AMF **155-1** may initiate a creation of a policy control session with the PCF **135** by sending a message to the PCF **135** (e.g., for a Npcf_PolicyControl_PolicyCreate service operation). The message from the new AMF **155-1** may comprise Ethernet packet filter set(s) information that is per PDU session (e.g., which may be indicated by a PDU session ID), per wireless device (e.g., that may be indicated by a wireless device identity), per data network (e.g., an APN indicated by a DNN), and/or per network slice (e.g., that may be indicated by an S-NSSAI received from the (R)AN **105**). The PCF **135** may make the access and mobility control policy decision based on the Ethernet packet filter set(s) information received from the New AMF **155-1** and/or respond to the new AMF **155-1** (e.g., via an Npcf_PolicyControl_PolicyCreate service operation message) with the access and mobility control policy for the wireless device **100**. The access and mobility control policy may comprise service area restrictions and/or a RAT frequency selection priority (RFSP) index. While step **1516** is additionally shown in FIG. **15D** for reference, this step may not be performed in FIG. **15D**, for example, if the PCF **135** is not used for these steps. For example, in FIG. **15D**, the new AMF **155-1** may send/receive one or more messages for policy control directly to/from the SMF **160**. Step **1516** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(123) At step **1517** (in FIGS. **15B** and **15D**), one or more PDU sessions may be created and/or modified, such as described further below regarding FIGS. **16A-16B** and/or **17A-17B**. The new

AMF **155-1** may enforce the access and mobility control policy, re-activate one or more PDU sessions, and/or create one or more PDU sessions. The interactions between the AMF(s) (e.g., new AMF **155-1** and/or old AMF **155-2**), SMF (e.g., SMF **160**), PCF (e.g., PCF **135**) (if supported) and/or UPF (e.g., UPF **110**) to re-activate one or more PDU sessions and/or create one or more PDU sessions may correspond to steps **1601** to **1606** (in FIGS. **16A-16B**). Step **1517** (in FIGS. **15B** and **15D**) may be performed, for example, in response to the message received from the PCF **135** (e.g., if supported). The new AMF **155-1** may make the access and mobility control policy decision based on the Ethernet packet filter set(s) information received from the (R)AN **105**, for example, if PCC is not supported and/or if there is no PCF in the network.

(124) At step **1518** (in FIGS. **15B** and **15D**), the new AMF **155-1** may send, to the (R)AN **105**, a PDU session request. The PDU session request may comprise a NAS message. The PDU session request (e.g., the NAS message) may comprise one or more of: a PDU Session ID; CN N3 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or TEID) for a PDU session; and/or a PDU session establishment accept (e.g., which may be targeted to the wireless device **100**).

(125) At step **1519** (in FIGS. **15B** and **15D**), an AN resource setup procedure may be performed between the (R)AN **105** and the wireless device **100**. The (R)AN **105** may issue an AN specific signaling exchange with the wireless device **100** that may be related to information received from SMF. A connection reconfiguration procedure (e.g., an RRC Connection Reconfiguration for a 3GPP RAN) may be performed such that the wireless device **100** may establish, for example, sufficient RAN resources according to one or more authorized QoS rules for the PDU Session(s). The (R)AN **105** may: allocate (R)AN N3 tunnel information comprising a (R)AN address, identity, and/or tunnel end identifier (TEID) of an N3 tunnel for a downlink for the PDU session(s); correlate the (R)AN N3 tunnel with the CN N3 tunnel for the PDU session(s); and/or forward the NAS message. The NAS message may comprise, for example, PDU session ID(s) and/or N1 SM information (e.g., a PDU session establishment accept) that may be provided at step **1518** to the UE. The (R)AN **105** may provide the NAS message to the UE, for example, if the necessary RAN resources have been established and/or if the allocation of (R)AN tunnel information has been successful.

(126) At step **1520** (in FIGS. **15B** and **15D**), the (R)AN **105** may send, to the new AMF **155-1**, a message comprising a PDU session response. The PDU session response (e.g., an N2 PDU session response) may comprise one or more of: PDU Session ID(s), cause information, and/or N2 SM information. The N2 SM information may comprise, for example, PDU Session ID(s), (R)AN N3 tunnel information, and/or a list of accepted and/or rejected QoS profile(s).

(127) At step **1521** (in FIGS. **15B** and **15D**), one or more PDU sessions may be modified, such as described further below regarding FIGS. **17A-17B**. One or more of the new AMF **155-1**, old AMF **155-2**, SMF **160**, and/or PCF **135** (if supported) may send, to the UPF **110**, the (R)AN N3 tunnel information. Interactions between AMF(s), SMF, PCF (if supported), and UPF to modify one or more PDU sessions may correspond to steps **1701** to **1706** in FIGS. **17A-17B**. Additionally or alternatively, step **1521** may be performed before step **1527** and/or after step **1526** described below.

(128) At step **1522** (in FIGS. **15B** and **15D**), the new AMF **155-1** may send a request to the N3IWF. At step **1523** (in FIGS. **15B** and **15D**) the N3IWF may send a response to the new AMF **155-1**. The New AMF **155-1** may determine to modify the N2AP UE-TNLA-binding toward N3IWF, for example, by sending an N2 request message. The N3IWF may respond to the N2 request message with an N2 response message.

(129) At step **1524** (in FIG. **15B**), the old AMF **155-2** may send, to the PCF **135**, a message for one or more policy deletions. The PCF **135** may send (e.g., as a response) a message to the old AMF **155-2**, for example, that may confirm one or more policy deletions. The old AMF **155-2** may terminate a wireless device context in the PCF **135**, for example, if the old AMF **155-2** previously requested wireless device context to be established in the PCF **135**. The old AMF **155-2** may terminate the wireless device context in the PCF **135** by invoking the

Npcf_PolicyControl_PolicyDelete service operation. While step **1524** is additionally shown in FIG. **15D** for reference, this step may not be performed in FIG. **15D**, for example, if the PCF **135** is not used for this step. For example, in FIG. **15D**, the old AMF **155-2** may send/receive one or more messages for policy deletion to/from the SMF **160**. Step **1524** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(130) At step **1525** (in FIGS. **15B** and **15D**), the new AMF **155-1** may send, to the wireless device **100**, a message comprising a registration acceptance. For example, the new AMF **155-1** may send a registration accept message to the wireless device **100** indicating that the registration has been accepted. A 5G-GUTI may be included in the registration accept message, for example, if the new AMF **155-1** allocates a new 5G-GUTI.

(131) At step **1526** (in FIGS. **15B** and **15D**), the wireless device **100** may send, to the new AMF **155-1**, a message comprising a registration completion. For example, the wireless device **100** may send a registration complete message to the new AMF **155-1** to acknowledge a new assignment, such as a new 5G-GUTI being assigned.

(132) At step **1527** (in FIGS. **15B** and **15D**), one or more PDU sessions may be released, such as described further below regarding FIGS. **18A-18B**. Interactions between AMF(s) (e.g., the new AMF **155-1** and/or the old AMF **155-2**), an SMF (e.g., the SMF **160**), a PCF (e.g., the PCF **135**) (if supported), and/or a UPF (e.g., the UPF **110**) to delete one or more PDU sessions may correspond to steps **1801-1806** in FIGS. **18A-18B**. Additionally or alternatively, step **1527** may be performed after step **1521** and/or before step **1522**.

(133) FIGS. **16A** and **16B** show examples of PDU session creation procedures. FIG. **16A** shows PDU session creation procedures that may involve a PCF (e.g., PCF **135**). FIG. **16B** shows PDU session creation procedures that may not involve a PCF (e.g., PCF **135**). Steps **1601-1606** in FIG. **16A** correspond to steps **1601-1606**, respectively, in FIG. **16B**, unless otherwise indicated. Steps **1601-1606** may be performed, for example, as at least part of step **1517** described above regarding FIGS. **15A-15D**.

(134) At step **1601** (in FIGS. **16A** and **16B**), the new AMF **155-1** may send, to the SMF **160**, a message (e.g., PDU session create request) to request establishment of one or more PDU sessions. The new AMF **155-1** may send the message to request a creation of a PDU session, for example, based on one or more of the following conditions: the wireless device **100** may attempt or indicate an intention to activate one or more existing PDU sessions that have already been established; the wireless device **100** may attempt to or indicate an intention to establish one or more new PDU sessions; a local policy that may indicate the new AMF **155-1** has attempted or indicated an intention to establish one or more new PDU sessions; and/or other reasons to activate existing PDU session and/or to establish one or more new PDU sessions. One or more old PDU sessions may be released after one or more new PDU sessions have been established. The message (e.g., PDU session create request) to request establishment of one or more PDU sessions may comprise one or more of: an S-NSSAI and/or a network slicing instance ID. The S-NSSAI may comprise a slice and/or service type (SST) and/or a slice differentiator (SD) which may indicate an expected network slice behavior in terms of features and services. The network slicing instance ID may identify a network slicing instance. A PDU Session ID may identify a PDU session. A device identifier and/or a user identity associated with the wireless device (e.g., for an Ethernet type wireless device) may comprise one or more of: a SUPI, 5G-GUTI, and/or other wireless device identifier; a Data Network Name (DNN); and/or Ethernet packet filter set(s) information. Ethernet packet filter set information may be on a per PDU session basis (e.g., which may be indicated by a PDU session ID), a per wireless device basis (e.g., which may be indicated by one or more wireless device identities), on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., indicated by one or more S-NSSAI).

(135) At step **1602** (in FIG. **16A**), the SMF **160** may send, to the PCF **135**, a message comprising a policy request to request one or more policies for one or more PDU sessions. The SMF **160** may

perform one or more steps, for example, after or in response to a message from step **1601**. The SMF **160** may allocate an IPv6 prefix for one or more PDU session and N6 point-to-point tunneling (e.g., if the PDU Type is Ethernet PDU, where the N6 tunnel may be used to transmit the user data between the UPF and a Data Network). The SMF **160** may allocate the CN N6 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or tunnel endpoint identifier (TEID)) and/or the CN N3 tunnel info (e.g., UPF **110** address, UPF **110** identity, and/or TEID) for the PDU sessions). The SMF **160** may select a PCF. For example, the SMF **160** may select the same PCF that may already be serving an existing PDU session(s) (e.g., indicated by PDU session ID(s)). Additionally or alternatively, the SMF **160** may select a PCF based on one or more of: the SUPI; an Ethernet MAC address, a wireless device address (e.g., for IPv4), a prefix (e.g., for IPv6) of the Ethernet payload for the existing PDU session(s) (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload); and/or a DNN. While step **1602** is additionally shown in FIG. **16B** for reference, this step may not be performed in FIG. **16B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **16B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **1602** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(136) Additionally or alternatively, the SMF **160** may select a new PCF. The SMF **160** may send, to the new PCF (not shown) a message (e.g., policy request) to request one or more policies for the PDU session(s). The message may comprise information received from the new AMF **155-1**, such as the Ethernet packet filter set(s) information on a per PDU session basis (e.g., which may be indicated by a PDU session ID), on a per wireless device basis (which may be indicated by one or more wireless device identities, on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., which may be indicated by one or more S-NSSAI). The information from the new AMF **155-1** may comprise a prefix (e.g., for IPv6) for the PDU session (s) and/or N6 point-to-point tunneling (e.g., if the PDU Type is Ethernet PDU).

(137) If step **1602** is omitted, the SMF **160** may make one or more policy decisions based on information received from the New AMF **155-1**, such as one or more of: Ethernet packet filter set(s) information), subscription information, and/or other information. The SMF **160** may create a service data flow template for a policy rule based on the information received from the New AMF **155-1**.

(138) At step **1603** (in FIG. **16A**), the PCF **135** may send, to the SMF **160**, a message comprising a policy response. The PCF **135** may make a policy decision that may be based on information received from the SMF **160**. The policy decision may be based on, for example, one or more of: Ethernet packet filter set(s) information, subscription information, and/or other information. The PCF **135** may create a service data flow template for the policy rule based on the information received from the SMF **160**. The PCF **135** may send, to the SMF **160**, a message (e.g., a policy response) comprising one or more of: a QoS policy for the PDU session(s); a charging policy for the PDU session(s); traffic steering control for steering traffic; and/or other policies. The message comprising the policy response may comprise, for example, Ethernet packet filter sets information. While step **1603** is additionally shown in FIG. **16B** for reference, this step may not be performed in FIG. **16B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **16B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **1603** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(139) At step **1604** (in FIGS. **16A** and **16B**), the SMF **160** may send, to the UPF **110**, a message (e.g., user plane session establishment request) to request establishment of one or more user plane sessions for one or more PDU sessions. The SMF **160** may send the message to request establishment of the one or more user plane sessions for the one or more PDU sessions after or in response to receiving a policy from the PCF **135** (e.g., at step **1603**). The message to request establishment of one or more user plane sessions for the one or more PDU sessions may comprise one or more of: an S-NSSAI and/or a network slicing instance ID; the PDU session ID(s); the

device identifier and/or user identity associated with a wireless device (e.g., the wireless device **100**); a data network name (DNN); CN N6 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or TEID) and/or CN N3 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or TEID) for the PDU session(s) (e.g., if corresponding tunnel information is allocated by the SMF), and/or one or more policies for the PDU sessions (e.g., which may be included with Ethernet packet filter set(s) information).

(140) At step **1605** (in FIGS. **16A** and **16B**), the UPF **110** may send, to the SMF **160**, a message comprising a response to the request (e.g., at step **1604**). The UPF **110** may send, for example, a user plane session establishment response that is based on the message received from the SMF **160**. The UPF **110** may set up the user plane session(s). The UPF **110** may acknowledge the SMF **160**, for example, by sending the response message (e.g., user plane session establishment response). The response message may comprise one or more of: the CN N6 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or TEID) and/or CN N3 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or TEID) for the PDU session(s) (e.g., if corresponding tunnel information is allocated by the UPF). The UPF **110** may perform service flow detection and/or policy enforcement with Ethernet packet filter set information, for example, after or upon receiving the user plane data packet.

(141) At step **1606** (in FIGS. **16A** and **16B**), the SMF **160** may send, to the new AMF **155-1**, a message comprising a session creation response (e.g., PDU session create response). The SMF **160** may acknowledge the new AMF **155-1**, for example, by sending a response message (e.g., a PDU session create response). The response message may comprise one or more of: the allowed S-NSSAI and/or the network slicing instance ID; the PDU session ID(s); a device identifier and/or a user identity associated with the wireless device (e.g., wireless device **100**); the data network name (DNN); CN N3 tunnel info (e.g., UPF **110** address, or UPF **110** identity, and/or TEID) for the PDU session(s); and/or one or more policies for the PDU sessions comprising (e.g., which may be included with the Ethernet packet filter set(s) information).

(142) FIGS. **17A** and **17B** show examples of PDU session modification procedures. FIG. **17A** shows PDU session modification procedures that may involve a PCF (e.g., PCF **135**). FIG. **17B** shows PDU session modification procedures that may not involve a PCF (e.g., PCF **135**). Steps **1701-1706** in FIG. **17A** correspond to steps **1701-1706**, respectively, in FIG. **17B**, unless otherwise indicated. Steps **1701-1706** may be performed, for example, as at least part of step **1517** and/or step **1521** described above regarding FIGS. **15A-15D**.

(143) At step **1701** (in FIGS. **17A** and **17B**), the new AMF **155-1** may send, to the SMF **160**, a message (e.g., PDU session modification request) to request a modification (e.g., an update) of one or more PDU sessions. The message to request a modification of one or more PDU sessions may comprise one or more of: the (R)AN N3 tunnel information (e.g., (R)AN address, RAN identity, and/or TEID) for the PDU session(s); an S-NSSAI and/or a network slicing instance ID; PDU session ID(s) for one or more PDU sessions; device identifier and/or user identity associated with a wireless device (e.g., the wireless device **100**); data network name (DNN); and/or Ethernet packet filter set(s) information on a per PDU session basis (e.g., which may be indicated by a PDU session ID), on a per wireless device basis (e.g., which may be indicated by one or more wireless device identities, on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., which may be indicated by one or more S-NSSAI).

(144) At step **1702** (in FIG. **17A**), the SMF **160** may send, to the PCF **135**, a message comprising a policy request to request one or more policies for one or more PDU sessions. The message comprising the policy request may comprise information received from the new AMF **155-1**, such as one or more of: Ethernet packet filter set(s) information; a prefix (e.g., for IPv6) for the PDU session(s); and/or N6 point-to-point tunneling (e.g., if the PDU type is an Ethernet PDU). Step **1702** may correspond to step **1602**. While step **1702** is additionally shown in FIG. **17B** for reference, this step may not be performed in FIG. **17B**, for example, if the PCF **135** is not used for

this step. For example, in FIG. 17B, the SMF 160 may determine one or more policies without communication with a PCF. Step 1702 may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(145) At step 1703 (in FIG. 17A), the PCF 135 may send, to the SMF 160, a message comprising a policy response. The PCF 135 may make a policy decision based on information received from the SMF 160. The policy decision may be based on, for example, one or more of: Ethernet packet filter set(s) information, subscription information, and/or other information. The PCF 135 may create a service data flow template for the policy rule based on the information received from the SMF 160. The PCF 135 may send, to the SMF 160, a message (e.g., a policy response) comprising one or more of: a QoS policy for the PDU session(s); a charging policy for the PDU session(s); traffic steering control for steering traffic; and/or other policies. The message comprising the policy response may comprise, for example, Ethernet packet filter sets information. Step 1703 may correspond to step 1603. While step 1703 is additionally shown in FIG. 17B for reference, this step may not be performed in FIG. 17B, for example, if the PCF 135 is not used for this step. For example, in FIG. 17B, the SMF 160 may determine one or more policies without communication with a PCF. Step 1703 may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(146) At step 1704 (in FIGS. 17A and 17B), the SMF 160 may send, to the UPF 110, a message (e.g., user plane session modification request) to request modification of one or more user plane sessions for one or more PDU sessions. The SMF 160 may send the message to request modification of the one or more user plane sessions, for example, after or in response to receiving one or more policies from the PCF 135. The message to request modification of the one or more user plane sessions may comprise one or more of: Ethernet packet filter set(s) information, subscription information, and/or other information. The SMF 160 may create a service data flow template for one or more policy rules, for example, based on information received from the new AMF 155-1. The SMF 160 may send to the UPF 110 the message to request modification (e.g., update) of one or more user plane sessions for one or more PDU sessions comprising one or more of: (R)AN N3 tunnel information (e.g., (R)AN address, (R)AN identity, and/or TEID) for the PDU session(s); S-NSSAI and/or network slicing instance ID; PDU session ID(s); device identifier and/or user identity associated with the wireless device; a data network name (DNN); CN N6 tunnel info (e.g., UPF 110 address, UPF 110 identity, and/or TEID) and CN N3 tunnel information (e.g., UPF 110 address, UPF 110 identity, and/or TEID) for the PDU session(s); and/or one or more policies for the PDU session(s) (e.g., which may be included with the Ethernet packet filter set(s) information).

(147) At step 1705 (in FIGS. 17A and 17B), the UPF 110 may send, to the SMF 160, a message comprising a response to the request (e.g., at step 1704). The UPF 110 may send, for example, a user plane session modification response that is based on the message received from the SMF 160. The UPF 110 may update the user plane session(s). The UPF 110 may correlate a CN N3 tunnel with a (R)AN N3 tunnel for the PDU session(s). The UPF 110 may acknowledge the SMF 160, for example, by sending the response message (e.g., user plane session modification response). The response message may comprise one or more of: the CN N6 tunnel information (e.g., UPF 110 address, UPF 110 identity, and/or TEID) and/or CN N3 tunnel information (e.g., UPF 110 address, UPF 110 identity, and/or TEID) for the PDU session(s) (e.g., if corresponding tunnel information is allocated by the UPF). The UPF 110 may perform service flow detection and/or policy enforcement with Ethernet packet filter set information, for example, after or upon receiving the user plane data packet.

(148) At step 1706 (in FIGS. 17A and 17B), the SMF 160 may send, to the new AMF 155-1, a message comprising a session modification response (e.g., PDU session modification response). The SMF 160 may acknowledge the new AMF 155-1, for example, by sending a response message (e.g., a PDU session modification response). The response message may comprise one or more of:

the allowed S-NSSAI and/or the network slicing instance ID; the PDU session ID(s); a device identifier and/or a user identity associated with the wireless device (e.g., wireless device **100**); the data network name (DNN); the CN N3 tunnel information (e.g., UPF **110** address, UPF **110** identity, and/or TEID) for the PDU session(s); and/or one or more policies for the PDU sessions (e.g., which may be included with the Ethernet packet filter set(s) information).

(149) FIGS. **18A** and **18B** show examples of PDU session release procedures. FIG. **18A** shows PDU session release procedures that may involve a PCF (e.g., PCF **135**). FIG. **18B** shows PDU session release procedures that may not involve a PCF (e.g., PCF **135**). Steps **1801-1806** in FIG. **18A** correspond to steps **1801-1806**, respectively, in FIG. **18B**, unless otherwise indicated. Steps **1801-1806** may be performed, for example, as at least part of step **1521** described above regarding FIGS. **15A-15D**.

(150) At step **1801** (in FIGS. **18A** and **18B**), the new AMF **155-1** may send, to the old AMF **155-2**, a message (e.g., PDU session release request) to request releasing of one or more PDU sessions. The message may comprise one or more of: the S-NSSAI and/or the network slicing instance ID, the PDU session ID(s), a device identifier and/or a user identity associated with the wireless device, and/or the data network name (DNN).

(151) At step **1802** (in FIGS. **18A** and **18B**), the old AMF **155-2** may send, to the SMF **160**, a message (e.g., PDU session release request) to request releasing of one or more PDU sessions. The message may be sent by the old AMF **155-2** after or in response to receiving the PDU session release request message from the new AMF **155-1** (e.g., at step **1801**). The message sent by the old AMF **155-2** may comprise the information received from the new AMF **155-1** (e.g., at step **1801**).

(152) At step **1803** (in FIGS. **18A** and **18B**), the SMF **160** may send, to the UPF **110**, a message (e.g., user plane session release request) to request releasing of one or more user plane sessions for the PDU session(s). The SMF **160** may send the message after or in response to receiving the PDU session release request message from the old AMF **155-2**. The message sent by the SMF **160** may comprise the information received from the old AMF **155-2** (e.g., at step **1802**).

(153) At step **1804** (in FIGS. **18A** and **18B**), the UPF **110** may send, to the SMF **160**, a message (e.g., user plane session release response) to respond to the message to request releasing of one or more user plane sessions for the PDU session(s). The UPF **110** may release the corresponding user plane sessions. The UPF **110** may acknowledge, to the SMF **160**, by sending a response message (e.g., user plane session release response). If the UPF **110** has already released the corresponding user plane session (s), the UPF **110** may acknowledge the SMF **160** by sending a response message (e.g., user plane session release response).

(154) At step **1805** (in FIGS. **18A** and **18B**), the SMF **160** may send, to the old AMF **155-2**, a message (e.g., PDU session release response) comprising a response to a release request. The SMF **160** may acknowledge, to the old AMF **155-2**, a release, for example, by sending a response message (e.g., PDU session release response).

(155) At step **1806** (in FIGS. **18A** and **18B**), the old AMF **155-2** may send, to the new AMF **155-1**, a message (e.g., PDU session release response) comprising a response to a release request. The old AMF **155-2** may acknowledge the new AMF **155-1** by sending a response message (e.g., PDU session release response). The new AMF **155-1** may send one or more messages to the (R)AN **105** and/or to the wireless device **100** to release the related resource. Step **1804** and/or step **1805** may be omitted. For example, the UPF **110** may release the user plane session(s) without a request from the SMF **160**.

(156) At step **1807** (in FIG. **18A**), the SMF **160** may send, to the PCF **135**, a message (e.g., policy delete request) to request removal of one or more policies for the PDU session(s). The message to request removal of the one or more policies for the PDU sessions may comprise the information received from the old AMF **155-2** (e.g., from step **1802**). While step **1807** is additionally shown in FIG. **18B** for reference, this step may not be performed in FIG. **18B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **18B**, the SMF **160** may remove one or more policies

for the PDU sessions from the SMF **160**, without communicating with a PCF. Step **1807** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(157) At step **1808** (in FIG. **18A**), the PCF **135** may send, to the SMF **160**, a message (e.g., policy delete response) to confirm deletion of one or more policies for the PDU session(s). The PCF **135** may acknowledge, to the SMF **160**, deletion of one or more policies for the PDU session(s) by sending a response message (e.g., policy delete response). While step **1808** is additionally shown in FIG. **18B** for reference, this step may not be performed in FIG. **18B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **18B**, the SMF **160** may remove one or more policies for the PDU sessions from the SMF **160**, without communicating with a PCF. Step **1808** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(158) FIGS. **19A** and **19B** show examples of PDU session establishment procedures. FIG. **19A** shows PDU session establishment procedures that may involve a PCF (e.g., PCF **135**). FIG. **19B** shows PDU session establishment procedures that may not involve a PCF (e.g., PCF **135**). Steps **1901-1917** in FIG. **19A** correspond to steps **1901-1917**, respectively, in FIG. **19B**, unless otherwise indicated.

(159) At step **1901** (in FIGS. **19A** and **19B**), the wireless device **100** may send, to the AMF **155**, a message (e.g., PDU session establishment request) comprising a request to establish one or more PDU sessions. The message may be a NAS Message comprising one or more of: S-NSSAI, DNN, PDU session ID, request type, and/or N1 SM container (e.g., for a PDU Session establishment request). The wireless device **100** may initiate a wireless device requested PDU session establishment procedure, for example, by the transmission of the NAS message, which may comprise a PDU session establishment request within an N1 SM container. The PDU session establishment request may comprise a PDU type (e.g., Ethernet), SSC mode, protocol configuration options, and/or a PDU session ID that may be generated by the wireless device **100**. In a NAS Message and/or an N1 SM container, the wireless device **100** may include one or more Ethernet packet filter sets for a PDU session that may be indicated by a PDU session ID, and/or Ethernet packet filter set(s) on a per wireless device basis (e.g., which may be indicated by one or more wireless device identities), and/or on a per data network bases (e.g., which may be an APN indicated by a DNN), on a per network slice basis (e.g., which may be indicated by an S-NSSAI). An Ethernet packet filter set may comprise one or more of: a source MAC address, a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); C-TAG and/or S-TAG VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as set forth in IEEE 802.1Q); and/or IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). The IP packet filter set may comprise one or more of: source IP address, destination IP address, or prefix (e.g., for IPv6); source port number and/or destination port number; protocol ID of the protocol above IP and/or next header type; type of service (e.g., for IPv4), traffic class (e.g., for IPv6), and/or Mask; flow label (e.g., for IPv6); and/or security parameter index.

(160) At step **1902** (in FIGS. **19A** and **19B**), the AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_CreateSMRequest) requesting a PDU session creation. The AMF **155** may select an SMF (e.g., SMF **160**). The AMF **155** may send to the SMF **160** the message requesting the PDU session creation. The message may comprise one or more of: SUPI, DNN, S-NSSAI, PDU session ID, AMF ID, request type, and/or N1 SM container (e.g., corresponding to a PDU Session Establishment Request), device and/or user location information, access type, PEI). The message sent by the AMF **155** may comprise the information (e.g., Ethernet packet filter set(s) information) received from the wireless device **100** (e.g., at step **1901**).

(161) At step **1903** (in FIGS. **19A** and **19B**), the SMF **160** and/or the UDM **140** may send one or more messages to the other. The SMF **160** may register with the UDM **140**, for example, if the SMF **160** has not yet registered and/or if subscription data is not available. The SMF **160** may retrieve subscription data. Subscribers may be notified, for example, if subscription data is modified. The SMF **160** may select an UPF (e.g., UPF **110**) and/or trigger the PDU session

establishment authentication and/or authorization, for example, if the SMF **160** determines a requirement to perform secondary authorization and/or authentication during an establishment of the PDU session by a DN-AAA server.

(162) At step **1904** (in FIG. **19A**), the SMF **160** may send, to the PCF **135**, a message (e.g., Npcf_SMPolicyControl_Get) requesting a policy control. The SMF **160** may invoke the Npcf_SMPolicyControl_Get operation, for example, after or in response to receiving the message from the AMF **155** (e.g., at step **1902**). The SMF **160** may send the message requesting a policy control to establish a PDU session with the PCF **135** and obtain default PCC rules for the PDU session. The message requesting a policy control may comprise one or more of: the Ethernet packet filter set(s) information for a PDU session (e.g., indicated by the PDU session ID), and/or Ethernet packet filter set(s) on a per wireless device basis (e.g., which may be indicated by one or more wireless device identities, on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., which may be indicated by an S-NSSAI received from the AMF **155**). While step **1904** is additionally shown in FIG. **19B** for reference, this step may not be performed in FIG. **19B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **19B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **1904** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network. The SMF **160** may determine one or more policy decisions, for example, based on information received from the AMF **155** (e.g., Ethernet packet filter set(s) information), subscription information, and/or other information. The SMF **160** may create a service data flow template for one or more policy rules, for example, based on the Ethernet packet filter set(s) information received from the AMF **155**.

(163) At step **1905** (in FIG. **19A**), the PCF **135** may send, to the SMF **160**, a message (e.g., Nsmf_EventExposure_Subscribe) providing subscribe information. The PCF **135** may perform one or more steps, for example, after or in response to a message from step **1904**. The PCF **135** may make one or more policy decisions, for example, based on information received from the SMF **160** (e.g., Ethernet packet filter set(s) information, subscription information), and/or other information. The PCF **135** may create a service data flow template for one or more policy rules, for example, based on the Ethernet packet filter set(s) information received from the SMF **160**. The PCF **135** may send, to the SMF **160**, a message (e.g., policy response) by providing one or more of: a QoS policy for the PDU session(s); a charging policy for the PDU session(s); traffic steering control for steering traffic; and/or other policies. The PCF **135** may subscribe the event(s) in the SMF **160**, for example, by invoking the Nsmf_EventExposure_Subscribe operation. While step **1905** is additionally shown in FIG. **19B** for reference, this step may not be performed in FIG. **19B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **19B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **1905** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(164) At step **1906** (in FIG. **19A**), the SMF **160** may send, to the PCF **135**, a message (e.g., Nsmf_EventExposure_Notify) reporting one or more events. The SMF **160** may invoke, for example, the Nsmf_EventExposure_Notify service operation, to report one or more events to the PCF **135** that may have been previously subscribed. While step **1906** is additionally shown in FIG. **19B** for reference, this step may not be performed in FIG. **19B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **19B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **1906** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(165) At step **1907** (in FIG. **19A**), the PCF **135** may send, to the SMF **160**, a message (e.g., Npcf_SMPolicyControl_UpdateNotify) updating one or more policies. The PCF **135** may provide one or more updated policies to the SMF **160** by invoking the Npcf_SMPolicyControl_UpdateNotify service operation. The PCF **135** may provide an authorized session-AMBR and/or an authorized 5QI and/or ARP to the SMF **160**. The PCF **135** may provide

the one or more updated policies with the Ethernet packet filter set(s) information. While step **1907** is additionally shown in FIG. **19B** for reference, this step may not be performed in FIG. **19B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **19B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **1907** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network. The SMF **160** may make one or more policy decisions, for example, based on information received from the AMF **155** (e.g., Ethernet packet filter set(s) information), subscription information, and/or other information. The SMF **160** may create the service data flow template for one or more policy rules based on the Ethernet packet filter set(s) information received from the AMF **155**.

(166) At step **1908** (in FIGS. **19A** and **19B**), the SMF **160** may send, to the UPF **110**, a message (e.g., N4 session establishment and/or modification request) establishing and/or updating one or more sessions. The SMF **160** may initiate an N4 session establishment procedure with a selected UPF **110**, for example, if the request type indicates an initial request and/or if PDU session establishment authentication and/or authorization was not previously performed. The SMF **160** may initiate an N4 session modification procedure with a selected UPF **110**, for example, if the request type does not indicate an initial request and/or if PDU session establishment authentication and/or authorization was previously performed. The SMF **160** may send an N4 session establishment and/or modification request to the UPF **110**. The SMF **160** may provide packet detection. The packet detected may be provided with the Ethernet packet filter set(s) information. The SMF **160** may provide enforcement and/or reporting rules to be installed on the UPF **110** for the one or more PDU sessions. CN Tunnel information may be provided to UPF **110**, for example, if CN tunnel information is allocated by the SMF **160**.

(167) At step **1909** (in FIGS. **19A** and **19B**) the UPF **110** may send, to the SMF **160**, a message (e.g., N4 session establishment and/or modification response) responding to a message establishing and/or updating one or more sessions (e.g., at step **1908**). The UPF **110** may provide an acknowledgement to the SMF **160**, for example, by sending an N4 session establishment and/or modification response. CN tunnel information may be provided to SMF **160**, for example, if CN tunnel information is allocated by the UPF **110**. The UPF **110** may perform (e.g., based on the Ethernet packet filter set(s) information) service flow detection and/or policy enforcement after and/or upon receiving a user plane data packet.

(168) At step **1910** (in FIGS. **19A** and **19B**), the SMF **160** may send, to the AMF **155**, a message (e.g., Nsmf_PDUSession_CreateSM response) responding to a session creation request (e.g., at step **1902**). The message may comprise one or more of: cause information, N2 SM information (e.g., a PDU session ID, QoS profile(s), CN tunnel information, S-NSSAI, and/or Session-AMBR), and/or N1 SM container (e.g., a PDU session establishment accept). The PDU session establishment accept may comprise one or more of: a QoS rule, an SSC mode, an S-NSSAI, an allocated address (e.g., for IPv4), and/or a session-AMBR. The N2 SM information may comprise information that the AMF **155** may forward to the (R)AN **105** which may comprise the CN tunnel information that may correspond to the Core Network address of the N3 tunnel corresponding to the PDU session. A QoS profile may provide the (R)AN **105** with mapping between QoS parameters and QoS flow identifiers. Multiple QoS profiles may be provided to the (R)AN **105**. The PDU session ID may be used by AN signaling with the wireless device **100**, for example, to indicate to the wireless device **100** an association between an AN resource and a PDU session for the wireless device **100**.

(169) At step **1911** (in FIGS. **19A** and **19B**), the AMF **155** may send, to the (R)AN **105**, a message (e.g., N2 PDU session request) requesting a session. An N2 PDU session request may comprise N2 SM information and/or a NAS message. The NAS message may comprise a PDU Session ID and/or an N1 SM container (e.g., PDU session establishment accept). The AMF **155** may send the NAS message (e.g., comprising a PDU session ID and PDU session establishment accept) targeted to the wireless device **100**. The AMF **155** may send the N2 SM information (e.g., received from the

SMF **160**) within an N2 PDU session request to the (R)AN **105**.

(170) At step **1912** (in FIGS. **19A** and **19B**), the (R)AN **105** and/or the wireless device **100** may send to the other one or more messages for an AN resource setup. The (R)AN **105** may issue an AN specific signaling exchange with the wireless device **100** that may be associated with the information received from SMF **160** (e.g., at step **1911**). For example, a connection reconfiguration (e.g., an RRC connection reconfiguration in a 3GPP RAN) may be performed. The wireless device **100** may establish required RAN resources related to the QoS rules for the PDU session request (e.g., received at step **1910**). The (R)AN **105** may allocate (R)AN N3 tunnel information for the PDU session. The (R)AN **105** may forward the NAS message (e.g., PDU session ID and/or an N1 SM container comprising a PDU session establishment accept) provided in step **1910** to the wireless device **100**. The (R)AN **105** may provide the NAS message to the wireless device **100**, for example, if the required RAN resources have been established and/or if the allocation of (R)AN tunnel information has been successful. The wireless device **100** may send, to the (R)AN **105**, a message comprising one or more of: the Ethernet packet filter sets for a PDU session (e.g., which may be indicated by a PDU session ID) and/or Ethernet packet filter set(s) on a per wireless device basis (e.g., which may be indicated by one or more wireless device identities), on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., which may be indicated by one or more S-NSSAI). An Ethernet packet filter set may comprise one or more of: a source MAC address, a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); C-TAG and/or S-TAG VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as set forth in IEEE 802.1Q); and/or an IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). The IP packet filter set may comprise one or more of: source IP address, destination IP address, and/or prefix (e.g., for IPv6); source port number and/or destination port number; protocol ID of the protocol above IP and/or a next header type; type of service (e.g., for IPv4), traffic class (e.g., for IPv6), and/or a mask; flow label (e.g., for IPv6); and/or a security parameter index. The wireless device **100** may send the same Ethernet packet filter set(s) information as at step **1901**. Additionally or alternatively, the wireless device **100** may send an updated Ethernet packet filter set(s) information that may differ from the Ethernet packet filter set(s) information sent at step **1901**. The (R)AN **105** may perform one or more operations based on updated Ethernet packet filter set(s) information.

(171) At step **1913** (in FIGS. **19A** and **19B**), the (R)AN **105** may send, to the AMF **155**, a message (e.g., N2 PDU session response) responding to a session request (e.g., at step **1911**). An N2 PDU session response may comprise one or more of: a PDU session ID, cause information, and/or N2 SM information (e.g., a PDU session ID, (R)AN tunnel information, a list of accepted and/or rejected QoS profiles). The (R)AN **105** may send, to the AMF **155**, the Ethernet packet filter set(s) information received from the wireless device **100**. The (R)AN **105** may send the Ethernet packet filter set(s) information with the message responding to the session request. The (R)AN tunnel information may correspond to the Access Network address of the N3 tunnel corresponding to the PDU session.

(172) At step **1914** (in FIGS. **19A** and **19B**), the AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_UpdateSMContext request) requesting session information (e.g., N2 SM information). The AMF **155** may forward the N2 SM information received from the (R)AN **105** (e.g., at step **1913**) to the SMF **160**. The message to the SMF **160** may comprise the Ethernet packet filter set(s) information received from the (R)AN **105** (e.g., at step **1913**).

(173) At step **1915** (in FIGS. **19A** and **19B**), the SMF **160** may send, to the UPF **110**, a message (e.g., N4 session modification request) requesting a session modification. If PCC is not supported and/or if there is no PCF in the network, the SMF **160** may make one or more policy decisions, for example, based on the information received from the AMF **155** (e.g., Ethernet packet filter set(s) information), subscription information, and/or other information. The SMF **160** may create a service data flow template for one or more policy rules, for example, based on the Ethernet packet

filter set(s) information received from the AMF **155**. The SMF **160** may initiate an N4 session establishment procedure with the UPF **110**, for example, if the N4 session for the PDU session was not previously established. The SMF **160** may initiate an N4 session modification procedure with the UPF **110**, for example, if the N4 session for the PDU session was previously established. The SMF **160** may provide AN tunnel information and/or CN tunnel information. It may be necessary for the SMF **160** to provide the CN tunnel information, for example, if the SMF **160** selected CN tunnel information. The SMF **160** may include one or more policies for the PDU session in the message requesting the session modification. The SMF **160** may include, with the one or more policies for the PDU session, the Ethernet packet filter set(s) information that may be received from the PCF **135**.

(174) At step **1916** (in FIGS. **19A** and **19B**), the UPF **110** may send, to the SMF **160**, a message (e.g., N4 session modification response) responding to a session modification request (e.g., at step **1915**). The UPF **110** may provide a N4 session establishment and/or modification response to the SMF **160**. The UPF **110** may perform, using the Ethernet packet filter set(s) information, service flow detection and/or policy enforcement, for example, after and/or upon receiving a user plane data packet.

(175) At step **1917** (in FIGS. **19A** and **19B**), the SMF **160** may send, to the AMF **155** a message (e.g., Nsmf_PDUSession_UpdateSMContext response) responding to a request for session information (e.g., at step **1914**). The message may comprise cause information. After this step, the AMF **155** may forward relevant events to the SMF **160**, for example, at a handover where the (R)AN tunnel information may change and/or if the AMF **155** is relocated.

(176) FIGS. **20A** and **20B** show examples of service request procedures. A wireless device **100** may initiate a service request procedure for an Ethernet type PDU session. FIG. **20A** shows service request procedures that may involve a PCF (e.g., PCF **135**). FIG. **20B** shows service request procedures that may not involve a PCF (e.g., PCF **135**). Steps **2001-2023** in FIG. **20A** correspond to steps **2001-2023**, respectively, in FIG. **20B**, unless otherwise indicated.

(177) At step **2001** (in FIGS. **20A** and **20B**), the wireless device **100** may send, to the (R)AN **105**, a message requesting a service. The message may be an AN message. The message may comprise one or more of: AN parameters and/or an MM NAS service request (e.g., PDU session(s) to be activated, security parameters, and/or PDU session status). The AN parameters may comprise an establishment cause (e.g., for an NG-RAN). The establishment cause may provide a reason for requesting the establishment of an RRC connection. The wireless device **100** may send a NAS service request message, destined to the AMF **155**, and/or encapsulated in an RRC message to the (R)AN **105**. One or more RRC messages may be used to send a 5G-GUTI and/or the NAS message. The message to the (R)AN **105** requesting a service may comprise one or more of: the Ethernet packet filter sets for a PDU session (e.g., indicated by a PDU session ID), and/or Ethernet packet filter set(s) on a per wireless device basis (e.g., which may be indicated by one or more wireless device identities), on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., which may be indicated by one or more S-NSSAI). The Ethernet packet filter set may comprise one or more of: a source MAC address and/or a destination MAC address; Ethertype (e.g., as set forth in IEEE 802.3); C-TAG and/or S-TAG VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as set forth in IEEE 802.1Q); and/or IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). The IP packet filter set may comprise one or more of: source IP address, destination IP address, and/or prefix (e.g., for IPv6); source port number and/or destination port number; protocol ID of the protocol above IP and/or a next header type; type of service (e.g., for IPv4), traffic class (e.g., for IPv6), and/or mask; flow label (e.g., for IPv6); and security parameter index.

(178) At step **2002** (in FIGS. **20A** and **20B**), the (R)AN **105** may send, to the AMF **155**, a message requesting service. The message may be an N2 message. The message may comprise N2

parameters and/or an MM NAS service request. The (R)AN **105** may include, in the message requesting service, the Ethernet packet filter set(s) information received from the wireless device **100** (e.g., at step **2001**). The N2 parameters may comprise one or more of: 5G-GUTI (e.g., for an NG-RAN), location information, RAT type, and/or establishment cause. The AMF **155** may initiate (e.g., based on the PDU session status) a PDU session release procedure for the PDU sessions associated with the PDU session ID(s) that may be indicated by the wireless device **100** as not being available.

(179) At step **2003** (in FIGS. **20A** and **20B**), the AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_UpdateSMContext request) requesting information. The message may comprise one or more of: PDU session ID, cause information, wireless device location information, and/or access type. The AMF **155** may send, to the SMF **160**, the Ethernet packet filter set(s) information received from the (R)AN **105**. The AMF **155** may send the Ethernet packet filter set(s) information with the message requesting information. The Nsmf_PDUSession_UpdateSMContext request procedure may be invoked, for example, if the wireless device **100** identifies one or more PDU sessions that are to be activated in the MM NAS Service Request message.

(180) At step **2004** (in FIG. **20A**), the SMF **160** may send, to the PCF **135**, a message (e.g., Npcf_SMPolicyControl_Get) requesting policy control information. The SMF **160** may invoke the Npcf_SMPolicyControl_Get operation to obtain one or more policies for one or more PDU sessions, after or in response to receiving the message from the AMF **155** in step **2003**. The SMF **160** may send, to the PCF **135**, the Ethernet packet filter set(s) information received from the AMF **155**. The SMF **160** may send the Ethernet packet filter set(s) information with the message requesting policy control information. While step **2004** is additionally shown in FIG. **20B** for reference, this step may not be performed in FIG. **20B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **20B**, the SMF **160** may determine or obtain one or more policies without communicating with a PCF. Step **2004** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network. The SMF **160** may make one or more policy decisions, for example, based on the information received from the AMF **155** (e.g., Ethernet packet filter set(s) information), subscription information, and/or other information. The SMF **160** may create the service data flow template for the one or more policy rules, for example, based on the Ethernet packet filter set(s) information received from the AMF **155**.

(181) At step **2005** (in FIG. **20A**), the PCF **135** may send, to the SMF **160**, a message (e.g., Nsmf_EventExposure_Subscribe) responding to a request for policy control information. The PCF **135** may perform one or more steps, for example, after or in response to receiving the message from the SMF **160**. The PCF **135** may make one or more policy decisions, for example, based on the information received from the SMF **160** (e.g., Ethernet packet filter set(s) information), subscription information, and/or other information. The PCF may create the service data flow template for the one or more policy rules, for example, based on the Ethernet packet filter set(s) information received from the SMF **160**. The PCF **135** may send, to the SMF **160**, a message (e.g., a policy response) comprising one or more of: a QoS policy for the PDU session(s); a charging policy for the PDU session(s); traffic steering control for steering traffic; and/or other policies. The PCF **135** may send, with the message providing one or more policies, the Ethernet packet filter set(s) information. The PCF **135** may subscribe one or more event(s) in the SMF **160**, for example, by invoking the Nsmf_EventExposure_Subscribe operation. While step **2005** is additionally shown in FIG. for reference, this step may not be performed in FIG. **20B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **20B**, the SMF **160** may determine or obtain one or more policies without communicating with a PCF. Step **2005** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(182) At step **2006** (in FIGS. **20A** and **20B**), the SMF **160** may select a new UPF (e.g., new I-UPF **110-1**) to act as an intermediate UPF for a PDU session. The SMF **160** may send, to the new I-UPF **110-1**, a message (e.g., N4 session establish request) requesting session establishment. The session

establishment request message may comprise information for packet detection, data forwarding, enforcement, and/or reporting rules to be installed on the new I-UPF **110-1**. The session establishment request message may be sent with the Ethernet packet filter set(s) information. The PDU session anchor addressing information (e.g., on N9) for the PDU Session may be provided to the new I-UPF **110-1**. The SMF **160** may include a data forwarding indication, for example, if a service request is triggered by the network and/or if a new I-UPF **110-1** is selected by the SMF **160** to replace the old I-UPF **110-2**.

(183) At step **2007** (in FIGS. **20A** and **20B**), the new I-UPF **110-1** may send, to the SMF **160**, a message (e.g., N4 session establish response) responding to a session establishment request (e.g., at step **2006**). The new I-UPF **110-1** may provide CN DL tunnel information for a PSA UPF **110-3** (e.g., which may be acting as a PDU session anchor) and/or UL tunnel information (e.g., CN N3 tunnel information) to the SMF **160**, for example, if the new I-UPF **110-1** allocates CN tunnel information. The new I-UPF **110-1** (e.g., acting as an N3 terminating point) may send CN DL tunnel information to the SMF **160** for the old I-UPF **110-2**, for example, if a data forwarding indication is received by the new I-UPF **110-1**. The new I-UPF **110-1** may perform (e.g., based on the Ethernet packet filter set(s) information) service flow detection and/or policy enforcement, after and/or upon receiving a user plane data packet.

(184) At step **2008** (in FIGS. **20A** and **20B**), the SMF **160** may send, to the PSA UPF **110-3**, a message (e.g., N4 session modification request) requesting a session modification. The SMF **160** may send an N4 session modification request message to a PDU session anchor (PSA) (e.g., UPF **110-3**), for example, if the SMF **160** selects a new UPF to act as intermediate UPF for the PDU session. The message requesting a session modification may provide the DL tunnel information from the new I-UPF **110-1**. The SMF **160** may send, to the PSA UPF **110-3**, information for packet detection, data forwarding, enforcement, and/or reporting rules. The SMF **160** may send (e.g., with the message requesting a session modification) the Ethernet packet filter set(s) information to the PSA UPF **110-3**. The PSA UPF **110-3** may perform (e.g., based on the Ethernet packet filter set(s) information), service flow detection and/or policy enforcement, after and/or upon receiving the user plane data packet.

(185) At step **2009** (in FIGS. **20A** and **20B**), the PSA UPF **110-3** may send, to the SMF **160**, a message (e.g., N4 session modification response) that may respond to a session modification request (e.g., at step **2008**).

(186) At step **2010** (in FIGS. **20A** and **20B**), the SMF **160** may send, to the old I-UPF **110-2**, a message (e.g., N4 session modification request) requesting a session modification. The message may comprise a new I-UPF **110-1** address and/or a new I-UPF **110-1** DL tunnel ID. The SMF **160** may send the N4 session modification request message to the old I-UPF **110-2**, for example, if the service request is triggered by the network and/or if a new I-UPF **110-1** is selected by the SMF **160** to replace the old I-UPF **110-2**. The message requesting the session modification may provide the DL tunnel information from the new I-UPF **110-1**, which may be acting as an N3 terminating point.

(187) At step **2011** (in FIGS. **20A** and **20B**), the old I-UPF **110-2** may send, to the SMF **160**, a message (e.g., N4 session modification response) responding to a session modification request (e.g., at step **2010**). The old I-UPF **110-2** may forward its buffered data to the new I-UPF **110-1**, which may be acting as N3 terminating point.

(188) At step **2012** (in FIGS. **20A** and **20B**), the SMF **160** may send, to the AMF **155**, a message (e.g., Nsmf_PDUSession_UpdateSMContext response) responding to a message requesting information (e.g., at step **2003**). The message responding to the request may comprise N1 SM information (e.g., PDU session ID(s) and/or PDU session re-establishment indication), N2 SM information (e.g., PDU session ID(s), QoS profile(s), CN N3 tunnel information, and/or S-NSSAI), and/or cause information. The SMF **160** may determine whether UPF reallocation is performed, for example, after or in response to receiving a message (e.g., Nsmf_PDUSession_UpdateSMContext request in step **2013**) from the AMF **155** and/or after determining that the message from the AMF

155 comprises cause information that includes an establishment of user plane resources. The SMF **160** may determine whether UPF relocation is performed, for example, based on the wireless device **100** location information, UPF service area, and/or one or more policies (e.g., operator policies). The SMF **160** may generate N2 SM information and/or send a response (e.g., Nsmf_PDUSession_UpdateSMContext response) to the AMF **155** to establish the user plane(s), for example, for a PDU Session that the SMF **160** has determined is still being served by the current UPF (e.g., the PSA UPF **110-3** and/or the old I-UPF **110-2**). The N2 SM information may comprise information that the AMF **155** may provide to the (R)AN **105**. The SMF **160** may send, via the AMF **155**, a message (e.g., Nsmf_PDUSession_UpdateSMContext response) comprising N1 SM information for the wireless device **100**, for example, for a PDU session that the SMF **160** may have determined to require a UPF relocation for the PSA-UPF **110-3**. The N1 SM information may comprise a corresponding PDU session ID and/or a PDU session re-establishment indication. (189) At step **2013** (in FIGS. **20A** and **20B**), the AMF **155** may send, to the (R)AN **105**, a request message (e.g., N2 request). The request message may comprise one or more of: N2 SM information received from the SMF **160**, a security context, an AMF signaling connection ID, a handover restriction list, an MM NAS service accept, a list of recommended cells, tracking areas (TAs), and/or NG-RAN node identifiers. The AMF **155** may include, in or with the request message, at least one N2 SM information from the SMF **160**, for example, if a procedure is triggered for PDU session user plane activation.

(190) At step **2014** (in FIGS. **20A** and **20B**), the (R)AN **105** and/or the wireless device **100** may send one or more messages to the other for a connection reconfiguration (e.g., RRC connection reconfiguration). The (R)AN **105** may perform RRC connection reconfiguration with the wireless device **100**, for example, based on one or more of: QoS information for the QoS flows of the PDU sessions comprising activated UP connections, and/or data radio bearers. The (R)AN **105** may forward an MM NAS service accept to the wireless device **100**. The wireless device **100** may locally delete context of PDU sessions that may not be available (e.g., that may not be available in the 5GC). The wireless device **100** may initiate (e.g., after the service request procedure is complete) PDU session re-establishment for such unavailable PDU session(s) and/or other PDU sessions, for example, if the N1 SM information is present in the service accept and/or indicates one or more PDU sessions should be re-established. The wireless device **100** may send, to the (R)AN **105**, a message comprising one or more of: the Ethernet packet filter sets for a PDU session (e.g., indicated by a PDU session ID) and/or Ethernet packet filter set(s) on a per wireless device basis (e.g., which may be indicated by one or more wireless device identities), on a per data network basis (e.g., which may be an APN indicated by a DNN), and/or on a per network slice basis (e.g., which may be indicated by one or more S-NSSAI). An Ethernet packet filter set may comprise one or more of: a source MAC address and/or a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); a C-TAG and/or S-TAG VID fields (e.g., as set forth in IEEE 802.1Q); a C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as set forth in IEEE 802.1Q); and/or an IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). The IP packet filter set may comprise one or more of: a source IP address, a destination IP address, and/or a prefix (e.g., for IPv6); a source port number and/or a destination port number; a protocol ID of the protocol above IP and/or a next header type; a type of service (e.g., for IPv4), a traffic class (e.g., for IPv6), and/or a mask; a flow label (e.g., for IPv6); and/or a security parameter index. The wireless device **100** may send the same Ethernet packet filter set(s) information as in step **2001**. Additionally or alternatively, the wireless device **100** may send updated Ethernet packet filter set(s) information that may differ from the Ethernet packet filter set(s) information send at step **2001**. The (R)AN **105** may use the updated Ethernet packet filter set(s) information for one or more steps. (191) At step **2015** (in FIGS. **20A** and **20B**), the (R)AN **105** may send, to the AMF **155**, a message (e.g., N2 request acknowledgment) acknowledging a request (e.g., at step **2013**). The message acknowledging the request may comprise N2 SM information. The N2 SM information may

comprise one or more of: RAN tunnel information, a list of accepted QoS flows for the PDU sessions having activated UP connections, and/or a list of rejected QoS flows for the PDU Sessions having activated UP connections. The (R)AN **105** may include, in or with the message to the AMF **155** acknowledging the request, the Ethernet packet filter set(s) information received from the wireless device **100** (e.g., at step **2001** and/or at step **2014**).

(192) At step **2016** (in FIGS. **20A** and **20B**), the AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_UpdateSMContext request) requesting information. The message may request the information (and/or updated information) corresponding to the information requested at step **2003**. The message at step **2016** may request N2 SM information (e.g., RAN tunnel information) and/or RAT type) per accepted PDU session. The AMF **155** may include, in or with the message at step **2016**, the Ethernet packet filter set(s) information received from the (R)AN **105** (e.g., at step **2002** and/or step **2015**).

(193) At step **2017** (in FIG. **20A**), the SMF **160** may send, to the PCF **135**, a message (e.g., Nsmf_EventExposure_Notify) reporting one or more events. The SMF **160** may invoke, for example, the Nsmf_EventExposure_Notify service operation, to report one or more events to the PCF **135** that may have been previously subscribed. While step **2017** is additionally shown in FIG. **20B** for reference, this step may not be performed in FIG. **20B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **20B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **2017** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network.

(194) At step **2018** (in FIG. **20A**), the PCF **135** may send, to the SMF **160**, a message (e.g., Npcf_SMPolicyControl_UpdateNotify) updating one or more policies. The PCF **135** may provide one or more updated policies to the SMF **160** by invoking the Npcf_SMPolicyControl_UpdateNotify service operation. The PCF **135** may provide an authorized session-AMBR and/or an authorized 5QI and/or ARP to the SMF **160**. The PCF **135** may provide the one or more policies with the Ethernet packet filter set(s) information. While step **2018** is additionally shown in FIG. **20B** for reference, this step may not be performed in FIG. **20B**, for example, if the PCF **135** is not used for this step. For example, in FIG. **20B**, the SMF **160** may determine one or more policies without communicating with a PCF. Step **2018** may be omitted, for example, if PCC is not supported and/or if there is no PCF in the network. The SMF **160** may make one or more policy decisions, for example, based on information received from the AMF **155** (e.g., Ethernet packet filter set(s) information), subscription information, and/or other information. The SMF **160** may create the service data flow template for one or more policy rules based on the Ethernet packet filter set(s) information received from the AMF **155**.

(195) At step **2019** (in FIGS. **20A** and **20B**), the SMF **160** may send, to the new I-UPF **110-1**, a message (e.g., N4 session modification request) requesting a session modification. The SMF **160** may initiate an N4 session modification procedure and/or provides RAN tunnel information, for example, if the SMF **160** selected a new UPF (e.g., the new I-UPF **110-1**) to act as intermediate UPF for the PDU session. The SMF **160** may provide information for one or more rules for packet detection, data forwarding, enforcement, and/or reporting rules to be installed on the new I-UPF **110-1**. The SMF **160** may include the information for the one or more rules in or with the Ethernet packet filter set(s) information.

(196) At step **2020** (in FIGS. **20A** and **20B**), the new I-UPF **110-1** may send, to the SMF **160**, a message (e.g., N4 session modification response) responding to a session modification request (e.g., at step **2019**). The message at step **2020** may comprise information (and/or updated information) corresponding to the information provided by the message at step **1916**.

(197) At step **2021** (in FIGS. **20A** and **20B**), the SMF **160** may send, to the AMF **155**, a message (e.g., Nsmf_PDUSession_UpdateSMContext response) responding to a request for session information (e.g., at step **2016**). The message may comprise cause information.

(198) At step **2022** (in FIGS. **20A** and **20B**), the SMF **160** and/or the new I-UPF **110-1** may send

one or more messages to the other for a session modification (e.g., N4 session modification). The SMF **160** may send an N4 session modification request to new I-UPF **110-1** (which may be acting as an N3 terminating point to release a forwarding tunnel), for example, if the forwarding tunnel has been established and/or if a timer SMF **160** may have set for the forwarding tunnel has expired. The new I-UPF **110-1** may respond to the SMF **160** by sending an N4 session modification response.

(199) At step **2023** (in FIGS. **20A** and **20B**), the SMF **160** and/or the old I-UPF **110-2** may send one or more messages to the other for a session modification and/or release (e.g., N4 session modification and/or release). The SMF **160** may send to the old I-UPF **110-2** an N4 session modification request providing (R)AN tunnel information, for example, if the SMF **160** determined to continue using the old I-UPF **110-2** before step **2006**. The SMF **160** may initiate a resource release by sending an N4 session release request (e.g., release cause) to the old I-UPF **110-2**, for example, if the SMF **160** determined to select a new UPF to act as intermediate UPF before step **2006** and/or if the old I-UPF **110-2** is not PSA UPF.

(200) FIG. **21** shows an Ethernet over wireless communications procedure that may be performed, in whole or in part, by one or more computing devices. As examples, the procedure shown in FIG. **21** may be performed by a session management function (e.g., the SMF **160**). Additionally or alternatively, at least some of the procedure shown in FIG. **21** may be performed by a policy control function (e.g., PCF **135**), a wireless device (e.g., wireless device **100**), and/or a data network (e.g., DN **115**). Any other computing device may perform one or more portions of the procedures shown in FIG. **21** for Ethernet over wireless communications.

(201) At step **2101**, a wireless device (e.g., the wireless device **100**) may send, to a session management function (e.g., the SMF **160**) one or more messages comprising one or more Ethernet packet filter sets. The Ethernet packet filter sets may comprise one or more of a source MAC address, a destination MAC address, an Ethertype, a virtual local area network tag, and/or an IP packet filter set. The Ethernet packet filter set may be associated with one or more of: a PDU session, the wireless device, a data network, and/or a network slice. The wireless device may send the one or more messages to an access network (e.g., the (R)AN **105**), to one or more base stations, and/or to an access and mobility management function (e.g., the AMF **155**). The access network may send the one or more messages to the session management function (e.g., via a user plane function such as the UPF **110**) and/or the access and mobility management function. The access and mobility management function may send the one or more messages to the session management function. The session management function may receive the one or more messages.

(202) At step **2102**, a computing device (e.g., a session management function) may determine whether the one or more Ethernet packet filter sets comprise a request for an Ethernet type PDU session. The computing device may make such a determination based on an Ethertype in the Ethernet packet filter sets. If the computing device determines that at least one of the Ethernet packet filter sets is not associated with a request for an Ethernet type PDU session, the procedure may continue to step **2103**. If the computing device determines that at least one of the Ethernet packet filter sets is associated with a request for an Ethernet type PDU session, the procedure may continue to step **2106**.

(203) At step **2103**, the computing device (e.g., a session management function) may determine whether to redirect the wireless device. For example, if the one or more messages from step **2101** indicate a type of service that is not supported for the wireless device (e.g., based on one or more policies or an availability of one or more applications), the computing device may send a message to the wireless device indicating one or more options for the wireless device to obtain support for the type of service (e.g., updating one or more policies to include a registration of one or more services associated with the type, or identifying another computing device that may provide services for the type). If the computing device determines to redirect the wireless device (e.g., based on an indication from the wireless device requesting redirection), at step **2104**, the computing

device may redirect the wireless device to an offer for initiating service of the type of service not presently supported for the wireless device. If the computing device determines not to redirect the wireless device (e.g., based on a timer expiration or receiving an indication from the wireless device declining redirection), at step **2105**, the computing device may discard the Ethernet packet filter set(s) associated with the type that is not supported for the wireless device. After step **2104** and/or step **2105**, the procedure may end.

(204) At step **2106**, the computing device (e.g., a session management function) may determine an application and/or service for Ethernet over wireless communications for the wireless device, for example, if a type of a session request associated indicated by the one or more messages is confirmed, at step **2102**, to be an Ethernet type. The computing device may determine at least one policy rule (e.g., a QoS rule), one or more parameters for the at least one policy rule (e.g., QoS parameters), and/or a policy decision (e.g., whether QoS is satisfied), based on the one or more Ethernet packet filter sets. The computing device may determine an application and/or type of service based on a MAC address (e.g., a destination MAC address and/or a source MAC address) in the one or more Ethernet packet filter sets. The destination MAC address may indicate an application server that may be associated with a one or more applications and/or services. The source MAC address may indicate a location and/or a profile associated with the wireless device that may indicate one or more applications and/or services.

(205) At step **2107**, the computing device (e.g., a session management function) may apply a first policy. The first policy may comprise one or more rules. A rule may be a policy rule (e.g., a rule associated with a policy), a charging rule (e.g., a rule associated with a charging policy), or a policy and charging rule (e.g., a policy and charging control rule (PCC)). A policy rule may comprise, for example, one or more of a: quality of service (QoS) rule, a gating rule, a traffic detection rule, a traffic steering control rule, and/or any other rule that may be associated with a user, device, and/or service. A QoS rule may be based on one or more priority levels (e.g., high priority, low priority, or any other level of priority). A priority level may be associated with a particular value or range of values for a bandwidth, latency, and/or allowance and retention (ARP). A gating rule may be based on a packet type (e.g., Ethertype) or a service access level (e.g., user and/or device authorization to access one or more services using Ethernet over wireless communications). A traffic detection rule may be based on a determination of whether signal traffic that may be associated with an Ethernet PDU session may be satisfied for a request for the Ethernet PDU session. The traffic detection rule may comprise detecting a service flow based on receiving a user plane data packet. A traffic steering control rule may comprise directing traffic associated with an Ethernet PDU session for optimal network performance.

(206) At step **2108**, the computing device (e.g., a session management function and/or a user plane function) may determine whether the first policy is satisfied. For example, based on whether the first policy is satisfied (e.g., a gating rule), the computing device may allow or discard packets. If the first policy is not satisfied, the procedure may continue to step **2103** described above. If the first policy is satisfied, the procedure may continue to step **2109**.

(207) At step **2109**, the computing device (e.g., a session management function, a policy control function, and/or a user plane function) may determine one or more second policies to apply to the Ethernet packet filter set(s). The one or more second policies may comprise one or more rules, such as a policy rule, a charging rule, and/or a PCC. The one or more second policies may comprise for example, one or more of a: quality of service (QoS) rule, a gating rule, a traffic detection rule, a traffic steering control rule, and/or any other rule that may be associated with a user, device, and/or service, such as described above regarding step **2107**. The one or more second policies may comprise at least one charging rule (e.g., a PCC). A charging rule may be associated with charging (e.g., online charging, offline charging, and/or converged charging) associated with a particular user, device, and/or group of users and/or devices. Charging information may be based on one or more ratings (e.g., cost-per-service associated with one or more users and/or devices) and/or

addresses (e.g., source MAC address of the wireless device and/or destination MAC address of an application server associated with the service requested by the wireless device). The computing device may store and/or maintain at least some information about one or more charging rules that may be associated with a wireless device. Additionally or alternatively, the computing device (e.g., a session management function) may obtain one or more charging rules and/or updates to one or more charging rules from a second computing device (e.g., a policy control function such as the PCF **135**).

(208) At step **2110**, the computing device (e.g., a session management function) may determine whether the one or more second policies requires an updated policy. If at least one of the one or more second policies require an update (e.g., based on the computing device not having at least one of the one or more second policies and/or not having a recent version of at least one of the one or more second policies), the procedure may continue to step **2111**. If at least one of the one or more second policies do not require an update, the procedure may continue to step **2113**.

(209) At step **2111**, the computing device (e.g., a session management function) may send a request for one or more updated policies. The computing device may send the request to a second computing device (e.g., a policy control function). The request for one or more updated policies may comprise a request for a policy and charging control rule and/or the one or more Ethernet packet filter sets for a data flow. The computing device (e.g., a session management function) may send a message to a third computing device (e.g., a user plane function such as UPF **110**) comprising the one or more Ethernet packet filter sets for the data flow and/or one or more parameters indicating a policy rule. The message to the third computing device (e.g., a user plane function) may comprise a request to establish a user plane session.

(210) At step **2112**, the computing device (e.g., a session management function) may receive, from the second computing device (e.g., a policy control function), a response message comprising one or more updated policies. The one or more updated policies may comprise at least one charging policy (e.g., a PCC) corresponding to the requested policy and charging control rule. The computing device (e.g., a session management function) may send the one or more updated policies to the third computing device (e.g., a user plane function). The computing device (e.g., a session management function) may receive from the third computing device (e.g., a user plane function) a message indicating that the third computing device has received the message from the computing device. The message from the third computing device (e.g., a user plane function) may comprise a user plane data packet. The third computing device (e.g., a user plane function) may enforce the policy rule and/or the policy and charging control rule sent at step **2111**, for example, based on quality of service parameters associated with information in the one or more Ethernet packet filter sets.

(211) At step **2113**, the computing device (e.g., a user plane function and/or a session management function) may apply the one or more second policies to the Ethernet packet filter set(s). For example, the computing device may provide for an Ethernet PDU session requested by the wireless device to the extent the request complies with the policy rules of the one or more second policies, and/or the computing device may associate charging information with the Ethernet PDU session requested by the wireless device.

(212) At step **2114**, the computing device (e.g., a user plane function, an access network, and/or a session management function) may send and/or receive data packets associated with the Ethernet PDU session requested by the wireless device. The wireless device may receive the data packets associated with the Ethernet PDU session requested by the wireless device. After step **2114**, the Ethernet PDU session requested by the wireless device may end and the procedure shown in FIG. **21** may end.

(213) FIG. **22** shows an example of procedures involving a network exposure function (NEF) in which a data network (DN) may send, to an NEF, one or more Ethernet packet filter set(s) information, wireless device identities and/or identifiers, and/or addresses (e.g., source MAC

addresses and/or destination MAC addresses).

(214) At step **2201**, the DN **115** may send, to the NEF **125**, a first message (e.g., Ethernet MAC addresses provision). The first message may comprise one or more Ethernet MAC addresses. Additionally or alternatively, the first message may comprise one or more of: wireless device identities and/or identifiers (e.g., wireless device NAI, SUPI, 5G-GUTI, and/or other identifiers); data network name (DNN) and/or an APN; PDU session ID(s); S-NSSAI (e.g., indicating a network slice); and/or Ethernet packet filter sets per wireless device (e.g., which may be indicated by one or more wireless device identities), per data network (e.g., which may be an APN indicated by a DNN), per network slice (e.g., which may be indicated by an S-NSSAI); and/or per PDU session (e.g., which may be indicated by a PDU session ID). An Ethernet packet filter set may comprise one or more of: a source MAC address and/or a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); Customer-VLAN tag (C-TAG) and/or Service-VLAN tag (S-TAG) VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as set forth in IEEE 802.1Q); and IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). An IP packet filter set may comprise one or more of: a source IP address, a destination IP address, and/or a prefix (e.g., for IPv6); a source port number and/or a destination port number; a protocol ID of the protocol above IP and/or a next header type; a type of service (e.g., for IPv4), a traffic class (e.g., for IPv6), and/or mask; a flow label (e.g., for IPv6); and/or a security parameter index.

(215) At step **2202**, the NEF **125** may perform one or more steps, for example, after or in response to receiving the first message from the DN **115**. The NEF **125** may select an SMF (e.g., the SMF **160**). The NEF **125** may select an SMF by using an NRF, for example, by providing one or more of the following information, that may be received from the DN **115**, to the NRF: wireless device identity and/or identifier; data network name (DNN); PDU session ID; and/or S-NSSAI. The NEF **125** may send, to a selected SMF (e.g., the SMF **160**), a second message (e.g., Ethernet MAC addresses provision). The second message may comprise some or all of the information in the first message received from the DN **115** at step **2201**.

(216) At step **2203**, the SMF **160** may send, to the NEF **125**, a third message (e.g., Ethernet MAC addresses response). The SMF **160** may store information received from the second message (e.g., MAC addresses and/or Ethernet packet filter set(s) information) and/or send to the NEF **125** the third message (e.g., Ethernet MAC addresses response) after or in response to receiving the second message from the NEF **125** at step **2202**.

(217) At step **2204**, the NEF **125** may send, to the DN **115**, a fourth message (e.g., Ethernet MAC addresses response). The NEF **125** may send to the DN **115** the fourth message (e.g., Ethernet MAC addresses response), for example, after or in response to receiving the third message from the SMF **160** at step **2203**. The fourth message may comprise some or all of the information in the third message received from the SMF **160** at step **2203**.

(218) Steps **2201-2204** may occur at any time, including at a time that may or may not be associated with steps **2205-2221**. For example, steps **2201-2204** may occur periodically, as part of a procedure to initiate communications with the DN **115** and/or any device, as part of a procedure to configure one or more devices for communications in a network, as part of a procedure to provide network updates, and/or as part of any other procedure.

(219) At step **2205**, a wireless device **100** may send, to the AMF **155**, a message (e.g., PDU session establishment request) requesting establishment of a session. The session may comprise an Ethernet type PDU session (e.g., Ethernet over wireless communications). The wireless device **100** may initiate a PDU session establishment procedure, for example, by sending to an AMF **155** an NAS Message. The NAS message may comprise one or more of: an S-NSSAI, a DNN, a PDU session ID, a request type, and/or an N1 SM container. The N1 SM container may comprise a PDU session establishment request. The NAS Message and/or an N1 SM container may comprise one or more wireless device identities and/or identifiers (e.g., SUPI, 5G-GUTI, and/or others). The

wireless device **100** may initiate the wireless device requested PDU session establishment procedure, for example, by the transmission of a NAS message containing a PDU session establishment request within an N1 SM container. The PDU session establishment request may comprise one or more of: a PDU type (e.g., Ethernet), an SSC mode, protocol configuration options, and/or a PDU session ID that may be generated by the wireless device **100**.

(220) At step **2206**, the AMF **155** may send, to the SMF **160**, a message (e.g., Namf_PDUSession_CreateSMContext) for a session. The AMF **155** may perform one or more steps, for example, after or in response to receiving the message at step **2205**. The AMF **155** may select an SMF (e.g., the SMF **160**). The AMF **155** may select an SMF (e.g., SMF **160**) using an NRF, for example, by providing one or more of the following information, that may be received from the wireless device **100**, to the NRF: wireless device identity and/or identifier; data network name (DNN); PDU session ID; and/or S-NSSAI. The NRF may select an SMF based on information that the NRF receives from the AMF **155**, which may comprise the same information that the AMF **155** received from the wireless device **100** (e.g., at step **2206**). The NRF may select an SMF based on the same NRF selection procedure in step **2202**. The NRF may select an SMF based on a comparison of information the NRF received from the AMF **155** (e.g., at step **2206**) with information the NRF received from the NEF **125** (e.g., at step **2202**). The AMF **155** may send, to the SMF **160**, a message (e.g., Namf_PDUSession_CreateSMRequest) comprising one or more of: a SUPI, a DNN, a S-NSSAI, a PDU session ID, an AMF ID, a request type, an N1 SM container (e.g., PDU session establishment request), user and/or device location information, an access type, and/or a PEI. The N1 SM container may comprise a PDU session establishment request.

(221) At step **2207**, the SMF **160** and/or the UDM **140** may send one or more messages to the other, for example, for a subscription retrieval. The SMF **160** may correlate, compare, and/or map information received from the AMF **155** (e.g., at step **2206**) with information received from the NEF **125** (e.g., at step **2202**), for example, after or in response to receiving the message from the AMF **155**. The SMF **160** may correlate and/or compare addresses and/or Ethernet packet filter set(s) that may have been received from the NEF **125**, with one or more of the following information that may have been received from the AMF **155**: wireless device identities and/or identifiers; data network name (DNN); PDU session ID; and/or S-NSSAI. The SMF **160** may register with the UDM **140**, for example, if the SMF **160** has not yet registered and/or if subscription data is not available. The SMF **160** may retrieve subscription data. The SMF **160** may subscribe to be notified, for example, if subscription data is modified. The SMF **160** may select a UPF and/or trigger a PDU session establishment authentication and/or authorization, for example, if the SMF **160** may be required to perform secondary authorization and/or authentication at an establishment (e.g., by a DN-AAA server) of a PDU session.

(222) At step **2208**, the SMF **160** may send, to the PCF **135**, a message (e.g., Npcf_SMPolicyControl_Get) requesting policy control information. The SMF **160** may invoke an operation (e.g., Npcf_SMPolicyControl_Get) to establish a PDU session with the PCF **135** and/or to obtain policy, charging, and/or PCC rules for the PDU session. The message requesting policy control information may comprise one or more of: information received from the AMF **155** (e.g., at step **2205**), and/or Ethernet packet filter set(s) information per the PDU session (e.g., indicated by a PDU session ID), per wireless device (e.g., which may be indicated by one or more wireless identities and/or identifiers), per data network (e.g., which may be an APN indicated by a DNN), and/or per network slice (e.g., which may be indicated by an S-NSSAI).

(223) At step **2209**, the PCF **135** may send, to the SMF **160**, a message (e.g., Nsmf_EventExposure_Subscribe). The PCF **135** may perform one or more steps, for example, after or in response to receiving the message from the SMF **160** (e.g., at step **2208**). The PCF **135** may determine one or more policy decisions. The one or more policy decisions may be based on information received from the SMF **160** (e.g., Ethernet packet filter set(s) information),

subscription information, and/or other information. The PCF **135** may create a service data flow template for one or more policy rules, for example, based on Ethernet packet filter set(s) information received from the SMF **160** (e.g., at step **2206**). The PCF **135** may send to the SMF **160** a message (e.g., policy response) comprising one or more of: a QoS policy for the PDU session; a charging policy for the PDU session; traffic steering control for steering traffic; and/or other policies. The PCF **135** may send, to the SMF **160**, the Ethernet packet filter set(s) information with one or more policies. The PCF **135** may subscribe one or more event in the SMF **160**, for example, by invoking the Nsmf_EventExposure_Subscribe operation.

(224) At step **2210**, the PCF **135** may send, to the SMF **160**, a message (e.g., Nsmf_EventExposure_Notify) reporting one or more events. The SMF **160** may invoke the Nsmf_EventExposure_Notify service operation, for example, to report one or more events to the PCF **135** that has been previously subscribed.

(225) At step **2211**, the SMF **160** may send, to the PCF **135**, a message (e.g., Npcf_SMPolicyControl_UpdateNotify) providing information. The information may comprise policy information, charging information, and/or PCC information. The PCF **135** may provide one or more updated policies to the SMF **160** by invoking the Npcf_SMPolicyControl_UpdateNotify service operation. The PCF **135** may provide authorized session-AMBR and/or authorized 5QI and/or ARP to the SMF **160**.

(226) At step **2212**, the SMF **160** may send, to the UPF **110**, a message (e.g., N4 session establish and/or modification request) requesting session establishment and/or modification. The SMF **160** may initiate an N4 session establishment procedure with the selected UPF **110**, for example, if a request type indicates an initial request and/or if a PDU session establishment authentication and/or authorization was not previously performed. The SMF **160** may initiate an N4 session modification procedure with the selected UPF **110**, for example, if a request type does not indicate an initial request and/or if a PDU session establishment authentication and/or authorization was previously performed. The SMF **160** may send an N4 session establishment and/or modification request to the UPF **110**. The SMF **160** may provide packet detection, enforcement, and/or reporting rules that may be installed on the UPF **110** for the PDU Session. The SMF **160** may provide the Ethernet packet filter set(s) information with or in one or more message for the packet detection, enforcement, and/or reporting rules. The CN tunnel information may be provided to the UPF **110** in this step, for example, if CN tunnel information is allocated by the SMF **160**.

(227) At step **2213**, the UPF **110** may send, to the SMF **160**, a message (e.g., N4 session establish/modification response) responding to a session establish and/or modification request (e.g., at step **2212**). The UPF **110** may acknowledge the SMF **160** by sending an N4 session establishment and/or modification response. The CN tunnel information may be provided to the SMF **160** in this step, for example, if CN tunnel information is allocated by the UPF **110**. The UPF **110** may perform service flow detection and/or policy enforcement using Ethernet packet filter set(s) information, for example, after or upon receiving a user plane data packet. The message responding to the session establish and/or modification request may comprise Ethernet packet filter set(s) information.

(228) At step **2214**, the SMF **160** may send, to the AMF **155**, a message (e.g., Nsmf_PDUSession_CreateSM response) for a session. The message at step **2214** may respond to the message at step **2206**. The message for the session may comprise one or more of: cause information, N2 SM information (e.g., PDU session ID, QoS profile(s), CN tunnel information, S-NSSAI, and/or session-AMBR), and/or an N1 SM container (e.g., a PDU session establishment accept. The PDU session establishment accept may comprise one or more of: a QoS rule, an SSC mode, an S-NSSAI, allocated address (e.g., for IPv4), and/or session-AMBR. The N2 SM information may comprise information that the AMF **155** may forward to the (R)AN **105**, which may comprise CN tunnel information corresponding to a Core Network address of the N3 tunnel corresponding to the PDU session. The QoS profile may provide the (R)AN **105** with the mapping

between QoS parameters and QoS flow identifiers. Multiple QoS profiles may be provided to the (R)AN **105**. The PDU session ID may be used by AN signaling (e.g., with the wireless device **100**) to indicate to the wireless device **100** an association between an AN resource and a PDU session for the wireless device **100**.

(229) At step **2215**, the AMF **155** may send, to the (R)AN **105**, a message (e.g., N2 PDU session request) requesting a session. (N2 SM information, NAS message (PDU Session ID, N1 SM container (PDU session establishment accept))). The AMF **155** may send the NAS message containing PDU Session ID and PDU session establishment accept targeted to the wireless device **100** and the N2 SM information received from the SMF **160** within the N2 PDU session request to the (R)AN **105**.

(230) At step **2216**, the (R)AN **105** and/or the wireless device **100** may send one or more messages to the other for an AN resource setup. The (R)AN **105** may issue an AN specific signaling exchange with the wireless device **100**. The AN specific signaling exchange may be related to information received from SMF **160** (e.g., at steps **2214** and/or **2215**). For example, a connection reconfiguration (e.g., an RRC connection reconfiguration for a 3GPP RAN) may be performed. The wireless device **100** may establish the necessary RAN resources related to QoS rules for the PDU session request. The (R)AN **105** may allocate (R)AN N3 tunnel information for the PDU session. The (R)AN **105** may forward a NAS message and/or one or more of a: PDU session ID and/or an N1 SM container (e.g., PDU session establishment accept). The (R)AN **105** may provide the NAS message to the wireless device **100**, for example, if the necessary RAN resources have been established and/or if the allocation of (R)AN tunnel information has been successful.

(231) At step **2217**, the (R)AN **105** may send, to the AMF **155**, a message (e.g., N2 PDU session response) responding to a session request (e.g., at step **2215**). The message responding to the session request may comprise one or more of: a PDU session ID, cause information, and/or N2 SM information. The N2 SM information may comprise one or more of: a PDU session ID, (R)AN tunnel information, and/or a list of accepted and/or rejected QoS profiles. The (R)AN tunnel information may correspond to the access network address of an N3 tunnel corresponding to the PDU session.

(232) At step **2218**, the AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_UpdateSMContext Request) requesting information. The message requesting information may comprise N2 SM information. The AMF **155** may forward N2 SM information received from the (R)AN **105** (e.g., at step **2217**) to the SMF **160**.

(233) At step **2219**, the SMF **160** may send, to the UPF **110**, a message (e.g., N4 session modification request) requesting a session modification. The SMF **160** may perform one or more actions, for example, after or in response to receiving the message at step **2218**. The SMF **160** may initiate an N4 session establishment procedure with the UPF **110**, for example, if the N4 session for the PDU session was not previously established. The SMF **160** may initiate an N4 session modification procedure with the UPF **110**, for example, if the N4 session for this PDU session was previously established. The SMF **160** may provide AN tunnel information and CN tunnel information. The CN tunnel information may be required to be provided, for example, if the SMF **160** selected CN tunnel information. The message requesting a session modification may comprise one or more policies for the PDU session. The Ethernet packet filter set(s) information may be included in or with the one or more policies.

(234) At step **2220**, the UPF **110** may send, to the SMF **160**, a message (e.g., N4 session modification response) responding to a session modification request (e.g., received at step **2219**). The UPF **110** may provide an N4 session establishment and/or modification response to the SMF **160**. The UPF may perform the service flow detection and policy enforcement using Ethernet packet filter set (s) information, for example, after or upon receiving a user plane data packet.

(235) At step **2221**, the SMF **160** may send, to the AMF **155**, a message (e.g., Nsmf_PDUSession_UpdateSMContext response) responding to a request for information (e.g.,

received at step **2218**). The message at step **2221** may comprise cause information. After step **2221**, the AMF **155** may forward one or more relevant events to the SMF **160**, for example, at handover, if the (R)AN tunnel information changes, and/or if the AMF **155** is relocated.

(236) FIG. **23** shows an example of procedures involving a session management function (SMF) in which a data network (DN) may send, to an SMF, one or more Ethernet packet filter set(s) information, wireless device identities and/or identifiers, and/or addresses (e.g., source MAC addresses and/or destination MAC addresses).

(237) At step **2301**, the DN **115** may perform one or more of the following steps. The DN **115** may select an SMF (e.g., the SMF **160**). The DN **115** may select an SMF using an NRF, for example, by providing one or more of the following information to the NRF: wireless device identity and/or identifier (e.g., NAI, SUPI, 5G-GUTI); data network name (DNN) and/or an APN; PDU session ID; and/or S-NSSAI (e.g., which may indicate a network slice). The DN **115** may send, to the SMF **160**, a first message (e.g., Ethernet MAC addresses provision). The first message may comprise one or more Ethernet MAC addresses. Additionally or alternatively, the first message may comprise one or more of: wireless device identities and/or identifiers (e.g., wireless device NAI, SUPI, 5G-GUTI, and/or other identifiers); data network name (DNN) and/or an APN; PDU session ID(s); S-NSSAI (e.g., indicating a network slice); and/or Ethernet packet filter sets per wireless device (e.g., which may be indicated by one or more wireless device identities), per data network (e.g., which may be an APN indicated by a DNN), per network slice (e.g., which may be indicated by an S-NSSAI); and/or per PDU session (e.g., which may be indicated by a PDU session ID). An Ethernet packet filter set may comprise one or more of: a source MAC address and/or a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); Customer-VLAN tag (C-TAG) and/or Service-VLAN tag (S-TAG) VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as indicated in IEEE 802.1Q); and IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). An IP packet filter set may comprise one or more of: a source IP address, a destination IP address, and/or a prefix (e.g., for IPv6); a source port number and/or a destination port number; a protocol ID of the protocol above IP and/or a next header type; a type of service (e.g., for IPv4), a traffic class (e.g., for IPv6), and/or a mask; a flow label (e.g., for IPv6); and/or security parameter index.

(238) At step **2302**, the SMF **160** may send, to the DN **115**, a second message (e.g., Ethernet MAC addresses response). The SMF **160** may send to the DN **115** the second message (e.g. Ethernet MAC addresses response), for example, after or in response to receiving the first message from the DN **115** (e.g., at step **2301**).

(239) Steps **2301-2302** may occur at any time, including at a time that may or may not be associated with steps **2305-2321**. For example, steps **2301-2302** may occur periodically, as part of a procedure to initiate communications with the DN **115** and/or any device, as part of a procedure to configure one or more devices for communications in a network, as part of a procedure to provide network updates, and/or as part of any other procedure.

(240) At step **2305**, a wireless device **100** may send, to the AMF **155**, a message (e.g., PDU session establishment request) requesting establishment of a session. The session may comprise an Ethernet type PDU session (e.g., Ethernet over wireless communications). The wireless device **100** may initiate a PDU session establishment procedure, for example, by sending to an AMF **155** an NAS Message. The NAS message may comprise one or more of: an S-NSSAI, a DNN, a PDU session ID, a request type, and/or an N1 SM container. The N1 SM container may comprise a PDU session establishment request. The NAS Message and/or an N1 SM container may comprise one or more wireless device identities and/or identifiers (e.g., SUPI, 5G-GUTI, and/or others). The wireless device **100** may initiate the wireless device requested PDU session establishment procedure, for example, by the transmission of a NAS message containing a PDU session establishment request within an N1 SM container. The PDU session establishment request may comprise one or more of: a PDU type (e.g., Ethernet), an SSC mode, protocol configuration

options, and/or a PDU session ID that may be generated by the wireless device **100**.

(241) At step **2306**, the AMF **155** may send, to the SMF **160**, a message (e.g., Namf_PDUSession_CreateSMContext) for a session. The AMF **155** may perform one or more steps, for example, after or in response to receiving the message at step **2305**. The AMF **155** may select an SMF (e.g., the SMF **160**). The AMF **155** may select an SMF using an NRF, for example, by providing one or more of the following information, that may be received from the wireless device **100**, to the NRF: wireless device identity and/or identifier; data network name (DNN); PDU session ID; and/or S-NSSAI. The NRF may select an SMF based on information that the NRF receives from the AMF **155**, which may comprise the same information that the AMF **155** received from the wireless device **100** (e.g., at step **2306**). The NRF may select an SMF based on the same NRF selection procedure in step **2301**. The NRF may select an SMF based on a comparison of information the NRF received from the AMF **155** (e.g., at step **2306**) with information the NRF received from the DN **115** (e.g., at step **2301**). The AMF **155** may send, to the SMF **160**, a message (e.g., Namf_PDUSession_CreateSMRequest) comprising one or more of: a SUPI, a DNN, a S-NSSAI, a PDU session ID, an AMF ID, a request type, an N1 SM container, a user location information, an access type, and/or a PEI. The N1 SM container may comprise a PDU session establishment request.

(242) At step **2307**, the SMF **160** and/or the UDM **140** may send one or more messages to the other, for example, for a subscription retrieval. The SMF **160** may correlate, compare, and/or map information received from the AMF **155** (e.g., at step **2306**) with the information received from the DN **115** (e.g., at step **2301**), for example, after or in response to receiving the message from the AMF **155**. The SMF **160** may correlate and/or compare addresses and/or Ethernet packet filter set(s) that may have been received from the DN **115**, with one or more of the following information that may have been received from the AMF **155**: wireless device identities and/or identifiers; data network name (DNN); PDU session ID; and/or S-NSSAI. The SMF **160** may register with the UDM **140**, for example, if the SMF **160** has not yet registered and/or if subscription data is not available. The SMF **160** may retrieve subscription data. The SMF **160** may subscribe to be notified, for example, if subscription data is modified. The SMF **160** may select a UPF and/or trigger a PDU session establishment authentication and/or authorization, for example, if the SMF **160** may be required to perform secondary authorization and/or authentication at an establishment (e.g., by a DN-AAA server) of a PDU session.

(243) Steps **2308-2321** correspond to steps **2208-2221**, respectively, as described above.

(244) FIG. **24** shows an example of procedures involving an application function (AF) in which a data network (DN) may send, to an AF, one or more Ethernet packet filter set(s) information, wireless device identities and/or identifiers, and/or addresses (e.g., source MAC addresses and/or destination MAC addresses).

(245) At step **2401**, the DN **115** may send to, the AF **145**, a first message (e.g., Ethernet MAC addresses provision). The first message may comprise one or more Ethernet MAC addresses. Additionally or alternatively, the first message may comprise one or more of: wireless device identities and/or identifiers (e.g., wireless device NAI, SUPI, 5G-GUTI, and/or other identifiers); data network name (DNN) and/or an APN; PDU session ID(s); S-NSSAI (e.g., indicating a network slice); and/or Ethernet packet filter sets per wireless device (e.g., which may be indicated by one or more wireless device identities), per data network (e.g., which may be an APN indicated by a DNN), per network slice (e.g., which may be indicated by an S-NSSAI); and/or per PDU session (e.g., which may be indicated by a PDU session ID). An Ethernet packet filter set may comprise one or more of: a source MAC address and/or a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); Customer-VLAN tag (C-TAG) and/or Service-VLAN tag (S-TAG) VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as indicated in IEEE 802.1Q); and IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). An IP packet filter set may comprise one or more of: a source IP

address, a destination IP address, and/or a prefix (e.g., for IPv6); a source port number and/or a destination port number; a protocol ID of the protocol above IP and/or a next header type; a type of service (e.g., for IPv4), a traffic class (e.g., for IPv6), and/or a mask; a flow label (e.g., for IPv6); and/or security parameter index.

(246) At step **2402**, the AF **145** may perform one or more steps, for example, after or in response to receiving the first message from the DN **115**. The AF **145** may select a PCF (e.g., the PCF **135**). The AF **145** may select a PCF by using an NRF, for example, by providing one or more of the following information, that may be received from the DN **115**, to the NRF: wireless device identity and/or identifier; data network name (DNN); PDU session ID; and/or S-NSSAI. The AF **145** may send, to a selected PCF (e.g., the PCF **135**), a second message (e.g., Ethernet MAC addresses provision). The second message may comprise some or all of the information in the first message received from the DN **115** at step **2401**.

(247) At step **2403**, the PCF **135** may send, to the AF **145**, a third message (e.g., Ethernet MAC addresses response). The PCF **135** may store information received from the second message (e.g., MAC addresses and/or Ethernet packet filter set(s) information) and/or send to the AF **145** the third message (e.g., Ethernet MAC addresses response), after or in response to receiving the second message from the PCF **135** at step **2402**.

(248) At step **2404**, the AF **145** may send, to the DN **115**, a fourth message (e.g., Ethernet MAC addresses response). The AF **145** may send to the DN **115** the fourth message (e.g., Ethernet MAC addresses response), for example, after or in response to receiving the third message from the PCF **135** at step **2403**. The fourth message may comprise some or all of the information in the third message received from the PCF **135** at step **2403**.

(249) Steps **2401-2404** may occur at any time, including at a time that may or may not be associated with steps **2405-2421**. For example, steps **2401-2404** may occur periodically, as part of a procedure to initiate communications with the DN **115** and/or any device, as part of a procedure to configure one or more devices for communications in a network, as part of a procedure to provide network updates, and/or as part of any other procedure.

(250) At step **2405**, the wireless device **100** may send, to the AMF **155**, a message (e.g., PDU session establishment request) requesting establishment of a session. The session may comprise an Ethernet type PDU session (e.g., Ethernet over wireless communications). The wireless device may initiate a PDU session establishment procedure, for example, by sending to an AMF **155** an NAS Message. The NAS message may comprise one or more of: an S-NSSAI, a DNN, a PDU session ID, a request type, and/or an N1 SM container. The N1 SM container may comprise a PDU session establishment request. The NAS Message and/or an N1 SM container may comprise one or more wireless device identities and/or identifiers (e.g., SUPI, 5G-GUTI, and/or others). The wireless device **100** may initiate the wireless device requested PDU session establishment procedure, for example, by the transmission of a NAS message containing a PDU session establishment request within an N1 SM container. The PDU session establishment request may comprise one or more of: a PDU type (e.g., Ethernet), an SSC mode, protocol configuration options, and/or a PDU session ID that may be generated by the wireless device **100**.

(251) At step **2406**, the AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_CreateSMContext) for a session. The AMF **155** may perform one or more steps, for example, after or in response to receiving the message at step **2405**. The AMF **155** may select an SMF (e.g., the SMF **160**). The AMF **155** may select an SMF such as described above regarding step **2405**. The AMF **155** may send, to the SMF **160**, a message (e.g., Nsmf_PDUSession_CreateSMRequest) comprising one or more of: a SUPI, a DNN, a S-NSSAI, a PDU session ID, AMF ID, a request type, an N1 SM container, user and/or device location information, an access type, and/or a PEI. The N1 SM container may comprise a PDU session establishment request.

(252) At step **2407**, the SMF **160** and/or the UDM **140** may send one or more messages to the

other, for example, for a subscription retrieval. The SMF **160** may register with the UDM **140**, for example, if the SMF **160** has not previously registered and/or if subscription data is not available. The SMF **160** may retrieve subscription data and subscribes to be notified, for example, if subscription data is modified. The SMF **160** may select a UPF and/or trigger a PDU session establishment authentication and/or authorization, for example, if the SMF **160** may be required to perform secondary authorization and/or authentication at an establishment (e.g., by a by a DN-AAA server) of a PDU session. The SMF **160** may perform some or all of step **2307** described above.

(253) At step **2408**, the SMF **160** may send, to the PCF **135**, a message (e.g., Npcf_SMPolicyControl_Get) requesting policy control information. The SMF **160** may perform one or more of the following steps, for example, after or in response to step **2407**. The SMF **160** may select a PCF (e.g., the PCF **135**). The SMF **160** may select a PCF using an NRF, for example, by providing one or more of the following information, that may be received from the AMF **155**, to the NRF: wireless device identity and/or identifier; data network name (DNN); PDU session ID; and/or S-NSSAI. The NRF may select a PCF based on the same NRF selection procedure in step **2402**. The NRF may select a PCF based on a comparison of information the NRF received from the SMF **160** (e.g., at step **2406**) with information the NRF received from the AF **145** in (e.g., at step **2402**). The NRF may select the same PCF **135** as at step **2402**. The SMF **160** may invoke the Npcf_SMPolicyControl_Get operation to establish a PDU session with the PCF **135** and/or obtain policy, charging, and/or PCC rules for the PDU session. The message requesting policy control information may comprise information received from the AMF **155** (e.g., wireless device identities and/or identifiers, DNN, PDU session ID, and/or S-NSSAI).

(254) At step **2409**, the PCF **135** may send, to the SMF **160**, a message (e.g., Nsmf_EventExposure_Subscribe). The PCF **135** may perform one or more steps, for example, after or in response to receiving the message from the SMF **160** (e.g., at step **2408**). The PCF **135** may correlate, compare, and/or map information received from the AF **145** (e.g., at step **2402**) with the information received from the SMF **160**. The PCF **135** may correlate and/or compare addresses and/or Ethernet packet filter set(s) that may have been received from the AF **145**, with one or more of the following information received from the SMF **160**: wireless device identities and/or identifiers; data network name (DNN); PDU session ID; and/or S-NSSAI. The PCF **135** may determine one or more policy decisions. The one or more policy decisions may be based on information received from the AF **145** (e.g., Ethernet packet filter set(s) information), information received from the SMF **160**, and/or other information. The PCF may create a service data flow template for one or more policy rules, for example, based on Ethernet packet filter set(s) information received from the SMF **160** (e.g., at step **2406**). The PCF **135** may send to the SMF **160** a message (e.g., policy response) by providing one or more of: a QoS policy for the PDU session; a charging policy for the PDU session; traffic steering control for steering traffic; and/or other policies. The PCF **135** may send, to the SMF **160**, the Ethernet packet filter set(s) information with one or more policies. The PCF **135** may subscribe one or more events in the SMF **160**, for example, by invoking the Nsmf_EventExposure_Subscribe operation.

(255) Steps **2410-2421** correspond to steps **2210-2221**, respectively, as described above.

(256) FIG. **25** shows an example of procedures involving a unified data management (UDM) in which a data network (DN) may send, to a UDM, one or more Ethernet packet filter set(s) information, wireless device identities and/or identifiers, and/or addresses (e.g., source MAC addresses and/or destination MAC addresses).

(257) At step **2501**, the DN **115** may send, to the UDM **140**, a first message (e.g., Ethernet MAC addresses provision). The first message may comprise one or more Ethernet MAC addresses. Additionally or alternatively, the first message may comprise one or more of: wireless device identities and/or identifiers (e.g., wireless device NAI, SUPI, 5G-GUTI, and/or other identifiers); data network name (DNN) and/or an APN; PDU session ID(s); S-NSSAI (e.g., indicating a

network slice); and/or Ethernet packet filter sets per wireless device (e.g., which may be indicated by one or more wireless device identities), per data network (e.g., which may be an APN indicated by a DNN), per network slice (e.g., which may be indicated by an S-NSSAI); and/or per PDU session (e.g., which may be indicated by a PDU session ID). An Ethernet packet filter set may comprise one or more of: a source MAC address and/or a destination MAC address; an Ethertype (e.g., as set forth in IEEE 802.3); Customer-VLAN tag (C-TAG) and/or Service-VLAN tag (S-TAG) VID fields (e.g., as set forth in IEEE 802.1Q); C-TAG and/or S-TAG PCP and/or DEI fields (e.g., as indicated in IEEE 802.1Q); and IP packet filter set (e.g., if Ethertype indicates an IPv4 payload and/or an IPv6 payload). An IP packet filter set may comprise one or more of: a source IP address, a destination IP address, and/or a prefix (e.g., for IPv6); a source port number and/or a destination port number; a protocol ID of the protocol above IP and/or a next header type; a type of service (e.g., for IPv4), a traffic class (e.g., for IPv6), and/or a mask; a flow label (e.g., for IPv6); and/or security parameter index.

(258) At step **2502**, the UDM **140** may send, to the DN **115**, a second message (e.g., Ethernet MAC addresses response). The UDM **140** may store received information (e.g., addresses and/or Ethernet packet filter set(s) information) and/or send to the DN **115** a response message (e.g., Ethernet MAC addresses response), for example, after or in response to receiving the first message from the DN **115**.

(259) Steps **2501-2502** may occur at any time, including at a time that may or may not be associated with steps **2505-2521**. For example, steps **2501-2502** may occur periodically, as part of a procedure to initiate communications with the DN **115** and/or any device, as part of a procedure to configure one or more devices for communications in a network, as part of a procedure to provide network updates, and/or as part of any other procedure.

(260) At step **2505**, the wireless device **100** may send, to the AMF **155**, a message (e.g., PDU establishment request) requesting establishment of a session. The session may comprise an Ethernet type PDU session (e.g., Ethernet over wireless communications). The wireless device **100** may initiate a PDU session establishment procedure, for example, by sending to an AMF **155** an NAS Message. The NAS message may comprise one or more of: an S-NSSAI, a DNN, a PDU session ID, a request type, and/or an N1 SM container. The N1 SM container may comprise a PDU session establishment request. The NAS Message and/or an N1 SM container may comprise one or more wireless device identities and/or identifiers (e.g., SUPI, 5G-GUTI, and/or others). The wireless device **100** may initiate the wireless device requested PDU session establishment procedure, for example, by the transmission of a NAS message containing a PDU session establishment request within an N1 SM container. The PDU session establishment request may comprise one or more of: a PDU type (e.g., Ethernet), an SSC mode, protocol configuration options, and/or a PDU session ID that may be generated by the wireless device **100**.

(261) At step **2506**, the AMF **155** may send, to the SMF **160**, a message (e.g., Namf_PDUSession_CreateSMContext) for a session. The AMF **155** may perform one or more steps, for example, after or in response to receiving the message at step **2505**. The AMF **155** may select an SMF (e.g., the SMF **160**) and send to the SMF **160** a message (e.g., Nsmf_PDUSession_CreateSMRequest) comprising one or more of: a SUPI, a DNN, a S-NSSAI, a PDU session ID, an AMF ID, a request type, an N1 SM container, user location information, an access type, and/or a PEI. The N1 SM container may comprise a PDU session establishment request.

(262) At step **2507**, the SMF **160** and/or the UDM **140** may send one or more messages to the other, for example, for a subscription retrieval. The SMF **160** may send, to the UDM **140**, a message to obtain subscription data, for example, after or in response to the message received from the AMF **155**. The SMF **160** may send, to the UDM **140**, at least one message comprising one or more of: wireless device identities and/or identifiers; data network name (DNN); PDU session ID; and/or S-NSSAI. The UDM **140** may correlate, compare, and/or map information received from the

DN **115** (e.g., at step **2501**) with information received from the SMF **160**, after or in response to receiving the message from the SMF **160**. The SMF **160** may correlate and/or compare addresses and/or Ethernet packet filter set(s) that may have been received from the DN **115**, with one or more of the following information received from the SMF **160**: wireless device identities and/or identifiers; data network name (DNN); PDU session ID; and/or S-NSSAI. The UDM **140** may send, to the SMF **160**, subscription data with or in a message comprising Ethernet packet filter set(s) received from the DN **115**. The SMF **160** may correlate and/or compare information received from the UDM **140** with information received from the AMF **155**, for example, after or in response to receiving the information from the UDM **140**. For example, the SMF **160** may correlate and/or compare addresses and/or Ethernet packet filter set(s) received from the UDM **140** with one or more of the following information that may be received from the AMF **155**: wireless device identities and/or identifiers; data Network Name (DNN); PDU session ID; and/or S-NSSAI.

(263) At step **2508**, the SMF **160** may send, to the PCF **135**, a message (e.g., Npcf_SMPolicyControl_Get) requesting policy control information. The SMF **160** may invoke the Npcf_SMPolicyControl_Get operation, for example, to establish a PDU session with the PCF **135** and/or obtain policy, charging, and/or PCC rules for the PDU session. The message requesting policy control information may comprise Ethernet packet filter set(s) information per the PDU session (e.g., which may be indicated by a PDU session ID), per wireless device (e.g., which may be indicated by one or more wireless device identities), per data network (e.g., which may be an APN indicated by a DNN), and/or per network slice (e.g., which may be indicated by an S-NSSAI).

(264) Steps **2509-2521** correspond to steps **2209-2221**, respectively, as described above.

(265) FIG. **26** shows an Ethernet over wireless communications procedure that may be performed, in whole or in part, by one or more computing devices. As examples, the procedure shown in FIG. **26** may be performed by a session management function (e.g., the SMF **160**). Additionally or alternatively, at least some of the procedure shown in FIG. **26** may be performed by a policy control function (e.g., PCF **135**), a unified data management (e.g., UDM **140**), a network exposure function (e.g., NEF **125**), an access and mobility management function (e.g., AMF **155**), a network repository function (e.g., NRF), an access network (e.g., (R)AN **105**), a wireless device (e.g., wireless device **100**), and/or a data network (e.g., DN **115**). The data network may be remote from a network for the wireless device (e.g., a 5GC). The data network may be in a second network (e.g., that may be controlled by a second network operator) outside of a first network (e.g., that may be controlled by a first operator). The data network may be a DN-AAA server. Any other computing device (e.g., such as shown in FIGS. **22-25**) may perform one or more portions of the procedures shown in FIG. **26** for Ethernet over wireless communications.

(266) At step **2600**, a data network (e.g., DN **115**) may send, to a computing device (e.g., the NEF **125**, the AF **145**, the UDM **140**, the PCF **135**, the SMF **160**, or any other device such as shown in FIGS. **22-25**), one or more Ethernet MAC addresses (e.g., source Ethernet MAC addresses and/or destination Ethernet MAC addresses). The computing device may send the one or more Ethernet MAC addresses to one or more second computing devices (e.g., the UDM **140**, the PCF **135**, and/or the SMF). The one or more second computing devices may send the one or more Ethernet MAC addresses to a session management function (e.g., the SMF **160**). The one or more Ethernet MAC addresses may be included in one or more Ethernet packet filter sets that may be sent at step **2600**. Step **2600** may comprise one or more of steps **2201-2204**, **2301-2302**, **2401-2404**, and/or **2501-2502**, described above. Step **2600** may occur at any time, including at a time that may or may not be associated with steps **2601-2614**, described below. For example, step **2600** may occur periodically, as part of a procedure to initiate communications with the DN **115** and/or any device, as part of a procedure to configure one or more devices for communications in a network, as part of a procedure to provide network updates, and/or as part of any other procedure. Additionally or alternatively, step **2600** may be performed before, during, or after step **2601** and/or step **2602**, described below.

(267) At step **2601**, a wireless device (e.g., the wireless device **100**) may send, to a computing device (e.g., the (R)AN **105**, the AMF **155**, the UPF **110**, the SMF **160**, and/or the PCF **135**) one or more messages comprising one or more Ethernet packet filter sets. The wireless device may send the one or more messages to a session management function via one or more of a radio access network (e.g., the (R)AN **105**), an access and mobility management function (e.g., the AMF **155**), and/or a user plane function (e.g., the UPF **110**). The Ethernet packet filter sets may comprise one or more of a source Ethernet MAC address, a destination Ethernet MAC address, an Ethertype, a virtual local area network tag, and/or an IP packet filter set. The Ethernet packet filter set may be associated with one or more of: a PDU session, the wireless device, a data network, and/or a network slice. The wireless device may send the one or more messages to an access network (e.g., the (R)AN **105**), to one or more base stations, and/or to an access and mobility management function (e.g., the AMF **155**). The access network may send the one or more messages to the session management function (e.g., via a user plane function such as the UPF **110**) and/or the access and mobility management function. The access and mobility management function may send the one or more messages to the session management function. The session management function may receive the one or more messages. The session management function may receive the one or more Ethernet MAC addresses. Step **2601** may comprise one or more of steps **2205**, **2206**, **2305**, **2306**, **2405**, **2406**, **2505**, and/or **2506**, described above.

(268) At step **2602**, a computing device (e.g., a session management function or any device shown in FIGS. **22-25**) may determine whether the one or more Ethernet packet filter sets comprise a request for an Ethernet type PDU session. The computing device may make such a determination based on an Ethertype in the Ethernet packet filter sets. If the computing device determines that at least one of the Ethernet packet filter sets is not associated with a request for an Ethernet type PDU session, the procedure may continue to step **2603**. If the computing device determines that at least one of the Ethernet packet filter sets is associated with a request for an Ethernet type PDU session, the procedure may continue to step **2606**.

(269) At step **2603**, the computing device (e.g., a session management function or any device shown in FIGS. **22-25**) may determine whether to redirect the wireless device. For example, if the one or more messages from step **2601** indicate a type of service that is not supported for the wireless device (e.g., based on one or more policies or an availability of one or more applications), the computing device may send a message to the wireless device indicating one or more options for the wireless device to obtain support for the type of service (e.g., updating one or more policies to include a registration of one or more services associated with the type, or identifying another computing device that may provide services for the type). If the computing device determines to redirect the wireless device (e.g., based on an indication from the wireless device requesting redirection), at step **2604**, the computing device may redirect the wireless device to an offer for initiating service of the type of service not presently supported for the wireless device. If the computing device determines not to redirect the wireless device (e.g., based on a timer expiration or receiving an indication from the wireless device declining redirection), at step **2605**, the computing device may discard the Ethernet packet filter set(s) associated with the type that is not supported for the wireless device. After step **2604** and/or step **2605**, the procedure may end.

(270) At step **2606**, the computing device (e.g., a session management function or any device shown in FIGS. **22-25**) may determine an application and/or service for Ethernet over wireless communications for the wireless device, for example, if a type of a session request associated indicated by the one or more messages is confirmed, at step **2602**, to be an Ethernet type. The computing device may determine at least one policy rule (e.g., a QoS rule), one or more parameters for the at least one policy rule (e.g., QoS parameters), and/or a policy decision (e.g., whether QoS is satisfied), based on the one or more Ethernet packet filter sets. The computing device may determine an application and/or type of service based on an Ethernet MAC address (e.g., a destination Ethernet MAC address and/or a source Ethernet MAC address) in the one or more

Ethernet packet filter sets received at step **2601** and/or in the one or more Ethernet MAC addresses received at step **2600**. The destination Ethernet MAC address may indicate an application server that may be associated with a one or more applications and/or services. The source Ethernet MAC address may indicate a location and/or a profile associated with the wireless device that may indicate one or more applications and/or services.

(271) At step **2607**, the computing device (e.g., a session management function or any device shown in FIGS. 22-25) may determine and/or apply a first policy. The first policy may comprise one or more rules. A rule may be a policy rule (e.g., a rule associated with a policy), a charging rule (e.g., a rule associated with a charging policy), or a policy and charging rule (e.g., a policy and charging control rule (PCC)). A policy control function (e.g., PCF **135**) may determine the first policy (e.g., a PCC) and/or may send the first policy to the computing device (e.g., SMF **160**). The first policy may be determined based on the one or more Ethernet MAC addresses (e.g., one or more source Ethernet MAC addresses and/or one or more destination Ethernet MAC addresses). The first policy may comprise a PCC comprising the one or more Ethernet source MAC addresses and a QoS policy. A policy rule may comprise, for example, one or more of a: quality of service (QoS) rule, a gating rule, a traffic detection rule, a traffic steering control rule, and/or any other rule that may be associated with a user, device, and/or service. A policy may comprise one any one or more rules. For example, a QoS policy may comprise a QoS rule. A QoS rule may be based on one or more priority levels (e.g., high priority, low priority, or any other level of priority). A priority level may be associated with a particular value or range of values for a bandwidth, latency, and/or allowance and retention (ARP). A gating rule may be based on a packet type (e.g., Ethertype) or a service access level (e.g., user and/or device authorization to access one or more services using Ethernet over wireless communications). A traffic detection rule may be based on a determination of whether signal traffic that may be associated with an Ethernet PDU session may be satisfied for a request for the Ethernet PDU session. The traffic detection rule may comprise detecting a service flow based on receiving a user plane data packet. A traffic steering control rule may comprise directing traffic associated with an Ethernet PDU session for optimal network performance.

Additionally or alternatively, at optional step **2607a**, the computing device may compare, correlate, and/or map the one or more Ethernet MAC addresses with the one or more Ethernet packet filter sets. For example, the computing device may compare one or more source Ethernet MAC addresses with information in an Ethernet packet filter set. A PCC (such as the first policy or one or more second policies) may be based on the comparison. If a source Ethernet MAC address matches an Ethernet MAC address in the Ethernet packet filter set (or does not match an address in a disallowed list in the Ethernet packet filter set), one or more Ethernet packets may be sent to the wireless device. If a source Ethernet MAC address does not match an Ethernet MAC address in the Ethernet packet filter set (or matches an address in a disallowed list in the Ethernet packet filter set), one or more Ethernet packets may not be sent to the wireless device and/or may be discarded. Step **2607a** may be performed as part of applying the first policy at step **2607** and/or as a separate step (e.g., before, during, or after step **2607**). Step **2607** and/or step **2607a** may correspond to one or more of steps **2206**, **2207**, **2306**, **2307**, **2406-2409**, and/or **2506-2509**.

(272) At step **2608**, the computing device (e.g., a session management function or any device shown in FIGS. 22-25) may determine whether the first policy is satisfied. For example, based on whether the first policy is satisfied (e.g., a gating rule), the computing device may allow or discard packets. If the first policy is not satisfied, the procedure may continue to step **2603** described above (e.g., for packet discard and/or redirection to offering a service). If the first policy is satisfied, the procedure may continue to step **2609**.

(273) At step **2609**, the computing device (e.g., a session management function or any device shown in FIGS. 22-25) may determine one or more second policies to apply to the Ethernet packet filter set(s). The one or more second policies may comprise one or more rules, such as a policy rule, a charging rule, and/or a PCC. The one or more second policies may comprise for example,

one or more of a: quality of service (QoS) rule, a gating rule, a traffic detection rule, a traffic steering control rule, and/or any other rule that may be associated with a user, device, and/or service, such as described above regarding step **2607**. The one or more second policies may comprise at least one charging rule (e.g., a PCC). A charging rule may be based on charging (e.g., online charging, offline charging, and/or converged charging) associated with a particular service, application, user, device, and/or group of users and/or devices. Charging information may be based on one or more ratings (e.g., cost-per-service associated with one or more users and/or devices) and/or addresses (e.g., source Ethernet MAC address of the wireless device and/or destination Ethernet MAC address of an application server associated with the service requested by the wireless device). The computing device may store and/or maintain at least some information about one or more charging rules that may be associated with a wireless device. Additionally or alternatively, the computing device may obtain one or more charging rules and/or updates to one or more charging rules from a second computing device (e.g., a policy control function such as the PCF **135**).

(274) At step **2610**, the computing device (e.g., a session management function or any device shown in FIGS. **22-25**) may determine whether the one or more second policies requires an updated policy. If at least one of the one or more second policies require an update (e.g., based on the computing device not having at least one of the one or more second policies and/or not having a recent version of at least one of the one or more second policies), the procedure may continue to step **2611**. If at least one of the one or more second policies do not require an update, the procedure may continue to step **2613**.

(275) At step **2611**, the computing device (e.g., a session management function or any device shown in FIGS. **22-25**) may send a request for one or more updated policies. The computing device may send the request to a second computing device (e.g., a policy control function). The request for one or more updated policies may comprise a request for a policy and charging control rule and/or the one or more Ethernet packet filter sets for a data flow. The computing device (e.g., a session management function) may send a message to a third computing device (e.g., a user plane function such as UPF **110**) comprising the one or more Ethernet packet filter sets for the data flow and/or one or more parameters indicating a policy rule. The message to the third computing device (e.g., a user plane function) may comprise a request to establish a user plane session.

(276) At step **2612**, the computing device (e.g., a session management function or any device shown in FIGS. **22-25**) may receive, from the second computing device (e.g., a policy control function), a response message comprising one or more updated policies. The one or more updated policies may comprise at least one charging policy (e.g., a PCC) corresponding to the requested policy and charging control rule. The computing device (e.g., a session management function) may send the one or more updated policies to the third computing device (e.g., a user plane function). The computing device (e.g., a session management function) may receive from the third computing device (e.g., a user plane function) a message indicating that the third computing device has received the message from the computing device. The message from the third computing device (e.g., a user plane function) may comprise a user plane data packet. The third computing device (e.g., a user plane function) may enforce the policy rule and/or the policy and charging control rule sent at step **2611**, for example, based on quality of service parameters associated with information in the one or more Ethernet packet filter sets.

(277) At step **2613**, a computing device (e.g., a user plane function, a session management function, and/or any device shown in FIGS. **22-25**) may apply the one or more second policies to the Ethernet packet filter set(s). For example, the computing device may provide for an Ethernet PDU session requested by the wireless device to the extent the request complies with the policy rules of the one or more second policies, and/or the computing device may associate charging information with the Ethernet PDU session requested by the wireless device.

(278) At step **2614**, the computing device (e.g., a user plane function, an access network, a session

management function, and/or on any device shown in FIGS. 22-25) may send and/or receive data packets associated with the Ethernet PDU session requested by the wireless device. The wireless device may receive the data packets associated with the Ethernet PDU session requested by the wireless device. After step 2614, the Ethernet PDU session requested by the wireless device may end and the procedure shown in FIG. 26 may end.

(279) One or more features of the disclosure may be implemented in a computer-usable data and/or computer-executable instructions, such as in one or more program modules, executed by one or more computers or other devices. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types when executed by a processor in a computer or other data processing device. The computer executable instructions may be stored on one or more computer readable media such as a hard disk, optical disk, removable storage media, solid state memory, RAM, etc. The functionality of the program modules may be combined or distributed as desired. The functionality may be implemented in whole or in part in firmware or hardware equivalents such as integrated circuits, field programmable gate arrays (FPGA), and the like. Particular data structures may be used to more effectively implement one or more features of the disclosure, and such data structures are contemplated within the scope of computer executable instructions and computer-usable data described herein.

(280) Many of the elements in examples may be implemented as modules. A module may be an isolatable element that performs a defined function and has a defined interface to other elements. The modules may be implemented in hardware, software in combination with hardware, firmware, wetware (i.e., hardware with a biological element) or a combination thereof, all of which may be behaviorally equivalent. For example, modules may be implemented as a software routine written in a computer language configured to be executed by a hardware machine (such as C, C++, Fortran, Java, Basic, Matlab or the like) or a modeling/simulation program such as Simulink, Stateflow, GNU Octave, or LabVIEWMathScript. Additionally or alternatively, it may be possible to implement modules using physical hardware that incorporates discrete or programmable analog, digital and/or quantum hardware. Examples of programmable hardware may comprise: computers, microcontrollers, microprocessors, application-specific integrated circuits (ASICs); field programmable gate arrays (FPGAs); and complex programmable logic devices (CPLDs). Computers, microcontrollers, and microprocessors may be programmed using languages such as assembly, C, C++ or the like. FPGAs, ASICs, and CPLDs may be programmed using hardware description languages (HDL), such as VHSIC hardware description language (VHDL) or Verilog, which may configure connections between internal hardware modules with lesser functionality on a programmable device. The above mentioned technologies may be used in combination to achieve the result of a functional module.

(281) A non-transitory tangible computer readable media may comprise instructions executable by one or more processors configured to cause operations of multi-carrier communications described herein. An article of manufacture may comprise a non-transitory tangible computer readable machine-accessible medium having instructions encoded thereon for enabling programmable hardware to cause a device (e.g., a wireless device, wireless communicator, a UE, a base station, and the like) to enable operation of multi-carrier communications described herein. The device, or one or more devices such as in a system, may include one or more processors, memory, interfaces, and/or the like. Other examples may comprise communication networks comprising devices such as base stations, wireless devices or user equipment (UE), servers, switches, antennas, and/or the like. A network may comprise any wireless technology, including but not limited to, cellular, wireless, Wi-Fi, 4G, 5G, any generation of 3GPP or other cellular standard or recommendation, wireless local area networks, wireless personal area networks, wireless ad hoc networks, wireless metropolitan area networks, wireless wide area networks, global area networks, space networks, and any other network using wireless communications. Any device (e.g., a wireless device, a base

station, or any other device) or combination of devices may be used to perform any combination of one or more of steps described herein, including, e.g., any complementary step or steps of one or more of the above steps.

(282) Although examples are described above, features and/or steps of those examples may be combined, divided, omitted, rearranged, revised, and/or augmented in any desired manner. Various alterations, modifications, and improvements will readily occur to those skilled in the art. Such alterations, modifications, and improvements are intended to be part of this description, though not expressly stated herein, and are intended to be within the spirit and scope of the disclosure. Accordingly, the foregoing description is by way of example only, and is not limiting.

Claims

1. A method comprising: receiving, by a policy control function device, at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device; and sending, by the policy control function device, at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.
2. The method of claim 1, wherein the receiving the at least one Ethernet MAC address comprises receiving, by the policy control function device, at least one Ethernet packet filter set, wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.
3. The method of claim 1, further comprising receiving, from the wireless device, an Ethernet packet filter set, wherein the at least one PCC rule is based on a comparison of the at least one Ethernet MAC address with information in the Ethernet packet filter set.
4. The method of claim 1, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.
5. The method of claim 1, wherein the receiving the at least one Ethernet MAC address comprises receiving, from a first device associated with a data network and via a second device, the at least one Ethernet MAC address, and wherein the second device comprises at least one of: a network exposure function device; an application function device; a unified data management device; or a second policy control function device.
6. The method of claim 1, wherein the policy control function device is selected, by a session management function device, based on the at least one Ethernet MAC address.
7. The method of claim 1, wherein the at least one Ethernet MAC address comprises an Ethernet source MAC address.
8. The method of claim 1, further comprising determining, by the policy control function device based on the at least one Ethernet MAC address for the wireless device, the at least one PCC rule.
9. The method of claim 8, wherein the determining the at least one PCC rule comprises determining the at least one PCC rule based on at least one of: Ethernet packet filter set information or subscription information.
10. The method of claim 1, wherein the receiving the at least one Ethernet MAC address comprises receiving the at least one Ethernet MAC address from a session management function device, and wherein the sending the at least one PCC rule comprises sending the at least one PCC rule to the session management function device.
11. A method comprising: sending, by a session management function device to a policy control function device, at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device; and receiving, by the session management function device, at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.

12. The method of claim 11, wherein the sending the at least one Ethernet MAC address comprises sending at least one Ethernet packet filter set, wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.
13. The method of claim 11, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.
14. The method of claim 11, further comprising selecting, by the session management function device based on the at least one Ethernet MAC address, the policy control function device.
15. The method of claim 11, wherein the at least one Ethernet MAC address comprises an Ethernet source MAC address.
16. The method of claim 11, wherein the receiving the at least one PCC rule comprises receiving the at least one PCC rule from the policy control function device.
17. A policy control function device comprising: one or more processors; and memory storing instructions that, when executed by the one or more processors, configure the policy control function device to: receive at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device; and send at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.
18. The policy control function device of claim 17, wherein the instructions, when executed by the one or more processors, configure the policy control function device to receive the at least one Ethernet MAC address by receiving at least one Ethernet packet filter set, and wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.
19. The policy control function device of claim 17, wherein the instructions, when executed by the one or more processors, further configure the policy control function device to receive, from the wireless device, an Ethernet packet filter set, and wherein the at least one PCC rule is based on a comparison of the at least one Ethernet MAC address with information in the Ethernet packet filter set.
20. The policy control function device of claim 17, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.
21. The policy control function device of claim 17, wherein the instructions, when executed by the one or more processors, configure the policy control function device to receive the at least one Ethernet MAC address by receiving, from a first device associated with a data network and via a second device, the at least one Ethernet MAC address, and wherein the second device comprises at least one of: a network exposure function device; an application function device; a unified data management device; or a second policy control function device.
22. The policy control function device of claim 17, wherein the policy control function device is selected, by a session management function device, based on the at least one Ethernet MAC address.
23. The policy control function device of claim 17, wherein the at least one Ethernet MAC address comprises an Ethernet source MAC address.
24. The policy control function device of claim 17, wherein the instructions, when executed by the one or more processors, further configure the policy control function device to determine, based on the at least one Ethernet MAC address for the wireless device, the at least one PCC rule.
25. The policy control function device of claim 24, wherein the instructions, when executed by the one or more processors, configure the policy control function device to determine the at least one PCC rule by determining the at least one PCC rule based on at least one of: Ethernet packet filter set information or subscription information.
26. The policy control function device of claim 17, wherein the instructions, when executed by the

one or more processors, configure the policy control function device to receive the at least one Ethernet MAC address by receiving the at least one Ethernet MAC address from a session management function device, and wherein the instructions, when executed by the one or more processors, configure the policy control function device to send the at least one PCC rule by sending the at least one PCC rule to the session management function device.

27. A session management function device comprising: one or more processors; and memory storing instructions that, when executed by the one or more processors, configure the session management function device to: send, to a policy control function device, at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device; and receive at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.

28. The session management function device of claim 27, wherein the instructions, when executed by the one or more processors, configure the session management function device to send the at least one Ethernet MAC address by sending at least one Ethernet packet filter set, wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.

29. The session management function device of claim 27, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.

30. The session management function device of claim 27, wherein the instructions, when executed by the one or more processors, further configure the session management function device to select, based on the at least one Ethernet MAC address, the policy control function device.

31. The session management function device of claim 27, wherein the at least one Ethernet MAC address comprises an Ethernet source MAC address.

32. The session management function device of claim 27, wherein the instructions, when executed by the one or more processors, configure the session management function device to receive the at least one PCC rule by receiving the at least one PCC rule from the policy control function device.

33. A non-transitory computer-readable medium storing instructions that, when executed, configure a policy control function device to: receive at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device; and send at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.

34. The non-transitory computer-readable medium of claim 33, wherein the instructions, when executed, configure the policy control function device to receive the at least one Ethernet MAC address by receiving at least one Ethernet packet filter set, and wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.

35. The non-transitory computer-readable medium of claim 33, wherein the instructions, when executed, further configure the policy control function device to receive, from the wireless device, an Ethernet packet filter set, and wherein the at least one PCC rule is based on a comparison of the at least one Ethernet MAC address with information in the Ethernet packet filter set.

36. The non-transitory computer-readable medium of claim 33, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.

37. The non-transitory computer-readable medium of claim 33, wherein the instructions, when executed, configure the policy control function device to receive the at least one Ethernet MAC address by receiving, from a first device associated with a data network and via a second device, the at least one Ethernet MAC address, and wherein the second device comprises at least one of: a network exposure function device; an application function device; a unified data management

device; or a second policy control function device.

38. A non-transitory computer-readable medium storing instructions that, when executed, configure a session management function device to: send, to a policy control function device, at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device; and receive at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.

39. The non-transitory computer-readable medium of claim 38, wherein the instructions, when executed, configure the session management function device to send the at least one Ethernet MAC address by sending at least one Ethernet packet filter set, wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.

40. The non-transitory computer-readable medium of claim 38, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.

41. A system comprising: a policy control function device; and a session management function device configured to: send, to the policy control function device, at least one Ethernet medium access control (MAC) address, for a packet data unit (PDU) session, of a wireless device, wherein the policy control function device is configured to: send, to the session management function device, at least one policy and charging control (PCC) rule, for the PDU session, that is based on the at least one Ethernet MAC address for the wireless device.

42. The system of claim 41, wherein the session management function device is configured to send the at least one Ethernet MAC address by sending at least one Ethernet packet filter set, and wherein the at least one Ethernet packet filter set comprises an Ethertype and the at least one Ethernet MAC address.

43. The system of claim 41, wherein the policy control function device is further configured to receive, from the wireless device, an Ethernet packet filter set, and wherein the at least one PCC rule is based on a comparison of the at least one Ethernet MAC address with information in the Ethernet packet filter set.

44. The system of claim 41, wherein the at least one PCC rule comprises at least one of: a quality of service policy associated with the wireless device; a charging policy associated with the wireless device; traffic steering control; or Ethernet packet filter set information.
