

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12401937
B2
August 26, 2025
Kim; Sungjin et al.

Battery and electronic device including the same

Abstract

An electronic device according to an embodiment of the disclosure may include: a battery including an anode having a first length and a cathode having a second length different from the first length, a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery, and a speaker stacked with the battery. The flexible printed circuit board may include a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode. A first current of a first winding direction generated due to a length difference between the cathode and the anode may flow in the battery, and a second current of a second winding direction opposite to the first winding direction may flow in a wiring disposed closer to the speaker between the power wiring and the ground wiring.

Inventors: Kim; Sungjin (Suwon-si, KR), Kim; Chulhan (Suwon-si, KR), Han; Kiwook (Suwon-si, KR), Kim; Sohee (Suwon-si, KR), Park; Haekeu (Suwon-si, KR), Chang; Juhee (Suwon-si, KR), Jung; Sigyung (Suwon-si, KR), Jeong; Hyeonyeong (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008778438

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 18/353384

Filed: July 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240031730 A1	Jan. 25, 2024

Foreign Application Priority Data

KR	10-2022-0089447	Jul. 20, 2022
KR	10-2022-0099582	Aug. 09, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/009920 20230712 PENDING child-doc US 18353384

Publication Classification

Int. Cl.: H04R1/10 (20060101); H05K1/02 (20060101); H05K1/16 (20060101)

U.S. Cl.:

CPC H04R1/1091 (20130101); H05K1/028 (20130101); H05K1/165 (20130101);

Field of Classification Search

CPC: H04R (1/1019); H04R (1/10); H04R (1/1025); H04R (1/1061); H04R (25/605); H04R (25/60); H04R (25/604); H04R (25/30); H04R (25/602); H05K (1/028); H05K (1/165)

USPC: 381/74; 381/323; 381/324; 381/328

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0077484	12/2017	Yeung et al.	N/A	N/A
2018/0242074	12/2017	Xu et al.	N/A	N/A
2021/0037304	12/2020	Huang et al.	N/A	N/A
2021/0083315	12/2020	Pregler et al.	N/A	N/A
2021/0176557	12/2020	Schreuder	N/A	N/A
2021/0250676	12/2020	Kim et al.	N/A	N/A
2021/0400370	12/2020	Pine et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
113225633	12/2020	CN	N/A
213960298	12/2020	CN	N/A
215070172	12/2020	CN	N/A
216528992	12/2021	CN	N/A
115064750	12/2021	CN	N/A
115103255	12/2021	CN	N/A
217691453	12/2021	CN	N/A
116683123	12/2022	CN	N/A
4443576	12/2023	EP	N/A
20180000499	12/2017	KR	N/A
10-2021-0101597	12/2020	KR	N/A

20220012591	12/2021	KR	N/A
10-2022-0037250	12/2021	KR	N/A
10-2022-0101834	12/2021	KR	N/A

OTHER PUBLICATIONS

Search Report and Written Opinion dated Oct. 13, 2023 issued in International Patent Application No. PCT/KR2023/009920. cited by applicant

Extended European Search Report dated May 22, 2025 issued in European Patent Application No. 23843257.9. cited by applicant

Primary Examiner: Matar; Ahmad F.

Assistant Examiner: Diaz; Sabrina

Attorney, Agent or Firm: Nixon & Vanderhye, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2023/009920 designating the United States, filed on Jul. 12, 2023, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No 10-2022-0089447, filed on Jul. 20, 2022, in the Korean Intellectual Property Office, and to Korean Patent Application No. 10-2022-0099582, filed on Aug. 9, 2022, in the Korean Intellectual Property Office, the disclosures of all of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) The disclosure relates to a battery and an electronic device including the same.

Description of Related Art

(2) Owing to the development of information and communication technology and semiconductor technology, various electronic devices have been rapidly proliferated and increasingly used. Particularly, recent electronic devices have been developed for communication while being carried. Further, electronic devices may output stored information as sound or an image. As the integration level of the electronic devices increases and ultra-high speed, large-capacity wireless communication becomes common, a single electronic device such as a mobile communication terminal is equipped with various functions over the recent years. For example, not only a communication function but also a multimedia function such as music/video playback is integrated in a single electronic device. Such electronic devices are miniaturized so that users may conveniently carry them.

(3) As electronic devices are used in daily living, users' demands for portability and usability of the electronic devices may increase. According to the users' demands, for example, wearable electronic devices that may be carried and used while worn on the body, such as wireless earphones, smart watches, or glasses-type electronic devices, are commercialized, and secondary batteries which are chargeable and dischargeable are used as a power source of the electronic devices.

SUMMARY

(4) An electronic device according to an example embodiment of the disclosure may include: a battery including an anode having a first length and a cathode having a second length different from the first length, a flexible printed circuit board electrically connected to the battery and

surrounding at least part of a side surface of the battery, and a speaker stacked with the battery. The flexible printed circuit board may include: a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode. A first current having a first winding direction, generated due to a length difference between the cathode and the anode, may flow in the battery. A second current having a second winding direction opposite to the first winding direction may flow in a wiring disposed closer to the speaker between the power wiring and the ground wiring.

(5) An electronic device according to an example embodiment of the disclosure may include: a battery including an anode having a first length and a cathode having a second length greater than the first length, a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery, and a speaker stacked with the battery. The flexible printed circuit board may include a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode. A first current having a first winding direction generated based on a length difference between the cathode and the anode may flow in the battery. A second current having a second winding direction opposite to the first winding direction may flow in the ground wiring disposed closer to the speaker than the power wiring.

(6) An electronic device according to an example embodiment of the disclosure may include: a battery including an anode having a first length and a cathode having a second length greater than the first length, a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery, and a speaker stacked with the battery. The flexible printed circuit board may include a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode. A first current having a first winding direction generated based on a length difference between the cathode and the anode may flow in the battery. A second current having a second winding direction identical to the first winding direction may flow in the power wiring disposed closer to the speaker than the ground wiring.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment of the disclosure.
- (2) FIG. 2 is a block diagram illustrating an audio module according to an embodiment of the disclosure.
- (3) FIG. 3 is a perspective view illustrating an electronic device according to an embodiment of the disclosure.
- (4) FIG. 4 is a cross-sectional view illustrating an electronic device, viewed from a side, according to an embodiment of the disclosure.
- (5) FIG. 5 is a side view illustrating a speaker and a battery according to an embodiment of the disclosure.
- (6) FIGS. 6A to 6E are perspective views illustrating an electronic device according to an embodiment of the disclosure.
- (7) FIG. 7A is a front view illustrating a battery and a printed circuit board according to an embodiment of the disclosure.
- (8) FIG. 7B is a perspective view illustrating a battery and a printed circuit board according to an embodiment of the disclosure.
- (9) FIG. 8A is a perspective view and an exploded perspective view illustrating a battery according to an embodiment of the disclosure.
- (10) FIG. 8B is a diagram illustrating an electrode assembly viewed from above.
- (11) FIG. 9A is a diagram illustrating a printed circuit board according to an embodiment of the disclosure.

- (12) FIG. 9B is a front view illustrating a speaker, a battery, and a printed circuit board according to an embodiment of the disclosure.
- (13) FIG. 9C is a cross-sectional view illustrating the speaker, the battery, and the printed circuit board of FIG. 9B, taken along line A-A', with a current flow and a direction of lines of magnetic force according to an embodiment of the disclosure.
- (14) FIG. 9D is a diagram illustrating current directions in a battery and a printed circuit board according to an embodiment of the disclosure.
- (15) FIG. 9E is a diagram illustrating noise measurement results according to an embodiment of the disclosure.
- (16) FIG. 10A is a diagram illustrating a printed circuit board according to an embodiment of the disclosure.
- (17) FIG. 10B is a front view illustrating a speaker, a battery, and a printed circuit board according to an embodiment of the disclosure.
- (18) FIG. 10C is a cross-sectional view illustrating the speaker, the battery, and the printed circuit board of FIG. 10B, taken along line A-A', with a current flow and a direction of lines of magnetic force according to an embodiment of the disclosure.
- (19) FIG. 10D is a diagram illustrating current directions in a battery and a printed circuit board according to an embodiment of the disclosure.
- (20) FIG. 10E is a diagram illustrating noise measurement results according to an embodiment of the disclosure.

DETAILED DESCRIPTION

- (21) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment of the disclosure.
- (22) Referring to FIG. 1, an electronic device **101** in a network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**). The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform one data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main

processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(23) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(24) The memory **130** may store one data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(25) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(26) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(27) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(28) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(29) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(30) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state.

According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(31) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(32) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(33) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(34) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(35) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(36) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(37) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(38) The wireless communication module **192** may support a 5G network, after a 4G network, and

next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(39) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(40) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or close to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or close to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(41) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(42) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The

electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(43) The electronic device according to an embodiment may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(44) It should be appreciated that an embodiment of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B”, “at least one of A and B”, “at least one of A or B”, “A, B, or C”, “at least one of A, B, and C”, and “at least one of A, B, or C”, may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd”, or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with”, “coupled to”, “connected with”, or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(45) As used in connection with an embodiment of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, logic, logic block, part, or circuitry. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(46) According to an embodiment, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to an embodiment, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to an embodiment, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(47) FIG. 2 is a block diagram **200** illustrating the audio module **170** according to an embodiment.

Referring to FIG. 2, the audio module **170** may include, for example, an audio input interface **210**, an audio input mixer **220**, an analog-to-digital converter (ADC) **230**, an audio signal processor **240**, a digital-to-analog converter (DAC) **250**, an audio output mixer **260**, or an audio output interface **270**.

(48) The audio input interface **210** may receive an audio signal corresponding to a sound obtained from the outside of the electronic device **101** via a microphone (e.g., a dynamic microphone, a condenser microphone, or a piezo microphone) that is configured as part of an input module (e.g., the input module **150** of FIG. 1) or separately from the electronic device **101**. For example, if an audio signal is obtained from an external electronic device (e.g., the electronic device **102** of FIG. 1) (e.g., a headset or a microphone), the audio input interface **210** may be connected with the external electronic device **102** directly via a connecting terminal (e.g., the connecting terminal **178** of FIG. 1), or wirelessly (e.g., Bluetooth™ communication) via a wireless communication module (e.g., the wireless communication module **192**) to receive the audio signal. According to an embodiment, the audio input interface **210** may receive a control signal (e.g., a volume adjustment signal received via an input button) related to the audio signal obtained from the external electronic device **102**. The audio input interface **210** may include a plurality of audio input channels and may receive a different audio signal via a corresponding one of the plurality of audio input channels, respectively. According to an embodiment, additionally or alternatively, the audio input interface **210** may receive an audio signal from another component (e.g., the processor **120** or the memory **130**) of the electronic device **101**.

(49) The audio input mixer **220** may synthesize a plurality of inputted audio signals into at least one audio signal. For example, according to an embodiment, the audio input mixer **220** may synthesize a plurality of analog audio signals inputted via the audio input interface **210** into at least one analog audio signal.

(50) The ADC **230** may convert an analog audio signal into a digital audio signal. For example, according to an embodiment, the ADC **230** may convert an analog audio signal received via the audio input interface **210** or, additionally or alternatively, an analog audio signal synthesized via the audio input mixer **220** into a digital audio signal.

(51) The audio signal processor **240** may perform various processing on a digital audio signal received via the ADC **230** or a digital audio signal received from another component of the electronic device **101**. For example, according to an embodiment, the audio signal processor **240** may perform changing a sampling rate, applying one or more filters, interpolation processing, amplifying or attenuating a whole or partial frequency bandwidth, noise processing (e.g., attenuating noise or echoes), changing channels (e.g., switching between mono and stereo), mixing, or extracting a specified signal for one or more digital audio signals. According to an embodiment, one or more functions of the audio signal processor **240** may be implemented in the form of an equalizer.

(52) The DAC **250** may convert a digital audio signal into an analog audio signal. For example, according to an embodiment, the DAC **250** may convert a digital audio signal processed by the audio signal processor **240** or a digital audio signal obtained from another component (e.g., the processor (**120**) or the memory (**130**)) of the electronic device **101** into an analog audio signal.

(53) The audio output mixer **260** may synthesize a plurality of audio signals, which are to be outputted, into at least one audio signal. For example, according to an embodiment, the audio output mixer **260** may synthesize an analog audio signal converted by the DAC **250** and another analog audio signal (e.g., an analog audio signal received via the audio input interface **210**) into at least one analog audio signal.

(54) The audio output interface **270** may output an analog audio signal converted by the DAC **250** or, additionally or alternatively, an analog audio signal synthesized by the audio output mixer **260** to the outside of the electronic device **101** via the sound output module **155**. The sound output module **155** may include, for example, a speaker, such as a dynamic driver or a balanced armature

driver, or a receiver. According to an embodiment, the sound output module **155** may include a plurality of speakers. For example, the audio output interface **270** may output audio signals having a plurality of different channels (e.g., stereo channels or 5.1 channels) via at least some of the plurality of speakers. According to an embodiment, the audio output interface **270** may be connected with the external electronic device **102** (e.g., an external speaker or a headset) directly via the connecting terminal **178** or wirelessly via the wireless communication module **192** to output an audio signal.

(55) According to an embodiment, the audio module **170** may generate, without separately including the audio input mixer **220** or the audio output mixer **260**, at least one digital audio signal by synthesizing a plurality of digital audio signals using at least one function of the audio signal processor **240**.

(56) According to an embodiment, the audio module **170** may include an audio amplifier (not shown) (e.g., a speaker amplifying circuit) that is capable of amplifying an analog audio signal inputted via the audio input interface **210** or an audio signal that is to be outputted via the audio output interface **270**. According to an embodiment, the audio amplifier may be configured as a module separate from the audio module **170**.

(57) FIG. **3** is a perspective view illustrating an electronic device **300** according to an embodiment.

(58) The electronic device **300** illustrated in FIG. **3** may be the same as or similar to the electronic device **101** illustrated in FIG. **1**. Accordingly, a description of the same components may be avoided.

(59) Referring to FIG. **3**, the electronic device **300** may include a first housing **310** and a second housing **320** connected to (or coupled with) the first housing **310**.

(60) According to an embodiment, the electronic device **300** may correspond to an electronic device wearable on a user's body part (e.g., a user's ear or head). The electronic device **300** may include an in-ear earset, an in-ear headset, or a hearing aid. Besides, the electronic device **200** may include an electronic device in which a speaker is mounted.

(61) In the drawings of the disclosure, a kernel-type in-ear earset mounted on the external auditory meatus leading from the pinna to the eardrum may be described as an example of the electronic device **300**. The disclosure is not limited thereto, and the electronic device **300** may be an open-type earphone mounted on the pinna.

(62) According to an embodiment, the electronic device **300** may be connected to an external electronic device wiredly or wirelessly. In this case, the electronic device **300** may serve as an audio output device that outputs a sound signal generated from the external electronic device to the outside. In an example, the electronic device **300** may serve as an audio input device that receives an audio signal corresponding to a sound obtained from the outside of the external electronic device.

(63) According to an embodiment, the first housing **310** and the second housing **320** may include partial curved surfaces having a specified curvature. In an example, the first housing **310** may extend seamlessly from one end thereof and be connected to the second housing **320**. For example, the first housing **310** and the second housing **320** may be formed to contact each other on an X-Z plane.

(64) According to an embodiment, the first housing **310** or the second housing **320** may be formed of coated or tinted glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), resin (e.g., polycarbonate, polyethylene, polypropylene, or polystyrene), or a combination of at least two of the above materials. In an example, the first housing **310** and the second housing **320** may be formed by injection.

(65) According to an embodiment, the second housing **320** may include a protrusion **321** seated on an ear of a user who uses the electronic device **300**. In an example, the protrusion **321** may be formed to extend in a -Y-axis direction from the second housing **320**.

(66) The electronic device **300** illustrated in FIG. **3** corresponds to one example, not limiting the

shape of a device to which the technical idea of the disclosure is applied. The technical idea of the disclosure is applicable to various types of wearable electronic devices including a protrusion seated on an ear. For example, the technical idea of the disclosure may also be applied to a wearable electronic device in the shape of a kidney bean.

(67) An embodiment will be described below in the context of the electronic device **300** illustrated in FIG. 3, for convenience of description.

(68) FIG. 4 is a cross-sectional view illustrating the electronic device **300**, viewed from a side thereof according to an embodiment. The cross-sectional view of FIG. 4 may be understood as a side cross-sectional view of the electronic device **300** of FIG. 3 viewed from a +Z axis direction.

(69) Referring to FIG. 4, the electronic device **300** may include a speaker **410**, a battery **420**, and a printed circuit board (PCB) **430** (e.g., a printed board assembly (PBA), a flexible PCB (FPCB), or a rigid-flexible PCB (RFPCB)) in an internal space formed by the first housing **310** and the second housing **320**. In an example, the electronic device **300** may include other components in addition to the components illustrated in FIG. 4. For example, the electronic device **300** may further include a wireless communication circuit or a microphone in the internal space formed by the first housing **310** and the second housing **320**. In another example, some of the components of the electronic device **300** illustrated in FIG. 4 may be omitted or replaced with other similar components. For example, the electronic device **300** may be configured such that the protrusion **321** does not protrude outward from the electronic device **300**.

(70) According to an embodiment, the electronic device **300** may include the speaker **410** inside the second housing **320** such that the speaker **420** is close to the protrusion **321**. The speaker **410** may function to receive an electrical signal through a circuit (e.g., the PCB **430**) inside the electronic device **300** and convert the received electrical signal into physical vibrations.

(71) According to an embodiment, the speaker **410** may be disposed in parallel with the battery **420** in the second housing **320**. For example, the speaker **410** may be stacked with the battery along a Y axis. For example, the speaker **410** may be disposed coaxially with the battery **420**.

(72) According to an embodiment, the speaker **410** may include a first surface **411** facing the protrusion **321** (e.g., the -Y-axis direction in FIG. 4), and a second surface **412** opposite to the first surface **411** (e.g., a +Y-axis direction of FIG. 4).

(73) According to an embodiment, the speaker **410** may output a front-radiated sound through the first surface **411** facing the protrusion **321**. The speaker **410** may output a rear-radiated sound through the second surface **412** opposite to the first surface **411**.

(74) According to an embodiment, the battery **420** may be disposed in the internal space of the electronic device **300** formed by coupling between the first housing **310** and the second housing **320**. According to an embodiment, the battery **420** may supply power to at least one component of the electronic device **300**. According to an embodiment, the battery **420** may be a rechargeable secondary cell. In an example, components included in the electronic device **300** may be driven by power output from the battery **420**.

(75) According to an embodiment, the battery **420** may be formed in various shapes. According to an embodiment, the battery **420** may be a small battery to be disposed in a miniaturized wearable electronic device (e.g., the electronic device **300** of FIG. 3). For example, the battery **420** may be a coin-shaped or cylinder-shaped battery.

(76) According to an embodiment, the battery **420** may include a plurality of batteries. For example, the battery **420** may include an inner battery and an outer battery surrounding the inner battery.

(77) According to an embodiment, the battery **420** may include a cathode substrate, an anode substrate, a separator, and an electrolyte. In an example, the cathode substrate and the anode substrate included in the battery **420** may form a winding structure.

(78) According to an embodiment, the battery **420** may be disposed in an area corresponding to the second surface **412** of the speaker **410**. In an example, the battery **420** may be disposed to face the

second surface **412** of the speaker **410**. In an example, the battery **420** may be stacked on the second surface **412** of the speaker **410** (e.g., in the +Y direction in FIG. 4).

(79) According to an embodiment, the battery **420** may include a first surface facing the speaker **410** (e.g., the -Y-axis direction in FIG. 4) and a second surface opposite to the first surface (e.g., the +Y-axis direction in FIG. 4).

(80) According to an embodiment, the PCB **430** may be disposed in the internal space of the electronic device **300** formed by the coupling between the first housing **310** and the second housing **320**. In an example, at least one electronic component (e.g., the communication module **190** or the sensor module **176** of FIG. 1) may be mounted on the PCB **430**.

(81) According to an embodiment, the PCB **430** may include an FPCB.

(82) According to an embodiment, the PCB **430** may be electrically connected to the battery **420** and disposed to surround at least part of a side surface of the battery **420**.

(83) According to an embodiment, a space for accommodating other electronic components in addition to the speaker **410**, the battery **420**, and the PCB **430** may further be formed in the internal space formed by the coupling between the first housing **310** and the second housing **320**. While the speaker **410**, the battery **420**, and the PCB **430** are shown as arranged in parallel in FIG. 4, this arrangement does not necessarily limit the internal shapes of the first housing **310** and the second housing **320** and the arrangement of the components. The detailed arrangement of the components included in the first housing **310** and the second housing **320** may vary according to embodiments.

(84) FIG. 5 is a side view illustrating the speaker **410** and the battery **420** according to an embodiment of the disclosure.

(85) Referring to FIG. 5, an electronic device (e.g., the electronic device **300** of FIG. 4) may include the speaker **410** and the battery **420**. The speaker **410** and the battery **420** illustrated in FIG. 5 may be the same as or similar to the speaker **410** and the battery **420** illustrated in FIG. 4. Therefore, a description of the same components may be avoided. The structure of FIG. 5 may be selectively combined with the structures of FIGS. 3 and 4.

(86) Referring to FIG. 5, according to an embodiment, the speaker **410** and the battery **420** may be disposed close to each other. For example, the speaker **410** and the battery **420** may be stacked. For example, the speaker **410** may be disposed in one direction (the Y-axis direction) of the battery **420**.

(87) According to an embodiment, the speaker **410** may be formed to be substantially circular. The speaker **410** may be formed to be circular with respect to a central axis **410A**.

(88) According to an embodiment, the battery **420** may be formed to be substantially circular. The battery **420** may be formed to be circular with respect to a central axis **420A**.

(89) According to an embodiment, the speaker **410** and the battery **420** may be coaxially disposed. According to an embodiment, the central axis **410A** of the speaker **410** and the central axis **420A** of the battery **420** may be disposed close to each other or coincide with each other.

(90) According to an embodiment, the speaker **410** may receive power directly or indirectly from the battery **420** and convert an electrical signal into wave energy. According to an embodiment, the speaker **410** may be electrically connected directly to the battery **420** and receive power from the battery **420**. According to an embodiment, as the speaker **410** is electrically connected to the PCB **430**, and the PCB **430** is electrically connected to the battery **420**, the speaker **410** may receive power from the battery **420** through the PCB **430**. According to an embodiment, the speaker **410** may be electrically connected to a power management module (e.g., the power management module **188** of FIG. 1) and receive power from the power management module **188**.

(91) FIGS. 6A to 6E are perspective views illustrating an electronic device **500** according to an embodiment of the disclosure. FIG. 7A is a front view illustrating a battery **510** and PCBs **520** and **540** according to an embodiment of the disclosure. FIG. 7B is an exploded perspective view illustrating the battery **510** and the PCBs **520** and **540** according to an embodiment of the disclosure. FIG. 8A is a perspective view and exploded perspective view illustrating the battery **510** according to an embodiment of the disclosure. FIG. 8B is a diagram illustrating an electrode

assembly **516** viewed from above.

(92) Referring to FIGS. **6A** to **8B**, according to an embodiment, the electronic device **500** (e.g., the electronic device **101** of FIG. **1** or the electronic device **300** of FIG. **3**) may include a housing (e.g., the first housing **310** and the second housing **320** of FIGS. **3** and **4**), the battery **510** disposed inside the housing, the PCBs **520** and **540** (e.g., FPCBs or RFPCBs), and a speaker **530** stacked with the battery **510**. For example, the electronic device **500** of FIGS. **6A** to **7B** is the electronic device **300** of FIGS. **3** to **4** from which the housing (e.g., the first housing **310** and the second housing **320** of FIGS. **3** to **4**) is removed.

(93) Referring to FIGS. **6A** to **8B**, the configurations of the electronic device **500**, the battery **510**, the PCBs **520** and **540**, and the speaker **530** of FIGS. **6A** to **8B** may be wholly or partially identical to those of the electronic device **300**, the battery **420**, the PCB **430**, and the speaker **410** of FIGS. **4** and **5**. The structures of FIGS. **6A** to **8B** may be selectively combined with the structures of FIGS. **4** and **5**.

(94) In FIGS. **6A** to **8B**, 'X' may be defined and interpreted as a width direction of the electronic device **500**, 'Y' may be defined and interpreted as a depth direction of the electronic device **500**, and 'Z' may be defined and interpreted as a height direction of the electronic device **500**. In an embodiment of the disclosure, 'X' may mean a (1-1).sup.th direction (+X direction) and a (1-2).sup.th direction (-X direction). In an embodiment of the disclosure, 'Y' may mean a (2-1).sup.th direction (+Y direction) and a (2-2).sup.th direction (-Y direction). In an embodiment of the disclosure, 'Z' may mean a (3-1).sup.th direction (+Z direction) and a (3-2).sup.th direction (-Z direction).

(95) According to an embodiment, referring to FIG. **8A**, the battery **510** may be a coin-type battery. The battery **510** may include an exterior member **518** in the form of a can and/or cup to be coupled, a cover **517** sealing the exterior member **518**, the electrode assembly **516** in a jelly-roll or stack structure, and an electrolyte (not shown) injected into the battery **510**. The electrode assembly **516** may include at least one anode **511**, at least one cathode) **512**, at least one separator **513** disposed between the at least one anode **511** and the at least one cathode **512**, an anode tab **514** connected to an end of the anode **511**, and a cathode tab **515** connected to an end of the cathode **512**.

(96) According to an embodiment, the electrode assembly **516** may be a form in which the anode **511**, the cathode **512**, and the separator **513** are wound sequentially from a central axis, as illustrated in FIG. **8B**.

(97) According to an embodiment, the anode **511** may include an anode substrate, an anode mixture (an anode active material, a conductive material, and a binder) coated on one surface of the anode substrate, and the anode tab **514** attached to the one surface of the anode substrate.

(98) According to an embodiment, the cathode **512** may include a cathode substrate, a cathode mixture (a cathode active material, a conductive material, and a binder) applied to one surface of the cathode substrate, and the cathode tab **515** attached to the one surface of the cathode substrate.

(99) According to an embodiment, the battery **510** may be in the form of a jelly roll formed by winding the anode **511** and the cathode **512** with the separator **513** interposed therebetween. The anode **511**, the cathode **512**, and the separator **513** may be wound in a first direction (e.g., a clockwise direction) or in a second direction (e.g., a counterclockwise direction) opposite to the first direction. The winding directions of the anode **511**, the cathode **512**, and the separator **513** are not limited, and various design modifications may be made according to manufacturing methods.

(100) According to an embodiment, the anode **511** may include an anode substrate and an anode mixture surrounding the anode substrate. For example, the anode substrate may be disposed between a pair of anode mixtures. According to an embodiment, the anode substrate may include aluminum (Al). According to an embodiment, the anode mixture may include a lithium (Li) oxide including a transition metal (e.g., at least one of cobalt (Co), manganese (Mn), or iron (Fe)).

(101) According to an embodiment, the cathode **512** may include a cathode substrate and a cathode mixture surrounding the cathode substrate. For example, the cathode substrate may be disposed

between a pair of cathode mixtures. According to an embodiment, the cathode substrate may include copper (Cu). According to an embodiment, the cathode mixture may include a graphite and/or lithium (Li) titanium (Ti) oxide.

(102) According to an embodiment, the separator **513** may be positioned between the anode **511** and the cathode **512** and configured for insulation. According to an embodiment, the separator **513** may be a non-conductive porous body that may physically separate the anode **511** and the cathode **512** from each other and move a specified material (e.g., Li ions). According to an embodiment, the separator **513** may be a synthetic resin (e.g., polyethylene or polypropylene).

(103) According to an embodiment, the battery **510** may include the anode tab **514** and the cathode tab **515**. According to an embodiment, the anode tab **514** may be electrically connected to the anode **511**, and the cathode tab **515** may be electrically connected to the cathode **512**. For example, the anode tab **514** may be connected to the anode substrate, and the cathode tab **515** may be connected to the cathode substrate.

(104) According to an embodiment, the anode tab **514** and the cathode tab **515** may be located in different directions with respect to the battery **510**. For example, the anode tab **514** may be located in the (3-1).sup.th direction of the battery **510** (e.g., the +Z direction in FIG. **8A**), and the cathode tab **515** may be located in the (3-2).sup.th direction of the battery **510** (e.g., the -Z direction in FIG. **8A**). As the anode tab **514** and the cathode tab **515** are spaced apart from each other, an internal short circuit of the battery **510** and/or a battery (e.g., the battery **420** of FIG. **4**) may be prevented or reduced.

(105) According to an embodiment, referring to FIG. **6A**, an FPCB **520** may be electrically connected to the battery **510** and disposed to surround at least part of a side surface of the battery **510**. For example, a solder of the FPCB **520** may be electrically connected to the cathode tab **515** and the anode tab **514** of the battery **510**. According to an embodiment, a main PCB **540** may be disposed on the battery **510** (e.g., in the +Z direction of FIG. **6A**) and electrically connected to the FPCB **520**.

(106) According to an embodiment, referring to FIGS. **6A** to **6E**, the FPCB **520** may surround at least part of the battery **510**. The FPCB **520** may be disposed to surround at least part of the speaker **530**. For example, the FPCB **520** may surround the battery **510** and the speaker **530** in a third direction (e.g., the Z-axis direction in FIG. **6A**). An end of the FPCB **520** may be connected to the main PCB **540**.

(107) According to an embodiment, the FPCB **520** may include a power wiring **521** VBAT electrically connected to the anode **511** of the battery **510**, a ground wiring **522** GND electrically connected to the cathode **512**, and a signal wiring (not shown).

(108) According to an embodiment, current may flow as follows. Current may flow from the anode **511** of the battery **510** to the power wiring **521** of the FPCB **520** through the anode tab **514** connected to the anode **511**, flow from the power wiring **521** of the FPCB **520** to the ground wiring **522** of the FPCB **520**, and flow to the cathode tab **515** and the cathode **512** of the battery **510** through the ground wiring **522** of the FPCB **520**. For example, current may flow from the anode **511** of the battery **510** to the power wiring **521** of the FPCB **520** through the anode tab **514** connected to the anode **511**, flow from the power wiring **521** of the FPCB **520** to the main PCB **540** (main PBA), and flow from the main PCB **540** (main PBA) to the ground wiring **522** of the FPCB **520**, flow from the ground wiring **522** of the FPCB **520** to a battery protection circuit module integrated circuit (PCM IC), and flow to the cathode tab **515** and the cathode **512** of the battery **510** through the battery PCM IC.

(109) According to an embodiment, the speaker **530** may be disposed close to the battery **510**. For example, the speaker **530** may be stacked with the battery **510**. For example, the speaker **530** may be disposed coaxially with the battery **510**. For example, the central axis of the speaker **530** and the central axis of the battery **510** may be disposed close to each other or coincide with each other. However, the arrangement and position of the speaker **530** is not limited to the above embodiment,

and various design modifications may be made depending on the size or arrangement relationship of surrounding structures.

(110) According to an embodiment, the anode **511** and the cathode **512** of the battery **510** may have different lengths. The length of the anode **511** may be a first length (e.g., a length from the central axis of the battery **510** to the anode tab **514**), and the length of the cathode **512** may be a second length (e.g., a length from the central axis of the battery **510** to the cathode tab **515**) different from the first length. The difference in length between the anode **511** and the cathode **512** may be a third length **l3**. According to an embodiment, the second length may be greater than the first length. The second length may be greater than the first length by the third length **l3**. According to an embodiment, the first length may be greater than the second length. However, the lengths of the anode **511** and the cathode **512** are not limited to those of the above embodiment, and many design modifications may be made according to design methods.

(111) According to an embodiment, a first magnetic field may be formed by the anode **511**, and a second magnetic field may be formed in a direction opposite to a direction of the first magnetic field by the cathode **512**. Since the anode **511** and the cathode **512** are wound overlapping each other, the magnetic fields may be counterbalanced in a section where the anode **511** and the cathode **512** overlap.

(112) According to an embodiment, referring to FIG. **8B**, because the lengths of the anode **511** and the cathode **512** are different, a first current formed to flow in a first winding direction {circle around (1)} may flow in the battery **510** due to the difference in length between the cathode **512** and the anode **511**. A third magnetic field may be formed by the first current. For example, when the second length (not shown) of the cathode **512** is greater than the first length (not shown) of the anode **511**, the third magnetic field may be formed based on a negative current by a longer portion of the cathode **512**. When the first current is the negative current, the first winding direction {circle around (1)} may be opposite to the winding directions of the anode **511**, the cathode **512**, and the separator **513**. For example, when the winding directions of the anode **511**, the cathode **512**, and the separator **513** are clockwise, the first winding direction {circle around (1)} may be counterclockwise. For example, when the winding direction of the battery **510** is counterclockwise, the first winding direction {circle around (1)} may be clockwise.

(113) In general, the third magnetic field generated by the difference in length between the cathode **512** and the anode **511** may affect the nearby speaker **530**. For example, current may be induced in a coil of the speaker **530** included in the speaker **530** by the third magnetic field and affect vibration of a diaphragm of the speaker **530**, thereby generating noise (e.g., an electromagnetic field). For example, periodic noise may occur due to a peak current.

(114) According to an embodiment, a pure iron sheet may be applied between the battery **510** and the speaker **530** to prevent the noise. According to an embodiment, an eccentric design may be applied to the arrangement of the speaker **530** and the battery **510** to prevent the noise.

(115) According to an embodiment, the disclosure may effectively alleviate or remove noise using at least one wiring of the FPCB **520** through which a second current flows, the second current being formed to flow in a second winding direction {circle around (2)} opposite to the first winding direction {circle around (1)} in which the first current flows. This will be described later.

(116) FIGS. **9A** to **10E** illustrate noise test results according to the positions of wirings of the FPCB **520**.

(117) FIG. **9A** is a diagram illustrating the FPCB **520** according to an embodiment of the disclosure. FIG. **9B** is a front view illustrating the speaker **530**, the battery **510**, and the FPCB **520** according to an embodiment of the disclosure. FIG. **9C** is a cross-sectional view illustrating the speaker **530**, the battery **510**, and the FPCB **520** of FIG. **9B**, taken along line A-A' according to an embodiment of the disclosure, with a current flow and directions of lines of magnetic force. FIG. **9D** is a diagram illustrating current directions in the battery **510** and the FPCB **520** according to an embodiment of the disclosure. FIG. **9E** is a diagram illustrating noise measurement results

according to an embodiment of the disclosure.

(118) FIG. 10A is a diagram illustrating the FPCB 520 according to an embodiment of the disclosure. FIG. 10B is a front view illustrating the speaker 530, the battery 510, and the FPCB 520 according to an embodiment of the disclosure. FIG. 10C is a cross-sectional view illustrating the speaker 530, the battery 510, and the FPCB 520 of FIG. 10B, taken along line A-A', with a current flow and directions of lines of magnetic force according to an embodiment of the disclosure. FIG. 10D is a diagram illustrating current directions in the battery 510 and the FPCB 520 according to an embodiment of the disclosure. FIG. 10E is a diagram illustrating noise measurement results according to an embodiment of the disclosure.

(119) Referring to FIGS. 9A to 10E, according to an embodiment, the electronic device 500 (e.g., the electronic device 101 of FIG. 1 or the electronic device 300 of FIGS. 3 and 4) may include a housing (e.g., the first housing 310 and the second housing 320 of FIGS. 3 and 4), the battery 510 disposed inside the housing, and the FPCB 520 (e.g. a PCB or an RFPCB) disposed to surround at least part of a side surface of the battery 510, the speaker 530 stacked with the battery 510, and the main PCB 540 disposed on the battery 510.

(120) Referring to FIGS. 9A to 10E, the configurations of the electronic device 500, the battery 510, the FPCB 520, and the speaker 530 of FIGS. 9A to 10E may be wholly or partially identical to those of the electronic device 500, the battery 510, the FPCB 520, and the speaker 530 of FIGS. 6A to 8B. The structures of FIGS. 10A to 10E may be selectively combined with the structures of FIGS. 6A to 8B.

(121) In FIGS. 9A to 10E, 'X' may be defined and interpreted as a width direction of the electronic device 500, 'Y' may be defined and interpreted as a depth direction of the electronic device 500, and 'Z' may be defined and interpreted as a height direction of the electronic device 500. In an embodiment of the disclosure, 'X' may mean the (1-1).sup.th direction (+X direction) and the (1-2).sup.th direction (-X direction). In an embodiment of the disclosure, 'Y' may mean the (2-1).sup.th direction (+Y direction) and the (2-2).sup.th direction (-Y direction). In an embodiment of the disclosure, 'Z' may mean the (3-1).sup.th direction (+Z direction) and the (3-2).sup.th direction (-Z direction).

(122) According to an embodiment, the first current formed to flow in the first winding direction {circle around (1)} may flow in the battery 510 due to the difference in length between the cathode 512 and the anode 511. The second current formed to flow in the second winding direction {circle around (2)} may flow through the ground wiring 522 of the FPCB 520. A third current formed to flow in a third winding direction {circle around (3)} may flow through the power wiring 521 of the FPCB 520. The second winding direction {circle around (2)} and the third winding direction {circle around (3)} may be opposite to each other. FIGS. 9A to 10E are based on the assumption that the electronic device 500 is mounted on a user's left body.

(123) FIGS. 9A to 10E are based on the assumption that the battery 510 is wound in the clockwise direction, and the first winding direction {circle around (1)} is the counterclockwise direction, like FIG. 8.

(124) According to an embodiment, referring to FIGS. 9A and 9B, the power wiring 521 of the FPCB 520 may be formed as a single thick wiring. The ground wiring 522 may be formed of a plurality of thin wirings. When a position at which the power wiring 521 of the FPCB 520 is disposed is briefly shown on the drawing and the remaining portion is defined as a position at which the ground wiring 522 is disposed, the power wiring 521 may be disposed closer to the speaker 530 than the ground wiring 522.

(125) According to an embodiment, a first area 520a of the FPCB 520 may be an area including a solder directly connected to the battery 510. The solder of the FPCB 520 may be electrically connected to the cathode tab 515 and the anode tab 514 of the battery 510. The first area 520a may be in a shape surrounding at least part of a side surface of the battery 510.

(126) According to an embodiment, a second area 520b of the FPCB 520 may be an area

electrically connected to the main PCB **540**. An end of the second area **520b** may contact the main PCB **540**.

(127) According to an embodiment, a third area **520c** of the FPCB **520** may contact at least part of side surfaces of the battery **510** and the speaker **530**. The wiring arrangement of the third area **520c** may determine the direction of a magnetic field and affect noise generation. According to an embodiment, referring to FIGS. **9A** and **9B**, the power wiring **521** maybe disposed in a downward direction (e.g., the $-Z$ direction in FIG. **9B**), and the ground wiring **522** may be disposed in an upward direction (e.g., the $+Z$ direction in FIG. **9B**) in the third area **520c**. According to an embodiment, referring to FIGS. **10A** and **10B**, the power wiring **521** may be disposed in the upward direction (e.g., the $+Z$ direction of FIG. **9B**), and the ground wiring **522** may be disposed in the downward direction (e.g., $-Z$ direction of FIG. **9B**), in the third area **520c**. Different directions of a magnetic field and different noise according to wiring positions will be described below.

(128) According to an embodiment, the second current flowing through the ground wiring **522** of the FPCB **520** may be flow in an opposite direction to the first current of the battery **510**. The third current flowing through the power wiring **521** of the FPCB **520** may flow in the same direction as the first current of the battery **510** (see FIG. **9D**). For example, when the first winding direction {circle around (1)} is counterclockwise, the second winding direction {circle around (2)} may be clockwise, and the third winding direction {circle around (3)} may be counterclockwise.

(129) According to an embodiment, a current flowing in a wiring disposed closer to the speaker **530** between the power wiring **521** and the ground wiring **522** of the FPCB **520** may be flow in the same direction as the first current of the battery **510**. Referring to FIGS. **9C** and **9D**, the third current flowing through the power wiring **521** disposed closer to the speaker **530** between the power wiring **521** and the ground wiring **522** of the FPCB **520** may be flow in the same direction as the first current of the battery **510**. The second current flowing in the ground wiring **522** disposed further apart from the speaker **530** between the power wiring **521** and the ground wiring **522** of the FPCB **520** may flow in the opposite direction to the first current of the battery **510**. For example, referring to FIGS. **9C** and **9D**, the first winding direction {circle around (1)}, in which the first current flows through the battery **510**, may be counterclockwise, the second winding direction {circle around (2)} of the second current flowing through the ground wiring **522** relatively spaced apart from the speaker **530** may be clockwise, and the third winding direction {circle around (3)} of the third current flowing through the power wiring **521** disposed relatively close to the speaker **530** may be counterclockwise. However, the directions of currents flowing through the battery **510** and the power wiring **521** and the ground wiring **522** of the FPCB **520** are not limited to the above embodiment, and various design modifications may be made by the shape, arrangement relationship, and/or structure of the electronic device **500**.

(130) According to an embodiment, as the power wiring **521** of the FPCB **520** through which a current flows in the same direction as the first current of the battery **510** is disposed closer to the speaker **530**, a magnetic force line **M** of the FPCB **520** may be formed to face, for example, between the $+X$ direction and the $-Z$ direction of FIG. **9C**. The magnetic force line **M** of the FPCB **520** may be the sum of a magnetic force **m1** formed by the power wiring **521** and a magnetic force **m2** formed by the ground wiring **522**. At least part of the magnetic force **m1** formed by the power wiring **521** of the FPCB **520** may penetrate at least part of the speaker **530** in an upward direction **F**. At least part of the magnetic force **m1** formed by the power wiring **521** may penetrate, for example, at least part of the speaker **530** between the $-X$ direction and the $+Z$ direction of FIG. **9C**. As a result, noise may occur.

(131) According to an embodiment, referring to FIG. **9E**, a peak noise level generated by the magnetic field of the FPCB **520** may be -97 dB at 1.6 kHz.

(132) According to an embodiment, referring to FIGS. **10A** and **10B**, when a position at which the power wiring **521** of the FPCB **520** is disposed is briefly shown on the drawing, and the remaining portion is defined as a position at which the ground wiring **522** is disposed, the ground wiring **522**

may be disposed closer to the speaker **530** than the power wiring **521**.

(133) According to an embodiment, a current flowing in a wiring (e.g., the ground wiring **522**) disposed closer to the speaker **530** between the power wiring **521** and the ground wiring **522** of the FPCB **520** may flow in the opposite direction to the first current of the battery **510**. Referring to FIGS. **10C** and **10D**, the second current flowing through the ground wiring **522** disposed closer to the speaker **530** between the power wiring **521** and the ground wiring **522** of the FPCB **520** may flow in the opposite direction to the first current of the battery **510**. The third current flowing in the power wiring **521** disposed further apart from the speaker **530** between the power wiring **521** and the ground wiring **522** of the FPCB **520** may flow in the same direction as the first current of the battery **510**. For example, referring to FIGS. **10C** and **10D**, the first winding direction {circle around (1)}, in which the first current flows through the battery **510**, may be counterclockwise, the second winding direction {circle around (2)} of the second current flowing through the ground wiring **522** disposed relatively close to the speaker **530** may be clockwise, and the third winding direction {circle around (3)} of the third current flowing through the power wiring **521** disposed relatively apart from the speaker **530** may be counterclockwise.

(134) According to an embodiment, as the ground wiring **522** of the FPCB **520** through which a current flows in the opposite direction to the first current of the battery **510** is disposed closer to the speaker **530**, the magnetic force line **M** of the FPCB **520** may be formed to face, for example, between the $-X$ direction and the $-Z$ direction of FIG. **10C**. The magnetic force line **M** of the FPCB **520** may be the sum of the magnetic force **m1** formed by the power wiring **521** and the magnetic force **m2** formed by the ground wiring **522**. Although the magnetic force **m2** formed by the ground wiring **522** of the FPCB **520** may penetrate at least part of the speaker **530**, this may be counterbalanced due to the opposite direction to the third magnetic field formed by the battery **510**. Accordingly, noise may be reduced or canceled.

(135) According to an embodiment, referring to FIG. **10E**, a peak noise level generated by the magnetic field of the FPCB **520** may be -104 dB at 1.6 kHz. It may be noted that a noise value is reduced, compared to noise (FIG. **9E**) in the electronic device **500** according to an embodiment.

(136) It may be noted that when the ground wiring **522** formed to allow the second current to flow therethrough in the second winding direction {circle around (2)} opposite to the first winding direction {circle around (1)} is disposed closer to the speaker **530**, a noise value is reduced compared to the respective embodiments (e.g., FIGS. **9A** to **9E** and FIGS. **10A** to **10E**).

(137) In general, the third magnetic field caused by the difference in length between a cathode (e.g., the cathode **512** of FIG. **8A**) and an anode (e.g., the anode **511** of FIG. **8A**) mounted inside a battery (e.g., the battery **510** of FIG. **6A**) may affect a nearby speaker (e.g., the speaker **530** of FIG. **6A**). For example, a current may be induced in a coil included in the speaker **530** by the third magnetic field and affect vibration of a diaphragm of the speaker **530**, thereby causing noise (e.g., an electromagnetic field). For example, periodic noise may occur due to a peak current.

(138) According to an embodiment of the disclosure, noise may be effectively alleviated or cancelled by disposing at least one wiring of the FPCB **520**, which is formed to allow a current to flow therethrough in an opposite direction to a current flowing in the battery **510** to prevent and/or reduce noise, close to the speaker **530**.

(139) An electronic device (e.g., the electronic device **500** in FIG. **6A**) according to an example embodiment of the disclosure may include: a battery (e.g., the battery **510** in FIG. **8A**) including an anode (e.g., the anode **511** in FIG. **8A**) having a first length and a cathode (e.g., the cathode **512** in FIG. **8A**) having a second length different from the first length; a flexible printed circuit board (e.g., the flexible printed circuit board **520** in FIG. **6A**) electrically connected to the battery and surrounding at least part of a side surface of the battery; and a speaker (e.g., the speaker **530** in FIG. **6A**) stacked with the battery. The flexible printed circuit board may include a power wiring (e.g., the power wiring **521** in FIG. **9A**) electrically connected to the anode and a ground wiring (e.g., the ground wiring **522** in FIG. **9A**) electrically connected to the cathode.

(140) A first current of a first winding direction (e.g., the first winding direction {circle around (1)} in FIG. 10D) generated due to a length difference between the cathode and the anode may flow in the battery. Noise may be canceled and/or reduced by allowing a second current of a second winding direction (e.g., the second winding direction {circle around (2)} in FIG. 10D) opposite to the first winding direction to flow in a wiring disposed closer to the speaker between the power wiring and the ground wiring.

(141) According to an example embodiment, the second length may be greater than the first length.

(142) According to an example embodiment, the battery may include an electrode assembly in a shape of a roll with the anode and the cathode wound therearound.

(143) According to an example embodiment, a winding direction of the electrode assembly may be opposite to the first winding direction.

(144) According to an example embodiment, at least part of a first magnetic field formed in the battery may be counterbalanced by a second magnetic field formed by the second current.

(145) According to an example embodiment, a third current of a third winding direction (e.g., {circle around (3)} in FIG. 10D) identical to the first winding direction may flow in a wiring spaced further apart from the speaker between the power wiring and the ground wiring.

(146) According to an example embodiment, the ground wiring may be disposed closer to the speaker than the power wiring.

(147) According to an example embodiment, the power wiring may be disposed closer to the speaker than the ground wiring.

(148) According to an example embodiment, a central axis of the battery may correspond to a central axis of the speaker.

(149) According to an example embodiment, the electrode assembly may further include an anode tab connected to the anode and a cathode tab connected to the cathode.

(150) According to an example embodiment, the electrode assembly may further include a separator disposed between the anode and the cathode.

(151) An electronic device (e.g., the electronic device in FIG. 6A) according to an example embodiment may include: a battery including an anode having a first length and a cathode having a second length greater than the first length; a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery; and a speaker stacked with the battery.

(152) The flexible printed circuit board may include a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode, a first current of a first winding direction generated due to a length difference between the cathode and the anode may flow in the battery, and a second current of a second winding direction opposite to the first winding direction may flow in the ground wiring disposed closer to the speaker than the power wiring.

(153) According to an example embodiment, the battery may include an electrode assembly in a shape of a roll with the anode and the cathode wound therearound.

(154) According to an example embodiment, a winding direction of the electrode assembly may be opposite to the first winding direction.

(155) According to an example embodiment, at least part of a first magnetic field formed in the battery may be counterbalanced by a second magnetic field formed by the second current.

(156) According to an example embodiment, a third current of a third winding direction identical to the first winding direction may flow in the power wiring.

(157) According to an example embodiment, a central axis of the battery may correspond to a central axis of the speaker.

(158) According to an example embodiment, the electrode assembly may further include an anode tab connected to the anode and a cathode tab connected to the cathode.

(159) According to an example embodiment, the electrode assembly may further include a separator disposed between the anode and the cathode.

(160) An electronic device (e.g., the electronic device **500** in FIG. **6A**) according to an example embodiment of the disclosure may include: a battery including an anode having a first length and a cathode having a second length greater than the first length; a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery; and a speaker stacked with the battery.

(161) The flexible printed circuit board may include a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode, a first current of a first winding direction generated due to a length difference between the cathode and the anode may flow in the battery, and a second current of a second winding direction identical to the first winding direction may flow in the power wiring disposed closer to the speaker than the ground wiring.

(162) The above-described battery (e.g., the battery **510** of FIG. **6A**) and electronic device (e.g., the electronic device **500** of FIG. **6A**) including the same according to various example embodiments of the disclosure are not limited to the foregoing embodiments and drawings, and it will be apparent to those skilled in the art that many replacements, modifications, and changes can be made within the scope of the disclosure.

Claims

1. An electronic device comprising: a battery including an anode having a first length and a cathode having a second length different from the first length; a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery; and a speaker stacked with the battery, wherein the flexible printed circuit board includes a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode, wherein a first current of a first winding direction generated due to a length difference between the cathode and the anode is configured to flow in the battery, and wherein a second current of a second winding direction opposite to the first winding direction is configured to flow in a wiring disposed closer to the speaker between the power wiring and the ground wiring.
2. The electronic device of claim 1, wherein the second length is greater than the first length.
3. The electronic device of claim 1, wherein the battery includes an electrode assembly comprising electrodes in a shape of a roll with the anode and the cathode wound therearound.
4. The electronic device of claim 3, wherein a winding direction of the electrode assembly is opposite to the first winding direction.
5. The electronic device of claim 1, wherein at least part of a first magnetic field formed in the battery is configured to be counterbalanced by a second magnetic field formed by the second current.
6. The electronic device of claim 1, wherein a third current of a third winding direction identical to the first winding direction is configured to flow in a wiring spaced further apart from the speaker between the power wiring and the ground wiring.
7. The electronic device of claim 1, wherein the ground wiring is disposed closer to the speaker than the power wiring.
8. The electronic device of claim 1, wherein the power wiring is disposed closer to the speaker than the ground wiring.
9. The electronic device of claim 1, wherein a central axis of the battery corresponds to a central axis of the speaker.
10. The electronic device of claim 3, wherein the electrode assembly further includes an anode tab connected to the anode and a cathode tab connected to the cathode.
11. The electronic device of claim 3, wherein the electrode assembly further includes a separator disposed between the anode and the cathode.
12. An electronic device comprising: a battery including an anode having a first length and a cathode having a second length greater than the first length; a flexible printed circuit board

electrically connected to the battery and surrounding at least part of a side surface of the battery; and a speaker stacked with the battery, wherein the flexible printed circuit board includes a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode, wherein a first current of a first winding direction generated due to a length difference between the cathode and the anode is configured to flow in the battery, and wherein a second current of a second winding direction opposite to the first winding direction is configured to flow in the ground wiring disposed closer to the speaker than the power wiring.

13. The electronic device of claim 12, wherein the battery includes an electrode assembly comprising electrodes in a shape of a roll with the anode and the cathode wound therearound.

14. The electronic device of claim 13, wherein a winding direction of the electrode assembly is opposite to the first winding direction.

15. The electronic device of claim 12, wherein at least part of a first magnetic field formed in the battery is counterbalanced by a second magnetic field formed by the second current.

16. The electronic device of claim 12, wherein a third current of a third winding direction identical to the first winding direction is configured to flow in the power wiring.

17. The electronic device of claim 12, wherein a central axis of the battery corresponds to a central axis of the speaker.

18. The electronic device of claim 13, wherein the electrode assembly further includes an anode tab connected to the anode and a cathode tab connected to the cathode.

19. The electronic device of claim 13, wherein the electrode assembly further includes a separator disposed between the anode and the cathode.

20. An electronic device, comprising: a battery including an anode having a first length and a cathode having a second length greater than the first length; a flexible printed circuit board electrically connected to the battery and surrounding at least part of a side surface of the battery; and a speaker stacked with the battery, wherein the flexible printed circuit board includes a power wiring electrically connected to the anode and a ground wiring electrically connected to the cathode, wherein a first current of a first winding direction generated due to a length difference between the cathode and the anode is configured to flow in the battery, and wherein a second current of a second winding direction identical to the first winding direction is configured to flow in the power wiring disposed closer to the speaker than the ground wiring.
