

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402045
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lee; Hoyeon et al.

Device and method for processing service policy in wireless communication system

Abstract

The present disclosure relates to a 5th (5G) generation or pre-5G communication system for supporting a higher data transmission rate beyond a 4th (4G) generation communication system such as long term evolution (LTE). The present disclosure is to process policy and parameter information for providing a service in a wireless communication system, and an operating method of a base station may include obtaining mapping information of service quality related to direct communication between a first system and a second system, and switching between the quality of service of the first system and the quality of service of the second system using the mapping information.

Inventors:	Lee; Hoyeon (Suwon-si, KR), Kim; Sunghoon (Suwon-si, KR)
Applicant:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Family ID:	1000008778398
Assignee:	Samsung Electronics Co., Ltd. (Suwon-si, KR)
Appl. No.:	17/594100
Filed (or PCT Filed):	April 02, 2020
PCT No.:	PCT/KR2020/004533
PCT Pub. No.:	WO2020/204641
PCT Pub. Date:	October 08, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220159527 A1	May. 19, 2022

Foreign Application Priority Data

KR	10-2019-0038279	Apr. 02, 2019
KR	10-2020-0019909	Feb. 18, 2020

Publication Classification

Int. Cl.: H04W76/14 (20180101); H04W4/40 (20180101); H04W4/50 (20180101); H04W8/22 (20090101); H04W28/02 (20090101); H04W28/24 (20090101); H04W36/00 (20090101); H04W88/06 (20090101)

U.S. Cl.:

CPC H04W36/0066 (20130101); H04W4/40 (20180201); H04W4/50 (20180201); H04W8/22 (20130101); H04W28/0268 (20130101); H04W28/24 (20130101); H04W36/037 (20230501); H04W76/14 (20180201); H04W88/06 (20130101)

Field of Classification Search

CPC: H04W (36/0066); H04W (4/40); H04W (4/50); H04W (8/22); H04W (28/0268); H04W (28/24); H04W (76/14); H04W (88/06); H04W (12/08); H04W (12/60); H04W (36/037); H04W (60/04); H04W (8/24); H04W (92/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9826564	12/2016	Kweon	N/A	H04L 67/12
10827409	12/2019	Kim et al.	N/A	N/A
10880710	12/2019	Baek et al.	N/A	N/A
2012/0014281	12/2011	Chun et al.	N/A	N/A
2016/0374134	12/2015	Kweon	N/A	H04W 4/70
2018/0352448	12/2017	Ryu et al.	N/A	N/A
2019/0037448	12/2018	Shan	N/A	H04W 60/04
2019/0394625	12/2018	Kim et al.	N/A	N/A
2020/0100088	12/2019	Kim et al.	N/A	N/A
2020/0112850	12/2019	Lee et al.	N/A	N/A
2020/0137711	12/2019	Cho	N/A	H04W 8/06
2022/0095260	12/2021	Shan	N/A	H04W 60/04
2022/0159527	12/2021	Lee	N/A	H04W 8/24

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108029009	12/2017	CN	N/A
108476394	12/2017	CN	N/A
10-2020-0039306	12/2019	KR	N/A
2018117774	12/2017	WO	N/A
2018128505	12/2017	WO	N/A

OTHER PUBLICATIONS

Supplementary European Search Report dated Aug. 12, 2022 in connection with European Patent Application No. 20 78 2745, 19 pages. cited by applicant

International Search Report and Written Opinion of the International Searching Authority dated Jul. 17, 2020 in connection with International Application No. PCT/KR2020/004533, 12 pages. cited by applicant

LG Electronics, "Update of Solution#6," S2-186587 (revision of S2-18xxxx), SA WG2 Meeting #128, Vilnius, Lithuania, Jul. 2-6, 2018, 7 pages. cited by applicant

Tencent, "QoS Handling for V2X communication over PC5 reference point," S2-1900074 (Revision of S2-19xxxx), 3GPP TSG-SA WG2 Meeting #130, Kochi, India, Jan. 21-25, 2019, 2 pages. cited by applicant

ZTE, et al., "Considerations on NR V2X," R3-186422, 3GPP TSG RAN WG3 Meeting #102, Spokane, USA, Nov. 12-16, 2018, 3 pages. cited by applicant

ETSI TS 123 285 V16.3.0 (Jul. 2020), Universal Mobile Telecommunications System (UMTS); LTE; Architecture enhancements for V2X services (3GPP TS 23.285 version 16.3.0 Release 16), Jul. 2020, 40 pages. cited by applicant

Supplementary Partial European Search Report dated May 9, 2022, in connection with European Application No. 20782745.2, 21 pages. cited by applicant

3GPP TR 23.786 V16.0.0 (Mar. 2019), Technical Report, 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Study on architecture enhancements for the Evolved Packet System (EPS) and the 5G System (5GS) to support advanced V2X services (Release 16), Mar. 2019, 37 pages. cited by applicant

3GPP TS 23.285 V16.0.0 (Mar. 2019), Technical Specification, 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Architecture enhancements for V2X services (Release 16), Mar. 2019, 37 pages. cited by applicant

Intel, "Update on Functional Entities description," S2-1901886 (revision of S2-190xxxx), SA WG2 Meeting #131, Santa Cruz, Tenerife, Spain, Feb. 25-Mar. 2019, 2 pages. cited by applicant

Communication pursuant to Article 94(3) EPC dated Jul. 18, 2024, in connection with European Application No. 20782745.2, 13 pages. cited by applicant

LG Electronics, "Conclusion of KI#13," S2-1811965 (revision of S2-18xxxx), SA WG2 Meeting #129bis, West Palm Beach, USA, Nov. 26-30, 2018, 3 pages. cited by applicant

Notification of The First Office Action issued Dec. 25, 2024, in connection with Chinese Patent Application No. 202080027413.2, 21 pages. cited by applicant

Vice-Chair (InterDigital), "Report of the LTE break-out session (ProSe and eDRX)," R2-153885, 3GPP TSG RAN WG2 #91, Beijing, China, Aug. 24-28, 2015, 21 pages. cited by applicant

Notice of Preliminary Rejection dated Jul. 4, 2025, in connection with Korean Application No. 10-2020-0019909, 14 pages. cited by applicant

"3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Procedures for the 5G System; Stage 2; (release 16)", 3GPP TS 23.502 V16.0.1, Apr. 2019, 420 pages. cited by applicant

Primary Examiner: Perez; Julio R

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a 371 National Stage of International Application No. PCT/KR2020/004533, filed on Apr. 2, 2020, which claims priority to Korean Patent Application No. 10-2019-0038279,

filed Apr. 2, 2019, and Korean Patent Application No. 10-2020-0019909, filed Feb. 18, 2020, the disclosures of which are herein incorporated by reference in their entirety.

BACKGROUND

1. Field

(2) The present disclosure generally relates to a wireless communication system, and more specifically, to an apparatus and a method for processing policy and parameter information for providing a service in the wireless communication system.

2. Description of Related Art

(3) To satisfy a wireless data traffic demand which is growing after a 4th generation (4G) communication system is commercialized, efforts are exerted to develop an advanced 5th generation (5G) communication system or a pre-5G communication system. For this reason, the 5G communication system or the pre-5G communication system is referred to as a beyond 4G network communication system or a post long term evolution (LTE) system.

(4) To achieve a high data rate, the 5G communication system considers its realization in an extremely high frequency (mmWave) band (e.g., 60 GHz band). To mitigate a path loss of propagation and to extend a propagation distance in the extremely high frequency band, the 5G communication system is discussing beamforming, massive multiple input multiple output (MIMO), full dimensional (FD)-MIMO, array antenna, analog beam-forming, and large scale antenna techniques.

(5) Also, for network enhancement of the system, the 5G communication system is developing techniques such as evolved small cell, advanced small cell, cloud radio access network (RAN), ultra-dense network, device to device (D2D) communication, wireless backhaul, moving network, cooperative communication, coordinated multi-points (CoMP), and receive interference cancellation. Besides, the 5G system is developing hybrid frequency shift keying and quadrature amplitude modulation (FQAM) and sliding window superposition coding (SWSC) as advanced coding modulation (ACM) schemes, and filter bank multi carrier (FBMC), non orthogonal multiple access (NOMA), and sparse code multiple access (SCMA) as advanced access technologies.

(6) The 5G system is considering supporting various services compared to the existing 4G system. For example, the most representative services are enhanced mobile broad band (eMBB), ultra-reliable and low latency communication (URLLC), massive machine type communication (mMTC), evolved multimedia broadcast/multicast service (eMBMS), and so on. A system providing the URLLC service may be referred to as a URLLC system, and a system providing the eMBB service may be referred to as an eMBB system. Herein, the terms service and system may be used interchangeably.

(7) Meanwhile, the Internet is evolving from a human-centered connection network in which humans create and consume information, to an Internet of things (IoT) network which exchanges and processes information between distributed components such as objects. Internet of everything (IoE) technology which combines IoT technology with big data processing technology through connection with a cloud server is also emerging. To implement the IoT, technology elements such as sensing technology, wired and wireless communication and network infrastructure, service interface technology, and security technology are required, and techniques such as a sensor network for connection between objects, machine to machine (M2M), and machine type communication (MTC) are recently studied. The IoT environment may provide intelligent internet technology (IT) service which creates a new value in human life by collecting and analyzing data generated from the connected objects. The IoT may be applied to fields such as a smart home, a smart building, a smart city, a smart car or a connected car, a smart grid, health care, smart home appliances, and advanced medical services through convergence and composition between the existing IT and various industries.

(8) Hence, various attempts for applying the 5G communication system to the IoT network are being made. For example, the technologies such as sensor network, M2M, and MTC are

implemented by schemes such as beamforming, MIMO, and array antenna which are the 5G communication technologies. Applying a cloud radio access network (RAN) as the big data processing technology as aforementioned may be said to be an example of the convergence of the 5G technology and the IoT technology.

(9) Vehicle to everything (V2X) is a general term which refers to all kinds of the communication scheme applicable to a road vehicle, and various additional services are available besides an initial safety use case in combination with the wireless communication technology development. A wireless access in vehicular environments (WAVE) standard based on institute of electrical and electronic engineers (IEEE) 802.11p and IEEE P1609 is standardized as V2X service provision technology. However, the WAVE which is a kind of dedicated short range communication (DSRC) technology has limitation in that a message transmission distance between a vehicle and a vehicle is limited.

(10) To overcome this limitation, 3rd generation partnership project (3GPP) is working on a cellular-based V2X technology standard. Release 14/Release 15 has completed LTE-based evolved packet system (EPS) V2X standard, and Release 16 is working on new radio (NR)-based 5th generation system (5G) V2X standardization.

SUMMARY

(11) Based on the discussions described above, the present disclosure provides an apparatus and a method for effectively processing policy and parameter information for providing a service in a wireless communication system.

(12) In addition, the present disclosure provides an apparatus and a method for providing mapping information of quality of service (QoS) parameters for direct communication in a wireless communication system.

(13) In addition, the present disclosure provides an apparatus and a method for switching QoS parameters for direct communication in a wireless communication system.

(14) According to various embodiments of the present disclosure, an operating method of a base station in a wireless communication system may include obtaining mapping information of service quality related to direct communication between a first system and a second system, and switching between the quality of service of the first system and the quality of service of the second system using the mapping information.

(15) According to various embodiments of the present disclosure, an operating method of a terminal in a wireless communication system in a wireless communication system may include obtaining mapping information of service quality related to direct communication between a first system and a second system, and switching between the quality of service of the first system and the quality of service of the second system using the mapping information.

(16) According to various embodiments of the present disclosure, a base station apparatus in a wireless communication system may include at least one transceiver, and at least one processor connected to the at least one transceiver, and the at least one processor may control to obtain mapping information of quality of service related to direct communication between a first system and a second system, and to switch between the quality of service of the first system and the quality of service of the second system using the mapping information.

(17) According to various embodiments of the present disclosure, a terminal apparatus in a wireless communication system may include a transceiver and at least one processor connected to the transceiver, and the at least one processor may control to obtain mapping information of quality of service related to direct communication between a first system and a second system, and to switch between the quality of service of the first system and the quality of service of the second system using the mapping information.

(18) An apparatus and a method according to various embodiments of the present disclosure, may effectively operate direct communication between different systems, by using information of service quality mapping information related to direct communication between a first system and a

second system.

(19) Effects obtainable from the present disclosure are not limited to the above-mentioned effects, and other effects which are not mentioned may be clearly understood by those skilled in the art of the present disclosure through the following descriptions.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a structure of a first communication system according to an embodiment of the present disclosure.

(2) FIG. 2 illustrates a structure of a second communication system according to an embodiment of the present disclosure.

(3) FIG. 3 illustrates an interworking structure between communication systems according to an embodiment of the present disclosure.

(4) FIG. 4 illustrates a configuration of a network entity in a wireless communication system according to an embodiment of the present disclosure.

(5) FIG. 5 illustrates a configuration of a terminal in a wireless communication system according to an embodiment of the present disclosure.

(6) FIG. 6 illustrates a flowchart for using mapping information of service quality in a wireless communication system according to an embodiment of the present disclosure.

(7) FIG. 7 illustrates a flowchart for providing mapping information of service quality in a wireless communication system according to an embodiment of the present disclosure.

(8) FIG. 8A illustrates a procedure for a base station to obtain service policy/parameter information from a network of a first communication system during an initial registration process in a wireless communication system according to an embodiment of the present disclosure.

(9) FIG. 8B illustrates a procedure for a terminal to obtain the service policy and parameter information from the network of the first communication system in the wireless communication system according to an embodiment of the present disclosure.

(10) FIG. 9A illustrates a procedure for a terminal and a base station to obtain service policy/parameter information from a network of a second communication system during an initial registration process in a wireless communication system according to an embodiment of the present disclosure.

(11) FIG. 9B illustrates a procedure for the terminal to obtain the service policy/parameter information from the network at a network request from the second communication system in the wireless communication system according to an embodiment of the present disclosure.

(12) FIG. 9C illustrates a procedure for the terminal to obtain the service policy/parameter information from the network of the second communication system at a terminal request in the wireless communication system according to an embodiment of the present disclosure.

(13) FIG. 10 illustrates a procedure for a terminal to request and obtain a radio resource for direct communication from a network entity of a second communication system in a wireless communication system according to an embodiment of the present disclosure.

(14) FIG. 11 illustrates a procedure for a terminal to request and obtain a radio resource for direct communication from a network entity of a first communication system in a wireless communication system according to an embodiment of the present disclosure.

(15) FIG. 12 illustrates a procedure for establishing connection between a base station and a second communication system in a wireless communication system according to an embodiment of the present disclosure.

(16) FIG. 13 illustrates a procedure for establishing connection between a base station and a first communication system in a wireless communication system according to an embodiment of the

present disclosure.

(17) FIG. 14A illustrates a procedure for a terminal to obtain system information from a network in a wireless communication system according to an embodiment of the present disclosure.

(18) FIG. 14B illustrates another procedure for the terminal to obtain the system information from the network in the wireless communication system according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

(19) Terms used in the present disclosure are used for describing particular embodiments, and are not intended to limit the scope of other embodiments. A singular form may include a plurality of forms unless it is explicitly differently represented. All the terms used herein, including technical and scientific terms, may have the same meanings as terms generally understood by those skilled in the art to which the present disclosure pertains. The terms defined in a general dictionary among terms used in the present disclosure may be interpreted to have the same or similar meanings with the context of the relevant art, and, unless explicitly defined in this disclosure, it shall not be interpreted ideally or excessively as formal meanings. In some cases, even terms defined in this disclosure should not be interpreted to exclude the embodiments of the present disclosure.

(20) In various embodiments of the present disclosure to be described below, a hardware approach is described as an example. However, since the various embodiments of the present disclosure include a technology using both hardware and software, the various embodiments of the present disclosure do not exclude a software-based approach.

(21) Hereinafter, the present disclosure relates to an apparatus and a method for processing policy and parameter information for providing a service in a wireless communication system.

Particularly, the present disclosure describes a technique for switching between parameters for direct communication (e.g., PC5 communication, proximity service (ProSe), sidelink communication, vehicle to everything (V2X) communication) between user equipments (UEs) in the wireless communication system.

(22) Terms for identifying access nodes, terms indicating network entities, terms indicating messages, terms indicating interfaces between network entities, and terms indicating various identification information, which are used in the following descriptions, are for the sake of explanations. Accordingly, the present disclosure is not limited to the terms to be described, and may use other terms referring to a subject having technically identical meaning.

(23) To ease the following description, the present disclosure describes various embodiments using terms and names defined in specifications for an evolved packet system (EPS) system and a 5th generation (5G) system, which is illustrations for explanations. Various embodiments of the present disclosure may be easily modified and applied to other communication system.

(24) In describing the embodiments of the present disclosure in detail, a communication standard defined by 3rd Generation Partnership Project (3GPP) shall be mainly targeted, but the main subject of the present disclosure may be applied to other communication system having similar technical background with slight modification within a range not significantly departing from the scope of the present disclosure, which will be determined by those having technical background skilled in the technical field of the present disclosure.

(25) In describing the embodiments of the present disclosure in detail, a vehicle communication service will be mainly targeted, but the main subject of the present disclosure may be applied to other services provided in the EPS network or the 5G network with slight modifications within a range not significantly departing from the scope of the present disclosure, which will be determined by those having technical background skilled in the technical field of the present disclosure.

(26) FIG. 1 illustrates a structure of a first communication system according to an embodiment of the present disclosure. According to an embodiment, the first communication system illustrated in FIG. 1 may be a mobile communication system based on a long term evolution (LTE) standard.

(27) Referring to FIG. 1, the first communication system includes an evolved node B (eNB) 120, a

mobility management entity (MME) **125**, a serving/packet data network-gateway (S/P-GW) **130**, a home subscription server (HSS) **135**, a V2X control function (CF) **140**, and a V2X application server (AS) **145**. The S/P-GW **130** may be divided into a serving-gateway (S-GW) and a packet data network-gateway (P-GW). The eNB **120** may be referred to as a ‘base station’, an ‘evolved-universal mobile telecommunication system terrestrial radio access network (E-UTRAN)’, a ‘radio access network (RAN) node’ or other term having an equivalent technical meaning.

(28) A user equipment (UE) **110a**, **110b**, **110c**, or **110d** accesses an external network through the eNB **120** and the S/P-GW **130**. It is necessary to generate packet data network (PDN) connection for the UE **110a**, **110b**, **110c** or **110d** to transmit and receive data through the S/P-GW **130**, and one PDN connection may include one or more EPS bearers. The UE **110a**, **110b**, **110c** or **110d** may be referred to as a ‘terminal’, a ‘mobile station’, a ‘subscriber station’, a ‘remote terminal’, a ‘wireless terminal’, or a ‘user device’ or other term having an equivalent technical meaning. For the sake of descriptions below, the present disclosure describes embodiments using the UE **110a** among the UEs **110a**, **110b**, **110c**, or **110d**, and the other UEs **110b**, **110c**, and **110d** may operate similarly.

(29) An application function (AF) is a device which exchanges information related to an application at an application level with a user. The V2X AS **145** is a device for providing an application-level V2X service. The V2X AS **145** may include an AF function.

(30) The eNB **120** is an RAN node and corresponds to a radio network controller (RNC) of a UTRAN system and a base station controller (BSC) of a global system for mobile communications (GSM) enhanced data rates for GSM evolution (EDGE) RAN (GERAN) system. The eNB **120** is connected with the UE **110a** over a radio channel, and performs a similar role to the existing RNC/BSC.

(31) In the LTE, every user traffic including a real-time service such as voice over Internet protocol (VoIP) over the Internet protocol is serviced over a shared channel. Accordingly, a device for collecting and scheduling context information of the UE **110a** is required, and the eNB **120** may serve as a scheduler.

(32) The S/P-GW **130** is a device which provides a data bearer, and generates or removes the data bearer under control of the MME **125**. The MME **125** is a device which manages various control functions, and one MME **125** may be connected to a plurality of eNBs including the eNB **120**.

(33) The HSS **135** is a device which stores and manages subscription information of the UEs including the UE **110a**. The subscription information may be referred to as ‘UE subscription information’ or ‘terminal subscription information’. In addition, the HSS **135** may store subscription information for providing the V2X service. <Table 1> is an example of the V2X service related subscription information managed by the HSS **135**.

(34) TABLE-US-00001 TABLE 1 a) whether the UE is authorized to perform V2X communication over PC5 reference point as Vehicle UE, Pedestrian UE, or both. b) UE-PC5-AMBR for V2X communication over PC5 reference point, including UE- PC5-AMBR for LTE PC5. c) UE-PC5-AMBR for V2X communication over PC5 reference point, including UE- PC5-AMBR for NR PC5. d) the list of the PLMNs where the UE is authorized to perform V2X communication over PC5 reference point. e) cross-RAT PC5 control authorization.

(35) The V2X CF **140** is a device which manages service policy and parameter information to provide the V2X service. <Table 2> and <Table 3> show examples of the V2X service policy and parameter information managed by the V2X CF **140**. The UE **110a** may establish a PDN connection with the V2X CF **140** through the eNB **120** and the S/P-GW **130** through a procedure shown in FIG. 8A, that is, after completing registration in the network, and obtain V2X service policy and parameter information from the V2X CF **140**. Alternatively, the V2X service policy and parameter information shown in <Table 2> or <Table 3> may be pre-configured in the UE **110a**, and the UE **110a** may use the pre-configured information. <Table 2> is the example of V2X service policy and parameters for direct communication (e.g., ProSe).

(36) TABLE-US-00002 TABLE 2 1) Authorization policy: When the UE is “served by E-UTRA”

or “served by NR”: PLMNs in which the UE is authorized to perform V2X communications over PC5 reference point when “served by E-UTRA” or “served by NR”. For each above PLMN: RAT(s) over which the UE is authorized to perform V2X communications over PC5 reference point. When the UE is “not served by E-UTRA” and “not served by NR”: Indicates whether the UE is authorized to perform V2X communications over PC5 reference point when “not served by E-UTRA” and “not served by NR”. RAT(s) over which the UE is authorized to perform V2X communications over PC5 reference point. 2) Radio parameters when the UE is “not served by E-UTRA” and “not served by NR”: Includes the radio parameters per PC5 RAT (i.e. LTE PC5, NR PC5) with Geographical Area(s) and an indication of whether they are “operator managed” or “non-operator managed”. The UE uses the radio parameters to perform V2X communications over PC5 reference point when “not served by E-UTRA” and “not served by NR” only if the UE can reliably locate itself in the corresponding Geographical Area. Otherwise, the UE is not authorized to transmit. NOTE: Whether a frequency band is “operator managed” or “non-operator managed” in a given Geographical Area is defined by local regulations. 3) Policy/parameters per RAT for PC5 Tx Profile selection: The mapping of service types (e.g. PSID or ITS-AIDs) to Tx Profiles. 4) Policy/parameters related to privacy: The list of V2X services, e.g. PSID or ITS-AIDs of the V2X applications, with Geographical Area(s) that require privacy support. 5) Policy/parameters when LTE PC5 is selected: The mapping of Destination Layer-2 ID(s) and the V2X services, e.g. PSID or ITS-AIDs of the V2X application. NOTE 2: PLMN operators coordinate to make sure Destination Layer-2 ID(s) for different V2X services are configured in a consistent manner. NOTE 3: To pre-configure a UE with the provisioning parameters, at least the “not served by E-UTRAN” parameters of 1) and 2), and the parameters of 3) need to be included. The mapping of ProSe Per-Packet Priority and packet delay budget for V2X communication (autonomous resources selection mode). The mapping of service types (e.g. PSID or ITS-AIDs) to V2X frequencies (see TS 36.300 [10] for further information) with Geographical Area(s). The list of V2X services, e.g. PSID or ITS-AIDs of the V2X applications, allowed to use a specific PPPR value. 6) Policy/parameters when NR PC5 is selected: The mapping of service types (e.g. PSID or ITS-AIDs) to V2X frequencies with Geographical Area(s). The destination Layer-2 ID for PC5 unicast link establishment. The list of V2X services that are allowed to use a specific 5QI 7) Policy/parameters related to QoS: The mapping of PPPP and 5QI. The mapping of PPPR and 5QI.

(37) In describing the embodiments of the present disclosure, QoS related parameters defined in the 5G system may be referred to as ‘5G quality of service indicator (5QI)’ or ‘PC5 5QI (PQI)’, and 5QI’ and ‘PQI’ may be used interchangeably. <Table 3> is the example of V2X service policy and parameters for network communication (e.g., Uu communication).

(38) TABLE-US-00003 TABLE 3 1) PLMNs in which the UE is authorized to use MBMS based V2X communication. Corresponding V2X USD(s) for receiving MBMS based V2X traffic in the PLMN. The V2X USD(s) may be obtained through the V2 reference point from the V2X Application Server. NOTE: The V2 reference point procedure is not specified in this Release. 2) V2X Application Server address information. List of FQDNs or IP addresses of the V2X Application Servers, associated with served geographical area information and list of PLMNs that the configuration applies to. 3) V2X Application Server discovery using MBMS. List of PLMNs and corresponding V2X Server USDs for receiving V2X Application Server information via MBMS. 4) Mapping of the V2X services, e.g. PSID or ITS-AIDs of the V2X application to: V2X Application Server address (consisting of IP address/FQDN and UDP port) for unicast, - V2X USD for MBMS.

(39) To provide the LTE PC5 communication, a quality of service (QoS) model based on ProSe per packet priority (PPPP)/ProSe per packet reliability (PPPR) may be used. The QoS parameters for the LTE PC5 communication may include PPPP and PPPR. The PPPP may include a value indicating a priority level. For example, the PPPP may be expressed as a value ranging from ‘1’ to ‘8’. If the PPPP is ‘1’, it may be determined that its priority is higher than the PPPP which is ‘2’.

The PPPR may include a value indicating a reliability level. For example, the PPPR may be expressed as a value ranging from ‘1’ to ‘8’. If the PPPR is ‘1’, it may be determined that higher reliability is required than the PPPR which is ‘2’.

(40) To provide new radio (NR) PC5 communication, a QoS model based on the PQI may be used. A QoS parameter for the NR PC5 communication, i.e., the PQI may include at least one of a priority level, a packet delay budget, a packet error rate, an averaging window, and a maximum data burst volume. In addition, to provide the NR PC5 communication, a communication range value may be used together with the PQI. The following <Table 4> shows an example of the PQI. <Table 4> is the example of the 5QI value defined in the 3GPP standard.

(41) TABLE-US-00004 TABLE 4 Default Maximum Data Default Packet Burst Default 5QI Resource Priority Packet Delay Error Volume Averaging Value Type Level Budget Rate (NOTE 2) Window Example Services 1 GBR 20 100 ms 10.sup.-2 N/A 2000 ms Conversational Voice (NOTE 11, NOTE 13) 2 (NOTE 1) 40 150 ms 10.sup.-3 N/A 2000 ms Conversational Video (NOTE 11, (Live Streaming) NOTE 13) 3 30 50 ms 10.sup.-3 N/A 2000 ms Real Time Gaming, (NOTE 14) (NOTE 11, V2X messages NOTE 13) Electricity distribution - medium voltage, Process automation - monitoring 4 50 300 ms 10.sup.-6 N/A 2000 ms Non-Conversational (NOTE 11, Video (Buffered NOTE 13) Streaming) 65 7 75 ms 10.sup.-2 N/A 2000 ms Mission Critical user (NOTE 9, (NOTE 7, plane Push To Talk NOTE 12) NOTE 8) voice (e g., MCPTT) 66 20 100 ms 10.sup.-2 N/A 2000 ms Non-Mission-Critical (NOTE 12) (NOTE 10, user plane Push To NOTE 13) Talk voice 67 15 100 ms 10.sup.-3 N/A 2000 ms Mission Critical Video (NOTE 12) (NOTE 10, user plane NOTE 13) 75 (NOTE 14) 5 Non-GBR 10 100 ms 10.sup.-6 N/A N/A IMS Signalling NOTE 10, NOTE 13) 6 (NOTE 1) 60 300 ms 10.sup.-6 N/A N/A Video (Buffered (NOTE 10, Streaming)TCP-based NOTE 13) (e.g., www, e-mail, chat, ftp, p2p file sharing, progressive video, etc.) 7 70 100 ms 10.sup.-3 N/A N/A Voice, Video (Live (NOTE 10, Streaming)Interactive NOTE 13) Gaming 8 80 300 ms 10.sup.-6 N/A N/A Video (Buffered (NOTE 13) Streaming)TCP-based (e.g., www, e-mail, chat, ftp, p2p file sharing, progressive 9 90 video, etc.) 69 5 60 ms 10.sup.-6 N/A N/A Mission Critical delay (NOTE 9, (NOTE 7, sensitive signalling NOTE 12) NOTE 8) (e.g., MC-PTT signalling) 70 55 200 ms 10.sup.-6 N/A N/A Mission Critical Data (NOTE 12) (NOTE 7, (e.g. example services NOTE 10) are the same as 5QI 6/8/9) 79 65 50 ms 10.sup.-2 N/A N/A V2X messages (NOTE 10, NOTE 13) 80 68 10 ms 10.sup.-6 N/A N/A Low Latency eMBB (NOTE 5, applications NOTE 10) Augmented Reality 82 Delay 19 10 ms 10.sup.-4 255 2000 ms Discrete Automation Critical (NOTE 4) bytes (see TS 22.261 [2]) GBR 83 22 10 ms 10.sup.-4 1354 2000 ms Discrete Automation (NOTE 4) bytes (see TS 22.261 [2]) (NOTE 3) 84 24 30 ms 10.sup.-5 1354 2000 ms Intelligent transport (NOTE 6) bytes systems (see (NOTE 3) TS 22.261 [2]) 85 21 5 ms 10.sup.-5 255 2000 ms Electricity (NOTE 5) bytes Distribution- high voltage (see TS 22.261 [2]) NOTE 1: A packet which is delayed more than PDB is not counted as lost, thus not included in the PER. NOTE 2: It is required that default MDBV is supported by a PLMN supporting the related 5QIs. NOTE 3: This MDBV value is set to 1354 bytes to avoid IP fragmentation for the IPv6 based, IPsec protected GTP tunnel to the 5G-AN node (the value is calculated as in Annex C of TS 23.060 [56] and further reduced by 4 bytes to allow for the usage of a GTP-U extension header). NOTE 4: A delay of 1 ms for the delay between a UPF terminating N6 and a 5G-AN should be subtracted from a given PDB to derive the packet delay budget that applies to the radio interface. NOTE 5: A delay of 2 ms for the delay between a UPF terminating N6 and a 5G-AN should be subtracted from a given PDB to derive the packet delay budget that applies to the radio interface. NOTE 6: A delay of 5 ms for the delay between a UPF terminating N6 and a 5G-AN should be subtracted from a given PDB to derive the packet delay budget that applies to the radio interface. NOTE 7: For Mission Critical services, it may be assumed that the UPF terminating N6 is located “close” to the 5G-AN (roughly 10 ms) and is not normally used in a long distance, home routed roaming situation. Hence delay of 10 ms for the delay between a UPF terminating N6 and a 5G-AN should be subtracted from this PDB to

derive the packet delay budget that applies to the radio interface. NOTE 8: In both RRC Idle and RRC Connected mode, the PDB requirement for these 5QIs can be relaxed (but not to a value greater than 320 ms) for the first packet(s) in a downlink data or signalling burst in order to permit reasonable battery saving (DRX) techniques. NOTE 9: It is expected that 5QI-65 and 5QI-69 are used together to provide Mission Critical Push to Talk service (e.g., 5QI-5 is not used for signalling). It is expected that the amount of traffic per UE will be similar or less compared to the IMS signalling. NOTE 10: In both RRC Idle and RRC Connected mode, the PDB requirement for these 5QIs can be relaxed for the first packet(s) in a downlink data or signalling burst in order to permit battery saving (DRX) techniques. NOTE 11: In RRC Idle mode, the PDB requirement for these 5QIs can be relaxed for the first packet(s) in a downlink data or signalling burst in order to permit battery saving (DRX) techniques. NOTE 12: This 5QI value can only be assigned upon request from the network side. The UE and any application running on the UE is not allowed to request this 5QI value. NOTE 13: A delay of 20 ms for the delay between a UPF terminating N6 and a 5G-AN should be subtracted from a given PDB to derive the packet delay budget that applies to the radio interface. NOTE 14: This 5QI is not supported as it is only used for transmission of V2X messages over MBMS bearers as defined in TS 23.285 [72],

(42) According to an embodiment of the present disclosure, information related to mapping (hereafter, 'mapping information') between the PPPP/PPPR-based QoS model for the LTE PC5 communication and the PQI-based QoS model for the NR PC5 communication may be defined. For example, the mapping information may be defined as 'policy/parameters related to QoS' of <Table 2>. Specifically, the mapping information may be defined as 'the mapping of PPPP and 5QI', 'the mapping of PPPR and 5QI' as shown in <Table 2>. The mapping information may be determined according to at least one of the following various schemes.

(43) According to an embodiment, to determine PPPP mapping which may be used interchangeably with the priority level of the PQI, a PPPP value or value interval mapped with the priority level value or value interval among the PQI may be defined. For example, priority level values '7' and '15' may be mapped to the PPPP value '1'. As another example, priority level values '0' to '20' may be mapped to the PPPP value '1'.

(44) According to an embodiment, to determine the PPPP mapping which may be used interchangeably with the packet delay budget of the PQI, the packet delay budget mapped with the PPPP may be defined. A packet delay budget value or value interval as the PQI mapped with a packet delay budget value or value interval mapped with the PPPP may be defined. For example, the packet delay budget value mapped with the PPPP value '1' is defined as '110 ms', and the packet delay budget value '110 ms' derived from the PPPP may map the packet delay budget value as the PQI to '110 bms'. As another example, the packet delay budget value '110 ms' derived from the PPPP may be mapped to the interval of the packet delay budget value as the PQI from '0ms' to '110 ms'.

(45) According to an embodiment, to determine the PPPR mapping which may be used interchangeably with the packet error rate of the PQI, a PPPR value or value interval mapped with a packet error rate value or value interval as the PQI may be defined. For example, a packet error rate values '10-6' and '10-5' may be mapped to the PPPR value '1'. As another example, a packet error rate value from '10-6' to '10-5' may be mapped to the PPPR value '1'.

(46) According to an embodiment, a PPPP value and/or a PPPR value mapped with the PQI value may be defined to determine the PPPP or the PPPR which may be used interchangeably with the PQI value (e.g., corresponding to the 5QI value in <Table 4>). For example, the PQI value '1' may be mapped to the PPPP value '1' and/or the PPPR value '5'.

(47) The mapping information between the LTE QoS model (e.g., PPPP/PPPR) and the NR QoS model (e.g., PQI) may be defined as in the various examples described above, and the mapping information between the LTE QoS model and the NR QoS model may be transmitted to at least one of the terminal and the base station through the procedures of FIG. 8A through FIG. 9C.

(48) FIG. 2 illustrates a structure of a second communication system according to an embodiment of the present disclosure. According to an embodiment, the second communication system illustrated in FIG. 2 may be a mobile communication system based on 5G.

(49) Referring to FIG. 2, the second communication system includes a next generation node B (gNB) **210**, an access and mobility management function (AMF) **215**, a session management function (SMF) **220**, a user plane function (UPF) **225**, unified data management (UDM) **235**, unified data repository (UDR) **230**, a policy control function (PCF) **240**, a network exposure function (NEF) **245**, and an application function (AF) **250**. The gNB **210** may be referred to as a 'base station', a 'next generation-RAN (NG-RAN)', a 'RAN node', or other term having an equivalent technical meaning.

(50) UEs **110a**, **110b**, **200a**, and **200b** access an external network through the gNB **210** and the UPF **225**. For the UE to transmit and receive data through the UPF **225**, it needs to generate a PDU session, and one PDU session may include one or more QoS flows. The UE **110a**, **110b**, **200a** or **200b** may be referred to as a 'terminal', a 'mobile station', a 'subscriber station', a 'remote terminal', a 'wireless terminal', or a 'user device' or other term having an equivalent technical meaning. For the sake of descriptions below, the present disclosure describes embodiments using the UE **110a** of the UEs **110a**, **110b**, **200a**, and **200b**, and the other UEs **110b**, **200a**, and **200b** may operate similarly.

(51) The gNB **210** is an RAN node and corresponds to the eNB of the EPC system. The gNB **210** is connected to the UE **110a** over a radio channel and performs a similar role to the existing RNC/BSC. In the 5G, since every user traffic including a real-time service such as VoIP through Internet protocol is serviced through a shared channel, a device for collecting and scheduling context information of the UE **110a** is required, which is managed by the gNB **210**.

(52) The AMF **215** is a device which manages various control functions, and one AMF **215** may be connected to a plurality of base stations. The UPF **225** is a device which provides a data bearer, and creates or removes a PDU session under control of the SMF **220**. The UDM **235** is a device which stores and manages subscription information of the UE **110a**. In addition, the UDM **235** may store subscription information for providing the V2X service. <Table 1> shows the example of the V2X service related subscription information managed by the UDM **235**.

(53) The PCF **240** is a device which controls a policy related to the user's QoS, and a policy and charging control (PCC) rule corresponding to the policy is transmitted to and applied to the SMF **220** and the UPF **225**. In addition, the PCF **240** may manage service policy and parameter information to provide the V2X service. <Table 2> and <Table 3> show the examples of the V2X service policy and parameter information managed by the PCF **240**. The V2X service policy and parameter information may be stored in the UDR **230**. The PCF **240** may obtain the V2X service policy and parameter information from the UDR **230**. The UE **110a** may obtain the V2X service policy and parameter information from the PCF **240** through the procedure shown in FIG. 5. Alternatively, the V2X service policy and parameter information shown in <Table 2> and <Table 3> may be pre-configured in the terminal, and the terminal may use the pre-configured information. The AF **250** is a device which exchanges application related information with the user at the application level. A V2X AS **145** is a device for providing the application level V2X service. The V2X AS **145** may include the AF **250** function.

(54) FIG. 3 illustrates an interworking structure between communication systems according to an embodiment of the present disclosure. According to an embodiment, the structure illustrated in FIG. 3 may be the interworking structure of the LTE-based mobile communication system and the 5G-based mobile communication system (e.g., NR).

(55) Referring to FIG. 3, for interworking between a first communication system and a second communication system, an SGW **300**, a UPF+PGW-U **305**, an SMF+PGW-C **510**, a v-PCF **315**, an HSS+UDM **320**, and a v-V2X CF **325** may be deployed with the first communication system and the second communication system.

(56) FIG. 4 illustrates a configuration of a network entity in a communication system according to an embodiment of the present disclosure. The configuration illustrated in FIG. 4 may be understood as one configuration of an eNB **120**, an MME **125**, an S/P-GW **130**, an HSS **135**, a V2X CF **140**, a gNB **210**, an AMF **215**, an SMF **220**, a UPF **225**, a UDM **235**, a UDR **230**, a PCF **240**, a NEF **245** and an AF **250**. A term such as ‘unit’ or ‘er’ used hereafter indicates a unit for processing at least one function or operation, and may be implemented using hardware, software, or a combination of hardware and software.

(57) Referring to FIG. 4, the network entity includes a communication unit **410**, a storage unit **420**, and a control unit **430**.

(58) The communication unit **410** provides an interface for performing communication with other devices in the network. That is, the communication unit **410** converts a bit stream transmitted from the network entity to other device into a physical signal, and converts a physical signal received from other device into a bit stream. That is, the communication unit **410** may transmit and receive signals. Accordingly, the communication unit **410** may be referred to as a modem, a transmitter, a receiver or a transceiver. At this time, the communication unit **410** enables the network entity to communicate with other devices or system via backhaul connection (e.g., wired backhaul or wireless backhaul) or via a network.

(59) The storage unit **420** stores a basic program for operating the network entity, an application program, and data such as setting information. The storage unit **420** may include a volatile memory, a non-volatile memory or a combination of a volatile memory and a non-volatile memory. The storage unit **420** provides the stored data according to a request of the control unit **430**.

(60) If the network entity of FIG. 4 is a base station (e.g., the eNB **120** or the gNB **210**), the network entity may further include a wireless communication unit. The wireless communication unit performs functions for transmitting and receiving signals over a radio channel. For example, the wireless communication unit performs a conversion function between a baseband signal and a bit string according to the physical layer standard of the system. For example, in data transmission, the wireless communication unit generates complex symbols by encoding and modulating a transmit bit stream. In addition, in data reception, the wireless communication unit restores the received bit stream by demodulating and decoding the baseband signal.

(61) In addition, the wireless communication unit up-converts the baseband signal into a radio frequency (RF) band signal, transmits it via an antenna, and down-converts an RF band signal received via the antenna into a baseband signal. For doing so, the wireless communication unit may include a transmit filter, a receive filter, an amplifier, a mixer, an oscillator, a digital to analog convertor (DAC), an analog to digital convertor (ADC), and the like. In addition, the wireless communication unit may include a plurality of transmit/receive paths. Further, the wireless communication unit may include at least one antenna array including a plurality of antenna elements.

(62) In terms of hardware, the wireless communication unit may include a digital unit and an analog unit, and the analog unit may include a plurality of sub-units according to an operating power and an operating frequency. The digital unit may be implemented with at least one processor (e.g., a digital signal processor (DSP)).

(63) The wireless communication unit transmits and receives the signals as stated above. Hence, whole or part of the wireless communication unit may be referred to as ‘a transmitter’, ‘a receiver’, or ‘a transceiver’. Also, in the following explanations, the transmission and the reception over the radio channel is used as the meaning which embraces the above-stated processing of the wireless communication unit.

(64) The control unit **430** controls general operations of the network entity. For example, the control unit **430** transmits and receives signals through the communication unit **410**. In addition, the control unit **430** records and reads data in and from the storage unit **420**. For doing so, the control unit **430** may include at least one processor. According to various embodiments, the control

unit **430** may control the network entity to perform operations according to various embodiments to be described.

(65) FIG. 5 illustrates a configuration of a terminal in a communication system according to an embodiment of the present disclosure. The configuration illustrated in FIG. 5 may be understood as the configuration of the UE **110a**, **110b**, **110c**, **11d**, **200a** or **200b**. A term such as ‘~unit’ or ‘~er’ used hereafter indicates a unit for processing at least one function or operation, and may be implemented using hardware, software, or a combination of hardware and software.

(66) Referring to FIG. 5, the terminal includes a communication unit **510**, a storage unit **520**, and a control unit **530**.

(67) The communication unit **510** may perform functions for transmitting and receiving signals over a radio channel. For example, the communication unit **510** performs a conversion function between a baseband signal and a bit string according to the physical layer standard of the system. For example, in data transmission, the communication unit **510** generates complex symbols by encoding and modulating a transmit bit string. Also, in data reception, the communication unit **510** restores a receive bit string by demodulating and decoding a baseband signal. Also, the communication unit **510** up-converts the baseband signal to an RF band signal, transmits it via an antenna, and down-converts an RF band signal received via the antenna to a baseband signal. For example, the communication unit **510** may include a transmit filter, a receive filter, an amplifier, a mixer, an oscillator, a DAC, an ADC, and the like.

(68) Also, the communication unit **510** may include a plurality of transmit and receive paths. Further, the communication unit **510** may include at least one antenna array including a plurality of antenna elements. In view of the hardware, the communication unit **510** may include a digital circuit and an analog circuit (e.g., an RF integrated circuit (RFIC)). Herein, the digital circuit and the analog circuit may be implemented as a single package. Also, the communication unit **510** may include a plurality of RF chains. Further, the communication unit **510** may perform beamforming.

(69) The communication unit **510** transmits and receives the signals as stated above. Hence, whole or part of the communication unit **510** may be referred to as ‘a transmitter’, ‘a receiver’, or ‘a transceiver’. In addition, the transmission and the reception over the radio channel are used as the meaning which embraces the above-stated processing of the communication unit **510** in the following explanations.

(70) The storage unit **520** stores a basic program for operating the terminal, an application program, and data such as setting information. The storage unit **520** may include a volatile memory, a non-volatile memory, or a combination of a volatile memory and a non-volatile memory. The storage unit **520** provides the stored data according to a request of the control unit **530**.

(71) The control unit **530** controls general operations of the terminal. For example, the control unit **530** transmits and receives signals through the communication unit **510**. Also, the control unit **530** records and reads data in and from the storage unit **320**. The control unit **530** may execute functions of a protocol stack required by the communication standard. For doing so, the control unit **530** may include at least one processor or microprocessor, or may be part of a processor. In addition, part of the communication unit **510** and the control unit **530** may be referred to as a communication processor (CP). According to various embodiments, the control unit **530** may control the terminal to carry out operations according to various embodiments to be explained.

(72) FIG. 6 illustrates a flowchart for using mapping information of QoS in a wireless communication system according to an embodiment of the present disclosure. FIG. 6 illustrates an operating method of a device using the QoS mapping information. For example, the device may be a base station (e.g., the eNB **120** or the gNB **210**) or a UE (e.g., the UE **110a**, **110b**, **110c**, **110d**, **200a** or **200b**).

(73) Referring to FIG. 6, in step **601**, the device obtains QoS mapping information between different systems. The QoS mapping information may include at least one of information notifying that switching between parameters indicating the QoS required for communication in a first system

and a second system is allowed, information indicating correspondence between the parameters indicating the QoS required for the communication in the first system and the second system, and information indicating a switching rule between the parameters indicating the QoS required for the communication in the first system and the second system. For example, one of the first system and the second system may be a system based on the LTE standard as shown in FIG. 1, and the other may be a system based on the NR standard as shown in FIG. 2. The QoS mapping information may be obtained through a unique procedure for providing the mapping information, or a procedure for other purpose (e.g., a procedure for registering in the network, a procedure for accessing the network or a procedure for updating a tracking area (TA)).

(74) In step **603**, the device performs an operation related to direct communication using the mapping information. For example, the device may switch the QoS parameters of the first system to the QoS parameters of the second system using the mapping information. The switched QoS parameters may be used for various operations related to the direct communication. For example, the switched QoS parameters may be used for resource allocation, resource request, service availability determination, and so on.

(75) As in the embodiment described with reference to FIG. 6, the device may obtain the QoS mapping information between the first system and the second system. In this regard, the device may transmit to the network, capability information notifying that direct communication related operations based on the QoS mapping information may be performed. In other words, since providing the mapping information to the device even though the mapping information is unavailable causes unnecessary signaling overhead, the device may inform the network of the necessity of the mapping information by transmitting the capability information reporting that the mapping information is available.

(76) As in the embodiment described with reference to FIG. 6, the device may switch the QoS parameters of the first system to the QoS parameters of the second system.

(77) According to an embodiment, if the device is a base station, the device may receive from the terminal a message requesting resource allocation for the direct communication, and switch the QoS parameters of the first system included in the message to the QoS parameters of the second system. For example, the device may select a system adequate for the direct communication based on link status of the first system and the second system, and switch the QoS parameters for the resource allocation according to the selection.

(78) According to another embodiment, if the device is a UE, the device may switch the QoS parameters of the first system generated by an application to the QoS parameters of the second system. As an example, to perform the direct communication in other system than a system corresponding to the QoS parameters provided by the application, the device may switch the QoS parameters generated by the application. As another example, if a system used to provide a service of each application is defined but the QoS parameters provided by the application do not correspond to the defined system, the device may switch the QoS parameters generated by the application.

(79) FIG. 7 is a flowchart for providing mapping information of QoS in a wireless communication system according to an embodiment of the present disclosure. FIG. 7 illustrates an operating method of a device for providing the QoS mapping information. For example, the device may be a core network entity (e.g., the HSS **135**, the MME **125**, the V2X CF **140**, the S/P-GW **130**, the UDR **230**, the PCF **240**, or the AMF **215**) or a base station (e.g., the eNB **120** or the gNB **210**).

(80) Referring to FIG. 7, in step **701**, the device generates a message including QoS mapping information between different systems. The QoS mapping information may include at least one of information notifying that switching between parameters indicating the QoS required for communication in a first system and a second system is allowed, information indicating correspondence between the parameters indicating the QoS required for the communication in the first system and the second system, and information indicating a switching rule between the

parameters indicating the QoS required for the communication in the first system and the second system. For example, one of the first system and the second system may be a system based on the LTE standard as shown in FIG. 1, and the other may be a system based on the NR standard as shown in FIG. 2. The message including the QoS mapping information may be generated by a request of other device, or may be generated by determination of the device.

(81) In step 703, the device transmits the message including the QoS mapping information. The message including the QoS mapping information may be transmitted through a unique procedure for providing the mapping information, or a procedure for other purpose (e.g., a procedure for registering in a network, a procedure for accessing a network or a procedure for updating a TA).

(82) According to various embodiments, an operating method of a base station in a wireless communication system may include obtaining information of QoS mapping related to direct communication between a first system and a second system, and switching between QoS of the first system and QoS of the second system using the mapping information.

(83) In some embodiments, obtaining the mapping information may include transmitting a first message for registration of a terminal to a higher network entity, receiving a second message as a response to the first message, and obtaining the mapping information from the second message.

(84) In some embodiments, the method further includes receiving a first message requesting a resource for direct communication from the terminal, and transmitting a second message notifying a result of the resource allocation, and the second message may be generated based on QoS parameters related to the direct communication included in the first message and the mapping information.

(85) In some embodiments, the method further includes transmitting a first message for establishing connection with a network to a higher network entity, and receiving a second message which is a response to the first message from the higher network entity, and the first message may include capability information of the base station related to the QoS mapping.

(86) In some embodiments, the capability information may include information indicating presence or absence of cross-radio access technology (RAT) PC5 control capability.

(87) In some embodiments, an operating method of a terminal in a wireless communication system may include obtaining information of QoS mapping related to direct communication between a first system and a second system, and switching between QoS of the first system and QoS of the second system using the mapping information.

(88) In some embodiments, the method further includes transmitting a first message requesting resources for direct communication to a base station, and receiving a second message notifying a result of the resource allocation, and the first message may include QoS parameters of the first system or the second system.

(89) In some embodiments, the first message may indicate whether the resources requested based on at least one of a message type, an indication, a destination address value, and the QoS parameters included in the first message are first system resources or second system resources.

(90) According to various embodiments, a base station apparatus in a wireless communication system includes at least one transceiver, and at least one processor connected to the at least one transceiver, and the at least one processor may control to obtain mapping information of QoS related to direct communication between a first system and a second system, and to perform switching between QoS of the first system and QoS of the second system using the mapping information.

(91) In some embodiments, the at least one processor may control to transmit a first message for registration of a terminal to a higher network entity, receive a second message as a response to the first message, and obtain the mapping information from the second message.

(92) In some embodiments, the at least one processor controls to receive a first message requesting resources for direct communication from the terminal, and to transmit a second message informing an allocation result of the resource, and the second message may be generated based on the QoS

parameters related to the direct communication included in the first message and the mapping information.

(93) In some embodiments, the at least one processor controls to transmit a first message for establishing connection with a network to a higher network entity, and to receive a second message which is a response to the first message from the higher network entity, and the first message may include capability information of the base station related to the QoS mapping.

(94) In some embodiments, the capability information may include information indicating presence or absence of cross-RAT PC5 control capability.

(95) In some embodiments, a terminal apparatus in a wireless communication system includes a transceiver, and at least one processor connected to the transceiver, and the at least one processor may control to obtain information of QoS mapping related to direct communication between a first system and a second system, and to perform switching between QoS of the first system and QoS of the second system by using the mapping information.

(96) In some embodiments, the at least one processor controls to transmit a first message requesting resources for the direct communication to the base station, and to receive a second message informing an allocation result of the resource, and the first message may include QoS parameters of the first system or the second system.

(97) In some embodiments, the first message may indicate whether resources requested based on at least one of a message type, an indication, a destination address value, and the QoS parameters included in the first message are first system resources or second system resources.

(98) Hereinafter, the present disclosure describes specific examples of providing, obtaining, and using mapping information of QoS parameters between different systems. In the following descriptions, messages with specific names are mentioned, which are for convenience of descriptions, and do not limit the present invention.

(99) FIG. 8A illustrates a procedure for a base station to obtain service policy/parameter information from a network of a first communication system during an initial registration process in a wireless communication system according to an embodiment of the present disclosure. The procedure illustrated in FIG. 8A is a procedure in which the UE **110a** registers at the network, and the registration procedure may be referred to as network attachment. A default EPS bearer is created during the network attachment, and thus always-on IP connectivity is possible.

(100) According to FIG. 8A, in step **801**, the UE **110a** may transmit an initial attach request message to the eNB **120**. The UE **110a** may transmit the attach request message to the eNB **120** using a radio resource control (RRC) connection setup complete message.

(101) In step **803**, the eNB **120** may transmit the initial attach request message to the MME **125** to access. The eNB **120** may transmit the attach request message using an initial UE message which is an S1-MME control message. The initial attach request message may include UE capability information supported by the UE **110a**. The UE capability information may include at least one of V2X capability indication, LTE PC5 capability, and NR PC5 capability. The initial attach request message may be included in an S1 application protocol (S1AP) initial UE message and delivered to the MME **125**. The eNB **120** may deliver the initial UE message including V2X support capability information of the eNB **120**, for example, V2X support, cross-RAT PC5 control capability information to the MME **125**. According to another embodiment, a tracking area update (TAU) message may be used, in place of the initial attach request message.

(102) In step **805**, the MME **125** may transmit a message requesting subscription information of the UE **110a** (e.g., a UE subscription request message) to the HSS **135**. In step **807**, the HSS **135** may response to the MME **125** a response message (e.g., a UE subscription response message) including the UE subscription information. The subscription information of the UE **110a** may include at least one of the items shown in <Table 1>. According to an embodiment of the present disclosure, the HSS **135** may store the V2X service policy and parameter information for the direct communication (e.g., ProSe) shown in <Table 2>. The subscription information responded by the

HSS 135 to the MME 125 may include at least some of the V2X service policy and parameter information for the direct communication (e.g., ProSe) shown in <Table 2>.

(103) Next, in step 809, the MME 125 may transmit to the eNB 120 an S1AP initial context setup request message including an attach accept message or a TAU accept message. The MME 125 may determine information included in the initial context setup request message and provided to the eNB 120 based on the UE capability and eNB capability (RAN capability) information received in step 803.

(104) According to an embodiment, if the UE capability includes V2X capability indication and the eNB capability includes V2X support, the initial context setup request message may include at least one of the V2X service authorized indication (e.g., a of Table 1) and UE-PC5-aggregated maximum bit rate (AMBR) for LTE PC5 (e.g., b of Table 1).

(105) According to another embodiment, if the UE capability includes the V2X capability indication and the NR PC5 capability, and the eNB capability includes the V2X support and the cross-RAT PC5 control, the initial context setup request message may include at least one of V2X service authorized indication (e.g., a of <Table 1>), UE-PC5-AMBR for LTE PC5 (e.g., b of Table 1), UE-PC5-AMBR for NR PC5 (e.g., c of <Table 1>), cross-RAT PC5 control authorization (e.g., e of <Table 1>), and V2X service policy and parameter information for direct communication (e.g., ProSe) (e.g., at least one of the items of <Table 2>).

(106) In step 811, the eNB 120 transmits an RRC connection reconfiguration message including the attach accept message to the UE 110a. Next, although not depicted in FIG. 8A, the UE 110a transmits an RRC connection reconfiguration complete message to the eNB 120, and the eNB 120 transmits an initial context setup response message to the new MME 125. Next, in step 813, the UE 110a transmits a direct transfer message including the attach complete message to the eNB 120. In step 815, the eNB 120 delivers the attach complete message to the new MME 125.

(107) FIG. 8B illustrates a procedure for the terminal to obtain the service policy and parameter information from the network of the first communication system in the wireless communication system according to an embodiment of the present disclosure. FIG. 8B illustrates the procedure for the terminal to obtain V2X service policy and parameter information. According to the procedure shown in FIG. 8B, after completing the registration at the network through the procedure shown in FIG. 8A, the UE 110a may establish PDN connection with the V2X CF 140 through the eNB 120 and the S/P-GW 130, and obtain the V2X service policy and parameter information from the V2X CF 140.

(108) Referring to FIG. 8B, in step 817, the HSS 135 may receive V2X related subscription information and service policy/parameter information from the V2X CF 140. In step 819, the UE 110a may transmit a V2X policy provisioning request message to the V2X CF 140. The V2X policy provisioning request message may include UE capability (e.g., LTE PC5 capability, NR PC5 capability, etc.). In step 821, the V2X CF 140 receiving the V2X policy provisioning request message may reply with a V2X policy provisioning response message. The V2X policy provisioning response message may include at least some of the V2X service policy and parameter information shown in <Table 2> and <Table 3>.

(109) In the embodiment described with reference to FIG. 8B, the HSS 135 and the V2X CF 140 may exchange UE subscription information and service policy/parameter information related to the V2X, in step 817. Referring to FIG. 8A and FIG. 8B, step 817 is performed after the network registration of the UE 110a. However, according to another embodiment, step 817 may be performed before the network registration of the UE 110a, that is, before step 801. In addition, if there is a change in the UE subscription information and the service policy/parameter information related to the V2X, the HSS 135 or the V2X CF 140 may update the information by triggering step 817.

(110) FIG. 9A through FIG. 9C illustrate a procedure for a terminal to obtain service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>) from a

network according to an embodiment of the present disclosure.

(111) FIG. 9A illustrates a procedure for a terminal and a base station to obtain service policy/parameter information from a network of a second communication system during an initial registration process in a wireless communication system according to an embodiment of the present disclosure. FIG. 9A illustrates signaling between the UE **110a**, the gNB **210**, the AMF **215**, the PCF **240**, the UDM **235**, and the UDR **230**. Herein, the gNB **210** may be referred to as an ‘access network (An)’ or a ‘RAN’.

(112) Referring to FIG. 9A, in step **901**, the UDM **235** may transmit subscription information of the UE **110a** to the PCF **240**. For example, if the subscription information of the UE **110a** stored in the UDM **235** is updated, the UDM **235** may provide the updated subscription information. In step **903**, the UDR **230** may transmit policy related information (e.g., V2X service parameters) to the PCF **240**. For example, if the policy related information stored in the UDR **230** is updated, the UDR **230** may provide the updated policy related information. In FIG. 9A, it is shown that step **901** and step **903** are performed prior to subsequent steps. However, according to another embodiment, at least one of step **901** and step **903** may be omitted, or may be performed at different times. That is, step **901** and step **903** may be performed independently from the registration procedure of the UE **110a**.

(113) In step **905**, the UE **110a** may transmit a registration request message to the gNB **210**. In step **907**, the gNB **210** may transmit the registration request message to the AMF **215**. The AMF **215** receiving the registration request message from UE **110a** via the gNB **210** may request UE subscription information of the UE **110a** from the UDM **235** through signaling with the UDM **235**, and obtain the subscription information from the UDM **235**, in step **909**. In step **911**, the AMF **215** may request policy information related to the UE **110a** from the PCF **240** through signaling with the PCF **240**, and obtain the policy information.

(114) In step **905**, the UE **110a** may include UE capability information supported by the UE **110a** and/or UE policy container (e.g., V2X policy) information in the registration request message and thus transmit the capability information and/or the UE policy container information to the gNB **210**. The gNB **210** may deliver the registration request message received from the UE **110a** to the AMF **215**. At this time, if the UE **110a** supports the V2X service, information indicating that the UE **110a** supports the V2X service may be provided to the AMF **215** by being included in the UE capability information (e.g., V2X capability indication). In addition, information indicating that the UE **110a** supports PC5 communication may be provided to the AMF **215** by being included in UE LTE PC5 capability and UE NR PC5 capability information.

(115) The registration request message transmitted in step **907** may be delivered to the AMF **215** by being included in a next generation application protocol (NGAP) initial UE message transmitted by the gNB **210** to the AMF **215**. The gNB **210** may include gNB **210** support capability information, for example, V2X support and cross-RAT PC5 control in the initial UE message.

(116) In step **909**, the AMF **215** may request subscription information of the UE **110a** from the UDM **235**, and the UDM **235** may transmit a message requesting the subscription information to the UDR **230**. The message for requesting the subscription information of the UE **110a** may include identification information indicating the UE **110a** (e.g., subscriber permanent identifier (SUPI) of the UE **110a**, 5G-globally unique temporary identifier (GUTI), international mobile subscriber identity (IMSI), etc.)). The UDR **230** may reply to the UDM **235** with a DM query response message including the subscription information of the UE **110a**. The UDM **235** receiving the UE subscription information may reply to the AMF **215** with a UE subscription response message. The UE subscription response message may include at least one of the UE subscription information for the V2X service shown in <Table 1> (e.g., V2X service authorized information of the UE **110a**, V2X capability of the UE **110a**, PC5 LTE capability of the UE **110a**, PC5 NR capability of the UE **110a**, cross-RAT PC5 control authorized information of the UE **110a**, etc.).

(117) According to an embodiment, if the AMF **215** determines that the UE **110a** supports the V2X

service based on the UE capability information received from the UE **110a**, the AMF **215** may select the PCF **240** supporting the V2X service. In step **911**, the AMF **215** may request policy information related to the UE **110a** from the selected PCF **240**. The message transmitted in step **911** may include UE policy container (e.g., V2X policy) information received from the UE **110a** by the AMF **215**.

(118) The PCF **240** may obtain V2X service parameters to be applied to the UE **110a** from the UDR **230** using one of various methods. For example, in step **903**, if the V2X service parameter update is needed, the UDR **230** may provide the V2X service parameters to the PCF **240**. As another example, in step **911**, the PCF **240** may request and obtain the V2X service parameters from the UDR **230**. According to an embodiment, the V2X service parameters provided by the UDR **230** to the PCF **240** may include the V2X service policy and parameter information shown in <Table 2> and <Table 3>.

(119) Meanwhile, the PCF **240** may receive the subscriber information of the UE **110a** and information of functionality or capability supported by the UE **110a** in step **911**. That is, the AMF **215** may provide the UE capability information and/or the UE subscription information obtained from the UDM **235** to the PCF **240** in step **911**.

(120) In step **911**, the PCF **240** provides the policy information to be applied to the UE **110a** to the AMF **215**, wherein the parameters for the V2X service obtained from the UDR **230** may be included in the policy information. If the PCF **240** transmits the parameter policy information for the V2X service to the AMF **215**, the PCF **240** may configure a policy container according to the following method.

(121) According to an embodiment, the PCF **240** may include policy/parameter information related to the LTE PC5 among the V2X service policies and parameters for the direct communication (e.g., ProSe) of <Table 2> into one policy container. In addition, the PCF **240** may include policy/parameter information related to the NR PC5 among the V2X service policies and parameters for the direct communication (e.g., ProSe) of <Table 2> into one policy container. In addition, the PCF **240** may include V2X service policy and parameter information for the network communication (e.g., Uu communication) of <Table 3> into one policy container. The PCF **240** may designate a policy section ID indicating the V2X service policy and parameter information to the V2X policy, and include it in the policy container. The PCF **240** may notify that the corresponding policy information is the policy for the V2X through the policy section ID, and that the V2X service policy and parameter information is included.

(122) In step **913** and step **915**, the AMF **215** may deliver a registration accept message including the parameter information for the V2X service obtained from the PCF **240** to the UE **110a** via the gNB **210**. At this time, the AMF **215** may determine information to be provided to the gNB **210** using the registration accept message included in the NGAP initial context setup message and information to be provided to the UE **110a** by using and including the registration accept message based on the UE capability and the RAN capability information received in step **907**.

(123) According to an embodiment, if the UE capability includes the V2X capability indication and the NR PC5 capability, and the gNB capability includes the V2X support, the registration accept message transmitted in step **913** may include at least one of V2X service authorized indication (e.g., a of <Table 1>), UE-PC5-AMBR for NR PC5 (e.g., c of <Table 1>), PLMN list for the UE **110a** to use the PC5 communication (e.g., d of <Table 1>), cross-RAT PC5 control authorization (e.g., e of <Table 1>), and policy container including the policy/parameter information related to the NR PC5 among the V2X service policies and parameters for the direct communication (e.g., ProSe) of <Table 2>.

(124) According to an embodiment, if the UE capability includes V2X capability indication, LTE PC5 capability, and NR PC5 capability, and the gNB capability includes V2X support and cross-RAT PC5 control, the registration accept transmitted in step **913** may include at least one of V2X service authorized indication (e.g., a of <Table 1>), UE-PC5-AMBR for LTE PC5 (e.g., b of

<Table 1>), UE-PC5-AMBR for NR PC5 (e.g., c of <Table 1>), PLMN list for the UE **110a** to use the PC5 communication (e.g., d of <Table 1>), cross-RAT PC5 control authorization (e.g., e of <Table 1>), policy container including policy/parameter information related to the LTE PC5 among the V2X service policies and parameters for the direct communication (e.g., ProSe) of <Table 2>, and policy container including policy/parameter information related to the NR PC5 among the V2X service policies and parameters for the direct communication (e.g.: ProSe) of <Table 2>.

(125) Alternatively, in step **917** and step **919**, the AMF **215** may deliver the parameter information for the V2X service received from the PCF **240** to the UE **110a** through a separate procedure. The parameter information for providing the V2X service included in the registration accept message transmitted in step **913** and step **915** or the UE policy delivery message transmitted in step **917** and step **919** may include at least one of the service policy/parameter information described in the present disclosure. At this time, in step **917** and step **919**, the parameter information for the V2X service included in a NGAP downlink non-access stratum (NAS) transport message and a NAS message for the AMF **215** to provide the policy information to the terminal may be determined in a similar manner to step **913** and step **915**. In step **917**, the AMF **215** may deliver a NGAP UE context modification request message to the gNB **210**. The NGAP UE context modification request message is a message used to change the context information of the terminal configured in the gNB **210**, and the gNB **210** stores and applies the parameter information for the V2X service received through the NGAP UE context modification request message in the context of the terminal. In response to this, the gNB **210** may transmit a UE context modification response message to the AMF **215**, and thus notify that the context of the terminal is changed and applied according to the received information.

(126) FIG. **9B** illustrates a procedure for the terminal to obtain the service policy/parameter information from the network at a network request of the second communication system in the wireless communication system according to an embodiment of the present disclosure. FIG. **9B** is an example of another procedure for the UE **110a** to obtain the service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>). According to the embodiment of FIG. **9B**, the UE **110a** may obtain UE policy related information using a UE configuration update procedure.

(127) Referring to FIG. **9B**, in step **923**, the PCF **240** may determine to update the UE policy. The PCF **240** may receive and store the updated service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>) of the terminal from the UDR **230** as in step **903** of FIG. **9A** as described above. At this time, the PCF **240** may determine whether the update of the UE policy is needed during the initial registration procedure (e.g., the procedure of FIG. **9A**) of the UE **110a**, or determine whether the update of the UE policy is needed by the network being triggered that the UE policy is needed after the initial registration. For example, during the initial registration procedure, the PCF **240** may determine whether the UE policy update is required based on the UE policy container (e.g., V2X policy) information received from the AMF **215**, and information associated with access selection and PDU selection of the terminal (e.g., may be included in Npcf_UEPolicyControl_Create request). Alternatively, if there occurs an event such as changing the location of the UE **110a** or changing the subscription information of the UE **110a**, for example, a slice service to which the UE **110a** is subscribed (subscribed single-network slice selection assistance information (S-NSSAI)), the PCF **240** may determine whether the UE policy needs to be changed. In addition, as described in the section related to step **911** of FIG. **9A**, the PCF **240** may determine to deliver the service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>) received from the UDR **230** to the UE **110a**.

(128) In step **925**, the PCF **240** may transmit the service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>) to the AMF **215**. At this time, if the V2X service policy parameters shown in <Table 1> are transmitted as the service policy/parameter information, the service policy/parameter information may include at least part of the V2X service

parameters shown in <Table 1>. According to an embodiment, the service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>) may be transmitted to the AMF 215 by being included in the Namf_Communication_N1N2MessageTransfer message. The Namf_Communication_N1N2MessageTransfer message may include the SUFI, the UE policy container, and the like.

(129) In step 927, if the UE 110a is registered in the network and is in a state for being serviced, the AMF 215 may determine to deliver the UE policy received from the PCF 240 to the UE 110a. If the UE 110a is registered in any one of 3GPP and non-3GPP access, the AMF 215 may deliver the UE policy to the UE 110a through the access connected by registering the UE 110a. If the UE 110a is registered at both of the 3GPP and the non-3GPP access and is connectable, the AMF 215 may select a specific access according to AMF 215 local policy, and deliver the UE policy the UE 110a. If the UE 110a is not registered in or is not connectable to either the 3GPP or the non-3GPP access, in step 935, the AMF 215 may notify UE policy transmission failure to the PCF 240 through a specific message (e.g., Namf_Communication_N1N2TransferFailureNotification). If the AMF 215 determines to deliver the UE policy to the UE 110a through the 3GPP access, if the UE 110a is in a CM-IDLE state, the AMF 215 may transmit a paging message to the UE 110a and thus initiate a paging procedure by a network triggered service request. The UE 11a receiving the paging request message may perform the paging procedure.

(130) In step 929 and step 931, the AMF 215 may deliver the UE policy to the UE 110a. In this case, if the UE policy includes the V2X service, the UE policy may include at least one of the V2X service policy parameters shown in <Table 1>. In this case, the AMF 215 may deliver a NAS message (e.g., a downlink NAS message or a MANAGE UE POLICY COMMAND message) for providing the policy to the UE to deliver the parameter. For doing so, the AMF 215 may include the NAS message in an NGAP downlink NAS transport or a NGAP UE context modification request message transmitted to the gNB 210. The parameter information for the V2X service provided by the AMF 215 in step 929 and step 931 may be determined in a similar manner to step 913 and step 915. If the AMF 215 delivers the NGAP UE context modification request message to the gNB 210, the gNB 210 may store and apply the parameter information for the V2X service received through the NGAP UE context modification request message in the context of the terminal. The gNB 210 may transmit a UE context modification response message to the AMF 215 as a response thereto, and thus inform that the context of the terminal is changed and applied according to the received information.

(131) In step 933, the UE 110a receiving the information of the UE policy may store the obtained information, and transmit a reply message informing that the corresponding information is received to the AMF 215. In step 935, the AMF 215 may inform the PCF 240 that the service policy/parameter information (e.g., the V2X service policy parameters illustrated in <Table 1>) is transmitted to the UE 110a. In this case, the message transmitted in step 935 may be a Namf_N1MessageNotify message. In addition, the PCF 240 may maintain the UE policy, and inform the UDR 230 of the updated UE policy.

(132) FIG. 9C illustrates a procedure for the terminal to obtain the service policy/parameter information from the network of the second communication system at a UE request in the wireless communication system according to an embodiment of the present disclosure. FIG. 9C is an example of yet another procedure for the UE 110a to obtain the service policy/parameter information (e.g., the V2X service policy parameters shown in <Table 1>). According to the embodiment of FIG. 9C, the UE 110a may obtain the UE policy by triggering the UE policy acquisition.

(133) Referring to FIG. 9C, in step 937, the UE 110a may transmit a message requesting the UE policy to the AMF 215. In this case, the message requesting the UE policy may be a UE policy provisioning request message, and may include a UE policy container (e.g., the V2X policy).

(134) In step 939, the AMF 215 may transmit a message requesting UE policy information to the

PCF **240**. The message requesting the UE policy information may be a Npcf_UEPolicyControl_Update request, and may include the UE policy container (e.g., the V2X policy) received from the terminal.

(135) In step **941**, the PCF **240** receiving the message requesting the UE policy information may determine whether the UE policy update is necessary. Subsequent step **941**, step **943**, step **945**, step **947**, step **949**, step **951**, and step **953** may be performed similarly to the operations described with reference to FIG. **9B**. For example, the PCF **240** may transmit the UE policy information to the AMF **215** in step **943**, and the AMF **215** may determine to deliver the UE policy to the UE **110a** and deliver it in step **945**, step **947**, and step **949**. In response to the UE policy, the UE **110a** may transmit a response message to the AMF **215** in step **951**, and the AMF **215** may transmit a message indicating whether the UE policy transmission is successful or not to the PCF **240** in step **953**.

(136) The procedures for obtaining the service parameter/policy described with reference to FIG. **9A**, FIG. **9B**, and FIG. **9C** may be equally applied to the other terminals (e.g., the UE **110b**, the UE **110c**, the UE **110d**, the UE **200a**, and the UE **200b**).

(137) FIG. **10** illustrates a procedure for a terminal to request and obtain radio resources for direct communication from a network entity of a second communication system in a wireless communication system according to an embodiment of the present disclosure.

(138) Referring to FIG. **10**, in step **1001**, the base station **210** may obtain V2X service subscription information, policy and parameter information from the AMF **215**. For example, the base station **210** may obtain the V2X service subscription information, and the policy and parameter information as in step **913** of FIG. **9A**, step **917** of FIG. **9A**, or step **929** of FIG. **9B**.

(139) In step **1003**, the UE **110a** may determine to transmit data using the LTE PC5. In step **1005**, the UE **110a** may transmit a sidelink (SL) resource request message for requesting LTE PC5 resources to the base station **210**. The SL resource request message may include at least one of a PPPP (and/or PPPR) requested by the data to be transmitted by the UE **110a**, a destination address of the data to be transmitted by the UE **110a** (e.g., Destination Layer-2 ID), and PQI required by the data to be transmitted by the UE **110a**, and a QoS flow identifier (QFI) indicating the PQI.

(140) According to the request of the UE **110a**, the base station **210** determines radio resources to be allocated to the UE **110a**. To determine the radio resources to be allocated to the UE **110a**, the base station **210** may use QoS mapping information (e.g., ‘the mapping of PPPP and 5QI’ and/or ‘the mapping of PPPR and 5QI’). For example, if receiving the PQI from the UE **110a** in step **1005**, the base station **210** may convert the PQI received from the UE **110a** to the PPPP (and/or PPPR) value using the QoS mapping information, and determine the radio resources to be assigned to the UE **110a**. Alternatively, if receiving the PPPP (and/or PPPR) from the UE **110a** in step **1005**, the base station **210** may convert the PPPP (and/or PPPR) received from the UE **110a** to a PQI value using the QoS mapping information, and determine the radio resources to be assigned to the UE **110a**. Herein, the QoS mapping information may be obtained from the AMF **215** according to step **913** of FIG. **9A**, step **917** of FIG. **9A**, and step **929** of FIG. **9B**. Alternatively, the QoS mapping information may be pre-configured in the base station **210**, and the base station **210** may use the pre-configured information.

(141) In step **1007**, the base station **210** may transmit an SL resource response message including radio resource information allocated to the UE **110a**. Herein, the radio resource may include at least one of a resource allocated exclusively to the UE **110a** or a resource competitively used with other UE. In step **1009**, the UE **110a** may transmit data. The UE **110a** may transmit the data by using at least part of the radio resources allocated by the base station **210**.

(142) In the embodiment described with reference to FIG. **10**, the UE **110a** determines to use the LTE PC5. According to another embodiment, the NR PC5, rather than the LTE PC5, may be used. In this case, each step of FIG. **10** includes the following operations.

(143) In step **1003**, the UE **110a** may determine to transmit data using the NR PC5. Next, in step

1005, the UE **110a** may transmit an SL resource request message for requesting NR PC5 resources to the base station **210**. The SL resource request message may include at least one of a PPPP (and/or PPPR) requested by the data to be transmitted by the UE **110a**, a destination address of the data to be transmitted by the UE **110a** (e.g., Destination Layer-2 ID), and PQI required by the data to be transmitted by the UE **110a**, and QFI indicating the PQI.

(144) According to the request of the UE **110a**, the base station **210** determines radio resources to be allocated to the UE **110a**. To determine the radio resources to be allocated to the UE **110a**, the base station **210** may use QoS mapping information (e.g., ‘the mapping of PPPP and 5QI’ and/or ‘the mapping of PPPR and 5QI’). For example, if receiving the PQI from the UE **110a** in step **1005**, the base station **210** may convert the PQI received from the UE **110a** to a PPPP (and/or PPPR) value using the QoS mapping information, and determine the radio resources to be allocated to the UE **110a**. Alternatively, if receiving the PPPP (and/or PPPR) from the UE **110a** in step **1005**, the base station **210** may convert the PPPP (and/or PPPR) received from the UE **110a** to a PQI value using the QoS mapping information, and determine the radio resources to be allocated to the UE **110a**. Herein, the QoS mapping information may be obtained from the AMF **215** according to step **913** of FIG. 9A, step **917** of FIG. 9A, and step **929** of FIG. 9B. Alternatively, the QoS mapping information may be pre-configured in the base station **210**, and the base station **210** may use the pre-configured information.

(145) In step **1007**, the base station **210** may transmit an SL resource response message to the UE **110a**. The SL resource response message may include information of the radio resources allocated to the UE **110a**. Herein, the radio resource may include at least one of a resource exclusively allocated to the UE **110a** or a resource competitively used with other UE. In step **1009**, the UE **110a** may transmit data. The UE **110a** may transmit the data by using at least part of the radio resources allocated by the base station **210**.

(146) In the embodiment described with reference to FIG. 10, the UE **110a** may request resources for direct communication from the base station **210**. At this time, the UE **110a** may selectively request one of the LTE PC5 resource or the NR PC5 resource. Herein, the LTE PC5 resource request and the NR PC5 resource request may be distinguished according to one of various methods.

(147) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished by being performed by different messages. For example, if the UE **110a** requests the PC5 resource from the base station **210**, the UE **110a** may use different SL resource request messages, to distinguish the LTE PC5 resource request and the NR PC5 resource request. Hence, the base station **210** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the type of the SL resource request message.

(148) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished by an indication in the message. For example, the same SL resource request message is used, but the UE **110a** may include the indication indicating one of the LTE PC5 or the NR PC5 in the SL resource request message. Thus, the base station **210** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying a value of the indication included in the SL resource request message.

(149) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished using a value of the destination address (e.g., Destination Layer-2 ID) included in the message. For example, values for indicating the destination address may be divided into a first range corresponding to the LTE PC5 resource and a second range corresponding to the NR PC5 resource. Specifically, in using one SL resource request message, the UE **110a** may distinguish Destination Layer-2 ID indicating the LTE PC5 and Destination Layer-2 ID indicating the NR PC5 using different values. Hence, the base station **210** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the destination address value included in the SL resource request message.

(150) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished based on the type of the required parameter included in the message. For example, the message requesting the LTE PC5 resource may include a parameter used for the LTE-based direct communication, and the message requesting the 5G PC5 resource may include a parameter used for the 5G-based direct communication. Specifically, if requesting the LTE PC5 resource, the UE **110a** may include only the PPPP (and/or PPPR) required by the data in the SL resource request message, and exclude the 5QI required by the data. Similarly, in addition, if requesting the NR PC5 resource, the UE **110a** may include only the 5QI required by the data in the SL resource request message, and exclude the PPPP (and/or PPPR) required by the data. Hence, the base station **210** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the type of QoS related parameters included in the SL resource request message.

(151) FIG. **11** illustrates a procedure for a terminal to request and obtain radio resources for direct communication from a network entity of a first communication system in a wireless communication system according to an embodiment of the present disclosure.

(152) Referring to FIG. **11**, in step **1101**, the base station **210** may obtain V2X service subscription information, and policy and parameter information from the MME **125**. For example, the base station **210** may obtain the V2X service subscription information, and the policy and parameter information as in step **809** of FIG. **8A**.

(153) In step **1103**, the UE **110a** may determine to transmit data using the LTE PC5. In step **1105**, the UE **110a** may transmit an SL resource request message for requesting LTE PC5 resources to the base station **120**. The SL resource request message may include at least one of a PPPP (and/or PPPR) required by the data to be transmitted by the UE **110a**, a destination address of the data to be transmitted by the UE **110a** (e.g., Destination Layer-2 ID), and PQI required by the data to be transmitted by the UE **110a**, and QFI indicating the PQI.

(154) According to the request of the UE **110a**, the base station **120** determines radio resources to be allocated to the UE **110a**. To determine the radio resources to be allocated to the UE **110a**, the base station **120** may use QoS mapping information (e.g., ‘the mapping of PPPP and 5QI’ and/or ‘the mapping of PPPR and 5QI’). For example, if receiving the PQI from the UE **110a** in step **1105**, the base station **120** may convert the PQI received from the UE **110a** to a PPPP (and/or PPPR) value using the QoS mapping information, and determine the radio resources to be assigned to the UE **110a**. Alternatively, if receiving the PPPP (and/or PPPR) from the UE **110a** in step **1105**, the base station **210** may convert the PPPP (and/or PPPR) received from the UE **110a** to a PQI value using the QoS mapping information, and determine the radio resources to be assigned to the UE **110a**. Herein, the QoS mapping information may be obtained from the MME **125** according to step **809** of FIG. **8A**. Alternatively, the QoS mapping information may be pre-configured in the base station **120**, and the base station **120** may use the pre-configured information.

(155) In step **1107**, the base station **120** may transmit an SL resource response message. The SL resource response message may include radio resource information allocated to the UE **110a**. Herein, the radio resource may include at least one of a resource exclusively allocated to the UE **110a** or a resource competitively used with other UE. In step **1109**, the UE **110a** may transmit data. The UE **110a** may transmit the data by using at least part of the radio resources allocated by the base station **120**.

(156) In the embodiment described with reference to FIG. **11**, the UE **110a** determines to use the LTE PC5. According to another embodiment, the NR PC5, rather than the LTE PC5, may be used. In this case, each step of FIG. **10** includes the following operations.

(157) In step **1103**, the UE **110a** may determine to transmit data using the NR PC5. Next, in step **1105**, the UE **110a** may transmit an SL resource request message for requesting NR PC5 resources to the base station **120**. The SL resource request message may include at least one of a PPPP (and/or PPPR) required by the data to be transmitted by the UE **110a**, a destination address of the

data to be transmitted by the UE **110a** (e.g., Destination Layer-2 ID), and PQI required by the data to be transmitted by the UE **110a**, and QFI indicating the PQI.

(158) According to the request of the UE **110a**, the base station **120** determines radio resources to be allocated to the UE **110a**. To determine the radio resources to be allocated to the UE **110a**, the base station **120** may use QoS mapping information (e.g., ‘the mapping of PPPP and 5QI’ and/or ‘the mapping of PPPR and 5QI’). For example, if receiving the PQI from the UE **110a** in step **1105**, the base station **120** may convert the PQI received from the UE **110a** to a PPPP (and/or PPPR) value using the QoS mapping information, and determine the radio resources to be allocated to the UE **110a**. Alternatively, if receiving the PPPP (and/or PPPR) from the UE **110a** in step **1105**, it may convert the PPPP (and/or PPPR) received from the UE **110a** to a PQI value using the QoS mapping information stored in the base station **120**, and determine the radio resources to be allocated to the UE **110a**. Herein, the QoS mapping information may be obtained from the MME **125** according to step **809** of FIG. **8A**. Alternatively, the QoS mapping information may be pre-configured in the base station **120**, and the base station **120** may use the pre-configured information.

(159) In step **1107**, the base station **120** may transmit an SL resource response message. The SL resource response message may include information of the radio resources allocated to the UE **110a**. Herein, the radio resource may include at least one of a resource exclusively allocated to the UE **110a** or a resource competitively used with other UE. In step **1109**, the UE **110a** may transmit data. The UE **110a** may transmit the data by using at least part of the radio resources allocated from the base station **210**.

(160) In the embodiment described with reference to FIG. **11**, the UE **110a** may request resources for the direct communication from the base station **120**. At this time, the UE **110a** may selectively request one of the LTE PC5 resource or the NR PC5 resource. Herein, the LTE PC5 resource request and the NR PC5 resource request may be distinguished according to one of various methods.

(161) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished by being performed by different messages. For example, if the UE **110a** requests the PC5 resource from the base station **120**, the UE **110a** may use different SL resource request messages, to distinguish the LTE PC5 resource request and the NR PC5 resource request. Hence, the base station **120** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the type of the SL resource request message.

(162) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished by an indication in the message. For example, the same SL resource request message is used, but the UE **110a** may include the indication indicating one of the LTE PC5 or the NR PC5 in the SL resource request message. Thus, the base station **120** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the value of the indication included in the SL resource request message.

(163) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished using a value of the destination address (e.g., Destination Layer-2 ID) included in the message. For example, values for indicating the destination address may be divided into a first range corresponding to the LTE PC5 resource and a second range corresponding to the NR PC5 resource. Specifically, in using one SL resource request message, the UE **110a** may distinguish Destination Layer-2 ID indicating the LTE PC5 and Destination Layer-2 ID indicating the NR PC5 using different values. Hence, the base station **210** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the destination address value included in the SL resource request message.

(164) According to an embodiment, the LTE PC5 resource request and the NR PC5 resource request may be distinguished based on the type of the required parameter included in the message. For example, the message requesting the LTE PC5 resource may include the parameter used for the LTE-based direct communication, and the message requesting the 5G PC5 resource may include

the parameter used for the 5G-based direct communication. Specifically, if requesting the LTE PC5 resource, the UE **110a** may include only the PPPP (and/or PPPR) required by the data in the SL resource request message, and exclude the 5QI required by the data. Similarly, if requesting the NR PC5 resource, the UE **110a** may include only the 5QI required by the data in the SL resource request message, and exclude the PPPP (and/or PPPR) required by the data. Hence, the base station **210** may determine whether the requested resource is the LTE PC5 resource or the NR PC5 resource, by identifying the type of the QoS related parameter included in the SL resource request message.

(165) FIG. **12** illustrates a procedure for establishing connection between a base station and a second communication system in a wireless communication system according to an embodiment of the present disclosure. FIG. **12** illustrates signaling between the gNB **210** and the AMF **215**. The gNB **210** may be referred to as the NG-RAN.

(166) Referring to FIG. **12**, in step **1201**, the gNB **210** transmits an NG setup request message to the AMF **215**. The NG setup request message may include V2X capability information. In step **1203**, the AMF **215** transmits an NG setup response message to the gNB **210**. That is, the gNB **210** and the AMF **215** may exchange information used between the two, and perform the N2 setup procedure to configure connection information. The N2 setup procedure may be performed regardless of the UE.

(167) According to the N2 setup procedure, the gNB **210** and the AMF **215** may obtain necessary information for their interconnection, and obtain information of capability supported by each entity. According to an embodiment, if performing the NG setup procedure with the AMF **215**, the gNB **210** may inform the AMF **215** of whether it supports the V2X, and whether cross-RAT PC5 control capability is present. Herein, the cross-RAT PC5 control capability may mean capability of the gNB **210** for supporting both of the LTE PC5 and the NR PC5 for the V2X PC5 communication. In addition, the cross-RAT PC5 control capability may mean capability of the gNB **210** for setting and providing information for the NR PC5 in the LTE RAT to the terminal, or for setting and providing information for the LTE PC5 in the NR RAT to the terminal. The capability information may be delivered to the AMF **215** by being included in the message transmitted in step **1201** in the form of information such as radio capability of the gNB **210** or V2X capability of the gNB **210**. The AMF **215** may complete the NG setup procedure, by transmitting the message to the gNB **210** in step **1203**.

(168) FIG. **13** illustrates a procedure for establishing connection between a base station and a first communication system in a wireless communication system according to an embodiment of the present disclosure. FIG. **13** illustrates signaling between the eNB **120** and the MME **125**. The eNB **120** may be referred to as an E-UTRAN.

(169) Referring to FIG. **13**, in step **1301**, the eNB **120** transmits an S1 setup request message to the MME **125**. The S1 setup request message may include V2X capability information. In step **1303**, the MME **125** transmits an S1 setup response message to the eNB **120**. The eNB **120** and the MME **125** may exchange information used between the two, and perform an S1 setup procedure to configure connection information. The S1 setup procedure may be conducted regardless of the UE.

(170) According to the S1 setup procedure, the eNB **120** and the MME **125** may obtain necessary information for their interconnection, and obtain information of functionality supported by each entity. According to an embodiment, if performing the S1 setup procedure with the MME **125**, the eNB **120** may inform the MME **125** of whether it supports the V2X, and whether it has cross-RAT PC5 control capability. Herein, the cross-RAT PC5 control capability may mean capability of the eNB **120** for supporting both the LTE PC5 and the NR PC5 for the V2X PC5 function. In addition, the cross-RAT PC5 control capability may mean capability of the eNB **120** for setting and providing information for the NR PC5 in the LTE RAT to the terminal, or for setting and providing information for the LTE PC5 in the NR RAT to the terminal. The capability information may be delivered to the MME **125** by being included in a message transmitted in step **1301** in the form of

information such as radio capability of the eNB **120** or V2X capability of the eNB **120**. The MME **125** may complete the NG setup procedure by transmitting the message to the eNB **120** in step **1303**.

(171) The UE according to various embodiments of the present disclosure may obtain function information supported by the network. Hereafter, a procedure for the UE to identifying a function supported by the network (e.g., a cross-RAT PC5 control function) through signaling from the base station is described through FIG. **14A** through FIG. **14B**.

(172) FIG. **14A** illustrates a procedure for a terminal to obtain system information from a network in a wireless communication system according to an embodiment of the present disclosure. FIG. **14** illustrates signaling between the terminal **110a** and the base station. In FIG. **14A**, the base station exemplifies the eNB **120**. The eNB **120** may be referred to as the E-UTRAN.

(173) Referring to FIG. **14A**, the terminal **110a** accessing the EPC network may receive system information from the base station (eNB) **120** in step **1401**. The system information in step **1401** may include functionality supported by the base station **120**. The functionality supported by the base station **120** may include cross-RAT PC5 control capability information. The system information in step **1401** may include PC5 resource information. The PC5 resource information may include LTE PC5 resource pool or NR PC5 resource pool information.

(174) The terminal **110a** receiving the system information of step **1401** from the base station **120** may perform a PC5 operation based on at least one of the functionality information supported by the base station **120** and the PC5 resource pool information included in the system information. For example, if the base station **120** supports the cross-RAT PC5 control function, the terminal **110a** may transmit an LTE PC5 or NR PC5 resource request message to the base station **120**. If the NR PC5 resource pool information is included in the system information, the terminal **110a** may store the NR PC5 resource pool information received from the base station **120**, and use it for NR PC5 communication. Alternatively, for example, if the base station **120** does not support the cross-RAT PC5 control function, the terminal **110a** may transmit the LTE PC5 resource request message to the base station **120**, and may not transmit the NR PC5 resource request message.

(175) If the base station **120** does not support the cross-RAT PC5 control function, the base station **120** may include an indication indicating no support for the cross-RAT PC5 control function in the message (i.e., the system information (SI) message) of step **1401**. Alternatively, the base station **120** may not include the cross-RAT PC5 control function related information in the message of step **1401**. The terminal **110a** may identify that the cross-RAT PC5 control function related information is not included in the message of step **1401**. The terminal **110a** may determine that the base station **120** does not support the cross-RAT PC5 control function based on the identification.

(176) According to another embodiment, instead of the SI message of step **1401**, the message (e.g., RRC connection reconfiguration/Initial Attach Response) of step **811** may be used.

(177) FIG. **14B** illustrates another procedure for the terminal to obtain the system information from the network in the wireless communication system according to an embodiment of the present disclosure. FIG. **14** illustrates signaling between the terminal **110a** and the base station. In FIG. **14B**, the base station exemplifies the gNB **210**. The gNB **210** may be referred to as the NG-RAN.

(178) Referring to FIG. **14B**, the terminal **110a** accessing the 5G network may receive the system information from the base station (gNB) **210** in step **1451**. The system information in step **1451** may include functionality supported by the base station **210**. The functionality supported by the base station **210** may include the cross-RAT PC5 control capability information. The system information in step **1401** may include PC5 resource information. The PC5 resource information may include the LTE PC5 resource pool or NR PC5 resource pool information.

(179) The terminal **110a** receiving the system information of step **1451** from the base station **210** may perform the PC5 operation based on at least one of the functionality information supported by the base station **210** and the PC5 resource pool information included in the system information. For example, if the base station **210** supports the cross-RAT PC5 control function, the terminal **110a**

may transmit an LTE PC5 or NR PC5 resource request message to the base station **210**. If the system information includes the LTE PC5 resource pool information, the terminal **110a** may store the LTE PC5 resource pool information received from the base station **210**, and use it for the LTE PC5 communication. Alternatively, for example, if the base station **210** does not support the cross-RAT PC5 control function, the terminal **110a** may transmit the NR PC5 resource request message to the base station **210**, and may not transmit the LTE PC5 resource request message.

(180) If the base station **210** does not support the cross-RAT PC5 control function, the base station **210** may include an indication indicating no support for the cross-RAT PC5 control function in the message (i.e., the SI message) of step **1451**. Alternatively, the base station **210** may not include the cross-RAT PC5 control function related information in the message of step **1451**. The terminal **110a** may identify that the cross-RAT PC5 control function related information is not included in the message of step **1451**. The terminal **110a** may determine that the base station **210** does not support the cross-RAT PC5 control function based on the identification.

(181) According to another embodiment, in place of the SI which is the message of step **1451**, the message (Registration Accept) message of step **915** may be used. The message (Registration Accept) of step **915** may be included in the RRC connection reconfiguration message and transmitted.

(182) The terminal according to various embodiments of the present disclosure may obtain the function information supported by the network. The terminal **110a** may register in the 5G system (e.g., 5GC) based on the procedure shown in FIG. **9A**.

(183) The terminal **110a** may transmit a registration request message to the AMF **215** via the base station **210**, in step **905** and step **907** of FIG. **9**. The registration request message may include the capability information of the terminal in the form of 5GS mobility management (5GMM) capability or S1 UE network capability. For example, the capability information of the terminal may be PC5 capability for V2X (e.g., LTE PC5 only, NR PC5 only, both LTE and NR PC5). Also, for example, the capability information of the terminal may be the cross-RAT PC5 capability.

(184) The AMF **215** receiving the registration request message of step **907**, may obtain the UE subscription information from the UDM **235** in step **909**. The UE subscription information may include at least one or more information of “V2X services authorized” indication, UE-PC5-AMBR per PC5 RAT, and cross-RAT PC5 control authorization.

(185) According to another embodiment, the AMF **215** may obtain the policy information (e.g., V2X policy information, PC5 policy information, etc.) from the PCF **240** in step **911**. The policy information may include at least one or more information of “V2X services authorized” indication, UE-PC5-AMBR per PC5 RAT, and cross-RAT PC5 control authorization.

(186) The AMF **215** may determine information to be included in the registration accept message based on at least one of the registration request message received from the terminal **110a**, the UE subscription information received from the UDM **235**, and the policy information received from the PCF **240**. For example, if the terminal **110a** supports the NR PC5 function or supports the cross-RAT PC5 capability, and the cross-RAT PC5 authorization information is included in the UE subscription information or the policy information, the AMF **215** may determine to provide the terminal **110a** with a cross-RAT PC5 scheduling function. The registration accept message may include information indicating that the cross-RAT PC5 scheduling is possible (e.g., “cross-RAT PC5 control authorized” indication). The AMF **215** may transmit the registration accept message to the base station **210** and the terminal **110a**, in step **913** and step **915**. The AMF **215** may transmit to the base station **210** the registration accept message including the information indicating that cross-RAT PC5 scheduling is possible. The AMF **215** may transmit the registration accept message including the information indicating that the cross-RAT PC5 scheduling is possible to the terminal **110a** via the base station **210**.

(187) The base station **210** receiving the registration accept message from the AMF **215** may identify that the terminal **110a** is authorized to use the cross-RAT PC5 scheduling function based

on the information included in the registration accept message.

(188) The terminal **110a** receiving the registration accept message from AMF **215** may identify that the terminal **110a** is authorized to use the cross-RAT PC5 scheduling function based on the information included in the registration accept message.

(189) In some embodiments, the terminal **110a** authorized by the AMF **215** for the cross-RAT PC5 scheduling may operate in-coverage in the NR PC5 and the LTE PC5. Hence, it may store the LTE PC5 resource pool information received from the base station **210** in step **1401** of FIG. **14**, and use it for the LTE PC5 communication.

(190) In addition, in some embodiments, the terminal authorized by the AMF **215** for the cross-RAT PC5 scheduling may perform the procedure of FIG. **10**. In step **1003**, the terminal **110a** may determine to transmit the resource to the LTE PC5. In step **1005**, the terminal **110a** may transmit the LTE PC5 resource request message to the base station **210** (e.g., the gNB). The base station **210** may determine that the terminal **110a** is a terminal authorized to make the LTE PC5 resource request, based on the information (e.g., the information indicating that cross-RAT PC5 scheduling is possible) received from the AMF **215** in step **1001**. Thus, the base station **210** may allocate the LTE PC5 resource to the terminal **110a** in step **1007**. The terminal **110a** allocated the LTE PC5 resource from base station **210**, may transmit data to the LTE PC5 in step **1009**.

(191) In addition, in some embodiments, the terminal not authorized from AMF **215** for the cross-RAT PC5 scheduling may operate in-coverage in the NR PC5, and operate out-of-coverage in the LTE PC5.

(192) In addition, in some embodiments, the terminal not authorized from the AMF **215** for the cross-RAT PC5 scheduling may not perform the procedure of FIG. **10**, in the LTE PC5 communication.

(193) In addition, in some embodiments, the terminal authorized from the AMF **215** for cross-RAT PC5 scheduling may perform the procedure of FIG. **10**. The terminal **110a** may determine to transmit the resource to the LTE PC5 in step **1003**. In step **1005**, the terminal **110a** may transmit the LTE PC5 resource request message to the base station **210**. Based on the information (e.g., the information indicating that the cross-RAT PC5 scheduling is possible) received from the AMF **215** in step **1001**, the base station **210** may determine that the terminal **110a** is a terminal not authorized for the LTE PC5 resource request. Accordingly, the base station **210** may not allocate the LTE PC5 resource to the terminal **110a** in step **1007**. The terminal **110a** not allocated the LTE PC5 resource from the base station **210**, may transmit data to the LTE PC5 in the out-of-coverage mode in step **1009**.

(194) The terminal according to various embodiments of the present disclosure may acquire the function information supported by the network. The terminal **110a** may register in the EPC system by performing the procedure shown in FIG. **8A**.

(195) The terminal **110a** may transmit an initial attach request message to the MME **125** via the base station **120** (e.g., the eNB), in step **801** and step **803** of FIG. **8**. The initial attach request message may include the UE capability information in the form of UE network capability. For example, the UE capability information may include PC5 capability for V2X (e.g., LTE PC5 only, NR PC5 only, both LTE and NR PC5), cross-RAT PC5 capability, and so on.

(196) The MME **125** receiving the initial attach request message of step **803**, may obtain the UE subscription information from the HSS **135** in step **805**. The UE subscription information may include at least one or more information of "V2X services authorized" indication, UE-PC5-AMBR per PC5 RAT, and cross-RAT PC5 control authorization.

(197) The MME **125** may determine information to be included in the initial context setup request/initial attach response message based on at least one of the initial attach request message received from the terminal **110a** and the UE subscription information received from the HSS **135**. For example, if the terminal **110a** supports the NR PC5 function or the cross-RAT PC5 capability, and the UE subscription information includes the cross-RAT PC5 authorization information, the

MME 125 may determine to provide the terminal 110a with the cross-RAT PC5 scheduling function. The MME 125 may include information indicating that the cross-RAT PC5 scheduling is possible (e.g., “cross-RAT PC5 control authorized” indication) in the initial context setup request/initial Attach response message. The MME 125 may transmit the initial context setup request/initial attach response message to the base station 120 and the terminal 110a in step 809 through step 811. The MME 125 may transmit the initial context setup request/initial attach response message to the base station 120 in step 809. The MME 125 may transmit the initial context setup request/initial attach response message to the terminal 110a via the base station 120 in step 809.

(198) The base station 120 receiving the initial context setup request message from the MME 125 may identify that the terminal 110a is authorized to use the cross-RAT PC5 scheduling function based on the information included in the initial context setup request message.

(199) The terminal 110a receiving the initial attach response message from the MME 125 may identify that the terminal 110a is authorized to use the cross-RAT PC5 scheduling function based on the information included in the initial attach response message.

(200) In addition, in some embodiments, the terminal authorized by the MME for the cross-RAT PC5 scheduling may operate in-coverage in the NR PC5 and the LTE PC5. Accordingly, the NR PC5 resource pool information received from the base station 120 in step 1401 of FIG. 14 may be stored, and used for the NR PC5 communication.

(201) In addition, in some embodiments, the terminal authorized by the MME for the cross-RAT PC5 scheduling may perform the procedure of FIG. 11. The terminal 110a may determine to transmit the resource to the NR PC5 in step 1103. The terminal 110a may transmit an NR PC5 resource request message to the base station 120 in step 1105. Based on the information (e.g., information indicating that the cross-RAT PC5 scheduling is possible) received from the MME 125 in step 1101, the base station 120 may determine that the terminal 110a is the terminal authorized to make the NR PC5 resource request. Hence, the base station 120 may allocate the NR PC5 resource to the terminal 110a in step 1107. The terminal 110a allocated the NR PC5 resource from the base station 120 may transmit data to the NR PC5 in step 1109.

(202) In addition, in some embodiments, the terminal not authorized by the MME for the cross-RAT PC5 scheduling may operate in-coverage in the LTE PC5, and operate out-of-coverage in the NR PC5.

(203) In addition, in some embodiments, the terminal not authorized by the MME for the cross-RAT PC5 scheduling may not perform the procedure of FIG. 11, in the NR PC5 communication.

(204) In addition, in some embodiments, the terminal not authorized by the MME 125 for the cross-RAT PC5 scheduling may perform the procedure of FIG. 11. The terminal 110a may determine to transmit the resource to the NR PC5 in step 1103. The terminal 110a may transmit the NR PC5 resource request message to the base station 120 in step 1105. Based on the information (e.g., information indicating that the cross-RAT PC5 scheduling is possible) received from the MME 125 in step 1101, the base station 120 may determine that the terminal 110a is the terminal not authorized for the NR PC5 resource request. Thus, the base station 120 may not allocate the NR PC5 resource to the terminal 110a in step 1107. The terminal 110a not allocated the NR PC5 resource from the base station 120 may transmit data to the NR PC5 in the out-of-coverage mode, in step 1109.

(205) FIG. 3 has illustrated the interworking structure of the 5G system and the EPC system according to various embodiments of the present disclosure. The AMF 215 and the MME 125 may be connected through the N26 interface.

(206) The terminal 110a according to various embodiments of the present disclosure may be registered in the 5G system (e.g., 5GC) and connected to the AMF 215. The AMF 215 may store the UE capability information (e.g., including at least one of PC5 capability for V2X (LTE PC5 only, NR PC5 only, both LTE and NR PC5), cross-RAT PC5 capability) received from the terminal

in step **907** of FIG. **9A**. The AMF **215** may store the UE capability information as UE context. The AMF **215** may store the UE subscription information or the policy information received from the UDM **235** or the PCF **240** in step **909** through step **911** of FIG. **9A**. The AMF **215** may store the UE subscription information or the policy information as the UE context. The UE subscription information or the policy information may include at least one or more information of PC5 authorized information (whether the UE is authorized to perform V2X communication over PC5 reference point as Vehicle UE, Pedestrian UE, or both, including for LTE PC5 and for NR PC5), “V2X service authorized” indication, UE-PC5-AMBR per PC5 RAT, cross-RAT PC5 control authorization, PLMN list (the list of the PLMNs where the UE is authorized to perform V2X communication over PC5 reference point). For each PLMN in the list, the RAT(s) over which the UE is authorized to perform V2X communications over PC5 reference point, and PC5 QoS parameters are included.

(207) According to various embodiments of the present disclosure, the terminal **110a** registered in the 5G system and connected to the AMF **215** may move to the EPC system (e.g., handover, idle mode mobility, connected mode mobility, etc.). Hence, the AMF **215** may transmit the UE context stored in the AMF **215** to the MME **125** through the N26 interface. The UE context may include the UE capability information, the UE subscription information, the policy information, and the like. The MME **125** may store and use the UE context received from the AMF **215**.

(208) For example, the UE context may include information indicating that the terminal **110a** may use the LTE PC5 function and the NR PC5 function, and that the terminal **110a** is a terminal authorized for the cross-RAT PC5 control. Based on the UE context, the MME **125** may determine to provide the UE **110a** with the cross-RAT PC5 scheduling function.

(209) The AMF **215** may determine UE context information to transmit to the MME **125**. For example, the AMF **215** may identify whether the PLMN ID of the MME **125** is included in the PLMN list of the UE context. If the PLMN list includes the PLMN ID of the MME **125**, the AMF **215** may include the PLMN list in the UE context information transmitted to the MME **125**. If the PLMN list does not include the PLMN ID of the MME **125**, the AMF **215** may not include the PLMN list in the UE context information transmitted to the MME **125**.

(210) To transmit the UE context to the MME **125**, the AMF **215** may convert the UE context of the 5G format to the UE context of the EPS format. For example, the UE context converted into the EPS format may be referred to as mapped EPS UE contexts or mapped EPS UE contexts for V2X. The AMF **215** may transmit the UE context converted into the EPS format to the MME **125** through the N26 interface. The UE context converted into the EPS format may be included in a message such as relocation request, relocation complete notification, and context response and transmitted to the MME **125**.

(211) The MME **125** may include information (e.g., “cross-RAT PC5 control authorized” indication) indicating that the cross-RAT PC5 scheduling is possible in a message (e.g., initial context setup request, handover request, etc.) transmitted to the base station **120** to which the UE **110a** is connected. The base station **120** receiving the message from the MME **125** may identify that the terminal **110a** is authorized to use the cross-RAT PC5 scheduling function based on the information included in the message.

(212) The MME **125** may include the information (e.g., “cross-RAT PC5 control authorized” indication) indicating that the cross-RAT PC5 scheduling is possible in a message (e.g., TAU accept, etc.) transmitted to the terminal **110a**. The terminal **110a** receiving the message from the MME **125** may identify that the terminal **110a** is authorized to use the cross-RAT PC5 scheduling function based on the information included in the message.

(213) The terminal **110a** according to various embodiments of the present disclosure may be registered in the EPC system and connected to the MME **125**. The MME **125** may store the UE capability information (e.g., PC5 capability for V2X (LTE PC5 only, NR PC5 only, both LTE and NR PC5), cross-RAT PC5 capability) received from the terminal in step **803** of FIG. **8A**. The MME

may store the UE capability information as the UE context. The MME **125** may store the UE subscription information received from the HSS **135** in step **807** of FIG. **8A**. The MME **125** may store the UE subscription information as the UE context. The UE subscription information may include at least one or more information of PC5 authorized information (whether the UE is authorized to perform V2X communication over PC5 reference point as Vehicle UE, Pedestrian UE, or both, including for LTE PC5 and for NR PC5), “V2X service authorized” indication, UE-PC5-AMBR per PC5 RAT (including UE-PC5-AMBR for LTE PC5 and UE-PC5-AMBR for NR PC5), cross-RAT PC5 control authorization, PLMN list (the list of the PLMNs where the UE is authorized to perform V2X communication over PC5 reference point). For each PLMN in the list, the RAT(s) over which the UE is authorized to perform V2X communications over PC5 reference point, and PC5 QoS parameters are included.

(214) According to various embodiments of the present disclosure, the terminal **110a** registered in the EPC system and connected to the MME **125** may move to the 5G system (e.g., handover, idle mode mobility, connected mode mobility, etc.). Hence, the MME **125** may transmit the UE context stored in the MME **125** to the AMF **215** through the N26 interface. The UE context may include the UE capability information, the UE subscription information, the policy information, and the like.

(215) The MME **125** may determine UE context information to transmit to the AMF **215**. For example, the MME **125** may identify whether the PLMN ID of the AMF **215** is included in the PLMN list of the UE context. If the PLMN list includes the PLMN ID of AMF **215**, the MME **125** may include the PLMN list in the UE context information transmitted to the AMF **215**. If the PLMN list does not include the PLMN ID of the AMF **215**, the MME **125** may not include the PLMN list in the UE context information transmitted to the AMF **215**.

(216) The MME **125** may transmit the UE context of the EPS format to the AMF **215** through the N26 interface. The UE context of the EPS format may be included in a message such as forward relocation request, forward relocation complete notification ack, and context response and transmitted to the AMF **215**.

(217) The AMF **215** may store and use the UE context received from the MME **125**.

(218) For example, the AMF **215** may convert the UE context of the EPS format received from the MME **125** to the UE context of the 5G format. The UE context may include information indicating that the terminal **110a** may use the LTE PC5 function and the NR PC5 function, and that the terminal **110a** is authorized for the cross-RAT PC5 control. Based on the UE context, the AMF **215** may determine to provide the cross-RAT PC5 scheduling function to the UE **110a**.

(219) The AMF **215** may include information (e.g., “cross-RAT PC5 control authorized” indication) indicating that the cross-RAT PC5 scheduling is possible in a message (e.g., initial context setup request, handover request, etc.) transmitted to the base station **210** connected to the terminal **110a**. The base station **210** receiving the message from the AMF **215** may identify that the terminal **110a** is authorized to use the cross-RAT PC5 scheduling function based on the information included in the message.

(220) The AMF **215** may include the information (e.g., “cross-RAT PC5 control authorized” indication) indicating that the cross-RAT PC5 scheduling is possible in a message (e.g., registration accept, etc.) transmitted to the terminal **110a**. The terminal **110a** receiving the message from the AMF **125** may identify that the terminal **110a** is authorized to use the cross-RAT PC5 scheduling function based on the information included in the message.

(221) Various embodiments of the present disclosure are related to the cross-RAT PC5 control capability of the terminal. The UE capability information of the terminal may include information (e.g., information element (IE)) for indicating whether the cross-RAT PC5 control capability is supported or not. The cross-RAT PC5 control capability may indicate the capability that the eNB **120** may configure the information for the NR PC5 in the LTE RAT and provide it to the terminal, or configure the information for the LTE PC5 in the NR RAT and provide it to the terminal. The

policy information delivered by the policy related entity (e.g., the PCF **240**) to the authorization management entity (e.g., the AMF **215**) may include at least one or more information of “V2X services authorized” indication, UE-PC5-AMBR per PC5 RAT, cross-RAT PC5 control authorization.

(222) In various embodiments of the present disclosure, the message (e.g., a registration accept message) between the terminal, the base station (e.g., the eNB **120** or the gNB **120**), and the core network entity (e.g., the AMF **215**) may include the information (e.g., “cross-RAT PC5 control authorized” indication) indicating that the cross-RAT PC5 scheduling is possible. The terminal may perform the LTE PC5 communication in the in-coverage mode or the out-of-coverage mode, depending on whether it is authorized by the AMF for the cross-RAT PC5 scheduling. In addition, the terminal may perform the NR PC5 communication in the in-coverage mode or the out-of-coverage mode, depending on whether it is authorized by the MME for the cross-RAT PC5 scheduling.

(223) In some embodiments, the base station may determine whether the terminal is authorized for the cross-RAT PC5 scheduling based on the information obtained from the AMF. The base station may determine whether to allocate the resource for the LTE PC5 communication to the terminal based on the determination. If the terminal is not authorized by the AMF for the cross-RAT PC5 scheduling, the base station may not allocate the resource for the LTE PC5 communication to the terminal. The terminal may perform the LTE PC5 communication in the out-of-coverage mode. If the terminal is authorized by the AMF for the cross-RAT PC5 scheduling, the base station may allocate the resource for the LTE PC5 communication to the terminal. The terminal may perform the LTE PC5 communication in the in-coverage mode.

(224) In addition, in some embodiments, the base station may determine whether the terminal is authorized for the cross-RAT PC5 scheduling based on information obtained from the MME. The base station may determine whether to allocate the resource for the NR PC5 communication to the terminal based on the determination. If the terminal is not authorized by the MME for the cross-RAT PC5 scheduling, the base station may not allocate the resource for the NR PC5 communication to the terminal. The terminal may perform the NR PC5 communication in the out-of-coverage mode. If the terminal is authorized by the MME for the cross-RAT PC5 scheduling, the base station may allocate the resource for the LTE NR communication to the terminal. The terminal may perform the NR PC5 communication in the in-coverage mode.

(225) The methods according to the embodiments described in the claims or the specification of the disclosure may be implemented in software, hardware, or a combination of hardware and software.

(226) As for the software, a computer-readable storage medium storing one or more programs (software modules) may be provided. One or more programs stored in the computer-readable storage medium may be configured for execution by one or more processors of an electronic device. One or more programs may include instructions for controlling the electronic device to execute the methods according to the embodiments described in the claims or the specification of the disclosure.

(227) Such a program (software module, software) may be stored to a random access memory, a non-volatile memory including a flash memory, a read only memory (ROM), an electrically erasable programmable ROM (EEPROM), a magnetic disc storage device, a compact disc (CD)-ROM, digital versatile discs (DVDs) or other optical storage devices, and a magnetic cassette. Alternatively, it may be stored to a memory combining part or all of those recording media. In addition, a plurality of memories may be included.

(228) Also, the program may be stored in an attachable storage device accessible via a communication network such as Internet, Intranet, local area network (LAN), wide LAN (WLAN), or storage area network (SAN), or a communication network by combining these networks. Such a storage device may access a device which executes an embodiment of the present disclosure through an external port. In addition, a separate storage device on the communication network may

access the device which executes an embodiment of the present disclosure.

(229) In the specific embodiments of the present disclosure, the elements included in the disclosure are expressed in a singular or plural form. However, the singular or plural expression is appropriately selected according to a proposed situation for the convenience of explanation, the disclosure is not limited to a single element or a plurality of elements, the elements expressed in the plural form may be configured as a single element, and the elements expressed in the singular form may be configured as a plurality of elements.

(230) Meanwhile, while the specific embodiment has been described in the explanations of the present disclosure, it will be noted that various changes may be made therein without departing from the scope of the disclosure. Thus, the scope of the disclosure is not limited and defined by the described embodiment and is defined not only the scope of the claims as below but also their equivalents.

Claims

1. A method performed by a mobile management entity (MME), the method comprising: receiving an attach request message or a tracking area update (TAU) message comprising user equipment (UE) capability information, from a UE; receiving a message comprising subscription information comprising quality of service (QoS) parameters, a UE-PC5-aggregated maximum bit rate (AMBR) for long term evolution (LTE) PC5, and a UE-PC5-AMBR for new radio (NR) PC5, from a home subscription server (HSS); and transmitting the QoS parameters, the UE-PC5-AMBR for LTE PC5, and the UE-PC5-AMBR for NR PC5 included in the received subscription information through an initial context setup request message or a handover request message to a base station (BS), wherein the UE capability information indicates whether the UE supports new radio (NR) PC5, and wherein the QoS parameters indicate 5G quality of service indicator (5QI) for vehicle to everything (V2X).
2. The method of claim 1, wherein the subscription information further includes an indication indicating V2X service authorization per PC5 radio access technology (RAT), and wherein the indication indicating V2X service authorization per PC5 RAT is included in the initial context setup request message or the handover request message.
3. The method of claim 2, further comprising: receiving V2X related information from an access and mobility management function (AMF), wherein the V2X related information comprises information indicating V2X services authorized per PC5 RAT, a UE-PC5-AMBR per PC5 RAT, and PC5 QoS parameters.
4. A mobile management entity (MME), the MME comprising: at least one transceiver; and at least one processor, wherein the at least one processor is configured to: receive an attach request message or a tracking area update (TAU) message comprising user equipment (UE) capability information, from a UE, receive a message comprising subscription information comprising quality of service (QoS) parameters, a UE-PC5-aggregated maximum bit rate (AMBR) for long term evolution (LTE) PC5, and a UE-PC5-AMBR for new radio (NR) PC5, from a home subscription server (HSS), and transmit the QoS parameters, the UE-PC5-AMBR for LTE PC5, and the UE-PC5-AMBR for NR PC5 included in the received subscription information through an initial context setup request message or a handover request message to a base station (BS), wherein the UE capability information indicates whether the UE supports new radio (NR) PC5, and wherein the QoS parameters indicate 5G quality of service indicator (5QI) for vehicle to everything (V2X).
5. The MME of claim 4, wherein the subscription information further includes an indication indicating V2X service authorization per PC5 radio access technology (RAT), and wherein the indication indicating V2X service authorization per PC5 RAT is included in the initial context setup request message or the handover request message.
6. The MME of claim 5, wherein the at least one processor is further configured to receive V2X related information from an access and mobility management function (AMF), and wherein the

V2X related information comprises information indicating V2X services authorized per PC5 RAT, a UE-PC5-AMBR per PC5 RAT and PC5 QoS parameters.
