

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402463
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Li; Xin Xing et al.

Display device connecting light emitting elements to first and second contact electrodes via third contact electrode

Abstract

A display device includes at least one first and second electrodes extending in a first direction, at least one first and second light emitting elements disposed therebetween, a first contact electrode partially covering the first electrode and contacting a first end of the first light emitting element, a second contact electrode partially covering the second electrode and contacting a third end of the second light emitting element, and a third contact electrode disposed between the first and second contact electrodes and contacting a second end of the first light emitting element and a fourth end of the second light emitting element, in which a distance between the first and second electrodes is greater than a longitudinal length of at least one of the first and second light emitting elements, and the first and second light emitting elements are connected in series between the first and second electrodes.

Inventors: Li; Xin Xing (Suwon-Si, KR), Kong; Tae Jin (Suwon-Si, KR), Lee; Hee Keun (Suwon-Si, KR), Cho; Hyun Min (Seoul, KR), Tae; Chang Il (Seoul, KR)

Applicant: Samsung Display Co. Ltd. (Yongin-si, KR)

Family ID: 1000008778484

Assignee: SAMSUNG DISPLAY CO., LTD. (Yongin-si, KR)

Appl. No.: 17/502829

Filed: October 15, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220037397 A1	Feb. 03, 2022

Foreign Application Priority Data

KR	10-2018-0089839	Aug. 01, 2018
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc US 16461780 US 11152424 WO PCT/KR2019/000530 20190114 child-doc US 17502829

Publication Classification

Int. Cl.: **H10H29/14** (20250101); **H10H20/831** (20250101); **H10H20/84** (20250101); **H10H20/856** (20250101); **H10H20/857** (20250101)

U.S. Cl.:

CPC **H10H29/142** (20250101); **H10H20/831** (20250101); **H10H20/84** (20250101); **H10H20/857** (20250101); H10H20/856 (20250101)

Field of Classification Search

CPC: H01L (27/156); H01L (33/38); H01L (33/44); H01L (33/62); H01L (33/60); H10H (29/142); H10H (20/831); H10H (20/84); H10H (20/857); H10H (20/856)

USPC: 257/88

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9229236	12/2015	Hino et al.	N/A	N/A
9287242	12/2015	Shibata et al.	N/A	N/A
9570425	12/2016	Do	N/A	N/A
10211418	12/2018	Im et al.	N/A	N/A
10825393	12/2019	Kim	N/A	G09G 3/3233
2008/0251381	12/2007	Shibata et al.	N/A	N/A
2011/0254043	12/2010	Negishi et al.	N/A	N/A
2012/0146066	12/2011	Tischler et al.	N/A	N/A
2017/0179192	12/2016	Zhang et al.	N/A	N/A
2018/0019369	12/2017	Cho et al.	N/A	N/A
2018/0111829	12/2017	Sam et al.	N/A	N/A
2018/0122837	12/2017	Kang	N/A	H01L 33/38
2018/0174519	12/2017	Kim	N/A	H01L 27/156
2018/0175009	12/2017	Kim et al.	N/A	N/A
2018/0287010	12/2017	Sung	N/A	B82B 3/0066
2019/0181301	12/2018	Kim	N/A	H01L 33/44
2019/0385991	12/2018	Kim	N/A	H01L 25/167

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107623013	12/2017	CN	N/A
112437986	12/2020	CN	N/A
2011-103435	12/2010	JP	N/A

2011-205060	12/2010	JP	N/A
10-2013-0080412	12/2012	KR	N/A
10-2014-0085331	12/2013	KR	N/A
10-1436123	12/2013	KR	N/A
10-2016-0059574	12/2015	KR	N/A
10-2018-0007376	12/2017	KR	N/A
10-2018-0009015	12/2017	KR	N/A
10-2018-0072909	12/2017	KR	N/A
10-2018-0081378	12/2017	KR	N/A

OTHER PUBLICATIONS

International Search Report corresponding to International Application No. PCT/KR2019/000530 dated Apr. 30, 2019. cited by applicant

Written Opinion corresponding to International Application No. PCT/KR2019/000530, dated Apr. 30, 2019. cited by applicant

Primary Examiner: Jones; Eric W

Attorney, Agent or Firm: KILE PARK REED & HOUTTEMAN PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION(S) (1) This is a continuation application of U.S. patent application Ser. No. 16/461,780, filed May 16, 2019, now U.S. Pat. No. 11,152,424 issued Oct. 19, 2021, the disclosure of which is incorporated herein by reference in its entirety. U.S. patent application Ser. No. 16/461,780 claims priority to and benefit of International Application No. PCT/KR2019/000530, filed on Jan. 14, 2019, which claims under 35 U.S.C. § 119 (a) and 365(b) priority to and benefits of Korean Patent Application No. 10-2018-0089839, filed on Aug. 1, 2018 in the Korean Intellectual Property Office, the entire contents of which are incorporated herein by reference.

BACKGROUND

Field

(1) Exemplary embodiments of the invention relate generally to a display device, and, more specifically, to a display device including an inorganic light emitting diode array.

Discussion of the Background

(2) The importance of a display device has increased with the development of multimedia. Accordingly, various types of display devices such as an organic light emitting display (OLED) and a liquid crystal display (LCD) have been used.

(3) A display device is a device for displaying an image, and includes a display panel, such as a light emitting display panel or a liquid crystal panel. The light emitting display panel may include light emitting elements, such as light emitting diodes (LEDs). Light emitting diodes (LEDs) may include an organic light emitting diode (OLED) using an organic material as a fluorescent material, and an inorganic light emitting diode using an inorganic material as a fluorescent material.

(4) An organic light emitting diode (OLED) can be manufactured through a relatively simple manufacturing process, and its usage of an organic material as a fluorescent material provides flexible characteristics. However, the organic material is known to be vulnerable to high-temperature driving environments and have a relatively low efficiency with blue light.

(5) On the other hand, an inorganic light emitting diode generally has more durability even in high-

temperature environments and higher efficiency with blue light than an organic light emitting diode because it uses an inorganic semiconductor as a fluorescent material. Further, various processes for simplifying the manufacture of an inorganic light emitting diode have been developed, such as transfer methods using dielectrophoresis (DEP). As such, research on inorganic light emitting diodes having improved durability and efficiency than organic light emitting diodes is being continued.

(6) The above information disclosed in this Background section is only for understanding of the background of the inventive concepts, and, therefore, it may contain information that does not constitute prior art.

SUMMARY

(7) Display devices constructed according to exemplary embodiments of the invention are capable of reducing the capacity of a driving transistor, improving voltage distribution efficiency, and reducing the power loss due to wire resistance by forming the wirings of light emitting elements in series.

(8) Additional features of the inventive concepts will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the inventive concepts.

(9) According to an aspect of the invention, a display device includes at least one first electrode and at least one second electrode extending in a first direction and spaced apart from each other in a second direction different from the first direction, at least one first light emitting element and at least one second light emitting element disposed between the first electrode and the second electrode, a first contact electrode partially covering the first electrode and contacting a first end of the first light emitting element, a second contact electrode spaced apart from the first contact electrode, partially covering the second electrode, and contacting a third end of the second light emitting element and a third contact electrode disposed between the first contact electrode and the second contact electrode and contacting a second end of the first light emitting element and a fourth end of the second light emitting element, in which a distance between the first electrode and the second electrode is greater than a longitudinal length of at least one of the first light emitting element and the second light emitting element, and the first light emitting element and the second light emitting element are connected in series between the first electrode and the second electrode.

(10) The distance between the first electrode and the second electrode may be less than about 2 times of the longitudinal length of at least one of the first light emitting element and the second light emitting element.

(11) A width of the third contact electrode may be less than the distance between the first contact electrode and the second contact electrode, and be greater than the longitudinal length of at least one of the first light emitting element and the second light emitting element.

(12) The first light emitting element may include a plurality of first light emitting elements spaced apart from each other in the first direction, and the second light emitting element may include a plurality of second light emitting elements spaced apart from each other in the first direction.

(13) The second end of at least one of the first light emitting elements and the fourth end of at least one of the second light emitting elements face each other.

(14) The first light emitting elements and the second light emitting elements may be aligned to face each other along the second direction.

(15) The second end of the first light emitting elements and the fourth end of the second light emitting elements may be substantially aligned along the first direction, and at least one of the first light emitting elements and at least one of the second light emitting elements may be disposed to partially overlap each other in the first direction.

(16) Each of the first light emitting element and the second light emitting element may include a first conductive semiconductor layer, an active layer, and a second conductive semiconductor layer, one of the first conductive semiconductor layer and the second conductive semiconductor layer

may be a p-type conductive semiconductor layer, and the other one thereof is an n-type conductive semiconductor layer, and the second end of the first light emitting element and the fourth end of the second light emitting element may have different types of conductive semiconductor layers.

(17) According to another aspect of the invention, a display device includes a first conductive electrode layer including a first electrode and a second electrode spaced apart from the first electrode, a first light emitting element having one end electrically connected to the first electrode and a second light emitting element having one end electrically connected to the second electrode, a second conductive electrode layer including a first contact electrode disposed on the first electrode and contacting the one end of the first light emitting element and a second contact electrode disposed on the second electrode and contacting the one end of the second light emitting element and a third conductive electrode layer including a third contact electrode contacting the other end of the first light emitting element and the other end of the second light emitting element, wherein the first conductive electrode layer is in contact with the second conductive electrode layer, and the first light emitting element and the second light emitting element are connected in series between the first electrode and the second electrode.

(18) The other end of the first light emitting element and the other end of the second light emitting element, which are in contact with the third conductive electrode layer face each other.

(19) The display device may further include a first insulating layer disposed to cover a part of the first conductive electrode layer, wherein at least a part of the first insulating layer may be in contact with the second conductive electrode layer and the third conductive electrode layer.

(20) The second conductive electrode layer and the third conductive electrode layer may be disposed on substantially the same layer.

(21) The display device may further include a second insulating layer disposed between the second conductive electrode layer and the third conductive electrode layer.

(22) At least a part of a lower surface of the insulating layer may be in contact with the second conductive electrode layer, and at least a part of an upper surface thereof may be in contact with the third conductive electrode layer.

(23) At least a part of a lower surface of the insulating layer may be in contact with the third conductive electrode layer, and at least a part of an upper surface thereof may be in contact with the second conductive electrode layer.

(24) According to the other aspect of the invention, a display device includes a first electrode connected to a thin film transistor, a second electrode connected to a common power supply wiring, at least one first light emitting diode having one end electrically connected to the first electrode, at least one second light emitting diode having one end electrically connected to the second electrode, a first contact electrode partially covering the first electrode and contacting the one end of the first light emitting diode, a second contact electrode partially covering the second electrode and contacting the one end of the second light emitting diode and a floating electrode disposed between the first contact electrode and the second contact electrode and contacting the other end of the first light emitting diode and the other end of the second light emitting diode, wherein the first light emitting diode and the second light emitting diode are connected in series between the first electrode and the second electrode.

(25) The first contact electrode, the second contact electrode, and the floating electrode may extend substantially in a first direction, and the first light emitting diode and the second light emitting diode may be longitudinally disposed along a second direction intersecting the first direction.

(26) Each of the first light emitting diode and the second light emitting diode may include a first conductive semiconductor layer, an active layer, and a second conductive semiconductor layer, any one of the first conductive semiconductor layer and the second conductive semiconductor layer may be a p-type conductive semiconductor layer, and the other one thereof is an n-type conductive semiconductor layer, the first conductive semiconductor layer of the first light emitting diode may be electrically connected to the first electrode, the second conductive semiconductor layer of the

first light emitting diode may be electrically connected to the floating electrode, the first conductive semiconductor layer of the second light emitting diode may be electrically connected to the floating electrode, and the second conductive semiconductor layer of the second light emitting diode may be electrically connected to the second electrode.

(27) The first electrode and the second electrode may be spaced apart from each other, and a distance between the first electrode and the second electrode may be less than about 2 times of a longitudinal length of at least one of the first light emitting diode and the second light emitting diode.

(28) The longitudinal length of at least one of the first light emitting diode and the second light emitting diode may be about 3 μm to 6 μm .

(29) Accordingly, display devices constructed according to exemplary embodiments of the invention may include light emitting elements, both ends of each which are electrically connected to a first electrode and a third contact electrode or are electrically connected to a third contact electrode and a second electrode. The light emitting elements may be partially connected in series, thereby improving voltage distribution efficiency, the capacity design of a thin film transistor, and the loss due to the wire resistance, in the driving of the display device.

(30) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the invention, and together with the description serve to explain the inventive concepts.

(2) FIG. 1 is a plan view of an exemplary embodiment of a display device constructed according to the principles of the invention.

(3) FIG. 2 is an enlarged view of portion A of FIG. 1.

(4) FIG. 3 is an equivalent circuit diagram of one representative pixel of the display device of FIG. 1 according to an exemplary embodiment.

(5) FIG. 4 is an equivalent circuit diagram of one representative pixel of a display device according to another exemplary embodiment.

(6) FIG. 5 is a cross-sectional view taken along lines I-I', and of FIG. 1.

(7) FIG. 6 is a schematic perspective view of a light emitting element according to an exemplary embodiment.

(8) FIGS. 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, and 21 are plan views and cross-sectional views schematically illustrating a method of manufacturing a display device according to an exemplary embodiment.

(9) FIG. 22 is a cross-sectional view of a display device according to another exemplary embodiment.

(10) FIGS. 23, 24, 25, 26, and 27 are plan views and cross-sectional views illustrating some of the steps of a method of manufacturing the display device of FIG. 22 according to an exemplary embodiment.

(11) FIG. 28 is a cross-sectional view of a display device according to still another exemplary embodiment.

(12) FIGS. 29 and 30 are cross-sectional views illustrating some of the steps of a method of manufacturing the display device of FIG. 28 according to an exemplary embodiment.

DETAILED DESCRIPTION

(13) In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of various exemplary embodiments or implementations of the invention. As used herein “embodiments” and “implementations” are interchangeable words that are non-limiting examples of devices or methods employing one or more of the inventive concepts disclosed herein. It is apparent, however, that various exemplary embodiments may be practiced without these specific details or with one or more equivalent arrangements. In other instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessarily obscuring various exemplary embodiments. Further, various exemplary embodiments may be different, but do not have to be exclusive. For example, specific shapes, configurations, and characteristics of an exemplary embodiment may be used or implemented in another exemplary embodiment without departing from the inventive concepts.

(14) Unless otherwise specified, the illustrated exemplary embodiments are to be understood as providing exemplary features of varying detail of some ways in which the inventive concepts may be implemented in practice. Therefore, unless otherwise specified, the features, components, modules, layers, films, panels, regions, and/or aspects, etc. (hereinafter individually or collectively referred to as “elements”), of the various embodiments may be otherwise combined, separated, interchanged, and/or rearranged without departing from the inventive concepts.

(15) The use of cross-hatching and/or shading in the accompanying drawings is generally provided to clarify boundaries between adjacent elements. As such, neither the presence nor the absence of cross-hatching or shading conveys or indicates any preference or requirement for particular materials, material properties, dimensions, proportions, commonalities between illustrated elements, and/or any other characteristic, attribute, property, etc., of the elements, unless specified. Further, in the accompanying drawings, the size and relative sizes of elements may be exaggerated for clarity and/or descriptive purposes. When an exemplary embodiment may be implemented differently, a specific process order may be performed differently from the described order. For example, two consecutively described processes may be performed substantially at the same time or performed in an order opposite to the described order. Also, like reference numerals denote like elements.

(16) When an element, such as a layer, is referred to as being “on,” “connected to,” or “coupled to” another element or layer, it may be directly on, connected to, or coupled to the other element or layer or intervening elements or layers may be present. When, however, an element or layer is referred to as being “directly on,” “directly connected to,” or “directly coupled to” another element or layer, there are no intervening elements or layers present. To this end, the term “connected” may refer to physical, electrical, and/or fluid connection, with or without intervening elements. Further, the D1-axis, the D2-axis, and the D3-axis are not limited to three axes of a rectangular coordinate system, such as the x, y, and z-axes, and may be interpreted in a broader sense. For example, the D1-axis, the D2-axis, and the D3-axis may be perpendicular to one another, or may represent different directions that are not perpendicular to one another. For the purposes of this disclosure, “at least one of X, Y, and Z” and “at least one selected from the group consisting of X, Y, and Z” may be construed as X only, Y only, Z only, or any combination of two or more of X, Y, and Z, such as, for instance, XYZ, XYY, YZ, and ZZ. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(17) Although the terms “first,” “second,” etc. may be used herein to describe various types of elements, these elements should not be limited by these terms. These terms are used to distinguish one element from another element. Thus, a first element discussed below could be termed a second element without departing from the teachings of the disclosure.

(18) Spatially relative terms, such as “beneath,” “below,” “under,” “lower,” “above,” “upper,” “over,” “higher,” “side” (e.g., as in “sidewall”), and the like, may be used herein for descriptive purposes, and, thereby, to describe one elements relationship to another element(s) as illustrated in

the drawings. Spatially relative terms are intended to encompass different orientations of an apparatus in use, operation, and/or manufacture in addition to the orientation depicted in the drawings. For example, if the apparatus in the drawings is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary term “below” can encompass both an orientation of above and below. Furthermore, the apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations), and, as such, the spatially relative descriptors used herein interpreted accordingly.

(19) The terminology used herein is for the purpose of describing particular embodiments and is not intended to be limiting. As used herein, the singular forms, “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. Moreover, the terms “comprises,” “comprising,” “includes,” and/or “including,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, components, and/or groups thereof, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. It is also noted that, as used herein, the terms “substantially,” “about,” and other similar terms, are used as terms of approximation and not as terms of degree, and, as such, are utilized to account for inherent deviations in measured, calculated, and/or provided values that would be recognized by one of ordinary skill in the art.

(20) Various exemplary embodiments are described herein with reference to sectional and/or exploded illustrations that are schematic illustrations of idealized exemplary embodiments and/or intermediate structures. As such, variations from the shapes of the illustrations as a result, for example, of manufacturing techniques and/or tolerances, are to be expected. Thus, exemplary embodiments disclosed herein should not necessarily be construed as limited to the particular illustrated shapes of regions, but are to include deviations in shapes that result from, for instance, manufacturing. In this manner, regions illustrated in the drawings may be schematic in nature and the shapes of these regions may not reflect actual shapes of regions of a device and, as such, are not necessarily intended to be limiting.

(21) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure is a part. Terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and should not be interpreted in an idealized or overly formal sense, unless expressly so defined herein.

(22) FIG. 1 is a plan view of an exemplary embodiment of a display device constructed according to the principles of the invention.

(23) A display device **10** may include at least one region defined as a pixel PX. A plurality of pixels PX may be arranged in a display unit of the display device **10** to emit light having a specific wavelength band to the outside of the display device **10**. FIG. 1 exemplarily illustrates three pixels PX1, PX2, and PX3, but the inventive concepts are not limited to a particular number of pixels PX in the display device **10**. FIG. 1 also exemplarily shows that a plurality of pixels PX are arranged only in one direction, for example, in a first direction D1, however, in some exemplary embodiments, the plurality of pixels PX may be arranged in a second direction D2 intersecting the first direction D1. Further, at least one or more pixels PX shown in FIG. 1 may be formed together as one pixel PX. In some exemplary embodiments, the pixels may be arranged substantially in a vertical direction (or second direction D2) or in a zigzag form, rather than being arranged in parallel in the first direction D1 as shown in FIG. 1.

(24) The display device **10** may include a light emitting area where light emitting elements are arranged to emit light of a specific color, and a non-light emitting area defined as an area other than the light emitting area. The non-light emitting area may be covered by at least one member so as not to be seen from the outside. The non-light emitting area may be provided with various members for driving the light emitting elements arranged in the light emitting area. For example, the non-

light emitting area may be provided with a wiring for applying an electrical signal to the light emitting area, a circuit unit, a driving unit, and the like. However, the inventive concepts are not limited thereto.

(25) Each of the plurality of pixels PX may include at least one light emitting element **350** emitting light having a specific wavelength band to display a color. Light emitted from the light emitting element **350** may be viewed from the outside of the display device **10**. In an exemplary embodiment, light emitting elements **350** emitting light of different colors from each other, for example, red, green, and blue colors, may be provided for each of the pixels PX to display colors different from each other. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, pixels PX displaying different colors from each other may include light emitting elements **350** emitting light of the same color (for example, blue), and the colors of the respective pixels PX may be displayed by providing a wavelength conversion layer or a color filter on a light emitting path. In another exemplary embodiment, adjacent pixels PX may emit light of the same color.

(26) Referring to FIG. **1**, the display device **10** may include a plurality of electrodes **310** and **320** and a plurality of light emitting elements **350**. At least a part of the each of the electrodes **310** and **320** may be disposed in each pixel PX, electrically connected to the light emitting elements **350**, and apply electrical signals to the light emitting elements such that the light emitting elements may emit light of a specific color.

(27) Further, at least a part of the each of the electrodes **310** and **320** may be used to form an electric field in the pixel PX in order to align the light emitting elements **350**. More particularly, aligning the light emitting elements **350** emitting light of different colors from each other in the plurality of pixels PX may require an accurate alignment of the light emitting elements **350** for each pixel PX. According to an exemplary embodiment, when the light emitting elements **350** are aligned using dielectrophoresis, a solution containing the light emitting elements may be applied onto the display device **10**, and an AC power may be applied to the solution to form an electric field, and thus, the light emitting elements **350** may be aligned by a dielectrophoretic force.

(28) The plurality of electrodes **310** and **320** may include a first electrode **310** and a second electrode **320**. In an exemplary embodiment, the first electrode **310** may be a pixel electrode that may be individually provided for each pixel PX, and the second electrode **320** may be a common electrode connected in common along the plurality of pixels PX. Any one of the first electrode **310** and the second **320** may be an anode electrode of the light emitting element **350**, and the other thereof may be a cathode electrode of the light emitting element **350**, or vice versa.

(29) The first electrode **310** and the second electrode **320** may include electrode stem portion **310S** and **320S** substantially extending in a first direction D1 and electrode branch portions **310B** and **320B** substantially extending in a second direction D2 intersecting the first direction D1 and branched from the electrode stem portions **310S** and **320S**, respectively.

(30) More specifically, the first electrode **310** may include a first electrode stem portion **310S** substantially extending in the first direction D1 and at least one first electrode branch portion **310B** branched from the first electrode stem portion **310S** and substantially extending in the second direction D2. One end of the first electrode stem portion **310S** may be connected to a signal application pad, and the other end thereof may substantially extend in the first direction D1 but electrically separated between the pixels PX. The signal application pad may be connected to the display device or an external power source to apply an electrical signal to the first electrode stem portion **310S** or apply an AC power thereto at the time of aligning the light emitting elements **350**.

(31) The first electrode stem portion **310S** of any one pixel may be disposed on substantially the same line extending from the first electrode stem portion **310S** of a neighboring pixel in the same row, such as in the first direction D1. In particular, both ends of the first electrode stem portion **310S** of one pixel may be spaced apart from those of adjacent pixels PX, whereas the first electrode stem portion **310S** of the neighboring pixel may be aligned along an imaginary line extending from

the first electrode stem portion **310S** of the one pixel PX. Such arrangement of the first electrode stem portions **310S** may be obtained by, for example, forming one stem electrode during a manufacturing process, aligning the light emitting elements **350**, and then disconnecting the stem electrode using a laser. Accordingly, the first electrode stem portion **310S** disposed in each pixel PX may apply different electrical signals from each other to the respective pixels PX, and the respective pixels PX may be driven separately from each other.

(32) The first electrode branch portion **310B** may be branched from at least a part of the first electrode stem portion **310S** and substantially extend in the second direction D2. The first electrode branch portion **310B** may be spaced apart from the second electrode stem portion **320S** disposed to face the first electrode stem portion **310S**. In particular, one end of the first electrode branch portion **310B** may be connected to the first electrode stem portion **310S**, and the other end thereof may be disposed in the pixel PX while being spaced apart from the second electrode stem portion **320S**. Since the first electrode branch portion **310B** is connected to the first electrode stem portion **310S** that may be individually provided for each pixel P, the first electrode branch portion **310B** of each pixel PX may receive different electrical signals from each other.

(33) Further, the first electrode branch portion **310B** may be spaced apart from an opposing, second electrode branch portion **320B**, which will be described in more detail later. FIG. 1 exemplarily shows that two first electrode branch portions **310B** are spaced apart from each other and the second electrode branch portion **320B** is disposed between the two first electrode branch portions **310B**, however, the inventive concepts are not limited thereto, and in some exemplary embodiments, a plurality of first electrode branch portions **310B** may be provided. In this case, the plurality of first electrode branch portions **310B** are alternately arranged with the plurality of second electrode branch portions **320B**, and a third contact electrode **363** may be disposed between the first electrode branch portion **310B** and the second electrode branch portion.

(34) The second electrode **320** may include a second electrode stem portion **320S** substantially extending in the first direction D1, spaced apart from the first electrode stem portion **310S** and facing the first electrode stem portion **310S**, and at least one second electrode branch portion **320B** branched from the second electrode stem portion **320S**, substantially extending in the second direction D2, spaced apart from the first electrode branch portion **310B** and facing the first electrode branch portion **310B**. One end of the second electrode stem portion **320S** may be connected to a signal application pad, and the other end of the second electrode stem portion **320S** may extend to the plurality of pixels PX adjacent in the first direction D1. In particular, the second electrode stem portion **320S** may be electrically connected between the pixels PX. Accordingly, both ends of the second electrode stem portion **320S** of any one pixel may be connected to one end of the second electrode stem portion **320S** of a neighboring pixel PX between the respective pixels PX, so that the same electrical signal may be applied to the respective pixels PX.

(35) The second electrode branch portion **320B** may be branched from at least a part of the second electrode stem portion **320S** and substantially extend in the second direction D2. The second electrode branch portion **320B** may be spaced apart from the first electrode stem portion **310S**. More particularly, one end of the second electrode branch portion **320B** may be connected to the second electrode stem portion **320S**, and the other end thereof may be disposed in the pixel PX while being spaced apart from the first electrode stem portion **310S**. Since the second electrode branch portion **320B** is connected to the second electrode stem portion **320S** electrically connected to each pixel P, the second electrode branch portion **320B** in each pixel PX may receive the same electrical signal.

(36) The second electrode branch portion **320B** may be spaced apart from the first electrode branch portion **310B** and face the first electrode branch portion **310B**. Here, since the first electrode stem portion **310S** and the second electrode stem portion **320S** are spaced apart from each other and face each other in opposite directions with respect to the center of each pixel PX, the first electrode branch portion **310B** and the second electrode branch portion **320B** may substantially extend in

directions opposite to each other. In particular, the first electrode branch portion **310B** substantially extends in one direction of the second direction **D2**, and the second electrode branch portion **320B** substantially extends in the other direction of the second direction **D2**, so that one ends of the respective branch portions may be disposed in directions opposite to each other with respect to the center of the pixel **PX**. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, the first electrode stem portion **310S** and the second electrode stem portion **320S** may be spaced apart from each other in the same direction with respect to the center of the pixel **PX**. In this case, the first electrode branch portion **310B** and the second electrode branch portion **320B**, respectively branched from the first electrode stem portion **310S** and the second electrode stem portion **320S**, may extend substantially in the same direction.

(37) FIG. 1 exemplarily shows that one pixel **PX** includes one second electrode branch portion **320B**, however, the inventive concepts are not limited thereto, and a plurality of second electrode branch portions **320B** may be disposed in one pixel **PX**.

(38) A plurality of light emitting elements **350** may be arranged between the first electrode branch portion **310B** and the second electrode branch portion **320B**. The plurality of light emitting elements **350** may include at least one first light emitting element **350a** having one end electrically connected to the first electrode branch portion **310B** and at least one second light emitting element **350b** having one end electrically connected to the second electrode branch portion **320B**. The other end of the first light emitting element **350a** and the other end of the second light emitting element **350b** may be electrically connected to the third contact electrode **363**, which will be described in more detail later.

(39) The plurality of first light emitting elements **350a** and the second light emitting elements **350b** may be spaced from each other substantially in the second direction **D2** and may be aligned substantially parallel to each other. Further, the plurality of first light emitting elements **350a** may be spaced apart from the second light emitting devices **350b** with respect to the third contact electrode **363**.

(40) An interval between the light emitting elements **350** is not particularly limited. In some exemplary embodiments, some of the plurality of light emitting elements **350** may be arranged adjacent to each other to form a group, and others of the plurality of light emitting elements **350** may be arranged to be spaced apart from each other to form another group. In other exemplary embodiments, the plurality of light emitting elements **350** may be substantially arranged and aligned in one direction with non-uniform density.

(41) The interval between adjacent first light emitting elements **350a** may not be constant, and an interval between adjacent second light emitting elements **350b** may also not be constant.

Accordingly, any one of the first light emitting elements **350a** may not be aligned with any one of the second light emitting elements **350b** in the first direction **D1**. In some exemplary embodiments, the second light emitting element **350b** may be disposed to partially overlap a region where the first light emitting elements are aligned along the second direction **D2**.

(42) Although FIG. 1 exemplarily shows that the light emitting elements **350** are aligned in a direction in which the first electrode branch portion **310B** and the second electrode portion **320B** are spaced apart from each other, and are spaced apart from each other so as not to overlap each other in the second direction **D2**, but the inventive concepts are not limited thereto. In some exemplary embodiments, some of the light emitting elements may partially overlap each other in a direction to which the first electrode branch portion **310B** and the second electrode branch portion **320B** are extended, and are spaced apart from each other so as not to be in direct contact with each other.

(43) The plurality of first light emitting elements **350a** may be connected to each other in parallel by electrically connecting one end of each of the first light emitting elements **350a** to the first electrode branch portion **310B**. The plurality of second light emitting elements **350b** may be connected to each other in parallel by electrically connecting one end of each of the second light

emitting elements **350b** to the second electrode branch portion **320B**. The first light emitting elements **350a** and the second light emitting elements **350b** may be connected in series with each other by bringing the other end of each of the first light emitting elements **350a** and the other end of each of the second light emitting elements **350b** into contact with the third contact electrode **363**. (44) In this manner, even if any of the first light emitting elements **350a** is shorted and causes another first light emitting element **350a** connected thereto in parallel to not emit light, the second light emitting elements **350b** connected with each other in parallel and connected to the first light emitting elements **350a** in series may receive electrical signals. As such, even if any one of the light emitting elements **350** in the pixel PX is disconnected, the defective light emission of the pixel PX can be prevented by another light emitting element **350**.

(45) Further, when the first light emitting element **350a** and the second light emitting element **350b** are electrically connected to each other in series, a voltage applied to the light emitting elements **350** may be increased as compared to when the light emitting elements **350** are connected to each other in parallel, which may increase voltage distribution efficiency. Further, the amount of current required to drive the light emitting elements connected in series may be decreased, so that the capacity of a driving transistor for applying a current to the light emitting elements **350** may be decreased, and the power loss from a power supply wiring may be decreased. Accordingly, in the driving the display device **10** constructed according to the principles of the invention, voltage efficiency and/or light emitting efficiency may be improved.

(46) At least one contact electrode **360** may be disposed in a region between the first electrode branch portion **310B** and the second electrode branch portion **320B**, and may be disposed on each of the electrode branch portions **310B** and **320B**.

(47) A plurality of contact electrodes **360** may be arranged to substantially extend in the second direction D2, and be spaced apart from each other in the first direction D1. The contact electrodes **360** may be in contact with at least one end of each of the light emitting elements **350**, and some of the contact electrodes **360** may be in contact with the first electrode **310** and the second electrode **320** to receive electrical signals. As such, the contact electrodes **360** may transmit the electrical signals received from the first electrode **310** or the second electrode **320** to the light emitting elements **350**.

(48) More specifically, the contact electrode **360** may be disposed on the electrode branch portions **310B** and **320B** to partially cover the electrode branch portions **310B** and **320B**. The contact electrode **360** may include a first contact electrode **361** and a second contact electrode **362**, each contacting one end of the light emitting element **350**, and a third contact electrode **363** disposed between the first electrode branch portion **310B** and the second electrode branch portion **320B** and contacting the other end of the light emitting element **350**.

(49) The first contact electrode **361** may be disposed on the first electrode branch portion **310B**, and may be in contact with one end of the first light emitting element **350a** electrically connected to the first electrode **310**. The second contact electrode **362** may be disposed on the second electrode branch portion **320B**, and may be in contact with one end of the second light emitting element **350b** electrically connected to the second electrode **320**. The third contact electrode **363** may be in contact with the other end of each of the first light emitting element **350a** and the second light emitting element **350b**.

(50) In some exemplary embodiments, one end of the light emitting element **350** electrically connected to the first electrode branch portion **310B** or the second electrode branch portion **320B** may include a conductive material layer doped with an n-type dopant or a p-type dopant, and the other end of the light emitting element **350** contacting the third contact electrode **363** may include a conductive material layer doped with a p-type dopant or an n-type dopant, without being limited thereto.

(51) The first contact electrode **361** and the second contact electrode **362** may be disposed on the first electrode branch **310B** and the second electrode branch **320B** to partially cover the first

electrode branch **310B** and the second electrode branch **320B**, respectively. As shown in FIG. 1, the first contact electrode **361** and the second contact electrode **362** may be disposed to substantially extend along the second direction **D2**, spaced apart from each other to face each other. One end of each of the first contact electrode **361** and the second contact electrode **362** may expose at least a portion of one end of each of the electrode branch portions **310B** and **320B**, respectively. Further, the other end of each of the first contact electrode **361** and the second contact electrode **362** may be spaced apart from the electrode stem portions **310S** and **320S**, respectively. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, the other end of each of the first contact electrode **361** and the second contact electrode **362** may cover each of the electrode branch portions **310B** and **320B**, respectively.

(52) The third contact electrode **363** may be disposed between the first contact electrode **361** and the second contact electrode **362**. The third contact electrode **363** may be extended and spaced apart from each of the first contact electrode **361** and the second contact electrode **362**. More particularly, the third contact electrode **363** may be disposed in parallel to the first contact electrode **361** and the second contact electrode **362**, and may have substantially the same shape as each of the first contact electrode **361** and the second contact electrode **362**.

(53) The third contact electrode **363** may substantially extend in the second direction **D2**, but both ends thereof in the second direction **D2** may be spaced apart from the first electrode stem portion **310S** and the second electrode stem portion **320S**, respectively. In particular, the third contact electrode **363** may be electrically separated from the electrode stem portions **310S** and **320S**. In an exemplary embodiment, the third contact electrode **363** may be a floating electrode to which an electrical signal is not directly applied from the electrode stem portions **310S** and **320S**. However, the inventive concepts are not limited thereto.

(54) The third contact electrode **363** may form a different conductive electrode layer from the first contact electrode **361** and the second contact electrode **362**. For example, when a first conductive electrode layer **CEL1** (see FIG. 5), in which the first electrode **310** and the second electrode **320** are disposed, a second conductive electrode layer **CEL2**, in which the first contact electrode **361** and the second contact electrode **362** are disposed, and a third conductive electrode layer **CEL3**, in which the third contact electrode **363** is disposed, are defined, the second conductive electrode layer **CEL2** may be disposed on the first conductive electrode layer **CEL1** and may partially be in contact with the first conductive electrode layer **CEL1**. The third conductive electrode layer **CEL3** may be disposed on the second conductive electrode layer **CEL2**, with an insulating layer (see FIG. 5) disposed therebetween to electrically insulate the third conductive electrode layer **CEL3** from the second conductive electrode layer **CEL2**. However, the inventive concepts are not limited thereto, and details thereof will be described later with reference to cross-sectional views.

(55) As described above, the light emitting element **350** may be aligned between the first electrode branch **310B** and the second electrode branch **320B**, and both ends of the light emitting element **350** may be in contact with at least one of the contact electrodes **360**. The arrangement of the first electrode branch portion **310B** and the second electrode branch portion **320B**, the width of the contact electrodes **360**, particularly, the third contact electrode **363**, and the like may be variously changed such that the light emitting element **350** may be in contact with the electrodes **310** and **320** and the contact electrode **360**.

(56) FIG. 2 is an enlarged view of portion A of FIG. 1.

(57) Referring to FIG. 2, one end of the first light emitting element **350a** and one end of the second light emitting element **350b** may be electrically connected to the first electrode branch portion **310B** and the second electrode branch portion **320B** through the first contact electrode **361** and the second contact electrode **362**, respectively. The third contact electrode **363** may contact the other end of the first light emitting element **350a** and the other end of the second light emitting element **350b**.

(58) The distance **11** between one side of the first electrode branch portion **310B** and the opposing

side of the second electrode branch portion **320B** may be greater than the length h of the long axis of the light emitting element **350**. The first light emitting elements **350a** and the second light emitting elements **350b** may be aligned substantially in the first direction **D1** between the first electrode branch portion **310B** and the second electrode branch portion **320B**. When the first light emitting elements **350a** and the second light emitting elements **350b** are aligned along the same row extending in the first direction **D1**, the first light emitting elements **350a** and the second light emitting elements **350b** may be partially spaced apart from each other so as not to be in direct contact with each other.

(59) As such, the distance **11** between the opposing sides of the first electrode branch portion **310B** and the second electrode branch portion **320B** may be greater than the length h of the long axis of the light emitting element **350**. For example, the distance **11** may be about 1 time to about 2 times of the length h of the long axis of the light emitting element **350**. For example, the length h of the long axis of the light emitting element **350** may be about $3.0\ \mu\text{m}$ to about $6.0\ \mu\text{m}$, and the distance **11** between the opposing sides of the first electrode branch portion **310B** and the second electrode branch portion **320B** may be about $6.0\ \mu\text{m}$ to about $12.0\ \mu\text{m}$. However, the inventive concepts are not limited thereto.

(60) The width $d1$ of the first contact electrode **361** and a width $d2$ of the second contact electrode **362** may each be wider than the widths of the corresponding electrode branches **310B** and **320B**. As such, even if one end of the light emitting element **350** is not directly connected to the first electrode branch portion **310B** or the second electrode branch portion **320B**, it may be electrically connected to the first electrode branch portion **310B** or the second electrode branch portion **320B** through the contact electrode **360**. The third contact electrode **363** may have a predetermined width in contact with both one end of the first light emitting element **350a** and opposing end of the second light emitting element **350b**.

(61) The width $d3$ of the third contact electrode **363** may be greater than the length h of the long axis of the light emitting element **350**, but may be less than a distance **12** between one side of the first contact electrode **361** and the opposing side of the second contact electrode **362**. When the width $d3$ of the third contact electrode **363** is too narrow, the third contact electrode **363** may not be in contact with the end of any one light emitting element **350** when the first light emitting element **350a** and the second light emitting element **350b** are spaced apart from each other. In contrast, when the width $d3$ of the third contact electrode **363** is too wide, the third contact electrode **363** may be in direct contact with the first contact electrode **361** or the second contact electrode **362**. As such, the width $d3$ of the third contact electrode **363** may be greater than the length h of the long axis of the light emitting element **350**, but shorter than the distance **12** between the opposing sides of the first contact electrode **361** and the second contact electrode **362**.

(62) However, in some exemplary embodiments, the width $d3$ of the third contact electrode **363** may be greater than the distance **12** between the opposing sides of the first contact electrode **361** and the second contact electrode **362**. Referring to a cross-sectional view of the display device **10** to be described later, the first contact electrode **361** and the second contact electrode **362** may form a second conductive electrode layer **CEL2**, and the third contact electrode **363** may form a third conductive electrode layer **CEL3**. Here, the second conductive electrode layer **CEL2** and the third conductive electrode layer **CEL3** may be disposed on different layers with the third insulating layer **530** interposed therebetween. In this case, at least a part of the third contact electrode **363** may overlap the first contact electrode **361** and the second contact electrode **362** in a cross-sectional view.

(63) Referring back to FIG. **1**, the first electrode stem portion **310S** and the second electrode stem portion **320S** may be electrically connected to the thin film transistor **120** (see FIG. **5**) or the power supply wiring **161** to be described later through contact holes, for example, a first contact hole **CNTD** and a second contact hole **CNTS**, respectively. FIG. **1** exemplarily shows that the contact holes on the first electrode stem portion **310S** and the second electrode stem portion **320S** are

disposed for each pixel PX, but the inventive concepts are not limited thereto. As described above, since the second electrode stem portion **320S** may extend to be electrically connected to an adjacent pixel PX, in some exemplary embodiments, the second electrode stem portion **320S** may be electrically connected to a thin film transistor through one contact hole.

(64) FIG. 3 is an equivalent circuit diagram of one representative pixel of the display device of FIG. 1 according to an exemplary embodiment. FIG. 3 exemplarily shows an *i*th and *j*th pixel PX(*i,j*) among a plurality of pixels PX in the display device **10**.

(65) Referring to FIG. 3, the *i*th and *j*th pixel PX(*i,j*) of the display device **10** may include an *i*th scan line SL_{*i*}, a *j*th data line DL_{*j*}, a first switching element TR_{**1**}, a second switching element TR_{**2**}, and a light emitting element **350**, and a storage capacitor C_{st}.

(66) The first switching element TR_{**1**} may be electrically connected to the *i*th scan line SL_{*i*}, the *j*th data line DL_{*j*}, and the second switching element TR_{**2**}. In an exemplary embodiment, the first switching element TR_{**1**} and the second switching element TR_{**2**} may be three terminal elements, such as thin film transistors. Hereinafter, the first switching element TR_{**1**} and the second switching element TR_{**2**} will be described with reference to thin film transistors.

(67) The first switching element TR_{**1**} may include a control electrode electrically connected to the *i*th scan line SL_{*i*}, a first electrode electrically connected to the *j*th data line DL_{*j*}, and a second electrode electrically connected to a control electrode of the second switching element TR_{**2**}.

(68) The second switching element TR_{**2**} may include a control electrode electrically connected to the second electrode of the first switching element TR_{**1**}, a first electrode electrically connected to a first driving voltage line VDDL to which a first driving voltage VDD is provided, and a second electrode electrically connected to the light emitting element **350**.

(69) The storage capacitor C_{st} may include a first electrode electrically connected to the second electrode of the first switching element TR_{**1**}, and a second electrode electrically connected to the first driving voltage line VDDL to which the first driving voltage VDD is provided.

(70) The first switching element TR_{**1**} may be turned on according to a scan signal S_{*i*} received from the *i*th scan line SL_{*i*}, and may supply a data signal D_{*j*} received from the *j*th data line DL_{*j*} to the storage capacitor C_{st}. The storage capacitor C_{st} may charge a voltage difference between a voltage of the received data signal D_{*j*} and a first driving voltage VDD. The second switching device TR_{**2**} may control the amount of driving current supplied to the light emitting element **350** according to the voltage charged in the storage capacitor C_{st}. In particular, the first switching element TR_{**1**} may be a switching transistor, and the second switching element TR_{**2**} may be a driving transistor.

(71) One end of the light emitting element **350** connected to the first electrode **310** may be electrically connected to the second electrode of the second switching element TR_{**2**}. The light emitting element **350** may receive current through the second electrode of the second switching element TR_{**2**}. The other end of the light emitting element **350** connected to the second electrode **320** may be electrically connected to a second driving voltage line VSSL. As such, the light emitting element **350** may receive a second driving voltage VSS. The first driving voltage VDD may have a higher voltage level than the second driving voltage VSS.

(72) As shown in FIG. 3, the plurality of light emitting elements **350** may be connected in series between the second switching element TR_{**2**} and the second driving voltage line VSSL to which second driving voltage VSS is provided. As shown in the drawing, the inventive concepts are not limited to a particular number of the light emitting elements connected in series. In this manner, the voltage distribution efficiency between the light emitting elements **350** and the first driving voltage VDD and second driving voltage VSS necessary for driving the respective light emitting elements **350** can be improved. Since the current flowing through the second switching element TR_{**2**} decreases as the light emitting elements **350** are connected in series, determining the capacity of the thin film transistor may become easier. Further, since the current flowing through the second switching element TR_{**2**} is decreased, the power loss in the power supply line or the power loss in the first driving voltage line VDDL and the second driving voltage line VSSL may be reduced.

(73) Although FIG. 3 exemplarily illustrates that the display device **10** includes two switching elements, that is, the first switching element **TR1** and the second switching element **TR2**, and one capacitor, that is, the storage capacitor **Cst**, the inventive concepts are not limited thereto. For example, in some exemplary embodiments, the display device **10** may include a greater number of switching elements. Hereinafter, an equivalent circuit diagram of a display device according to another exemplary embodiment will be described with reference to FIG. 4.

(74) FIG. 4 is an equivalent circuit diagram of one representative pixel of a display device according to another exemplary embodiment. FIG. 4 exemplarily shows an *i*th and *j*th pixel **PX(i,j)**.

(75) Referring to FIG. 4, the *i*th and *j*th pixel **PX(i,j)** of the display device **10** may include an *i*th scan line **SLi**, an *i*-1th scan line **SLi-1**, a *j*th data line **DLj**, an *i*th light emission control line **Ei**, first to seventh switching elements **TR1** to **TR7**, a light emitting element **350**, and a storage capacitor **Cst**.

(76) One end of the light emitting element **350** connected to the first electrode **310** may be electrically connected to one electrode of the fifth switching element **TR5** and one electrode of the seventh switching element **TR7**. The light emitting element **350** may receive current through the one electrode of the fifth switching element **TR5** and the one electrode of the seventh switching element **TR7**. The other end of the light emitting element **350** connected to the second electrode **320** may be electrically connected to a second driving voltage line **VSSL** to receive a second driving voltage **VSS**.

(77) One electrode of the first switching element **TR1** is electrically connected to a first node **N1**, and the other electrode of the first switching element **TR1** is electrically connected to a second node **N2**. The gate electrode of the first switching element **TR1** is electrically connected to one end of the storage capacitor **Cst** through a third node **N3**. The first switching element **TR1** is electrically connected to one end of the light emitting element **350** via the fifth switching element **TR5**. The first switching element **TR1** may receive a data signal of the *j*th data line **DLj** according to the switching operation of the second switching element **TR2** and supply current to the light emitting element **350**.

(78) One electrode of the second switching element **TR2** is electrically connected to the *j*th data line **DLj**, and the other electrode of the second switching element **TR2** is electrically connected to the first node **N1**. The gate electrode of the second switching element **TR2** is electrically connected to the *i*th scan line **SLi**. The other electrode of the second switching element **TR2** electrically connected to the first node **N1** is electrically connected to the first driving voltage line **VDDL** through the fourth switching element **TR4**. The first switching element **TR1** may be turned on by a scan signal of the *i*th scan line **SLi** to transfer the data signal transferred to the *j*th data line **DLj** to the first switching element **TR1**.

(79) One electrode of the third switching element **TR3** is electrically connected to the second node **N2**, and the other electrode of the third switching element **TR3** is electrically connected to the third node **N3**. The gate electrode of the third switching element **TR3** is electrically connected to the *i*th scan line **SLi**. When the scan signal is applied to the *i*th scan line **SLi**, the third switching element **TR3** is turned on to be diode-connected with the first switching element **TR1**.

(80) One electrode of the fourth switching element **TR4** is electrically connected to the first driving voltage line **VDDL** to be supplied with the first driving voltage **VDD**. The other electrode of the fourth switching element **TR4** is electrically connected to the first node **N1**, and the gate electrode of the fourth switching element **TR4** is electrically connected to the *i*th light emission control line **Ei**.

(81) One electrode of the fifth switching element **TR5** is electrically connected to the second node **N2**, and the other electrode of the fifth switching element **TR5** is electrically connected to the one end of the light emitting element **350**. The gate electrode of the fifth switching element **TR5** is electrically connected to the *i*th light emission control line **Ei**. The fourth switching element **TR4** and the fifth switching element **TR5** are simultaneously turned on in response to the light emission

control signal received through the *i*th light emission control line *E_i*, and thus, the first driving voltage VDD is transferred to the light emitting element **350** as driving current.

(82) One electrode of the sixth switching element **TR6** is electrically connected to the third node **N3**, and the other electrode of the sixth switching element **TR6** is supplied with an initialization power *Vinit*. The gate electrode of the sixth switching element **TR6** is electrically connected to the *i*-1th scan line *SL_{i-1}*. When scan signals are sequentially supplied to the scan lines *SL*, the scan signal may be supplied to the *i*th scan line *SL_i* after the scan signal is supplied to the *i*-1th scan line *SL_{i-1}*. The sixth switching element **TR6** is turned on in response to the scan signal transferred through the *i*-1th scan line *SL_{i-1}* to transfer the initialization power *Vinit* to the gate electrode of the first switching element **TR1**, so as to initialize the voltage of the gate electrode of the first switching element **TR1**.

(83) One electrode of the seventh switching element **TR7** is electrically connected to the one end of the light emitting element **350**, and the other electrode of the seventh switching element **TR7** is supplied with the initialization power *Vinit*. The gate electrode of the seventh switching element **TR7** is electrically connected to the *i*-1th scan line *SL_{i-1}*. The seventh switching element **TR7** may be turned on in response to the scan signal to initialize one end electrode of the light emitting element **350**.

(84) The first to seventh switching elements **TR1** to **TR7** may be thin film transistors. In each of the first to seventh switching elements **TR1** to **TR7**, one end thereof may be any one of a source electrode and a drain electrode, and the other end may be the other one of a source electrode and a drain electrode.

(85) One end of the storage capacitor *Cst* may be electrically connected to the first driving voltage line *VDDL* to be supplied with the first driving voltage VDD, and the other end thereof may be electrically connected to the third node **N3**.

(86) Hereinafter, more specific structures of a plurality of members disposed on the display device **10** will be described with reference to FIG. 5.

(87) FIG. 5 is a cross-sectional view taken along lines I-I', and of FIG. 1. Although FIG. 5 exemplarily shows a cross-section of only one pixel **PX**, other pixels **PX** may have substantially the same structure. FIG. 5 shows a cross-section across one end and the other end of one light emitting element **350**.

(88) Referring to FIGS. 1 to 5, the display device **10** may include a substrate **110**, thin film transistors **120** and **140** disposed on the substrate **110**, electrodes **310** and **320** disposed on the thin film transistors **120** and **140**. The thin film transistors may include a first thin film transistor **120** and a second thin film transistor **140**, which may be a driving transistor and a switching transistor, respectively. Each of the thin film transistors **120** and **140** may include an active layer, a gate electrode, a source electrode, and a drain electrode. The first electrode **310** may be electrically connected to the drain electrode of the first thin film transistor **120**.

(89) The substrate **110** may be an insulating substrate. The substrate **110** may be made of an insulating material, such as glass, quartz, or a polymer resin. Examples of the polymer resin may include polyethersulphone (PES), polyacrylate (PA), polyarylate (PAR), polyetherimide (PEI), polyethylene naphthalate (PEN), polyethylene terephthalate (PET), polyphenylene sulfide (PPS), polyallylate, polyimide (PI), polycarbonate (PC), cellulose triacetate (CAT), cellulose acetate propionate (CAP), and combinations thereof. The substrate **110** may be a rigid substrate, but in some exemplary embodiments, the substrate **110** may be a flexible substrate capable of bending, folding, rolling, or the like.

(90) A buffer layer **115** may be disposed on the substrate **110**. The buffer layer **115** may prevent the diffusion of impurity ions and the penetration of moisture or external air, and may provide a planar surface. The buffer layer **115** may include silicon nitride, silicon oxide, or silicon oxynitride.

(91) A semiconductor layer is disposed on the buffer layer **115**. The semiconductor layer may include a first active layer **126** of the first thin film transistor **120**, a second active layer **146** of the

second thin film transistor **140**, and an auxiliary layer **163**. The semiconductor layer may include polycrystalline silicon, monocrystalline silicon, an oxide semiconductor, or the like.

(92) A first gate insulating layer **170** is disposed on the semiconductor layer. The first gate insulating layer **170** covers the semiconductor layer. The first gate insulating layer **170** may function as a gate insulating film of the thin film transistor. The first gate insulating layer **170** may include silicon oxide, silicon nitride, silicon oxynitride, aluminum oxide, tantalum oxide, hafnium oxide, zirconium oxide, titanium oxide, or the like. These compounds may be used alone or in combination with each other.

(93) A first conductive layer is disposed on the first gate insulating layer **170**. The first conductive layer may include a first gate electrode disposed on the first active layer **126** of the first thin film transistor **120**, a second gate electrode disposed on the second active layer **146** of the second thin film transistor **140**, and a power supply wiring **161** disposed on the auxiliary layer **163**, with the first gate insulating layer **170** therebetween. The first conductive layer may include at least one metal selected from molybdenum (Mo), aluminum (Al), platinum (Pt), palladium (Pd), silver (Ag), magnesium (Mg), gold (Au), nickel (Ni), neodymium (Nd), iridium (Ir), chromium (Cr), calcium (Ca), titanium (Ti), tantalum (Ta), tungsten (W), and copper (Cu). The first conductive layer may have a single-layer or a multilayer structure.

(94) A second gate insulating layer **180** is disposed on the first conductive layer. The second gate insulating layer **180** may be an interlayer insulating film. The second gate insulating layer **180** may include an inorganic insulating material, such as silicon oxide, silicon nitride, silicon oxynitride, hafnium oxide, aluminum oxide, titanium oxide, tantalum oxide, or zinc oxide.

(95) A second conductive layer is disposed on the second gate insulating layer **180**. The second conductive layer includes a capacitor electrode **128** disposed on the first gate electrode **121** with the second gate insulating layer **180** therebetween. The capacitor electrode **128** may form a storage capacitor together with the first gate electrode **121**.

(96) The second conductive layer may include at least one metal selected from molybdenum (Mo), aluminum (Al), platinum (Pt), palladium (Pd), silver (Ag), magnesium (Mg), gold (Au), nickel (Ni), neodymium (Nd), iridium (Ir), chromium (Cr), calcium (Ca), titanium (Ti), tantalum (Ta), tungsten (W), and copper (Cu).

(97) An interlayer insulating layer **190** is disposed on the second conductive layer. The interlayer insulating layer **190** may be an interlayer insulating film. Moreover, the interlayer insulating layer **190** may provide a planar surface. The interlayer insulating layer **190** may include an organic insulating material such as polyacrylate resin, epoxy resin, phenolic resin, polyamide resin, polyimide resin, unsaturated polyester resin, polyphenyleneether resin, polyphenylenesulfide resin, or benzocyclobutene (BCB).

(98) A third conductive layer is disposed on the interlayer insulating layer **190**. The third conductive layer includes a first drain electrode **123** and a first source electrode **124** of the first thin film transistor **120**, a second drain electrode **143** and a second source electrode **144** of the second thin film transistor **140**, and a power supply electrode **162** disposed on the power supply wiring **161**.

(99) Each of the first source electrode **124** and the first drain electrode **123** may be electrically connected to the first active layer **126** through a first contact hole **129** penetrating the interlayer insulating layer **190** and the second gate insulating layer **180**. Each of the second source electrode **144** and the second drain electrode **143** may be electrically connected to the second active layer **146** through a second contact hole **149** penetrating the interlayer insulating layer **190** and the second gate insulating layer **180**. The power supply electrode **162** may be electrically connected to the power supply wiring **161** through a third contact hole **169** penetrating the interlayer insulating layer **190** and the second gate insulating layer **180**.

(100) The third conductive layer may include at least one metal selected from molybdenum (Mo), aluminum (Al), platinum (Pt), palladium (Pd), silver (Ag), magnesium (Mg), gold (Au), nickel

(Ni), neodymium (Nd), iridium (Ir), chromium (Cr), calcium (Ca), titanium (Ti), tantalum (Ta), tungsten (W), and copper (Cu). The third conductive layer may have a single-layer or a multilayer structure. For example, the third conductive layer may have a laminate structure of Ti/Al/Ti, Mo/Al/Mo, Mo/AlGe/Mo, or Ti/Cu.

(101) An insulating substrate layer **300** is disposed on the third conductive layer. The insulating substrate layer **300** may include an organic insulating material, such as polyacrylate resin, epoxy resin, phenolic resin, polyamide resin, polyimide resin, unsaturated polyester resin, polyphenyleneether resin, polyphenylenesulfide resin, or benzocyclobutene (BCB). The surface of the insulating substrate layer **300** may be flat.

(102) A plurality of partition walls **410** and **420** may be disposed on the insulating substrate layer **300**. The plurality of partition walls **410** and **420** are spaced apart from each other and face each other in each of the pixels PX. The first electrode **310** and the second electrode **320** may be disposed on the partition walls **410** and **420** spaced apart from each other, for example, a first partition wall **410** and a second partition wall **420**. Referring to FIGS. **1** and **5**, FIG. **1** exemplarily shows each pixel PX includes three partition walls, more specifically, two first partition walls **410** and one second partition wall **420**, and thus, two first electrodes **310** and one second electrode **320** are disposed thereon. FIG. **5** exemplarily shows a cross-sectional view of one first partition wall **410** and one second partition wall **420**, and the arrangement structure thereof may be equally applied to other first partition walls **410** not shown in FIG. **5**.

(103) However, the inventive concepts are not limited thereto, and a greater number of partition walls **410** and **420** may be disposed in one pixel PX. For example, a greater number of partition walls **410** and **420** may be disposed in one pixel PX, and thus, a greater number of first and second electrodes **210** and **220** may be disposed. The partition walls **410** and **420** may include at least one first partition wall **410** on which the first electrode **210** is disposed, and at least one second partition wall **420** on which the second electrode **220** is disposed. In this case, the first partition wall **410** and the second partition wall **420** may be spaced apart from and opposing each other, and the plurality of partition walls may be alternately arranged in one direction. In some exemplary embodiments, two first partition walls **410** may be spaced apart from each other, and one second partition wall **420** may be disposed therebetween.

(104) The first electrode **310** and the second electrode **320** may include the electrode stem portions **310S** and **320S** and the electrode branch portions **310B** and **320B**, respectively, which may be disposed on the first partition wall **410** and the second partition wall **420**, respectively.

(105) The plurality of partition walls **410** and **420** may be made of substantially the same material, and thus, may be formed in one process. In this case, the partition walls **410** and **420** may form one lattice pattern. The partition walls **410** and **420** may include polyimide (PI).

(106) At least some of the plurality of partition walls **410** and **420** may be disposed at the boundary between the respective pixels PX to distinguish the pixels PX from each other. These partition walls may be arranged in a substantially lattice pattern together with the first partition wall **410** and second partition wall **420** described above. At least some of the plurality of partition walls **410** and **420** disposed at the boundary between the respective pixels PX may be disposed to cover the electrode lines of the display panel **10**.

(107) Each of the plurality of partition walls **410** and **420** may have a structure in which at least a part thereof protrudes from the insulating substrate layer **300**. Each of the partition walls **410** and **420** may protrude upwardly with respect to a plane on which the light emitting element **350** is disposed, and at least a part of the protruding portion may have an inclination. Each of the partition walls **410** and **420** protruding with an inclination may reflect light incident on reflective layers **311** and **321** disposed thereon, which will be described later. Light emitted from the light emitting element **350** towards the reflective layers **311** and **321** may be reflected and transmitted to the outside of the display device **10**, for example, above the partition walls **410** and **420**. FIG. **5** exemplarily shows that each of the partition walls **410** and **42** has a protruding structure having an

angled corner shape, in which both side surfaces are flat and one upper side is flat, however, the inventive concepts are not limited to a particular shape of the partition walls **410** and **420**. For example, in some exemplary embodiments, each of the partition walls **410** and **42** may have a structure protruding in a curved shape.

(108) The reflective layers **311** and **321** may be disposed on the plurality of partition walls **410** and **420**.

(109) The first reflective layer **311** covers the first partition wall **410**, and a part thereof is electrically connected to the first drain electrode **123** of the first thin film transistor **120** through a fourth contact hole **319_1** penetrating the insulating substrate layer **300**. The second reflective layer **321** covers the second partition wall **420**, and a part thereof is electrically connected to the power supply electrode **162** through a fifth contact hole **319_2** penetrating the insulating substrate layer **300**.

(110) The first reflective layer **311** may be electrically connected to the first drain electrode **123** of the first thin film transistor **120** through the fourth contact hole **319_1** in the pixel PX. As such, the first thin film transistor **120** may be disposed in a region overlapping the pixel PX. The first reflective layer **311** is electrically connected to the first thin film transistor **120** through the first electrode contact hole CNTD disposed on the first electrode stem portion **310S**, as shown in FIG. **1**. The first electrode contact hole CNTD may be the fourth contact hole **319_1**.

(111) The second reflective layer **321** may be electrically connected to the power supply electrode **162** through the fifth contact hole **319_2** in the pixel PX. As shown in FIG. **5**, the second reflective layer **321** is electrically connected to the power supply electrode **162** through the fifth contact hole **319_2** in one pixel PX. The second electrode **320** of each pixel PX is electrically connected to the power supply wiring **161** through the plurality of second electrode contact holes CNTS on the second electrode stem portion **320S**, as shown in FIG. **1**. The second electrode contact hole CNTD may be the fifth contact hole **319_2**.

(112) As described above, in FIG. **1**, the first electrode contact hole CNTD and the second electrode contact hole CNTS are disposed on the first electrode stem portion **310S** and the second electrode stem portion **320S**, respectively. Accordingly, in the cross-sectional view of the display device **10** as shown in FIG. **5**, the first electrode **310** and the second electrode **320** are electrically connected to the first thin film transistor **120** or the power supply wiring **161** through the fourth contact hole **319_1** and the fifth contact hole **319_2**, respectively, in a region spaced apart from the partition walls **410** and **420** where the first electrode branch portion **310B** and the second electrode branch portion **320B** are disposed.

(113) However, the inventive concepts are not limited thereto. For example, referring back to FIG. **1**, the second electrode contact hole CNTS may be disposed at various other positions of the second electrode stem portion **320S**, and in some exemplary embodiments, the second electrode contact hole CNTS may be disposed on the second electrode branch portion **320B**. Further, in some exemplary embodiments, the second reflective layer **321** may be connected to one second electrode contact hole CNTS or one fifth contact hole **319_2** in a region other than the pixel PX.

(114) The display device **10** may include an area other than the light-emitting area where the light emitting elements **350** are disposed, for example, a non-light emitting area where the light emitting elements **350** are not disposed. As described above, the second electrodes **320** of each pixel PX are electrically connected to each other through the second electrode stem portion **320S**, so as to receive the same electrical signal.

(115) In some exemplary embodiments, in the case of the second electrode **320**, the second electrode stem portion **320S** may be electrically connected to the power supply electrode **162** through one second electrode contact hole CNTS formed in the non-light emitting area located at the outside of the display device **10**. Unlike the display device **10** shown in FIG. **1**, even when the second electrode stem portion **320S** is connected to the power supply electrode **162** through one contact hole, since the second electrode stem portion **320S** is extended to the adjacent pixel PX and

is electrically connected, the same electric signal may be applied to the second electrode branch portion **320B** of each pixel PX. In the case of the second electrode **320** of the display device **10**, the position of the contact hole for receiving an electric signal from the power supply electrode **162** may be varied according to the structure of the display device **10**.

(116) Referring back to FIGS. **1** and **5**, each of the reflective layers **311** and **321** may include a high-reflectance material to reflect light emitted from the light emitting element **350**. For example, each of the reflective layers **311** and **321** may include a material, such as silver (Ag) or copper (Cu), but the inventive concepts are not limited thereto.

(117) A first electrode layer **312** and a second electrode layer **322** may be disposed on the first reflective layer **311** and the second reflective layer **321**, respectively.

(118) The first electrode layer **312** may be directly disposed on the first reflective layer **311**. The first electrode layer **312** may have substantially the same pattern as the first reflective layer **311**. The second electrode layer **322** may be directly disposed on the second reflective layer **321** and spaced apart from the first electrode layer **312**. The second electrode layer **322** may have substantially the same pattern as the second reflective layer **321**.

(119) In an exemplary embodiment, the electrode layers **312** and **322** may cover the underlying reflective layers **311** and **321**, respectively. More particularly, the electrode layers **312** and **322** may be formed to be larger than the reflective layers **311** and **321** to cover the side surfaces of ends of the electrode layers **312** and **322**. However, the inventive concepts are not limited thereto.

(120) The first electrode layer **312** and the second electrode layer **322** may transmit electric signals transmitted to the first reflective layer **311** and second reflective layer **321** connected to the first thin film transistor **120** or the power supply electrode **162** to contact electrodes to be described later. The electrode layers **312** and **322** may include a transparent conductive material. For example, the electrode layers **312** and **322** may include a material, such as indium tin oxide (ITO), indium zinc oxide (IZO), or indium tin-zinc oxide (ITZO), but the inventive concepts are not limited thereto. In some exemplary embodiments, the reflective layers **311** and **321** and the electrode layers **312** and **322** may have a structure in which a transparent conductive layer, such as ITO, IZO, or ITZO, and a metal layer, such as silver or copper, are laminated one over the other. For example, the reflective layers **311** and **321** and the electrode layers **312** and **322** may have a laminate structure of ITO/silver (Ag)/ITO.

(121) The first reflective layer **311** and the first electrode layer **312**, which are disposed on the first partition wall **410**, may form the first electrode **310**. The first electrode **310** may protrude to a region extending from both ends of the first partition wall **410**, and thus, the first electrode **310** may be in contact with the insulating substrate layer **300** in the protruding region. The second reflective layer **321** and the second electrode layer **322**, which are disposed on the second partition wall **420**, may form the second electrode **320**. The second electrode **320** may protrude to a region extending from both ends of the second partition wall **420**, and thus, the second electrode **320** may be in contact with the insulating substrate layer **300** in the protruding region.

(122) The respective reflective layers **311** and **321** and respective electrode layers **312** and **322** of the first electrode **310** and the second electrode **320** may form the first conductive electrode layer CEL1 as described above.

(123) The first electrode **310** and the second electrode **320** may be disposed to cover substantially the entire region of the first partition wall **410** and substantially the entire region of the second partition wall **420**, respectively. However, as described above, the first electrode **310** and the second electrode **320** are spaced apart from and opposing each other. As will be described later, a first insulating layer **510** may be disposed between the first electrode **310** and second electrode **320** spaced apart from each other, and the light emitting element **350** may be disposed on the first insulating layer **510**.

(124) Further, the first reflective layer **311** may receive a driving voltage from the first thin film transistor **120**, and the second reflective layer **321** may receive a power supply voltage from the

power supply wiring **161**, so that the first electrode **310** and the second electrode **320** receive a driving voltage and a power supply voltage, respectively. The first electrode **310** may be electrically connected to the first thin film transistor **120**, and the second electrode **320** may be electrically connected to the power supply wiring **161**. Accordingly, the first contact electrode **361** and the second contact electrode **362** disposed on the first electrode **310** and the second electrode **320** may receive the driving voltage and the power supply voltage. The driving voltage and the power supply voltage are transmitted to the light emitting element **350** through the third contact electrode **363** disposed between the first electrode **310** and the second electrode **320**, and a predetermined current flows through the light emitting element **350** to emit light.

(125) The first insulating layer **510** is disposed on the first electrode **310** and the second electrode **320** to partially cover them. The first insulating layer **510** may cover most of the upper surfaces of the first electrode **310** and the second electrode **320**, and may expose a part of the first electrode **310** and a part of the second electrode **320**. The first insulating layer **510** may be disposed in a space between the first electrode **310** and second electrode **320**. The first insulating layer **510** may have an island shape or a linear shape formed along a space between the first electrode branch portion **310B** and the second electrode branch portion **320B** in a plan view.

(126) FIG. 5 exemplarily shows that the first insulating layer **510** is disposed in a space between one first electrode **310** (for example, the first electrode branch portion **310B**) and one second electrode **320** (for example, the second electrode branch portion **320B**). However, as described above, since the first electrodes **310** may be provided in plural and the second electrodes **320** may be provided plural, the first insulating layer **510** may be also disposed between one first electrode **310** and another second electrode **320** or between one second electrode **320** and another second electrode **320**. Further, the first insulating layer **510** may be disposed on sides opposite to the facing sides of the first electrode **310** and the second electrode **320** so as to partially cover them. More particularly, the first insulating layer **510** may expose the centers of the first electrode **310** and the second electrode **320**.

(127) The light emitting element **350** is disposed on the first insulating layer **510**. The first insulating layer **510** may be disposed between the light emitting element **350** and the insulating substrate layer **300**. The lower surface of the first insulating layer **510** may be in contact with the insulating substrate layer **300**, and the light emitting element **350** may be disposed on the upper surface of the first insulating layer **510**. Further, both side surfaces of the first insulating layer **510** may be in contact with the first electrode **310** and the second electrode **320** to electrically insulate them from each other.

(128) The first insulating layer **510** may partially overlap each of the electrodes **310** and **320**, for example, a part of a region protruding in a direction in which the first electrode **310** and the second electrode **320** face each other. The first insulating layer **510** may also be disposed in a region where the inclined side surface and flat upper surfaces of each of the partition walls **410** and **420** overlap each of the electrodes **310** and **320**.

(129) For example, the first insulating layer **510** may cover each end protruding in a direction in which the first electrode **310** and the second electrode **320** face each other. The first insulating layer **501** may be in contact with a part of the lower surface of the insulating substrate layer **300**, and may be in contact with the side surface of each of the electrodes **310** and **320**, and a part of the lower surface of each of the electrodes **310** and **320**. In this manner, the first insulating layer **510** may protect the region overlapping each of the electrodes **310** and **320**, and electrically insulate them from each other. Further, the first insulating layer **510** may prevent the first conductive semiconductor layer **351** and second conductive semiconductor layer **352** (see FIG. 6) of the light emitting element **350** from being in direct contact with other substrates to prevent damage to the light emitting element **350**.

(130) However, the inventive concepts are not limited thereto, and the first insulating layer **510** may be disposed only in the region overlapping the inclined surfaces of the partition walls **410** and

420 among the regions on the first electrode **310** and the second electrode **320**. In this case, the lower portion of the first insulating layer **510** ends at the inclined surface of each of the partition walls **410** and **420**, and each of the electrodes **310** and **320** disposed on a part of the inclined surface of each of the partition walls **410** and **420** is exposed to be in contact with the contact electrode **360**.

(131) Further, the first insulating layer **510** may be disposed such that both ends of the light emitting device **350** are exposed. Accordingly, the contact electrode **360** may be in contact with the exposed upper surface of each of the electrodes **310** and **320** and both ends of the light emitting element **350**, and the contact electrode **360** may transmit an electrical signal applied to the first electrode **310** and the second electrode **320** to the light emitting element **350**.

(132) At least one light emitting element **350** may be disposed between the first electrode **310** and the second electrode **320**. FIG. 5 exemplarily shows that two light emitting elements **350** are disposed between the first electrode **310** and the second electrode **320** in a cross-section, however, the inventive concepts are not limited thereto, and the plurality of light emitting elements **350** may be arranged in a different direction (for example, second direction D2) on a plane, as shown in FIG. 1.

(133) More specifically, the plurality of light emitting elements **350** may include at least one first light emitting element **350a** having one end electrically connected to the first electrode **310** and at least one second light emitting element **350b** having one end electrically connected to the second electrode **320**. One end of the first light emitting element **350a** may be connected to the first electrode **310**, and the other end thereof may be in contact with the third contact electrode **363**. One end of the second light emitting element **350b** may be connected to the second electrode **320**, and the other end thereof may be in contact with the third contact electrode **363**. As described above, the first light emitting element **350a** and the second light emitting element **350b** may be connected in series to each other.

(134) The plurality of first light emitting elements **350a** may be connected in parallel to each other, and the plurality of second light emitting elements **350b** may be connected in parallel to each other, while the first light emitting element **350a** and the second light emitting element **350b** may be connected in series to each other. In this manner, even if any one of the first light emitting elements **350a** is shorted, and thus, other first light emitting elements **350a** do not emit light, the plurality of second light emitting elements **350b** connected in series to the first light emitting elements **350a**, and connected in parallel between the second light emitting elements **350b** may simultaneously emit light. As such, the plurality of light emitting elements **350** in one pixel PX are connected in series or in parallel to each other, so that it is possible to prevent defective pixels PX even if any one of the light emitting elements **350** is shorted.

(135) Meanwhile, although FIG. 1 illustrates that only the light emitting elements **350** emitting light of the same color are arranged in each pixel PX, the inventive concepts are not limited thereto. As described above, in some exemplary embodiments, the light emitting elements **350** emitting light of different colors from each other may be arranged in one pixel PX.

(136) As described above, the distance between the first electrode **310** and the second electrode **320** is longer than the length h of the long axis of the light emitting element **350**. For example, the distance between the first and second electrodes **310** and **320** may be about two times or less of the length h thereof. As such, the third contact electrode **363** between the first electrode **310** and the second electrode **320** may easily make electrical contact with the light emitting element **350**.

(137) The light emitting element **350** may include a light emitting diode. The light emitting element **350** may have a nanostructure, whose size is generally in nanometers. The light emitting element **350** may be an inorganic light emitting diode including an inorganic material. When the light emitting element **350** is an inorganic light emitting diode, and when a light emitting material having an inorganic crystal structure is disposed between two electrodes facing each other and an electric field is formed in the light emitting material in a specific direction, the inorganic light

emitting diode may be aligned between the two electrodes formed with a specific polarity.

(138) In some exemplary embodiments, the light emitting element **350** may have a structure in which a first conductive semiconductor layer **351**, an active material layer **353**, a second conductive semiconductor layer **352**, and a second electrode material layer **357** are laminated. The first conductive semiconductor layer **351**, the active material layer **353**, the second conductive semiconductor layer **352**, and the second electrode material layer **357** may be sequentially arranged in a direction horizontal to the insulating substrate layer **300**. In particular, the light emitting element **350**, in which the plurality of layers are laminated, may be disposed in a horizontal direction with respect to the insulating substrate layer **300**. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, the light emitting element **350** may have a reversed stacked sequence from that described above between the first electrode **310** and the second electrode **320**.

(139) The second insulating layer **520** may be disposed to overlap at least a part of the region on the light emitting device **350**. The second insulating layer **520** may protect the light emitting element **350**, and may fix the light emitting element **350** between the first electrode **310** and the second electrode **320**.

(140) Although FIG. 5 shows that the second insulating layer **520** is disposed only on the upper surface of the light emitting element **350** in a cross-sectional view, in some exemplary embodiments, the second insulating layer **520** may surround the outer surface of the light emitting element **350**. In particular, as in the first insulating layer **510**, the second insulating layer **520** may extend in the second direction D2 along a space between the first electrode branch portion **310B** and the second electrode branch portion **320B**, so as to have an island-type shape or a linear shape in a plan view.

(141) Further, a part of the second insulating layer **520** may be disposed in a region where the lower surface of the light emitting element **350** is in contact with the first insulating **510**. This configuration may be formed when the light emitting element **350** is aligned on the first insulating layer **510** and the second insulating layer **520** is disposed on the first insulating layer **510** at the time of manufacturing the display device **10**. When voids are formed in the first insulation layer **510** contacting the lower surface of the light emitting element **350**, a part of the material of the second insulating layer **520** may penetrate into the voids when the second insulating layer **520** is formed, so as to form the configuration.

(142) The second insulating layer **520** is disposed to expose both side surfaces of the light emitting element **350**. In particular, since the length of the second insulating layer **520** disposed on the upper surface of the light emitting element **350** in the cross-section, measured in the uniaxial direction, is shorter than the length of the light emitting element **350**, the second insulating layer **520** may be recessed inwardly from both side surfaces of the light emitting element **350**. Accordingly, the side surfaces of the first insulating layer **510**, the light emitting element **350**, and the second insulating layer **520** may be laminated stepwise. In this case, the contact electrodes **361** and **362** to be described later may be brought into smooth contact with both ends of the light emitting element **350**. However, the inventive concept are not limited thereto, and in some exemplary embodiments, the length of the second insulating layer **520** may be substantially the same as the length of the light emitting element **350**, so that both sides thereof may be aligned with each other.

(143) The second insulating layer **520** may be disposed to cover the first insulating layer **510**, and then patterned to be in contact with the contact electrode **360** in a region where the light emitting element **350** is exposed. The process of patterning the second insulating layer **520** may be performed by a general dry etching or wet etching method. In this case, in order to prevent the first insulating layer **510** from being patterned, the first insulating layer **510** and the second insulating layer **520** may include materials having different etching selection ratios from each other. In particular, when patterning the second insulating layer **520**, the first insulating layer **510** may function as an etching stopper.

(144) Accordingly, even when the second insulating layer **520** covers the outer surface of the light emitting element **350**, and is patterned to expose both ends of the light emitting element **350**, the material of the first insulating layer **510** may not be damaged. In particular, the first insulating layer **510** and the light emitting element **350** may form a smooth contact surface at both ends of the light emitting element **350**, at which the light emitting element **350** is in contact with the contact electrode **360**. When the contact electrode **360** in contact with the light emitting element **350** is formed, voids from the patterning process may not be formed in the first insulating layer **510** that is in contact with the lower surface of the light emitting element **350**, such that the contact electrode **360** may be prevented from being disconnected by the voids.

(145) The first contact electrode **361** disposed on the first electrode **310** and overlapping at least a part of the second insulating layer **520**, the second contact electrode **362** disposed on the second electrode **320** and overlapping at least a part of the second insulating layer **520**, and the third contact electrode **363** disposed between the first contact electrode **361** and the second contact electrode **362** may be disposed on the second insulating layer **520**.

(146) The first contact electrode **361** and the second contact electrode **362** may be disposed on the upper surface of the first electrode **310** and the upper surface of the second electrode **320**, respectively. More specifically, the first contact electrode **361** and the second contact electrode **362** may be in contact with the first electrode layer **312** and the second electrode layer **322**, respectively, in the region where the first insulating layer **510** is patterned to expose a part of the first electrode **310** and a part of the second electrode **320**. Each of the first contact electrode **361** and the second contact electrode **362** may be in contact with one end side surface of the light emitting element **350**, for example, the first conductive semiconductor layer **351**, the second conductive semiconductor layer **352**, or the electrode material layer **357**. As such, the first contact electrode **361** and the second contact electrode **362** may transmit electrical signals applied to the first electrode layer **312** and the second electrode layer **322** to the light emitting element **350**.

(147) The first contact electrode **361** may be disposed on the first electrode **310** to partially cover the first electrode **310**, and may be partially in contact with the light emitting element **350**, the first insulating layer **510**, and the second insulating layer **520**. One end of the first contact electrode **361** in a direction in which a third contact electrode **363** is disposed may be disposed on the second insulating layer **520**. The second contact electrode **362** may be disposed on the second electrode **320** to partially cover the second electrode **320**, and may be partially in contact with the light emitting element **350**, the first insulating layer **510**, and the second insulating layer **520**. One end of the second contact electrode **362** in a direction in which the third contact electrode **363** is disposed may be disposed on the second insulating layer **520**.

(148) As shown in FIG. 1, the first contact electrode **361** or the second contact electrode **362** is not disposed on the first electrode hole CNTD and the second electrode contact hole CNTS disposed on the first electrode stem portion **310S** and the second electrode stem portion **320S**. More particularly, referring to FIG. 5, each of the first contact electrode **361** and the second contact electrode **362** may not overlap a region where the first electrode hole CNTD and the second electrode contact hole CNTS are disposed. However, the inventive concepts are not limited thereto. In some exemplary embodiments, a part of each of first contact electrode **361** and the second contact electrode **362** may be disposed in a region overlapping the first electrode hole CNTD and the second electrode contact hole CNTS on the first electrode **310** and the second electrode **320**.

(149) The third contact electrode **363** may be in contact with the other end side surface of the light emitting element **350**, at which the light emitting element **350** does not contact the first contact electrode **361** or the second contact electrode **362**. The third contact electrode **363** may partially contact the first insulating layer **510**, the second insulating layer **520**, and the third insulating layer **530**. Both ends of the third contact electrode **363** may be disposed on the third insulating layer **530** to be electrically insulated from the first contact electrode **361** and the second contact electrode **362**.

(150) The first contact electrode **361** or the second contact electrode **362** may be spaced apart from the third contact electrode **363** on the second insulating layer **520** or the third insulating layer **530**. In particular, the first contact electrode **361**, the second contact electrode **362**, and the third contact electrode **363** may be laminated so as to partially overlap the third insulating layer **530** in a vertical direction.

(151) The second conductive electrode layer **CEL2** including the first contact electrode **361** and the second contact electrode **362** may be disposed on the first conductive electrode layer **CEL1** to partially contact the first conductive electrode layer **CEL1**. The third insulating layer **530** may be disposed on the second conductive electrode layer **CEL2**, and the third conductive electrode layer **CEL3** including the third contact electrode **363** may be disposed on the third insulating layer **530**. The third insulating layer **530** may electrically insulate the second conductive electrode layer **CEL2** from the third conductive electrode layer **CEL3**. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, the laminating sequence of the second conductive electrode layer **CEL2** and the third conductive electrode layer **CEL3** may be reversed. Meanwhile, in another exemplary embodiment, the third insulating layer **530** may be omitted, and the second conductive electrode layer **CEL2** and the third conductive electrode layer **CEL3** may be disposed on substantially the same plane. Details thereof will be described with reference to other embodiments.

(152) In particular, the first contact electrode **361** and the second contact electrode **362** may be disposed on the upper surfaces of the first electrode **310** and the second electrode **320**, respectively. Specifically, the first contact electrode **361** and the second contact electrode **362** may be in contact with the first electrode layer **312** and the second electrode layer **322** on the upper surfaces of the first electrode **310** and the second electrode **320**. The region disposed to cover the first electrode **310** and the second electrode **320** on the upper surfaces of the first partition wall **410** and the second partition wall **420** may be patterned to expose the first electrode layer **312** and the second electrode layer **322**, and thus, the first insulating layer **510** and the second insulating layer **520** may be electrically connected to the respective contact electrodes **361** and **362** in the exposed region.

(153) The first contact electrode **361** and the second contact electrode **362** may be in contact with one end and the other end of the light emitting element **350**, for example, the first conductive semiconductor layer **351** and the electrode material layer **357**, respectively. Thus, the first contact electrode **361** and the second contact electrode **362** may transmit an electric signal applied to the first electrode layer **312** and the second electrode layer **322** to the light emitting element **350**.

(154) The first contact electrode **361** and the second contact electrode **362** may receive different power from the first thin film transistor **120** and the power supply wiring **161**, respectively. For example, the first contact electrode **361** may receive a driving voltage applied from the first thin film transistor **120** to the first electrode **310**, and the second contact electrode **362** may receive a common power supply voltage applied from the power supply wiring **161** to the second electrode **320**. However, the inventive concepts are not limited thereto.

(155) One end of the light emitting element **350** may be in contact with the first contact electrode **361** or the second contact electrode **362**, and the other end thereof may be in contact with the third contact electrode **363**. As described above, the light emitting elements **350** may include a first light emitting element **350a** and a second light emitting element **350b**, and the first light emitting element **350a** and the second light emitting element **350b** may receive different electric signals from the first contact electrode **361** and the second contact electrode **362**, respectively. However, the other end of the first light emitting element **350a** and the other end of the second light emitting element **350b** may both contact the third contact electrode **363**, so that the first light emitting element **350a** and the second light emitting element **350b** may be connected in series to receive different electrical signals from each other.

(156) The contact electrodes **361**, **362**, and **363** may include a conductive material. For example, the contact electrodes **361**, **362**, and **363** may include ITO, IZO, ITZO, or aluminum (Al).

However, the inventive concepts are not limited thereto.

(157) Further, the contact electrodes **361**, **362**, and **363** may include substantially the same material as the electrode layers **312** and **322**. The contact electrodes **361**, **362**, and **363** may be disposed in substantially the same pattern on the electrode layers **312** and **322** to contact the electrode layers **312** and **322**. For example, the first contact electrode **361** contacting the first electrode layer **312** and the second contact electrode **362** contacting the second electrode layer **322** may receive electrical signals applied from the first electrode layer **312** and the second electrode layer **322**, and transmit the electrical signals to the light emitting element **350**.

(158) The third insulating layer **530** may be disposed on the first contact electrode **361** and the second contact electrode **362** to electrically insulate the first contact electrode **361** and the second contact electrode **362** from the third contact electrode **363**. The third insulating layer **530** may be disposed to cover the first contact electrode **361** and the second contact electrode **362**, and may be disposed not to overlap a part of the light emitting element **350** such that the light emitting element **350** is in contact with the third contact electrode **363**. The third insulating layer **530** may partially contact the first contact electrode **361**, the second contact electrode **362**, and the second insulating layer **520** on the upper surface of the second insulating layer **520**. The third insulating layer **530** may be disposed to cover one end of the first contact electrode **361** and one end of the second contact electrode **362** on the upper surface of the second insulating layer **520**. Thus, the third insulating layer **530** may protect the first contact electrode **361** and the second contact electrode **362**, and electrically insulate the first contact electrode **361** and the second contact electrode **362** from the third contact electrode **363**.

(159) One end of the third insulating layer **530** in a direction in which the third contact electrode **363** is disposed may be aligned with one side surface of the second insulating layer **520**.

(160) The passivation layer **550** may be formed on the third insulating layer **530** and the third contact electrode **363** to protect members disposed on the insulating substrate layer **300** from external environments. When the first contact electrode **361**, the second contact electrode **362**, and the third contact electrode **363** are exposed, a contact electrode material may be disconnected if an electrode is damaged. As such, the passivation may cover these members. More particularly, the passivation layer **550** may be disposed to cover the first electrode **310**, the second electrode **320**, the light emitting element **350**, and the like. As described above, when the third insulating layer **530** is omitted, the passivation layer **550** may be formed on the first contact electrode **361**, the second contact electrode **362**, and the third contact electrode **363**. In this case, the passivation layer **550** may electrically insulate the first contact electrode **361**, the second contact electrode **362**, and the third contact electrode **363** from each other.

(161) Each of the first insulating layer **510**, second insulating layer **520**, third insulating layer **530**, and passivation layer **550** may include an inorganic insulating material. For example, the first insulating layer **510**, the second insulating layer **520**, the third insulating layer **530**, and the passivation layer **550** may include an inorganic insulating material, such as silicon oxide (SiOx), silicon nitride (SiNx), silicon oxynitride (SiOxNy), aluminum oxide (Al₂O₃), or aluminum nitride (AlN). The first insulating layer **510**, the second insulating layer **520**, the third insulating layer **530**, and the passivation layer **550** may include substantially the same material, but may include different materials from each other in some exemplary embodiments. In addition, various materials providing insulating properties to the first insulating layer **510**, the second insulating layer **520**, the third insulating layer **530**, and the passivation layer **550** may be applicable.

(162) The first insulating layer **510** and the second insulating layer **520** may have different etching selection ratios, as described above. For example, when the first insulating layer **510** includes silicon oxide (SiOx), the second insulating layer **520** may include silicon nitride (SiNx). As another example, when the first insulating layer **510** includes silicon nitride (SiNx), the second insulating layer **520** may include silicon oxide (SiOx). However, the inventive concepts are not limited thereto.

(163) As described above, the display device **10** according to an exemplary embodiment may include the first electrode **310** and the second electrode **320**, and may include the first light emitting element **350a** and the second light emitting element **350b** disposed between the first electrode **310** and the second electrode **320**, which are electrically connected by the third contact electrode **363**. The first light emitting element **350a** and the second light emitting element **350b** may receive different electrical signals from the first electrode **310** and the second electrode **320**, and may both be in contact with the third contact electrode **363** to be connected in series to each other. In this manner, the display device **10** can prevent defective light emission in the pixel PX even if any one of the light emitting elements **350** in one pixel PX is shorted.

(164) The light emitting elements **350** may be manufactured on a substrate by an epitaxial growth method. The light emitting elements **350** may be manufactured by forming a seed crystal layer for forming a semiconductor layer on a substrate, and depositing a desired semiconductor material on the seed crystal layer to grow the seed crystal layer. Hereinafter, a structure of the light emitting element **350** according to exemplary embodiments will be described in detail with reference to FIG. 6.

(165) FIG. 6 is a schematic perspective view of a light emitting element according to an exemplary embodiment.

(166) Referring to FIG. 6, the light emitting element **350** may include a plurality of conductive semiconductor layers **351** and **352**, an active material layer **353** disposed between the plurality of conductive semiconductor layers **351** and **352**, an electrode material layer **357**, and an insulating material layer **358**. The electrical signal applied from the first electrode **310** and the second electrode **320** may be transmitted to the active material layer **353** through the plurality of conductive semiconductor layers **351** and **352** to emit light.

(167) More specifically, the light emitting element **350** may include a first conductive semiconductor layer **351**, a second conductive semiconductor layer **352**, an active material layer **353** disposed between the first conductive semiconductor layer **351** and the second conductive semiconductor layer **352**, an electrode material layer **357** disposed on the second conductive semiconductor layer **352**, and an insulating material layer **358**. FIG. 6 exemplarily shows that the light emitting element **350** has a structure in which the first conductive semiconductor layer **351**, the active material layer **353**, the second conductive semiconductor layer **352**, and the electrode material layer **357** are sequentially laminated, however, the inventive concepts are not limited thereto. In some exemplary embodiments, the electrode material layer **357** may be omitted. In some exemplary embodiments, the electrode material layer may also be disposed on at least one of both side surfaces of the first conductive semiconductor layer **351** and the second conductive semiconductor layer **352**. Hereinafter, the light emitting element **350** will be described with reference to the structure shown in FIG. 6 as an example.

(168) The first conductive semiconductor layer **351** may be an n-type semiconductor layer. For example, when the light emitting element **300** emits light of a blue wavelength band, the first conductive semiconductor layer **351** may be a semiconductor material having a formula of $\text{In}_x\text{Al}_y\text{Ga}_{1-x-y}\text{N}$ ($0 \leq x \leq 1$, $0 \leq y \leq 1$, $0 \leq x+y \leq 1$). For example, the semiconductor material may be at least one of InAlGa_N, Ga_N, AlGa_N, InGa_N, Al_N, and In_N, which are doped with an n-type semiconductor. The first conductive semiconductor layer **351** may be doped with a first conductive dopant, and, for example, the first conductive dopant may be Si, Ge, Sn, or the like. The length of the first conductive semiconductor layer **351** may be in the range of about 1.5 μm to about 5 μm, without being limited thereto.

(169) The second conductive semiconductor layer **352** may be a p-type semiconductor layer. For example, when the light emitting element **300** emits light of a blue wavelength band, the second conductive semiconductor layer **352** may be a semiconductor material having a formula of $\text{In}_x\text{Al}_y\text{Ga}_{1-x-y}\text{N}$ ($0 \leq x \leq 1$, $0 \leq y \leq 1$, $0 \leq x+y \leq 1$). For example, the semiconductor material may be at least one of InAlGa_N, Ga_N, AlGa_N, InGa_N, Al_N, and In_N, which are doped with a p-type

semiconductor. The second conductive semiconductor layer **352** may be doped with a second conductive dopant, and, for example, the second conductive dopant may be Mg, Zn, Ca, Se, Ba, or the like. The length of the second conductive semiconductor layer **352** may be in the range of about 0.08 μm to about 0.25 μm , without being limited thereto.

(170) The active material layer **353** may be disposed between the first conductive semiconductor layer **351** and the second conductive semiconductor layer **352**, and may include a material having a single or multiple quantum well structure. When the active material layer **353** includes a material having a multiple quantum well structure, in which a plurality of quantum layers and a plurality of well layers are alternately laminated. The active material layer **353** may emit light by coupling of electron-hole pairs according to an electrical signal applied through the first conductive semiconductor layer **351** and the second conductive semiconductor layer **352**. For example, when the active material layer **353** emits light of a blue wavelength band, it may include a material, such as AlGaIn or AlInGaIn. In particular, when the active material layer **353** has a multiple quantum well structure in which a plurality of quantum layers and a plurality of well layers are alternately laminated, the quantum layer may include a material, such as AlGaIn or AlInGaIn, and the well layer may include a material, such as GaN or AlGaIn. However, the inventive concepts are not limited thereto. The active material layer **353** may have a structure in which semiconductor materials having high bandgap energy and semiconductor materials having low bandgap energy are alternately laminated, and may include other Group semiconductor materials depending on the wavelength band of the emitted light. Accordingly, light emitted from the active material layer **353** is not limited to light of a blue wavelength band, and in some exemplary embodiments, the active material layer **353** may emit light of a red wavelength band or light of a green wavelength band. The length of the active material layer **353** may be in the range of about 0.05 μm to about 0.25 μm , without being limited thereto.

(171) Light emitted from the active material layer **353** may be emitted not only onto the outer surface of the light emitting element **300** in the length direction, but also onto both side surfaces thereof. More particularly, the direction of light emitted from the active material layer **353** is not limited to one direction.

(172) The electrode material layer **357** may be an ohmic contact electrode. However, the inventive concepts are not limited thereto, and the electrode material layer **357** may be a Schottky contact electrode in some exemplary embodiments. The electrode material layer **357** may include a conductive metal. For example, the electrode material layer **357** may include at least one of aluminum (Al), titanium (Ti), indium (In), gold (Au), and silver (Ag). The electrode material layer **357** may include substantially the same material, or may also include different materials. However, the inventive concepts are not limited thereto.

(173) The insulating material layer **358** may be formed at the outside of the light emitting element **350** to protect the light emitting element **350**. For example, the insulating material layer **358** is formed to surround the side surface of the light emitting element **350**, and thus, may not be formed at both ends of the light emitting element **300** in the length direction, for example, at both ends thereof at which the first conductive semiconductor layer **351** and the second conductive semiconductor layer **352** are disposed. However, the inventive concepts are not limited thereto. The insulating material layer **358** may include a material having insulating properties, such as silicon oxide (SiO_x), silicon nitride (SiN_x), silicon oxynitride (SiO_xN_y), aluminum nitride (AlN), or aluminum oxide ($\text{Al}_{\text{sub}2}\text{O}_{\text{sub}3}$). Accordingly, it is possible to prevent an electrical short that may occur when the active material layer **353** is in direct contact with the first electrode **310** or the second electrode **320**.

(174) The insulating material layer **358** may extend in the length direction to cover the first conductive semiconductor layer **351** to the electrode material layer **357**. However, the inventive concepts are not limited thereto. The insulating material layer **358** may cover only the first conductive semiconductor layer **351**, the active material layer **353**, and the second conductive

semiconductor layer **352**, or may cover only a part of the outer surface of the electrode material layer **357** to expose a part of the outer surface of the electrode material layer **357**.

(175) Further, in some exemplary embodiments, the insulating material layer **358** may be surface-treated so as to be dispersed in a solution without being agglomerated with another insulating material layer **358**. When aligning the light emitting elements to be described later, the light emitting elements **350** in the solution may be maintained in a dispersed state, so that the light emitting elements **350** may be independently aligned between the first electrode **310** and the second electrode **320**. For example, the insulating material layer **358** may be hydrophobically or hydrophilically surface-treated, so that the light emitting elements **350** may be maintained in a state in which the light emitting elements **350** are dispersed with each other in the solution.

(176) The length of the insulating material layer **358** may be in the range of about 0.5 μm to about 1.5 μm , without being limited thereto.

(177) The light emitting element **350** may have a substantially cylindrical shape. However, the inventive concepts are not limited to a particular shape of the light emitting element **350**, and in some exemplary embodiments, the light emitting element **350** may have various shapes, such as a substantially cubical shape, a substantially rectangular parallelepiped shape, and a substantially hexagonal column shape. The length of the light emitting element **350** may be in the range of about 1 μm to about 10 μm , or about 2 μm to about 5 μm , and preferably may be about 4 μm . The diameter of the light emitting element **350** may be in the range of about 400 nm to about 700 nm, and preferably may be about 500 nm.

(178) Hereinafter, a method of manufacturing a display device **10** according to an exemplary embodiment will be described in detail with reference to FIGS. **7** to **21**.

(179) FIGS. **7** to **21** are plan views and cross-sectional views schematically illustrating a method of manufacturing a display device according to an exemplary embodiment. Hereinafter, a procedure of manufacturing the display device **10** of FIG. **1** is shown in plan views, and the order in which a plurality of members are laminated in each plan view is shown in cross-sectional views. That is, the cross-sectional views shown below show the order in which the cross-sectional structures of the corresponding plan views are formed.

(180) Meanwhile, in the following cross-sectional views, the connecting structure between the electrodes **310** and **320** with the first thin film transistor **120** or the power supply wiring **161** through the fourth contact hole **319_1** and the fifth contact hole **319_2** of FIG. **5** will be omitted. In addition, the order in which each of the electrodes **310** and **320**, the light emitting element **350**, the contact electrode **360**, and the plurality of insulating layers are laminated will be described in detail.

(181) First, referring to FIGS. **7** to **9**, a plurality of electrodes **310** and **320** are formed on the insulating substrate layer **300**. The process of forming the plurality of electrodes **310** and **320** may be performed by patterning a metal or an organic material through a general mask process, for example.

(182) As described above with reference to FIG. **1**, the first electrode stem portion **310S** and the second electrode stem portion **320S** substantially extend in the first direction **D1**, and are spaced apart from each other and face each other. Although FIG. **1** shows that the first electrode stem portions **310S** are electrically separated and spaced apart from each other between neighboring pixels **PX**, in FIG. **7**, one end of the first electrode stem portion **310s** may also extend to a plurality of adjacent pixels **PX**. One end of the first electrode stem portion **310S** and one end of the second electrode stem portion **320S** may be connected to a signal application pad, and thus, AC power may be applied when aligning the light emitting elements **350**, which will be described later.

(183) The first electrode branch portion **310B** and the second electrode branch portion **320B** are branched from the first electrode stem portion **310S** and the second electrode stem portion **320S**, respectively, and substantially extend in the second direction **D2**. As described above, the first electrode branch portion **310B** and the second electrode branch portion **320B** extend in directions

opposite to each other, and are spaced apart from the second electrode stem portion **320S** and the first electrode stem portion **310S**, respectively.

(184) In particular, the first electrode **310** and second electrode **320** of FIG. 7 are substantially the same as the first electrode **310** and second electrode **320** of FIG. 1, except that the first electrode stem portion **310S** of FIG. 7 extends to the neighboring pixel PX and is electrically connected to the first electrode stem portion **310S** of each pixel PX. A detailed description thereof will be omitted.

(185) FIGS. 8 and 9 are cross-sectional views showing a procedure in which the plurality of electrodes **310** and **320** shown in FIG. 7 are formed.

(186) Referring to FIG. 8, a first partition wall **410** and a second partition wall **420** are disposed on the insulating substrate layer **300** to be spaced apart from each other, and the first electrode **310** and the second electrode **320** are disposed to cover first partition wall **410** and the second partition wall **420**, respectively. As described above, the members may be formed by patterning a metal or an organic material through a general mask process. In the following cross-sectional views, the process of forming each of the members will be omitted. The first electrode **310** and the second electrode **320** may form a first conductive electrode layer CEL1.

(187) Referring to FIG. 9, a first insulating material layer **511** is formed to cover the first electrode **310** and the second electrode **320**. The first insulating material layer **511** is patterned in a subsequent process to be described later to form the first insulating layer **510** of FIG. 5. The first insulating material layer **511** is not shown in FIG. 7, but may be disposed to the first electrode branch portion **310B** and the second electrode branch portion **320B**. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, the first insulating material layer **511** may cover the first electrode stem portion **310S** and the second electrode stem portion **320S**.

(188) Next, referring to FIGS. 10 to 12, light emitting elements **350** are disposed between the first electrode branch portion **310B** and the second electrode branch portion **320B**. The light emitting elements **350** may include a first light emitting element **350a** having one end electrically connected to the first electrode branch portion **310B** and a second light emitting element **350b** having one end electrically connected to the second electrode branch portion **320B**. The plurality of light emitting elements **350** may be aligned by dielectrophoresis (DEP).

(189) FIGS. 11 and 12 are cross-sectional views showing a procedure for aligning the light emitting elements **350** shown in FIG. 10.

(190) First, referring to FIG. 11, a solution containing the light emitting elements **350** is applied between the first electrode **310** (or the first electrode branch **310B**) and the second electrode **320** (or the second electrode branch **320B**). The solution may have a formulation such as ink or paste, and may include a solvent such as acetone, water, alcohol, or toluene. However, the solution is not particularly limited as long as the solution can be vaporized at room temperature or by heat.

(191) Next, an AC power is applied to the first electrode **310** and the second electrode **320**, and a capacitance from an electric field E is formed between the first electrode **310** and the second electrode **320**. When the capacitance is formed, bipolarity is induced in the light emitting elements **350** under a non-uniform electric field E, and the light emitting elements **350** are subjected to a dielectrophoresis force (DEP force). Therefore, the light emitting elements **350** may be aligned between the first electrode **310** and the second electrode **320** by the dielectrophoretic force. For example, one end of the light emitting element **350** may be connected to the first electrode **310**, and the other end thereof may be connected to the second electrode **320**.

(192) The dielectrophoretic force applied to the light emitting element **350** by the capacitance may cause the light emitting element **350** to have certain directionality between the electrodes **310** and **320**. For example, the first conductive semiconductor layer **351** of the light emitting element **350** may be connected to the side surface of the first electrode branch portion **310B** or the second electrode branch portion **320B**, and the second conductive semiconductor layer **352** of the light

emitting element **350** may be connected to the side surface of the second electrode branch portion **320B** or the first electrode branch portion **310B**. However, the inventive concepts are not limited thereto, and the light emitting elements **350** may be aligned in any direction between the electrodes **310** and **320**. The second insulating material layer **521** may be patterned in a subsequent process to be described later to form the second insulating layer **520**. Here, the first insulating material layer **511** functions as an etching stopper, and thus, only the second insulating material layer **521** may be selectively patterned.

(193) Next, referring to FIG. **12**, a second insulating material layer **521** is formed to cover the first insulating material layer **511** and the light emitting element **350**. The second insulating material layer **521** is disposed on the upper surface of the light emitting element **350** in a cross-section, but may substantially cover the outer surface of the light emitting element **350**. Accordingly, the light emitting element **350** may be fixed between the first electrode **310** and the second electrode **320**. Further, as described above, the second insulating material layer **521** may include a material having a different etching selection ratio from the first insulating material layer **511**.

(194) Although not shown in FIG. **10**, like the first insulating material layer **511**, the second insulating material layer **521** may be disposed to cover the first electrode branch portion **310B** and the second electrode branch portion **320B**. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, the second insulating material layer **521** may cover the first electrode stem portion **310S** and the second electrode stem portion **320S**.

(195) As described above, the form in which the light emitting elements **350** are aligned is not limited to the forms shown in the drawings. The light emitting elements **350** may be spaced apart from each other as shown in the drawings. However, in some exemplary embodiments, some of the light emitting elements **350** may partially overlap each other in one direction, while being spaced apart from each other.

(196) Next, referring to FIGS. **13** to **17**, a first contact electrode **361** and a second contact electrode **362** are formed on the first electrode branch portion **310B** and the second electrode branch portion **320B**, respectively, which are in contact with one end of the light emitting element **350**. One end of the first light emitting element **350a** may be in contact with the first contact electrode **361**, and one end of the second light emitting element **350b** may be in contact with the second contact electrode **362**.

(197) FIGS. **14** to **17** are cross-sectional views schematically showing a procedure of forming the first contact electrode **361** and the second contact electrode **362** which are in contact with one end of the first light emitting element **350a** and one end of the second light emitting element **350b**, respectively.

(198) First, referring to FIG. **14**, the second insulating material layer **521** is patterned such that the first insulating material layer **511** disposed on the first electrode **310** and the second electrode **320** is partially exposed, and one end of the first light emitting element **350a** and one end of the second light emitting element **350b** are exposed. Since the second insulating material layer **521** includes a material having a different etching selection ratio from the first insulating material layer **511**, only the second insulating material layer **521** may be selectively patterned. Thus, when one end of the first light emitting element **350a** and one end of the second light emitting element **350b** are exposed, the contact surface of the first insulating material layer **511** with the lower surfaces of the first light emitting element **350a** and the second light emitting element **350b** may extend substantially horizontally toward each of the electrodes **310** and **320**, to facilitate smooth contact.

(199) Next, referring to FIG. **15**, the first insulating material layer **511** is patterned such that a part of the first electrode **310** and a part of the second electrode **320** are exposed. FIG. **15** exemplarily shows that a region where the first insulating material layer **511** is in contact with the upper surface of the first electrode **310** and the upper surface of the second electrode **320** is patterned. However, the inventive concepts are not limited thereto, and in some exemplary embodiments, a region where the first insulating material layer **511** is in contact with the inclined side surface of the first electrode

310 and the inclined side surface of the upper surface the second electrode **320** may be patterned. Here, a part of the first insulating material layer **511** is exposed, thereby forming the first insulating layer **510**.

(200) Next, referring to FIG. **16**, a first contact electrode **361** contacting one end side surface of the first light emitting element **350a** and a second contact electrode **362** contacting one end side surface of the second light emitting element **350b** are formed. The first contact electrode **361** may be disposed to cover the first electrode **310**, the first insulating material layer **511**, and a part of the second insulating material layer **521**, and may also be in contact with the exposed first electrode **310** shown in FIG. **15**. The second contact electrode **362** may be disposed to cover the second electrode **320**, the first insulating material layer **511**, and a part of the second insulating material layer **521**, and may also be in contact with the exposed second electrode **320** shown in FIG. **15**.

(201) As described above, since the contact surface of the first insulating material layer **511** with the lower surfaces of the first light emitting element **350a** and the second light emitting element **350b** extends substantially horizontally toward each of the electrodes **310** and **320**, the electrode material of the first contact electrode **361** and second contact electrode **362** contacting one end side surface of each of the light emitting elements **350a** and **350b** may be smoothly connected. The first contact electrode **361** and the second contact electrode **362** may be disposed on the first conductive electrode layer CEL1 to form a second conductive electrode layer CEL2.

(202) Next, referring to FIG. **17**, a third insulating material layer **531** is formed to cover the second conductive electrode CEL2 and the second insulating material layer **521**. The third insulating material layer **531** may be patterned in a subsequent process to be described later to form a third insulating layer **530**. The third insulating material layer **531** may protect the first contact electrode **361** and the second contact electrode **362**, and electrically insulate the first contact electrode **361** and the second contact electrode **362** from the third contact electrode **363**. The third insulating material layer **531** may include a material having substantially the same etching selection ratio as the second insulating material layer **521**, such that the third insulating material layer **531** and the second insulating material layer **521** may be simultaneously patterned. However, the inventive concepts are not limited thereto.

(203) Next, referring to FIGS. **18** to **20**, a third contact electrode **363** is formed between the first contact electrode **361** and the second contact electrode **362**. The third contact electrode **363** may simultaneously contact the other end of the first light emitting element **350a** and the other end of the second light emitting element **350b**.

(204) FIGS. **19** and **20** are cross-sectional views schematically showing a procedure of forming the contact electrode **363**.

(205) First, referring to FIG. **19**, the second insulating material layer **521** and the third insulating material layer **531** are patterned such that the opposing ends of the first light emitting element **350a** and the second light emitting element **350b** and the first insulating layer **510** disposed therebetween are exposed. Here, a part of the second insulating material layer **521** and a part of the third insulating material layer **531** are patterned, so as to form the first insulating layer **520** and the third insulating layer **530**, respectively. The second insulating material layer **521** and the third insulating material layer **531** may be simultaneously patterned in one process, and one end of the second insulating layer **520** and one end of the third insulating layer **530** may be aligned with each other.

(206) Next, referring to FIG. **20**, a third contact electrode **363** is formed to simultaneously contact with the other end of the first light emitting element **350a** and the other end of the second light emitting element **350b**. The third contact electrode **363** may be disposed to cover the first insulating layer **510** and a part of the third insulating layer **530**, and may be in contact with the opposing side surfaces of the ends of the first light emitting element **350a** and the second light emitting element **350b** as shown in FIG. **19**.

(207) As described above, since the contact surface of the first insulating layer **510** with the lower surfaces of the first light emitting element **350a** and the second light emitting element **350b** may

extend substantially horizontally in a direction opposite to the direction of each of the electrodes **310** and **320**, the electrode material of the third contact electrode **363** contacting the opposing end side surfaces of the light emitting elements **350a** and **350b** may be smoothly connected. The third contact electrode **363** may be disposed on the third insulating layer **530** to form a third conductive electrode layer CEL3. The third conductive electrode layer CEL3 may be disposed on the second conductive electrode layer CEL2.

(208) A passivation layer **550** is disposed on the third conductive electrode layer CEL3 to cover the plurality of members disposed on the insulating substrate layer **300**. The structure or arrangement of the passivation layer **550** are substantially the same as those described above.

(209) Referring to FIG. **21**, the first electrode stem portion **310S** may be electrically separated along cutting portions CB, so as to manufacture the display device **10** of FIG. **1**. The method of electrically separating the first electrode stem portion **310S** is not particularly limited. For example, the first electrode **310** located at the cut portion CB may be disconnected by using a laser.

Accordingly, the first electrode stem portion **310S** may be disposed in a state where the first electrode stem portion **310S** is electrically separated between the neighboring pixels PX.

(210) The first electrode **310** and the second electrode **320** may be electrically connected to the first thin film transistor **120** and the power supply electrode **162** through the first electrode contact hole CNTD on the first electrode stem portion **310S** and the second electrode contact hole CNTS on the second electrode stem portion **320S**. Accordingly, a current from a driving voltage and a power supply voltage may flow between the first electrode **310** and the second electrode **320**. The first light emitting element **350a** and the second light emitting element **350b**, which are disposed between the first electrode **310** and the second electrode **320**, may be connected in series.

(211) As described above, in the display device **10** according to an exemplary embodiment, the third contact electrode **363** may be disposed between the first electrode branch portion **310B** and the second electrode branch portion **320B**, and thus, the light emitting elements **350** arranged between the electrodes may be connected in series. Accordingly, in the driving of the display device **10**, voltage distribution efficiency, capacity design of the thin film transistor, power loss due to wire resistance, and the like may be improved.

(212) Hereinafter, a display device **10** according to another exemplary embodiment will be described.

(213) The arrangement of the second conductive electrode layer CEL2 provided with the first contact electrode **361** and the second contact electrode **362**, and the third conductive electrode layer CEL3 provided with the third contact electrode **363** is not limited to that of the display device shown in FIG. **1**. For example, the third conductive electrode layer CEL3 may be disposed at a lower position than the second conductive electrode layer CEL2 in a cross-sectional view, and the second conductive electrode layer CEL2 and the third conductive electrode layer CEL3 may be disposed substantially on the same plane. Hereinafter, a display device according to still another exemplary embodiment will be described.

(214) FIG. **22** is a cross-sectional view of a display device according to another exemplary embodiment, and FIGS. **23** to **26** are plan views and cross-sectional views illustrating some processes of a method of manufacturing the display device of FIG. **22**.

(215) Referring to FIG. **22**, a display device **10_1** may be configured such that a third conductive electrode layer CEL3_1 is disposed at a lower position than a second conductive electrode layer CEL2_1 in a cross-sectional view. In particular, in the display device **10_1** of FIG. **22**, a third contact electrode **363_1** may be disposed at a lower position than a first contact electrode **361_1** and a second contact electrode **362_1**. Thus, a third insulating layer **530_1** may be disposed to cover the third contact electrode **363_1**, and the first contact electrode **361_1** and the second contact electrode **362_1** may be disposed on the third insulating layer **530_1**.

(216) The third contact electrode **363_1** is not in contact with a first conductive electrode layer CEL1_1 forming the first electrode **310** and the second electrode **320**. The first conductive

electrode layer CEL1_1 is in contact with the second conductive electrode layer CEL2_1. This arrangement of the second conductive electrode layer CEL2_1 and the third conductive electrode layer CEL3_1 may be formed when the third conductive electrode layer CEL3_1 is arranged prior to the second conductive electrode layer CEL2_1 during the process of manufacturing the display device 10_1.

(217) First, referring to FIG. 23, a second insulating material layer 521_1 is patterned such that the opposing ends of the first light emitting element 350a and the second light emitting element 350b are exposed as shown in FIG. 12. Unlike the display device 10 of FIG. 1, the order of patterning the second insulating material layer 521_1 may be changed, such that the third conductive electrode layer CEL3_1 is disposed first.

(218) Next, referring to FIG. 24, a third contact electrode 363_1 is formed so as to be in contact with the side surfaces of the exposed ends of the first light emitting element 350a and the second light emitting element 350b and a part of the second insulating material layer 521_1. The third contact electrode 363_1 may form the third conductive electrode layer CEL3_1.

(219) Next, referring to FIG. 25, a third insulating material layer 531_1 is formed so as to cover the third contact electrode 363_1 and the second insulating material layer 521_1. The third insulating material layer 531_1 may electrically insulate the third conductive electrode layer CEL3_1 from the second conductive electrode layer CEL2_1.

(220) Next, referring to FIGS. 26 and 27, the second insulating material layer 521_1 and the third insulating material layer 531_1 are patterned so as to expose one end of each of the first light emitting element 350a and the second light emitting element 350b in a direction toward each of the electrodes 310 and 320. A part of a first insulating material layer 511_1 is patterned so as to expose a part of the first electrode 310 and a part of the second electrode 320. Then, a first contact electrode 361_1 and a second contact electrode 362_1 are formed. Here, the first contact electrode 361_1 and the second contact electrode 362_1 may form the second conductive electrode layer CEL2_1, and may be in contact with the first conductive electrode layer CEL1_1.

(221) Unlike the display device 10 of FIG. 1, the display device 10_1 of FIG. 22 may be configured such that the third conductive electrode layer CEL3_1, the third insulating layer 530_1, and the second conductive electrode layer CEL2_1 are laminated in a cross-sectional view. However, as described above, the first conductive electrode layer CEL1_1 may be in contact with only the second conductive electrode layer CEL2_1, and the third conductive electrode layer CEL3_1 may be formed as a floating electrode, to which no electric signal is directly applied from each of the electrodes 310 and 320.

(222) Further, as described above, the second conductive electrode layer CEL2 and the third conductive electrode layer CEL3 may be disposed on substantially the same layer.

(223) FIG. 28 is a cross-sectional view of a display device according to still another exemplary embodiment, and FIGS. 29 and 30 are cross-sectional views illustrating some processes of a method of manufacturing the display device of FIG. 28.

(224) Referring to FIG. 28, a display device 10_2 may be configured such that a third conductive electrode layer CEL3_2 is disposed on substantially the same layer as a second conductive electrode layer CEL2_2. In this case, the third insulating layer 350 may be omitted. This arrangement of the second conductive electrode layer CEL2_2 and the third conductive electrode layer CEL3_2 may be formed when the third conductive electrode layer CEL3_2 and the second conductive electrode layer CEL2_2 are formed simultaneously during the process of manufacturing the display device 10_2.

(225) First, referring to FIG. 29, the second insulating material layer 521 is patterned such that both ends of each of the first light emitting element 350a and the second light emitting element 350b are simultaneously exposed, as shown in FIG. 12, so as to form a second insulating layer 520_2. In the display device 10_1 of FIG. 22, unlike the display device 10 of FIG. 1, the second insulating material layer 521 may be patterned together with the first electrode 310 and the second electrode

320 in a region between the first electrode **310** and the second electrode **320**, such that the third conductive electrode layer **CEL3_2** and the second conductive electrode layer **CEL2_2** are simultaneously placed. After the second insulating layer **520_2** is formed, the first insulating material layer **511** is patterned such that the first electrode **310** and a part of the second electrode **320** are exposed, so as to form a first insulating layer **510_2**.

(226) Next, referring to FIG. **30**, a first contact electrode **361_2**, a second contact electrode **362_2**, and a third contact electrode **363_2** may be simultaneously disposed in one process. Thus, the second conductive electrode layer **CEL2_2** and the third conductive electrode layer **CEL3_2** may be disposed on substantially the same layer. However, the first contact electrode **361_2** and the second contact electrode **362_2** may be spaced apart from each other on the third contact electrode **363_2** and the second insulating layer **520_2**, respectively, and a passivation layer **550** may be disposed in the spaced region as shown in FIG. **28**. The passivation layer **550** may protect the first contact electrode **361_2**, the second contact electrode **362_2**, and the third contact electrode **363_2**, and may electrically insulate them from each other.

(227) The display device according to exemplary embodiments may include light emitting elements, both ends of each which are electrically connected to a first electrode and a third contact electrode or are electrically connected to a third contact electrode and a second electrode. The light emitting elements may be partially connected in series, thereby improving voltage distribution efficiency, the capacity design of a thin film transistor, and the loss due to the wire resistance, in the driving of the display device.

(228) Although certain exemplary embodiments and implementations have been described herein, other embodiments and modifications will be apparent from this description. Accordingly, the inventive concepts are not limited to such embodiments, but rather to the broader scope of the appended claims and various obvious modifications and equivalent arrangements as would be apparent to a person of ordinary skill in the art.

Claims

1. A display device comprising: a first electrode and a second electrode spaced apart from each other, and the first electrode and the second electrode extending in a first direction; a first light emitting element of which a first end is disposed on the first electrode; a second light emitting element of which a first end is disposed on the second electrode; a first contact electrode disposed on the first electrode and electrically contact with the first end of the first light emitting element by directly contacting a vertical edge of the first end of the first light emitting element in a thickness direction intersecting the first direction; a second contact electrode disposed on the second electrode and electrically contact with the first end of the second light emitting element by directly contacting a vertical edge of the first end of the second light emitting element; a third contact electrode spaced apart from the first contact electrode and the second contact electrode; and a third insulating layer having a first part overlapping the first light emitting element including the first end thereof and directly on the first contact electrode, and a second part spaced apart from the first part and overlapping the second light emitting element including the first end thereof and directly on the second contact electrode: wherein the third contact electrode is electrically contact with a second end of the first light emitting element by directly contacting a vertical edge of the second end of the first light emitting element and a second end of the second light emitting element by directly contacting a vertical edge of the second end of the second light emitting element; the first light emitting element and the second light emitting element each comprise a top surface extending, in the first direction, from a top end of the vertical edge of the corresponding first end to a top end of the vertical edge of the corresponding second end directly contacting the third contact electrode, and the third contact electrode is directly on the first part of the third insulating layer and extending continuously in the first direction to be directly on the second part of the third insulating layer.

2. The display device of claim 1, further comprising: a first insulating layer disposed on the first electrode and the second electrode, wherein the first light emitting element and the second light emitting element are disposed on the first insulating layer.
3. The display device of claim 2, further comprising: a second insulating layer disposed on at least portion of the first light emitting element and the second light emitting element; the third insulating layer disposed on the second insulating layer and overlapping at least one end of the first light emitting and the second light emitting element.
4. The display device of claim 3, wherein the first contact electrode and the second contact electrode are disposed on the third insulating layer, and the third contact electrode is disposed between the second insulating layer and the third insulating layer.
5. The display device of claim 1, wherein the first light emitting element and the second light emitting element comprise: a first semiconductor layer; a second semiconductor layer; an active layer disposed between the first semiconductor layer and the second semiconductor layer; and at least one insulating film covering at least an outer surface of the active layer.
6. The display device of claim 5, wherein the first light emitting element and the second light emitting element further comprise at least one contact electrode layer on end of the first semiconductor layer or the second semiconductor layer, and at least portion of a side surface of the contact electrode layer is covered by the insulating film.
7. The display device of claim 5, wherein the active layer of the first light element is located at the second end of the first light emitting element, and the active layer of the second light element is located at the second end of the second light emitting element.
8. The display device of claim 1, further comprising: a first electrode line extending in a second direction intersect with the first direction; and a second electrode line extending in the second direction and spaced apart from the first electrode line, wherein the first light emitting element and the second light emitting element are disposed between the first electrode line and the second electrode line.
9. The display device of claim 8, wherein the first electrode line is electrically connected to the first electrode, and the second electrode line is electrically connected to the second electrode.
10. The display device of claim 1, wherein the first light emitting element and the second light emitting element each comprise an active layer disposed between a first semiconductor layer and a second semiconductor layer in the first direction.
11. The display device of claim 1, wherein the first contact electrode and the second contact electrode are spaced apart from the third contact electrode in the thickness direction by the third insulating layer.
12. The display device of claim 1, wherein the third contact electrode has a lower planar surface coplanar with and directly contacting a bottom surface of the first light emitting element at the second end, the lower planar surface of the third contact electrode extending continuously from the bottom surface of the first light emitting element at the second end in the first direction and coplanar with and directly contacting a bottom surface of the second light emitting element at the second end.
13. The display device of claim 1, wherein the first part of the third insulating layer is spaced apart from the second part by the third contact extending therebetween in the thickness direction and the first direction.
14. A display device comprising: a first electrode and a second electrode spaced apart from each other, and the first electrode and the second electrode extending in a first direction; a first light emitting element of which a first end is disposed on the first electrode; a second light emitting element of which a first end is disposed on the second electrode; a first contact electrode disposed on the first electrode and electrically contact with the first end of the first light emitting element; a second contact electrode disposed on the second electrode and electrically contact with the first end of the second light emitting element; and a third contact electrode spaced apart from the first

contact electrode and the second contact electrode, wherein the third contact electrode is electrically contact with a second end of the first light emitting element and a second end of the second light emitting element; a third electrode spaced apart from the second electrode with therebetween the first electrode; a third light emitting element of which a first end is disposed on the third electrode; and a fourth light emitting element of which a first end is disposed on the second electrode, wherein the second contact electrode is electrically contact with the first end of the fourth light emitting element.

15. The display device of claim 14, further comprising: a fourth contact electrode disposed on the third electrode and electrically contact with the first end of the third light emitting element; and a fifth contact electrode spaced apart from the third contact electrode and the second contact electrode; wherein the fifth contact electrode is electrically contact with a second end of the third light emitting element and a second end of the fourth light emitting element.

16. A display device comprising: a first electrode and a second electrode spaced apart from each other, and the first electrode and the second electrode extending in a first direction; a first light emitting element of which a first end is disposed on the first electrode; a second light emitting element of which a first end is disposed on the second electrode; a first contact electrode disposed on the first electrode and electrically contact with the first end of the first light emitting element; a second contact electrode disposed on the second electrode and electrically contact with the first end of the second light emitting element; and a third contact electrode spaced apart from the first contact electrode and the second contact electrode, wherein the third contact electrode is electrically contact with a second end of the first light emitting element and a second end of the second light emitting element; a third electrode spaced apart from the first electrode; a fourth electrode spaced apart from the third electrode; a third light emitting element of which a first end is disposed on the third electrode; a fourth light emitting element of which a first end is disposed on the fourth electrode; a fourth contact electrode disposed on the third electrode and electrically contact with the first end of the third light emitting element; a fifth contact electrode disposed on the fourth electrode and electrically contact with the first end of the fourth light emitting element; and a sixth contact electrode spaced apart from the fourth contact electrode and the fifth contact electrode, wherein the sixth contact electrode is electrically contact with a second end of the third light emitting element and a second end of the fourth light emitting element.

17. The display device of claim 16, wherein a distance between the first electrode and the third electrode is greater than a distance between the first electrode and the second electrode.

18. A display device comprising: a plurality of pair electrodes including first electrodes spaced apart from each other, and the plurality of pair electrodes comprising a first pair electrode and a second pair electrode spaced apart from the first pair electrode; a second electrode disposed between and physically separated from the first pair electrode and the second pair electrode; a plurality of light emitting elements of which one end is disposed on the first electrode or the second electrode; a first contact electrode disposed on the first electrode of pair electrode and electrically contact with the light emitting element; a second contact electrode disposed on the second electrode and electrically contact with the light emitting element; and a third contact electrode spaced apart from the first contact electrode and the second contact electrode and electrically contact with the light emitting element, wherein a distance between the first electrode and the second electrode is smaller than a distance between the first electrodes of the pair electrode.

19. The display device of claim 18, wherein the light emitting element is not disposed between the first electrodes of pair electrode.

20. The display device of claim 18, wherein the plurality of light emitting elements comprise: a first light emitting element of which a first end is disposed on the first electrode of the first pair electrode; and a second light emitting element of which a first end is disposed on the second electrode, wherein the first end of the first light emitting element is contact with the first contact electrode, the first end of the second light emitting element is contact with the second contact

electrode, and a second end of the first light emitting element and a second end of the second light emitting element are contact with the third contact electrode.

21. The display device of claim 18, further comprising: an electrode line extending in one direction, and the second electrode is electrically connected to the electrode line.

22. The display device of claim 18, further comprising: a first insulating layer disposed on the first electrode and the second electrode; a second insulating layer disposed on at least portion of the light emitting elements; and a third insulating layer disposed on the second insulating layer and overlapping at least one end of the first light emitting and the second light emitting element, wherein the plurality of light emitting elements are disposed on the first insulating layer, the first contact electrode and the second contact electrode are disposed on the third insulating layer, and the third contact electrode is disposed between the second insulating layer and the third insulating layer.

23. A display device comprising: a plurality of pair electrodes including first electrodes spaced apart from each other, and the plurality of pair electrodes comprising a first pair electrode and a second pair electrode spaced apart from the first pair electrode; a second electrode disposed between the first pair electrode and the second pair electrode; a plurality of light emitting elements of which one end is disposed on the first electrode or the second electrode; a first contact electrode disposed on the first electrode of pair electrode and electrically contact with the light emitting element; a second contact electrode disposed on the second electrode and electrically contact with the light emitting element; and a third contact electrode spaced apart from the first contact electrode and the second contact electrode and electrically contact with the light emitting element, wherein: a distance between the first electrode and the second electrode is smaller than a distance between the first electrodes of the pair electrode; the plurality of light emitting elements comprise: a third light emitting element of which a first end is disposed on the first electrode of the second pair electrode; and a fourth light emitting element of which a first end is disposed on the second electrode and contact with the second contact electrode, and the display device further comprises: a fourth contact electrode disposed on the first electrode of the second pair electrode; and a fifth contact electrode spaced apart from the second contact electrode and the fourth contact electrode.

24. The display device of claim 23, wherein the first end of the third light emitting element is contact with the fourth contact electrode, and a second end of the third light emitting element and a second end of the fourth light emitting element are contact with the fifth contact electrode.
