

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396535
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Graf; Fabian et al.

Portable, heatable container

Abstract

A container for storing, transporting, and heating foods and drinks, in particular foods and drinks prepared for consumption by small children and babies. It is intended to be able to be used simply and safely by small children. The container includes a cylindrical outer casing with a closed base, the upper covering surface of which can be closed with a lid. A heatable inner cylinder with a base is arranged in the outer casing.

Inventors:	Graf; Fabian (Zürich, CH), Kenessey; Aron (Meilen, CH)
Applicant:	Faitron AG (St. Gallen, CH)
Family ID:	1000008782450
Assignee:	Faitron AG (St. Gallen, CH)
Appl. No.:	16/474094
Filed (or PCT Filed):	December 18, 2017
PCT No.:	PCT/IB2017/058035
PCT Pub. No.:	WO2018/122669
PCT Pub. Date:	July 05, 2018

Prior Publication Data

Document Identifier	Publication Date
US 20200121047 A1	Apr. 23, 2020

Foreign Application Priority Data

CH	01753/16	Dec. 28, 2016
----	----------	---------------

Publication Classification

Int. Cl.: A45C11/20 (20060101); A61J9/00 (20060101)

U.S. Cl.:

CPC A45C11/20 (20130101); A61J9/008 (20130101);

Field of Classification Search

CPC: A45C (11/20); A61J (9/008); A61J (9/02); A61J (2200/42); H05B (6/105); H05B (6/108); H05B (6/12); H05B (1/0244); A47G (19/2288); A47J (41/0044); A47J (36/2461); A47J (36/2472)

USPC: 206/11.1- 1; 206/541; 219/621

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2551728	12/1950	Cybulski	74/567	B23G 7/00
3745290	12/1972	Harnden, Jr.	220/574	A47J 39/00
3762542	12/1972	Grimes	206/525	A61J 9/008
3869968	12/1974	Ihlenfeld	99/280	A47J 31/0573
4170931	12/1978	Fajans	392/467	A47J 31/053
4354082	12/1981	Tellert	219/625	H05B 6/12
4356382	12/1981	Keramati	417/208	A47J 31/0573
4667085	12/1986	Rommel	219/439	A47J 27/002
4920868	12/1989	Gehrmann	99/279	A47J 31/0573
4930902	12/1989	Yata	374/150	G01K 1/14
4969392	12/1989	Steele	99/305	A47J 31/56
5168793	12/1991	Padamsee	220/592.21	A47J 41/005
5699719	12/1996	Lucas	99/305	A47J 41/0016
5844212	12/1997	Dickens	219/637	B29C 66/81871
5890629	12/1998	Loew	222/144.5	B67D 3/0035
6065609	12/1999	Lake	206/217	A47J 31/02
6072161	12/1999	Stein	219/386	A47J 36/2472
6082591	12/1999	Healey	222/572	B65D 1/023
6286415	12/2000	Leung	99/290	A47J 31/441
6310329	12/2000	Carter	219/442	A47J 36/2461
6793075	12/2003	Jeter	215/11.4	A47G 19/2272
6809302	12/2003	Jones	219/521	A47J 36/2438
6852954	12/2004	Liu	219/387	A47J 36/2472
D538111	12/2006	Liu	D7/608	N/A
7431613	12/2007	Liu	439/248	A47J 36/2472
D589751	12/2008	Liu	D7/510	N/A
7942145	12/2010	Palena	126/263.01	F24V 30/00

8020507	12/2010	Strong	215/11.1	A61J 9/085
8334780	12/2011	Mendoza, Jr.	340/584	A47J 41/0094
8796598	12/2013	England	219/623	A47J 27/002
9485811	12/2015	Sansom	N/A	H05B 3/685
9636281	12/2016	Makrinos	N/A	A61J 9/0623
9801482	12/2016	Alexander	N/A	H05B 1/0244
9995529	12/2017	Banks	N/A	F25B 21/02
10051994	12/2017	Dunn	N/A	A47J 36/2438
11576509	12/2022	Baerman	N/A	A47J 36/2461
2002/0035929	12/2001	Kanba	99/279	A47J 31/0605
2004/0025702	12/2003	Cutter	99/279	A47J 27/21
2004/0065635	12/2003	Turnbough	215/396	A61J 9/00
2004/0140304	12/2003	Leyendecker	219/521	A47J 36/2433
2005/0045624	12/2004	Groll	219/621	A47J 27/10
2006/0120218	12/2005	Lansing	368/10	A61J 7/0409
2006/0162341	12/2005	Milazzo	62/3.6	F25D 31/005
2006/0266224	12/2005	Hammad	99/279	A47J 31/545
2007/0039477	12/2006	Bowden	99/279	A47J 31/005
2008/0041859	12/2007	Teglbjarg	220/592.16	A47J 36/2461
2008/0083692	12/2007	Strickler	215/11.6	A61J 11/045
2008/0142529	12/2007	LaGuardia	220/592.2	G01K 11/165
2008/0179311	12/2007	Koro	219/430	A47J 36/2416
2008/0251063	12/2007	Palena	126/263.09	F24V 30/00
2009/0184081	12/2008	Wu	215/11.1	A61J 9/02
2009/0266240	12/2008	Elissen	99/323.3	A47J 36/165
2010/0116819	12/2009	Pan	219/621	H05B 6/12
2010/0119668	12/2009	Maupin	426/241	A23L 3/32
2011/0048241	12/2010	Smit	99/323	A47J 31/50
2011/0170917	12/2010	Yoshikawa	399/329	G03G 15/2025
2011/0222931	12/2010	Shinshi	399/329	G03G 15/2064
2012/0085724	12/2011	Barker	215/11.2	A61J 9/02
2013/0105468	12/2012	Reischmann	219/622	A47J 36/02
2013/0126551	12/2012	Unger	220/660	B65D 1/0223
2013/0247591	12/2012	DeMasi	62/4	F25D 5/02
2013/0323371	12/2012	Kutcher	99/323.3	A23L 2/38
2014/0001142	12/2013	Wu	215/11.2	A61J 9/02
2014/0048440	12/2013	Prickett, Jr.	206/459.5	B65D 25/205
2014/0061210	12/2013	O'Hanley	220/592.25	A47J 41/0077
2014/0072287	12/2013	Zakowski	392/394	A47J 36/2433
2015/0122765	12/2014	Cannon	215/11.2	A61J 9/085
2015/0182063	12/2014	Mills	99/283	A47J 31/40
2015/0245421	12/2014	Heczko	99/323.3	H05B 6/1245
2015/0245723	12/2014	Alexander	219/387	A47J 39/025
2015/0250683	12/2014	Cross	206/459.1	A61J 9/06
2015/0366759	12/2014	Perera	215/11.1	A61J 9/008
2015/0375900	12/2014	Larson	206/459.5	B65D 23/0828
2016/0068294	12/2015	Gorbold	215/12.1	C03C 8/08

2016/0242598	12/2015	Alexander	N/A	H05B 3/06
2016/0278568	12/2015	Richter	N/A	A47J 31/057
2017/0075312	12/2016	Hammond	N/A	A61J 9/00
2017/0087524	12/2016	Deshpande	N/A	B65D 51/2892
2017/0094721	12/2016	Moore	N/A	B65D 1/02
2017/0210516	12/2016	Tebbe	N/A	B65D 43/166
2017/0295992	12/2016	Mangold	N/A	A47J 31/467
2017/0318999	12/2016	Han	N/A	A47J 31/4478
2018/0243173	12/2017	Kessels	N/A	G01F 15/063
2019/0015299	12/2018	Pyka	N/A	A61J 9/06
2019/0096224	12/2018	Shoham	N/A	G08B 21/182
2019/0269578	12/2018	Goodin	N/A	A47J 36/2433
2019/0298616	12/2018	Quintero	N/A	A61J 11/008
2020/0297149	12/2019	Park	N/A	A47J 27/21091
2020/0377285	12/2019	Beckham	N/A	B65D 81/3876

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2874482	12/2015	CA	A23L 33/40
106073385	12/2015	CN	A47G 19/2288
207996308	12/2017	CN	N/A
110638655	12/2019	CN	N/A
10 2007 036 361	12/2008	DE	N/A
2020 130 10997	12/2013	DE	N/A
102014111817	12/2015	DE	A47J 27/21008
202019105723	12/2020	DE	A61J 9/008
2551728	12/1982	FR	B65D 25/56
05111437	12/1992	JP	N/A
WO-0207575	12/2001	WO	A47J 27/21041
WO-2008038054	12/2007	WO	B65D 51/226
WO-2010087560	12/2009	WO	A61J 9/02
2011/112284	12/2010	WO	N/A
WO-2013097977	12/2012	WO	A47J 31/057
2015/177726	12/2014	WO	N/A
WO-2016160019	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report for PCT/IB2017/058035 filed dated Feb. 23, 2018. cited by applicant
Office Action dated Sep. 24, 2024 for EP17 829 297.5. cited by applicant

Primary Examiner: Cheung; Chun Hoi

Attorney, Agent or Firm: Pleit Intellectual Property Law

Background/Summary

FIELD OF THE INVENTION

- (1) The invention relates to a lunch container for storing, transporting and for heating foods and drinks, in particular food and drinks prepared for consumption by small children and babies.
- (2) This is a lunch container which allows pre-prepared foods and drinks, for instance for on the go or for journeys to be transported and heated up within minutes in situ and thereby makes it possible to have a hot meal or hot drink, in particular milk, anywhere and at any time.

BACKGROUND

- (3) Known are heatable lunch boxes with a hinged lid or sides wherein closing of the lid or sides takes place by means of a zip fastener or Velcro strip.
- (4) A container for foodstuffs, in particular bread and toppings, according to WO 2011/112284 A1 has a flexible partition in order to produce an upper and a lower bowl. It serves exclusively to maintain an existing temperature of the food by means of an inserted heating or cooling gel.
- (5) From DE 202013010997 U1 a folding container is known which is designed in such a way that on folding out an upper bowl nothing can fall out. The folding container comprises an upper bowl and a lower bowl which are connected to each other in a hinged manner on one longitudinal side. On the opposite longitudinal side a snap-type connection is provided. The upper bowl is provided with an upper inner lid and the lower bowl with a lower inner lid so that both inner volumes can be closed off completely and independently of each other. On each side opposite the linkage of the inner lid a lid closure in the form of a snap-in projection is provided in the upper bowl and the lower bowl.
- (6) Disclosed in WO 2015/177726 A1 is a lunch box which is suitable for storing, transporting and heating foodstuffs, in particular ready-to-eat foods. It comprises an upper bowl and a lower bowl which are connected to each other in a hinged manner on one longitudinal side, wherein on the opposite longitudinal side a closure is provided. Arrangeable in the lower bowl is an inner bowl with a circumferential and angled edge area, to which is assigned thermal insulation and a heating element, wherein moulded into the circumferential edge of the inner bowl is a groove for receiving a seal.
- (7) The aforementioned prior art is not suitable for use by small children and also not for the storage, heating and keeping warm of drinks. Known, however, are normal baby bottles which can be inserted into a multisided heating container, comparable with a water bath with heating elements.

- (8) In addition there are normal coffee beakers for on the move, which heat up from the bottom, but which are only designed for hot drinks and for adults.

SUMMARY OF THE INVENTION

- (9) One aspect of the invention relates to a lunch container for small children and babies which is suitable for storing, transporting and for heating foods and drinks and which can be used simply and safely by small children.
- (10) In an embodiment, the lunch container, which in terms of its external appearance is designed in similar way to a drinks bottle. It comprises an essentially cylindrical and thermally insulating outer casing with a closed base, the upper covering surface of which can be closed with a lid. Arranged in the outer casing is a, preferably wirelessly, for example inductively heatable inner cylinder with a base. In particular, paste-like foods and drinks such as milk or tea can be heated.
- (11) In order to heat the foods or drinks, particularly the base and also the wall of the inner cylinder can be heated. Inversely cooling is also possible. Thanks to the insulation of the outer casing used this can scarcely become warmer than hand temperature. When using the lunch container the sustaining of injuries, in particularly burns, by the user, an adult as well as a baby or small child can thus be ruled out.
- (12) Energy for the inner cylinder is preferably supplied wirelessly and/or inductively so that the outer casing may not have to have any connections or switches. When on the go the use of a power

pack or something similar is also possible. A charger can be based on the usual mains system of 230V AC or also 5/20V or 12/24V DC so that connection to a computer by way of a USB interface or to a cigarette lighter of a car is possible.

(13) In the previously known containers or coffee beakers on the other hand, paste-like foods for children cannot be heated and cannot be consumed directly by small children.

(14) Preferred embodiments of the invention are also disclosed.

(15) For a visible indication of the filling level of the inner cylinder this can be provided with a, preferably transparent, slit with a corresponding shape on the outer casing, Alternatively an optical/electronic display is also possible.

(16) For example, the lid can be provided with an inner thread for screw connection to an outer thread of the outer casing. To facilitate handling by children the lid is preferably provided with at least one moulded-on handle, wherein the handle can also be fastened on the lid. Particularly preferably two handles are provided. The handle is designed in such a way that small children of various ages can securely grasp it.

(17) In a further preferred embodiment the lid is provided with an opening for receiving a teat. The teat can be adapted to the dispensing of fluids or pasty foods. The opening and teat can be protected against external influences by a mountable protective cap.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The invention will be described in more detail below in examples of embodiment by means of the drawing and its function will be explained. In these,

(2) FIG. 1: shows a lunch container in accordance with the invention with a teat;

(3) FIG. 2: shows a lunch container according to FIG. 1 with a protective cap

(4) FIG. 3: shows a charger for the lunch container;

(5) FIG. 4: shows the lunch container according to the invention in another form of embodiment;

(6) FIG. 5: shows the lunch container according to the invention in a further form of embodiment.

DETAILED DESCRIPTION OF THE INVENTION

(7) A lunch container **1** according to the invention is similar in dimensions to a short and broad drinks bottle or cup.

(8) FIG. 1 shows an embodiment of a lunch container **1** according to the invention. It comprises an essentially cylindrical and thermally insulating outer casing **2** with a closed base, the upper cover surface of which is closed with a lid **3**.

(9) Arranged in the outer casing **2** is a preferably wirelessly, for example, inductively heatable inner cylinder **7** with a base **8**. If this is not possible when used on the go, a USB connection or DC plug, not shown, to a power pack, which is not shown, can be produced.

(10) Instead of being a heatable inner cylinder **7**, the inner cylinder **7** can be surrounded by a mat-like heating element **16** which brings about heating of the inner cylinder **7**.

(11) The end surface of the inner cylinder **7** facing the lid **3** is open.

(12) Thanks to the insulation of the outer casing **2** that is used, the latter can hardly become warmer than hand warmth. When the lunch container is being used it can therefore be ruled out that the user, an adult as well as a baby or small child will incur injuries, in particular burns.

(13) For a visible indication of the filling level of the inner cylinder **7** it is provided with a slit **9** of transparent or translucent plastic with a corresponding shape in the outer casing **2**. The filling level can thereby be inspected from outside.

(14) Alternatively optical/electronic displaying of the filling level is possible.

(15) Applied on the outer casing **2** is also a, for example, annular temperature indicator **11** which, for instance by means of LEDs illuminated in colour, shows certain temperatures of the drink or a

food present in the container. For example a green LED in the case of an appropriate drinking/eating temperature or a red or blue LED in the case of too high or too low a temperature. (16) As shown, the outer casing **2** can be designed in one part or also in two parts. In the two-part embodiment the outer casing **2** has a lower section and an upper section with an annular temperature indicator located between them (FIG. 4).

(17) The lid **3** is provided with an inner thread for screwing onto an outer thread of the outer casing **2**.

(18) To facilitate handling by children the lid **3** in this form of embodiment is provided with two moulded-on handles **4** which are shaped in such a way that they can be securely grasped by small children or different ages.

(19) The lid **3** is also provided with an opening **13** for receiving a base **6** of a teat **5** (known from drinks bottles). Preferred here are snap-on or click-on connections in the case of elastic plastic materials or pressing in of the base **6** into the opening in the case of deformable, rubber-like materials of the teat **5**.

(20) The opening **13** and teat **5** can be protected against outside influences by a protective cap **14** mountable on the lid **3** (FIG. 2).

(21) Depending on the consistency of the paste-like food or the drinks, teats **5** of different, more particularly elastic materials and with a different teat opening are available.

(22) Heatable in particular are paste-like foods and drinks, such as milk or tea.

(23) In the shown form of embodiment energy for the inner cylinder **7** and the base **8** is supplied wirelessly and inductively so that the outer casing **2** does not have to have any connections or switches. For this, the lunch container **1** according to the invention is placed with the base of the outer casing **2** onto the charging surface of a corresponding charging device **12**. The charging device (FIG. 3) can be based on the conventional mains network of 110-230V AC, or on 5/20V or 12/24V DC so that connection to a computer by means of a USB interface or to a cigarette lighter of a car is possible.

(24) FIG. 5 shows the lunch container **1** in a further form of embodiment with a heightened lid **3**. The lid **3** can therefore be designed without a handle or can only have one handle **4**.

(25) Heating of the food or the drink can be controlled conventionally or by means of an app via a mobile phone **15** so that the user can precisely set and control a predetermined temperature. Various heating programs are also possible.

(26) A possible electronic control system comprises the electronic circuit, a safety circuit, a power switch and also a power pack. The electronic circuit should comprise at least a temperature sensor, a heating switch, a start-stop switch and the output for the LEDs. The electronic circuit can also allow various heating modes.

(27) In the known manner, the heating element of the inner cylinder **7** and the base **8** comprise, for example, a metallic heating foil or the inner cylinder **7** and the base **8** are themselves designed as a heating element.

LIST OF REFERENCE NUMBERS

(28) **1** Portable, heatable container **2** Outer casing **3** Lid **4** Handles **5** Teat **6** Base of teat **7** Inner cylinder **8** Base of inner cylinder **9** Slit **10** Filling level indicator **11** Temperature indicator **12** Charging station **13** Opening for receiving base of teat **14** Protective cap **15** Mobile phone **16** Heating element

Claims

1. A container configured for storing, transporting, and heating foods and drinks, the container comprising: a thermally insulating essentially cylindrical single walled outer casing comprising two separate parts consisting of a lower section and an upper section, the lower section and the upper section of the outer casing having an illuminated annular temperature indicator therebetween; a

heatable single walled inner cylinder arranged and contained within the outer casing; and a lid configured for releasably closing an upper surface of the upper section of the outer casing, wherein an outer surface of the outer casing maintains a temperature that prevents injury to a user holding the container when the container is being heated and during use after heating, and the container further comprises heating elements that can only heat the inner cylinder when the container is engaged with a charging station.

2. The container according to Claim 1, wherein the heatable inner cylinder includes a filling level indicator.
 3. The container according to Claim 1, wherein the lid includes an inner thread for engaging with an outer thread of the outer casing.
 4. The container according to Claim 1, wherein the lid includes at least one moulded-on handle.
 5. The container according to Claim 1, wherein the lid includes an opening for receiving a base of a teat.
 6. The container according to Claim 1, wherein the container is configured for engagement with a charging station, the inner cylinder being configured to be inductively heated when the container is engaged with the charging station, and the inner cylinder being configured to not be heatable when the container is not engaged with the charging station.
 7. The container according to Claim 1, wherein the heatable inner cylinder includes a filling level indicator and the outer casing includes a transparent slit therethrough for viewing the filling level indicator.
 8. The container according to Claim 1, wherein the container is configured for inductive heating of the inner cylinder that is controllable by an App of a mobile phone.
 9. The container according to claim 1, wherein the heatable inner cylinder includes a base and a side wall that are themselves the heating elements of the container.
 10. The container according to Claim 1, wherein no power storage elements are located between the outer casing and the inner cylinder or below the base of the inner cylinder.
 11. The container according to Claim 1, wherein no control circuitry is located between the outer casing and the inner cylinder or below the base of the inner cylinder.
 12. The container according to claim 1, wherein the container is configured to be inductively heated by the heating elements, and at least part of the inner cylinder itself comprises the heating elements for inductively heating the container.
 13. The container according to Claim 12, wherein the base and the side wall of the inner cylinder are configured to be inductively heated.
-