

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396922
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Tsai; Ching-Fu

Device, body, method and system for health-care

Abstract

A health care device includes a health care body for positioning a body part of a user, so as to maintain a first specific positional relationship with the body part, wherein the body part has an acupoint; an acupoint work piece for performing a health care work onto the use through the acupoint; and a work piece holder having a first end connected to the health care body and a second end for fixing the acupoint work piece, so that under the first specific positional relationship, the acupoint work piece performs the health care work under the condition that the acupoint work piece has a second specific positional relationship with the acupoint. A health care body, method and system are also provided.

Inventors:	Tsai; Ching-Fu (Taipei, TW)
Applicant:	TAO MINING CO., LTD. (Taipei, TW)
Family ID:	1000008782373
Assignee:	TAO MINING CO., LTD. (Taipei, TW)
Appl. No.:	17/801698
Filed (or PCT Filed):	April 30, 2020
PCT No.:	PCT/CN2020/088533
PCT Pub. No.:	WO2021/217675
PCT Pub. Date:	November 04, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230133328 A1	May. 04, 2023

Publication Classification

Int. Cl.: **A61H39/04** (20060101); **A61H39/00** (20060101); **A61H39/06** (20060101); **A61H39/08** (20060101); **A61N2/00** (20060101); **G16H70/20** (20180101)

U.S. Cl.:

CPC **A61H39/04** (20130101); **A61H39/002** (20130101); **A61H39/06** (20130101); **A61H39/08** (20130101); **A61N2/006** (20130101); **G16H70/20** (20180101); A61H2039/005 (20130101); A61H2201/0119 (20130101); A61H2201/0192 (20130101); A61H2201/0196 (20130101); A61H2201/0207 (20130101); A61H2201/0221 (20130101); A61H2201/0278 (20130101); A61H2201/1207 (20130101); A61H2201/1246 (20130101); A61H2201/1436 (20130101); A61H2201/1604 (20130101); A61H2201/1607 (20130101); A61H2201/1635 (20130101); A61H2201/164 (20130101); A61H2201/165 (20130101); A61H2201/1659 (20130101); A61H2201/1671 (20130101); A61H2201/1676 (20130101); A61H2201/5071 (20130101); A61H2203/0468 (20130101); A61H2205/022 (20130101); A61H2205/04 (20130101); A61H2205/067 (20130101); A61H2205/081 (20130101); A61H2205/108 (20130101)

Field of Classification Search

CPC: A61H (2201/1607); A61H (2201/164); A61H (2201/165); A61H (2205/108); A61F (5/3761); A61F (5/3769)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10307332	12/2018	Cheng	N/A	A61H 39/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201959428	12/2010	CN	N/A
203647552	12/2013	CN	N/A
105056403	12/2014	CN	N/A
205094975	12/2015	CN	N/A
105816316	12/2015	CN	N/A
106726467	12/2016	CN	N/A
107213013	12/2016	CN	N/A
108524257	12/2017	CN	N/A
109011174	12/2017	CN	N/A
209137280	12/2018	CN	N/A
209809013	12/2018	CN	N/A
20020028036	12/2001	KR	N/A
2015037763	12/2014	WO	N/A

OTHER PUBLICATIONS

International Search Report issued in corresponding International Patent Application No. PCT/CN2020/088533 on Jan. 28, 2021, consisting of 8 pp. (English Translation Provided). cited by

applicant

Written Opinion issued in corresponding International Patent Application No.

PCT/CN2020/088533 on Jan. 28, 2021, consisting of 4 pp. cited by applicant

Office Action issued in corresponding Taiwanese Patent Application No. 109114665 on Jul. 16, 2020, consisting of 7 pp. cited by applicant

Office Action issued in corresponding Taiwanese Patent Application No. 109114666 on Dec. 28, 2020, consisting of 7 pp. cited by applicant

Office Action issued in corresponding Taiwanese Patent Application No. 109114667 on Dec. 25, 2020, consisting of 8 pp. cited by applicant

Office Action issued in corresponding Taiwanese Patent Application No. 109114665 on Apr. 16, 2021, consisting of 4 pp. cited by applicant

Primary Examiner: Woo; Julian W

Attorney, Agent or Firm: Volpe Koenig

Background/Summary

FIELD OF THE INVENTION

(1) This invention relates to device, body, method and system for health-care, especially based on Chinese medical theory.

BACKGROUND OF THE INVENTION

(2) Those who lose their health will know that being sick-free or painless is a great blessing in life. Human nature is usually greedy for life and fear of death. It is one of the big desires of ordinary people to get life prolonged. Everyone seems to agree that prevention is better than cure, but facing the life journey of birth, aging, sickness and death, not everyone has the opportunity or the perseverance to always pay attention to prevention. The invention follows the examples of Chinese genius doctors Hua Tuo and Bian Que, and is intended to bring health and happiness to mankind.

SUMMARY OF THE INVENTION

(3) Because of extremely diversified disclosures of the present inventions, for facilitating the examination, it is to be noted that the claims currently on file of this application are directed to seek patent protections for specific inventions exemplarily embodied in FIGS. 4A to 5A. In a nutshell, the present invention hopes to bring Hua Tuo and Bian Que back to the world. The ensuing questions are: how to perform dreams or ideals? How to put imagination into practical content? Because the issues are very big, readers or examiners are invited to carefully review and examine what are described later.

(4) Traditional Chinese medicine or acupuncture theory is scattered in ancient Chinese classics, where the cores or subtle implications thereof are described in Huangdi Neijing Suwen and Lingshu. Among these cultural treasures, not only can we see the exquisiteness of medical theory or logic, but they have also been seen clinically effective or widely reported, which cannot be extensively quoted here. For example, acupuncture and moxibustion have an extremely effective analgesic effect in clinic. For some organic diseases, even cancer, the analgesic effect can be maintained for a week, which was frequently reported.

(5) It is recorded in Bazheng Gods Thesis Chapter, Suwen, The Yellow Emperor's Neijing that “observing the unknown world means that the shape, Qi (vitality), Rong and Wei are invisible to the outside, while the artisan (i.e., medical expert, good doctor, Hua Tuo or Bian Que) knows it well. Because coldness and warmth of the sun, emptiness of the moon, ups and downs of the air in the four seasons, and variation of their combination, participation and arrangement are invisible to

or unrecognized by the general public but detected by the artisan, it is thus called observing the unknown world. Only those that are communicable to the infinite future can be passed on to later generations. That which has been detected different by an artisan is externally invisible and cannot be entirely seen. As it is not tangibly visible and cannot be tasted, it is thus called unknown world, just like talking about the gods.” The Chapter continues with “an insufficient evil means one Qi deviated from eight righteous ones. A normal evil happens when one labors to sweat into running into an evil wind through the muscles texture, which, however, is mild and not felt or discernible.” The Chapter continued, “a superior artisan cures a potential sickness upon its burgeoning through detecting Qis by checking 9 pulses in three parts and is so qualified through adequately regulating the Qis. An inferior artisan gets rid of a sickness after it has been fully developed or the yin-yang Qi balance has been broken. The need to cure a sickness after it has been developed comes from the failure in detecting the yin-yang unbalance after checking 9 pulses in the three parts. Such artisan can cure a sickness after it has been fully developed to be known as the sickness and eventually cure the sickness through confirmations from 9 pulses in the three parts. Such artisan is merely like a doorkeeper because it cannot know what is budding but what the outbreak evil is.” The purpose and ideal of the present invention are to equip every family or person with a caring superior doctor for life.

(6) Patent examination is to determine whether an invention is different from conventional technology, and an invention is often originating from the lack or deficiency of conventional technology. The value of an invention to mankind depends on how much it contributes to society, while the patent or market value of an invention depends on whether it is practical or not, and whether all competitors have to follow suit. Although the various values of an invention are not necessarily related to the level of technology or the exquisiteness of the skill, it should be worthy of our efforts if we can solve some problems systematically or comprehensively and achieve the effects of human relief. What follow will make a comprehensive review of related technologies. Wherever there are discussions about existing technologies, it is possible to capture the source of creativity or ideas.

(7) From the perspective of “modern science”, acupuncture is a phenomenon of sensing along the meridians. This can be learned by those with acupuncture experience: when acupuncture is applied at the correct point, the patient will feel a special feeling along the corresponding meridian lines, and the sensation is often soreness, swelling, numbness, heat, cold, pain or electric shock. These feelings may appear alone, but most of them are mixed feelings of soreness, swelling, and numbness. The ancient book names it qi sense, or qi obtainment. At this time, the person applying the needle will also perceive that the needle seems to be sucked, awkwardly operable, not easy to turn, and not easy to be pulled out.

(8) In modern society having a tight or speedy pace, acupuncture and moxibustion have once been ignored because of their insufficient consideration in hygiene in the past and slow curative effects. There are lots of efforts tried to construct modern theories therefor, such as material metabolism theory or energy metabolism theory, either from molecular, atomic or particle aspect or wave aspect where it is proposed that there are many optically non-uniform tubular structures or sheet-like structures in the human body, in which because they are not uniform either in the performance of visible light reflection, refraction coefficient, and polarization ability, or in the performance of infrared or microwave reflection, refraction coefficient, and polarization ability, an electromagnetic wave guide system is thus formed in the human body.

(9) According to the above, the internal qi of traditional Chinese therapy is the relationship among electromagnetic waves, meridians and acupoints in the human body. The slow speed of the sense transmission along the meridians is derived from the group speed of the waveguide. Meridians are not like blood vessels, lymphatic vessels or nerve fibers with clear boundaries, but are strip-shaped areas with fuzzy boundaries and with the highest conductance value on the central axis of each meridian, while radially diminishing gradually from the central axis. Specifically, the meridians are

like mountains, and the acupoints are like individual peaks on the mountains. In other words, the center of the acupuncture point is the top of each mountain peak. However, with continuous conductance measurement at the same point, the conductance of the human body fluctuates with the time, which the ancients called the Ziwu Liuzhu, that is, the qi and blood flow dynamically circulate in the body in accordance with the season, moon phase, and time. Nevertheless, this conductance change happens throughout the entire body and does not seriously affect the difference between acupoints and non-acupoints, so it does not affect the clinical conductance measurement.

(10) What surprises the modern science (especially modern medicine or modern biology) is the holographic phenomenon of the acupoints. Regarding the so-called holographic phenomenon, regardless of ear acupuncture or foot massage, in a small area, there are acupoints reflecting all the organs of the whole body. Even in each small finger joint area, acupoints reflecting all the organs of the whole body can be found. In other words, when a certain organ has a disease, not only the conductance of the main acupoints on the 14 main meridians increases significantly, but also in the local area of the specific acupoint. It is thus quite possible that every point in the body is a micro meridian point.

(11) When a person's physiological or psychological state changes, the probability distribution curve of conductance data in any area of the body will change accordingly, and it seems that the mystery of the meridian points will eventually be revealed. Meridians are electrical channels, optical channels, microwave channels, sound channels, and chemical channels. What is measured on the meridian points is not skin resistance, but body conductance or electric field strength, where conductance is proportional to the square of the conductance field strength. It thus can be concluded that the meridian system in the scriptures is a kind of energy distribution in the human body. This energy distribution can neither be seen with the naked eye, nor be tracked with a scalpel.

(12) The energy distribution structure in the preceding paragraph is understood by modern physics as a dissipative structure being a dynamic structure. It exists by continuous energy supply and fully conforms to the dissipative structure formed by electromagnetic waves, which cannot be simply understood from physiology. But understanding Chinese classical medicine in this way may bring physiology, biology and medicine to a new milestone. The so-called dissipative structure, taking a dynamic waterfall as an example, can only exist when there is a source of high water level, and once the source stops, the waterfall will disappear quickly. Because the prerequisites are that the structure is constantly consuming energy, it is called the dissipative structure. Others, such as candles, mountain springs, fountains, lanterns, sky lanterns, flutes, whirlpools, tornadoes, and lightning, are all living structures. Once the environment is closed, this structure will instantly disappear.

(13) The meridian system is a kind of dissipative structure formed by electromagnetic standing waves. Because two waves can exist in the same position and superimpose or cancel each other, new interference waves are formed by point-by-point construction or destruction. When the human body meridian system may be understood as a three-dimensional electromagnetic standing wave interference pattern, we could then find ways to interfere and/or change its interference pattern to change the energy distribution and restore the patient's health. It may be magical, but for thousands of years, the ancestors used a single needle to heal countless ancestors with Qi and blood circulation, deficiency syndrome, excessiveness syndrome, Ziwu Liuzhu, qi obtainment, yin and yang, tonic method, and draining method.

(14) Regardless of whether coming from health concerns, the traditional acupuncture has been developed to include many other ways to change the aforementioned interference patterns, such as hyperthermia, infrared therapy, spectrum therapy, electroacupuncture, laser acupuncture, microwave acupuncture, etc., all of which belong to non-intrusive or non-contact interference and change media.

(15) The dissipation theory or structure mentioned above, where playing Dongxiao involves the

same theory and the human body is also a resonant cavity, contains numerous electromagnetic standing waves interacting with each other to form complex standing wave interference patterns while acupuncture points play a key role in interfering with individual or combined standing waves, because acupuncture points always have the highest conductance, or are the places where the peaks of individual or combined electromagnetic standing waves are located. Specifically, when a certain organ has a problem, its natural frequency or accompanying standing wave changes. As a result, the energies of some acupuncture points increase or decrease abnormally, and the resistances on the acupuncture points in turn decrease or increase accordingly. Therefore, no matter whether it is intrusive or non-intrusive, we can build/destroy/correct individual or total standing waves through acupoints, so that the organs or patients can return to normal/healthy.

(16) Light and microwaves are both electromagnetic waves. The light commonly referred to by the world refers to visible light, which only occupies a very small share of the entire electromagnetic spectrum. The transmission speed of a single electromagnetic wave is extremely fast (up to 300,000 kilometers per second), but the transmission speed of the meridian sense is less than ten centimeters per second (where it takes tens of minutes to convert from one interference pattern to another). The reason is that the number of electromagnetic waves in the body is counted in billions (or even tens or tens of billions), and the propagation speed of the summing signal is accordingly reduced. This is also the reason why we often hear that any object is nothing but a mass of vibration frequencies.

(17) Non-intrusive acupuncture and moxibustion, such as laser acupuncture, although it is called a kind of acupuncture, there is no actual puncturing action. Because it is non-intrusive, safe and painless, it is easily accepted by patients. More and more new treatments having effects not inferior to the traditional acupuncture and moxibustion are reported. Although the laser acupuncture is a painless and safe treatment option, clear dosage guidelines have yet to be established. Other non-intrusive acupuncture and moxibustion, such as the now popular physiotherapy techniques, such as hyperthermia, infrared therapy, spectrum therapy, electroacupuncture, microwave acupuncture, etc., because they all introduce electromagnetic waves of different wavelengths into the human body, they should also have standards to be established.

(18) In Western society, microwaves with a frequency range of 40-70 GHz are used to balance and treat the unique frequency (characteristic frequency) of a person (or even a specific organ), which is called Microwave Resonance Therapy (MRT). Of course, microwave acupuncture is also based on acupuncture. It is a method of infusing microwaves with the same frequency as the characteristic frequency into acupuncture points or directly irradiating acupoints to generate resonance to treat diseases by connecting a microwave antenna to the needle handle. In practice, it is found that the resonance frequency in the meridian channels will flow from the internal organs to tips of the fingers or toes, and then be reflected back to the organs. When sick, the amplitude of the inherent frequency (characteristic frequency) will decrease or disappear. An extra energy with a very low energy level (one millionth or one billionth of a watt) can restore the resonance frequency of a specific organ or human body to the standard value, thereby helping/completing the treatment.

(19) In 1934, the professional Journal of Acupuncture and Moxibustion in China published the clinical application of electroacupuncture for the first time. In the late 1950s, there were extensive researches on electroacupuncture and it was used clinically for surgical anesthesia. Modern electroacupuncture devices are small in size, often powered by batteries. Small clips are connected to the wires from the device and clamped on the acupuncture needles inserted into the body. When the electric current is generated, the patient feels a slight beating or fluctuating sensation, as if a feather is sweeping the skin. Of course, we should avoid placing electrodes near the heart, or not allow current to pass through the midline of the body (i.e. an imaginary line from the nose bridge to the navel).

(20) Either the “Bianque-A Microwave Acupuncture Apparatus” developed by Beijing Electronic Instrument Factory in 1980, or the various acupoint therapy apparatuses that have sprung up recently, in order to meet the needs of different diseases or different parts, their appearances look

very different. They all suffer from difficulties in accurately aligning with the acupoints, but require the assistance of the patient or the user, such as trying to keep the affected part deliberately attached to or close to the working surface of the respective instrument, in order to better obtain the service or treatment effect from the instrument. In addition, in order to cope with the continuous renovations of laser acupuncture, hyperthermia, infrared therapy, spectrum therapy, electroacupuncture, microwave acupuncture, etc., because of their different working principles, if we want to obtain the therapeutic effect, the instrument itself or the working point, working surface or working area of the instrument must be different. In order to have a relatively accurate positional relationship between the acupuncture points on the human body to be worked and the working point, working surface or working area of the instrument, for achieving a better therapeutic effect, usually the manual of the instrument will explain how to self-adjust the body posture, or the operator will assist in adjusting the patient's posture for receiving instrument/treatment services. For example, the circular or arcuate treatment instrument is mostly used for joints, shoulders, waist, etc.; the elongate treatment instrument is suitable for acupoints in elongate regions such as the spine or body part. Nevertheless, as mentioned above, either the user needs to cause her/his the affected part close to or attach to the working point, working surface or working area of the instrument, or it is necessary to put the instrument directly on the patient's body, so that the working point, working face or working area of the instrument can serve (e.g., irradiate) the affected area. At this time, the patient's affected part (or acupuncture points on the affected part) and the working point, working surface or working area of the instrument in fact only maintain in a rough, roughly or almost correct relative positional relationship. This kind of arrangement not only results in the positional discrepancy between the instrument and the patient, but also in angular relationship therebetween, and even in the distance therebetween. The correctness or properness of the distance between the instrument and the affected part of the patient usually determines whether the best effect can be obtained, or whether it will unfortunately cause harm to be detailed later.

(21) If we use the microwave acupoint therapy device for explanations in details, we can understand the aforementioned difficulties. Specifically, the effects of microwave therapy are usually based on thermal effects, but non-thermal effects cannot be ruled out (e.g., local microwave acupoint stimulation may be conducted through the meridians for producing effects of “guiding qi to where the disease exists”). The maximum microwave radiation can penetrate 50 millimeters into the body surface, and the body temperature of the exposed area can be significantly increased, which is deeper and stronger than the heat of moxibustion. The distance between the patient's affected part (or acupuncture points on the affected part) and the working point, working surface or working area of the instrument as mentioned in the preceding paragraph obviously determines whether the affected part will be burned by moxibustion.

(22) When microwaves irradiate the human body, there are mainly two effects, namely thermal action and thermal external action (which is different from ultrashort wave, where the latter is produced by electric current, while the former by electromagnetic wave). The so-called thermal action comes from the oscillation of electrolyte ions and electrolyte dipoles, or the high-frequency oscillation of water molecules, which causes the tissue to generate a large amount of heat energy, thereby increasing the tissue temperature, dilating blood vessels, and accelerating blood flow (which can increase by 50%). The so-called thermal external effects are the special physiological effects of microwave radiation on the human body (where the relevant research is still limited), and known to possibly affect the function of the nervous system (where short-term or low-dose radiation can enhance the excitatory process, while long-term or large-dose radiation reverses inhibition). Compared with infrared radiation and other light radiations, microwave has a deeper effect, that is, it is difficult for infrared to penetrate the lipid layer, but microwave can penetrate the lipid layer to reach the muscle layer. The therapeutic effects thereof are not to be detailed here.

(23) Microwave acupuncture has a strong qi sense (swelling, heavy, soreness, numbness, feeling hot, sensation of movement and warmth) to the meridian points, and can be conducted along the

meridian for sweating (similar to the Burning Mountain Fire skill). Further, the strength of the qi sense can be quantitatively controlled by the microwave treatment instrument. Microwave acupoint irradiation has functions of both acupuncture and warm moxibustion. When the microwave power reaches a certain value, there is a high-frequency discharge phenomenon on the needle tip, but its power (2 watts) is much less than that of the microwave physiotherapy machine (200 watts), so no special protection is required.

(24) Microwave acupuncture point therapy instruments can be roughly divided into three categories: one is microwave radiator (which is straightforwardly directed at acupoints or lesions and is similar to laser irradiation at acupoints), the second is microwave acupuncture (therapy) instrument (having a radiation antenna needle for radiating acupuncture points), and the third is the magnetic needle.

(25) Microwave acupuncture point radiators or microwave radiators generally include 5 types: (1) circular radiator, whose opening end is round, and whose external shape is hemispherical, cylindrical, reflective mask-shaped, etc., mainly used for acupoints at joints, shoulders or waist, or breast lesions; (2) elongate (or rectangular) radiator having a rectangular opening, and mostly used in elongate areas of the body, such as the spine or body part; (3) saddle-shaped radiator having a concave surface, used to treat acupuncture points at large areas such as waist, knee, back, hip, buttocks, chest or abdomen, and capable of being directly attached to the affected surface for treatment; (4) focusing radiator, with a diameter of 1, 1.5, or 3.5 cm, used to treat small parts not suitable for treatments by the aforementioned three kinds; and (5) ear radiator, which is dedicated to irradiate ear acupoints or be inserted into the ear canal for treatment and has a replaceable rubber sleeve.

(26) The microwave acupuncture instrument consists of four parts: a DC variable power supply, a microwave oscillator (1,000-2,000) MHz, an output coaxial cable and a microwave antenna. The microwave antenna includes a needle clamp, a needle, and a spiral spring coaxial transmitter. The needle is a component of the co-radiation antenna. The microwave energy is transmitted to the needle via the coaxial cable by the oscillator, and then radiated to the human body acupoints).

(27) To understand the microwave Di needle, we need to know first that the Di needle is one of the nine ancient needles, and has a large body and a round tip. It is a kind of round and slightly pointed acupoint work piece with a thick needle body and a millet-like tip. It is used to press the acupoints for guiding the qi and blood without piercing into the skin. In “Yellow Emperor's Neijing Lingshu, Nine Needles Twelve Originals Chapter,” it is disclosed that “the third Di needle has three and a half body inches . . . , the tip sharpness is as sharp as a millet, and is used to press the pulse without piercing into the skin, so as to cause Qi.” In “Yellow Emperor's Neijing Lingshu, Nine Needles Theory Chapter,” it is disclosed that “the Di needle, which is imitated from the millet's sharpness, is three and a half body inches long and mainly used for pressing the pulse to get the qi to drain the evil qi.” The microwave Di needle is produced through combining the modern microwave physiotherapy, and was successfully trial-produced in Mainland China in 1979. The microwave needles have functions and effects of traditional Di needle, finger needle and moxibustion through merging the performance and characteristics of modern low-frequency and high-frequency electrotherapy.

(28) The principles for acupoint selection and combination compatibility in microwave therapy are the same as those for other acupoint therapies, and can be either based on three options of local, adjacent, and remote selection methods, and/or the tenderness point or the focus of the disease. Of course, it is also possible to select acupuncture points in consideration of the characteristics of the instrument, such as its number of output heads or the stretching range.

(29) When irradiating acupoints on the limbs, the patient usually takes the lying or sitting position, while the recommended distance between the radiator and the acupoint skin is 10-15 cm (or 5 cm at the ear). As for the time and power thereof, they depend on the specific condition (e.g. for ears 8-10 watts, neck 20-40 watts, chest and abdomen 60-100 watts, waist and back 80-120 watts, for 5-10

minutes). Regarding the acupoints around the knee and shoulder joints, saddle-shaped radiators are often used; for the acupuncture points on the chest, abdomen, back and waist, the patient should choose the supine or prone position, for being served by the round or elongate radiator; as for the neck acupoints and ear points, patients often use the sitting position, for being served by the circular or convergent radiators.

(30) From the above discussions, we can find that all existing technologies encounter the following problems. Taking the microwave radiator as an example, whether using a universal bracket to fix the microwave radiator at the “ideal” position, or manually pressing the Di needle microwave radiator on the acupuncture point to be treated, the relative positions (including distance and orientation) between the working point of the instrument and the acupuncture point have not been or cannot be accurately determined. Although the acupuncture points in Chinese medicine are not a point with almost no area in the geometric imagination, but a small area, it is obvious that if we want to maintain the correct or better relative positions between the working point of the instrument and the acupuncture point for a period of time with either universal joints or artificial efforts, it is significantly difficult, at least because (1) the adjustment range of the working point of the instrument has its limit, and (2) the patient will inevitably adjust her/his posture unconsciously.

(31) The problem in the preceding paragraph will bring about another problem, that is, because the theoretical relative position cannot be obtained or ensured, it is impossible for the instrument to be scientifically qualitative (effect) and quantitative (for receiving the instrument service time and intensity). Therefore, taking the microwave therapeutic apparatus as an example, we need be very careful to prevent high temperature and overheating. Although it is theoretically known that the relative position should be adjusted so that the patient has a comfortable warm feeling and soreness, but not a tingling sensation, each person has nevertheless different feelings or tolerance levels, so that there are qualitative or quantitative difficulties. For patients with low pain tolerance, the dosage may not be enough to obtain curative effect; on the contrary, for patients with high pain tolerance, the dosage may actually be excessive to cause temporary or permanent hurt.

(32) The problem mentioned in the preceding paragraph makes it easy for us to understand another problem: when the acupoints are located near the face, brain, eyes, ovaries or testicles, in order to avoid excessive radiation or damage, the existing technology has to recommend a distance of 5 cm and a power of not more than 15 watts, for a time less than 10 minutes. It is thus known that if we can get the theoretical relative position, we can not only get great flexibility in designing the instrument or using the design, but also ensure the obtainment of the effects.

(33) The problem mentioned in the preceding paragraph makes us understand the importance of being “qualitative” or “quantitative”. In detail, the guarantee of the relative position in theory allows us to accurately study the nature and extent of the effects of the instrumental acupoint work piece. For example, when patients have severe local organic or ischemic vascular diseases, excessive radiation not only does not improve their blood circulation, but also often aggravates local hypoxia due to temperature rise, so both doctors and patients have psychological barriers in using the instrument. However, if the theoretical guarantee of relative positions, after successful qualitative and quantitative researches, even for patients with active tuberculosis, high fever, bleeding-prone diseases, advanced hypertension, heart failure, fractures and the inability to clearly express the microwave needle sensation of the group of patients and children, they will no longer belong to the group that is not suitable for acupoint microwave therapy.

(34) After solving the problems mentioned in the preceding paragraph, we will be inspired to understand: because of the qualitative and quantitative success, we can design an effect-focused instrument acupoint work piece (because the efficiency or effect is sufficient, there is no need for too large or wide working area) without harming innocent adjacent people or staff. This is because long-term microwave radiation is harmful to the human body since the microwave therapy device leaks a small amount of microwaves and radiates to the surrounding space, which may cause injuries to the innocent staff.

(35) After solving the problems mentioned in the preceding paragraph, we can't help but jump for joy because the following various effects will be not only be guaranteed, but easier to be achieved through the establishment of relevant theoretical relative positions. Specifically, high intensity, high dose (3 W/cm²) ultrasound (acoustic) waves have inhibitory or destructive effects on various tissues and organs, causing irreversible changes in tissue morphology; but (A) low-intensity, medium and small dose (therapeutic dose) ultrasound effects on peripheral nerves and spinal cord are first excited and then inhibited, so it has analgesic effect on neuralgia; (B) a small dose can congest heart capillaries and increase interstitial cells, so it can improve blood circulation; (C) although the sensitivity of each part of the kidney to ultrasonic waves is different (where the cortex close to curve tubules are the most sensitive, while the medullary collecting duct and the urinary tube connective tissue basement membrane are the least sensitive), the therapeutic dose of ultrasound acting on the kidney area has functions of expanding blood vessels and promoting renal blood circulation; (D) high-dose ultrasound on the ovaries or testicles has inhibitory or even damaging effects, so some people have tried it to be used for birth control in recent years; (E) therapeutic dose ultrasound can improve skin nutrition, promote dermal regeneration, strengthen epithelial formation, and cause increased sweat gland secretion; (F) multiple applications of small dose ultrasound waves can stimulate the growth of bone callus (while it should be noted that a slightly larger dose of 10 minutes will slow down the bone healing).

(36) The effects mentioned in the preceding paragraph were obtained through the establishment of the relative position in theory. We may wonder whether these effects also exist when applied in other therapies. According to physical experiments and clinical practices, the magnetic line bundle of the magnetic needle (non-intrusive) can penetrate the human body skin to a depth of 6-9 cm, which is approximately equivalent to the depth of a traditional acupuncture needle. It is speculated that when a certain acupoint in the human body receives stimulation, it will cause the local cell receptors to produce bioelectricity, and at the same time there will be “qi” in the meridian points, which is to be conducted along the meridian system. The sensed conduction route is consistent with the route predicted by the acupuncture theory. Medical practices have also verified that even though the effects of magnetic fields or magnetic lines of force and needle (intrusive) acupuncture may not be equivalent, their effectiveness is quite consistent. For example, using warm water to soak one's feet and then massage and magnetically absorb the Yongquan acupoint is very effective in treating BPH (prostatic hyperplasia) nocturia and frequent urination. Here is a brief description of acupoint magnetotherapy (using a magnetic device with north and south poles to a certain acupoint in the human body) to examine its applicability as follows.

(37) In “Historical Records-Biography of Bian Que Cang,” it describes the use of magnets to treat diseases in 180 BC. In the second century BC, the Chinese pharmacology monograph “Shen Nong's Materia Medica” officially listed magnets as medicines: “Magnet tastes hot, has a cold nature and mainly cures body paralysis, rheumatism, pain in the limbs unable to hold things . . . and deafness”. In the Collection of Famous Doctors by Tao Hongjing in the Southern and Northern Dynasties, the effects of magnets are recorded: “they foster kidney qi, strengthen bone qi, nourish essence, eliminate trouble, lubricate joints, eliminate carbuncle, fistula, cervical nucleus, sore throat, epilepsy in children”. Yang Shangshan's “Yellow Emperor's Neijing Taisu” in Sui Dynasty, when interpreting the phrase “walking with heavy footsteps” in the “Lingshu, Meridian” Chapter, collaterally mentioned the external effect of the magnet: “What heavy footsteps mean that you put the magnets in your shoes fastened by straps to feel heavy upon walking. After you feel it becomes light, you can gradually increase the weight in order to enhance the fire qi. If you recover from the disease, you should gradually remove the magnets. This is the ancient method of treating the kidney.” “Precious Prescriptions for Emergency Medicine” in Tang Dynasty has a prescription for treating a bleeding wound: “Applying the magnet powder to the wound for relieving pain and stopping bleeding.” It is described in Li Shizhen's masterpiece of pharmacology “Compendium of Materia Medica” in Ming Dynasty: “A true magnet of a bean size, calcined with pangolin, is

ground to be collected in a line shape which is then wrapped in the new cotton to be inserted into the ear. Then, a piece of pig iron is kept in the mouth, and the deafness is cured after the ear feels wind and rain.” Inspired by the “Compendium of Materia Medica” magnet therapy for deafness, acupoint magnetic therapy emerged in mainland China in the early 1960s. Some acupuncture scholars in Shanghai tried to combine acupuncture with a magnetic field and use magnetic needles (magnetized needles) to effectively treat tinnitus; in 1965, medical workers in Hunan also combined the magnetic field theory and the meridian theory to achieve clinical treatment results; major breakthroughs in the application of magnetic therapy in the 1970s were caused by easy accessibility of permanent magnet materials (mainly rare earth cobalt alloys, permanent magnet ferrites, and aluminum nickel cobalt magnets) so that the acupoint magnetic therapy becomes popular. For example, in 1970, it was successfully trial-produced magnetic beads for acupoint application to treat diseases in Baotou City, Inner Mongolia; since 1973, rare earth alloy magnetic sheets were first used for magnetic therapy of various diseases in Hunan Province; in 1974, Beijing Acupuncture workers cooperated with some researchers to turn a static magnetic field into a dynamic magnetic field to make a rotating magnetic therapy machine, which expanded the treatment range to a certain extent and improved the curative effect on certain diseases; in 1978, the first mainland China conference of magnetic therapy scientific research collaboration was held in Xuzhou City, Jiangsu Province.

(38) Since 1980, acupoint magnetotherapy has made unprecedented progress. While the magnetostatic method of fixing magnetic beads or sheet on a certain acupuncture point or part has little to do with the present invention, all of the moving magnetism method of using a gyromagnetic machine to stimulate the acupuncture points, the combination of magnetism and traditional acupoint workpieces to form the magnetic Di needle, the magnetic round plum needle, the photomagnetic method of combining magnetism with helium-neon laser irradiation, and the magnetoelectric method combining with the electroacupuncture therapy, all of which have been applied to nearly 70 diseases in various departments including internal, external, women, children, ophthalmology, otolaryngology and oral cavity, all of them have the aforementioned qualitative and quantitative problems. Therefore, if we want to standardize or normalize magnetic appliances, there comes the dilemma that the discussed foregoing variables are unpredictable and impossible to cope with. The root of accurate qualitiveness and quantitiveness lies in the precise positioning of the acupuncture points. When the precise acupuncture points are secured, for example, the pulse current applied to the magnetic sheet of the acupoint electrode, or the intensity of the magnetic field of the magnetic head of the electromagnetic thermal needle placed on the intradermal needle (or ordinary needle), or the intensity of the magnetic field applied to the magnetic needle, upon qi-obtainment after the needle is pierced, can all be precisely regulated. So far, the most important core spirit of the present invention has emerged, that is, to assist, check or confirm the patient's accurate acupoints with scientific methods or equipment during the doctor's diagnosis and treatment.

(39) Through the foregoing discussions, we can summarize as follows: In the intrusive case, a wrong or deviant acupuncture of no medical effect may just make people feel disgusting. If side effects or other injuries occur, it is indeed unfortunate; in the non-intrusive case, a biased or wrong acupoint selection will cause qualitative, e.g. effective or not, or what kind of effect, and quantitative, e.g. how much irradiation or magnetic field strength is to be applied, difficulties, as mentioned above.

(40) Most of the above are based on researches from Taiwan and the Mainland China, and here is a brief description of how foreigners view the acupuncture. In 1950, a German, Dr. REINHOLD VOLL discovered that there are different potential differences in the human body. After experimental studies, it was found that the “change” circuit diagram of the human body's “electricity” is exactly the same as the “Meridian Diagram” in “Ancient China.” In 1949, after Dr. Yoshio Nakatani, a professor at Kyoto University in Japan, began to study the relationship between

skin resistance and disease symptoms, he found that it was consistent with traditional Chinese meridians, and developed a set of “scientific” disease detection methods, referred to as “good conduction meridian”. Recently, the “Federal Committee of German Doctors and Health Insurance” launched large-scale and high-standard human trials on headache, back pain and arthritis pain, and successively published that acupuncture does have an analgesic effect. However, because the sham control group with acupuncture at non-acupoint sites or insufficient needle penetration has similar analgesic effects to the real treatment group, it is suspected that the acupuncture itself may have a strong placebo effect and has nothing to do with acupuncture points. A few years ago, Dr. Edzard Ernst and graduate students in the United Kingdom designed a retractable needle. When inserted, the needle tip retracts into the needle tube and does not enter the skin, but it can make the subject think that there is a needle inserted (while the needle tube keep staying on the skin). That is, by using real and fake needles to conduct grouped randomized trials, the team of physicians found that fake acupuncture is as effective as real acupuncture in treating headaches and nausea and in preventing migraine. There is no anatomical basis for qi veins or acupuncture points, but American studies have found that acupuncture points are usually located at where the “connective tissue” is most dense. In 2002, Dr. Langevin from the University of Vermont in the United States published a study on *The Anatomical Record*, which showed that acupuncture and moxibustion on acupoints can have medical effects on the body. Western studies have shown that acupuncture and moxibustion can indeed relieve pain. The theory proposed is that the acupuncture stimulates the body to release endorphins. It also seems to increase the brain secretion of the chemical component serotonin (which can enhance the function of vasoconstriction), which changes the function of nerve cells, by which people feel “happiness and comfort”. If it is non-intrusive, stimulating acupuncture points with different frequencies or energy levels will relax nerves and muscles and make them beat, which is like passive exercise, and can improve local blood circulation.

(41) After the aforementioned close comparisons and discussions with conventional technologies, the goals or endeavors of the present invention should have been specifically presented. In fact, however, the above disclosure is only the basic level of what the present invention is attempted to arrive at, that is, the present invention actually has a higher level of goal pursuit. In the Huangdi (Yellow Emperor) *Neijing Suwen*, *Ci-Yao Chapter*, it is recorded “The Huangdi asks: I would like to know the gist of acupuncture. Qi Bo replied: There are grave and light diseases, while the acupuncture depth has shallow and deep. Each case has its own curing rationale, from which deviation should be avoided. An excessive depth will cause an internal hurt while an insufficiency will produce a superficial qi block which in turn invokes evil qi. An improper depth will cause a big trouble internally hurting the 5 organs to develop a serious disease.” Specifically, acupuncture or a specific case must be dealt with a specific depth in order not to incur the big trouble. As we cannot have an insufficient depth or improper depth in order not to invoke a big trouble or a serious disease, we need to detect or ensure the relative position between the needle and the acupoint for an intrusive needle. Likewise, for a non-intrusive therapy, if we can really detect or ensure the relative position of the acupuncture workpiece and the acupoint, we can confidently determine for a specific disease or physical therapy, what degree of the irradiation or electric field or intensity of the magnetic field should be accurately applied, thus ensuring the desired therapeutic effects without suffering from negative effects.

(42) In the Huangdi *Neijing Suwen*, *Zhiyao Chapter*, it is recorded that through the impermanence of birth, aging, sickness and death, each person suffers from a specific disease under a special cause. “Therefore, there are diseases in the epidermis, in the derma, in the adipose tissue, in the muscle, in the vein, in the sinew, in the bone, and in the marrow.” How a misdiagnosis or wrong treatment will result in has been briefly seen in the preceding paragraph. In Huangdi *Neijing Suwen*, *Zhiyao Chapter*, it takes the disease in the derma or adipose tissue as an example. If one can't grasp the essentials in depth, one should be cautious that “when we are to acupuncture the

derma or adipose tissue, there should be no subcutaneous layer piercing, because such piercing will indirectly damage the lungs, which in turn will incur warm malaria in autumn to be shuddering.”

(43) So far, the basic level of the present invention is to ensure the precise positioning between a patient or user's acupuncture point and the instrument, acupoint workpiece (non-intrusive) or an acupuncture device (intrusive) to guarantee that the acupuncture needle or workpiece has a correct or safe physical therapy or treatment. This goal, in a sense, is focused on the two-dimensional level, that is, how to solve or accurately position a patient or a user's acupoint with respect to the instrument, acupoint workpiece (non-intrusive) or a needle device (intrusive). As mentioned in the preceding paragraph, after ensuring the relative positional relationship, the pursuit of physical therapy or true needs of dealing with a specific disease can then be satisfactorily met through properly adjusting the parameters or variables involved in the third dimension (i.e. depth) and fourth dimension (i.e. angle). The present invention is not satiated through realizing the above two levels (basically belonging to the hardware). The Yellow Emperor Neijing Suwen, Yijing Qi-Change Chapter stated that in ancient times, the treatment of diseases was dealt with at the initial burgeoning of a disease, so the disease is difficult to adversely develop.

(44) According to the Yellow Emperor Neijing Suwen, as the time goes by, “in the medieval ancient time, the disease was cured only when it has been developed, by being served with a medicinal soup for ten days to eliminate any one of the eight-wind and five-paralysis diseases. If not cured in ten days, herbal roots and the grass are used, by which the root and the symptom of the disease are both attended to get rid of the evil qi.” As the human beings are born to chase fame and wealth in the economic world, they need to neglect or could not discern omens of disease until the disease has taken shape before they begin to think about treatment. At this time, it is necessary to rely on diet therapy or herbal medicine to eliminate the evil qi or drive away the disease. As for the human beings in the near ancient time, “the same is not true for the treatment of diseases. The treatment is not based on four seasons, ignores the sun and the moon, does not judge whether to combat or to follow the development, and is practiced after the disease is already established, by using the acupuncture from the outside and serving the medicinal soup into the body. An inferior artisan is aggressive enough to embark measures to attack the disease. It is not seldom to find out that while the disease is still there, a new disease emerges.” In modern treatments, the same disease (for example, a cold) has almost the same medicine. It does not care about personal physique, and may not believe in the relationship between the disease condition and the four seasons or yin and yang. There is no idea to predict when or what disease should be treated with the development trend or against the development trend. Accordingly, it is not seldom experienced that although the symptoms have been eliminated, because the “root” of the disease has not been cured, the bud of a new disease latent in the body is waiting for an opportunity to burgeon and then prosper.

(45) It is a further level of ideal of the present invention to focus on the level of “software”, which can adapt or adjust the body immediately when there is an initial omen of a disease so that the ideal in the Yellow Emperor Neijing Suwen, Yijing Qi-Change Chapter “keeping near to the health but away from death, along the prolonged path of life” can be realized.

(46) The ultimate level of the ideal of the present invention is to seek the health and happiness of all mankind, and to realize the ideal that may be moving in the preceding paragraph, so that every family or every person can have the software and hardware of the present invention even if their financial resources are relatively limited. When the present invention starts to be commercialized and becomes more advanced, every one may enjoy or receive physiotherapy or medical services like those provided by the reincarnation of Hua Tuo and Bian Que.

(47) Other features and advantages of the present application are described later, and can be apparent in the specification, or can be understood by practicing the present application. The purpose and other advantages of the present application can be realized and obtained by the structure specifically pointed out in the specification and the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The following drawings are drawn according to embodiments and are merely illustrative of the concepts of the present invention.

(2) FIG. 1 is a health care device for positioning fingers or toes.

(3) FIG. 2 is a health care device fixed on two different parts of the body part.

(4) FIG. 3A is a schematic diagram of the meridians and acupoints on the back.

(5) FIG. 3B is a simple health care device positioned with respect to the chest or back.

(6) FIG. 3C is an advanced health care device positioned with respect to the chest or back.

(7) FIG. 4A is the health care body of the health care device for the lower arm;

(8) FIG. 4B shows the health care body of the health care device for the upper arm;

(9) FIG. 4C is an embodiment of the length adjustment device of the health care body of the health care device;

(10) FIG. 4D is the first embodiment of the length adjustment plate of the length adjustment device of the health body of the health care device;

(11) FIG. 4E is a second embodiment of the length adjustment plate of the length adjustment device of the health body of the health care device;

(12) FIG. 5 is a health care device for lower limbs;

(13) FIG. 5A is a length adjustment plate of the lower limb health care body;

(14) FIG. 6 is a health care device for the head;

(15) FIG. 7 is a head health care device that can be accurately positioned;

(16) FIG. 7A is the second embodiment of the connecting piece of the acupoint work piece;

(17) FIG. 8 is the first embodiment of the work piece assembly;

(18) FIG. 8A is a schematic diagram of the third embodiment of the connecting piece of the acupoint work piece;

(19) FIG. 8B is an embodiment of the acupoint work piece;

(20) FIG. 8C is the second embodiment of the work piece assembly;

(21) FIG. 8D is another embodiment of the work piece holder;

(22) FIG. 9 is an embodiment of a workpiece assembly with a robotic arm;

(23) FIG. 9A is an embodiment of an automatic acupoint workpiece;

(24) FIG. 10 is a first embodiment of the health care methods of the present invention;

(25) FIG. 10A is a second embodiment of the health care methods of the present invention; and

(26) FIG. 10B is an embodiment of the health care system of the present invention.

(27) The reference numbers are: **1**: index finger **2**: first **11**: Erjian acupoint **12**: finger joint **13**: proximal end of middle phalanx of index finger **14**: distal end of proximal phalanx of index finger **21**: thumb **22**: index finger **24**: thumb joint **23**: Hegu acupoint **25**: second joint of index finger **26**: short thumb muscle **30**: Governor Vessel **31**: Foot-Taiyang Meridian **32**: Dazhui acupoint **33**: Taodao acupoint **34**: Shenzhu acupoint **35**: Ganshu acupoint **36**: Danshu acupoint **37**: Pishu acupoint **38**: Weicang acupoint **39**: Huangmen acupoint **40**: Zhishi acupoint **100**: health care device **101**: pivot part **102**: fixing body **103**: semicylindrical rod body **104**: recess **105**: soft layer of cloth **106**: semicylindrical male thread **110**, **110'**: health care body **112**: hollow cylindrical end part **120**: health care device **122**: health care body **124**: upper end shoulder **126**: abutting plate **128**: spring **130**: groove **131**: index finger plate **132**: index finger accommodating area **133**: shoulder **134**: spring **135**: index finger accommodating groove **136**: abutting plate **138**: index finger slot **140**: middle finger slot **142**: ring finger slot **144**: little finger slot **146**: recess **150**: health care device **152**: health care body **154**: pressing piece **156**: transverse piece **157**: upper end **158**: work piece support medium **160**: sleeve **162**: work piece connector **164**: end **166**: stanchion **168**: intermediate connecting piece **170**: health care device **172**: health care body **174**: first pair of stanchions **175**:

upper end 176: intermediate connecting piece 178: matching part 182: hole 184: second pair of stanchions 185: intermediate connecting piece 186: matching part 187: pivot 180, 188: thickness-halved area 189: clamp 190: protrusion 191: pin 192: clamp 193, 195: surface 194: flange 197: groove 196, 198: through hole 199: pin 200, 200': fixing piece 201: rod body 202: first end 203: female thread 204, 204': second end 205: universal ball joint seat 206: acupoint work piece connector 209: universal ball joint 300, 300': acupoint work piece 301: conducting wire 302, 302': acupoint work head 400: support transverse piece 401, 403: surface 402: connecting end 404: work piece support medium 405, 407: surface 406: adjustment sleeve 408: work piece connector 410: end 412: free end 500: health care device 501, 503: carrying base plate 502: health care body 505, 505': carpal protrusion of radius accommodating recess 506, 506': carpal protrusion of ulna accommodating recess 508: palm accommodating groove 510: cavity of positioning block 511, 512: paired recesses 504, 524: paired positioning blocks 513, 515: two ends of spring 514: plural springs 516: pair of lower lugs 517: inner wall of recess 518: pair of side grooves 519: inner wall of positioning block 520: recess of end of carrying base plate 526: recess 528: groove 530: lug 532: groove 534: recess 535: distal side of elbow end 536: groove 538: inner recess of adjacent ends of carrying base plates 540: tension spring 542: pin hole 544: pin 546: length adjustment medium 547: linking plate 548: pin hole 550: central groove of adjacent ends of carrying base plates 552: bottom cutout 554: bottom shaft hole 560: upper arm carrying base plate 562, 564: two carrier plates 566: axillary end 568: upper cutout 570: cutout 572: central pivot 574: length adjustment device 578: guiding sheet 580: cutout 582, 584: carrying base plate 586: length adjustment device of health care body 587: screw hole 588: rotatable screw rod 590: handle 591: longitudinal central groove 592: chain 594: positioning pin 595: sliding hole 596: length adjustment plate 597: distal groove 598: positioning pinhole 599: groove 600: trapezoidal piece 601: middle groove 602: side piece 603: two side bevels 604: spring 606: arc convex 608: groove 610: proximal groove 612: spring 614: guiding piece 616: sliding hole 618: guiding groove 620: trapezoidal piece and screw rod assembly 622: screw rod end 624: bottom hole 628: trapezoidal piece and screw rod assembly 630: trapezoidal piece 631: side bevel 632: shallow guiding groove 634: chuck 636: hole 638: screw rod 640: screw rod end 660: health care body 662: shank carrying base plate 664: thigh carrying base plate 666: (tibia) heel end of shank carrying base plate 668: side groove 670: recess 672, 674, 676: recess 678: slot 680: positioning block 681: opposite surface 682: lug 684: large lateral malleolus recess 686: middle lateral malleolus recess 685, 687, 689: malleolus recess 688: small lateral malleolus recess 690: length adjustment device 692: thread 694: operating rod 696: handle 698: chain 700: pin 702: carrying base plate of length adjustment device 704: screw hole 706: space between the thigh and shank carrying base plates 710: rod 712: rod hole 708: spring 714: positioning block 716: lug 718: recess 719: accommodating recess of knee tuberosity of the femur 720: central recess 722: through hole 724: pinhole 726: positioning block 728: positioning hole 730: (femur) buttock end of thigh carrying base plate 732: accommodating hole 734: spring 736: recess 738: stop 740: central concave 742: length adjustment trapezoidal piece 744, 746: two side bevels of trapezoidal piece 748: heel height adjustment medium X and Y: distances between two side bevels and the center of operating rod 760: head health care body 762: base plate 764: slot 766: head positioning plate 768, 770: connecting rod 772: oil cylinder 774, 776: first end and second end of oil cylinder 778: ear hole 780: inverted triangular hole 782: lower protruding slider 784: pressure sensor 786, 788: oil cylinder forward and backward buttons 790: circuit configuration 800: head health care device 802: health care body 804: rail body 806: gear slot 808: lower gear rack 810: upper surface 812: upper gear rack 814, 816: carrier body 818: paired positioning plate 820: positioning gear 822: stepping motor 824: gear protection sheet 826: motor shaft 828: gear 830: left end surface of carrier body 832: positioning rod 834: paired positioning slot 836: side positioning plate 838: stepping motor 840: screw rod 842: screw rod nest 844: two side wall upper surfaces 846: moving piece 848: work base 850: fixing screw bolt 852: middle protruding piece 854: groove 856: ball 858, 860: upper surface of carrier body 862, 864: proximal

surface of carrier body **870**: acupoint work piece connecting piece **874**: first end **876**: fixing nut **878**: internal thread **880**: second end **882**: acupoint work piece nut **884**: internal thread **900**: work base **902**: longitudinal through hole **904**: C-clamp **906**: work piece holder **908**: first end of work piece holder **910**: second end of work piece holder **912**: connector **914**: internal thread **916**: annular groove **918**: first end of work piece **920**: connecting piece **922**: second end of work piece **930**: work piece holder **932**: threaded section **934**: annular groove **936**: work base **938**: threaded hole **940**: acupoint work piece **942**: slender pneumatic cylinder **944**: threaded end **946**: piston rod of pneumatic cylinder **948**: upper connecting ring **950**: main connecting piece **952**: ring piece **954**: crankshaft **956**: work ring **958**: rubber pad **960**: work end **962**: work bottom **964**: work piece **966**: point opening **968**: first end of main connecting piece **970**: second end of main connecting piece **971**: work base **972**: angle controller **974**: angle control assembly **976**: work piece supporter **978**: fixing piece **980**: threaded barrel **982**: work piece supporter **984**: acupoint workpiece jaw **986**: screw **988**: holding part **1000**: work piece assembly matched with robotic arm **1002**: electric chuck **1004**: jaw **1006**: holding surface **1008**: rotating head **1010**: extension base **1012**: first end **1014**: connecting base **1016**: rotating shaft **1018**: rotating platform **1020**: work platform **1022**: work base **1024**: first end **1026**: second end **1028**: second end **1030**: first end **1032**: second end **1040**: automatic needle inserting acupoint work piece **1042**: rotating head **1044**: automatic needle inserting device **1046**: needle inserting mechanism **1048**: electric holder **1100**, **1110**, **1120**: steps of first embodiment of health care method **1130-1180**: steps of second embodiment of health care method **1200**: health care system **1210**: health care body **1215**: micro computer **1220**: central processing unit **1230**: memory **1240**: symptom treatment module **1250**: personal health care history record module **1260**: feedback/report module **1270**: screen **1280**: keyboard and/or mouse **1290**: microphone **1300**: lens **1400**: cloud database **1500**: service center **1600**: control module

DETAILED DESCRIPTION

(28) What follow will cooperate with the drawings to disclose how to realize the ideal of each level/each observation/each aspect of the present invention one by one. The following specific embodiments are specific examples used to assist in understanding a certain invention level/observation/solution, and are not the only feasible way or answer of the invention level/observation/solution. In fact, the descriptions of the specific embodiments of different invention levels/observation/solutions can be mutually referred to for replacement or modification. The present inventions should be groundbreaking, but the so-called groundbreaking inventions are only clever, organic or amazing new combinations of various components that are easily available in the world to realize the groundbreaking ideals. Specifically, the creation or advancement of the present invention generally does not lie in each component itself, but in the unexpected or creative combination of related components.

(29) Please refer to FIG. 1 showing the first embodiment of the present invention in the basic level, where the Erjian acupoint **11** (International Code LI2) on the index finger **1** is taken as an example. Acupoint **11** is located between the red and white fleshes at the end of the radial transverse crease of proximal phalanx bone (the third segment) of the index finger, and mainly treats sore throat, toothache, epistaxis, crooked mouth and eye, lethargy, and shoulder/back pain. The health care device **100** includes a health care body **110** having two pieces of hollow semicylindrical fixing bodies **102** pivotally interconnected through the pivot part **101**, each of which has a solid semicylindrical rod body **103** having a semicylindrical male thread **106**. Each fixing body **102** has a recess **104** accommodating a finger joint **12**, for example, the middle (second) and proximal (third) phalangeal joint. A cleanable or disinfectable soft layer of cloth or disposable paper **105** can be folded multiple times according to the user's fatness or finger thickness, so that when two fixing bodies **102** are tightly closed, index finger **1** or joint **12** determines or fixes the positional relationship between health care device **100** and index finger **1** or Erjian acupoint **11** (in this example) to obtain the previously described or expected effects. When two fixing bodies **102** are tightly closed, two semicylindrical rod bodies **103** constitute a complete bolt; and the protruding

parts of the proximal end **13** of the middle phalanx and the distal end of the proximal phalanx **14** of index finger **1** are accommodated in recess **104**.

(30) A fixing piece **200** has a rod body **201** for providing a distance or height required for configuring or operating an acupoint work piece **300**, where rod body **201** has a first end **202**. After a female thread **203** in first end **202** engages with male thread **106** on two semicylindrical rod bodies **103**, rod body **201** is fixed on health care device **100**, while two semicylindrical fixing bodies **102** fix index finger **1** therein by locking first end **202** with two semicylindrical rod bodies **103**. Rod body **201** has a second end **204** configuring a universal joint seat **205** thereon for connecting with a universal ball joint **209** on an acupoint work piece connector **206**. Due to technological advancement, the rotational angle of the modern universal joint is extremely large, and it can withstand a considerable impact at a specific angle and/or position without being out of position. Moreover, if one universal joint is not enough, multiple universal joints can be serially connected to enhance the extent of the desired orientation.

(31) Acupoint work piece connector **206** has two lips **207** for passing and holding acupoint work piece **300** in a hollow space **208** thereof. Acupoint work piece **300** can be an energy work unit of microwave, laser or radiation as aforementioned, and has a conducting wire **301** for receiving electrical energy supply, so as to output energy from an acupoint work head **302**. Due to the configuration of connector **206** and fixing piece **200**, a work energy releasing unit can thus be in the form of acupoint work piece **300**, at which the work energy output is concentrated. Because a relative position of between acupoint work piece **300** and acupoint **11** has thus been determined, how or to what extent an acupoint work head **302** of acupoint work piece **300** can or should output the energy can also be precisely controlled or adjusted according to the specific requirement of the user/patient.

(32) Additionally, the bulks of health care device **100**, fixing piece **200** and acupoint work piece **300** are relatively limited. As long as conducting wire **301** is long enough, the user can either ideally move his position, or act at will without changing the relative position between acupoint work piece **300** and Erjian acupoint **11**, thereby not affecting the expected physiotherapy/treatment effect. Furthermore, there are various ways for connection between acupoint work piece connector **206** and acupoint work piece **300**, or between first end **202** and semicylindrical rod body **103**. For example, one is provided with an annular protrusion and the other matching piece is provided with an annular groove, so as to make the assembly between first end **202** and semicylindrical rod body **103** easier. Therefore, we can easily understand that the description for this figure or the embodiment is only an example for realizing the objects disclosed in the present invention.

(33) The first embodiment of the present invention is summarized as follows: health care device **100** includes health care body **110** for positioning body part **1** of a user, so as to maintain a first specific positional relationship with body part **1**, wherein body part **1** has acupoint **11**; acupoint work piece **300** for performing a health care work on acupoint **11**; and work piece holder **200** having first end **202** connected to health care body **110** and second end **204** for fixing acupoint work piece **300**, so that under the first specific positional relationship, acupoint work piece **300** performs the health care work under the condition that acupoint work piece **300** has a second specific positional relationship with acupoint **11**.

(34) In accordance with health care device **100** of the first embodiment, acupoint work piece **300** has acupoint work head **302**, and the second specific positional relationship refers to a positional relationship between acupoint **11** and acupoint work head **302**.

(35) In accordance with health care device **100** of the first embodiment, health care body **110** is to relatively position a finger, toe, arm or leg of the user.

(36) In accordance with health care device **100** of the first embodiment, health care body **110** is formed by two mutually pivoted fixing bodies **102** of a hollow semicylindrical crosssection, each of which has a semicylindrical rod body **103**, and two semicylindrical rod bodies **103** are combinable into a connecting rod.

(37) In accordance with health care device **100** of the first embodiment, each semicylindrical fixing body **102** has inner recess **104** to accommodate the body part or the joint of finger **1**, so that health care body **110** can properly fit or relatively position body part **1**.

(38) In accordance with health care device **100** of the first embodiment, the fixing piece **200** has a first end **202** being hollow for accommodating the connecting rod piece formed by the two semicircular section rod bodies **103**, and thus, the two hollow semicircular section fixing bodies **102** closely fit the body part **1** therein.

(39) In accordance with health care device **100** of the first embodiment, fixing piece **200** has second end **204** fixed to acupoint work piece connector **206** connecting acupoint work piece **300**, through a fixing medium which can be one or more serially connected universal joints.

(40) In accordance with health care device **100** of the first embodiment, the connection method between first end **202** of fixing piece **200** and two semicylindrical rod bodies **103** for forming the connecting rod piece, or between acupoint work piece connector **206** and acupoint work piece **300** can be male and female threads, an elastic holding, or an engagement of annular convex and annular concave through the material characteristics.

(41) From another aspect, the aforementioned embodiment discloses health care device **100** including health care body **110** for fixing body part **1** of a user, so as to maintain a first specific positional relationship with body part **1**; and work piece holder **200** having first end **202** connected to health care body **110**, and second end **204** fixing acupoint work piece **300**, and ensuring acupoint work piece **300** to perform the health care work under the condition that acupoint work piece **300** has a second specific positional relationship with acupoint **11** under the first specific positional relationship.

(42) From yet another aspect, the aforementioned embodiment discloses health care device **100** for holding acupoint work piece **300** thereon to engage in a health care work onto a user, wherein the user has a body part having acupoint **11**, and health care device **100** includes health care body **110** for relatively positioning body part **1** so that health care body **110** and body part **1** maintain a first specific positional relationship therebetween, and work piece holder **200** having first end **202** configured on health care body **110** and second end **204** for holding acupoint work piece **300**, and ensuring acupoint work piece **300** to perform the health care work under the condition that acupoint work piece **300** has a second specific positional relationship with acupoint **11** under the first specific positional relationship.

(43) Referring to FIG. 2 showing the second embodiment of the present invention of a basic level, the Hegu acupoint **23** (International Code LI4) located between the thumb **21** and the index finger **22** on the first **2** is taken as an example. Acupoint **23** is located between the first and the second metacarpal bones, but is slightly closed to the midpoint of the second metacarpal bone, and mainly treats headache, eye pain, sore throat, toothache, epistaxis, cold, stroke, and facial paralysis. The same as the first embodiment, this embodiment is focused on acupoints of special situation. When it is possible to overcome the difficulty of positioning a special acupoint with respect to an acupoint work piece (or its acupoint work head), the problems related to acupoints that are more common or easier to obtain the relative positions can be easily solved.

(44) Health care device **120** includes a health care body **122** being generally semi-cylindrical and having a groove **130** for accommodating a user's thumb **21** therein. The user's thumb joint **24** is sleeved with health care body **110** of the first embodiment having a hollow cylindrical end part **112** having two sides rested on two abutting plates **126** configured on two upper end shoulders **124** of health care body **122**. Two abutting plates **126** are pushed toward the thumb tip by two springs **128** respectively. Thereby, the relative position between thumb **21** and health care body **122** is secured.

(45) Health care body **122** has a recess **146** for fitting the short thumb muscle **26** of a user, for the user's feeling of gripping health care body **122**. Another health care body **110'** is sleeved on the second joint **25** of index finger **22**. Health care body **110** and health care body **110'** can be the same (where thumb **21** or index finger **22** is properly fit by cloth soft layer **105** of the first embodiment)

or different (where their outlines or sizes slightly vary with thumb **21** and index finger **22** respectively). After second joint **25** is sleeved in health care body **110'**, index finger **22** sleeved on health care body **110'** rests in the index finger accommodating area **132** through the index finger accommodating groove **135** configured between the index finger wall **131** and the shoulder **133**, while the right and upper sides of the hollow cylindrical end part **112'** of health care body **110'** urge against the abutting plate **136** connected to the connecting spring **134**. Abutting plate **136** here is generally inverted L-shaped, with its horizontal part and vertical part respectively urging against the right and upper sides of hollow cylindrical end part **112'** of health care body **110'** in FIG. 2. Further, the horizontal part of inverted L-shaped abutting plate **136** pivots thereon spring **134**, so that after index finger **22** is positioned properly, the vertical part of inverted L-shaped abutting plate **136** is rotated to urge against the upper side of hollow cylindrical end part **112'**. By this, on the one hand, index finger **22** is constrained to be positioned, and on the other hand, the relative positional relationship between the second end **204'** of the fixing piece **200'** and Hegu acupoint **23** is ensured accordingly. In other words, the relative positional relationship between the acupoint work head **302'** on the acupoint work piece **300'** and Hegu acupoint **23** is thus assured for the previously described or expected effects. Furthermore, health care body **122** is provided with an index finger slot **138** for insertion of index finger **22** placed in groove **132**. Certainly, health care body **122** can be further provided with a middle finger slot **140**, a ring finger slot **142** and a little finger slot **144** for optional insertion of the other three fingers. Each of finger slots **138-144** may or may not communicate with each other, or each has a completely or partially independent space for accommodating fingers individually or collectively.

(46) It should be noted that health care body **110** and health care body **110'** in this embodiment may have basic structural differences from health care body **110** in the first embodiment, because health care body **110** and health care body **110'** in this embodiment need not self-position by thumb joint **24** as that in the first embodiment **110**. In details, health care body **110'** can only extend over the middle part of a phalanx because one end of health care body **110'** will be stopped by the finger joint, so that health care body **110'** will not slip off. Since the other end of health care body **110'** will urge against abutting plate **126** or **136**, there is no trouble with positional assurance. The axial length of health care body **110'** may thus be shortened.

(47) The second embodiment of the present invention is summarized as follows: health care device **120** includes health care body **122** having two accommodating grooves **130**, **135** for relatively positioning two different parts **21**, **22** of a user's body part **2** respectively, so as to maintain a first specific positional relationship with body part **2**; and work piece holder **200** having first end **202** connected to the health care body **110'**, and second end **204** for fixing acupoint work piece **300'**, so that acupoint work piece **300'** and body part **2'** are in a second specific positional relationship under the first specific positional relationship.

(48) In accordance with health care device **120** of the second embodiment, there is acupoint **23** between two different parts **21**, **22**, acupoint work piece **300'** has an acupoint work head **302'**, and the second specific positional relationship refers to the positional relationship between acupoint **23** and the acupoint work head **302'**.

(49) In accordance with health care device **120** of the second embodiment, health care body **122** is used to relatively position the user's two fingers, such as thumb and index finger.

(50) In accordance with health care device **120** of the second embodiment, health care body **122** has two finger accommodating parts, such as thumb accommodating groove **130** and index finger accommodating groove **135**.

(51) In accordance with health care device **120** of the second embodiment, thumb accommodating groove **130** is defined by two shoulders **124**, two springs **128** respectively configured in two shoulders **124**, and two abutting plates **126** respectively connected to springs **128**.

(52) In accordance with health care device **120** of the second embodiment, index finger accommodating area **132** includes index finger stopping plate **131**, shoulder **133**, groove **135**

defined by index finger stopping plate **131** and shoulder **133**, spring **134** configured in shoulder **133**, and inverted L-shaped abutting plate **136** pivotally connected to spring **134**.

(53) In accordance with health care device **120** of the second embodiment, health care body **122** has recess **146** for fitting short thumb muscle **26**, so that the user can have a feeling of gripping health care body **122**.

(54) In accordance with health care device **120** of the second embodiment, health care body **122** has index finger slot **138** for accommodating the distal section of index finger **22**, and can have middle finger slot **140**, ring finger slot **142**, and little finger slot **144** for optional insertion of the other three fingers, wherein finger slots **138-144** may or may not communicate with each other, or each has a completely or partially independent space for accommodating fingers individually or collectively.

(55) From another aspect, health care device **120** holds an acupoint work piece (as described in FIG. **1** or the following embodiments) thereon to engage in a health care onto a user, wherein the user has body part **2** having two different parts **21**, **22**, there is acupoint **23** between the two different parts, and health care device **120** includes: health care body **122** having two abutting parts (**124-130** and **131-135**) for positioning two different parts **21**, **22** of body part **2**, so as to maintain a first specific positional relationship with body part **2**; and a work piece holder (as described in FIG. **1** or the following embodiments) having: a first end configured on the health care body; and a second end holding the acupoint work piece, for ensuring acupoint work piece **300** to perform the health care work when acupoint work piece **300** has a second specific positional relationship with acupoint **11** under the first specific positional relationship.

(56) From yet another aspect, health care device **120** includes health care body **122** having two abutting parts (**124-130** and **131-135**) for relatively positioning two different parts **21**, **22** of body part **2** of a user respectively, for maintaining a first specific positional relationship with body part **2**, wherein there is acupoint **23** between two different parts **21**, **22**; and a work piece holder (as described in FIG. **1** or the following embodiments) has: a first end configured on the health care body; and a second end holding an acupoint work piece (as described in FIG. **1** or the following embodiments) thereon, for ensuring acupoint work piece **300** to perform a health care work under the condition that acupoint work piece **300** has a second specific positional relationship with acupoint **11** under the first specific positional relationship.

(57) Distribution of acupoints in chest or abdomen of a human body is quite symmetrical. For the chest, the midline is the Conception Vessel with two Kidney Meridians of Foot-Shaoyin located 0.5 body inch away from two sides thereof, two Stomach Meridians of Foot-Yangming located another 1 body inch away (i.e. 1.5 body inches from the Conception Vessel), etc. For the back, the midline or spine is the Governor Vessel with two branches of two Bladder Meridians of Foot-Taiyang respectively located 1.5 and 3 body inches away from two sides thereof, etc. FIG. **3A** shows Governor Vessel **30**, Bladder Meridian **31** and acupoints, such as Dazhui acupoint (International Code GV14) **32**, Taodao acupoint (International Code GV13) **33**, Shenzhu acupoint (International Code GV12) **34**, Ganshu acupoint (International Code BL18) **35**, Danshu acupoint (International Code BL19) **36**, Pishu acupoint (International Code BL20) **37**, Weicang acupoint (International Code BL50) **38**, Huangmen acupoint (International Code BL51) **39** and Zhishi acupoint (International Code BL52) **40**.

(58) Please refer to FIG. **3B** showing a simple health care device **150** for chest or back. Health care device **150** has health care body **152**, support transverse piece **156** having two ends **164** connected to health care body **152**, and work piece support medium **158** fixed on support transverse piece **156**. Health care body **152** further has two stanchions **166** whose upper end **157** is pivoted on an end **164** of support transverse piece **156**, intermediate connecting piece **168** fixed on two stanchions **166**, and pressing piece **154** fixed on intermediate connecting piece **168**, wherein angles included between two stanchions **166** and intermediate connecting piece **168**, and between intermediate connecting piece **168** and pressing piece **154** are generally 90 degrees. That is, when

using, the user presses pressing piece **154** with his/her chest or back to ensure health care body **152** to be in a definite relative positional state. Because pressing piece **154** is to be pressed by the user, its shape should not cause uncomfortableness to the user, or its placement surface should have corresponding recess to avoid the user's discomfort.

(59) Work piece support medium **158** slidably sleeves thereon a sleeve **160** fixing thereon a work piece connector **162** for sleeving thereon an acupoint work piece as described in the first embodiment. Therefore, the physiotherapist or therapist can move/adjust the position of sleeve **160** on work piece support medium **158** to fix or secure the relative positional relationship between the acupoint work piece and the specific acupoint.

(60) There are so many acupoints in chest or back while health care device **150** seems too simple, so that we may agree that health care device **170** in FIG. 3C is somewhat advanced. Health care device **170** has health care body **172**, support transverse piece **400** having two ends **410** pivoted on health care body **172** respectively, and work piece support medium **404** slidably sleeved on support transverse piece **400**. Health care body **172** has a first pair of stanchions **174** whose upper end **175** is pivoted to an end of support transverse piece **400**, intermediate connecting piece **176** fixed on two stanchions **174**, matching part **178** fixed on intermediate connecting piece **176**, a second pair of stanchions **184**, intermediate connecting piece **185** fixed on two stanchions **184**, and matching part **186** fixed on intermediate connecting piece **185**, wherein angles included between two stanchions **174** (**184**) and intermediate connecting piece **176** (**185**), and between intermediate connecting pieces **176** (**185**) and matching parts **178** (**186**) are generally 90 degrees, and matching part **178** (**186**) has a thickness-halved area **180** (**188**), matching part **186** is pivoted on intermediate connecting piece **185** through pivot **187**, and thickness-halved areas **180** and **188** respectively have matching holes **182** and protrusions **190**. In use, matching part **186** and two stanchions **184** are first kept in parallel or coplanar, and after the user presses the combined matching parts **178** and **186** with his/her chest or back, two stanchions **184** are pivoted to have the right-angle relationship with matching part **186** for ensuring health care body **172** in a secured relative position. As mentioned above, because matching parts **178** and **186** are to be pressed by the user, their shapes should not cause uncomfortableness to the user, or their placement surface should have corresponding recesses to avoid the user's discomfort.

(61) As in the preceding example, work piece support medium **404** slidably sleeves thereon sleeve **406** fixing thereon work piece connector **408** for sleeving thereon the acupoint work piece in the first embodiment. Therefore, the physiotherapist or therapist can move/adjust the position of sleeve **406** on work piece support medium **404** to fix or secure the relative positional relationship between the acupoint work piece and the specific acupoint. Work piece support medium **404** has connecting end **402** slidably sleeved on support transverse piece **400**, and free end **412** clamped by a pair of clamps **189** and **192** on a second pair of stanchions **184**, wherein clamp **189** is fixed above the pair of stanchions **184**, clamp **192** is pivoted on the upper end of one stanchion **184** by pin **191**, the other stanchion **184** has flange **194**, the free end of clamp **192** has groove **197**, flange **194** and the free end of clamp **192** respectively have through holes **196** and **198**, and pin **199** passes through the through holes **196** and **198** so that the pair of clamps **189** and **192** hold free end **412**.

(62) Although precise fit is no longer a problem in nowadays technology, considering convenience of sliding (so a tolerance must be left) and security of positioning, corresponding surfaces **195** and **193** of clamps **189** and **192**, corresponding surfaces **401** and **403** of support transverse piece **400** and connecting end **402**, and corresponding surfaces **405** and **407** of work piece support medium **404** and adjustment sleeve **406** may be roughened or covered with a layer of thick or thin rubber material. Additionally, because acupoints in chest and abdominal are symmetrically distributed relative to the Conception Vessel or Governor Vessel, both symmetrical acupoints need physiotherapy/treatment, and adjustment sleeve **406** is thus preferably configured in pairs. Certainly, if multiple acupoints are simultaneously required to be treated, work piece support medium **404** can have an increased number.

(63) Preceding two embodiments are summarized as follows: health care device **150 (170)** includes health care body **152 (172)** having two supporting pieces **166 (174)**, each of which has upper end **157 (175)**, so as to maintain a first specific positional relationship with a user's body; support transverse piece **156 (400)** having two ends **164 (410)** pivoted on upper ends **157 (175)** of two supporting pieces respectively; and work piece support medium **404** having first end **402** connected to health care body **152 (172)**, and adjustment sleeve **406** sleeved thereon for fixing an acupoint work piece, so that the acupoint work piece and the body are in a second specific positional relationship under the first specific positional relationship.

(64) In accordance with health care device **150 (170)** of the embodiment, the body is chest or back of a human body, the acupoint work piece has an acupoint work head, and the second specific positional relationship refers to a relative positional relationship between a chest or back acupoint and the acupoint work piece.

(65) In accordance with health care device **150 (170)** of the embodiment, health care body **152 (172)** has pressing piece **154 (178, 186)** for being pressed by a user's chest or abdomen for securing the relative position between the users and health care body **152 (172)**.

(66) In accordance with health care device **150 (170)** of the embodiment, pressing piece **154** has two matching parts **178, 186**, each of which has thickness-halved area **180 (188)**, and thickness-halved areas **180, 188** have matching holes and protrusions respectively.

(67) In accordance with health care device **150 (170)** of the embodiment, health care body **172** has two pairs of stanchions **174, 184**, bottoms of each pair of stanchions **174, 184** are interconnected with intermediate connecting piece **176 (185)**, and matching part **186** is pivoted on intermediate connecting piece **185** by pivot **187**.

(68) In accordance with health care device **170** of the embodiment, work piece support medium **404** is slidably sleeved on support transverse piece **400**; and/or work piece support medium **404** slidably sleeves thereon sleeve **406**.

(69) In accordance with health care device **170** of the embodiment, a second pair of stanchions **184** of health care body **172** has a pair of clamps **189, 192** configured thereon for holding free end **412** of work piece support medium **404**.

(70) In accordance with health care device **170** of the embodiment, corresponding surfaces **195** and **193** of clamps **189** and **192**, corresponding surfaces **401** and **403** of support transverse piece **400** and connecting end **402**, and corresponding surfaces **405** and **407** of work piece support medium **404** and adjustment sleeve **406** are roughened or covered with a layer of rubber material.

(71) In accordance with health care device **170** of the embodiment, second adjustment sleeve **406**, and/or second work piece support medium **404** are/is further included.

(72) From another aspect, health care device **150 (170)** holds an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a health care onto a user, wherein the user has a body part having an acupoint, and the health care device includes: health care body (**152, 166, 154, 168; 172, 174, 178, 184, 190**) having a pair of supporting pieces (**152, 166; 172, 174; 184**), for maintaining a first specific positional relationship with a user's body; support transverse piece **400** having two ends **410** respectively connected to the supporting pieces; and work piece support medium **404** connected to support transverse piece **400** and sleeving thereon sleeve **406** holding the acupoint work piece, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(73) From yet another aspect, health care device **150 (170)** includes health care body (**152, 166, 154, 168; 172, 174, 178, 184, 190**) having a pair of supporting pieces (**152, 166; 172, 174; 184**) for relatively positioning a user's body part to maintain a first specific positional relationship with the body part, wherein the body part has an acupoint; support transverse piece **400** having two ends **410** respectively connected to the pair of supporting pieces; and work piece support medium **404** connected to the support transverse piece and sleeving thereon sleeve **406** holding the acupoint

work piece, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(74) The meridian path in either upper or lower arm is not regular or identifiable relatively easier like that (or acupoints) in chest or abdomen of the human body, runs either in yin or yang side of the arm. Contrasting to the acupuncturists who may identify it easily, it is not easy for the general public or beginners. We only deal with the positioning problem first. Please refer to FIG. 4A showing health care body 502 of upper arm health care device 500 of the present invention which has carrying base plates 501, 503, each of which has paired recesses 511, 512 respectively configuring pairs of positioning blocks 524, 504. Because all positioning blocks 524, 504 are similarly provided, only positioning block 504 is illustrated in details as follows.

(75) Positioning block 504 has a pair of lower lugs 516 slidably configured in a pair of side grooves 518 in recess 512. Two ends 513, 515 of each of springs 514 are respectively configured on inner wall 517 of recess 512 and inner wall 519 of the lower part of positioning block 504. Inner wall 517 and inner wall 519 are provided to compensate or offset the length of springs 514. In this invention, plural springs 514 always keep paired positioning blocks 504 as close as possible to each other in paired recesses 512. The remaining width of the cutout upper portion at the free end of carrying base plate 503 between paired recesses 512 is approximately the thickness of the lower arm wrist. Because people are unavoidably thin or fat, according to this invention, paired positioning blocks 504 can be adjusted automatically to hold the wrist part. Additionally, the lug in the figure is sheet-shaped, while cylindrical one may be more common. Because they make no substantial difference, it will not be further described.

(76) When acupoints of the Hand-Yangming Large Intestine Meridian (for example, Wenliu, International Code LI7, which mainly treats headache, sore throat, borborygmus, abdominal pain, and shoulder/back pain) are treated, the wrist should be held by paired positioning blocks 504 in the thickness direction to facilitate acupoint physiotherapy/treatment. At this time, the protrusion corresponding to the short abductor muscle of the user's thumb rests in cavity 510 recessed in positioning block 504. However, when acupoints of the Hand-Jueyin Pericardium Meridian (for example, Neiguan, International Code PC6, which mainly treats stomach pain, nausea, vomiting, chest pain, arrhythmia, stroke/dementia, elbow spasm, hot face, cloudy vision, shock) are treated, the wrist should be held by paired positioning blocks 504 in the width direction with the yin side up. At this time, a radial carpal protrusion of the lower arm abuts on recess 506 of left side positioning block 504, while an ulnar carpal protrusion of the lower arm abuts on recess 505' of right side positioning block 504 for co-performing the positioning effect. If we observe the wrist structure carefully, contrasting with the palm, the radial carpal protrusion of the lower arm is in a lower but anterior position, while the ulnar carpal protrusion is in an upper but posterior position, and thus we can use this structural feature to design positions of recesses 505, 506 of positioning block 504 for strengthening the positioning relationship or function. Specifically, no matter whether the yin side of the forearm (or lower arm) faces upward or downward, it can be effectively held by positioning blocks 504. Additionally, the user's palm stays free in groove 508 of positioning block 504.

(77) On the contrary, when acupoints of the Hand-Shaoyang Sanjiao Meridian (for example, Waiguan, International Code TES, which mainly treats unfavorable flexion and extension of elbow/arm, finger pain/inability to grip, hand tremor, deafness, tinnitus, headache, cheek pain, fever) are treated, the wrist should be held by paired positioning blocks 504 in the width direction with the yang side up. At this time, the ulnar carpal protrusion of the lower arm abuts on recess 505 of left side positioning block 504, while the radial carpal protrusion of the lower arm abuts on recess 506' of right side positioning block 504 for co-performing the positioning effect. There is a recess 520 at the end of carrying base plate 503. This recess 520 has two functions, wherein on the one hand, when the forearm side is kept laterally upright on base plate 503 (i.e., resting with

thickness), the abductor muscle of the user's little finger rests thereon; on the other hand, when the yin side of the forearm is placed on base plate **503**, the user's wrist/palm rest thereon.

(78) Please refer to the left portion of FIG. **4A** showing positioning block **524** and carrying base plate **501** for carrying the elbow joint. Positioning block **524** has recess **526** accommodating the most protruding sesamoid at the ulnar side of the elbow end of the humerus, and carrying base plate **501** correspondingly has recess **534** accommodating the most prominent part (i.e., elbow tip) of the elbow end of the ulna. The structure of the human body is very mysterious. When the forearm rests on carrying base plates **501**, **503**, whatever it is kept laterally upright or placed with the yang side, recesses **526** and **534** can accommodate the sesamoid and the most prominent part, respectively. However, when the forearm is kept laterally upright, left and lower sides of prominent muscles (composed of the palmar longus muscle, the flexor carpi radialis and the flexor carpi ulnaris) of the forearm are respectively positioned in groove **528** of positioning block **524** and groove **536** of carrying base plate **501**. As preceding positioning block **504** of the wrist joint, positioning blocks **524** are configured on paired recesses **511** of carrying base plate **501**, and has paired lugs **530** slidably configured in grooves **532** of recesses **511**.

(79) Please refer to the middle portion of FIG. **4A** showing length adjustment medium **546** configured between two carrying base plates **501**, **503**. The Creator is mysterious, and makes people either tall or short with arms either short or long. For example, it is said that Liu Bang's hands are long enough to extend beyond his knees, and thus length adjustment medium **546** is configured for accommodation. Adjacent ends of carrying base plates **501**, **503** have central groove **550** for accommodating linking plate **547** symmetrically. Each adjacent end of carrying base plates **501**, **503** has inner recesses **538**, so that pairs of tension springs **540** are configured symmetrically above and below linking plate **547** to pull together carrying base plates **501**, **503** as much as possible. Opposite sides of adjacent ends of carrying base plates **501**, **503** respectively have plural pairs of pin holes **542**, which correspond to plural pin holes **548** on both sides of linking plate **547**. When the distance between adjacent ends of carrying base plates **501**, **503** corresponding to the user's arm length is properly adjusted, four pins **544** can be inserted into corresponding pin holes **548** and corresponding two pairs of pin holes **542** to complete the arm length setting.

(80) Please refer to FIG. **4B**. Its right side is the forearm carrying base plate of FIG. **4A**, which is to be combined with the one for the upper arm to form a complete upper limb carrying base plate, and thus is slightly modified. Specifically, the elbow end of forearm carrying base plate **502** (or **501**) has bottom cutout **552** and bottom shaft hole **554**. Its left side is upper arm carrying base plate **560** having two carrier plates **562**, **564**. The elbow end of carrier plate **564** has upper cutout **568** and central pivot **572** pivoted on bottom shaft hole **554**. Contrasting with upper arm carrying base plate **560**, because the forearm can only be bent inward, rather than folded outward, its pivoting is directional. Viewing from FIG. **4B**, considering existence of the elbow end of the forearm carrying base plate **502**, when pivoting counterclockwise, its distal side **535** must interfere with the elbow end of upper arm carrying base plate **560**, so that if the elbow end of upper arm carrying base plate **564** is not modified accordingly, they cannot rotate with each other. Therefore, the elbow end of upper arm carrying base plate **564** has cutout **570** to accommodate distal side **535** of the elbow end of forearm carrying base plate **502**.

(81) Please refer to the left side of FIG. **4B**. Because the inner side of the upper arm is connected to the body, the inner and outer sides of the upper arm have different lengths relative to upper arm carrier plate **562**, and thus the distal side of axillary end **566** of carrier plate **562** has cutout **580** and semi-cylindrical part **576** connected thereto to urge against the user's axilla. Additionally, the proximal side of axillary end **566** of carrier plate **562** has a guiding sheet **578** conforming to the shoulder end of the user's upper arm. Certainly, in order to adapt to the forearm length, a length adjustment device **574** can be configured between two carrier plates **562**, **564**, which will not be detailed here.

(82) Please refer to FIG. **4C** showing an embodiment of length adjustment device **586** of the health

care body of the health care device of the present invention. Length adjustment plate **596** having sliding hole **595**, longitudinal central groove **591**, paired grooves **597** on both sides of the distal end, paired proximal grooves **610** and grooves **599** configured on both sides of length adjustment plate **596** is configured between two carrying base plates **582**, **584**. Adjacent distal ends of two carrying base plates **582**, **584** have paired arc convexes **606**, paired grooves **608** respectively configured on both sides of paired arc convexes **606**, paired middle grooves **601**, and paired springs **604** (corresponding/symmetrical to arc convexes **606**) configured between mutually corresponding paired grooves **608** and paired grooves **597**, wherein respective two ends of paired springs **604** are connected to respective corresponding grooves **608** and grooves **597**, longitudinal center groove **591** moves therein trapezoidal plate **600**, and when two carrying base plates **582**, **584** abut against length adjustment plate **596**, arc convexes **606** are accommodated into longitudinal center groove **591**. The distal plural pairs of springs **604** and the proximal plural pairs of springs **612** tend to combine carrying base plates **582**, **584** and length adjustment plate **596** planarly together because the three plates **582**, **584** and **596** are slidably sleeved together via distal side pieces **602** and sliding holes **616**, middle groove **601** and trapezoidal piece **600**, and corresponding paired guiding pieces **614** and paired guiding grooves **618** at the proximal side.

(83) Although there are adult, children, men and women, in fact, for the forearm or upper arm, the difference of lengths usually does not exceed 5 cm. Even if comparing a four-year-old child with a person who is two meters height, it is rare that the difference of lengths exceeds 15 cm. Length adjustment plate **596** has screw hole **587** and plural positioning pinholes **598**. Under the condition that the total length of three plates **582**, **584** and **596** is the shortest, there is no gap thereamong. Because trapezoidal piece and screw rod assembly **620** is configured, when it is necessary to increase its virtual length, the user rotates handle **590** of screw rod **588** to push trapezoidal piece **600** to move to the distal side. Since two side bevels **603** of trapezoidal piece **600** abut against arc convexes **606**, carrying base plates **582**, **584** are pushed out symmetrically to adjust the total virtual length of three plates **582**, **584** and **596**. When screw rod **588** is rotated to an appropriate extent to obtain a suitable total virtual length of three plates **582**, **584** and **596**, positioning pin **594** connected to screw rod **588** via chain **592** is inserted into positioning pinhole **598** nearest to the desired position to prevent springs **604**, **612** from possibly reversing screw rod **588**.

(84) Please refer to FIG. 4D showing a first embodiment of trapezoidal piece and screw rod assembly **620**. Trapezoidal piece **600** has a bottom hole **624** for accommodating screw rod end **622**. Please refer to FIG. 4E showing a second embodiment of trapezoidal piece and screw rod assembly **628**. In some cases, for example, when it is desired to control the thickness of carrying base plates **582**, **584** and **596**, or when the thickness of trapezoidal piece **630** is limited, chuck **634** can be configured to hold the bottom of trapezoidal piece **630**, and has hole **636** to match end **640** of screw rod **638**. Additionally, shallow guiding groove **632** may also be configured on side bevel **631** in proper circumstances to securely guide the relative movement between arc convexes **606** (FIG. 4C) and trapezoidal piece **630**.

(85) The preceding health care devices only are used for primary purposes or have primary functions, i.e., they are used to fix a rod-shaped acupoint work piece **300** as shown in FIG. 1. The health care devices discussed here are summarized as follows. Health care device (**500**) includes health care body (**502**) having carrying base plate (**501**, **503**) carrying a body part, and paired recesses (**511**, **512**), wherein the body part is an upper or lower limb or has an upper body part and a lower body part, any one of the body parts has a main limb bone, any body part or limb bone has two ends, and at least one of the two ends has a protruding features; paired positioning blocks (**524**, **504**) are respectively slidably configured on paired recesses (**511**, **512**), and have recesses (**505**, **506**) corresponding to the protruding features for holding the relevant body part therebetween by the protruding feature; and a work piece holder (not shown) has a first end connected to carrying base plate (**501**, **503**) or positioning block (**524**, **504**), and a second end holding an acupoint work piece.

(86) Health care device (500) includes health care body (502) having two carrying base plates (501, 503) adapting to a body part in length to carry the body part, and one end of each carrying base plate (501, 503) has paired recesses (511, 512), wherein the body part is an upper or lower limb and has an upper body part and a lower body part, any body part has a main limb bone, any body part or main limb bone has two ends, and at least one of the two ends has a protruding features; paired positioning blocks (524, 504) are respectively slidably configured on paired recesses (511, 512), and have recesses (505, 506) corresponding to the protruding features for holding the relevant body part therebetween by the protruding feature; and a work piece holder (as shown in FIG. 1 or the embodiments described later) has a first end connected to carrying base plate (501, 503) or positioning block (524, 504), and a second end holding an acupoint work piece (as shown in FIG. 1 or the embodiments described later).

(87) In accordance with health care device (500) of the two preceding embodiments, positioning block 504 has paired lower lugs 516; recess 512 has paired side grooves 518 respectively sliding therein paired lugs 516.

(88) In accordance with health care device (500) of the two preceding embodiments, positioning block (503) has a free end whose width is approximately the thickness of the lower arm wrist after deducting the width of paired recesses 512.

(89) In accordance with health care device (500) of the two preceding embodiments, one of positioning block (504) has cavity (510) accommodating the thumb short abductor muscle of the palm when the palm is upright, recess (506) abutting the radial carpal protrusion of the lower arm, recess (505) abutting the ulnar carpal protrusion of the lower arm, and groove (508) staying free the palm therein.

(90) In accordance with health care device (500) of the two preceding embodiments, the end of the free end of one carrying base plate (503) has recess (520) resting thereon an little finger abductor muscle of the user when the forearm is kept laterally upright (i.e., resting with thickness), and freely resting thereon the wrist/palm of the user when an inner (or yin) side of the lower arm is placed.

(91) In accordance with health care device (500) of preceding embodiments, when positioning block (524) is configured in recess (511) of carrying base plate (501) carrying the forearm elbow end, positioning block (524) has recess (526) accommodating a most protruding ulnar sesamoid at an elbow end of a humerus, carrying base plate (501) has recess (534) for accommodating a most prominent part (i.e., the elbow tip) of elbow end of the ulna, and positioning block (524) and carrying base plate (501) respectively has groove (528, 536) positioning therein a respective left or lower side of prominent muscles of the lower arm when the lower arm is kept laterally upright.

(92) In accordance with health care device (500) of preceding embodiments, two carrying base plates (501, 503) configure therebetween length adjustment medium (546) including paired central grooves (550) respectively configured on adjacent ends of carrying base plates (501, 503), linking plate (547) configured in paired central grooves (550), plural paired pinholes (542) respectively configured on opposite sides of adjacent ends of carrying base plates (501, 503), plural pinholes (548) respectively configured on linking plate (547) and corresponding to plural paired pinholes (542), and four pins (544) inserted into pinholes (548) of linking plate (547) and corresponding two pairs of pinholes (542) of carrying base plates (501, 503).

(93) In accordance with health care device (500) of preceding embodiments, health care device (500) further includes upper arm carrying base plate (560), wherein the elbow end of forearm carrying base plate 502 (or 501) has bottom cutout (552) and bottom shaft hole (554), upper arm carrying base plate (560) has two carrier plates (562, 564), the elbow end of carrier plate (564) has upper cutout (568) and central pivot (572) pivoting on bottom shaft hole (554), and the elbow end of carrier plate (564) has another cutout (570) accommodating distal side of elbow end (535) of forearm carrying base plate (502).

(94) In accordance with health care device (500) of preceding embodiments, the distal side of

axillary end (566) of carrier plate (562) near the axilla has cutout (580) and semi-cylindrical part (576) connected thereto to urge against the user's axilla, and the proximal side of axillary end (566) has guiding sheet (578) conforming to the shoulder end of the user's upper arm.

(95) From another aspect, health care device (500; 560) holds an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a health care onto a user, wherein the user has a body part having an acupoint, and the health care device (500; 560) includes: health care body (501, 503; 562, 564) having carrying base plate (502; 562) carrying the body part, for maintaining a first specific positional relationship with the body part, wherein the carrying base plate has an end, the body part has a main limb bone, and the body part or the main limb bone has a protruding feature corresponding to the recess; paired positioning blocks (504; 524) are respectively slidably configured on the carrying base plate, and have recesses (505; 526) corresponding to the protruding feature for confining the protruding feature to position the body part therebetween; and a work piece holder (as described in FIG. 1 or the following embodiments) has: a first end connected to the carrying base plate or the paired positioning blocks, and a second end holding the acupoint work piece, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(96) From yet another aspect, health care device (500; 560) includes: health care body (501, 503; 562, 564) having carrying base plate (502; 562) carrying a body part of a user, for maintaining a first specific positional relationship with the body part, wherein the carrying base plate has an end, the body part has a main limb bone, and the body part or the main limb bone has a protruding feature corresponding to the recess, and the body part has an acupoint; paired positioning blocks (504; 524) are respectively slidably configured on the carrying base plate, and have recesses (505; 526) corresponding to the protruding feature for confining the protruding feature to position the body part therebetween; and a work piece holder (as described in FIG. 1 or the following embodiments) has: a first end connected to the carrying base plate or the positioning block, and a second end holding an acupoint work piece (as described in FIG. 1 or the following embodiments), for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(97) A health care device (500) includes a health care body having two carrying base plates (582; 584) for carrying a body part; and length adjustment device (586) configured on two carrying base plates (582; 584) for adjusting an apparent length of the health care body to be adapted to a length of the user's body part.

(98) In accordance with the health care device of preceding embodiments, length adjustment device (586) is configured between two carrying base plates (582, 584) and has sliding hole 595; adjacent ends of two carrying base plates (582, 584) have paired arc convexes (606), paired middle grooves (601) and paired sliding holes (616); side piece (602) is inserted through sliding hole (595) and paired sliding holes (616), and slidably and planarly combines carrying base plates (582, 584) and length adjustment plate 596 together; and trapezoidal piece (600) is configured in paired middle grooves (601), and adjusts an apparent length of the health care body by an interaction between paired side bevels (603) and paired arc convexes (606).

(99) In accordance with the health care device of preceding embodiments, length adjustment plate (596) has screw hole (587), plural positioning pinholes (598) and rotatable screw rod (588) for operating trapezoidal piece (600) so as to adjust a contact position between paired side bevels (603) of trapezoidal piece (600) and arc convexes (606) to adjust a total virtual length of three plates (582, 584, 596).

(100) In accordance with the health care device of preceding embodiments, trapezoidal piece (600) has bottom hole (624), and screw rod (588) has end (622) configured freely rotatable in bottom hole 624.

(101) In accordance with the health care device of preceding embodiments, the health care device further includes chuck (634) having first end (642) for holding bottom (646) of trapezoidal piece (630), and second end (644) having hole (636) thereon configuring therein end (640) of screw rod (638).

(102) In accordance with the health care device of preceding embodiments, side bevel (631) of trapezoidal piece (630) has shallow guiding groove 632 for guiding therein arc convex (606).

(103) From another aspect, health care device (500; 560) holds an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a health care onto a user, wherein the user has a body part having an acupoint, and the health care device includes: a health care body having two carrying base plates (501, 503; 562, 564) carrying the body part, for maintaining a first specific positional relationship with the body part; a length adjustment device (546; 574; 568) configured between the two carrying base plates for adjusting an apparent length of the health care body to be adapted to a length of the body part; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to one of the two carrying base plates, and a second end holding the acupoint work piece, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(104) From yet another aspect, health care device (500; 560) includes: a health care body having two carrying base plates (501, 503; 562, 564) carrying and positioning a body part of a user, for maintaining a first specific positional relationship with the body part, wherein the body part has an acupoint; a length adjustment device (546; 574; 568) configured between the two carrying base plates for adjusting an apparent length of the health care body to be adapted to a length of the body part; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to one of the two carrying base plates, and a second end holding an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a health care onto a user, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(105) There are also many acupoints on the foot soles, for example, the Neiting acupoint (International Code ST44) of Stomach Meridians of Foot-Yangming located at 0.5 body inch behind the web edge between the second and third toes mainly treats headache, toothache, facial edema, bloody dysentery and gastrointestinal diseases. The suitable health care device may be the one shown in FIG. 1, which will not be detailed here. Additionally, the foot sole health care device may also be obtained by adopting or modifying the health care device of FIG. 3B.

(106) From this paragraph, the health care device suitable for the lower limb will be discussed. The lower limb includes the thigh and the shank, which are thicker but less bendable/flexible than the upper limb; for example, the rotatable angle of the knee/ankle is obviously less than that of the elbow/wrist. Additionally, the distribution regularity of acupoints in the lower limb is poorer than that of the upper limb, so that design principles of the health care device suitable for the upper limb cannot be or is not suitable for direct/complete application for the lower limb. According to acupuncture and moxibustion theories, when specific reference points of the thigh and shank are found, it can be found that there is a specific length ratio relationship between them. In details, the length from the greater trochanter of the femur to the outer Dubi acupoint (located between the femur and the tibia, and outwards below the kneecap) is 19 body inches, and the length from the outer Dubi acupoint to the lateral malleolus is 16 body inches, that is, the length ratio of these two sections is 19:16. The length is different for everyone because of their height, but the ratio is the same for everyone regardless of age. The former may mislead that the traditional Chinese medicine or the acupuncture is unscientific, while the latter arouses acclamations for mysteries of the human body or the wisdom of our ancestors.

(107) Please refer to FIG. 5. Health care body 660 of the lower limb health care device includes

shank carrying base plate **662**, thigh carrying base plate **664**, and length adjustment device **690**. Length adjustment device **690** plays the following roles: (1) forming a part of the carrying base plate or platform of health care body **660**; (2) for (tibia) heel end **666** of shank carrying base plate **662**, providing a carrying platform for the tibia knee end, and forming a combined shank carrying platform with shank carrying base plate **662**; (3) for (femur) buttock end **730** of thigh carrying base plate **664**, providing a carrying platform for the femur knee end, and forming a combined thigh and shank carrying platform with shank carrying base plate **662**; (4) adjusting an apparent length of the health care body to fit the specific leg length of each user; (5) simultaneously adjusting the apparent lengths of shank and thigh carrying base plates **662**, **664** for a specific user's thigh and shank; (6) simultaneously adjusting the apparent lengths of shank and thigh carrying base plates **662**, **664** according to the 16:19 ratio; and (7) forming the positioning device of the knee reference feature.

(108) Paired side grooves **668** are configured on shank carrying base plate **662** near heel end **666** for slidably configuring paired positioning blocks **680** therein. Because positioning blocks **680** are similar to positioning blocks **504**, **524** of FIG. 4A, they are only briefly described here. As mentioned above, the length from the outer Dubi acupoint to the lateral malleolus is 16 body inches. Although the length from the lateral malleolus to the heel is not within the feature length of the shank, the foot sole is connected to the shank, so that it is designed as follows. Considering the accommodation of the tibia outer protrusion of the shank of the user when the user lies pronely, and the accommodation of the calf, the calcaneal tendon and the calcaneus when the user lies supinely, shank carrying base plate **662** has central concave **740**, and heel end **666** has deeper recess **670**. Paired side grooves **668** are configured on shank carrying base plate **662** near heel end **666**. Each groove **668** has paired slots **678** for slidably configuring paired lugs **682** configured on each positioning block **680**. Heel height adjustment medium **748** is configured on positioning blocks **680** and heel end **666** for accommodating heel heights of different users. Ankle engaging recesses are configured on paired opposite surfaces **681** of paired positioning blocks **680**. Taking distal positioning block **680** of FIG. 5 as an example, its opposite surfaces **681** have large lateral malleolus recess **684**, middle lateral malleolus recess **686** and small lateral malleolus recess **688**. The purpose of configuring these three recesses is to match the user's height, and to accommodate therein the lateral malleolus. In details, in general, although there are children, adults, fatties and skinnies, in fact, the difference in length of shank (or including the distance between the lateral malleolus and the foot sole) is usually less than 50%. Specifically, the vertical (when standing) or horizontal (when lying) distance or height from the lateral malleolus to the heel is about 4 cm for a child and about 7 cm for a person of about 170 cm. Therefore, three recesses **672**, **674**, **676** are configured on recess **670** for the heel portion, paired recesses **672** and **688**, **674** and **686**, and **676** and **684** can well accommodate the specific length of each user, and in this manner, heel height adjustment medium **748** works.

(109) Certainly, in design, three heel recesses **672**, **674**, **676** can be a continuous inclined surface to create a stepless effect, and positioning block **680** can simply have one lateral malleolus recess. On the contrary, if the width of opposite surfaces **681** is increased, heel end **666** can be narrowed, and three recesses **672**, **674**, **676** are not needed. Additionally, the proximal positioning block **680** has a recess (not shown) corresponding to the medial malleolus. For facilitating the health care body assembly, opposite surfaces **681** on paired positioning blocks **680** can be respectively provided with three recesses **685**, **687**, **689** (or **684**, **686**, **688**) corresponding to the medial malleolus (or lateral malleolus), that is, it is unnecessary to pay attention to which positioning block **680** belongs to the distal or proximal side. It is also worth noting that when using the health care body, because acupoints are located on the leg back or the calf, the user may lie supinely or pronely. Taking FIG. 5 as an example, when lying supinely, the lateral malleolus of the right leg is on the distal side; when lying pronely, the lateral malleolus of the left leg is on the distal side. Thus the distal positioning block is provided with three additional malleolus recesses **685**, **687**, **689** for positioning

when lying pronely. It is also worth noting that when lying supinely, the calcaneal tendon will raise the height of the lateral malleolus, but when lying pronely, the distance between the leg back and the lateral malleolus is shortened. Thus, the height of three lateral malleolus recesses **685**, **687**, **689** on positioning block **680** is less than that of three lateral malleolus recesses **684**, **686**, **688**. Needless to say, the springs pulling paired positioning blocks **680** closer to each other are the same as those in FIG. **4A**, which will not be detailed here.

(110) Buttock end **730** of health care body **660** has recess **736** for accommodating muscles connecting between buttocks and the thigh, and its distal end has accommodating hole **732** for accommodating positioning block **726** having positioning hole **728** for containing the trochanter major protrusion at the femur buttock end. Plural springs **734** are configured between the distal wall of accommodating hole **732** and the distal wall of positioning block **726** to abut positioning block **726** against the trochanter major protrusion at the femur buttock end for positioning. The proximal side of buttock end **730** of thigh carrying base plate **664** has stop **738** for abutting against the bottom edge of the groin, to complete the complete positioning of buttock end **730** of the lower limb.

(111) Please refer to the middle part of FIG. **5** showing length adjustment device **690** of health care body **660**. Basically, length adjustment device **690** simultaneously serves as parts of both shank and thigh, and forms a complete platform for carrying shank and thigh with shank carrying base plate **662** and thigh carrying base plate **664**. The shank and thigh carrying base plates **662**, **664** are interconnected to have a longitudinally adjustable distance and form an integral lower limb health care body **660** by at least one pair of rods **710** and at least two pairs of rod holes **712** sleeving paired rods **710** and respectively configured on adjacent two ends and on both sides of carrying base plates **662**, **664**.

(112) Length adjustment device **690** mainly includes carrying base plate **702**, operating rod **694** and length adjustment trapezoidal piece **742** (also refer to FIG. **5A**). Length adjustment device **690** is similar to length adjustment device **586** in FIG. **4C**. In brief, only main differences are described here. Carrying base plate **702** has central recess **720**, screw hole **704** and a distal middle groove (not shown, for accommodating length adjustment trapezoidal piece **742**). Length adjustment trapezoidal piece **742** has two side bevels **744** and **746** for abutting against arc convexes (not shown, for clarity, refer to FIG. **4C**). The distal half of operating rod **694** has thread **692** for screwing into screw hole **704** to urge length adjustment trapezoidal piece **742** in the middle groove at the distal side of carrying base plate **702** as required, to increase the apparent length of the shank and thigh carrying platform according to the actual demand. When the user lies pronely, central recess **720** is provided for accommodating the user's protrusion of a kneecap.

(113) Paired positioning blocks **714** are configured in space **706** between thigh and shank carrying base plates **664**, **662** for positioning the corresponding features of tibia and femur around the knee. Specifically, for the knee, the most protruding part of the outer side is the knee tuberosity of the tibia, and the most protruding part of the inner side is the knee tuberosity of the femur. Thus, positioning block **714** at the distal end has recess **718** to accommodate the knee tuberosity of the tibia. Because only legs are changed when lying suprinely and pronely, and the position of the knee tuberosity of the tibia will not be changed, only one recess **718** is configured. Specifically, although the height of the tuberosity is different when lying suprinely and pronely, it can be compensated by the depth of central recess **720** or the central height of carrying base plate **702**. Likewise, only one accommodating recess **719** corresponding to the knee tuberosity of the femur on proximal end positioning block **714** in FIG. **5** is needed. As shown in FIG. **5**, the shape of lugs **716** of positioning block **714** is significantly different from that in FIG. **4A**, because thigh and shank carrying base plates **664**, **662** are separated from each other during the operation of length adjustment device **690**. Therefore, lugs **716**, slidably configured in paired sliding slots **750** on thigh and shank carrying base plates **664**, **662** respectively, are lengthened to be slidably positioned between positioning blocks **714** in the separation process of thigh and shank carrying base plates **664**, **662**. Additionally,

the springs (not shown, for clarity, refer to FIG. 4A) are respectively configured between positioning blocks **714** and carrying base plates **662**, **664**, so that positioning blocks **714** tend to be close to each other, to position the user's knee joint.

(114) One or more pairs of springs **708** are used to keep thigh and shank carrying base plates **664**, **662** close to each other. Because the characteristics of this embodiment, paired spring **708** may be installed after the positioning blocks are installed. Proximal positioning block **714** has through hole **722** for freely passing therethrough operating rod **694**, and plural pinholes **724** are configured on the proximal surface, so that when operating rod **694** is in the correct operating position, it can be fixed through pinning pin **700** connected to handle **696** through chain **698** in pinhole **724**. Please refer to FIG. 5A, the configurations of two side bevels **744** and **746** cause distances between each side bevel and the center of operating rod **694** to be respectively X and Y, and distances of X and Y have a ratio relationship of 16:19. Length adjustment device **690** is pushed away from shank and thigh carrying base plates **662**, **664** according to this ratio relationship, to perfectly and nondeformably adjust acupuncture lengths of thigh and shank for each user.

(115) The health care body of the lower limb health care device of the present invention is summarized as follows. Health care body (**660**) includes shank carrying base plate (**662**); thigh carrying base plate **664**; and length adjustment device (**690**) having a first part forming a combined shank carrying platform with shank carrying base plate (**662**), and a second part forming a combined thigh carrying platform with thigh carrying base plate (**664**).

(116) In accordance with the health care body of the preceding embodiment, length adjustment device (**690**) serves as a positioning device for the reference feature of the knee.

(117) According to a second embodiment of the health care body of the present lower limb health care device, health care body (**660**) includes shank carrying base plate (**662**) for carrying a user's shank and lateral malleolus; thigh carrying base plate (**664**) for carrying the user's thigh and the trochanter major protrusion of the femur; and length adjustment device (**690**) having a first and a second parts for respectively carrying the user's the knee lateral tuberosity of the tibia of the shank and the knee medial tuberosity of the femur of the thigh, wherein length adjustment device (**690**) can adjust the apparent length of the health care body to accommodate the user's specific leg length.

(118) In accordance with the health care bodies of the preceding embodiments, shank carrying base plate (**662**) and thigh carrying base plate (**664**) respectively co-form a shank and a thigh carrying platforms with the first and second parts of length adjustment device (**690**), and the length adjustment device simultaneously adjusts apparent lengths of the corresponding thigh and shank carrying platforms.

(119) According to a second embodiment of the health care body of the present lower limb health care device, health care body (**660**) includes shank carrying base plate (**662**) for carrying a user's shank and lateral malleolus; thigh carrying base plate **664** for carrying the user's thigh and trochanter major protrusion of the femur; and length adjustment device (**690**) having a first and a second parts for respectively carrying the user's the knee lateral tuberosity of the shank tibia and the knee medial tuberosity of the thigh femur, wherein shank carrying base plate (**662**) and thigh carrying base plate (**664**) respectively co-form a combined shank and thigh carrying platforms with the first and second parts of length adjustment device (**690**), which simultaneously adjusts under a ratio of 16:19 the combined shank and thigh carrying platforms.

(120) In accordance with the health care bodies of the preceding embodiments, shank carrying base plate (**662**) has central concave (**740**), wherein when the user lies prone, central concave (**740**) contains the outer protrusion of the shank tibia, and when the user lies supine, central concave (**740**) accommodates the shank calf.

(121) In accordance with the health care bodies of the preceding embodiments, shank carrying base plate (**662**) has heel end (**666**) having deeper recess (**670**) for containing therein the calcaneal tendon and the calcaneus when the user lies supine.

(122) In accordance with the health care bodies (660) of the preceding embodiments, shank carrying base plate (662) has heel end (666) and paired positioning blocks (680) slidably configured close to heel end (666) for containing a user's lateral malleolus and medial malleolus.

(123) In accordance with health care bodies (660) of the preceding embodiments, heel height adjustment medium (748) is configured on paired positioning blocks (680) and heel end (666) for being adapted to the specific heel height of each user.

(124) In accordance with health care bodies (660) of the preceding embodiments, paired positioning blocks (680) respectively have opposite surfaces (681) having recesses (684, 685, 686, 687, 688, 689) so designed that regardless of whether the user is lying supinely or pronely, and whether positioning blocks (680) are interchanged or not, the recesses can correctly accommodate the user's lateral malleolus and medial malleolus, respectively.

(125) In accordance with health care bodies (660) of the preceding embodiments, thigh carrying base plate (664) has buttock end (730) having recess (736) for accommodating the muscles connecting between buttocks and the thigh; positioning block (726) for containing the trochanter major protrusion at the femur buttock end of the user; and stop (738) configured on a side of buttock end (730) for abutting against the bottom edge of the user's groin.

(126) In accordance with health care bodies (660) of the preceding embodiments, length adjustment device (690) includes carrying base plate (702), operating rod (694) and length adjustment trapezoidal piece (742); length adjustment trapezoidal piece (742) has two side bevels (744, 746) for respectively abutting against shank and thigh carrying base plates (662, 664); distances between two side bevels (744, 746) and the center of operating rod (694) respectively are X and Y; and distances of X and Y have a ratio relationship of 16:19.

(127) In accordance with health care bodies (660) of the preceding embodiments, length adjustment device (690) includes paired positioning blocks (714) configured between thigh and shank carrying base plates (664, 662) for simultaneously positioning the knee tuberosity of the tibia and the knee tuberosity of the femur of a user.

(128) From another aspect, health care body (660) holds an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a health care onto a user, wherein the user has a lower limb having a shank, a thigh and an acupoint, and the health care body includes: a shank carrying base plate (662) and a thigh carrying base plate (664) respectively carrying and positioning the shank and the thigh, for maintaining a first specific positional relationship with the shank or the thigh; a length adjustment device (690) configured between the shank carrying base plate and the thigh carrying base plate, wherein the shank carrying base plate, the thigh carrying base plate and the length adjustment device have an actual total length and a virtual length, and the length adjustment device is used for adjusting the virtual length of the health care body; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to the shank or the thigh carrying base plate, and a second end holding the acupoint work piece thereon, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(129) From yet another aspect, health care device (660) includes: a health care body having a shank carrying base plate (662) and a thigh carrying base plate (664) carrying and positioning a lower limb/body part of a user, for maintaining a first specific positional relationship with the body part, wherein the lower limb has a shank, a thigh and an acupoint; length adjustment device (690) configured between the shank carrying base plate and thigh carrying base plate, wherein the shank carrying base plate, thigh carrying base plate and length adjustment device have an actual total length and a virtual/apparent length, and the length adjustment device is used for adjusting the virtual length of the health care body; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to the shank or thigh carrying base plate, and a second end holding an acupoint work piece (as described in FIG. 1 or the following

embodiments) thereon to engage in a health care onto a user, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(130) After discussions above, only the head of the human body remains untreated. In this regard, please refer to FIG. 6 showing head health care body **760** including base plate **762**, paired slots **764** on either of left and right sides, paired oil cylinders **772**, paired head positioning plates **766**, paired pressure sensors **784** configured on each paired positioning plates **766**, circuit configuration **790** integrating the operation of pressure sensors **784** and oil cylinders **772**, and paired oil cylinder forward and backward buttons **786**, **788** configured on either of left and right sides of base plate **762**. Specifically, below each positioning plate **766**, paired lower protruding sliders **782** having two side lugs are slidably configured in respective paired slots **764**. Oil cylinder **772** has first end **774** fixed on base plate **762** and second end **776** fixed on the corresponding positioning plate **766** by paired connecting rods **768**, **770**, so that the distance between paired positioning plates **766** is determined by paired oil cylinders **772**.

(131) When using, because there are many acupoints on face and back of the head, health care body **760** is not only suitable for the user lying supinely to perform the health care work on the face, but also suitable for the user lying pronely to perform the healthcare work on back of the head. It can be understood why the center of base plate **762** is provided with inverted triangular hole **780** to expose eyes and nose when the user lies pronely. When forward button **786** is operated, oil cylinders **772** pushes positioning plates **766** toward each other. First, the user's paired ears will pass through ear holes **778** on positioning plates **766**, followed by circuit arrangement **790** to cut off the power immediately when the temple, being the most protrusive on the user's head, is predeterminedly touched by related pressure sensors **784**, to complete the head's positioning. No matter whether the holder of the acupoint work piece is configured on base plate **762** or positioning plate **766**, it is easy to define the relative position with the acupoint, and thus not detailed here.

(132) It is worth noting that the movement device (i.e., oil cylinder **772** in the embodiment) of the preceding head healthcare device can also be simply modified to displace the length adjustment device of the more preceding embodiments to digitize and accurately control the total amount of displacement, which will not be detailed here.

(133) The head health care body is summarized as follows. Healthcare body (**760**) includes base plate (**762**) supporting a user's head; paired head positioning plates (**766**), symmetrical to the head's longitudinal axis, and movably configured transversely on base plate (**762**) for positioning the user's head to ensure the acupuncture work on the user's head or face; movement device (**772**) configured between base plate (**762**) and paired head positioning plates (**766**) for determining a spacing of paired head positioning plates (**766**) to be adapted to a width of the user's head or face; and an acupointing work piece configured on base plate (**762**) or head positioning plates (**766**) to perform a work to the acupoint.

(134) In accordance with the preceding head health care body, the head health care device further includes pressure sensor (**784**) configured on at least one of paired positioning plates (**766**), whose position corresponds to a vicinity of the user's temple, and when paired positioning plates (**766**) move until the head is touched by or sandwiched with pressure sensors (**784**), the movement device power is cut off.

(135) In accordance with the preceding head healthcare body, movement device (**772**) is oil or pneumatic cylinder.

(136) In accordance with the preceding head healthcare body, either side of base plate (**762**) has paired buttons (**786**, **788**) controlling the movement device to move forward and backward.

(137) In accordance with the preceding head health care body, base plate (**762**) has paired slots (**764**); and below each positioning plate (**766**), paired lower protruding sliders (**782**) having two-side lugs are slidably configured in corresponding paired slots (**764**).

(138) In accordance with the preceding head health care body, movement device (**772**) has first end

(774) fixed on base plate (762), and second end (776) fixed on respective positioning plate (766) by paired connecting rods (768, 770).

(139) In accordance with the preceding head healthcare body, base plate (762) has inverted triangular hole (780) to expose eyes and nose when the user lies prone.

(140) In accordance with the preceding head health care body, each positioning plate (766) has ear hole (778) for passing through the user's ear.

(141) From another aspect, healthcare body (760) holds an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a health care onto a user, wherein the user has head, face and acupoint, and the health care body includes: a base plate 662 carrying thereon the head or face, for maintaining a first specific positional relationship with the head or face; paired head positioning plates (766), symmetrical to the head's longitudinal axis, and movably configured transversely on the base plate for positioning the head or face to perform a healthcare work on the user through the acupoint; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to the base plate, and a second end holding the acupoint work piece thereon, for ensuring the acupoint work piece to perform the healthcare work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(142) From yet another aspect, health care body 760 includes: a base plate 664 carrying thereon a user's head or face, for maintaining a first specific positional relationship with the head or face, wherein the head or face has an acupoint; paired head positioning plates 766, symmetrical to the head's longitudinal axis, and movably configured transversely on the base plate for positioning the head or face to perform a healthcare work on the user through the acupoint; movement device 772 configured between base plate 762 and paired head positioning plates 766 for determining a spacing of the paired head positioning plates in adaptation to a width of the user's head or face; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to the base plate, and a second end holding an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in the healthcare work, for ensuring the acupoint work piece to perform the healthcare work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(143) Those who have researched acupuncture and have a keen mind may question that although the acupoint positioning mechanism described above is new, it is not yet complete or ideal. The reason why it is not complete is that taking the head healthcare body as an example, there are still acupoints on the head top. If the positioning device for the acupoint workpiece is configured on positioning plate 766, it seems that the distance is relatively long, which may raise an "accurate" positioning issue. Therefore, it seems that the following logic can be developed: If the accurate positioning of the acupoints in the head's front, back and top can be solved, this solution can be applied or modified, and the accurate positioning for the rest body will naturally be obtained. Certainly, in order to avoid any doubt for the skilled person in the art, while disclosing the solution below, it will be briefly explained why the accurate positioning for other acupoints is a piece of cake.

(144) FIG. 7 shows head health care device 800 for accurate positioning purposes, which includes health care body 802, where two positioning plates 766 in FIG. 6 are changed to two rail bodies 804 in this figure. In appearance, it seems that the complexity is involved, but this is the only way for the invention to jump from the basic level to the advanced level, which is described hereinafter. To avoid the figure being too complicated, the first displacement/adjustment device for the distance between two rail bodies 804 is disclosed in the preceding embodiments, and thus is no longer shown in FIG. 7. Each rail body 804 has upper surface 810, paired gear slots 806 configured on two longitudinal sides close to upper surface 810, and lower gear racks 808 are configured on the top surface of gear slots 806. Additionally, upper gear rack 812 is configured longitudinally along upper surface 810.

(145) The first displacement/adjustment device of two rail bodies **804** adjusts the distance therebetween, and carrier bodies **814**, **816** carry work base **848**. Carrier bodies **814**, **816** are two-piece because they need to follow the distance change between two rail bodies **804**, and to fully perform the carrying work. Paired positioning rods **832** are respectively configured on distal and proximal sides of left end surface **830** of carrier body **816**, and paired positioning slots **834** are correspondingly configured on carrier body **814**, so that no matter how two rail bodies **804** change within the necessary distance adjustment range, upper surfaces **858**, **860** of two carrier bodies **814**, **816** are coplanar.

(146) Proximal surfaces **862**, **864** of carrier bodies **814**, **816** each has paired positioning plates **818**, each of which has positioning gear **820** meshing with lower gear rack **808**. Each proximal surface **862**, **864** fixes therewith stepping motor **822** and gear protection sheet (with/without gear slot) **824**. Stepping motor **822** has motor shaft **826** coaxially fixing therewith gear **828**. Therefore, when gear **828** is driven to rotate by stepping motor **822**, because carrier bodies **814**, **816** have been fastened to lower gear rack **808** by positioning gear **820**, gear **828** will definitely mesh with upper gear rack **812** (or between upper gear rack **812** and gear protection sheet **824** with gear) to longitudinally move entire carrier bodies **814**, **816** along two rail bodies **804**. Additionally, the whole mechanism, i.e., all components carried and configured on carrier bodies **814**, **816**, achieves the second displacement/position adjustment function (that is, move longitudinally along rail body **804**), under cooperation of two sets of upper gears **828** and paired lower gears **820**. The functions/purposes of this second displacement/position adjustment will be described later.

(147) Side positioning plate **836** is fixed on carrier body **814** for fixing another stepping motor **838** driving screw rod **840**. The screw rod nest **842** is fixed on upper surfaces **858**, **860** for accommodating screw rod **840**, and has two side wall upper surfaces **844**. Work base **848** is driven by stepping motor **838** to move along two side wall upper surfaces **844** through moving piece **846** screwed to screw rod **840** to determine its work position. To adapt to the distance change between two rail bodies **804**, the right side bottom of screw rod nest **842** has middle protruding piece **852**, and upper surface **860** has corresponding groove **854** for allowing middle protruding piece **852** to freely slide in groove **854**. Certainly, to increase the sliding smoothness, plural balls **856** may be configured between middle protruding piece **852** and groove **854**. Therefore, the mechanism completes the third free movement of work base **848** on screw rod nest **842** to change its working position free from any influence from the preceding first and second displacements/position adjustments. Certainly, the functions/purposes of this third displacement/position adjustment or change will be detailed later. Work base **848** has fixing screw bolt **850** fixing a work piece, which will be detailed later.

(148) The standard body inch at the head and face depends on the Touwei acupoint of Stomach Meridians (International Code ST8, located at 0.5 body inch behind the hairline of the forehead, and mainly treating eye pain, unclear vision, unbearable headache, splitting headache, dizziness), and the distance between left and right Touwei acupoints defines 9 standard horizontal head body inches. Specifically, after the distance between two rail bodies **804** is adjusted by first displacement/adjustment device **772** in FIG. 6 to position a user's face, the third displacement/position adjustment mechanism (component assembly **838-856**) can be activated to perform the healthcare or medical work. First, this kind of work is therefore performed very delicately, because the positioning of the stepping motor can be extremely accurate; second, stepping motor **838** is activated first to obtain the specific size of each person, that is, moving work base **848** first to ascertain Touwei acupoints (International Code ST8), followed by calculating the real distance therebetween, and proportionately correlating this real distance to 9 body inches, whereby we can know the exact length of a body inch a specific person has; third, when the exact size of the specific person is known, it can be accurately found out where the other acupoints are based on this; fourth, when it can be accurately found out where the specific acupuncture point is, the healthcare or medical work on the acupoint is performed, that is, there is no risk of

misdiagnosis or mistreatment.

(149) As mentioned, in order not to make the figure too complicated, health care body **802** is somewhat simplified. Another point that should also be mentioned here is that FIG. 7 is suitable for the head and face healthcare. For Governor Vessel, there are Yamen acupoint (International Code GV15), Fengfu acupoint (International Code GV16), Naohu acupoint (International Code GV17), Qiangjian acupoint (International Code GV18) and Houding acupoint (International Code GV19) in the head back, and thus, the positions of health care body **802** corresponding to these acupoints must be hollowed out. There are two ways of hollowing out, hollowing horizontal grooves to expose spaces corresponding to these acupoints, or providing longitudinal holes corresponding to these acupoints. Because this is not difficult, it will not be further detailed or illustrated in this regard.

(150) Please refer to FIG. 7A showing acupoint workpiece connecting piece **870** having first end **874** connected to fixing nut **876**, and second end **880** connected to acupoint workpiece nut **882**. Fixing nut **876** is screwed on fixing screw bolt **850** with its internal thread **878**, so acupoint workpiece connecting piece **870** is precisely positioned on carrier bodies **814**, **816**, and work nut **882** is screwed to an acupoint work piece with its internal thread **884** to perform the healthcare or medical act on a certain acupoint. More details will be described later.

(151) The standard head vertical body inch is defined to 12 body inches from the front hairline to the back hairline. To find out how many centimeters the head vertical body inch a specific user has, the second displacement/position adjustment mechanism (component assembly **808**, **812** and **818-828**) is activated. Specifically, when stepping motor **822** is activated, upper gear **828** and paired lower gears **820** will drive carrier bodies **814**, **816** to move longitudinally along two rail bodies **804**, by which a probe workpiece fixed on work base **848** ascertain the real size between the front and back hairlines of a specific user. As this real size is defined as 12 standard head vertical inches, it can be known how many centimeters each head vertical inch of the user has. It may deserve mentioned here that to move carrier bodies **814**, **816** driven by stepping motor **822** smoothly along the longitudinally curved rail **804**, the interactive bottom surfaces related to carrier bodies **814**, **816** and upper surfaces of two rails **804** can have an appropriate arc, to facilitate the mutual relative movement, which will not be detailed here.

(152) Although the first (**772**), second (component assembly **808**, **812** and **818-828**) and third (component assembly **838-856**) displacement/position adjustment mechanisms in FIGS. 6, 7 and 7A take the head as an example, it should not be difficult for the skilled artisan to directly apply or modify it to the upper limb, lower limb or trunk healthcare body, so it will not be detailed here. However, it can be known that by the preceding mechanism, the following amazing effects can be achieved: 1. A certain acupoint can be accurately found out according to the extremely advanced modern stepping motor; 2. The specific body size of the specific user can be measured; 3. Because the body size of each body part is not necessarily the same, it can be used for different body parts of the same user, and the exact body size of a certain part can be found out; 4. A new milestone for further scientificization of acupoints or acupuncture is achieved.

(153) The health care device for accurate position is summarized as follows. Health care device (**800**) includes health care body (**802**); rail body (**804**) configured on health care body (**802**) generally along a body part of a user; work base (**848**) configured on rail body (**804**) for building thereon an acupoint workpiece, for ensuring the acupoint workpiece to perform a healthcare or medical work onto the body of the user; and driving device (**818-828**) configured between rail body (**804**) and work base (**848**), for moving work base (**848**) along rail body (**804**), so work base (**848**) and a specific part are in an optimum mutual relative positional relationship.

(154) In accordance with preceding health care device (**800**), health care device (**800**) further includes another rail body (**804**) configured on health care body (**802**), and two rail bodies (**804**) sandwich the body part; and displacement/position adjustment device (**772**) configured on health care body (**802**) and at least one rail body (**804**) to adjust the distance between two rail bodies

(804).

(155) In accordance with preceding health care device (800), rail body (804) has upper surface (810); near upper surface (810), paired gear slots (806) are configured on both longitudinal sides of rail body (804); a top surface of each gear slot (806) has (downward) lower gear rack (808); upper surface (810) longitudinally configures upper gear rack (812); and driving device (818-828) has upper gear (828) meshed with upper gear rack (812), and paired lower positioning gears (820) respectively meshed with paired lower gear racks (808).

(156) In accordance with preceding health care device (800), health care device (800) further includes two carrier bodies (814, 816), each of whose proximal surfaces (862, 864) has paired positioning plates (818); each positioning plate (818) has paired lower positioning gears (820); two proximal surfaces (862, 864) are respectively fixed with gear protection sheet (824) and stepping motor (822); and each stepping motor (822) has motor shaft (826) and upper gear (828) fixed coaxially.

(157) In accordance with preceding health care device (800), health care device (800) further includes a carrier configured between two rail bodies (804) and work base (848), wherein the carrier includes two carrier bodies (814, 816); and two carrier bodies (814, 816) have adjacent end surfaces (830) respectively having at least one pair of positioning rods (832) and at least one pair of positioning slots (834) corresponding to positioning rod (832), whereby no matter how a distance between two rail bodies (804) changes, upper surfaces (858, 860) of two carrier bodies (814, 816) are co-planar.

(158) In accordance with preceding health care device (800), health care device (800) further includes carrier body (814, 816) carrying thereon work base (848); carrier longitudinally moving stepping motor (838) configured on carrier body (814, 816); and screw rod (840) configured between stepping motor (818) and work base (848), wherein stepping motor (838) drives to rotate/move work base (848).

(159) In accordance with preceding health care device (800), carrier body (814, 816) has upper surface (858, 860); and health care device (800) further includes screw rod nest (842) and moving piece (846), wherein screw rod nest (842) is fixed on upper surfaces (858, 860) for accommodating screw rod (840), moving piece (846) is configured between work base (848) and screw rod (840), and stepping motor (838) determines the work position of work base (848).

(160) In accordance with preceding health care device (800), the carrier includes two carrier bodies (814, 816) respectively having two upper surfaces (858, 860); one upper surface (860) of the two upper surfaces has sliding groove (854); and screw rod nest (842) has middle protruding piece (854) corresponding to the bottom of upper surface (860), whereby middle protruding piece (852) freely slides in groove (854).

(161) In accordance with preceding health care device (800), health care device (800) further includes at least one ball (856) configured between middle protruding piece (852) and groove (854).

(162) In accordance with preceding health care device (800), health care device (800) further includes acupoint workpiece connecting piece (870), wherein acupoint workpiece connecting piece (870) has first end (874) connected to fixing nut (876), and second end (880) connected to acupoint workpiece nut (882); fixing nut (876) is screwed on fixing screw bolt (850) on work base (848); and work nut (882) screws thereto an acupoint work piece.

(163) From another aspect, health care device 800 holds an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in a healthcare onto a user, wherein the user has a body part having an acupoint, and the health care device includes: a health care body 802 carrying and positioning the body part, for maintaining a first specific positional relationship with the body part; a rail body 804 configured on the health care body and extended generally along the body part; a work base 848 configured on the rail body; an acupoint work piece (as described in FIG. 1 or the following embodiments) configured on the work base to perform a health related

work on the user through the acupoint; a driving device (**836-846**) configured between the rail body **804** and the work base **848** for moving the work base along the rail body; and a workpiece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to the health care body, and a second end holding the acupoint work piece thereon, for ensuring the acupoint work piece to perform the health related work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(164) From yet another aspect, health care device **800** includes a health care body **802** carrying and positioning a body part of a user, for maintaining a first specific positional relationship with the body part, wherein the body part has an acupoint; a rail body **804** configured on the health care body and extended generally along the body part; a work base **848** configured on the rail body to perform a health related work on the user through the acupoint; a driving device (**836-846**) configured between the rail body **804** and the work base **848** for moving the work base along the rail body; and a work piece holder (as described in FIG. 1 or the following embodiments) having: a first end connected to the health care body, and a second end holding an acupoint work piece (as described in FIG. 1 or the following embodiments) thereon to engage in the health related work, for ensuring the acupoint work piece to perform the health related work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(165) It is pitiful/regrettable if such a precise positioning or displacement adjustment mechanism is only used for completing the simple healthcare as shown in FIG. 1. The advanced application of the present invention will be described below to show its actual industrial value. The physical therapy on acupoints, or acupuncture-related act at present (1) relies on professionals, such as traditional Chinese physicians or their assistants; (2) relies on the handiness of professionals (who know the correct work position) or fixed relatively large equipment (often difficult to maintain or obtain relative positions between acupoints and relevant parts of the equipment); (3) trusts the professional to have sufficient physical strength to maintain suitable relative position or contact relationship between the acupoint work piece and acupoints within a specific period; and (4) trusts that the professional is in good spirits and mood during working hours, and will not misjudge acupoints to achieve the above-mentioned task in (3). However, at least because (1) people will get tired, (2) emotion will inevitably fluctuate, (3) mind may occasionally be absent, (4) consumers may not have enough financial resources or time to keep their bodies healthy by physical therapy or traditional Chinese clinic, and/or (5) service provider, such as traditional Chinese physicians, may experience cost pressure for hiring enough assistants, we can use the aforementioned precise positioning mechanism to at least complete (1) the precise relative positional relationship between acupoint work piece and acupoint; (2) continuously and reliably maintaining the relative positional relationship in (1); (3) obtaining for the user the present precise positioning device at an extremely economical cost and using it at home; (4) when the user's illness or discomfort is relieved by the present invention, s/he no longer needs to go to the hospital for treatment, which saves the burden on the national health insurance by at least one third (taking Taiwan as an example, it is over NT\$200 billion); and/or (5) the resources can be transferred to measures benefiting country and people under rational national policies.

(166) The ideal disclosures may be touching; but it must be implemented before gaining trust from others. According to Paragraphs 20 to 29 of the present specification, it can be known/inferred that there must be various acupoint work pieces on the market, for examples, (A) the microwave needle usually has a focal work point; (B) the radiator instrument often has a planar or curved output end; (C) the magnet has a specific work plane; (D) one end of the magnetic massager is a single relatively large ball, while the other end includes three relatively small balls. Please refer to FIG. 8 showing a specific embodiment of a workpiece assembly, including work base **900** configured on the aforementioned health care device, being equivalent to work base **848**, and having longitudinal through hole **902**. In this embodiment, work piece holder **906** has first end **908** configuring thereon

annular groove **916**, and second end **910** configuring thereon connector **912** having internal thread **914**. Work piece **964** has first end **918** screwed to internal thread **914**, and second end **922** being an acupoint workpiece for performing the health care work onto a user's acupoint, and first and second ends **918**, **922** are connected by connecting piece **920**.

(167) When using, first end **908** of work piece holder **906** passes through through hole **902**, and C-clamp **904** is fastened to annular groove **916** to position work piece **964**. If the acupoint work piece, i.e., second end **922** of work piece, is the microwave or radiation in the preceding paragraph, it is only necessary to determine or fix the relative positional relationship between acupoint work piece **922** and the acupoint; but if it is a magnet or magnetic massager, some pressure must be applied on the acupoint. To achieve the purpose of applying pressure, because connector **912** is cylindrical and first end **918** is columnar, their screwing depth can determine the work pressure applied to the acupoint, to adjust the work pressure of acupoint work piece **922**. Please refer to FIG. **8A**, the first end of work piece holder **930** has threaded section **932** and annular groove **934**, and threaded section **932** is to tightly fit with threaded hole **938** on work base **936** at a specific angle. In this way, the work angle of acupoint work piece **922** with respect to the acupoint can be adjusted.

(168) Please refer to FIG. **8B** showing an embodiment of acupoint work piece **940** in the present invention. Acupoint work piece **940** is basically slender pneumatic cylinder **942** having threaded end **944** connected to a work piece holder and work end **960**. Work bottom **962** adjacent to work end **960** has rotatably configured crankshaft **954**, point opening **966**, rubber pad **958** configured among crankshaft **954**, point opening **966** and work bottom **962**, main connecting piece **950** having first end **968** and second end **970** fixing thereon ring piece **952**, upper connecting ring **948** fixed on piston rod **946** of pneumatic cylinder **942** and interlocked with ring piece **952**, and work ring **956** fixed on first end **968** and movably buckled on the crank part of crankshaft **954**. When using, crankshaft **954** is driven to rotate downward through upper connecting ring **948**, main connecting piece **950** and work ring **956** when piston rod **946** moves down; and crankshaft **954** is reversely driven to rotate upward through the same components when the piston rod moves up. At this time, point opening **966** is in contact with an acupoint, and work ring **956** performs the massage operation on the user's acupoint through rubber pad **958** by the crankshaft's rotation. According to the acupoint's characteristics, the shape of point opening **966** can be determined, such as a small round area, or an arc slot corresponding to the working track of work ring **956**.

(169) Different embodiments disclosed in different stages or embodiments of the present application can be mutually replaceable, which should be noted. This paragraph summarizes the main requirements related to the acupoint work piece. Specifically, a health care device includes a health care body; work base (**900**) configured on the health care body for health-caring a user having an acupoint; a moving device configured between work base (**900**) and the health care body to move a position of work base (**900**) corresponding to the health care body; acupoint work piece (**922**) performing a health-care work onto the user through the acupoint; and work piece holder (**906**) for connecting acupoint work piece (**922**) to work base (**900**), so that acupoint work piece (**922**) can continue performing the health-care work under a specific relationship position relative to work base (**900**) or the acupoint.

(170) In accordance with preceding health care device, work piece holder (**906**) has first end **908** configured on work base (**900**), and second end (**910**) configuring thereon connector (**912**) having internal thread (**914**); and work piece (**964**) has first end (**918**) screwed to internal thread (**914**), and second end (**922**) for performing the health-care work onto a user's acupoint or part to be treated.

(171) In accordance with preceding health care device, connector (**912**) is cylindrical, and first end (**918**) of work piece (**964**) is columnar, whereby a screwed depth or extent therebetween can determine a work pressure of the acupoint or part to be treated exerted by second end (**922**).

(172) In accordance with preceding health care device, second end (**922**) of work piece (**964**) is an acupoint work piece.

(173) In accordance with preceding health care device, work base (**900**) has longitudinal through

hole (902); first end (908) of work piece holder (906) has annular groove (916); and after first end (908) passes through through hole (902), C-clamp (904) is fastened to annular groove (916) to position work piece (964).

(174) In accordance with preceding health care device, work base (900) has longitudinal through hole (902) having an end threaded hole (938); and first end (908) of work piece holder (906) has a threaded section (932), whereby we can adjust a work angle acupoint work piece 922 treats the acupoint or part to be healthcared through press-fit of threaded section (932) with threaded hole (938) under a specific angle.

(175) From another aspect, a health care device holds an acupoint work piece thereon to engage in a health-care onto a user, wherein the user has a body part having an acupoint, and the health care device includes: a health care body carrying the body part thereon, for maintaining a first specific positional relationship with the body part; work base 900, 936 configured on the health care body; an acupoint work piece configured on the work base to perform a health related work on the user through the acupoint; moving device (e.g., 836-846, 972, 1040) configured between the work base and the health care body for determining an orientation of the acupoint work piece relative to the health care body; and a work piece holder (e.g., 906, 930) having: a first end connected to the work base, and a second end holding the acupoint work piece thereon, for ensuring the acupoint work piece to perform the health related work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(176) From yet another aspect, a health care device includes a health care body carrying a body part of a user thereon, for maintaining a first specific positional relationship with the body part, wherein the body part has an acupoint; work base 900, 936 configured on the health care body to perform a health related work on the user through the acupoint; moving device (e.g., 836-846, 972, 1040) configured between the work base and the health care body for securing an orientation of the work base relative to the health care body on the health care body; and work piece holder (e.g., 906, 930) having: a first end connected to the work base, and a second end holding an acupoint work piece thereon to engage in the health related work, for ensuring the acupoint work piece to perform the health related work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(177) A work piece (940) for health care is configured on a health care device to perform a health-care work on a user's acupoint, wherein the health care device has a work base (900), and the acupoint work piece (940) includes work body (942) having first end (944) and second end (960), wherein first end (944) is connected to work base (900); and health care medium (922, 956) configured on second end (960) to perform the health-care work.

(178) In accordance with preceding work piece, the work body is slender pneumatic cylinder (942) having piston rod (946).

(179) In accordance with preceding work piece, work end (960) further includes crankshaft (954) rotatably configured on work end (960); point opening (966); rubber pad (958) configured between crankshaft (954) and point opening (966); and main connecting piece (950) connected between piston rod (946) and crankshaft (954), so that piston rod (954) drives crankshaft (954) to perform the health-care work.

(180) In accordance with preceding work piece, main connecting piece (950) has first end (968) and second end (970); second end (970) fixes therewith ring piece (952); work piece (940) further includes upper connecting ring (948) connected between piston rod (946) and ring piece (952); and work ring (956) is fixed on first end (968), and movably buckled to crankshaft (954).

(181) In accordance with preceding work piece, work ring (956) performs massage operation on body part or acupoint through rubber pad (958).

(182) In accordance with preceding work piece, point opening (966) is a round opening, or an arc slot corresponding to working track of work ring (956).

(183) In accordance with preceding work piece, the first end has a thread.

(184) In accordance with preceding work piece, a working medium of the health care medium is a microwave, a millimeter wave, a radiation heat, a magnetism, a frequency signal, a microcurrent or a wormwood heat.

(185) From another aspect, healthcare acupoint work piece (**942, 964**) is configured on health care body (e.g., **502, 562, 582**) to perform a health care work on an acupoint in a user's body part, wherein the health care body has work base (**900, 934**) carrying and positioning the body part for maintaining a first specific positional relationship with the body part, and the acupoint work piece includes: work body (**922, 942**) having first end (**944**) and second end (**960**), wherein the first end is connected to the work base; and a health care medium (**922; 946-958**) configured on the second end, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(186) From yet another aspect, acupoint work piece (**942, 964**) for health care includes work body (**922, 942**) configured on health care body (e.g., **502, 562, 582**), wherein the health care body carries and positions a body part of a user, the health care body maintains a first specific positional relationship with the body part having an acupoint, the health care body has work base (**900, 934**) to perform a health care work to user through the acupoint, and the work body includes: first end (**944**) connected to the work base; second end (**960**); and health care medium (**922; 946-958**) configured on the second end, for ensuring the acupoint work piece to perform the health care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(187) It is not difficult under the current technology if the accuracy of adjusting the working angle of the acupoint work piece is to be increased. Please refer to the second embodiment of the work piece assembly in FIG. 8C showing work base **971** corresponding to work base **848**. Work base **971** configures thereon angle controller **972** including angle control assembly **974** and work piece supporter **976**. Supporter **976** fixes thereon threaded barrel **980** through fixing piece **978**, whereby supporter **976** is controlled by angle control assembly **974** to secure for threaded barrel **980** a specific angle relative to work base **971** or the acupoint. FIG. 8D shows that highly resilient acupoint workpiece jaw **984** is fixed on workpiece supporter **982** by screw or rivet **986**, and acupoint workpiece jaw **984** has paired holding parts **988** for thinly holding an acupoint work piece therebetween.

(188) This paragraph summarizes the acupoint work piece having the accurate adjustment of the working angle. Specifically, a health care device includes a health care body; work base (**971**) configured on the health care body for health-caring a user having an acupoint; an acupoint work piece performing a health-care work onto the user through the acupoint; and angle controller (**972**) for connecting the acupoint work piece to work base (**971**), so that the acupoint work piece can continue performing the health-care work under a specific angle relative to work base (**971**) or the acupoint.

(189) In accordance with preceding health care device, the health care device further includes a moving device configured between work base (**971**) and the health care body to move a position of work base (**971**) relative to the health care body.

(190) In accordance with preceding health care device, the angle controller includes angle control assembly (**974**) and workpiece supporter (**976**) connected thereto to obtain a specific work angle of workpiece supporter (**976**) with respect to work base (**971**) or the acupoint.

(191) In accordance with preceding health care device, workpiece supporter (**976**) is highly resilient acupoint workpiece jaw (**984**) fixed on workpiece supporter (**982**) by rivet or screw (**986**).

(192) In accordance with preceding health care device, workpiece jaw (**984**) has paired resilient holding parts (**988**) for thinly holding an acupoint work piece therebetween.

(193) One should not consider that the disclosure of the technology related to the acupoint health care of the present invention has been completed with the aforementioned work pieces and health

care devices. Specifically, although the last embodiment above can solve the problem of precise angle control, taking the Gallbaldder Meridian as an example, its distribution path of some acupoints is rather irregular. For example, three acupoints, Yanglingquan (International Code GB34, mainly treating knee pain, sciatica, hemiplegia, lower limb numbness and cholecystitis), Yangjiao (International Code GB35, mainly treating chest/flank distention, chest tightness, pharyngitis, knee pain, leg/foot atrophy/weakness, facial swelling) and Waiqiu (International Code GB36, mainly treating headache, neck pain, hepatitis, lower limb paralysis, poisonous stasis from a vicious dog) cross front side, midline and back side of the yang surface of the shank. Even the positioning problem can be solved based on the above, it is not the best policy to invoke “a cannon” for only a few acupoints. Therefore, if there is a design that can allow the acupoint work piece to be optionally tilted relative to the work base, the usability or satisfaction of the design will be greatly improved.

(194) To the aforementioned purpose, please refer to FIG. 9 showing an embodiment of work piece assembly **1000** matching with a robotic arm. Modern technology is often amazing, where robots or robotic arms can often work with precision. Work assembly **1000** includes work base **1022** of FIG. 9 corresponding to work base **848** of FIG. 7, and work platform **1020** fixed thereon. Work platform **1020** carries rotating platform **1018** with a precisely controlled rotation angle, and rotating platform **1018** is connected to first end **1024** of connecting base **1014** with a precisely controlled pivot angle. First end **1012** of extension base **1010** is connected to rotating shaft **1016** of second end **1026** of connecting base **1014** with a precisely controlled pivot angle, and second end **1028** of extension base **1010** is fixed to first end **1030** of rotating head **1008** having second end **1032** precisely rotatably fixing thereon electric chuck **1002** having two jaws **1004** respectively having paired holding surfaces **1006** for holding the preceding acupoint work piece therebetween. Having these four rotations, it can be immediately imagined that: (1) some displacement designs or requirements in FIG. 7 can be replaced; (2) if this work piece assembly **1000** is combined with lower limb health care body **660** in FIG. 5, the irregular acupoints on the Gallbaldder Meridian are very easy to be found; (3) with respect to the reference point or positioning point of the acupoint work piece on the health care body, the planar distance, vertical height and relative angle of the acupoint work piece relative to the specific part or acupoint of the body to be health cared can be fully controlled (through the abovementioned four rotation movements, which can be accurately calculated and obtained); and (4) therefore, the medical-grade acts can be expected using the acupoint work piece. In this regard, the principle is detailed in the next paragraph.

(195) The body inch standards of hand and leg are mentioned above. If following standards of the chest and abdomen are realized, with the structure disclosed earlier, after finding the reference acupoint, can the specific body inch of a person be found and calculated? It also helps to find other acupoints automatically by the computer, and thus the misidentification of acupoints caused by the fatigue of the doctors or humans can be avoided, which will be detailed later. (1) The standard of chest vertical body inch: 6.8 body inches from Tiantu acupoint (International Code CV22) to Shanzhong acupoint (International Code CV17, the middle of two nipples); (2) the standard of upper abdomen vertical body inch: 8 body inches from branch bone (xiphoid process) to navel (International Code CV8, Shenque); (3) the standard of lower abdomen vertical body inch: 5 body inches from navel (International Code CV8) to Qugu (International Code CV2); (4) the standard of lateral abdomen vertical body inch: 9 body inches from Zhangmen (International Code LR13) to Huantiao (International Code GB30); and (5) the standard of trunk horizontal body inch: 8 body inches between two nipples. Therefore, after the Shanzhong acupoint is obtained, 1.6 body inches therebeneath is Zhongting acupoint (International Code CV16). In details, according to the preceding robotic arm device (components **1002-1020**), (1) the first rotation mechanism (between components **1018** and **1020**) can determine the angular relationship between the work base or the health care body and an acupoint; (2) the second pivoting mechanism (between components **1018** and **1014**) can at least determine the linear distance relationship between the work base or the

health care body and an acupoint alone or together with other mechanisms; (3) the third pivoting mechanism (between components **1010** and **1014**) can at least determine the height relationship between the work base or the health care body and an acupoint alone or together with other mechanisms; (4) the fourth rotation mechanism (between components **1010** and **1002**) can determine the angular relationship between the acupoint work piece and an acupoint; and (5) all these relationships can be easily and automatically calculated by the computer to obtain in which distance and orientation (actually representing an acupoint position) of the robotic arm device to enable the acupoint work piece to perform the health care or therapeutical work to the user through the acupoint under which specific angle. Therefore, although oblique acupuncture is often necessary for acupoints on the head/face, it is no longer a trouble because the control/adjustment of the relative inclination angle between the acupoint work piece and the work base has been made possible by the aforementioned mechanism. Certainly, it has been described that the robotic arm device can be directly configured on a health care body, or configured on a work base that has been configured on the health care body.

(196) The main requirements related to work piece assembly **1000** are summarized as follows. Specifically, a health care device includes a health care body for health-caring a user having an acupoint; work platform (**1020**) configured on the health care body; an acupoint work piece performing a health-care work onto the user through the acupoint; and robotic arm device (component assembly **1002-1020**) connected to the work platform (**1020**) for holding the acupoint work piece, so that the acupoint work piece can perform the health-care work under a specific relationship position relative to work platform (**1020**) or the acupoint.

(197) In accordance with preceding health care device, the health care device further includes work base (**1022**) configured between the health care body and work platform (**1020**); and a moving device (FIG. 7) configured between work base (**1022**) and the health care body.

(198) In accordance with preceding health care device, the health care device further includes rotating platform (**1018**) rotatably carried on work platform (**1020**).

(199) In accordance with preceding health care device, the health care device further includes connecting base (**1014**) pivotally connected on the rotating platform (**1018**).

(200) In accordance with preceding health care device, the health care device further includes extension base (**1010**) having first end (**1012**) and pivotally connected on connecting base (**1014**).

(201) In accordance with preceding health care device, the robotic arm device includes rotating head (**1008**) rotatably fixing precisely thereon electric chuck (**1002**) having two jaws (**1004**) respectively having paired holding surfaces (**1006**) to hold therebetween the acupoint work piece.

(202) It can be imagined that since the preceding health care device is precise enough, it is predictable it can be applied to the needle insertion of acupuncture. Because the control and adjustment of the angle can be completed by the preceding embodiments, it is easily understood according to FIG. 9A that the automatic needle insertion of acupuncture is feasible. Maybe people may question that as an acupuncture act is of a human nature, why does the present invention try to do it mechanically? This question is actually contrary to the appeal for “scientificization of traditional Chinese medicine (TCM)”, not to mention that the scientific spirit is a nature of TCM. First, the “Encyclopedia of Acupuncture/Moxibustion” points out: “Needle withdrawal should happen slowly, or it will cause injuries if rapid”, which means that the needle should be withdrawn slowly, which can wonderfully be performed by a machine which will follow instructions without mood or emotional effects. Second, according to the Yellow Emperor Neijing, Ci-Yao Chapter, which records “There are floating and sunk states, while the acupuncture depth is shallow or deep. Each case has its own curing rationale, from which deviation should be avoided. An excessive extent will cause an internal hurt while an insufficiency will produce a superficial block which in turn invokes an evil qi. An improper depth will cause a big trouble internally hurting the 5 organs to develop an ensuing serious disease”, each acupoint for a certain disease has its appropriate depth. By the same token, isn't it the best policy to determine the appropriate depth of needle

insertion by a machine to eliminate the interference of human factors?

(203) FIG. 9A shows an embodiment of automatic needle inserting acupoint work piece **1040** including rotating head **1042** similar to rotating head **1008** of Figure 9 and automatic needle inserting device **1044**. Automatic needle inserting device **1044** includes electric holder **1048** (or a non-electric holder) for holding an acupoint work device, and needle inserting mechanism **1046** capable of longitudinally moving electric holder **1048** and pivotably configured on rotating head **1042**. Needle inserting mechanism **1046** enables the acupoint work device to insert the needle orderly or controls the needle inserting speed by a stepless speed motor. As this technical task can be easily achieved by the skilled person in the art, which will not be detailed here. Certainly, when it is necessary to significantly drain the evil qi, the needle hole must be widened. At this time, the needle inserting parameters are not limited to the speed, but include the front, back, left and right polarizations. In view of above technical disclosures, these technical tasks should already be easily realizable by the skilled in the art, which will not be detailed here.

(204) The main requirements related to automatic needle inserting acupoint work piece **1040** are summarized as follows. Specifically, a health care device includes a health care body for health-caring a user having an acupoint; an acupoint work piece performing an acupuncture work onto the user through the acupoint; a robotic arm device (component assembly **1002-1020**) configured on the health care body for holding the acupoint work piece, so that the acupoint work piece can perform the acupuncture work under a specific relationship position relative to the health care body or the acupoint; and needle inserting mechanism (**1046**) configured between the acupoint work piece and the robotic arm device, and enabling the acupoint work piece to perform the acupuncture work on the user with a specific control parameter.

(205) In accordance with the preceding automatic needle inserting acupoint work piece, the specific control parameter is a speed control parameter.

(206) In accordance with the preceding automatic needle inserting acupoint work piece, the specific control parameter is a polarization parameter.

(207) In accordance with the preceding automatic needle inserting acupoint work piece, the automatic needle inserting acupoint work piece further includes holder (**1048**) for holding the acupoint work piece.

(208) In accordance with the preceding automatic needle inserting acupoint work piece, the automatic needle inserting acupoint work piece further includes needle inserting mechanism (**1046**) for longitudinally moving holder (**1048**).

(209) In accordance with the preceding automatic needle inserting acupoint work piece, the automatic needle inserting acupoint work piece further includes rotating head (**1042**) for rotatably configuring needle inserting mechanism (**1046**) on the robotic arm device.

(210) From another aspect, health care device **1000** holds an acupoint work piece thereon to engage in a health-care onto a user, wherein the user has a body part having an acupoint, and the health care device includes: health care body (e.g., **502**, **562**, **582**) carrying and positioning the body part, for maintaining a first specific positional relationship with the body part; work platform (**1020**) configured on the health care body; and a robotic arm device (**1002-1018**) connected to the work platform for holding the acupoint work piece, for ensuring the acupoint work piece to perform the health-care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional relationship.

(211) From yet another aspect, health care device (**1000**) includes a health care body (e.g., **502**, **562**, **582**) carrying and positioning a body part of a use, for maintaining a first specific positional relationship with the body part to engage in a health-care work onto the user, wherein the body part has an acupoint; work platform (**1020**) configured on the health care body; and a robotic arm device (**1002-1018**) connected to the work platform for holding the acupoint work piece, for ensuring the acupoint work piece to perform the health-care work when the acupoint work piece has a second specific positional relationship with the acupoint under the first specific positional

relationship.

(212) Descriptions on relevant hardware of the present invention have come to an end. It can be found that each paragraph is directed to adjust the “qi field” to recuperate the body instantly when there is an initial disease omen, for a longeval and healthy life as disclosed in the Yellow Emperor Neijing Suwen, Yijing Qi-Change Chapter, “while nearing being alive away from death, the living seedling is growing.” The present invention's gist is summarized with the FIG. **10** flowchart as follows: providing health care body **1100**, wherein the health care body has a first relative positional relationship with a user's body part having an acupoint; providing acupoint work piece having a second positional relationship with the health care body and a third positional relationship with the acupoint to perform a health care work on the user through the acupoint (**1110**); and providing a positioning device configured between the acupoint work piece and the health care body to position the acupoint work piece on the health care body, and ensure the acupoint work instrument to perform the health care work under the second and the third positional relationships (**1120**).

(213) From another aspect, the present invention is a health care method for health-caring a user, wherein the user has a body part having an acupoint, including: providing a health care body (**1130**); positioning the body part on the health care body under a first relative positional relationship between the health care body and the body part (**1140**); providing an acupoint work piece to perform a health care work onto the user through the acupoint (**1150**); providing a position adjustment device configured between the acupoint work piece and the health care body for maintaining a second positional relationship therebetween (**1160**); and ensuring the acupoint work piece to perform the health care work with a control parameter (**1180**).

(214) In accordance with the preceding health care method, the first relative positional relationship is to enable the body part to keep the relative positional relationship with the health care body in a specific posture.

(215) In accordance with the preceding health care method, the health care method further includes a step of enabling the acupoint work piece to have a specific angle relationship with the acupoint (**1170**) between the steps of providing the position adjustment device (**1160**) and ensuring the acupoint work piece to perform the health care work with the control parameter (**1180**).

(216) In accordance with the preceding health care method, the second relative positional relationship is to enable the acupoint work piece to keep the relative positional relationship with the health care body in at least one of a specific distance, direction and height.

(217) In accordance with the preceding health care method, the control parameter is a work mode for the acupoint work piece to perform the health care work.

(218) In accordance with the preceding health care method, the work mode is that the acupoint work piece and the acupoint remain mutually still.

(219) In accordance with the preceding health care method, the work mode is that the acupoint work piece and the acupoint keep therebetween a specific contact relationship.

(220) In accordance with the preceding health care method, the work mode is that the acupoint work piece performs a massage operation onto the user through the acupoint.

(221) In accordance with the preceding health care method, the work mode is that the acupoint work piece inserts into or draws out of the acupoint at a specific speed.

(222) From another aspect, a method using an acupoint work piece to perform a health care work on a user, wherein the user has a body part having an acupoint, includes: providing a health care body for carrying the body part **1110**; positioning the body part on the health care body so that the health care body and the body part have a first relative positional relationship therebetween **1120**; and providing a position adjustment device for maintaining a second positional relationship between the acupoint work piece and the health care body, or the acupoint work piece and the acupoint to ensure the acupoint work piece to perform the health care work with a control parameter (**1160**).

(223) From yet another aspect, a health care method includes: providing a health care body for health-caring a user (**1110**), wherein the user has a body part having an acupoint, and the health care body carries the body part, so that a health care effect is performed to the user when the health care body holds an acupoint work piece thereon; positioning the body part on the health care body so that the health care body and the body part have a first relative positional relationship therebetween **1120**; and providing a position adjustment device for maintaining a second positional relationship between the health care body and the acupoint work piece, or the acupoint work piece and the acupoint to ensure the acupoint work piece to perform the health care work with a control parameter (**1160**).

(224) If the preceding methods involve medical acts, they may be classified as disease treating methods, which may be patent-ineligible concepts in Taiwan and China. When it is only related to a health care act, it may not relate to a treating method.

(225) The disclosure of the present invention may be well-plotted, but must have an end. The last highlight or ideal of the present invention is hereby proposed: in order to seek the health/happiness of all mankind to realize the touching ideals disclosed previously, it is necessary to enable every family/person to possess the software/hardware of the present invention even if their financial resources are relatively limited. Except waiting for the present invention to be commercialized in large scale to reduce costs, it is clear good hardware alone should be insufficient, and success can be alleged in the end only when every one may enjoy or receive physiotherapy or medical services like those provided by the reincarnation of Hua Tuo or Bian Que. AlphaGo developed by Deep Mind company defeated the world's chess king, and it simply relies on accumulating all the world's experiences in the same brain and then making decisions. For another example, if an aircraft has an accident, it must be reported to the manufacturer to repair the design to prevent the same accident in future. If this spirit is upheld, and the previous wisdom since ancient times will first be collected and then organized by the outstanding people today, followed by the continuous true feedback on therapeutic effects of the acupoint therapy from the general public, why should it be worried about that Hua Tuo or Bian Que cannot reincarnate?

(226) For purposes of the preceding paragraph, please refer to FIG. **10B** showing an embodiment of health care system **1200** of the present invention including health care body **1210** having micro computer **1215** connected to cloud database **1400** and service center **1500** through an internet. Micro computer **1215** includes/configures central processing unit **1220**, memory **1230**, screen **1270**, keyboard/mouse **1280**, microphone **1290**, and lens **1300**. Since their mutual connection and configuration are common technologies, it will not be detailed here. It also makes no difference whether screen **1270** is touch type or non-touch type. Memory **1230** can store the application software required for interaction between the user and cloud database **1400** and service center **1500**, such as symptom treatment module **1240** for clicking or entering the current discomfort symptoms, to retrieve from cloud database **1400** which treatment scheme or acupoint(s) to receive the health care work. It can also be personal health care history record module **1250** recording a user's personal health care history. Certainly, it can also be feedback/report module **1260** for the feedback/report of the user's satisfaction or problems encountered in use after the health care work suggested by cloud database **1400**. Modules **1240**, **1250**, **1260** and other modules related to health care work can be individual or separate modules, or sub-modules integrated in the same program.

(227) Through cloud database **1400**, the user can search and confirm the symptoms or their treatment methods by screen **1270** and/or keyboard/mouse **1280**. Through service center **1500**, the user can consult, inquire about the symptom and/or confirm the act related to acupuncture or moxibustion by microphone **1290**/lens **1300**. Certainly, health care system **1200** must be confirmed by the national health authority as a doctor or qualified to perform a medical practice before performing needle injection. As mentioned, through collection of acupuncture or moxibustion information available so far, and research, confirmation, deep learning and constant user feedback, cloud database **1400** cooperated with service center **1500** stationed with traditional Chinese

physicians should be able to provide extremely amazing health care or medical effects. As there is no ending for learning, the present invention's disclosure is just a good start, and more efforts are still needed for Hua Tuo or Bian Que to be truly reincarnated. Control module **1600** stores, with supports from central processing unit **1220**, coordinates the health care device or the health care body previously disclosed to perform various relevant health care works.

(228) The first chapter, Nine Needles and Twelve Originals, of Lingshu of the Yellow Emperor's Neijing starts with “The Yellow Emperor asked Qibo: I have myriad thousands of people, and collect therefrom rents and taxes; I want to use micro-needles to smoothen their meridians, adjust their blood/qi, and flourish the meeting points of incoming and outgoing paths without drugs or medical appliances. What I want is that can be passed on to future generations, must be clear standards, will not be overturned, will be everlasting, is easy to use but difficult to forget, is classical but separated into chapters, distinguishes inner and outer symptoms, systemizes with beginning and ending, and is concretized into acupuncture scriptures. Is this something possible?” As the acupuncture effects have been worldwide confirmed, the present invention is to ignite the strong hope of welcoming incarnation of Hua Tuo or Bian Que. Through the joint participation of all human beings, we may welcome the return of Hua Tuo or Bian Que as soon as possible.

(229) Health care system (**1200**) is summarized as follows. Specifically, it includes health care body (**1210**) for health-caring a user, wherein the user has a body part having an acupoint; positioning medium (**524, 680, 714, 804**) configured on health care body (**1210**) and securing a positional relationship between the body part and the health care body; an acupoint work piece configured on the health care body and performing a health care work onto the user through the acupoint; and computer device (**1215**) configured on the health care body and controlling and/or monitoring the acupoint work piece to perform the health care work.

(230) In accordance with preceding health care system, the health care system further includes cloud database (**1400**) connected to computer device (**1215**) through an internet, and allowing the user to access therefrom knowledge and healthcare scheme or medical treatment related to acupuncture/moxibustion.

(231) In accordance with preceding health care system, computer device (**1215**) further includes symptom treatment module **1240** allowing the user to click or enter a current discomfort symptom, by which cloud database (**1400**) provides a specific treatment scheme or a specific acupoint to receive the health care work.

(232) In accordance with preceding health care system, computer device (**1215**) further includes feedback/report module (**1260**) allowing the user to feedback/report user satisfaction or problems encountered in use to cloud database (**1400**) after the health care work on a specific acupoint suggested by cloud database (**1400**).

(233) In accordance with preceding health care system, computer device (**1215**) further includes screen (**1270**) and keyboard/mouse (**1280**) allowing the user to search and confirm a symptom or its treatment method through cloud database (**1400**).

(234) In accordance with preceding health care system, the health care system further includes service center (**1500**) connected to computer device (**1215**) through an internet, and providing the user with a consultation related to acupuncture/moxibustion, or a confirmation of the user's own choice of a medical-level act.

(235) In accordance with preceding health care system, computer device (**1215**) further includes microphone (**1290**) and lens (**1300**) for a consultation by, an inquisition on the symptom of, or a confirmation from the user of an act related to acupuncture or moxibustion via service center (**1500**).

(236) In accordance with preceding health care system, computer device (**1215**) includes screen (**1270**) of a touch type or non-touch type.

(237) In accordance with preceding health care system, computer device (**1215**) further includes personal health care history record module (**1250**) recording a user's personal health care history.

(238) In accordance with preceding health care system, computer device (1215) further includes control module (1600) coordinating the health care body and/or the acupoint work piece to perform the health care work.

(239) In accordance with preceding health care system, the health care system further includes a position adjustment device configured between health care body (1140) and the acupoint work piece, so that the acupoint work piece and health care body (1140) have a relative positional relationship.

(240) From another aspect, health care system 1200 using an acupoint work piece to perform a health care work on a user having a body part having an acupoint, includes: health care body (1210) carrying the body part; positioning medium (524, 680, 714, 804) configured on the health care body and positioning the body part on the health care body so that the health care body and the body part have a first relative positional relationship therebetween; and computer device (1215) configured on the health care body, and controlling/monitoring the acupoint work piece to perform the health care work under a second positional relationship maintained between the health care body and the acupoint work piece, or the acupoint work piece and the acupoint.

(241) From yet another aspect, health care system (1200) includes: health care body (1210) performing a healthcare work on a user, wherein the user has a body part having an acupoint, and the health care body supports thereon the body part for the health care work when the health care body holds an acupoint work piece thereon; positioning medium (524, 680, 714, 804) configured on the health care body and positioning the body part on the health care body so that the health care body and the body part have a first specific positional relationship therebetween; and computer device (1215) configured on the health care body, and controlling/monitoring the acupoint work piece to perform the health care work under a second positional relationship maintained between the health care body and the acupoint work piece, or the acupoint work piece and the acupoint.

(242) Although the possible implementations of each of the above-mentioned embodiments have not been listed in detail, there are a lot of mutual references or substitutions among the various embodiments, and thus, an embodiment is likely to be a reference or alternative schemes for other embodiments. Because the content of this case is already quite long, it will not be detailed here in order to save the burden of all parties.

(243) In summary, it can be understood by those skilled in the art that a variety of modifications and variations may be made to the present invention without departing from the spirit or scope of the present invention defined in the appended claims, and their equivalents.

Claims

1. A health care device, comprising: a health care body having a first carrying base plate and a second carrying base plate for carrying a body part of a user, wherein the body part is an upper limb including an upper arm and a lower arm, or a lower limb including a thigh and a shank, the first and second carrying base plates are respectively configured to carry thereon the upper and lower arms or the thigh and the shank, wherein dimensions of the first and second base plates are combined to define a total length adapted to a length of the body part, and the body part has an acupoint; a first positioning mechanism slidably configured on the health care body, positioning the body part on the health care body, and securing a first specific positional relationship between the health care body and the body part; an acupoint work piece having a second specific positional relationship with the acupoint; and a work piece holder having: a first end connected to the health care body, or the first positioning mechanism; and a second end holding the acupoint work piece under the second specific positional relationship, and enabling the acupoint work piece to engage in a health care work towards the user through the acupoint under the first and second positional relationships.
2. The health care device as claimed in claim 1, wherein: the first carrying base plate has a third

end and a fourth end, and the second carrying base plate has a fifth end and a sixth end; the first positioning mechanism includes a first pair of positioning blocks respectively configured on two sides of the third end of the first carrying base plate; and the body part has a first protruding feature, and inner surfaces of the first pair of positioning blocks respectively have at least one recess configured to correspond to the first protruding feature to provide the first specific positional relationship.

3. The health care device as claimed in claim 2, wherein: the health care body further includes a length adjustment device; the fourth end and the fifth end dispose therebetween the length adjustment device; the length adjustment device adjusts a distance between the first carrying base plate and the second carrying base plate to adjust an apparent length of the health care body to be adapted to a length of the body part; and the third end has a pair of recesses respectively sliding therewith the first pair of positioning blocks to adjust a distance between the first pair of positioning blocks to be adapted to a width of the body part.

4. The health care device as claimed in claim 3, wherein each of the first pair of positioning blocks has a pair of lugs, the first carrying base plate has a pair of side grooves respectively communicating with the pair of recesses, the first pair of positioning blocks slide in the pair of side grooves via the lugs, each of the fourth end and the fifth end has a central groove and a plurality of first pin holes, and the length adjustment device includes: a linking plate, two sides of which are respectively configured in the central grooves; a plurality of second pin holes respectively configured on the two sides of the linking plate and corresponding to the plurality of first pin holes; and a plurality of pins respectively inserted into the plurality of first pin holes of the fourth end and the fifth end, and correspondingly into the plurality of second pin holes of the linking plate to fix the first carrying base plate, the second carrying base plate and the length adjustment device.

5. The health care device as claimed in claim 2, wherein each of the fourth end and the fifth end has an arc convex, a middle groove and a first sliding hole, and the length adjustment device includes: a length adjustment plate configured between the fourth end and the fifth end and has a second sliding hole; a side piece inserted through the second sliding hole and the first sliding holes, and slidably and planarly combining the first carrying base plate, the second carrying base plate and the length adjustment plate together; and a trapezoidal piece configured in the middle grooves and having a pair of side bevels, wherein the trapezoidal piece adjusts an apparent length of the health care body by an interaction between the pair of side bevels and the arc convexes.

6. The health care device as claimed in claim 5, wherein: the length adjustment plate further includes a screw hole, a plurality of positioning pin holes and a rotatable screw rod for operating the trapezoidal piece so as to adjust a contact position between the pair of side bevels of the trapezoidal piece and the arc convexes to adjust the total length to define a total virtual length of the first carrying base plate, the second carrying base plate and the length adjustment plate; or the trapezoidal piece has a bottom hole and the rotatable screw rod has an end, and the end is configured and freely rotatable in the bottom hole.

7. The health care device as claimed in claim 5, wherein: the length adjustment plate further includes a central recess for positioning a second protruding feature of the body part; and the second protruding feature is a protrusion of a kneecap of the user when the user lies prone.

8. The health care device as claimed in claim 5, further comprising a second pair of positioning blocks respectively and slidably configured on two sides of the length adjustment device for positioning a third protruding feature of the body part.

9. The health care device as claimed in claim 5, further comprising a third positioning block slidably configured on one side of the sixth end of the second carrying base plate for positioning a fourth protruding feature of the body part.

10. The health care device as claimed in claim 2, further comprising a second pair of positioning blocks respectively and slidably configured on two sides of the sixth end of the second carrying base plate for positioning a second protruding feature of the body part.

11. The health care device as claimed in claim 10, wherein the first carrying base plate and the second carrying base plate are used for carrying the lower arm, wherein: the sixth end of the second carrying base plate has an elbow containing recess for containing a most prominent part of an elbow of an ulna; each of the sixth end of the second carrying base plate and the second pair of positioning blocks has a groove positioning therein a respective left or lower side of prominent muscles of the lower arm when the lower arm is kept laterally upright; the third end of the first carrying base plate has a recess configured to rest thereon an abductor muscle of a little finger of the user when the lower arm is kept laterally upright, and freely resting thereon a wrist and a palm of the user when an inner (or yin) side of the lower arm is laterally placed on the first carrying base plate; the first pair of positioning blocks are configured with a cavity and a groove, wherein when the palm is upright, the cavity is configured to contain a short abductor muscle of a thumb of the palm therein and the groove allows the palm to stretch therein; the first pair of positioning blocks are used for containing a carpal protrusion of a radius of the lower arm and a carpal protrusion of the ulna of the lower arm of the user respectively; and the second pair of positioning blocks are used for containing a most protruding sesamoid at an ulna side of an elbow end of a humerus of the user.

12. The health care device as claimed in claim 11, further comprising a third carrying base plate configured to carry thereon the upper arm, and including a first carrier plate and a second carrier plate, wherein the first carrier plate is connected to the second carrying base plate, the second carrier plate has a semi-cylindrical part urging against an axilla of the user, and the second carrier plate has a guiding sheet conforming to a shoulder end of the upper arm of the user.

13. The health care device as claimed in claim 10, wherein the first carrying base plate and the second carrying base plate are respectively used for carrying the shank and the thigh, wherein: the first carrying base plate is configured with a central concave, wherein when the user lies prone, the central concave is configured to contain an outer protrusion of a tibia of the shank, and when the user lies supine, the central concave contains a calf of the shank; the third end of the first carrying base plate has a recess containing therein a calcaneal tendon and a calcaneus when the user lies prone; the sixth end of the second carrying base plate has a recess containing muscles connecting between buttocks and the thigh, and a stop abutting against a bottom edge of a groin of the user; the first pair of positioning blocks are respectively used for containing a lateral malleolus and a medial malleolus of the user; the second pair of positioning blocks are respectively used for containing a knee tuberosity of the tibia and a knee tuberosity of a femur of the user; and the third positioning block is used for containing a trochanter major protrusion at a buttock end of the femur of the user.

14. The health care device as claimed in claim 2, further comprising a heel height adjustment medium configured on the third end of the first carrying base plate for being adapted to a specific heel height of the user.

15. A health care device for holding an acupoint work piece thereon to engage in a health care work onto a user, wherein the user has a body part including an acupoint, the body part is an upper limb including an upper arm and a lower arm, or a lower limb including a thigh and a shank, and the health care device comprises: a health care body having a carrying platform, wherein the carrying platform includes a first base plate and a second base plate respectively configured to carry thereon the upper and lower arms or the thigh and the shank, and dimensions of the first and second base plates are combined to define a total length adapted to a length of the body part; a pair of positioning blocks slidably configured on the carrying platform, and configured to position the body part on the carrying platform and cause the health care body and the body part to have a first specific positional relationship therebetween; and a work piece holder connected to the carrying platform or the pair of positioning blocks, holding the acupoint work piece on the carrying platform or the pair of positioning blocks, securing the acupoint work piece and the acupoint to have a second specific positional relationship therebetween, and ensuring the acupoint work piece to

engage in the health care work onto the user through the acupoint under the first specific positional relationship and the second specific positional relationship.

16. The health care device as claimed in claim 15, further comprising a length adjustment device mounted on the health care body and used to adjust an apparent length of the total length of the carrying platform in response to a length of the body part.

17. The health care device as claimed in claim 15, wherein the carrying platform has a pair of recesses respectively mounting thereon the pair of positioning blocks to have a mutual distance in response to a width of the body part.
