

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397583
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Cai; Xiangyang

Wheel rotation speed measurement assembly and wheel hub driving system

Abstract

A wheel rotation speed measurement assembly and a wheel hub driving system. The assembly includes a wheel hub bearer, a synchronous shaft and a compiler. The wheel hub bearer has a central shaft and an outer ring. The central shaft is hollow with an inner cavity and forms a torsion-resistant connection with a vehicle suspension. The outer ring can be driven to rotate relative to the central shaft, and forms a torsion-resistant connection with the wheel hub. The synchronous shaft is arranged in the inner cavity and has an end that is close to the first end has a torsion-resistant connection with the outer ring. The compiler is mounted at an end of the synchronous shaft away from the first end. The assembly has a simple structure and can measure the wheel rotation speed directly. Rotation speed output by this compact wheel hub driving system can be accurately measured.

Inventors:	Cai; Xiangyang (Kunshan, CN)
Applicant:	Schaeffler Technologies AG & Co. KG (Herzogenaurach, DE)
Family ID:	1000008782484
Assignee:	Schaeffler Technologies AG & Co. KG (Herzogenaurach, DE)
Appl. No.:	18/018299
Filed (or PCT Filed):	July 16, 2021
PCT No.:	PCT/CN2021/106847
PCT Pub. No.:	WO2022/028231
PCT Pub. Date:	February 10, 2022

Prior Publication Data

Document Identifier

US 20230294454 A1

Publication Date

Sep. 21, 2023

Foreign Application Priority Data

CN

202010788769.X

Aug. 07, 2020

Publication Classification

Int. Cl.: G01P3/44 (20060101); B60B27/00 (20060101); B60K7/00 (20060101)

U.S. Cl.:

CPC B60B27/0068 (20130101); B60B27/001 (20130101); G01P3/44 (20130101);
B60B27/0015 (20130101); B60K7/0007 (20130101); B60K2007/0038 (20130101)

Field of Classification Search

CPC: B60B (27/0068)

USPC: 73/115.08

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3934685	12/1975	Jovick	N/A	N/A
6135571	12/1999	Mizukoshi	301/124.1	F16C 33/768

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104081073	12/2016	CN	N/A
104385900	12/2016	CN	N/A
209870094	12/2018	CN	N/A
2659450	12/1989	FR	N/A
2795145	12/1999	FR	F16D 41/064
1163039	12/1968	GB	N/A
2020066834	12/2019	WO	N/A

OTHER PUBLICATIONS

Sueshige et al. Machine Translation of FR-2795145-A1. Published Dec. 2000. Accessed Nov. 2024. (Year: 2000). cited by examiner

Primary Examiner: Lindsay, Jr.; Walter L

Assistant Examiner: Fadul; Philip T

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the U.S. National Phase of PCT Appln. No. PCT/CN2021/106847, filed Jul. 16, 2021, which claims the benefit of Chinese Patent Appln. No. 202010788769.X, filed Aug. 7, 2020, the entire disclosures of which are incorporated by reference herein.

TECHNICAL FIELD

(2) The disclosure relates to a wheel hub driving system, and also relates to a wheel rotation speed measurement assembly in the wheel hub driving system for measuring wheel rotation speed.

BACKGROUND

(3) Wheel hub driving is a way to drive a vehicle electrically. Generally, the wheel hub driving system integrates both a drive assembly and a brake assembly on an inner side of a wheel rim, wherein the drive assembly comprises a drive motor, a gear reducer and a wheel hub bearer.

(4) FIG. 1 is a schematic diagram of a possible wheel hub driving system comprising a drive motor W1, a reducer W2, a wheel hub bearer W3 and a brake W4. The torque from the drive motor W1 is transmitted to the wheel hub bearer W3 through the reducer W2, and a flange portion of an outer ring of the wheel hub bearer W3 is connected with the wheel hub through a bolt W5 so as to further transmit the torque to a wheel. The rotation speed of the wheel rim is the same as that of the wheel.

(5) Due to the limited space between the wheel hub driving system and the wheel rim, it is difficult to arrange a sensor to directly measure the wheel rotation speed. Therefore, in general, the wheel rotation speed can generally only be measured indirectly. For example, the wheel rotation speed is calculated by measuring the rotation speed of the drive motor W1 with an angle sensor.

(6) Indirect measurement may present problems such as low signal accuracy and delay in signal transmission, and thus, there may be a large error between the obtained wheel rotation speed and the actual rotation speed, which poses a threat to the safety of the wheel hub driving system.

SUMMARY

(7) The objective of the present disclosure is to provide a wheel rotation speed measurement assembly and a wheel hub driving system in order to overcome or at least alleviate the above-mentioned shortcomings existing in the prior art.

(8) According to a first aspect of the present disclosure, a wheel rotation speed measurement assembly is provided, which is used for measuring the rotation speed of a wheel driven by a wheel hub driving system, the wheel rotation speed measurement assembly comprising a wheel hub bearer, a synchronous shaft and a compiler, wherein the wheel hub bearer comprises a central shaft and an outer ring; the central shaft is a hollow shaft having a through inner cavity in an axial direction, and the central shaft is used for forming a rotationally-fixed connection with a vehicle suspension; the outer ring is sleeved at a first end of the central shaft, the outer ring can be driven by an electric motor of the wheel hub driving system to rotate relative to the central shaft, and the outer ring is used for forming a rotationally-fixed connection with a wheel hub; the synchronous shaft is arranged in the inner cavity, and an end of the synchronous shaft that is close to the first end has a rotationally-fixed connection with the outer ring; and the compiler is mounted at an end of the synchronous shaft that is away from the first end, and the compiler can be identified by a sensor so as to measure the rotation speed of the wheel.

(9) In at least one embodiment, the measurement assembly further comprises a synchronous cover; the synchronous cover is mounted at an end of the outer ring in such a manner that it is rotationally-fixed relative to the outer ring, and the synchronous shaft has a rotationally-fixed connection with the synchronous cover.

- (10) In at least one embodiment, a side of the synchronous cover facing the inner cavity is formed with a connecting groove, an end of the synchronous shaft facing the synchronous cover forms a connecting portion, and the connecting portion extends into the connecting groove, and thus the synchronous cover together with the synchronous shaft can rotate relative to the central shaft.
- (11) In at least one embodiment, the measurement assembly further comprises a bracket, the bracket is provided with a center hole and is of an annular shape; the bracket is arranged in the inner cavity and has a rotationally-fixed connection with the central shaft, the synchronous shaft passes through the center hole, and the synchronous shaft is supported by the bracket in a radial direction.
- (12) In at least one embodiment, bearings are arranged between the synchronous shaft and an inner circumferential wall of the bracket.
- (13) In at least one embodiment, the synchronous shaft is provided with shaft shoulders, the inner circumferential wall of the bracket is provided with annular positioning portions which are radially and outwardly recessed, and the bearings are arranged between the shaft shoulders and the positioning portions.
- (14) In at least one embodiment, two bearings are provided, and the two bearings are arranged at two ends of the bracket in the axial direction.
- (15) In at least one embodiment, the bearings are sliding bearings lubricated with grease or having a self-lubricating function.
- (16) In at least one embodiment, the measurement assembly further comprises a tail cover, and the tail cover is mounted on an end of the central shaft that is away from the first end so as to close the inner cavity.
- (17) According to a second aspect of the disclosure, a wheel hub driving system is provided, comprising a drive motor and a reducer, and also comprising a wheel rotation speed measurement assembly according to the present disclosure.
- (18) A rotor of the drive motor has a rotationally-fixed connection with an input end of the reducer, and the outer ring of the wheel hub bearer of the wheel rotation speed measurement assembly has a rotationally-fixed connection with an output end of the reducer.
- (19) The wheel rotation speed measurement assembly according to the present disclosure has a simple structure and is capable of measuring the wheel rotation speed directly.
- (20) Rotation speed output by the wheel hub driving system according to the present disclosure can be accurately measured, and the wheel hub driving system is compact in size.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of a possible wheel hub driving system.
- (2) FIG. 2 is a sectional view of a wheel rotation speed measurement assembly in an axial direction according to one embodiment of the present disclosure.
- (3) FIG. 3 is a schematic diagram of a synchronous cover of a wheel rotation speed measurement assembly according to one embodiment of the present disclosure.
- (4) FIG. 4 is a schematic diagram of a synchronous shaft of a wheel rotation speed measurement assembly according to one embodiment of the present disclosure.
- (5) FIG. 5 is a schematic diagram of a bracket of a wheel rotation speed measurement assembly according to one embodiment of the present disclosure.
- (6) FIG. 6 is a sectional view of FIG. 5 along an axial direction.

DETAILED DESCRIPTION

- (7) Exemplary embodiments of the present disclosure will be described below with reference to the drawings. It should be understood that the specific description is only used to teach those skilled in

the art how to implement the disclosure and is neither intended to be exhaustive of all possible variations of the present disclosure nor to limit the scope of the present disclosure.

(8) Unless otherwise specified, referring to FIG. 2, A represents an axial direction of a wheel rotation speed measurement assembly, and the axial direction A is consistent with the axial direction of a wheel hub bearer B in the wheel rotation speed measurement assembly; and R represents a radial direction of the wheel rotation speed measurement assembly, and the radial direction R is consistent with the radial direction of the wheel hub bearer B in the wheel rotation speed measurement assembly.

(9) The wheel rotation speed measurement assembly according to the present disclosure will be described with reference to FIGS. 2 to 6. The wheel rotation speed measurement assembly is a part of a wheel hub driving system and is used for measuring the rotation speed of a wheel driven by the wheel hub driving system.

(10) In this embodiment, the wheel rotation speed measurement assembly comprises a wheel hub bearer B, a synchronous shaft **10**, a synchronous cover **20**, a compiler **30**, a bracket **40**, a tail cover **50** and bearings **60**.

(11) The wheel hub bearer B comprises a central shaft B1, an outer ring B2 and rolling bodies arranged between the central shaft B1 and the outer ring B2.

(12) The central shaft B1 is a hollow shaft penetrating in the axial direction A. The central shaft B1 is fixed to a housing of the wheel hub driving system, and the housing is fixed to a vehicle suspension, or in other words, the central shaft B1 has a torsion-resistant (rotationally-fixed) connection with the vehicle suspension.

(13) The outer ring B2 is sleeved at one end of the central shaft B1 and can rotate relative to the central shaft B1. The outer ring B2 is used for connecting a wheel hub and an output end of a reducer (not shown) so that the torque from a drive motor (not shown) of the wheel hub driving system can be transmitted to a wheel hub through the reducer and the outer ring B2 in sequence. In the axial direction A, the length of the outer ring B2 is smaller than that of the central shaft B1. For the convenience of description below, the end of the central shaft B1 where the outer ring B2 is located is referred to as a first end of the central shaft B1.

(14) In this embodiment, an outer circumference of the outer ring B2 that is near the first end in the axial direction A has a flange portion protruding outward in the radial direction R, and the wheel hub (not shown) can be connected to the flange portion by a bolt W5.

(15) Preferably, in order to facilitate the axial positioning of the rolling body and the outer ring B2 on the central shaft B1, the outer diameter of a section of the central shaft B1 in the axial direction A and close to the first end is smaller than that of a section of the central shaft B1 away from the first end.

(16) The synchronous cover **20** is mounted at an end of the outer ring B2 that is close to the first end of the central shaft B1, and the synchronous cover **20** has a torsion-resistant connection with the outer ring B2 (for example, by means of a threaded connection or connecting in an interference fit manner).

(17) A side wall of the synchronous cover **20** facing the inner cavity B1a of the central shaft B1 is provided with a connecting stand **21** protruding toward the inner cavity B1a. A middle portion of the connecting stand **21** is recessed to form a connecting groove **211**. The connecting groove **211** is used for connecting the synchronous shaft **10** to be further described below.

(18) The synchronous cover **20** achieves the function of connecting the synchronous shaft **10** and the outer ring B2 as well as sealing the wheel hub bearer B at the end, thereby preventing pollutants such as splashing waste water from entering the interior of the wheel hub bearer B.

(19) The synchronous shaft **10** is arranged in the inner cavity B1a of the central shaft B1. One end of the synchronous shaft **10** and the synchronous cover **20** are connected at the connecting groove **211** in a torsion-resistant manner. Specifically, this end of the synchronous shaft **10** forms a connecting portion **11** having a special cross-sectional shape, and the cross-sectional shape of the

connecting portion **11** is the same as that of the connecting groove **211**.

(20) In this embodiment, the cross section of the connecting portion **11** that is perpendicular to the axial direction A is of a waist shape, which is formed, for example, by cutting the end of the synchronous shaft **10** along the axial direction. The distance between two plane portions of the waist shape is approximately equal to the width of the connecting groove **211**, so that the connecting portion **11** can extend into the connecting groove **211** and closely fit with the side wall of the connecting groove **211**. It should be understood that the cross sections of the connecting portion **11** and the connecting groove **211** may also have other shapes, and the present disclosure is not limited thereto.

(21) In this way, the synchronous cover **20** together with the synchronous shaft **10** can rotate synchronously, and because the synchronous cover **20** and the outer ring **B2** rotate synchronously, and the wheel and the outer ring **B2** rotate synchronously, the rotation of the synchronous shaft **10** is synchronous with the wheel.

(22) An end of the synchronous shaft **10** that is away from the connecting portion **11** is provided with the compiler **30**, which has a torsion-resistant connection with the synchronous shaft **10**. The above-mentioned end is away from the outer ring **B2** and a wheel rim, so there is enough space to arrange the compiler **30**, and a sensor for detecting a rotation signal of the compiler **30** can be conveniently arranged on the nearby vehicle suspension. The rotation speed of the compiler **30** measured by the sensor is the rotation speed of the wheel.

(23) In this embodiment, the compiler **30** is annular, an end of the synchronous shaft **10** that is away from the connecting portion **11** is provided with a compiler mounting portion **13** having a large outer diameter, and the annular compiler **30** is sleeved on the compiler mounting portion **13**. The compiler **30** is press-fitted with the compiler mounting portion **13** by means of interference fit or is mounted thereon by way of threaded connection.

(24) In order to stably support the synchronous shaft **10**, the bracket **40** is arranged in the inner cavity **B1a** and has a torsion-resistant connection with the central shaft **B1**.

(25) The bracket **40** is annular, and an outer circumferential wall of the bracket **40** forms an interference fit with an inner circumferential wall of the synchronous shaft **10** defining the inner cavity **B1a**.

(26) The synchronous shaft **10** passes through the center hole **41** of the bracket **40**, and the bearings **60** are arranged between the inner circumferential wall of the bracket **40** and the synchronous shaft **10**. Preferably, the bearings **60** are sliding bearings.

(27) In this embodiment, there are two bearings **60**, which are respectively arranged at two axial ends of the bracket **40**. An axial region of the synchronous shaft **10** for mounting the bearings **60** forms shaft shoulders **12**, and the inner circumferential wall of the bracket **40** forms two annular positioning portions **42** radially and outwardly recessed at both axial ends. Inner rings of the bearings **60** are mounted on the shaft shoulders **12**, and outer rings of the bearings **60** are mounted on the positioning portions **42**.

(28) Preferably, in order to facilitate the mounting of the bracket **40**, a portion of the central shaft **B1** that is away from the first end has a larger inner diameter, that is, a portion of the inner cavity **B1a** where the bracket **40** is mounted has a larger inner diameter, so that the inner cavity **B1a** forms a shape having a big end and a small end.

(29) The end of the central shaft **B1** that is away from the first end is provided with the tail cover **50**, and the tail cover **50** is used for closing the inner cavity **B1a** at this end, thereby preventing pollutants such as splashing waste water from entering the inner cavity **B1a**, or even further passing through the inner cavity **B1a** to flow to the first end of the central shaft **B1** and enter the interior of the wheel hub bearer **B**. In this embodiment, the tail cover **50** is embedded in the inner circumferential wall of the central shaft **B1**.

(30) It is inconvenient to replenish lubricant to the bearings **60** as the inner cavity **B1a** is closed by two covers, so the bearings **60** are preferably lubricated with grease, or are preferably those having

a self-lubricating function.

(31) It should be understood that the sensor for sensing the signal of the compiler **30** can be arranged outside the central shaft **B1**, for example, being mounted on the vehicle suspension. This sensor may or may not be a part of the wheel rotation speed measurement assembly of the present application.

(32) The disclosure has at least one of the following advantages: (i) The wheel rotation speed measurement assembly according to the present disclosure is capable of directly measuring the rotation speed of the wheel, and the acquired signal of the rotation speed is direct and reliable. (ii) The compiler **30** is accommodated in the closed inner cavity **B1a** and is not susceptible to contamination and damage. (iii) The compiler **30** may be a conventional compiler for the sensor for measuring the rotation speed. (iv) The wheel rotation speed measurement assembly according to the present disclosure effectively utilizes an internal space of the wheel hub driving system and does not need to occupy an extra space of the original wheel hub driving system.

(33) Naturally, the present disclosure is not limited to the above-mentioned embodiments, and a person skilled in the art could make various modifications to the above-mentioned embodiments of the present disclosure under the teaching of the present disclosure without departing from the scope of the present disclosure.

LIST OF REFERENCE NUMERALS

(34) **W1** Drive motor; **W2** Reducer; **W3** Wheel hub bearer; **W4** Brake; **W5** Bolt; **B** Wheel hub bearer; **B1** Central shaft; **B1a** Inner cavity; **B2** Outer ring; **10** Synchronous shaft; **11** Connecting portion; **12** Shoulder; **13** Compiler mounting portion; **20** Synchronous cover; **21** Connecting stand; **211** Connecting groove; **30** Compiler; **40** Bracket; **41** Center hole; **42** Positioning portion; **50** Tail cover; **60** Bearing.

Claims

1. A wheel rotation speed measurement assembly for measurement of a rotation speed of a wheel driven by a wheel hub driving system, the wheel rotation speed measurement assembly comprising: a wheel hub bearer; a synchronous shaft; a compiler; the wheel hub bearer comprises a central shaft and an outer ring, the central shaft is a hollow shaft having a penetrating inner cavity in an axial direction, the central shaft is used for forming a rotationally-fixed connection with a vehicle suspension; the outer ring is sleeved at a first end of the central shaft, the outer ring is driveable by an electric motor of the wheel hub driving system to rotate relative to the central shaft, the outer ring forms a rotationally-fixed connection with a wheel hub; the synchronous shaft is arranged in the inner cavity, an end of the synchronous shaft that is closer to the first end has a rotationally-fixed connection with the outer ring; and the compiler is mounted at an end of the synchronous shaft that is away from the first end, and the compiler is detected by a sensor in order to measure the rotation speed of the wheel.

2. The wheel rotation speed measurement assembly according to claim 1, further comprising a synchronous cover mounted at an end of the outer ring rotationally-fixed relative to the outer ring, and the synchronous shaft has a rotationally-fixed connection with the synchronous cover.

3. The wheel rotation speed measurement assembly according to claim 2, wherein, a side of the synchronous cover facing the inner cavity is formed with a connecting groove; an end of the synchronous shaft facing the synchronous cover forms a connecting portion; and the connecting portion extends into the connecting groove such that the synchronous cover together with the synchronous shaft are rotatable relative to the central shaft.

4. The wheel rotation speed measurement assembly according to claim 1, further comprising a bracket having a center hole therein and having an annular shape, the bracket is arranged in the inner cavity and has a rotationally-fixed connection with the central shaft, the synchronous shaft passes through the center hole and the synchronous shaft is supported by the bracket in a radial

direction.

5. The wheel rotation speed measurement assembly according to claim 4, wherein a bearing is arranged between the synchronous shaft and an inner circumferential wall of the bracket.

6. The wheel rotation speed measurement assembly according to claim 5, wherein the synchronous shaft includes shaft shoulders; the inner circumferential wall of the bracket is provided with annular positioning portions which are radially and outwardly recessed; and the bearing is arranged between the shaft shoulders and the positioning portion.

7. The wheel rotation speed measurement assembly according to claim 6, wherein two of the bearings are provided; and the two bearings are arranged at two ends of the bracket in the axial direction.

8. The wheel rotation speed measurement assembly according to claim 7, wherein the bearings are sliding bearings lubricated with grease or are self-lubricating.

9. The wheel rotation speed measurement assembly according to claim 1, further comprising a tail cover mounted on an end of the central shaft that is away from the first end that closes the inner cavity.

10. A wheel hub driving system, comprising: a drive motor, a reducer, and the wheel rotation speed measurement assembly according to claim 1, and a rotor of the drive motor has a rotationally-fixed connection with an input end of the reducer, and the outer ring of the wheel hub bearer of the wheel rotation speed measurement assembly has a rotationally-fixed connection with an output end of the reducer.

11. A wheel rotation speed measurement assembly for measurement of a rotation speed of a wheel driven by a wheel hub driving system, the wheel rotation speed measurement assembly comprising: a wheel hub bearer including a central shaft and an outer ring, the central shaft is a hollow shaft having a penetrating inner cavity that extends in an axial direction, the central shaft is configured to form a rotationally-fixed connection with a vehicle suspension; the outer ring is rotatably mounted at a first end of the central shaft, the outer ring is driveable by an electric motor of the wheel hub driving system to rotate relative to the central shaft and forms a rotationally-fixed connection with a wheel hub; a synchronous shaft arranged in the inner cavity, an end of the synchronous shaft that is closer to the first end has a rotationally-fixed connection with the outer ring; a compiler mounted at an end of the synchronous shaft that is away from the first end, and the compiler is configured to be detected in order to measure the rotation speed of the wheel.

12. The wheel rotation speed measurement assembly according to claim 11, further comprising a synchronous cover mounted at an end of the outer ring rotationally fixed relative to the outer ring, and the synchronous shaft has a rotationally-fixed connection with the synchronous cover.

13. The wheel rotation speed measurement assembly according to claim 12, wherein a side of the synchronous cover facing the inner cavity is formed with a connecting groove, an end of the synchronous shaft facing the synchronous cover includes a connecting portion, and the connecting portion extends into the connecting groove such that the synchronous cover together with the synchronous shaft are rotatable relative to the central shaft.

14. The wheel rotation speed measurement assembly according to claim 11, further comprising a bracket having a center hole therein and having an annular shape, the bracket is arranged in the inner cavity and has a rotationally-fixed connection with the central shaft, the synchronous shaft passes through the center hole and the synchronous shaft is supported by the bracket in a radial direction.

15. The wheel rotation speed measurement assembly according to claim 14, wherein a bearing is arranged between the synchronous shaft and an inner circumferential wall of the bracket.

16. The wheel rotation speed measurement assembly according to claim 15, wherein the synchronous shaft includes shaft shoulders, the inner circumferential wall of the bracket is provided with annular positioning portions which are radially and outwardly recessed, and the bearing is arranged between the shaft shoulders and the positioning portion.

17. The wheel rotation speed measurement assembly according to claim 16, wherein two of the bearings are provided, and the two bearings are arranged at two ends of the bracket in the axial direction.

18. The wheel rotation speed measurement assembly according to claim 17, wherein the bearings are sliding bearings lubricated with grease or are self-lubricating.

19. The wheel rotation speed measurement assembly according to claim 11, further comprising a tail cover mounted on an end of the central shaft that faces away from the first end that closes the inner cavity.
