

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398810
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Malavasi; Stefano

Energy recovery valve system with spherical segment valve for controlling the fluid flow in a duct

Abstract

A valve system includes a hollow valve body provided with an inlet and an outlet which allow a flow of a fluid in the valve body; the valve body housing an obstructor rotatable, about a rotation axis, between a first position, in which the obstructor stops the passage of fluid between the inlet and the outlet, and a second position, in which the obstructor allows a passage of fluid between the inlet and the outlet. The valve system provides for rotation of the obstructor between the first position and the second position. A rotor is placed inside the valve body and is provided with a rotation shaft. The valve body also includes a housing having a recess with a spherical segment configuration on a lateral portion of the valve body, in which the obstructor is at least partially housed in the second position.

Inventors:	Malavasi; Stefano (Milan, IT)
Applicant:	Politecnico di Milano (Milan, IT)
Family ID:	1000008782466
Assignee:	Politecnico Di Milano (Milan, IT)
Appl. No.:	18/002718
Filed (or PCT Filed):	June 18, 2021
PCT No.:	PCT/IB2021/055385
PCT Pub. No.:	WO2021/260508
PCT Pub. Date:	December 30, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230341058 A1	Oct. 26, 2023

Foreign Application Priority Data

IT 102020000014983 Jun. 23, 2020

Publication Classification

Int. Cl.: F16K5/06 (20060101); F16K47/04 (20060101)

U.S. Cl.:

CPC F16K5/0605 (20130101); F16K5/06 (20130101); F16K47/04 (20130101);

Field of Classification Search

CPC: F16K (5/0605); F16K (5/06); F16K (47/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4540025	12/1984	Ledeen	251/127	F16K 47/045
5016857	12/1990	Bovee	251/304	F16K 5/0605
5251815	12/1992	Foye	236/51	F24F 13/06
5406979	12/1994	McHugh	137/557	A62C 35/68
6029702	12/1999	Leinen	251/121	F16K 47/045
6520209	12/2002	Lundqvist	251/127	F16K 47/045
7044436	12/2005	Corbetta	251/315.01	F16K 47/045
8156801	12/2011	Gabard-Cuoq	251/315.16	G01F 1/10
8678778	12/2013	Bosbach	417/423.1	F16K 5/10
9599252	12/2016	Malavasi	N/A	F16K 47/045
11747835	12/2022	Ham	137/561R	G05D 7/0635
2014/0346776	12/2013	Hum	N/A	N/A
2015/0041002	12/2014	Malavasi	137/560	F16K 5/0605
2022/0317709	12/2021	Hwan	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102 088 879	12/2019	KR	N/A
2013/121375	12/2012	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Sep. 13, 2021, issued in PCT Application No. PCT/IB2021/055385, filed Jun. 18, 2021. cited by applicant

Primary Examiner: Schneider; Craig M

Assistant Examiner: Ballman; Christopher D

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to an energy recovery valve system with spherical segment valve for controlling the fluid flow in a duct.

BACKGROUND ART

(2) Devices called “ball valves” are known which are used as shut-off devices in ducts, typically pressurized ones.

(3) Ball valves allow for selectively closing the duct with which they are associated, so as to prevent a fluid, such as a gas, a liquid or steam, from flowing therein. For this purpose, the ball valves known in the art comprise an obstructer with a substantially spherical shape, housed in a suitable seat and having a substantially cylindrical through hole.

(4) The spherical obstructer of the ball valves known in the art can be oriented with its through hole coaxial to the flow, thus allowing the fluid to flow through the valve; the spherical obstructer can also be oriented perpendicularly to the direction coaxial to the duct. The spherical obstructer of a ball valve can be selectively rotated, typically by an angle of 0° to 90° , by means of a suitable actuator, such as a knob operable by a user.

(5) The ball valves known in the art permit adjusting the fluid flow in a duct, in which the valve has been inserted, by rotating the obstructer by an angle smaller than 90° , so as to obstruct only a part of the free cross-section of the duct. In this manner, the flow through the ball valve is reduced, but not completely prevented.

(6) The flow adjustment effectiveness of the ball valves known in the art is nevertheless poor. The adjustment of the flow through the valve is inaccurate, and it is difficult to precisely determine the quantity of gas or liquid actually flowing through a partially closed ball valve. Also, a known ball valve, when partially closed in order to adjust the flow of a fluid, introduces huge local energy dissipations within the fluid itself. Such dissipations lead to a reduction in the average velocity of the fluid, resulting in a reduced flow rate, but they typically bring no energetic benefit to the system in which the ball valve is inserted.

(7) International patent application WO2013/121375-A1 by the present Applicant describes, with reference to claim 1, a fluid flow control valve comprising a housing and a spherical obstructer comprising a through hole, wherein said spherical obstructer is inserted in said housing and is adapted to rotate therein about an axis of rotation between a first position, in which said through hole is substantially coaxial to said control valve to allow the passage of a fluid, and a second position, in which said through hole is substantially transversal to said control valve to prevent the passage of a fluid, characterized in that said control valve further comprises a rotor within said through hole, wherein said rotor is adapted to rotate in a continuous manner under the action of a fluid flowing through said control valve, rotating about a second axis of rotation substantially coinciding with said axis of rotation of said spherical obstructer.

(8) The spherical obstructer comprises two diametrically opposite spherical-segment parts, and a central hole through which the fluid can flow when the valve is partially or totally open.

(9) This known control valve permits recovering, due to the presence of the rotor, part of the energy that common control valves dissipate during their control action, and allows solving the problems set forth in said application. However, there is still room for improvement, and a few additional technical problems should be solved, in particular in order to broaden the field of use and application through improved behaviour and efficiency, e.g. for compressible fluids, while further reducing the manufacturing costs.

SUMMARY OF THE INVENTION

(10) It is therefore an object of the present invention to propose an energy recovery valve system with spherical segment valve for controlling the fluid flow in a duct, which represents an improvement over the prior art.

(11) The present invention relates to a valve system for controlling the fluid flow in a duct, which comprises a hemispherical or, more generally, spherical-segment obstructor, and a rotor shaped substantially as a turbine, which permits recovering part of the energy that prior-art control valves dissipate during their control action, and that would otherwise be dissipated and lost.

(12) Preferably, the axes of rotation of the obstructor and of the rotor overlap.

(13) Preferably, a deflector is also provided upstream of the valve system.

(14) Unlike the system described in the above-mentioned international patent application WO2013/121375-A1, the valve system according to the present invention does not use a spherical obstructor, but rather a hemispherical obstructor or, more generally, a spherical-segment obstructor.

(15) This difference brings substantial advantages, especially for a number of applications that require different characteristic curves of the flow coefficient of the control valve; moreover, this type of obstructor (hemispherical or spherical-segment type) gives the possibility of expanding the flow downstream of the obstructor, which is indispensable for working with compressible fluids.

(16) The use of a hemispherical or, more generally, spherical-segment obstructor reduces the torques required for moving the obstructor, so that smaller and less expensive actuators can be employed.

(17) Moreover, the valve system of the present invention ensures accurate control of the fluid flow, in particular also in partially open conditions.

(18) The present invention concerns a valve system for controlling the fluid flow in a duct, comprising: a valve body adapted to be inserted in an interruption of said duct, and provided with an inlet and an outlet for a flow of fluid in said duct, said valve body comprising a housing shaped substantially as a spherical segment upstream of the valve system with respect to the fluid flow on the side of said inlet, and a part opposite to said housing on the side of said outlet, an obstructor, placed inside said housing only upstream of the valve system with respect to the fluid flow, said obstructor having an axis of rotation and a spherical-segment outer contour, adapted to adhere to the spherical segment of said housing, actuation means adapted to rotate said obstructor from a first position, in which said duct is fully open, to a second position, in which said duct is fully closed, a rotor shaped substantially as a turbine, placed inside the valve body and provided with a rotation shaft substantially superposed on or parallel to the axis of rotation of the obstructor, said rotor being adapted to be rotated by said fluid flow.

(19) It is a particular object of the present invention to provide an energy recovery valve system with spherical segment valve for controlling the fluid flow in a duct as set out in the claims, which are an integral part of the present description.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Further objects and advantages of the present invention will become apparent from the following detailed description of an exemplary embodiment (and variants thereof) provided herein with reference to the annexed drawings, which are only supplied by way of non-limiting example, wherein:

(2) FIG. 1 schematically shows a sectional side view of a first embodiment of the valve system according to the present invention;

(3) FIG. 2 shows a perspective view of a first embodiment of a rotor of the valve system according to the present invention;

- (4) FIGS. **3**, **4** and **5** schematically show a sectional side view, orthogonal to that of FIG. **1**, of the first embodiment of the valve system for three different rotation angles of the obstructor, i.e. open, half-closed and closed;
- (5) FIGS. **6**, **7** and **8** schematically show a sectional side view, orthogonal to that of FIG. **1**, of a second embodiment of the valve system for three different rotation angles of the obstructor, i.e. open, half-closed and closed;
- (6) FIGS. **9**, **10** and **11** show further embodiments of the rotor of the control valve according to the present invention;
- (7) FIGS. **12**, **13** and **14** show further embodiments of the obstructor of the control valve according to the present invention;
- (8) FIG. **15** represents a further possible conformation of the control valve according to the present invention.
- (9) FIG. **16** represents a further possible position of the axis of rotation of the rotor of the control valve according to the present invention.
- (10) In the drawings, the same reference numerals and letters identify the same items or components.

DETAILED DESCRIPTION OF SOME EMBODIMENTS

- (11) FIG. **1** shows a schematic view of a valve system **101** according to the present invention. The valve system **101** comprises a substantially hollow valve body **102** provided with an inlet **103** and an outlet **104**, which allow a fluid to flow in a duct **105**. In operating conditions, the valve **101** can be mounted at a suitable interruption of the duct **105** included, for example, in a pressurized system.
- (12) The valve **101** comprises components that make it essentially a “spherical segment” valve. In fact, it comprises a housing **106** shaped substantially as a spherical segment that internally accommodates an obstructor **107**, which, when the valve is rotated, allows closing the valve **101** to stop the fluid flow between the inlet **103** and the outlet **104**, or partially or totally opening the valve to allow the fluid to flow.
- (13) As more clearly visible in FIGS. **3-8**, the obstructor **107** has a substantially hemispherical shape or, more generally, is shaped as a spherical segment, and comprises a through aperture **108**, the axis of which can be rotated into different positions.
- (14) For the valve system to operate correctly, the hemispherical or spherical-segment part **107** of the obstructor is placed only upstream of the valve system with respect to the fluid flow. The part of the valve body that comprises said outlet (**104**) downstream of the fluid flow is empty.
- (15) The conformation of the obstructor **107** shows an outer contour (relative to the conformation of the housing **106** of the valve body) shaped as a spherical segment, so that, during the opening and closing movements, it will perfectly adhere to the inner edge of the housing **106** of the valve body **102**. Preferably, the extension of the spherical segment is such as to ensure that the duct can be fully closed (FIG. **5**), and such as to not interfere with the flow when fully open (FIG. **3**).
- (16) The inner contour of the obstructor may have, for example, a linear shape as highlighted in FIGS. **3-8**, but other shapes are possible as well.
- (17) For example, with reference to FIGS. **12-14**, the obstructor may also have its inner contour shaped as a spherical segment: this will make it possible to, among other things, increase the dimensions of the turbine and hence the efficiency of the energy recovery system.
- (18) The obstructor **107** is connected to an actuator **109** that controls the rotation thereof as it is partially or totally opened or closed. The actuator may be either a mechanical one, e.g. a knob operable by a user, or else a pneumatic or electromechanical one, and can be turned to align the through hole **108** with the axis of the valve **101** (thereby allowing the fluid to flow through) or to arrange the through hole **108** substantially transversal to the axis of the valve **101** (thereby substantially preventing the fluid from flowing through).
- (19) The coupling between the housing **106** and the spherical obstructor **107** is such as to ensure

tightness when the obstructer is in the closed position, whether the fluid is a liquid, gas, steam or any other multi-phase fluid. In order to ensure such tightness, known elements and techniques can be used.

(20) Therefore, the obstructer **107** is adapted to rotate about the axis **110**.

(21) The valve system **101** further comprises a rotor **111** placed inside the through hole **108** and fixed to a shaft **112**, about which it is adapted to rotate. The shaft **112** is coaxial to the axis **110** or, in other embodiments described herein, at least substantially coaxial or parallel thereto, so that the obstructer **107** can be rotated in order to close the valve **101** without jeopardizing the operation of the rotor **111**. The rotor **111** is, in fact, adapted to rotate under the action of the fluid flowing through the valve **101** as will be described more in detail hereinafter.

(22) The shaft **112** has one end protruding from the spherical obstructer **107** and, in the non-limiting example of FIG. 1, also from the body of the valve **101**. The protruding end of the shaft **112** is mechanically connected, or directly connected in the example of FIG. 1, to a user apparatus **114**. The user apparatus **114** is adapted to use the mechanical power supplied by the shaft **112** due to the rotation of the rotor **111**. In this example, the actuator **109** is positioned at the axis **110** on the side of the valve **101** opposite to the user apparatus **114**.

(23) The user apparatus **114** may therefore be an electric generator, or a mechanical apparatus such as, for example, a fan. The user apparatus **114** may further comprise known transmission couplings or reducers, not shown for the sake of simplicity.

(24) FIG. 2 illustrates one possible embodiment of the rotor **111** fitted on the shaft **112**. The rotor **111** is shaped substantially as a turbine and comprises four blades **201** which, under the action of the fluid flow through the valve **101**, are adapted to rotate and produce a torque that will drive the shaft **112** of the rotor **111** itself.

(25) In one embodiment, the rotor **111** comprises a through hole **202** along the axis of the rotor **111**. Into this hole **202**, which preferably has a cross-like section, the shaft **112** can be inserted, which preferably has one end hinged into a cavity **115** (see FIG. 1) of the spherical obstructer **107** and the other end projecting out of the valve **101** and connected to the above-described user apparatus **114**.

(26) As far as construction materials are concerned, criteria of good engineering practice should be adopted, by using known metallic alloys typically employed for common control valves, and by taking into account operating pressures and temperatures, the aggressiveness of the working environment, and the corrosiveness of the fluid.

(27) It must be pointed out that a valve according to the present invention may be obtained by transforming a known ball valve, to which components like the rotor **111**, the shaft **112** and the user apparatus **114** are added after proper machining. In particular, the exemplary embodiment of the rotor **111** illustrated herein with reference to FIG. 2 (i.e. wherein the shaft **112** is separate from the rotor **111**) is particularly advantageous for transforming a ball valve, since the rotor **111** is adapted to be freely inserted into the through hole **108** and, therefore, the shaft **112** can subsequently be fitted into the hole of the spherical obstructer **107** along the axis **110**, thus connecting the rotor **111** to the shaft **112** by means of the shaped hole **202**.

(28) FIG. 3 schematically shows a sectional side view of the valve system **101** in operating conditions. The obstructer **107** is shown herein in the fully open configuration, wherein the axis of the through hole **108** is coaxial to the axis of the valve **101**, thus allowing the passage of the fluid.

(29) Under the action of the flowing fluid (schematized in this and in the next figures as partial flow lines), the rotor **111** rotates, thereby rotatably driving the shaft **112**.

(30) FIG. 4 schematically shows a sectional side view of the valve system in a partially open configuration, wherein the axis of the through hole **108** has been turned relative to the axis of the valve system **101** following a rotation of the obstructer **107**, thus still allowing the fluid to pass, but at a lower flow rate. In fact, the edge **401** of the obstructer **107** affects the fluid flow, introducing a load loss that reduces the fluid flow rate.

(31) Nevertheless, the rotor **111** keeps turning under the action of the flowing fluid. Even with the

valve partially closed, therefore, power recovery is still possible thanks to the torque provided by the shaft **112**. Moreover, by adjusting the resistant torque of the rotor **111** it is possible to improve the fluid flow adjustment even further.

(32) Preferably, the blades of the rotor **111** are curved towards the fluid inlet direction, thus improving the efficiency and facilitating the starting of the rotor. Moreover, preferably, the blades of the rotor **111** are so sized as to occupy, for at least some rotation positions of the rotor **111** in the through hole **108**, substantially the whole free section of the hole **108** itself without interfering with the motion of the obstructer.

(33) FIG. 5 schematically shows a sectional side view of the valve system in a closed configuration, wherein the axis of the through hole **108** has been turned by 90° relative to the axis of the valve **101** following a rotation of the obstructer **107**, thus substantially preventing the fluid from flowing through the valve. Since no fluid can flow around the rotor **111**, the latter will remain still and no power will be generated. In this configuration, the valve **101** permits closing the duct **105**, thus effectively performing the same task as prior-art ball valves. In this regard, the presence of the rotor **111** will not adversely affect the dimensions and performance of the valve **101**. As can be seen, the spherical segment of the obstructer **107** is at the front of the valve body with respect to the direction of the fluid flow.

(34) The obstructer **107** is so positioned that it fills only one of the two lateral parts of the valve body **102**, while the other lateral part **102'** is empty. Therefore, the latter can be constructed in different ways to meet specific requirements, e.g. as described with reference to FIGS. 6-8. Those parts which are equal to those described with reference to FIGS. 3-5 will not be described any further.

(35) According to this variant, since the obstructer has only one flow adjustment seat, the conformation of the free part of the valve body can be modified to obtain the best CV (flow coefficient) of the valve and make it usable in different conditions.

(36) Here, this free part **603** has a generic linear shape with a constant slope to join the downstream valve body, which has the same size as the pipe downstream and upstream of the valve body. This condition may be useful for applications with incompressible fluids, which do not tend to expand as pressure decreases. For compressible fluids, the fluid will expand downstream of the obstructer, at and downstream the turbine; in such cases, the particular conformation of the valve makes it possible to easily enlarge the terminal part of the valve body to allow the fluid to expand, so as to limit the velocity increase and connect the valve body to a downstream pipe **105'** which is bigger than the upstream duct **105**, see FIG. 15.

(37) In this configuration, it is no longer necessary to keep concentric with each other/on the same axis of rotation the obstructer actuation system and the turbine rotation axis. The latter (designated as **112'**) may be suitably moved downstream and offset to optimize the dimensions and position of the turbine (see FIG. 16).

(38) In general terms, therefore, the other lateral part of the valve body, opposite to the part that comprises the obstructer, comprises an empty part at said outlet **104**, and a joining part having a spherical-segment development **102'** or a linear development (**603**) at the duct interruption.

(39) According to further variant embodiments, a deflector **602** is positioned at the inlet of the valve body **102**, i.e. upstream of the rotor **111** with respect to the direction of the fluid flow.

(40) The deflector **602** improves the efficiency of the rotor **111** by directing the fluid flow towards the upper blades of the rotor **111**, which will therefore be subjected to a greater thrust.

(41) The deflector **602** may be a simple plate anchored and welded to a support, or it may have more aero-fluid-dynamically efficient shapes to avoid vein breaking.

(42) Preferably, the deflector **602** is placed in a position such that it is asymmetrical relative to the axis of rotation of the rotor **111**, i.e. in an asymmetric position in the cross-section of the valve body **102** with respect to the shaft **112**, preferably in the open part of the obstructer **107**.

(43) The deflector **602** also allows the rotor **111** to be more easily set in motion when the valve is

opened partially, by asymmetrically directing the fluid towards a blade of the rotor **111**, thereby facilitating the starting thereof.

(44) The deflector **602** contributes to avoiding any concentrated dissipation on the edge **401** of the obstruer **107**, which would affect the fluid flow. Thus, by controlling in a more effective manner the load losses that reduce the fluid flow through the valve, it is possible to further improve the adjustment of the fluid flow.

(45) A valve system according to the present invention may comprise a rotor made in accordance with different manufacturing solutions and having different shapes, which will essentially depend on the type of application of the valve itself.

(46) The construction of the rotor will primarily depend on the type of fluid for which the valve is to be optimized, whether gas, liquid, steam or any other multi-phase fluid.

(47) Such diversification is also related to specific liquid types, e.g. for liquids having different viscosity or density. For example, different characteristics, such as a higher flow coefficient, will be required from the valve for working with oil as opposed to water, so as to obtain an increased flow rate; also, the rotor blades will have to be self-cleaning.

(48) FIG. **9** shows a further embodiment of a rotor **901** which may be used in a control valve according to the present invention. In this variant, the rotor **901** comprises four blades that, under the action of the fluid flowing through the valve, are adapted to rotate and produce a torque that will drive the shaft **112**.

(49) The rotor **901** comprises a plurality of holes **902**, which increase the flow coefficient due to a larger flow surface, although to detriment of the efficiency of the turbine.

(50) The holes **902** are preferably located in the proximity of the axis of rotation of the rotor **901**, so that the outermost portions of the blades, i.e. where the lever arm is longest, will still be working, thus producing more power.

(51) Other variants of the rotor are also conceivable, which essentially differ from one another in the number of blades.

(52) FIG. **10** schematically shows a valve **101b** comprising a rotor **111b** comprising three blades, which is preferably adapted for use with very viscous liquids.

(53) FIG. **11** schematically shows a valve **101c** comprising a rotor **111c** comprising ten blades, which is preferably adapted for use with gases.

(54) In a preferred embodiment, as aforesaid, the blades of the rotor are curved towards the fluid inlet direction, so as to improve the efficiency and facilitate the starting of the rotor. The blades may alternatively be flat, e.g. should such choice be dictated by production cost requirements.

(55) A valve system according to the present invention permits, therefore, recovering at least part of the energy dissipated by the fluid flowing therethrough; at the same time, it also essentially maintains the control capability which is typical of this valve type. The energy recovered will depend on the fluid-dynamic conditions in which the valve will have to operate, the valve opening angle, i.e. the angle of rotation of the valve obstruer, and the efficiency of the turbine, which in turn will depend on its shape.

(56) A valve system according to the present invention also makes it possible to effectively exploit the turbine for most obstruer opening angles that allow fluid to flow through the valve.

(57) Furthermore, unlike the above-mentioned international patent application WO2013/121375-A1, in this case, even in situations wherein higher efficiency is obtained if the axis of rotation of the rotor does not coincide with the axis of rotation of the obstruer, the introduction of the rotor does not require any substantial modification to the structure or principle of operation of the spherical-segment valve, while at the same time providing a compact, easy-to-manufacture device.

(58) Preferably, the rotor comprises a shaft and a plurality of blades which are substantially transversal to the fluid flow and which are fixed to the shaft. This provides a highly efficient rotor having a simple construction.

(59) Preferably, the blades are so sized as to occupy, for some rotation positions of the rotor,

substantially the whole free cross-section of the valve body downstream of the spherical-segment obstrucuter.

(60) Preferably, the blades comprise holes on their surface in order to decrease the dissipations occurring in the fluid flowing across the rotor and to improve the flow control accuracy.

(61) Preferably, the control valve comprises a deflecting element positioned upstream of said rotor, which is adapted to fluid-dynamically interact with the fluid flow to improve the efficiency and facilitate the starting of the rotor.

(62) Preferably, the deflecting element is positioned asymmetrically in the valve, at a cross-section defined by the axis of rotation of the valve.

(63) Preferably, the valve can be associated with a mechanical user apparatus or an electric generator to transform the rotation of the rotor into usable energy. Thus, the valve provides a source of mechanical or electric energy that will be available even in remote or hardly accessible places, or anyway it can provide a power source in places where there are no electric grid wires.

(64) The above-described non-limiting examples may be subject to further variations without however departing from the protection scope of the present invention, including all equivalent embodiments known to a person skilled in the art.

(65) For example, many embodiments are conceivable for the rotor, depending on whether the valve system will have to prevalently operate in fully open or partially open conditions, with compressible or incompressible fluids; it is also possible to optimize the shape and construction of the various elements of the valve (diameter of the hole in the obstrucuter, valve body inlet and outlet diameters, dimensions and shape of the valve body, etc.) based on the prevalent operating conditions of the valve itself.

(66) It is also conceivable to position the actuator **109** on the same side of the valve **101** where the user apparatus **114** is located; this embodiment, although it requires a more complex construction (e.g. the actuator may require the presence of a hole through the shaft **112**), may be used when suggested by considerations about the outer dimensions of the valve itself.

(67) The elements and features shown in the various preferred embodiments may be combined together without however departing from the protection scope of the present invention.

(68) From the above description, those skilled in the art will be able to produce the object of the invention without introducing any further construction details.

Claims

1. A valve system for controlling a fluid flow in a duct, comprising: a substantially hollow valve body provided with an inlet and an outlet which allow a flow of a fluid in said valve body, said valve body houses an obstrucuter rotatable, about an axis of rotation, between: a first position, in which said valve system is closed, wherein said obstrucuter stops the flow of the fluid from passing between the inlet and the outlet of the valve body; and a second position, in which said valve system is partially or totally open, wherein said obstrucuter allows the flow of the fluid to pass between the inlet and the outlet of said valve body; an actuator adapted to rotate said obstrucuter between said first position and said second position; a rotor shaped substantially as a turbine, placed inside the valve body and provided with a rotation shaft, the rotation shaft being spaced apart from and parallel with respect to the axis of rotation of the obstrucuter, said rotor being adapted to be rotated by said flow of the fluid; wherein said valve body further comprises: a housing, arranged on a first lateral portion of the valve body and having a first recess in a configuration of a spherical segment; and a second recess disposed on a second lateral portion of the valve body, the second recess facing toward and being opposite to the first recess, wherein said obstrucuter has a spherical-segment outer contour which, in said second position, adheres to an inner edge of the housing of the valve body; wherein, in the first position, the spherical-segment outer contour of the obstrucuter is upstream of the axis of rotation with respect to a direction of the flow of

the fluid; wherein, in the second position, (i) the spherical-segment outer contour of the obstructor is at least partially disposed within the first recess, and (ii) the obstructor does not occupy, either entirely or partially, the second recess, wherein the second recess has a configuration different from the first recess so that a spacing between the first recess and the second recess toward the outlet is greater than a spacing between the first recess and the second recess toward the inlet, wherein said outlet has a cross section that is larger than a cross section of said inlet.

2. The valve system for controlling the fluid flow in a duct as in claim 1, wherein a portion of said second recess has a substantially linear shape with a constant slope that joins to said outlet.

3. The valve system for controlling the fluid flow in a duct as in claim 1, wherein said rotation shaft of the rotor comes out of said valve body and is connected to a user apparatus utilizing a rotation energy of the rotor during operation.

4. The valve system for controlling the fluid flow in a duct as in claim 1, wherein said rotor comprises a plurality of blades substantially transversal to the flow of said fluid and being fixed to said rotation shaft.

5. The valve system for controlling the fluid flow in a duct as in claim 4, wherein said blades are curved towards said inlet of the valve body.

6. The valve system for controlling a fluid flow in a duct as in claim 1, further comprising a deflecting element positioned upstream of said rotor and adapted to fluid-dynamically interact with the flow of said fluid.

7. The valve system for controlling the fluid flow in a duct as in claim 6, wherein said deflecting element is positioned asymmetrically relative to said rotation shaft.

8. The valve system for controlling the fluid flow in a duct as in claim 1, wherein said axis of rotation is substantially transversal to said flow of said fluid through said valve body.

9. The valve system for controlling the fluid flow in a duct as in claim 1, wherein, in the first position, the spherical-segment outer contour of the obstructor is at least partially disposed within the second recess.

10. The valve system for controlling the fluid flow in a duct as in claim 1, wherein, in the first position, the obstructor stops the flow of the fluid from passing between the inlet and the rotor but there is no blocking passing of the flow of the fluid from the rotor to the outlet.

11. The valve system for controlling the fluid flow in a duct as in claim 1, wherein, in said first position, the obstructor entirely closes said inlet and does not obstruct said outlet, wherein, in said second position, the obstructor leaves at least partially open said inlet and does not obstruct said outlet.

12. The valve system for controlling the fluid flow in a duct as in claim 1, wherein the valve body bounds a fluid passage through which the fluid passes as the fluid travels from the inlet to the outlet, the first recess and the second recess being disposed on opposing sides of the fluid passage.

13. The valve system for controlling the fluid flow in a duct as in claim 1, wherein when viewed in a plane that is normal to the axis of rotation of the obstructor and that centrally passes through the inlet and the outlet, the first recess has a first outer perimeter edge having a constant radius from the axis of rotation of the obstructor as the first outer perimeter edges extends from toward the inlet to toward the outlet and the second recess has a second outer perimeter edge having a radius from the axis of rotation of the obstructor that constantly flares radially outward as the second outer perimeter edge extends from toward the inlet to toward the outlet.
