

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401238
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Luo; Wenhui

Stator for motor and oil cooling motor

Abstract

A stator for a motor includes a stator core of a hollow columnar structure. The stator core includes a first end and a second end in an axial direction. The stator core defines a first oil cooling channel and a second oil cooling channel through in the axial direction. The first oil cooling channel has a first oil inlet at the first end and a first oil outlet at the second end. The second oil cooling channel has a second oil outlet at the first end and a second oil inlet at the second end. At the first end, the first oil inlet and the second oil outlet are arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core.

Inventors:	Luo; Wenhui (Beijing, CN)
Applicant:	XIAOMI EV TECHNOLOGY CO., LTD. (Beijing, CN)
Family ID:	1000008782448
Assignee:	XIAOMI EV TECHNOLOGY CO., LTD. (Beijing, CN)
Appl. No.:	17/895634
Filed:	August 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230369924 A1	Nov. 16, 2023

Foreign Application Priority Data

CN	202210507529.7	May. 10, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: H02K1/20 (20060101); H02K9/19 (20060101)

U.S. Cl.:CPC **H02K1/20** (20130101); **H02K9/19** (20130101);**Field of Classification Search****CPC:** H02K (1/20); H02K (5/203); H02K (9/19); Y02T (10/64)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0024129	12/2006	Pfannschmidt et al.	N/A	N/A
2017/0271955	12/2016	Hanumalagutti et al.	N/A	N/A
2022/0045576	12/2021	Druant	N/A	H02K 3/24
2023/0141526	12/2022	Alahyari	N/A	F16K 15/00
2023/0223801	12/2022	Druant	310/54	H02K 1/20
2023/0283148	12/2022	Xu	310/58	H02K 9/19
2024/0348127	12/2023	Gersten	N/A	H02K 16/00
2024/0364152	12/2023	Sever	N/A	H02K 3/345
2024/0372420	12/2023	Christensen	N/A	H02K 9/04
2024/0388168	12/2023	Ledieu	N/A	H02K 15/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108370180	12/2017	CN	N/A
112615445	12/2020	CN	N/A
113783323	12/2020	CN	N/A
114421677	12/2021	CN	N/A

OTHER PUBLICATIONS

Chinese Patent Application No. 202210507529.7, Office Action dated Jul. 1, 2023, 9 pages. cited by applicant

Chinese Patent Application No. 202210507529.7, English translation of Office Action dated Jul. 1, 2023, 14 pages. cited by applicant

European Patent Application No. 22192636.3, Office Action dated May 22, 2023, 10 pages. cited by applicant

Chinese Patent Application No. 202210507529.7, Office Action dated Mar. 25, 2023, 8 pages. cited by applicant

Chinese Patent Application No. 202210507529.7, English translation of Office Action dated Mar. 25, 2023, 8 pages. cited by applicant

Primary Examiner: Koehler; Christopher M

Assistant Examiner: Vo; Ethan Nguyen

Attorney, Agent or Firm: Cozen O'Connor

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) The present application claims benefit of priority to Chinese Patent Application No. 202210507529.7 filed on May 10, 2022, the entire contents of which are incorporated herein by reference for all purposes.

FIELD

(2) The present disclosure relates to the field of motor cooling technologies, and in particular, to a stator for a motor and an oil cooling motor.

BACKGROUND

(3) Taking a driving motor of a new energy vehicle as an example, the higher the speed, torque density, and power density of the motor, the higher the heat generated. Therefore, a heat dissipation/cooling structure of a motor is essential for reliable, stable, and efficient operation of the motor.

SUMMARY

(4) Embodiments of the present disclosure provide a stator for a motor. The stator includes a stator core of a hollow columnar structure. The stator core includes a first end and a second end in an axial direction, the stator core defines a first oil cooling channel and a second oil cooling channel, and the first oil cooling channel and the second oil cooling channel are through in the axial direction. The first oil cooling channel has a first oil inlet at the first end and a first oil outlet at the second end, the second oil cooling channel has a second oil outlet at the first end and a second oil inlet at the second end, and at the first end, the first oil inlet and the second oil outlet are arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core.

(5) Embodiments of the present disclosure further provides an oil cooling motor. The oil cooling motor includes a housing and a stator. The housing defines a housing oil inlet. The stator includes a stator core of a hollow columnar structure. The stator core includes a first end and a second end in an axial direction. The stator core defines a first oil cooling channel and a second oil cooling channel, and the first oil cooling channel and the second oil cooling channel are through in the axial direction. The first oil cooling channel has a first oil inlet at the first end and a first oil outlet at the second end, the second oil cooling channel has a second oil outlet at the first end and a second oil inlet at the second end, and at the first end, the first oil inlet and the second oil outlet are arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core. The stator is arranged in the housing, and the first oil inlet and the second oil inlet of the stator core are communicated with the housing oil inlet.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a sectional view of a partial structure of an oil cooling motor according to an example of the present disclosure;

(2) FIG. 2 is a schematic diagram of a stator core according to an example of the present disclosure;

(3) FIG. 3 is a schematic diagram of a first oil cooling channel and a second oil cooling channel of a stator core according to an example of the present disclosure;

(4) FIG. 4 is a schematic diagram of communication between first oil through holes of lamination stacks of a stator core;

(5) FIG. 5 is a schematic diagram of a first oil ring according to an example of the present

disclosure;

(6) FIG. 6 is a schematic diagram of a first oil ring and a second oil ring assembled at two ends of the stator core; and

(7) FIG. 7 is a schematic diagram of a partial structure illustrated in FIG. 6.

DETAILED DESCRIPTION

(8) Example embodiments will be described in detail herein, and examples thereof are illustrated in the drawings. When the following description relates to the drawings, the same numbers in different drawings denote same or similar elements unless otherwise indicated. Implementations described in the following example embodiments do not represent all implementations consistent with the present disclosure. Rather, they are merely examples of apparatuses and methods that are consistent with some aspects of the present disclosure.

(9) The terms used in the present disclosure are intended solely to describe particular embodiments and are not intended to limit the present disclosure. Unless defined otherwise, technical and scientific terms used in the present disclosure have the same meaning as is commonly understood by those of ordinary skill in the art to which the present disclosure belongs. “First”, “second”, and similar terms as used in the present disclosure do not denote any order, quantity, or importance, but rather are used to distinguish one component from another. Also, “one”, “a/an” and similar terms do not denote a limitation on quantity, but rather denote the presence of at least one of the referenced items, and may be specified separately when referring only to “one”. “A plurality of” or “several” means two or more. Unless otherwise noted, “front,” “back,” “lower,” and/or “upper”, “top”, “bottom” and other similar terms are only for the convenience of description, and are not intended to be limited to a particular position or space orientation. “Comprise”, “include” and similar terms mean that an element or item before “comprise” or “include” covers elements or items listed after “comprise” or “include” and equivalents thereof, and do not exclude other elements or items. “Connect”, “join” and similar terms are not limited to physical or mechanical connections, and may include electrical connections, whether direct or indirect.

(10) Motor cooling may be divided into air cooling, water cooling, and oil cooling. Oil cooling is becoming the first choice of a high-performance motor cooling scheme by virtue of advantages of natural electrical insulation and high degree of freedom in structural design.

(11) The driving motor of the new energy vehicle is mostly a permanent magnet synchronous motor. When the motor operates at a middle and low speed range, a stator part of the motor generates high heat. The majority of the heat is generated by a stator winding and a stator core. When the motor operates at a high speed range, heat generated by a rotor part of the motor increases dramatically. Therefore, if the stator part or rotor part of the driving motor cannot be effectively dissipated and cooled, overall performance of the motor may be directly affected, resulting in low reliability, stability, and efficiency of the operation of the motor, and seriously affecting the reliable and stable operation of the vehicle.

(12) Referring to FIG. 1, FIG. 1 is a schematic diagram of a partial structure of an oil cooling motor 1 according to an example of the present disclosure.

(13) The oil cooling motor 1 according to the embodiment of the present disclosure includes a housing 10, a stator 20, and a rotor (not illustrated). A receiving chamber 101 is formed inside the housing 10, the stator 20 and the rotor are both received in the receiving chamber 101, and the stator 20 is coaxial with the rotor. The stator 20 remains relatively fixed to the housing 10, the rotor is rotatable with respect to the stator 20, and the stator 20 is arranged around the outside of the rotor. The housing 10 further defines a housing oil inlet 102. Cooling oil may be transported into the stator core 21 through the housing oil inlet 102.

(14) The stator 20 includes a stator core 21 and a stator winding 22 assembled on the stator core 21. The stator core 21 has a hollow columnar structure, and the rotor is assembled at a hollow part of the stator core 21. The oil cooling motor 1 may cool the stator core 21 and the stator winding 22 by oil.

(15) Referring to FIG. 2, FIG. 2 is a schematic diagram of the stator core **21** according to an example of the present disclosure.

(16) The stator core **21** has a hollow cylindrical structure and has an axis O. An axial direction of the stator core **21** refers to an extension direction of the axis O, and a circumferential direction of the stator core **21** refers to a circumferential direction around the axis O.

(17) The stator core **21** includes a first oil cooling channel **210**, a second oil cooling channel **211**, and a first end **212** and a second end **213** in the axial direction. The first oil cooling channel **210** passes through the first end **212** and the second end **213**, and defines a first oil inlet **2100** at the first end **212** and a first oil outlet **2102** at the second end **213**. The first oil inlet **2100** allows oil to flow in. The first oil outlet **2102** allows oil to flow out. The second oil cooling channel **211** passes through the first end **212** and the second end **213**, and defines a second oil inlet **2110** at the second end **213** and a second oil outlet **2112** at the first end **212**. The second oil inlet **2110** allows oil to flow in. The second oil outlet **2112** allows oil to flow out. With the arrangement, cooling oil can be transported respectively from two axial ends of the stator core **21** to the stator core **21** through the first oil cooling channel **210** and the second oil cooling channel **211**, and the stator core **21** can be cooled through multiple oil channels in opposite circulation directions, which improves heat dissipation efficiency and achieves uniform heat dissipation.

(18) The present disclosure further proposes that, at the first end **212**, the first oil inlet **2100** and the second oil outlet **2112** are arranged along the circumferential direction of the stator core **21** and located on the same circumference centered around the axis of the stator core **21**. The first oil inlet **2100** and the second oil outlet **2112** are circumferentially distributed, so that the stator core **21** can be cooled at different parts in the circumferential direction. Moreover, this arrangement also enables the first oil inlet **2100** and the second oil outlet **2112** to be more compact in a radial direction of the stator core **21**, which is conducive to reducing a radial size of the stator core **21** at the first end **212**.

(19) Similarly, at the second end **213**, the first oil outlet **2102** and the second oil inlet **2110** may be arranged along the circumferential direction of the stator core **21** and located on the same circumference centered around the axis of the stator core **21**. In this way, it is conducive to reducing a radial size of the stator core **21** at the second end **213**.

(20) In an embodiment, the stator core **21** defines a plurality of first oil cooling channels **210** extending in parallel. Correspondingly, the plurality of first oil cooling channels **210** form a plurality of first oil inlets **2100** at the first end **212**, and form a plurality of first oil outlets **2102** at the second end **213**. The plurality of first oil inlets **2100** are communicated with the plurality of first oil outlets **2102** in a one-to-one correspondence manner. In this way, a cooling area of the stator core **21** can be increased, a cooling effect can be further improved, and heat dissipation uniformity of the stator **20** can be further improved.

(21) The stator core **21** may further define a plurality of second oil cooling channels **211** extending in parallel. The plurality of second oil cooling channels **211** form a plurality of second oil inlets **2110** at the second end **213**, and form a plurality of second oil outlets **2112** at the first end **212**. The plurality of second oil inlets **2110** are communicated with the plurality of second oil outlets **2112** in a one-to-one correspondence manner.

(22) In an embodiment, at the first end **212**, the plurality of first oil inlets **2100** are arranged along the circumferential direction, the plurality of second oil outlets **2112** are arranged along the circumferential direction, and the plurality of first oil inlets **2100** and the plurality of second oil outlets **2112** are interleaved. "Interleaved" herein means that the plurality of first oil inlets **2100** and the plurality of second oil outlets **2112** are arranged in a mixed manner in the circumferential direction. In this way, the plurality of first oil inlets **2100** and the plurality of second oil outlets **2112** can be separated from each other to prevent excessive concentration of the plurality of first oil inlets **2100** and excessive concentration of the plurality of second oil outlets **2112**. For example, as one implementation of interleaving, one or more second oil outlets **2112** are arranged between two

adjacent first oil inlets **2100**; or one or more first oil inlets **2100** are arranged between two adjacent second oil outlets **2112**. As another implementation of interleaving, the first oil inlets **2100** and the second oil outlets **2112** are arranged alternately. The interleaving has an advantage that circumferential parts of the stator core **21** can be cooled evenly and a temperature difference between different parts of the stator core **21** can be reduced. Specifically, during the flow of the cooling oil, the cooling oil and the stator core **21** may exchange heat constantly. At the first oil inlet **2100**, the cooling oil is at a relatively low temperature, and has a good heat exchange effect with the stator core **21**. At the second oil outlet **2112**, the cooling oil is at a relatively high temperature, and has a poor heat exchange effect with the stator core **21**. Through the interleaving of the first oil inlets **2100** and the second oil outlets **2112**, the temperature difference between the circumferential parts of the stator core **21** at the first end **212** can be reduced, so that the stator core **21** can dissipate heat evenly at the first end **212**.

(23) In an embodiment, at the second end **213**, the plurality of second oil inlets **2110** are arranged along the circumferential direction, the plurality of first oil outlets **2102** are arranged along the circumferential direction, and the plurality of second oil inlets **2110** and the plurality of first oil outlets **2102** are interleaved. In this way, a temperature difference between circumferential parts at the second end **213** is relatively small, so that the stator core **21** can dissipate heat evenly at the second end **213**.

(24) In an embodiment, a plurality of first oil cooling channels **210** and a plurality of second oil cooling channels **211** may be distributed along the whole circumference of the stator core **21** along the circumferential direction of the stator core **21**. Correspondingly, the plurality of first oil inlets **2100** and the plurality of second oil outlets **2112** formed at the first end **212** and the plurality of second oil inlets **2110** and the plurality of first oil outlets **2102** formed at the second end **213** are all distributed along the whole circumference of the stator core along the circumferential direction. In this way, the stator core **21** can achieve 360° heat dissipation in the circumferential direction. The plurality of first oil inlets **2100** and the plurality of second oil outlets **2112** are located on a same circumference centered around an axis of the stator core **21**, and the plurality of second oil inlets **2110** and the plurality of first oil outlets **2102** are located on the same circumference centered around the axis of the stator core **21**.

(25) In the embodiment illustrated in FIG. 2, the first oil inlet **2100** and the first oil outlet **2102** of the first oil cooling channel **210** are oppositely arranged along the axial direction of the stator core **21**. In this way, the first oil cooling channel **210** can be formed as a straight-through oil cooling channel, so that cooling parts of the stator core **21** can be relatively concentrated in the circumferential direction.

(26) In the embodiment illustrated in FIG. 2, the second oil inlet **2110** and the second oil outlet **2112** of the second oil cooling channel **211** are oppositely arranged along the axial direction of the stator core **21**. In this way, the second oil cooling channel **211** can be formed as a straight-through oil cooling channel, so that cooling parts of the stator core **21** can be relatively concentrated in the circumferential direction.

(27) Referring to FIG. 3, FIG. 3 is a schematic diagram of another embodiment of the first oil cooling channel **210** and the second oil cooling channel **211** in the stator core **21**.

(28) In the embodiment illustrated in FIG. 3, the first oil inlet **2100** and the first oil outlet **2102** of the first oil cooling channel **210** are staggered along the circumferential direction of the stator core **21**. In this way, the first oil cooling channel **210** can be formed as a spiral oil cooling channel, so that cooling parts of the stator core **21** can be relatively dispersed in the circumferential direction.

(29) In the embodiment illustrated in FIG. 3, the second oil inlet **2110** and the second oil outlet **2112** of the second oil cooling channel **211** are staggered along the circumferential direction of the stator core **21**. In this way, the second oil cooling channel **211** can be formed as a spiral oil cooling channel, so that cooling parts of the stator core **21** can be relatively dispersed in the circumferential direction.

(30) Shapes and sizes of the first oil inlet **2100** and the first oil outlet **2102** are not limited in the present disclosure. In this embodiment, the first oil inlet **2100** and the first oil outlet **2102** are both configured as square ports, and an opening area of the first oil inlet **2100** is equal to an opening area of the first oil outlet **2102**. In other embodiments, the first oil inlet **2100** and the first oil outlet **2102** may be both configured as circular ports, and a diameter of the first oil inlet **2100** may be equal or unequal to a diameter of the first oil outlet **2102**.

(31) Still referring to FIG. 2, the stator core **21** includes a plurality of lamination stacks **214** stacked along the axial direction. Each of the lamination stacks **214** is formed by a plurality of laminations stacked along a thickness direction. The plurality of laminations may be reliably coupled by welding, riveting or bonding. The number of the laminations in each lamination stack **214** is not limited, which may be selected and set according to an actual requirement. The laminations in the same lamination stack **214** may be identical laminations.

(32) Each of the lamination stacks **214** defines a first oil through hole **2140** and a second oil through hole **2142** through in the axial direction. The first oil through holes **2140** are sequentially communicated to form the first oil cooling channel **210**. The second oil through holes **2142** are sequentially communicated to form the second oil cooling channel **211**. In an embodiment, the first oil through hole **2140** in each lamination stack **214** has a straight-through structure, and the first oil through holes **2140** of the plurality of lamination stacks **214** are straight-through to form the first oil cooling channel **210** of the straight-through structure. Similarly, the second oil through hole **2142** in each lamination stack **214** has a straight-through structure, and the second oil through holes **2142** of the plurality of lamination stacks **214** are straight-through to form the second oil cooling channel **211** of the straight-through structure, which is not limited thereto.

(33) Referring to FIG. 4, FIG. 4 is a schematic diagram of communication between the first oil through holes **2140** of the lamination stacks **214**.

(34) In this embodiment, an area where two first oil through holes **2140** of two adjacent lamination stacks **214** are communicated may be changed, so as to increase an area of contact between the oil in the first oil cooling channel **210** and the lamination stacks **214**. Specifically, in at least two adjacent lamination stacks **214**, a circulation area S of the first oil through hole **2140** of the lamination stack **214** closer to the first oil inlet **2100** is greater than a communication area S' where the two first oil through holes **2140** of the adjacent lamination stacks **214** are communicated. In some embodiments, in at least one pair of adjacent lamination stacks **214**, a circulation area S of the first oil through hole **2140** of the lamination stack **214** closer to the first oil inlet **2100** is greater than a communication area S' where the two first oil through holes **2140** of the at least one of adjacent lamination stacks **214** are communicated. After the arrangement, when the oil flows from the first oil through hole **2140** of the left lamination stack **214** to the first oil through hole **2140** of the right lamination stack **214**, due to a decrease in the communication area S', the oil is subject to resistance during the circulation and may contact a peripheral part A of the first oil through hole **2140** of the right lamination stack **214**, which can increase an area of contact between the oil and the right lamination stack **214** and improve a heat exchange effect. In the embodiment illustrated in FIG. 4, the communication area S' where two adjacent first oil through holes **2140** are communicated is less than the circulation area of the first oil through hole **2140**, so that areas of contact between the oil and the plurality of lamination stacks **214** can be increased.

(35) The manner of decreasing the communication area S' is not limited. In an embodiment, the circulation area of the first oil through hole **2140** of the left lamination stack **214** may be greater than the circulation area of the first oil through hole **2140** of the right lamination stack **214**.

(36) In some other embodiments, the circulation areas of the first oil through holes **2140** of two adjacent lamination stacks **214** are equal, and two adjacent first oil through holes **2140** are partially staggered and partially communicated along the circumferential direction of the stator core **21**. In this way, two adjacent first oil through holes **2140** can be circumferentially offset. When the cooling oil flows from the first oil through hole **2140** of the left lamination stack **214** into the first

oil through hole **2140** of the right lamination stack **214**, a region of the right lamination stack **214** outside the first oil through hole **2140** may contact the cooling oil, increasing the area of contact between the right lamination stack **214** and the cooling oil, and enhancing the cooling effect. Moreover, in this embodiment, the lamination stack **214** may be stacked by identical laminations, which can reduce types of dies for stamping laminations and help reduce manufacturing costs of the laminations.

(37) In an embodiment, in order to increase an area of contact between the cooling oil in the second oil cooling channel **211** and the lamination stack **214**, the same implementation manner as the above may be adopted. Specifically, in at least two adjacent lamination stacks **214** of the plurality of lamination stacks **214**, a circulation area of the second oil through hole **2142** of the lamination stack **214** closer to the second oil inlet **2110** is greater than a communication area where the two second oil through holes **2142** of the adjacent lamination stacks **214** are communicated. The setting of the circulation areas of the second oil through holes **2142** in the lamination stacks **214** and the alignment manner of the second oil through holes **2142** may refer to those of the first oil through holes **2140**, which are not repeated herein.

(38) Referring to FIG. 1 and FIG. 5, FIG. 5 is a schematic diagram of a first oil ring **40**.

(39) In an embodiment, the oil cooling motor **1** further includes a first oil ring **40**. The first oil ring **40** is arranged at the first end **212** of the stator core **21**. The first oil ring **40** is coaxial with the stator core **21**. In an embodiment, a seal ring **41** fits over an end of the first oil ring **40** away from the stator core **21** along the axial direction. The seal ring **41** is clamped between the housing **10** and the first oil ring **40** along a radial direction of the first oil ring **40**, for sealing a gap between the housing **10** and the first oil ring **40**, which may also seal a channel between the housing oil inlet **102** and the first oil inlet **2100**.

(40) In an embodiment, the first oil ring **40** includes a first oil inlet chamber **401** communicated with the first oil inlet **2100** and a first oil outlet chamber **402** communicated with the second oil outlet **2112**. The first oil inlet chamber **401** is further communicated with the housing oil inlet **102**, so that the cooling oil can flow into the first oil inlet **2100** according to a preset path, and flow out of the second oil outlet **2112** to other parts of the stator **20** according to a preset path. In addition, with the arrangement of the first oil ring **40**, oil pipes can be omitted, which is beneficial to simplify the structure of the stator **20** and improve the compactness of the stator **20**. The first oil inlet chamber **401** and the first oil outlet chamber **402** are distributed on a same circumference centered around an axis of the first oil ring **40**.

(41) The specific structure of the first oil ring **40** is not limited in the present disclosure. In an embodiment, a first groove **403** and a first boss **404** circumferentially arranged and axially extending are formed on an outer surface of the first oil ring **40**, and the first groove **403** forms the first oil inlet chamber **401**. The first groove **403** extends axially, an end of the first groove **403** away from the stator core **21** is sealed by the seal ring **41** and is communicated with the housing oil inlet **102** in a sealing manner, and an end of the first groove **403** closer to the stator core **21** is communicated with the first oil inlet **2100**. An end surface on a side of the first boss **404** facing the stator core **21** defines the first oil outlet chamber **402**, and the first oil outlet chamber **402** extends axially in the first boss **404**. In the solution, the first oil inlet chamber **401** is formed by defining the first groove **403**, and the first oil outlet chamber **402** is formed by defining a chamber in the first boss **404**. In this way, isolation between the first oil inlet chamber **401** and the first oil outlet chamber **402** is realized, and the formation of the first oil inlet chamber **401** and the first oil outlet chamber **402** is simple, which are easy to machine and manufacture.

(42) In an embodiment where a plurality of first oil cooling channels **210** and a plurality of second oil cooling channels **211** are provided, the first oil ring **40** may define a plurality of first oil inlet chambers **401** and a plurality of first oil outlet chambers **402**. The first oil inlet chambers **401** and the first oil outlet chambers **402** may be interleaved.

(43) In an embodiment, a first oil injection hole **400** is formed on an inner surface of the first oil

ring **40**, the first oil injection hole **400** is communicated with the first oil outlet chamber **402**, the stator **20** includes a stator winding **22**, and the first oil injection hole **400** directly faces the stator winding **22**. In this way, the cooling oil flowing out of the first oil outlet chamber **402** may further cool the stator winding **22**, without a need to separately arrange an oil channel for cooling the stator winding **22**.

(44) Referring to FIG. **6** and FIG. **7**, FIG. **6** is a schematic diagram of a first oil ring **40** and a second oil ring **50** assembled at two ends of the stator core **21**. FIG. **7** is a schematic diagram of a partial structure illustrated in FIG. **6**.

(45) As illustrated in FIG. **6**, in an embodiment, a plurality of first oil inlet chambers **401** are communicated with each another at an end axially away from the stator core **21**, and the plurality of first oil inlet chambers **401** are communicated with the housing oil inlet **102**.

(46) As illustrated in FIG. **7**, a plurality of first oil inlets **2100** may be jointly communicated with one first oil inlet chamber **401**, and a plurality of second oil outlets **2112** may be jointly communicated with one first oil outlet chamber **402**, so that numbers of the first oil inlet chambers **401** and the first oil outlet chambers **402** can be reduced, and numbers of the first grooves **403** and the first bosses **404** can be reduced accordingly, which helps to simplify the structure of the first oil ring **40**.

(47) Referring to FIG. **1**, FIG. **6**, and FIG. **7**, in an embodiment, the stator **20** further includes a second oil ring **50** arranged at the second end **213**, the second oil ring **50** is coaxial with the stator core **21**, and the second oil ring **50** includes a second oil inlet chamber **501** communicated with the second oil inlet **2110** and a second oil outlet chamber **502** communicated with the first oil outlet **2102**.

(48) A second seal ring **51** fits over an end of the second oil ring **50** away from the stator core **21**. The second seal ring **51** is clamped between the housing **10** and the second oil ring **50** along a radial direction of the second oil ring **50**, for sealing a gap between the housing **10** and the second oil ring **50**. The second oil inlet chamber **501** is communicated with the housing oil inlet **102** and the second oil inlet **2110**, and the second oil inlet chamber **501** and the housing oil inlet **102** are communicated in a sealing manner through the second seal ring **51**. Two housing oil inlets **102** are provided and are spaced along the axial direction of the stator core **21**. One of the housing oil inlets **102** is communicated with the first oil inlet **2100** through the first oil inlet chamber **401**, and the other of the housing oil inlets **102** is communicated with the second oil inlet **2110** through the second oil inlet chamber **501**, so that the oil is fed simultaneously from the two axial ends of the stator core **21**.

(49) In an embodiment where a plurality of first oil cooling channels **210** and a plurality of second oil cooling channels **211** are provided, the second oil ring **50** may define a plurality of second oil inlet chambers **501** and a plurality of second oil outlet chambers **502**. The second oil inlet chambers **501** and the second oil outlet chambers **502** may be interleaved.

(50) A plurality of second oil inlet chambers **501** are communicated with each other at an end axially away from the stator core **21**, and the plurality of second oil inlet chambers **501** are communicated with the housing oil inlet **102**.

(51) In an embodiment, a second groove **503** and a second boss **504** circumferentially distributed and axially extending are formed on an outer surface of the second oil ring **50**, the second groove **503** forms the second oil inlet chamber **501**, an end surface on a side of the second boss **504** facing the stator core **21** defines the second oil outlet chamber **502**, and the second oil outlet chamber **502** extends axially.

(52) A plurality of second oil inlets **2110** may be jointly communicated with one second oil inlet chamber **501**, and a plurality of first oil outlets **2102** may be jointly communicated with one second oil outlet chamber **502**, so that numbers of the second oil inlet chambers **501** and the second oil outlet chambers **502** can be reduced, and numbers of the second grooves **503** and the second bosses **504** can be reduced accordingly, which helps to simplify the structure of the second oil ring **50**.

(53) In an embodiment, a second oil injection hole **500** (see FIG. 1) is formed on an inner surface of the second oil ring **50**, the second oil injection hole **500** is communicated with the second oil outlet chamber **502**, and the second oil injection hole **500** directly faces the stator winding **22**. In this way, the cooling oil flowing out of the second oil outlet chamber **502** may further cool the stator winding **22**, without a need to separately arrange an oil channel for cooling the stator winding **22**.

(54) In the embodiment illustrated in FIG. 1, the first oil injection hole **400** directly faces the stator winding **22** at the first end **212**, and the second oil injection hole **500** directly faces the stator winding **22** at the second end **213**, so that the two stator windings **22** of the stator **20** can be cooled separately.

(55) In this embodiment, the first oil ring **40** and the second oil ring **50** adopt an identical structure. The first oil ring **40** and the second oil ring **50** may be made from plastics with oil resistance and high-temperature resistance, including but not limited to, polyamide, high-temperature resistant nylon, and polyphenylene sulfide.

(56) The stator core **21** and the stator winding **22** in the present disclosure are fully and evenly cooled, which effectively reduces a risk of high-temperature aging failure of insulation of the motor system and improves power density and torque density of the motor.

(57) In the oil cooling motor according to the present disclosure, the cooling oil enters from the first oil ring **40**, and enters the second oil ring **50** through the first oil cooling channel **210** of the stator core **21** and then is sprayed out, enabling internal cooling and end cooling of the stator core **21** to be at a same rate of flow. Similarly, the cooling oil enters from the second oil ring **50**, and enters the first oil ring **40** through the second oil cooling channel **211** of the stator core **21** and then is sprayed out, enabling internal cooling and end cooling of the stator core **21** to be at a same rate of flow.

(58) The present disclosure provides an improved motor stator and an improved oil cooling motor, which can improve a cooling effect and improve compactness of the motor stator.

(59) The present disclosure provides a motor stator, including a stator core of a hollow columnar structure, the stator core including a first end and a second end in an axial direction, the stator core defining a first oil cooling channel and a second oil cooling channel through in the axial direction, the first oil cooling channel having a first oil inlet formed at the first end and a first oil outlet formed at the second end, the second oil cooling channel having a second oil outlet formed at the first end and a second oil inlet formed at the second end, and at the first end, the first oil inlet and the second oil outlet being arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core.

(60) In some examples, the stator core includes a plurality of lamination stacks stacked along the axial direction, each of the lamination stacks defines a first oil through hole through in the axial direction, the first oil through holes are sequentially communicated to form the first oil cooling channel, and in at least two adjacent lamination stacks, a circulation area of the first oil through hole of the lamination stack closer to the first oil inlet is greater than a communication area where the two first oil through holes of the adjacent lamination stacks are communicated.

(61) In some examples, in two adjacent lamination stacks, the first oil through hole of the lamination stack closer to the first oil inlet has a circulation area greater than a circulation area of the first oil through hole of the other lamination stack; or the first oil through holes of the two adjacent lamination stacks have equal circulation areas, and two adjacent first oil through holes are staggered in the circumferential direction and partially communicated.

(62) In some examples, the stator core includes a plurality of lamination stacks stacked along the axial direction, each of the lamination stacks defines a second oil through hole through in the axial direction, the second oil through holes are sequentially communicated to form the second oil cooling channel, and in at least two adjacent lamination stacks, the second oil through hole of the lamination stack closer to the second oil inlet has a circulation area greater than a communication

area where the two second oil through holes of the adjacent lamination stacks are communicated.

(63) In some examples, the first oil inlet and the first oil outlet are opposite along the axial direction of the stator core, or staggered along the circumferential direction of the stator core; and/or the second oil inlet and the second oil outlet are opposite along the axial direction of the stator core, or staggered along the circumferential direction of the stator core; and/or at the second end, the second oil inlet and the first oil outlet are arranged along the circumferential direction of the stator core and located on a same circumference centered around the axis of the stator core.

(64) In some examples, a plurality of first oil cooling channels are provided, and a plurality of second oil cooling channels are provided; at the first end, a plurality of first oil inlets are arranged along the circumferential direction of the stator core, a plurality of second oil outlets are arranged along the circumferential direction of the stator core, and the plurality of first oil inlets and the plurality of second oil outlets are interleaved; and/or at the second end, a plurality of second oil inlets are arranged along the circumferential direction of the stator core, a plurality of first oil outlets are arranged along the circumferential direction of the stator core, and the plurality of second oil inlets and the plurality of first oil outlets are interleaved.

(65) In some examples, the motor stator further includes a first oil ring arranged at the first end of the stator core, the first oil ring is coaxial with the stator core, and the first oil ring defines a first oil inlet chamber communicated with the first oil inlet and a first oil outlet chamber communicated with the second oil outlet.

(66) In some examples, an outer surface of the first oil ring is provided with a first groove and a first boss arranged in the circumferential direction and extending in the axial direction, the first groove forms the first oil inlet chamber, an end surface on a side of the first boss facing the stator core defines the first oil outlet chamber, and the first oil outlet chamber extends in the axial direction.

(67) In some examples, an inner surface of the first oil ring defines a first oil injection hole, the first oil injection hole is communicated with the first oil outlet chamber, the stator includes a stator winding, and the first oil injection hole directly faces the stator winding.

(68) In some examples, the motor stator further includes a second oil ring arranged at the second end of the stator core, the second oil ring is coaxial with the stator core, and the second oil ring includes a second oil inlet chamber communicated with the second oil inlet and a second oil outlet chamber communicated with the first oil outlet.

(69) In some examples, an outer surface of the second oil ring is provided with a second groove and a second boss arranged in the circumferential direction and extending in the axial direction, the second groove forms the second oil inlet chamber, an end surface on a side of the second boss facing the stator core defines the second oil outlet chamber, and the second oil outlet chamber extends in the axial direction.

(70) In some examples, an inner surface of the second oil ring defines a second oil injection hole, the second oil injection hole is communicated with the second oil outlet chamber, the stator includes a stator winding, and the second oil injection hole directly faces the stator winding.

(71) The present disclosure further provides an oil cooling motor, including: a housing, the housing defining a housing oil inlet, a motor stator as described in any of the above items, the motor stator is arranged in the housing and includes a stator core, a first oil inlet and a second oil inlet of the stator core being communicated with the housing oil inlet.

(72) The technical solution according to the present disclosure can achieve at least the following beneficial effects.

(73) The present disclosure provides a motor stator and an oil cooling motor. A stator core defines a first oil cooling channel and a second oil cooling channel in opposite circulation directions, so that cooling oil can be transported respectively from two axial ends of the stator core to the stator core through the first oil cooling channel and the second oil cooling channel, and the stator core can be cooled through multiple oil channels in opposite circulation directions, which improves heat

dissipation efficiency and achieves uniform heat dissipation. Moreover, the first oil inlet and the second oil outlet are arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core. This arrangement not only enables the stator core to be cooled at different parts in the circumferential direction, but also enables the first oil inlet and the second oil outlet to be more compact in a radial direction of the stator core, which is conducive to reducing a radial size of the stator core.

(74) The above are merely preferred embodiments of the present disclosure, which are not intended to limit the present disclosure. Any modification, equivalent replacement, improvement and the like made within the spirit and principle of the present disclosure should be included in the protection scope of the present disclosure.

Claims

1. A stator for a motor, comprising: a stator core of a hollow columnar structure, the stator core comprising a first end and a second end in an axial direction, the stator core defining a first oil cooling channel and a second oil cooling channel, the first oil cooling channel and the second oil cooling channel being through in the axial direction, the first oil cooling channel having a first oil inlet at the first end and a first oil outlet at the second end, the second oil cooling channel having a second oil outlet at the first end and a second oil inlet at the second end, and at the first end, the first oil inlet and the second oil outlet being arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core; and a first oil ring arranged at the first end of the stator core, wherein the first oil ring is coaxial with the stator core, and the first oil ring comprises a first oil inlet chamber communicated with the first oil inlet and a first oil outlet chamber communicated with the second oil outlet.
2. The stator according to claim 1, wherein the stator core comprises a plurality of lamination stacks stacked along the axial direction, each of the lamination stacks defines a respective first oil through hole through in the axial direction, the first oil through holes are sequentially communicated to form the first oil cooling channel, and in at least one pair of adjacent lamination stacks of the plurality of lamination stacks, the first oil through hole of the lamination stack closer to the first oil inlet has a circulation area greater than a communication area where the two first oil through holes of the at least one pair of adjacent lamination stacks are communicated.
3. The stator according to claim 2, wherein in the at least one pair of adjacent lamination stacks, the first oil through hole of the lamination stack closer to the first oil inlet has a circulation area greater than a circulation area of the first oil through hole of the other lamination stack.
4. The stator according to claim 2, wherein the first oil through holes of the two adjacent lamination stacks have equal circulation areas, and two adjacent first oil through holes are staggered in the circumferential direction and partially communicated.
5. The stator according to claim 2, wherein each of the plurality lamination stacks defines a respective second oil through hole through in the axial direction, the second oil through holes are sequentially communicated to form the second oil cooling channel, and in at least two adjacent lamination stacks, the second oil through hole of the lamination stack closer to the second oil inlet has a circulation area greater than a communication area where the two second oil through holes of the adjacent lamination stacks are communicated.
6. The stator according to claim 1, wherein the first oil inlet and the first oil outlet are opposite along the axial direction of the stator core.
7. The stator according to claim 1, wherein the first oil inlet and the first oil outlet are staggered along the circumferential direction of the stator core.
8. The stator according to claim 1, wherein the second oil inlet and the second oil outlet are opposite along the axial direction of the stator core.
9. The stator according to claim 1, wherein the second oil inlet and the second oil outlet are

staggered along the circumferential direction of the stator core.

10. The stator according to claim 1, wherein at the second end, the second oil inlet and the first oil outlet are arranged along the circumferential direction of the stator core and located on a same circumference centered around the axis of the stator core.

11. The stator according to claim 1, wherein a plurality of first oil cooling channels is provided, and a plurality of second oil cooling channels is provided; and at the first end, a plurality of first oil inlets is arranged along the circumferential direction of the stator core, a plurality of second oil outlets is arranged along the circumferential direction of the stator core, and the plurality of first oil inlets and the plurality of second oil outlets are interleaved.

12. The stator according to claim 1, wherein a plurality of first oil cooling channels is provided, and a plurality of second oil cooling channels is provided; and at the second end, a plurality of second oil inlets is arranged along the circumferential direction of the stator core, a plurality of first oil outlets are arranged along the circumferential direction of the stator core, and the plurality of second oil inlets and the plurality of first oil outlets are interleaved.

13. The stator according to claim 1, wherein an outer surface of the first oil ring comprises a first groove and a first boss arranged in the circumferential direction and extending in the axial direction, the first groove forms the first oil inlet chamber, an end surface of the first boss facing the stator core defines the first oil outlet chamber, and the first oil outlet chamber extends in the axial direction.

14. The stator according to claim 13, wherein an inner surface of the first oil ring defines a first oil injection hole, the first oil injection hole is communicated with the first oil outlet chamber, the stator comprises a stator winding, and the first oil injection hole directly faces the stator winding.

15. The stator according to claim 1, wherein the first oil ring comprises a plurality of first oil inlet chambers and a plurality of first oil outlet chambers, the plurality of first oil inlet chambers and the plurality of first oil outlet chambers are interleaved, and the plurality of first oil inlet chambers are communicated with each other at an end away from the stator core in the axial direction.

16. The stator according to claim 1, further comprising a second oil ring arranged at the second end of the stator core, wherein the second oil ring is coaxial with the stator core, and the second oil ring comprises a second oil inlet chamber communicated with the second oil inlet and a second oil outlet chamber communicated with the first oil outlet.

17. The stator according to claim 16, wherein an outer surface of the second oil ring comprises a second groove and a second boss arranged in the circumferential direction and extending in the axial direction, the second groove forms the second oil inlet chamber, an end surface of the second boss facing the stator core defines the second oil outlet chamber, and the second oil outlet chamber extends in the axial direction.

18. The stator according to claim 17, wherein an inner surface of the second oil ring defines a second oil injection hole, the second oil injection hole is communicated with the second oil outlet chamber, the stator comprises a stator winding, and the second oil injection hole directly faces the stator winding.

19. An oil cooling motor, comprising: a housing defining a housing oil inlet; a stator comprising: a stator core of a hollow columnar structure, the stator core comprising a first end and a second end in an axial direction, the stator core defining a first oil cooling channel and a second oil cooling channel, the first oil cooling channel and the second oil cooling channel being through in the axial direction, the first oil cooling channel having a first oil inlet at the first end and a first oil outlet at the second end, the second oil cooling channel having a second oil outlet at the first end and a second oil inlet at the second end, and at the first end, the first oil inlet and the second oil outlet being arranged along a circumferential direction of the stator core and located on a same circumference centered around an axis of the stator core; and a first oil ring arranged at the first end of the stator core, wherein the first oil ring is coaxial with the stator core, and the first oil ring comprises a first oil inlet chamber communicated with the first oil inlet and a first oil outlet

chamber communicated with the second oil outlet; wherein the stator is arranged in the housing, and the first oil inlet and the second oil inlet of the stator core are communicated with the housing oil inlet.
