

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250280966
Kind Code	A1
Publication Date	September 11, 2025
Inventor(s)	Alletto, Jr.; Eugene

CUSTOMIZABLE MATTRESS

Abstract

A customizable mattress includes a chassis defining a cavity. A spring pack is removably positioned within the cavity. A top pad removably covers at least a portion of the spring pack. In some embodiments, kits and methods of use are provided.

Inventors:	Alletto, Jr.; Eugene (Glen Head, NY)
Applicant:	BEDGEAR, LLC (Farmingdale, NY)
Family ID:	57944054
Assignee:	BEDGEAR, LLC (Farmingdale, NY)
Appl. No.:	19/169316
Filed:	April 03, 2025

Related U.S. Application Data

parent US division 17470252 20210909 parent-grant-document US 12318011 child US 19169316
parent US division 15220964 20160727 ABANDONED child US 17470252
us-provisional-application US 62200378 20150803

Publication Classification

Int. Cl.: **A47C27/00** (20060101); **A47C23/00** (20060101); **A47C27/05** (20060101); **A47C27/06** (20060101); **A47C27/07** (20060101)

U.S. Cl.:

CPC **A47C27/001** (20130101); **A47C23/002** (20130101); **A47C27/053** (20130101); **A47C27/062** (20130101); **A47C27/064** (20130101); **A47C27/07** (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure generally relates to bedding, and more particularly to customizable mattresses that include variable components that allow a sleeper to create a mattress that has performance characteristics specifically tailored to the sleeper's body type and/or sleep preferences while also allowing the sleeper to replace the variable components with other variable components should the variable components become worn and/or the sleeper's body type or sleep preferences change over time.

BACKGROUND

[0002] Sleep is critical for people to feel and perform their best, in every aspect of their lives. Sleep is an essential path to better health and reaching personal goals. Indeed, sleep affects everything from the ability to commit new information to memory to weight gain. It is therefore essential for people to use bedding that suit both their personal sleep preference and body type in order to achieve comfortable, restful sleep.

[0003] Certain components of a mattress, such as, for example, springs and/or a mattress topper may become worn before other components of the mattress. It would thus be beneficial to provide a mattress that allows some components to be replaced without replacing the entire mattress. Indeed, replacing the springs of a mattress, for example, without replacing other components of the mattress would significantly reduce the cost to the user who would otherwise have to buy a new mattress if the springs become worn or otherwise in need of replacement.

[0004] Furthermore, sleeper's body type may change over time. For example, a sleeper may lose or gain weight. The change in weight may be slight or significant. When the change in weight is significant, it may affect the type of bedding the sleeper requires to achieve restful sleep. For example, a significant gain in weight may require that a sleeper use a firmer mattress, to provide support for the added weight. The sleeper's sleep preference may also change over time. For example, a sleeper who typically likes to sleep on their back may, over time, prefer to sleep on his or her side. The change in sleep preference may affect the type of bedding the sleeper requires to achieve restful sleep. For example, a sleeper changing from a back sleeper to a side sleeper may require that the sleeper use a firmer mattress.

[0005] Accordingly, this disclosure is directed to customizable mattresses that include variable components that allow a sleeper to create a mattress that has performance characteristics specifically tailored to the sleeper's body type and/or sleep preferences while also allowing the sleeper to replace the variable components with other variable components over time should the variable components become worn and/or the sleeper's body type or sleep preferences change over time.

SUMMARY

[0006] A customizable mattress is provided, in accordance with the principles of the present disclosure. The customizable mattress includes a chassis that defines a cavity. A spring pack is removably positioned within the cavity. A top pad removably covers at least a portion of the spring pack. In some embodiments, the customizable mattress includes an outer lower covering that surrounds at least a portion of the chassis. In some embodiments, the customizable mattress includes retention fabric that covers at least a portion of the top pad.

[0007] In some embodiments, the spring pack is divided into a first side configured to support a first sleeper and a second side configured to support a second sleeper, the first side being removably coupled to the second side. In some embodiments, the spring pack is divided into a first side configured to support a first sleeper and a second side configured to support a second sleeper, the first side interlocking with the second side such that the first side is removably coupled to the

second side. In some embodiments, the spring pack is divided into a first side configured to support a first sleeper and a second side configured to support a second sleeper, the first side comprising a series of recesses, the second side comprising a series of projections disposed in the recesses to interlock the first side with the second side such that the first side is removably coupled to the second side. In some embodiments, the spring pack is divided into a first side configured to support a first sleeper and a second side configured to support a second sleeper, the first side being removably coupled to the second side, the first side having a different firmness than the second side. In some embodiments, the spring pack comprises a plurality of rows of springs, the springs in each row being connected to one another by a piece of material. In some embodiments, the material comprises at least one slit positioned between adjacent springs to prevent or limit movement of one of the adjacent springs when another one of the adjacent springs moves. In some embodiments, the material comprises welds positioned between adjacent springs to prevent or limit movement of one of the adjacent springs when another one of the adjacent springs moves.

[0008] In some embodiments, the chassis comprises a foam or formed plastic or similar material. In some embodiments, the chassis comprises a top portion, a bottom portion opposite the top portion and opposite side portions that extend between the top and bottom portions, the top and bottom portions each being removably coupled to the side portions. In some embodiments, the chassis comprises a top portion, a bottom portion opposite the top portion and opposite side portions that extend between the top and bottom portions, the side portions each including opposite first and second mortises, the top portion comprising tenons that fit into the first mortises to connect the top portion with the side portions, the bottom portion comprising tenons that fit into the second mortises to connect the top portion with the side portions. In some embodiments, the chassis comprises a top portion, a bottom portion opposite the top portion and opposite first and second side portions that extend between the top and bottom portions, the first side portion including opposite first and second mortises, the second side portion including opposite third and fourth mortises, the top portion including opposite fifth and sixth mortises, the bottom portion including opposite seventh and eighth mortises, the mattress further comprising a first corner piece comprising tenons that fit into the first and fifth mortises, a second corner pieces comprising tenons that fit into the second and seventh mortises, a third corner piece that fits into the third and sixth mortises and a fourth corner piece comprising tenons that fit into the fourth and eighth mortises to join the first and second side portions with the top and bottom portions.

[0009] In one embodiment, in accordance with the principles of the present disclosure, a kit is provided. The kit includes a customizable mattress having a chassis that defines a cavity. A spring pack is removably positioned within the cavity. A top pad removably covers at least a portion of the spring pack. In some embodiments, the customizable mattress includes an outer lower covering that surrounds at least a portion of the chassis. In some embodiments, the customizable mattress includes retention fabric that covers at least a portion of the top pad. In some embodiments, the spring pack comprises a plurality of spring packs each having a different firmness and the top pad comprises a plurality of top pads each having a different firmness. In some embodiments, the kit includes instructions for selecting one of the spring packs and one of the top pads based upon a sleeper's body type and/or sleep preference.

[0010] In one embodiment, in accordance with the principles of the present disclosure, a method is provided. The method includes the steps of: providing a kit that includes a customizable mattress having a chassis that defines a cavity, spring pack removably positioned within the cavity, a top pad removably covering at least a portion of the spring pack, an outer lower covering that surrounds at least a portion of the chassis and retention fabric that covers at least a portion of the top pad, wherein the spring pack comprises a plurality of spring packs each having a different firmness and the top pad comprises a plurality of top pads each having a different firmness; selecting one of the spring packs based upon a sleeper's first body type and/or sleep preference; selecting one of the top pads based upon the sleeper's first body type and/or sleep preference; positioning the selected

spring pack in the cavity; and covering the selected spring pack with the selected top pad. In some embodiments, the method includes the steps of: removing the selected top pad from the selected spring pack; removing the selected spring pack from the cavity; selecting a second spring pad based upon an updated second body type and/or sleep preference; positioning the selected second spring pad within the cavity; selecting a second top pad based upon the updated second body type and/or sleep preference; and covering the selected second spring pack with the selected second top pad. In some embodiments, the selected second spring pack has a firmness that is different than that of the selected spring pack and the selected second top pad has a firmness that is different than that of the selected top pad. In some embodiments, the method includes the steps of: removing the selected top pad from the selected spring pack after the selected top pad becomes worn; removing the selected spring pack from the cavity after the selected spring pad becomes worn; selecting a second spring pad; positioning the selected second spring pad within the cavity; selecting a second top pad; and covering the selected second spring pack with the selected second top pad.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The present disclosure will become more readily apparent from the specific description accompanied by the following drawings, in which:

[0012] FIG. 1 is a perspective view of a bedding system in accordance with the present disclosure;

[0013] FIG. 2A shows one step in the assembly of the bedding system shown in FIG. 1;

[0014] FIG. 2B shows one step in the assembly of the bedding system shown in FIG. 1;

[0015] FIG. 2C shows one step in the assembly of the bedding system shown in FIG. 1;

[0016] FIG. 2D shows one step in the assembly of the bedding system shown in FIG. 1;

[0017] FIG. 2E shows one step in the assembly of the bedding system shown in FIG. 1;

[0018] FIG. 2F shows one step in the assembly of the bedding system shown in FIG. 1;

[0019] FIG. 3 is a top view of components of the bedding system shown in FIG. 1;

[0020] FIG. 3A is a perspective view of one embodiment of a component of the bedding system shown in FIG. 1;

[0021] FIG. 3B is a perspective, breakaway view of one embodiment of a component of the bedding system shown in FIG. 1;

[0022] FIG. 4A is a top view of a component of the bedding system shown in FIG. 1;

[0023] FIG. 4B is a top view of a component of the bedding system shown in FIG. 1;

[0024] FIG. 4C is a top view of a component of the bedding system shown in FIG. 1;

[0025] FIG. 5A is a top view of one embodiment of a component of the bedding system shown in FIG. 1;

[0026] FIG. 5B is a top view of one embodiment of a component of the bedding system shown in FIG. 1;

[0027] FIG. 5C is a top view of one embodiment of a component of the bedding system shown in FIG. 1;

[0028] FIG. 6A is a top view of one embodiment of a component of the bedding system shown in FIG. 1;

[0029] FIG. 6B is a top view of one embodiment of a component of the bedding system shown in FIG. 1;

[0030] FIG. 6C is a top view of one embodiment of a component of the bedding system shown in FIG. 1;

[0031] FIG. 7 is a perspective, breakaway view of a component of the bedding system shown in FIG. 1;

[0032] FIG. 8A is a side view of one embodiment of a component of the bedding system shown in

FIG. 1;

[0033] FIG. 8B is a side view of one embodiment of a component of the bedding system shown in FIG. 1;

[0034] FIG. 8C is a side view of one embodiment of a component of the bedding system shown in FIG. 1;

[0035] FIG. 9 shows a comparison between a component of the bedding system shown in FIG. 1 and prior art components;

[0036] FIG. 10 is a perspective view of one embodiment of components of the bedding system shown in FIG. 1, with parts separated;

[0037] FIG. 10A is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0038] FIG. 11A is a side view of a component of the bedding system shown in FIG. 1;

[0039] FIG. 11B is a perspective view of a component of the bedding system shown in FIG. 1;

[0040] FIG. 11C is a top view of a component of the bedding system shown in FIG. 1;

[0041] FIG. 11D is a perspective view of a component of the bedding system shown in FIG. 1;

[0042] FIG. 12 is a perspective view of components of the bedding system shown in FIG. 1;

[0043] FIG. 12A is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0044] FIG. 12B is a side view of one embodiment of components of the bedding system shown in FIG. 1;

[0045] FIG. 12C is a perspective view of one embodiment of a component of the bedding system shown in FIG. 1;

[0046] FIG. 12D is a perspective view of one embodiment of a component of the bedding system shown in FIG. 1;

[0047] FIG. 13A is a perspective view of one embodiment of a component of the bedding system shown in FIG. 1;

[0048] FIG. 13B is a perspective view of one embodiment of a component of the bedding system shown in FIG. 1;

[0049] FIG. 13C is a perspective view of one embodiment of a component of the bedding system shown in FIG. 1;

[0050] FIG. 13D is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0051] FIG. 13E is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0052] FIG. 13F is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0053] FIG. 14 is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0054] FIG. 15 is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0055] FIG. 15A is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0056] FIG. 15B is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0057] FIG. 15C is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0058] FIG. 15D is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0059] FIG. 15E is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0060] FIG. 15F is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0061] FIG. 16 is a schematic showing elements of assembly of the bedding system shown in FIG. 1;

[0062] FIG. 17 shows instructions for customizing the bedding system shown in FIG. 1;

[0063] FIG. 17A shows details concerning zoning choices for the bedding system shown in FIG. 1;

[0064] FIG. 17B shows details concerning zoning choices for the bedding system shown in FIG. 1;

[0065] FIG. 17C shows details concerning zoning choices for the bedding system shown in FIG. 1;

[0066] FIG. 17D shows details concerning zoning choices for the bedding system shown in FIG. 1;

[0067] FIG. 17E-1 shows details concerning zoning choices for the bedding system shown in FIG. 1;

[0068] FIG. 17E-2 shows two sleepers atop a component of the bedding system shown in FIG. 1;

[0069] FIG. 17F shows perspective views of embodiments of the bedding system shown in FIG. 1;

[0070] FIG. 18 shows a chart used to customize the bedding system shown in FIG. 1;

[0071] FIG. 18A is a perspective view of the bedding system shown in FIG. 1 in a retail setting;

[0072] FIG. 19 is a perspective view of a bedding system in accordance with the present disclosure, with parts separated;

[0073] FIG. 20A is a perspective view of the bedding system shown in FIG. 19;

[0074] FIG. 20B is a perspective view of the bedding system shown in FIG. 19;

[0075] FIG. 21 is a side, breakaway view, in part phantom of components of the bedding system shown in FIG. 19;

[0076] FIG. 22 is a side, cross sectional view of components of the bedding system shown in FIG. 19;

[0077] FIG. 23 is a top view of one embodiment of components of the bedding system shown in FIG. 1;

[0078] FIG. 24 is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0079] FIG. 25 is a perspective view of one embodiment of components of the bedding system shown in FIG. 1;

[0080] FIG. 26 shows details of a method used in connection with the bedding system shown in FIG. 1;

[0081] FIG. 27 shows details of a method used in connection with the bedding system shown in FIG. 1;

[0082] FIG. 28 shows details of a method used in connection with the bedding system shown in FIG. 1; and

[0083] FIG. 29 shows details of a method used in connection with the bedding system shown in FIG. 1.

[0084] Like reference numerals indicate similar parts throughout the figures.

DETAILED DESCRIPTION

[0085] The present disclosure may be understood more readily by reference to the following detailed description of the disclosure taken in connection with the accompanying drawing figures, which form a part of this disclosure. It is to be understood that this disclosure is not limited to the specific devices, conditions or parameters described and/or shown herein, and that the terminology used herein is for the purpose of describing particular embodiments by way of example only and is not intended to be limiting of the claimed disclosure.

[0086] The present disclosure is directed to customizable mattresses. In some embodiments, a mattress fitting method is provided for selecting components of a customizable mattress based upon body type and sleep position. In some embodiments, the mattress fitting method includes selecting a mattress category based on quality, price and/or value. In some embodiments, the mattress category is based upon the number of zones in the mattress. For example, one of the

categories may include mattresses that have one zone such that the mattress is universal from head to foot; one of the categories may include mattresses that have three zones from head to foot; and one of the categories may include mattresses that have five or more zones or have additional zoning custom molded to a sleeper's body. In some embodiments, the additional zoning is determined by sinking the sleeper into a waterbed-like structure and using 3D mapping so that every location on the mattress is zoned to the sleeper's specific body contours, similar to racing car seats and dental molding. In some embodiments, the mattress categories are assigned numerical values for different ascending degrees of performance materials, personalized fit, and durability based on body type. In some embodiments, the numerical values of the mattress categories are 3, 5 and 7. In some embodiments, the mattress fitting method includes selecting the mattress category and selecting a level based upon body type and/or sleep position. In some embodiments, the levels are assigned numerical values for different body types and/or sleep positions. In some embodiments, the numerical values of the levels are 0, 1, 2 and 3. In some embodiments, the body types include small, medium and large body frames. In some embodiments, the body types include narrow, medium and broad body frames. In some embodiments, the sleep positions include stomach, back, side and multiple positions. In some embodiments, the multiple positions include any combination of stomach, back and side.

[0087] In some embodiments, the customizable mattress includes “driver vs. passenger” independent suspension choices that interlink and can be interchanged, to either side of the bed, as well as replaced over time. In some embodiments, the independent suspension is provided by springs or spring-like inner core support structures that stand and operate separately from each other via various methods of construction so the sleeper gets balanced support and flexibility with reduced motion transfer to other body areas and/or another sleeper. In some embodiments, the independent suspension includes a plurality of springs that each are positioned within spring pocket, the spring pockets being connected to one another by fabric. In some embodiments, the fabric is a flexible fabric that allows full individual movement that avoids dragging down adjoining springs. In some embodiments, the fabric includes sonic welds that define the spring pockets. A slit may be cut into the fabric between two rows of sonic welds to allow full individual movement that avoids dragging down adjoining springs. In some embodiments, the independent suspension includes a plurality of cradles each having a spring positioned therein to allow full individual movement that avoids dragging down other springs. In some embodiments, the springs snap into a cap and a base and include a cord between the cap and the base to give the spring a constant height. In some embodiments, the caps include a logo, such as, for example, a logo of the mattress manufacturer.

[0088] In some embodiments, an easy to ship and/or easy to carry packaging method is provided for transporting a customizable mattress. In some embodiments, the easy to ship and/or easy to carry packaging method includes packaging a modular customizable mattress in three or more boxes. In some embodiments, one box includes a first inner spring inner core of the customizable mattress. In some embodiments, one box includes a second inner spring inner core of the customizable mattress. In some embodiments, one box includes a frame or chassis of the customizable mattress. In some embodiments, one box includes a zippered topper or upper cover of the customizable mattress. In some embodiments, the chassis is made from a foam material, such as, for example, dual durometer foam or injection molded latex. In some embodiments, the easy to ship and/or easy to carry packaging method allows the modular pieces of the customizable mattress to be assembled at the moment of delivery by a retail store driver. In some embodiments, the easy to ship and/or easy to carry packaging method requires only a single driver, such as, for example, a delivery person, drone or UPS delivery to transport the modular pieces of the customizable mattress from a factory or warehouse to an end user.

[0089] In some embodiments, an easy to fit shopper and/or easy to return method is provided for purchasing and/or returning a customizable mattress. In some embodiments, the easy to fit shopper

and/or easy to return method includes providing an SKU optimized for a retailer. In some embodiments, the easy to fit shopper and/or easy to return method includes providing the least amount of SKUs, while providing the most options. In some embodiments, the easy to fit shopper and/or easy to return method includes swapping independent suspension cores or power plants to alternate sides such that the independent suspension cores still interlink. In some embodiments, the easy to fit shopper and/or easy to return method includes reselecting a support level.

[0090] In some embodiments, a subscription sales method is provided for purchasing replacement components for a customizable mattress. In some embodiments, the subscription sales method includes collecting customer information. In some embodiments, the subscription sales method includes reaching out to customers periodically, such as, for example, annually. In some embodiments, the subscription sales method includes reaching out to customers based upon the date the customizable mattress was purchased (mattress birthday). In some embodiments, the subscription sales method includes renewing the subscription.

[0091] In some embodiments, the customizable mattress includes an adjustable chassis that allows for articulation of one portion of the chassis relative to other portions of the chassis. In some embodiments, the adjustable chassis is manual or electric. In some embodiments, the adjustable chassis includes motion devices embedded within the chassis. In some embodiments, the customizable mattress includes a self-enclosed powered adjustable chassis.

[0092] In some embodiments, the chassis includes “X” technology that provides features of an ambient to allow the chassis to circulate and generate airflow within one or more zones. In some embodiments, the “X” technology allows the chassis to circulate and generate airflow without having air blow on the sleeper. That is, the airflow is similar to that of a radiant floor to provide creature comfort. In some embodiments, the “X” technology allows the chassis to be as efficient in heating and/or cooling the environment surrounding the customizable mattress for the sleeper's comfort as well as the system itself. In some embodiments, topper pads have a material surface texture for comfort and pressure sensitivity. In some embodiments, the customizable mattress includes various topper attachment concepts that allow for easy replacement and/or reselection of the comfort layer. In some embodiments, the topper attachment concepts include carabineer style connections. In some embodiments, the topper attachment concepts include stretched straps that connect the topper pad to a lower mattress. In some embodiments, the lower mattress is made from woven tent material. In some embodiments, the topper attachment concepts include hot rod strap style connections. In some embodiments, the topper attachment concepts include leather straps that connect the topper pad to a lower mattress.

[0093] In some embodiments, the customizable mattress includes a chassis that defines a cavity, two spring packs removably positioned within the cavity and a top pad that removably covers at least a portion of the spring pack. The spring packs and the top pad may have variable components. That is, different versions of the spring packs and the top pad are available to allow a sleeper to customize the mattress to suit his or her preferred sleep position and/or body type. In some embodiments, three versions of the spring packs are available and include a soft spring pack, a medium spring pack and a firm spring pack. In that each mattress includes two spring packs, this allows for six combinations: soft/soft, medium/medium, firm/firm, soft/medium, soft/firm and medium/firm. Furthermore, left/right reversals of the spring packs double the number of combinations. In some embodiments, the two spring packs of a given mattress interlock to allow a blend of firmness at the center. In some embodiments, the spring packs interlock using a one row, one spring blend. In some embodiments, the spring packs interlock using a two row, one spring blend. In some embodiments, the spring packs interlock using a one row, two spring blend. In some embodiments, three versions of the top pads are available and include a soft top pad, a medium top pad and a firm top pad. In some embodiments, the top pads include stitching that forms a pattern in the top pads. For example, in one embodiment, the top pads include a pattern that resembles a flame.

[0094] In some embodiments, the chassis is made from molded foam, carbon fiber or fiberglass or other thermo-molded plastic-like material foundation that shapes the interior or the exterior. In some embodiments, sculpting the exterior gives the mattress a unique appearance. In some embodiments, the chassis is made up of a plurality of separate pieces and the customizable mattress includes an outer lower cover that surrounds at least a portion of the chassis to hold the separate pieces together. The chassis may be rolled for delivery, with the outer lower cover coupled to the chassis. After delivery, chassis is unrolled, with the outer lower cover coupled to the chassis. Any of the separate pieces that are not connected to the chassis are then connected to the chassis. Selected spring packs are positioned within a cavity of the chassis. A top pad is then positioned over the spring packs.

[0095] Also, as used in the specification and including the appended claims, the singular forms “a,” “an,” and “the” include the plural, and reference to a particular numerical value includes at least that particular value, unless the context clearly dictates otherwise. Ranges may be expressed herein as from “about” or “approximately” one particular value and/or to “about” or “approximately” another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by use of the antecedent “about,” it will be understood that the particular value forms another embodiment. It is also understood that all spatial references, such as, for example, horizontal, vertical, top, upper, lower, bottom, left and right, are for illustrative purposes only and can be varied within the scope of the disclosure. For example, the references “upper” and “lower” are relative and used only in the context to the other, and are not necessarily “superior” and “inferior”.

[0096] The following discussion includes a description of a customizable mattress in accordance with the principles of the present disclosure. Alternate embodiments are also disclosed. Reference will now be made in detail to the exemplary embodiments of the present disclosure, which are illustrated in the accompanying figures. Turning to FIGS. **1-29**, there are illustrated components of a bedding system **10**.

[0097] System **10** includes a mattress **12**. Mattress **12** is configured to be customizable to create a mattress that has performance characteristics specifically tailored to the sleeper's body type and/or sleep preferences while also allowing the sleeper to replace components with other components should the components become worn and/or the sleeper's body type or sleep preferences change over time. Mattress **12** includes a chassis **14** having an inner surface that defines a cavity **16**, as shown in FIG. **2**. A pair of spring packs **18** are removably positioned within cavity **16**, as also shown in FIG. **2**. A top pad **20** removably covers at least a portion of spring pack **18**.

[0098] In some embodiments, shown in FIGS. **2** and **3**, chassis **14** includes a base **22**, opposite first and second side portions **22a**, **22b** that extend upwardly from base **22**, a top portion **22c** and a bottom portion **22d** opposite top portion **20c**, top and bottom portions **20c**, **20d** each extending between first and second side portions **22a**, **22b**. In some embodiments, first and second side portions **22a**, **22b** are fixed to base **22** and top and bottom portions **20c**, **20d** are removably connected to first and second side portions **22a**, **22b** and base **22**. First side portion **22a** includes opposite first and second mortises **24**, second side portion **22b** includes opposite third and fourth mortises **24**, top portion includes opposite fifth and sixth mortises **24** and bottom portion **22d** includes opposite seventh and eighth mortises **24**. Chassis **14** includes a first corner piece **26** comprising tenons **28** that fit into first and fifth mortises **24**, a second corner pieces comprising tenons **28** that fit into second and seventh mortises **24**, a third corner piece **26** that fits into third and sixth mortises **24** and a fourth corner piece **26** comprising tenons **28** that fit into the fourth and eighth mortises to join first and second side portions **22a**, **22b** with top and bottom portions **22c**, **22d**. A planar surface of base **22** and inner surfaces of first and second side portions **22a**, **22b**, top portion **22c** and bottom portion **22d** define the inner surface of chassis **14** that defines cavity **16**. One particular embodiment of chassis **14** is shown in FIG. **3A**.

[0099] In one embodiment, shown in FIG. 3B, chassis **14** includes at least one opening that defines a vent **25** extending through opposite inner and outer surfaces of chassis **14**. Vents **25** are configured to allow air flow in and out of cavity **60**. That is, vents **25** allow air to circulate and exchange from an inner core of mattress **12** to a room environment. In one embodiment, vent **25** is molded into sides of chassis **14**, such as, for example, at least one of side portions **22a**, **22b**. Each vent **25** includes a mesh material **35** positioned therein. Mesh material **35** acts as a filter to trap particulate matter as air flows in and out of cavity **60**. In some embodiments, at least one of base **22**, first and second side portions **22a**, **22b** and top portion **22c** includes one or more vent **25**. In some embodiments, at least one of vents **25** is positioned within a recessed cavity of chassis **14**.

[0100] In some embodiments, mattress **12** comprises an outer lower covering **30** that surrounds or encloses at least a portion of chassis **14**, as shown in FIGS. 2 and 3. In some embodiments, outer lower covering **30** covers an entire bottom surface of base **22**, entire outer surfaces of first and second side portions **22a**, **22b**, entire outer surfaces of top and bottom portions **22c**, **22d**, at least a portion of top surfaces of first and second side portions **22a**, **22b** and at least a portion of top surfaces of top and bottom portions **22c**, **22d**. In some embodiments, outer lower cover **30** may be configured to entirely cover the top surfaces of first and second side portions **22a**, **22b** and/or the top surfaces of top and bottom portions **22c**, **22d**. In some embodiments, outer lower cover **30** may be configured to entirely cover corner pieces **26**. In some embodiments, outer lower cover **30** includes curved corners that each cover at least a portion of one of corner pieces **26**. In some embodiments, outer lower covering **30** includes a mesh material.

[0101] In some embodiments, chassis **14** may be rolled for delivery, with outer lower cover **30** coupled to chassis **14**. In some embodiments, top and bottom portions **22c**, **22d** have been removed from chassis **14** prior to rolling chassis **14**. After delivery, chassis **14** is unrolled; with outer lower cover **30** coupled to chassis **14**. Tenons **28** of corner pieces **26** are positioned in mortises **24** of first and second side portions **22a**, **22b** and top and bottom portions **22c**, **22d** in the manner discussed above. Either before or after spring packs **18** are positioned within cavity **16**, outer lower cover **30** may be moved relative to top and bottom portions **22c**, **22d** such that outer lower cover **30** covers at least a portion of top and bottom portions **22c**, **22d**.

[0102] In some embodiments, spring packs **18** include a first spring pack **18a**, a second spring pack **18b** and a third spring pack **18c**, as shown in FIGS. 4A-4C. Spring packs **18a**, **18b**, **18c** are identical in terms of size and shape, but differ with regard to firmness. For example, spring pack **18b** may be firmer than spring pack **18a** and spring pack **18c** may be firmer than spring pack **18b**. In some embodiments, system **10** may include one or a plurality of additional spring packs each having a firmness that is different than that of spring packs **18a**, **18b**, and **18c**. In that mattress **12** includes two spring packs **18**, providing spring packs **18a**, **18b**, and **18c** with different firmnesses allows for six combinations: soft/soft, medium/medium, firm/firm, soft/medium, soft/firm and medium/firm. In some embodiments, spring packs **18a**, **18b**, **18c** are formed from the same material. In some embodiments, spring packs **18a**, **18b**, **18c** are formed from different materials.

[0103] In some embodiments, spring packs **18** each include projections **32** that are configured to be positioned within recesses **34** of another one of spring packs **18**, such as, for example, one of spring packs **18a**, **18b**, **18c**. Spring packs **18** each include a plurality of springs **36**, as shown in FIGS. 5A-5C. In one embodiment, shown in FIGS. 5A and 6A, projections **32** of spring packs **18** are each made up of one spring **36** and recesses **32** span the cross sectional distance or width of one spring **36** such that spring packs **18** have a one row one spring blend, as shown in FIGS. 5A and 6A.

[0104] In one embodiment, shown in FIGS. 5B and 6B, projections **32** of spring packs **18** are each made up of four springs **36** that are arranged to have a pyramidal or triangular configuration. That is, a tip of each projection **32** spans the cross sectional distance or width of one spring **36** and a base of each projection **32** that the tip extends from spans the cross sectional distance or width of three springs **36**. Recesses **32** each have a narrowed first end portion that receives the tip of one of projections **32**. The first end portion of recess **32** spans the cross sectional distance or width of one

spring **36**. Recesses **32** also include an enlarged second end portion that spans the cross sectional distance or width of three springs **36**. The enlarged second end portion of recess **32** receives the base of one of projections **32** such that spring packs **18** have a two row one spring blend, as shown in FIGS. **5B** and **6B**.

[0105] In one embodiment, shown in FIGS. **5C** and **6C**, projections **32** of spring packs **18** are each made up of two springs **36** and recesses **32** span the cross sectional distance or width of two springs **36** such that spring packs **18** have a one row two spring blend, as shown in FIGS. **5C** and **6C**.

[0106] In some embodiments, shown in FIGS. **7-9**, springs **36** are positioned in spring pockets **38**. Spring pockets **38** comprise a fabric that each enclose one of springs **36**. Adjacent spring pockets **38** are joined to one another by a material **40**. In some embodiments, material **40** is the same material as the fabric that makes up spring pockets **38**. In some embodiments, material **40** is a different material than the fabric that makes up spring pockets **38**. In some embodiments, spring pockets **38** include welds, such as, for example, sonic welds **42** that provide strength to spring pockets **38**. In some embodiments, welds **42** are double weld rows, as shown in FIG. **9**.

[0107] In one embodiment, shown in FIG. **8**, material **40** is free of any slits or vertical cuts. In some embodiments, shown in FIGS. **7** and **8B-9**, material **40** includes a slit **44** between adjacent welds **42**. In some embodiments, slits **44** are positioned between double welds **42**, as shown in FIG. **9**. Slits **44** allow a spring **36** in a spring pocket **38** to be compressed without compressing springs **36** in adjacent spring pockets **38**, as shown in FIG. **9**. That is, without slits **44**, compressing a spring **36** in a spring pocket **38** will also compress springs **36** in adjacent spring pockets **38**, as also shown in FIG. **9**. In one embodiment, shown in FIG. **8B**, slits **44** are made by making a short cut into material **40**. In this embodiment, slits **44** are between $0\text{-}\frac{1}{3}$ the height of material **40**, wherein the height of material **40** is defined by the height of springs **36** when springs are not compressed. In one embodiment, shown in FIG. **8C**, slits **44** are made by making a longer cut into material **40**. In this embodiment, slits **44** are between $\frac{1}{3}\text{-}\frac{1}{2}$ the height of material **40**, wherein the height of material **40** is defined by the height of springs **36** when springs are not compressed. In some embodiments, slits **44** are between $\frac{1}{2}\text{-}\frac{3}{4}$ the height of material **40**, wherein the height of material **40** is defined by the height of springs **36** when springs are not compressed.

[0108] In one embodiment, shown in FIG. **10**, chassis **14** includes a plurality of cradles **46** that each house one of springs **36**. Cradles **46** are fixed to chassis **14**. Cradles **46** each have a cylindrical configuration with an open top that allows springs **36** to be positioned therein. In some embodiments, cradles **46** each have a height that is less than that of springs **36** when springs **36** are not compressed such that top portions of springs **36** will extend out of cradles **46** when springs **36** are not compressed. In some embodiments, cradles **46** each have a height that is equal to that of springs **36** when springs **36** are compressed such that top portions of springs **36** will be flush with top portions of cradles **46** when springs **36** are compressed. That is, cradles **46** will fully surround springs **36** when springs **36** are compressed. In some embodiments, cradles **46** each have a height that is less than that of springs **36** when springs **36** are compressed such that top portions of springs **36** will extend out of cradles when springs **36** are compressed. Cradles **46** are spaced apart from one another such that when one spring **36** is compressed, cradles **46** prevent adjacent springs **36** from compressing. That is, cradles **46** allow springs **36** to stand and operate separately from other springs **36**.

[0109] In one embodiment, shown in FIG. **10A**, chassis **14** includes a plurality of cradles **47** that each house a lower portion of one of springs **36**. Cradles **47** are fixed relative to chassis **14**. In some embodiments, cradles **47** are formed from a silicon membrane. Cradles **47** each have a cylindrical configuration with an open top that allows the lower portions of springs **36** to be positioned therein. In some embodiments, cradles **47** each have a height that is less than that of springs **36** when springs **36** are not compressed such that top portions of springs **36** will extend out of cradles **46** when springs **36** are not compressed. Top pad **20** includes a plurality of spring cups **49** each configured to receive a top portion of one of springs **36**. Spring cups **49** are fixed relative to top pad

20. Each of spring cups **49** is coaxial with one of cradles **47** such that when springs are positioned within cradles **47** and spring cups **49**, an interlocking upper and lower mattress is created that does not need the support of side foam. This allows for the use of a mesh and/or breathable material to be used in place of side foam. As such, in this embodiment, chassis **14** may include a perforate side mesh to allow mattress **12** to breath, unlike traditional side foam.

[0110] In one embodiment, shown in FIGS. **11A-11D**, springs **36** each include a cap **48a**, a base **48b**, a coiled element **48c** and a cord **48d**. Cord **48** extends between cap **48a** and base **48b** such that cap **48a** and base **48b** each extend perpendicular to cord **48d**. In some embodiments, cord **48d** includes at least one bend, as shown in FIG. **11B**. Cord **48d** is configured to provide spring **36** with a constant height. That is, cord **48d** ensures that spring **36** cannot be compressed to have a height that is less than that of cord **48d**. A first end of coiled element **48c** is fixed to cap **48a** and an opposite second end of coiled element **48c** is fixed to base **48b**. In some embodiments, cap **48a** and base **48b** each include an arcuate cavity **48e** configured to receive one of the first and second ends of coiled element **48c**, as shown in FIGS. **11A** and **11B**. In some embodiments, the first and second ends of coiled element **48c** are configured to snap into cavities **48e**. In some embodiments, cap **48a** includes a logo, such as, for example, the logo of the manufacturer of mattress **12** that faces away from base **48b**.

[0111] In one embodiment, shown in FIG. **12**, spring packs **18** have an egg carton-like configuration that includes a plurality of spaced apart cavities **50** each having a bottom portion of one of springs **36** positioned therein. Spacing cavities **50** apart from one another also spaces springs **36** apart from one another. In this embodiment, spring packs **18** do not include any sleeves or spring pockets, such as, for example, spring pockets **38**. This allows better airflow between adjacent springs **36**. In the embodiment shown in FIG. **12**, base **48b** includes a dowel **49** and cap **48a** includes a sleeve **51** having a passageway configured to receive dowel **49** therein. Dowel **49** is movable within sleeve **51** such that cap **48a** moves toward base **48b** as coiled element **48c** compresses and cap **48a** moves away from base **48b** as coiled element **48c** decompresses or expands. In this embodiment, spring **36** comprises a plastic or rubberized material to hold the spring in tension to control firmness.

[0112] In one embodiment, shown in FIGS. **12B-12D**, top pad **20** may include cavities **50a** configured to receive top portions of springs **36**. Positioning springs **36** within cavities **50**, **50a** secures springs **36** between chassis **14** and top pad **20**. As shown in FIG. **12D**, spring **36** may be formed from a plurality of layers each having an undulating configuration. In particular, concave portions of a first undulating layer are in direct contact with convex portions of a second undulating layer and convex portions of the first undulating layer are in direct contact with concave portions of a third undulating layer, the first undulating layer being positioned between the second and third undulating layers. In some embodiments, spring **36** is formed from a single strip of material that is coiled to form the undulating layers.

[0113] In some embodiments, top pads **20** include a first top pad **20a**, a second top pad **20b** and a third top pad **20c**, as shown in FIGS. **13A-13C**. In some embodiments, top pads **20a**, **20b**, **20c** are identical in terms of size and shape, but differ with regard to firmness. For example, top pad **20b** may be firmer than top pad **20a** and top pad **20c** may be firmer than top pad **20b**. In some embodiments, system **10** may include one or a plurality of additional top pads each having a firmness that is different than that of spring packs **18a**, **18b**, and **18c**. In some embodiments, top pads **20a**, **20b**, **20c** are formed from the same material. In some embodiments, top pads **20a**, **20b**, **20c** are formed from different materials. In some embodiments, top pads **20a**, **20b**, **20c** each have a different thickness, as shown in FIG. **17F**.

[0114] In some embodiments, top pad **20** includes a first side **21** and a second side **23** that is removably attached to first side **21**, as shown in FIGS. **13D** and **13E**. In some embodiments, first and second sides **21**, **23** may have different characteristics, such as, for example, different firmnesses, different thicknesses, different materials, materials with different textures, etc. In some

embodiments, first and second sides **21**, **23** are connected to one another via a zipper, hook and loop fasteners, Velcro®, magnets connectors, buttons, etc. In some embodiments, top pad **20** includes a band **27** that extends between upper and lower surfaces of top pad **20**. Band **27** extends annularly or circumferentially about the perimeter of top pad **20**, as shown in FIG. **13E**. That is, band **27** perimetrically bounds the upper and lower surfaces of top pad **20**. Band **27** is configured to show levels of breathability and firmness of top band **27**. In some embodiments, the upper surface of top pad **20** has a honeycomb design.

[0115] In one embodiment, shown in FIG. **13F**, first side **21** includes zones **21a**, **21b**, **21c** and side **23** includes zones **23a**, **23b**, **23c**. At least one of zones **21a**, **21b**, **21c** are different from another one of zones **21a**, **21b**, **21c** as to firmness and at least one of zones **23a**, **23b**, **23c** is different from another one of zones **23a**, **23b**, **23c** as to firmness. Zones **21a**, **21b**, **21c** may be the same or different than zones **23a**, **23b**, **23c**.

[0116] In one embodiment, shown in FIG. **14**, top pads **20** are coupled to chassis **14** by carabineer style connections. In particular, top pad **20** includes a plurality of stretchable straps **52** each configured to connect to a buckle **54** on chassis **14**. Straps **52** are fixed to top pad **20** and buckles **54** are fixed to chassis **14** such that connecting straps **52** with buckles **54** secures top pad **20** to chassis **14**. In this embodiment, straps **52** have a loop-like configuration that is captured by a portion of buckle **54**. Top pad **20** has a textured upper surface for comfort and pressure sensitivity and chassis **14** is made from a woven tent material. In some embodiments, top pads **20** are at least partially covered with a retention fabric to further secure top pad **20** to chassis **14**. In some embodiments, the retention fabric entirely covers top pad **20**. In some embodiments, the retention fabric entirely covers top pad **20** and at least a portion of chassis **14**.

[0117] In one embodiment, shown in FIG. **15**, top pads **20** are coupled to chassis **14** by hot rod strap style connections. In particular, top pad **20** includes a plurality of leather straps **56** each configured to connect to a buckle **58** on chassis **14**. Straps **56** are fixed to top pad **20** and buckles **58** are fixed to chassis **14** such that connecting straps **56** with buckles **58** secures top pad **20** to chassis **14**. In this embodiment, straps **56** each include at least one opening configured to receive a prong of buckle **58** similar to how a prong of a belt buckle is received within a hole of a belt.

[0118] In one embodiment, shown in FIG. **15A**, top pad **20** has a material surface texture for comfort and pressure sensitivity. Chassis **14** includes a woven dimensional material with a silver or white stitch. Chassis **14** includes a panel **62** toward the foot of mattress **12**. In some embodiments, panel **62** includes indicia **64**. Indicia **64** may be stitched onto panel **62** or may be otherwise coupled to panel **62** by adhesive or some other material. In some embodiments, indicia **64** includes letters that spell a model or other words describing characteristics of mattress **12**. In one embodiment, indicia **64** includes letters that spell one or more words that describe top pad **20**, such as, for example, characteristics of top pad **20**. In one embodiment, indicia **64** includes letters that spell one or more words that describe the theme of mattress **12**, such as, for example, words relating to racing, cars, camping, outdoors, etc. In one embodiment, shown in FIG. **15B**, mattress **12** is stiffer than mattress **12** shown in FIG. **15A**. Topper pad **20** in FIG. **15B** is made from Patagonia style material for feel and durability. In one embodiment, shown in FIG. **15C**, mattress **12** is stiffer than mattress **12** shown in FIG. **15B**. Topper pad **20** in FIG. **15C** is made of material surface to depict firm comfort.

[0119] In one embodiment, shown in FIG. **15D**, sides **21**, **23** of top pad **20** each include color coded zones for comfort designation. Sides **21**, **23** are joined together by a center zipper **66**. Zippered corners **68** help to keep mattress **12** together. That is, zippered corners **68** secure top pad **20** to chassis **14**, while maintaining spring packs **18** between chassis **14** and top pad **20**. Chassis **14** includes one or a plurality of vents **70** that extends through inner and outer surfaces of chassis **14**. Vents **70** may each have an arcuate configuration, as shown in FIG. **15D**. Although the vent is shown in this configuration, other configurations such as, circular, elliptical, polygonal or the like are also possible. In some embodiments, at least one of base **22**, first and second side portions **22a**,

22b and top portion **22c** includes one or more vent **70**. Vents **70** are configured to allow air flow in and out of cavity **60**. That is, vents **70** allow air to circulate and exchange from an inner core of mattress **12** to a room environment.

[0120] In one embodiment, shown in FIG. **15E**, sides **21**, **23** of top pad **20** are stitched together. Sides **21**, **23** may be stitched together using a baseball style stitch. Band **27** is joined to the upper surface of top pad **20** using stitching. Likewise, band **27** is joined to the lower surface of top pad **20** using stitching. In some embodiments, the stitching that joins band **27** with the upper and lower surfaces of top pad **20** is a baseball style stitch. In one embodiment, shown in FIG. **15F**, chassis **14** includes a first piece of material **72** and a second piece of material **74** that is joined with first piece of material **72** along seams **76**. Second piece of material **74** is not joined to first piece of material **72** along seam **78** such that first and second pieces of material **72**, **74** form a pocket. In some embodiments, the pocket is configured for holding sheets in place and/or storage. It is envisioned that one or more of base **22**, first and second side portions **22a**, **22b** and top portion **22c** may include a pocket. As shown in FIG. **15F**, seam **78** extends at an acute angle relative to top pad **20** such that the depth of the pocket is greater at one end of the pocket than an opposite end of the pocket. However, in some embodiments, seam **78** extends parallel to top pad **20** such that the depth of the pocket is the same at one end of the pocket as the opposite end of the pocket.

[0121] As discussed above, mattress **12** is customizable according to the sleep position and/or body type of one or more sleepers. To achieve this, a plurality of spring packs **18** and top pads **20** having different firmnesses are available to be included in a given mattress **12**, as shown in FIG. **16**. This allows sleepers to choose spring packs **18** and top pads **20** having a firmness that correlates to their body type and/or sleep position. In some embodiments, only one type of chassis **14**, only one type of outer lower covering **30** and only one type of retention fabric are available, as shown in FIG. **16**. As such, mattress **12** may be customized by choosing spring packs **18** and top pads **20** having a firmness that correlates to their body type and/or sleep position and combining the same with chassis **14**, outer lower covering **30** and/or the retention fabric.

[0122] In some embodiments, a plurality of different chassis **14** are available to build a mattress **12**. For example, at least three types of chassis **14** may be provided, wherein each chassis **14** includes different zoning and/or materials, as shown in FIG. **17**. In some embodiments, the different types of chassis **14** are assigned a numerical value for different ascending degrees of performance, materials, personal fit and durability, based upon body type. Three different chassis are shown in FIG. **17F**. In some embodiments, chassis **14** is chosen from among the different types of chassis **14** based on the sleepers' body types and sleep positions. In some embodiments, the mattress category is based upon the number of zones in the mattress. For example, one of the categories may include mattresses that have one zone such that the mattress is universal from head to foot; one of the categories may include mattresses that have three zones from head to foot; and one of the categories may include mattresses that have five or more zones or have additional zoning custom molded to a sleeper's body, as shown in FIG. **17A**. In some embodiments, the additional zoning is determined by sinking the sleeper into a waterbed-like structure and using 3D mapping so that every location on the mattress is zoned to the sleeper's specific body contours, similar to racing car seats and dental molding. Examples of the types of zones that may be included in chassis **14** are shown in FIGS. **17B** and **17C**. As shown in FIGS. **17B** and **17C**, the zones may be specifically positioned to provide a selected amount of support for a particular body part. As shown in FIG. **17D**, chassis **14** may include a plurality of heated zones that may be variously positioned about chassis **14**. In some embodiments, the heated zones are arranged similar to that of a sneaker tread pattern. As shown in FIG. **17E**, one side of mattress **12** may include a first zone or zones, such as, for example, a "his zone," and another side of mattress **12** may include a second zone or zones, such as, for example, a "her zone" that is/are different from the first zone or zones.

[0123] Once the proper chassis **14** is selected, the sleeper then chooses spring packs **18** and a top pad **20** based on the sleepers' body types and sleep positions. In one embodiment, the sleeper may

consult a chart similar to that shown in FIG. 18 that assigns a number based upon the sleepers' body types and sleep positions. For example, a sleeper with a small frame (dress size 0-2 or jacket size 34-36) who sleeps on their stomach may have a number 0.0, while a sleeper with a large frame (dress size 12+ or jacket size 44+) who sleeps on their stomach may have a number 3.0. This indicates that the sleeper with the large frame will require a firmer spring pack **18** and/or top pad **20** than the sleeper with the small frame. As such, the sleeper with the large frame would likely select spring pack **18c** and the sleeper with the small frame would likely select spring pack **18a**.

Likewise, the sleeper with the large frame would likely select top pad **20c** and the sleeper with the small frame would likely top pad **20a**. As discussed above, spring packs **18a**, **18b**, **18c** can be combined with any of spring packs **18a**, **18b**, **18c** such that two spring packs **18** having the proper firmness can be selected for one mattress **12** so as to provide proper support for each of the two sleepers that sleeps on mattress **12**. Although mattress **12** has been discussed in terms of chassis **14**, spring packs **18a**, **18b**, **18c** and top pads **20a**, **20b**, **20c**, it should be understood that mattress **12** can include any of the chassis discussed in this disclosure, any of the spring packs discussed in this disclosure and any of the top pads discussed in this disclosure, in any combination. Indeed, the features or components of one embodiment discussed herein may be incorporated into any of the other embodiments discussed herein, thus providing a variety of options in forming a mattress that is specifically suited for a sleeper or sleepers. This is facilitated by, among other things, the modular nature of mattress **12**. FIG. 18A shows an assembled mattress **12** in a retail setting, such as, for example, a showroom that has been adapted to appear like a typical bedroom, with a rug, furniture and decorations typically found in a bedroom.

[0124] In one embodiment, shown in FIGS. 19-21, chassis **14** is powered for adjustability and/or articulation. Chassis **14** may be manual or electric. Motion devices may be embedded within chassis **14**. In particular, chassis **14** may include at least four portions **14a**, **14b**, **14c**, **14d** that are movable relative to one another, as shown in FIGS. 20A and 20B. Portions **14a**, **14b**, **14c**, **14d** are connected to one another by rotatable gears (FIG. 21) that are configured to rotate portions **14a**, **14b**, **14c**, **14d** relative to one another such that portions **14a**, **14b**, **14c**, **14d** can move from a first position, shown in FIG. 20A, in which portions **14a**, **14b**, **14c**, **14d** extend parallel to one another to a second position, shown in FIG. 20B, in which portions **14a**, **14b**, **14c**, **14d** extend at acute angles relative to one another. In some embodiments, the rotatable gears are configured to lock to fix portions **14a**, **14b**, **14c**, and **14d** in the first position and/or the second position.

[0125] In one embodiment, shown in FIG. 23, mattress **12** has a six zone system. In one embodiment, shown in FIG. 24, chassis **14** includes at least three portions **14a**, **14b**, **14c** that are joined to one another by hinges **15** such that portions **14a**, **14b**, **14c** are movable relative to one another. Mattress **12** includes a cushion **60** positioned within cavity **16**. Cushion **60** includes portions **1-6**, as shown in FIG. 24. Portions **1-6** are joined to one another by hinges **17**. This configuration allows mattress **12** to recline, while still providing multiple zones. In one embodiment, shown in FIG. 25, chassis **14** is a tray that does not articulate. In some embodiments, at least two of zones **1-6** have different characteristics, such as, for example, different firmnesses.

[0126] In some embodiments, system **10** includes an easy to ship/easy to carry packaging method, as shown in FIGS. 26 and 27, for transporting mattress **12**. The method includes packaging mattress **12** in four boxes. In some embodiments, one box includes one spring pack **18**, another box includes another spring pack **18**, another box includes chassis **14** and another box includes top pad **20**. In some embodiments, the easy to ship and/or easy to carry packaging method allows the modular pieces of the customizable mattress to be assembled at the moment of delivery by a retail store driver. In some embodiments, the easy to ship and/or easy to carry packaging method requires only a single driver, such as, for example, a delivery person, drone or UPS delivery to transport the modular pieces of the customizable mattress from a factory or warehouse to an end user. As shown in FIG. 27, the easy to ship/easy to carry packaging method includes assembling mattress **12**. In particular, chassis **14**, spring packs **18** and top pad **20** are unpacked from their respective boxes.

Spring packs **18** are positioned within cavity **16** of chassis **14**. Top pad **20** is positioned to cover spring packs **18** and portions of chassis **14**.

[0127] In some embodiments, system **10** includes an easy to fit to shopper/easy to return method, as shown in FIG. **28**. The method includes providing an SKU optimized for a retailer. In some embodiments, the easy to fit shopper and/or easy to return method includes providing the least amount of SKUs, while providing the most options. In one embodiment, carrier **14** includes one SKU, each spring pack **18** includes one SKU and top pad includes one SKU. Outer lower cover **30** and the retention fabric may each include one SKU, if used. The SKUs will help identify the components that are going to be used in a given mattress **12**. For example, each of the different versions or embodiments of chassis **14** will have its own unique SKU, each of the different versions or embodiments of spring packs **18** will have its own Stock Keeping Unit (SKU) and each of the different versions or embodiments of top pad **20** will have its own SKU. This allows a worker to select the proper components by reading the SKUs. For example, this ensures the worker will choose the chassis **14**, the spring packs **18** and the top pad **20** that each has the desired firmness or other characteristics selected by the consumer. In some embodiments, the easy to fit shopper and/or easy to return method includes swapping independent suspension cores or power plants to alternate sides such that the independent suspension cores still interlink. In some embodiments, the easy to fit shopper and/or easy to return method includes reselecting a support level.

[0128] In some embodiments, system **10** includes a subscription sales method that includes reaching out to customers based upon the date the customizable mattress was purchased (mattress birthday), as shown in FIG. **29**. In some embodiments, the subscription sales method includes renewing the subscription. In some embodiments, the subscription sales method includes collecting customer information. In some embodiments, chassis **14** has a five year warranty, in which case, the subscription sales method will begin contacting a customer who purchased a mattress **12** regarding replacing or upgrading chassis **14** five years or more after mattress **12** was purchased. In some embodiments, top pad **20** has a one year warranty, in which case, the subscription sales method will begin contacting a customer who purchased a mattress **12** regarding replacing or upgrading top pad one year or more after mattress **12** was purchased.

[0129] It will be understood that various modifications may be made to the embodiments disclosed herein. For example, features of any one embodiment can be combined with features of any other embodiment. Therefore, the above description should not be construed as limiting, but merely as exemplification of the various embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

Claims

1-20. (canceled)

21. A kit comprising: a mattress configured to be self-assembled, the mattress comprising: a chassis defining a cavity, a plurality of spring packs each having a respective firmness, the spring packs each being configured to be removably positioned within the cavity, and a top pad configured to be removably cover at least a portion of the spring pack that is positioned in the cavity; and instructions to self-assemble the mattress.

22. The kit recited in claim 21, wherein the instructions include directions for inserting one of the spring packs into the cavity.

23. The kit recited in claim 22, wherein the instructions include directions for positioning the top pad to cover the spring pack that was inserted into the cavity.

24. The kit recited in claim 21, wherein the instructions include directions for inserting two of the spring packs into the cavity.

25. The kit recited in claim 24, wherein the instructions include directions for positioning the top

pad to cover the spring packs that were inserted into the cavity.

26. The kit recited in claim 21, wherein the chassis includes a first side and a second side, the instructions including directions for inserting two of the spring packs into the cavity such that a first one of the spring packs is positioned in the first side and a second one of the spring packs is positioned in the second side.

27. The kit recited in claim 26, wherein the instructions include directions for positioning the top pad to cover the spring packs that were inserted into the cavity.

28. The kit recited in claim 26, wherein the instructions include directions for removing the first one of the spring packs and the second one of the spring packs from the cavity and then inserting the first one of the spring packs and the second one of the spring packs such that the first one of the spring packs is positioned in the second side and the first one of the spring packs is positioned in the first side.

29. The kit recited in claim 21, wherein the top pad is a first top pad and the instructions include directions for positioning the first top pad to cover the spring packs positioned in the cavity.

30. The kit recited in claim 29, wherein the instructions include directions for removing the first top pad from the chassis and then positioning a second top pad to removably cover the spring packs positioned in the cavity.

31. The kit recited in claim 30, wherein the first top pad has a firmness that is different than a firmness of the second top pad.

32. The kit recited in claim 21, wherein the chassis includes opposite front and rear walls and opposite first and second side walls each extending from the front wall to the rear wall, the top pad having a monolithic bottom wall configured to directly engage the walls and the side walls when the top pad covers the spring packs positioned in the cavity.

33. The kit recited in claim 21, wherein self-assembly includes assembling the mattress using only one person.

34. A method comprising: providing the kit recited in claim 21; and making the kit ready, prior to providing the kit, making the kit ready comprising selecting one of the spring packs from the plurality of spring packs, based upon a sleeper's body type.

35. A method comprising: providing the kit recited in claim 21; and making the kit ready, prior to providing the kit, making the kit ready comprising selecting one of the spring packs from the plurality of spring packs based upon a sleeper's sleep preference.

35. The method recited in claim 35, wherein the top pad is a first top pad and the instructions include directions for positioning the first top pad to cover the spring pack that is positioned in the cavity, the instructions including directions for removing the first top pad from the chassis and then positioning a second top pad to removably cover the spring pack that is positioned in the cavity.

36. The method recited in claim 35, wherein the first top pad has a firmness that is different than a firmness of the second top pad.

37. A method comprising: providing the kit recited in claim 21; and making the kit ready, prior to providing the kit, making the kit ready comprising selecting a first one of the spring packs from the plurality of spring packs based upon a first sleeper's body type and/or sleep preference and selecting a second one of the spring packs from the plurality of spring packs based upon a second sleeper's body type and/or sleep preference.

38. The method recited in claim 37, wherein the instructions include directions for inserting the first one of the spring packs and the second one of the spring packs in the cavity.

39. The method recited in claim 37, wherein the top pad is a first top pad and the instructions include directions for positioning the first top pad to cover the spring packs that are positioned in the cavity, the instructions including directions for removing the first top pad from the chassis and then positioning a second top pad to removably cover the spring packs that are positioned in the cavity.

40. A kit comprising: a mattress configured to be self-assembled, the mattress comprising: a chassis

comprising opposite front and rear walls and opposite first and second side walls each extending from the front wall to the rear wall, inner surfaces of the walls and the side walls defining a cavity, two spring packs each having a respective firmness, the spring packs each being configured to be removably positioned within the cavity, and a top pad configured to be removably cover at least a portion of the spring packs that are positioned in the cavity, the top pad having a monolithic bottom wall configured to directly engage the walls and the side walls when the top pad covers the spring packs that are positioned in the cavity; and instructions to self-assemble the mattress, self-assembly including assembling the mattress using only one person, the instructions including directions for inserting two of the spring packs into the cavity and directions for positioning the top pad to cover the spring packs that were inserted into the cavity.
