

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281864

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

CHOI; Sejin et al.

AIR CLEANER

Abstract

Disclosed is an air cleaner. The air cleaner includes a case including a suction port disposed in a peripheral surface of the case, the suction port being configured to introduce air to an inside of the case, a filter configured to remove foreign matter from the air introduced through the suction port, a blower fan disposed in the case that is configured to blow the air introduced through the suction port after the air is filtered by the filter, a discharge port disposed below the blower fan and the filter, the discharge port being configured to discharge the air blown by the blower fan in a downward direction, and a bottom plate disposed below the blower fan and the filter that is configured to be in contact with a floor, the bottom plate including a boss protruding upward.

Inventors: CHOI; Sejin (Seoul, KR), KIM; Hojung (Seoul, KR), KIM; Changkyum (Seoul, KR), CHOI; Chiyoung (Seoul, KR)

Applicant: LG ELECTRONICS INC. (Seoul, KR)

Family ID: 96948417

Assignee: LG ELECTRONICS INC. (Seoul, KR)

Appl. No.: 19/073767

Filed: March 07, 2025

Foreign Application Priority Data

KR

10-2024-0033179

Mar. 08, 2024

Publication Classification

Int. Cl.: B01D46/00 (20220101); B01D46/24 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the priority benefit of Korean Patent Application No. 10-2024-0033179, filed on Mar. 8, 2024 in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present disclosure relates to an air cleaner, and more particularly to an air cleaner capable of exhibiting improved air cleaning performance.

2. Description of the Related Art

[0003] An air cleaner is a device that filters air in a certain space and discharges the filtered air, thereby reducing the concentration of dust or bacteria in the air in the corresponding space. The air cleaner filters out foreign matter by generating a flow of air in the corresponding space, and discharges air with the foreign matter removed therefrom.

[0004] In order to quickly purify air in the indoor space, a discharge port may be formed in an upper portion of an air cleaner, and filtered air discharged upwardly may be guided so as to flow in all directions.

[0005] Further, in the case in which a discharge port is formed in an upper portion of an air cleaner, a separate fan for regulation of the direction of air discharged may be disposed at an upper portion of the air cleaner in order to cause filtered air to flow a long distance.

[0006] Related Art Document 1 (Korean Patent Laid-Open Publication No. 10-2020-0112592) discloses an air cleaner including a discharge port formed in the upper end thereof.

[0007] Related Art Document 2 (Korean Patent Laid-Open Publication No. 10-2017-0140578) discloses an air cleaner including blowing devices disposed in an upward-downward direction and discharge ports formed in the upper portion and the central portion thereof.

[0008] However, because the air cleaners of the related art discharge purified air upwardly, the discharge airflow directly reaches a user, thus causing discomfort to the user. Further, the air cleaners of the related art having this discharge structure have a limitation in removing particles that are relatively large and heavy and thus tend to settle on the floor.

SUMMARY OF THE INVENTION

[0009] An aspect of the present disclosure is directed to providing an air cleaner capable of preventing a discharge airflow from directly reaching a user and thus causing discomfort to the user.

[0010] Another aspect of the present disclosure is directed to providing an air cleaner capable of forming an airflow that effectively removes large and heavy particles.

[0011] A further aspect of the present disclosure is directed to providing an air cleaner capable of forming an airflow that effectively removes allergens causing allergies.

[0012] Still another aspect of the present disclosure is directed to providing an air cleaner capable of achieving improved air cleaning performance on large particles as well as small particles.

[0013] An air cleaner according to an embodiment of the present disclosure is configured to discharge purified air through the bottom thereof, thereby preventing the discharge airflow from directly reaching a user and thus causing discomfort to the user.

[0014] An air cleaner according to an embodiment of the present disclosure is configured to form an airflow at a height at which allergens causing allergies are mainly located, thereby effectively

removing the allergens.

[0015] An air cleaner according to an embodiment of the present disclosure includes a case having a suction port formed in the peripheral surface thereof, a blower fan disposed in the case, a filter configured to remove foreign matter from air introduced through the suction port, and a discharge port formed below the blower fan and the filter. Air with the foreign matter removed therefrom is discharged downwardly through the discharge port, thereby preventing the discharge airflow from directly reaching a user and thus causing discomfort to the user and effectively removing allergens.

[0016] The air cleaner according to the embodiment of the present disclosure further includes a bottom plate disposed below the blower fan and the filter so as to be in contact with the floor, and the bottom plate includes a boss protruding upward.

[0017] A curved portion, a flat portion extending laterally from the curved portion, and a boss protruding upward from an end portion of the flat portion may be formed on an upper surface of the bottom plate.

[0018] The boss may include an inclined surface, the height of which gradually increases in a radially outward direction.

[0019] The maximum height of the boss may be less than 10% of the radius of curvature of the curved portion.

[0020] The boss may be formed in a ring shape along the edge of the bottom plate.

[0021] The bottom plate may further include a central pillar supporting the blower fan from below, and the curved portion may be formed so as to surround the central pillar.

[0022] An angle between the central pillar and the curved portion may be smaller than the angle of the discharge airflow through the discharge port.

[0023] A lower discharge grille including a plurality of grilles may be disposed inside the discharge port in order to guide air discharged downwardly in the radially outward direction.

[0024] The plurality of grilles may have a concentric circle structure.

[0025] The plurality of grilles may have lengths greater than an interval between the plurality of grilles.

[0026] The plurality of grilles may be bent at a predetermined angle in the outward direction.

[0027] The predetermined angle may be 20 degrees to 40 degrees.

[0028] Each of the plurality of grilles may include a curved portion bent in the radially outward direction and a protruding portion protruding from an end portion of the curved portion in the radially outward direction.

[0029] The protruding portion may have a smaller thickness than the curved portion.

[0030] The length by which the protruding portion protrudes in the radially outward direction may be greater than the thickness of the curved portion.

[0031] An airflow guide may be disposed on an upper surface of the bottom plate so as to guide air discharged downwardly through the discharge port in the lateral direction.

[0032] The airflow guide may include a curved portion, a flat portion extending laterally from the curved portion, and a boss protruding upward from an end portion of the flat portion.

[0033] The boss may be formed in a ring shape along the edge of the airflow guide.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] The above and other objects, features, and other advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0035] FIG. 1 is a view showing the external appearance of an air cleaner according to an embodiment of the present disclosure;

[0036] FIG. 2 is a cross-sectional view of the air cleaner according to the embodiment of the present disclosure;

[0037] FIGS. 3 and 4 are exploded views of the air cleaner according to the embodiment of the present disclosure;

[0038] FIGS. 5 to 7 are views for explaining discharge of purified air through the bottom of the air cleaner according to the embodiment of the present disclosure;

[0039] FIGS. 8 and 9 are views for explaining a lower discharge grille according to the embodiment of the present disclosure;

[0040] FIGS. 10A to 10C are views for explaining the shape of the grille according to the embodiment of the present disclosure;

[0041] FIGS. 11 and 12 are views for explaining allergen particles; and

[0042] FIG. 13 is a view for explaining performance comparison between an air cleaner that discharges purified air through the bottom thereof and an air cleaner that discharges purified air through the top thereof.

DETAILED DESCRIPTION

[0043] Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings. The present disclosure may, however, be embodied in many different forms, and should not be construed as being limited to the embodiments set forth herein.

[0044] In the drawings, illustration of parts unrelated to the description is omitted to clearly and briefly describe the present disclosure, and the same or extremely similar components are denoted by the same reference numerals throughout the specification.

[0045] As used herein, the terms with which the names of components are suffixed, “module” and “unit”, are assigned to facilitate preparation of this specification, and are not intended to suggest unique meanings or functions. Accordingly, the terms “module” and “unit” may be used interchangeably.

[0046] It will be understood that although the terms “first”, “second”, etc., may be used herein to describe various components, these components should not be limited by these terms. These terms are only used to distinguish one component from another component.

[0047] FIG. 1 is a view showing the external appearance of an air cleaner according to an embodiment of the present disclosure, and FIG. 2 is a cross-sectional view of the air cleaner according to the embodiment of the present disclosure. FIGS. 3 and 4 are exploded views of the air cleaner according to the embodiment of the present disclosure.

[0048] Referring to FIGS. 1 to 4, the air cleaner 1 includes a case 10 forming the external appearance thereof. The case 10 may have suction ports 11a and 12a formed in the peripheral surface thereof in order to suction air from various directions. Air may be suctioned from all directions with respect to a central line passing through the internal center of the case 10 in an upward-downward direction. The suction ports 11a and 12a are provided in plural, and the plurality of suction ports 11a and 12a is spaced apart from each other in the circumferential direction of the case 10. The plurality of suction ports 11a and 12a is evenly formed in the circumferential direction along the peripheral surface of the case 10 so that air is capable of being suctioned into the case 10 from any direction.

[0049] In this specification, the upward-downward direction or the vertical direction is defined as an axial direction. The axial direction may correspond to the central axis-direction of a blower fan 140, which will be described later, i.e., the motor shaft direction of the fan. The radial direction or the horizontal direction may be understood as a direction perpendicular to the axial direction. The circumferential direction may be understood as a circumferential direction of an imaginary circle that is formed when rotating about the axial direction with a distance in the radial direction as a rotational radius.

[0050] The air cleaner 1 includes a blower fan 140 disposed in the case 10 and a filter 120 configured to remove foreign matter from air introduced through the suction ports 11a and 12a.

[0051] The air introduced through the suction ports **11a** and **12a** may pass through the filter **120**. The filter **120** may be formed in a cylindrical shape and may have a filter surface that filters air.

[0052] The case **10** may have a cylindrical shape. The case **10** may include a first case **11**, which has a semi-cylindrical shape and covers a portion of the outer circumferential surface of the air cleaner **1**, and a second case **12**, which has a semi-cylindrical shape and covers the remaining portion of the outer circumferential surface of the air cleaner **1**.

[0053] Alternatively, the case **10** may have a shape of a truncated cone (a cone with the top cut off), and each of the first case **11** and the second case **12** may have a shape of a semi-truncated cone.

[0054] The first case **11** and the second case **12** may be coupled to each other to form the external appearance of the air cleaner **1**. Because the first case **11** covers the front surface of the air cleaner **1**, the first case **11** may be referred to as a “front case” or a “front cover”. Because the second case **12** covers the rear surface of the air cleaner **1**, the second case **12** may be referred to as a “rear case” or a “rear cover”.

[0055] The suction ports **11a** and **12a** include a first suction port **11a** formed in the first case **11** and a second suction port **12a** formed in the second case **12**. The suction ports **11a** and **12a** allow the inside of the case **10** and the outside to communicate with each other. The suction ports **11a** and **12a** are provided in plural. The plurality of suction ports **11a** and **12a** may be formed in the peripheral surface of the case **10**.

[0056] The plurality of suction ports **11a** and **12a** is evenly formed in the circumferential direction along the outer circumferential surface of the case **10** so that air is capable of being suctioned into the case **10** from any direction.

[0057] The plurality of suction ports **11a** and **12a** is formed in a stripe shape that is elongated in the upward-downward direction. Alternatively, the plurality of suction ports **11a** and **12a** may be formed through perforation in a circular or elliptical shape.

[0058] As described above, because the case **10** is formed in a cylindrical shape and the plurality of suction ports **11a** and **12a** is formed along the outer circumferential surface of the case **10**, the amount of air suctioned may increase.

[0059] A discharge port **110a** that is open downward is formed in a lower portion of the air cleaner **1**. A lower discharge grille **110** is disposed inside the discharge port **110a** in order to change the direction of air flowing upward.

[0060] The annular discharge port **110a** is formed in a lower portion of the air cleaner **1**. Air with foreign matter removed therefrom by the filter **120** is discharged downwardly through the discharge port **110a**.

[0061] The lower discharge grille **110** may include a plurality of grilles bent at a predetermined angle in the outward direction. The lower discharge grille **110** may be disposed inside the discharge port **110a** in order to deliver the lower discharge airflow in the lateral direction.

[0062] The air cleaner **1** includes a filter mounting part **160** to which the filter **120** is mounted. The filter **120** may be removably mounted to the filter mounting part **160**. The filter **120** may have a hollow cylindrical shape, and air may be introduced through the outer circumferential surface of the filter **120**. While the air passes through the filter **120**, impurities such as fine dust may be removed from the air.

[0063] Because the filter **120** has a cylindrical shape, air is capable of being introduced into the filter **120** from any direction. Therefore, the air filtering area may increase.

[0064] The filter mounting part **160** may be formed in a cylindrical shape corresponding to the shape of the filter **120**. In the process of mounting the filter **120**, the filter **120** may be slidably fitted into the filter mounting part **160**. Conversely, in the process of demounting the filter **120**, the filter **120** may be slidably withdrawn from the filter mounting part **160**.

[0065] The air cleaner **1** includes a discharge port **110a** formed in the bottom thereof. The discharge port **110a** is formed below the blower fan **140** and the filter **120**. Air with foreign matter removed therefrom by the filter **120** is discharged downwardly through the discharge port **110a**.

[0066] In addition, a lower discharge grille **110** including a plurality of grilles is disposed at the bottom of the air cleaner **1** in order to guide a lower airflow.

[0067] The lower discharge grille **110** may include a plurality of grilles having a concentric circle structure. The plurality of grilles may be a plurality of circles having the same center and different radii. Each of the plurality of grilles may include a section bent in the radially outward direction. The lower discharge grille **110** may include a plurality of grilles bent at a predetermined angle in the outward direction. The lower discharge grille **110** may be disposed inside the discharge port **110a** in order to deliver the lower discharge airflow in the lateral direction.

[0068] A bottom plate **170** is disposed at a lower portion of the air cleaner **1**. The bottom plate **170** is disposed in contact with the floor to support the air cleaner **1**.

[0069] An airflow guide **170a** is disposed on the upper surface of the bottom plate **170** in order to guide air discharged downwardly through the discharge port **110a** in the lateral direction. The bottom plate **170** may further include a base **170b** that supports the airflow guide **170a**. The airflow guide **170a** may be formed on the upper surface of the base **170b**. In addition, the airflow guide **170a** and the base **170b** may be coupled to each other to constitute the bottom plate **170**.

[0070] In addition, the bottom plate **170** may further include a central pillar **175** that supports the blower fan **140** from below.

[0071] Air with foreign matter removed therefrom by the filter **120** is discharged downwardly through the discharge port **110a**.

[0072] General allergen particles have a size of about 3 μm to about 100 μm , which is greater than the size of fine dust, and thus tend to settle on the floor. The lower airflow discharged downwardly from the air cleaner **1** causes allergen particles to float in the air and thus to be collected by the filter **120**. In this way, it is possible to effectively remove allergens causing allergies using the lower airflow discharged downwardly from the air cleaner **1**.

[0073] In addition, the air cleaner **1** may include a UVC LED, which is disposed in the case **10** and outputs ultraviolet in a wavelength band that has a sterilization effect on bacteria, mold, and microorganisms, and an ionizer, which is disposed in the case **10** and eliminates germs and mold using electricity supplied thereto.

[0074] In addition, the air cleaner **1** includes a fan housing **145** accommodating the blower fan **140** and a support part **150** extending in the vertical direction from the fan housing **145**. The support part **150** may extend in the longitudinal direction of the air cleaner **1**.

[0075] The support part **150** may be provided in plural. For example, two support parts **150** may be disposed so as to face two opposite sides of the filter **120**. The number of support parts **150** may be varied depending on the size or specifications of the product. Some of the support parts **150** may be different in at least one of shape, size, or material from the remaining ones of the support parts **150**.

[0076] A bottom cover **180** is disposed at the bottom of the case **10**. The lower discharge grille **110** is disposed inside the bottom cover **180**.

[0077] The air cleaner **1** includes a fan housing **145** disposed below the filter **120**, a blower fan **140** rotatably disposed in the fan housing **145**, and a fan motor **130** configured to rotate the blower fan **140**.

[0078] The fan motor **130** may be supported by a motor fastening part **125**. The rotation shaft of the fan motor **130** may extend upward from the fan motor **130** and may pass through the bottom of the motor fastening part **125** to be connected to the blower fan **140**.

[0079] Magnets may be disposed on two opposite sides of the fan housing **145**. The magnets may be coupled to metallic pieces **15** of the first case **11**. In addition, the magnets may be coupled to metallic pieces **15** of the second case **12**.

[0080] In some embodiments, each of the magnets may include a plurality of magnets. Some of the plurality of magnets may be coupled to the metallic pieces **15** of the first case **11**, and the remaining ones of the plurality of magnets may be coupled to the metallic pieces **15** of the second case **12**.

[0081] The positions of the magnets and the metallic pieces **15** may be set to be opposite those

exemplified above. For example, the metallic pieces may be disposed on two opposite sides of the fan housing **145**, and the magnets may be disposed at the first case **11** and the second case **12**.

[0082] The plurality of support parts **150** extends upward from the fan housing **145**. For example, the support parts **150** may be beams that are elongated in the longitudinal direction.

[0083] A control module **200** is disposed above the filter **120**.

[0084] A top cover **230** and a case **210** are coupled to each other to form the external appearance of the control module **200**, and a main printed circuit board (PCB) on which circuits, such as a controller for control of overall operation of the air cleaner **1**, are mounted is accommodated in an inner space defined by the top cover **230** and the case **210**.

[0085] The case **210** has a central cavity formed therein, and a filter pressing plate **220** is disposed in the central cavity of the case **210**. The filter pressing plate **220** may be connected to a plurality of springs (not shown).

[0086] FIGS. **5** to **7** are views for explaining discharge of purified air through the bottom of the air cleaner according to the embodiment of the present disclosure.

[0087] FIG. **5** is a view showing the flow path of the lower discharge airflow, and FIG. **6** is a view visualizing the lower discharge airflow using a laser. FIG. **7** is an enlarged view of a lower discharge airflow guide structure.

[0088] Referring to FIGS. **5** to **7**, the discharge port **110a** is formed in the lower end of the air cleaner **1**, and the lower discharge grille **110** is disposed inside the discharge port **110a** in order to guide the lower discharge airflow.

[0089] The lower discharge grille **110** may include a plurality of grilles. The plurality of grilles may be bent at a predetermined angle in the radially outward direction. The lower discharge grille **110** may be disposed inside the discharge port **110a** in order to deliver the lower discharge airflow in the lateral direction.

[0090] When the blower fan **140** is rotated by the motor **130**, the air purified by the filter **120** is discharged through the discharge port **110a** as the lower discharge airflow.

[0091] The airflow guide **170a** is disposed on the upper surface of the bottom plate **170** in order to guide air discharged downwardly through the discharge port **110a** in the lateral direction.

[0092] The airflow guide **170a** includes a curved portion **173**, a flat portion **171** extending laterally from the curved portion **173**, and a boss **172** protruding upward from an end portion of the flat portion **171**.

[0093] The boss **172** may form an airflow that effectively causes allergen particles to float in the air. The boss **172** may reduce flow resistance at the end portion of the flat portion **171**. The boss **172** may prevent flow separation at the end portion of the flat portion **171**. The boss **172** may be formed in a ring shape along the edge of the airflow guide **170a**. The boss **172** may protrude from the flat portion **171** by a predetermined height **d1**, thereby preventing the occurrence of turbulence at the end portion of the flat portion **171** and causing the airflow to ascend. Accordingly, it is possible to effectively cause allergen particles settled on the floor to float in the air while preventing flow separation.

[0094] If the height **d1** of the boss **172** is too great, it may excessively increase the degree of ascending of the airflow, which is inappropriate for causing allergen particles settled on the floor to float in the air. For example, it is desirable that the height **d1** of the boss **172** be set to several millimeters (mm) or less, so long as the boss **172** is capable of preventing flow separation.

[0095] The boss **172** may include an inclined surface, the height of which gradually increases in the radially outward direction. Accordingly, the boss **172** may create an airflow that gradually rises along the inclined surface.

[0096] The curved portion **173** may be formed so as to surround the central pillar **175** of the bottom plate **170**. The curved portion **173** formed in a curved shape may reduce flow resistance. The curved portion **173**, which imparts a curvature to the airflow guide **170a**, may be formed so as to be round with a predetermined radius of curvature **R1**. The radius of curvature **R1** may be set so as to

guide the lower discharge airflow to smoothly flow in the lateral direction. Further, the maximum height **d1** of the boss **172** may be set to be less than 10% of the radius of curvature **R1** of the curved portion **173**.

[0097] The radius of curvature **R1** may be set corresponding to the grille bending angle of the lower discharge grille **110**. For example, a predetermined angle **ag1** based on the vertical direction may be determined corresponding to the grille bending angle of the lower discharge grille **110**, and the radius of curvature **R1** may be set so as to implement the determined angle **ag1**. In more detail, the angle **ag1** may be set to be smaller than the grille bending angle of the lower discharge grille **110**.

[0098] The predetermined angle **ag1** may be an angle between the central pillar **175** and the curved portion **173**. In this case, the predetermined angle **ag1** may be smaller than the angle of the discharge airflow through the discharge port **110**. The angle of the discharge airflow may correspond to the grille arrangement angle and grille bending angle of the lower discharge grille **110**. The grille bending angle may be an angle between an imaginary line extending in the horizontal direction and an imaginary line extending from an end portion of the bent curved section.

[0099] FIGS. **8** and **9** are views for explaining the lower discharge grille according to the embodiment of the present disclosure.

[0100] Referring to FIGS. **8** and **9**, the lower discharge grille **110** includes an outer wall **111**, an inner wall **112**, a plurality of grilles **113** disposed between the outer wall **111** and the inner wall **112** and having a concentric circle structure, and a support portion **114** supporting the grilles **113**.

[0101] A base **115** may be located inside the inner wall **112**. The blower fan **140** may be located above the base **115**, and the central pillar **175** may be located below the base **115**.

[0102] The lengths of the grilles **113** may be greater than an interval **d2** between the grilles **113**. Accordingly, it is possible to secure a sufficient distance for guiding an airflow in the lateral direction.

[0103] FIGS. **10A** to **10C** are views for explaining the shape of the grille according to the embodiment of the present disclosure.

[0104] Referring to FIG. **10A**, a linear grille **1010** may be disposed so as to be inclined at an angle corresponding to a discharge angle **ag2**. Also in this case, the airflow may be formed along the discharge angle **ag2** corresponding to the angle at which the linear grille **1010** is disposed.

[0105] Referring to FIG. **10B**, a grille **1020** may be bent in the radially outward direction, thereby discharging an airflow at the discharge angle **ag2**.

[0106] The grille bending angle of the lower discharge grille **110** may be set to 20 degrees to 40 degrees so that the airflow rises at 20 degrees or greater in order to cause allergen particles on the floor to float in the air. If the grille bending angle is less than 20 degrees, the airflow may not be sufficiently delivered in the lateral direction. If the grille bending angle is greater than 40 degrees, airflow loss may increase. Thus, allergen particles present around the bottom of the air cleaner **1** may not float in the air.

[0107] The thickness **d3** of a certain section of the grille **1020** may be set to be different from that of the remaining section of the grille **1020**.

[0108] Referring to FIG. **10C**, a grille **1030** may include a curved portion **1031** bent in the radially outward direction and a protruding portion **1032** protruding from an end portion of the curved portion **1031** in the radially outward direction. That is, the grille **1030** shown in FIG. **10C** may be a combination of the grille **1020** shown in FIG. **10B** and the protruding portion **1032**.

[0109] The thickness **d5** of the protruding portion **1032** may be smaller than the thickness **d3** of the curved portion **1031** so as to guide an airflow in the lateral direction without blocking the same.

[0110] Further, the length **d4** by which the protruding portion **1032** protrudes in the radially outward direction may be greater than the thickness **d3** of the curved portion **1031**.

[0111] FIGS. **11** and **12** are views for explaining allergen particles.

[0112] Referring to FIGS. **11** and **12**, general allergen particles, which have a size of about 3 μm to about 100 μm , are larger and heavier than indoor floating dust particles, which have a size of about 1 μm , and thus tend to settle on the floor. For example, mold particles have a size of about 10 μm , household dust allergen particles have a size of about 15 μm , and pollen particles have a size of about 50 μm .

[0113] Because virus or cigarette smoke particles have a very small size, the same tend to continuously float without settling on the floor. Indoor floating dust particles remain suspended in the air for a very long time. For example, it takes about 9 to 10 hours for indoor floating dust particles to settle from the ceiling to the floor of the room.

[0114] However, under the same conditions, mold particles, household dust allergen particles, and pollen particles float for a short time of several seconds to several minutes and then settle on the floor. Therefore, it is not easy for the conventional air cleaner to capture allergen particles. Conventionally, the only way to remove the settled particles is to use a vacuum cleaner.

[0115] According to the present disclosure, the lower airflow discharged downwardly from the air cleaner **1** may cause allergen particles to float in the air, and the floating allergen particles may be captured by the filter **120**.

[0116] Meanwhile, according to an embodiment of the present disclosure, the speed of the lower discharge airflow may be controlled in response to the terminal velocity of allergen particles. The speed of the lower discharge airflow may be set to be higher than the terminal velocity of allergen particles.

[0117] The rotational speed of the blower fan **140** may be controlled based on the terminal velocity of allergen particles. The rotational speed of the blower fan **140** may correspond to the speed of the lower discharge airflow set to be higher than the terminal velocity of allergen particles. The controller of the control module **200** may control the rotational speed of the blower fan **140**.

[0118] The terminal velocity of allergen particles may be calculated using balance between gravity, buoyancy, and drag force acting on allergen particles. For example, the terminal velocity of allergen particles may be calculated using Stokes' terminal velocity formula.

[0119] In order to cause mold particles having a size of about 10 μm and household dust allergen particles having a size of about 15 μm to float in the air, the speed of the lower discharge airflow may be set to be higher than the terminal velocity of larger household dust allergen particles. For example, the speed of the lower discharge airflow may be set to 0.0038 m/s or higher.

[0120] The curved portion **173** may guide the lower discharge airflow to smoothly flow in the lateral direction, thereby reducing flow resistance. According to the present disclosure, in order to deliver the lower discharge airflow in the lateral direction, the bottom plate **170** is imparted with a curvature, and the boss **172** is formed at an end portion of the flat portion **171**. Accordingly, a turbulent flow for causing allergen particles to float in the air may be created. That is, because the airflow guide **170a** is imparted with an inclination and a curvature and is provided with the boss for preventing flow separation, resistance to the lower discharge airflow may be minimized.

[0121] FIG. **13** is a view for explaining performance comparison between an air cleaner that discharges purified air through the bottom thereof and an air cleaner that discharges purified air through the top thereof.

[0122] FIG. **13** shows results of evaluating particle removal performance of an air cleaner that suctions air through the side surface thereof and discharges purified air through the bottom thereof and an air cleaner that suctions air through the side surface thereof and discharges purified air through the top thereof when the two types of air cleaners are driven in the same space for the same time period.

[0123] Referring to FIG. **13**, the two types of air cleaners exhibit similar particle removal performance with respect to a small particle having a size of 0.3 μm .

[0124] However, with respect to a large particle having a size of 2.8 μm , the bottom discharge-type air cleaner exhibits particle removal performance of 12.2%, and the top discharge-type air cleaner

exhibits particle removal performance of 10.6%. That is, the bottom discharge-type air cleaner exhibits higher particle removal performance than the top discharge-type air cleaner. Further, in the case of the top discharge-type air cleaner, performance of removing a large particle of 2.8 μm is improved only by 2% compared to performance of removing a small particle of 0.3 μm . On the other hand, in the case of the bottom discharge-type air cleaner, performance of removing a large particle of 2.8 μm is improved by 12% compared to performance of removing a small particle of 0.3 μm .

[0125] In general, an air cleaner is configured to suction outside air through suction ports formed in the lower portion and/or the central portion thereof and discharge purified air through the top thereof. Such a top discharge structure is effective in removing general fine dust, but is not effective in removing allergen particles and relatively large particles (particle size > 1 μm), which commonly tend to settle on the floor, compared to the bottom discharge structure. Further, the top discharge structure has a problem in that the discharge airflow directly reaches a user and thus causes discomfort to the user.

[0126] According to the present disclosure, purified air is discharged downwardly through the bottom of the product, thereby preventing the discharge airflow from directly reaching the user and thus causing discomfort to the user. Further, according to the present disclosure, it is possible to create an airflow specialized in removing allergen particles, i.e., a lower discharge airflow that is effective in causing large and heavy particles such as allergen particles to float in the air.

[0127] As is apparent from the above description, according to at least one of the embodiments of the present disclosure, because purified air is discharged through a discharge port formed below a blower fan and a filter, it is possible to prevent a discharge airflow from directly reaching a user and thus causing discomfort to the user.

[0128] According to at least one of the embodiments of the present disclosure, because purified air is discharged through a discharge port formed in the bottom of the product, it is possible to effectively remove allergens.

[0129] According to at least one of the embodiments of the present disclosure, because a lower discharge grille is disposed inside a discharge port in order to guide air discharged downwardly in the radially outward direction, it is possible to more effectively remove large and heavy particles.

[0130] According to at least one of the embodiments of the present disclosure, because a plurality of grilles having a concentric circle structure is provided and the length of each of the grilles is set to be greater than an interval between the grilles, it is possible to effectively change the direction of the discharge airflow.

[0131] According to at least one of the embodiments of the present disclosure, the plurality of grilles is bent at a predetermined angle in the outward direction, thereby guiding an airflow in the radially outward direction.

[0132] According to at least one of the embodiments of the present disclosure, because an upwardly protruding boss is formed on the upper surface of a bottom plate that is disposed below the blower fan and the filter so as to be in contact with the floor, it is possible to create an airflow that is effective in removing allergen particles.

[0133] According to at least one of the embodiments of the present disclosure, flow resistance may be reduced due to the boss protruding upward from an end portion of the bottom plate.

[0134] According to at least one of the embodiments of the present disclosure, because an airflow guide is disposed on the upper surface of the bottom plate in order to guide air discharged downwardly through the discharge port in the lateral direction, it is possible to effectively change the direction of the discharge airflow.

[0135] According to at least one of the embodiments of the present disclosure, because the airflow guide includes a curved portion, flow resistance may be reduced.

[0136] The effects achievable through the disclosure are not limited to the above-mentioned effects, and other effects not mentioned herein will be clearly understood by those skilled in the art from

the description of the claims.

[0137] Other effects will be clearly understood by those skilled in the art from the description of the claims.

[0138] Although the present disclosure has been described with reference to specific embodiments shown in the drawings, it is apparent to those skilled in the art that the present disclosure is not limited to those embodiments and is embodied in many forms without departing from the scope of the present disclosure, which is described in the following claims. These modifications should not be individually understood from the technical spirit or scope of the present disclosure.

Claims

1. An air cleaner comprising: a case including a suction port disposed in a peripheral surface of the case, the suction port being configured to introduce air to an inside of the case; a filter configured to remove foreign matter from the air introduced through the suction port; a blower fan disposed in the case, the blower fan being configured to blow the air introduced through the suction port after the air is filtered by the filter; a discharge port disposed below the blower fan and the filter, the discharge port being configured to discharge the air blown by the blower fan in a downward direction; and a bottom plate disposed below the blower fan and the filter, the bottom plate being configured to be in contact with a floor, the bottom plate comprising a boss protruding upward.
2. The air cleaner according to claim 1, wherein the boss comprises a ring shape and is disposed along an edge of the bottom plate.
3. The air cleaner according to claim 1, wherein the boss comprises an inclined surface, and wherein a height of the inclined surface increases in a radially outward direction.
4. The air cleaner according to claim 1, wherein the bottom plate further comprises a curved portion and a flat portion, the curved portion and the flat portion both being disposed on an upper surface of the bottom plate, and the flat portion extending laterally from the curved portion, and wherein the boss protrudes upward from an end portion of the flat portion.
5. The air cleaner according to claim 4, wherein a maximum height of the boss is less than 10% of a radius of curvature of the curved portion.
6. The air cleaner according to claim 4, wherein the bottom plate further comprises a central pillar configured to support the blower fan, and wherein the curved portion is disposed to surround the central pillar.
7. The air cleaner according to claim 6, wherein an angle between the central pillar and the curved portion is smaller than an angle of a discharge airflow through the discharge port and the central pillar.
8. The air cleaner according to claim 1, further comprising a lower discharge grille, the lower discharge grille comprising a plurality of grilles disposed inside the discharge port and being configured to guide air discharged downwardly in a radially outward direction.
9. The air cleaner according to claim 8, wherein the plurality of grilles are arranged in a concentric circle structure.
10. An air cleaner comprising: a case including a suction port disposed in a peripheral surface of the case, the suction port being configured to introduce air to an inside of the case; a filter configured to remove foreign matter from the air introduced through the suction port; a blower fan disposed in the case, the blower fan being configured to blow the air introduced through the suction port after the air is filtered by the filter; a discharge port disposed below the blower fan and the filter, the discharge port being configured to discharge the air blown by the blower fan in a downward direction; and a lower discharge grille comprising a plurality of grilles disposed inside the discharge port, the plurality of grilles being arranged in a concentric circle structure and configured to guide the air discharged downwardly in a radially outward direction.
11. The air cleaner according to claim 10, wherein each grille of the plurality of grilles has a length

that is greater than a length of an interval between the plurality of grilles.

12. The air cleaner according to claim 10, wherein each of the plurality of grilles is bent at an angle in the radially outward direction.

13. The air cleaner according to claim 12, wherein the angle is in a range of 20 degrees to 40 degrees.

14. The air cleaner according to claim 12, wherein each of the plurality of grilles comprises: a curved portion bent in the radially outward direction; and a protruding portion protruding from an end portion of the curved portion in the radially outward direction.

15. The air cleaner according to claim 14, wherein the protruding portion has a smaller thickness than a thickness of the curved portion.

16. The air cleaner according to claim 14, wherein a length of the protruding portion in the radially outward direction is greater than a thickness of the curved portion.

17. The air cleaner according to claim 10, further comprising a bottom plate disposed below the blower fan and the filter that is configured to be in contact with a floor.

18. The air cleaner according to claim 17, wherein the bottom plate comprises an airflow guide disposed on an upper surface of the bottom plate, the airflow guide being configured to guide the air discharged downwardly through the discharge port in a lateral direction.

19. The air cleaner according to claim 18, wherein the airflow guide comprises: a curved portion; a flat portion extending laterally from the curved portion; and a boss protruding upward from an end portion of the flat portion.

20. The air cleaner according to claim 19, wherein the boss includes a ring shape and is disposed along an edge of the airflow guide.
