

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402558
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	He; Kefeng et al.

Trimmer head and trimmer thereof

Abstract

A trimmer and a trimmer head include an upper cover assembly being connected to and driven by a motor, wherein the upper cover assembly is configured to be removably connected to at least one of a first trimming assembly or a second trimming assembly selectively, and is provided with at least one connection hole in its side wall; the first trimming assembly is configured to include a first lower cover, a first cutting member, and a first base; the second trimming assembly is configured to include a second lower cover, a second cutting member, and a second base; wherein the first base is at least partially inserted into the connection hole when the first trimming assembly is mounted, and the second lower cover is at least partially inserted into the connection hole when the second trimming assembly is mounted.

Inventors: He; Kefeng (Zhejiang, CN), He; Zhuangzhuang (Zhejiang, CN), He; Caifen (Zhejiang, CN), Wang; Haiwei (Zhejiang, CN), Cheng; Yinhua (Zhejiang, CN)

Applicant: ZHEJIANG SUNSEEKER INDUSTRIAL CO., LTD. (Zhejiang, CN)

Family ID: 86384663

Assignee: ZHEJIANG SUNSEEKER INDUSTRIAL CO., LTD. (Zhejiang, CN)

Appl. No.: 17/988312

Filed: November 16, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230157206 A1	May. 25, 2023

Publication Classification

Int. Cl.: A01D34/416 (20060101)

U.S. Cl.:

CPC **A01D34/4165** (20130101); **A01D34/4168** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0029483	12/2001	Price	30/276	A01D 34/736
2008/0010836	12/2007	Lacona	30/122	A01D 42/005
2010/0083506	12/2009	Bennett	30/122	A01D 34/4168
2014/0150267	12/2013	Sowell	30/340	A01D 34/84
2020/0000025	12/2019	Morabit	N/A	A01D 34/4165
2023/0157206	12/2022	He	30/276	A01D 34/4165

Primary Examiner: Payer; Hwei-Siu C

Attorney, Agent or Firm: KARCESKI IP LAW, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application relies on and claims priority to the following applications: Chinese Patent Application No. CN2021229092651, filed on Nov. 19, 2021 (published as CN217116927U), and Chinese Patent Application No. CN2021228569659, filed on Nov. 19, 2021 (published as CN217509420U), the entire contents of both of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The embodiments of the disclosure refer generally to garden tools, and more specifically to a trimmer head and a trimmer thereof.

BACKGROUND

(3) There are not many kinds of trimmer heads on the market with interchangeable string and blades. One of the main reasons is that the prior art needs to make a big change in the structure when designing two different kinds of trimming assembly of string and blades to one trimmer head. Especially for the string trimmer, the connection position of the trimming line is raised from the middle of the lower cover to the upper edge of the lower cover. In this way the distance between the trimming line and the lawn ground increases, which reduces the trimming efficiency and makes it more difficult to control the flatness of the lawn.

(4) On the other hand, in prior arts for the blade trimmer, the blade is mounted on the lower housing through the plug-in connector. In the actual trimming operation, when the blade encounters a hard object, the force on the blade is directly transferred to the lower housing. It is difficult to separately strengthen the stressed position of the lower housing as molded in one piece and easy to damage. Therefore, the whole lower housing needs to be replaced when damaged.

SUMMARY

(5) As will be disclosed in detail in the description, the inventors have realized that the traditional trimmer head brings about at least two problems. It is therefore an object of the teachings of this application to overcome or at least reduce those problems.

(6) According to one aspect there is provided a trimmer head which enables for a high-efficient trimming comprising an upper cover assembly being connected to and driven by a motor, wherein the upper cover assembly is configured to be removably connected to a first trimming assembly or a second trimming assembly selectively, and is provided with at least one connection hole in its side wall; the first trimming assembly is configured to include a first lower cover, a first cutting member and a first base; the second trimming assembly is configured to include a second lower cover, a second cutting member and a second base; wherein the first base is at least partially inserted into the connection hole when the first trimming assembly is mounted, and the second lower cover is at least partially inserted into the connection hole when the second trimming assembly is mounted.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The embodiments of the disclosure will be described in further detail under reference to the accompanying drawings in which:

(2) FIG. 1 is a perspective view of the trimmer head of an embodiment of the disclosure with the first trimming assembly mounted, with the side facing upward in the figure facing downward during operation.

(3) FIG. 2 is a perspective view of the trimmer head of an embodiment of the disclosure with the second trimming assembly mounted, with the side facing upward in the figure facing downward during operation.

(4) FIG. 3 is a exploded perspective view of the trimmer head of an embodiment of the disclosure with the first trimming assembly mounted, with the side facing upward in the figure facing downward during operation.

(5) FIG. 4 is a exploded perspective view of the trimmer head of an embodiment of the disclosure with the second trimming assembly mounted, with the side facing upward in the figure facing downward during operation.

(6) FIG. 5 is a cross-sectional view of the trimmer head of an embodiment of the disclosure with the first trimming assembly mounted, with the side facing upward in the figure facing downward during operation.

(7) FIG. 6 is a cross-sectional view of the trimmer head of an embodiment of the disclosure with the second trimming assembly mounted, with the side facing upward in the figure facing downward during operation.

(8) FIG. 7 is a perspective view of the upper cover of an embodiment of the disclosure when it is assembled with the first base.

(9) FIG. 8 is a perspective view of the mounting status of the holder into the upper cover and the first base of an embodiment of the disclosure.

DESCRIPTION OF EMBODIMENTS

(10) The following description is made for the purpose of illustrating the general principles of the present trimmer head and trimmer, and is not meant to limit the inventive concepts claimed in this document. Further, particular features described in this document can be used in combination with other described features in each of the various possible combinations and permutations.

(11) Unless otherwise specifically defined in this document, all terms are to be given their broadest possible interpretation including meanings implied from the specification as well as meanings understood by those skilled in the art and/or as defined in dictionaries, treatises, etc.

(12) It must also be noted that, as used in the specification and the appended claims, the singular forms “a”, “an” and “the” include plural referents unless otherwise specified. Unless defined otherwise, all technical and scientific terms used herein have the same meanings as commonly understood by one of ordinary skill in the art. All publications mentioned in this document are incorporated by reference. Nothing in this document is to be construed as an admission that the embodiments described in this document are not entitled to antedate such disclosure by virtue of prior invention. As used herein, the term “comprising” means “including, but not limited to”. Additionally, use the term “couple”, “coupled”, or “coupled to” may imply that two or more elements may be directly connected or may be indirectly coupled through one or more intervening elements.

(13) In this document, position-identifying terms such as “vertical”, “horizontal”, “front”, “rear”, “top”, and “bottom” are not intended to limit the invention to a particular direction or orientation, but instead are only intended to denote relative positions, or positions corresponding to directions shown when a structure or product is oriented as shown in the Figures.

(14) Referring to FIGS. 1, 3, 5, 7 and 8, an embodiment shows a trimmer head comprising an upper cover assembly **001** being connected to and driven by a motor, wherein the upper cover assembly **001** is configured to be removably connected to a first trimming assembly **100** or a second trimming assembly **200** selectively, and is provided with at least one connection hole **003** in its side wall. In this embodiment, a connection hole **003** is symmetrically provided on both walls of the upper cover assembly **001** along the bottom center line.

(15) The first trimming assembly **100** is configured to include a first lower cover **01**, a first cutting member and a first base **111**. In this embodiment, the first base **111** is connected to the upper cover assembly **001** when the first trimming assembly **100** is mounted. The first base **111** is configured to include a first fixing part **12** that is at least partially inserted into the connection hole **003** when the first trimming assembly **100** is mounted.

(16) Referring to FIGS. 3 and 5, the first lower cover **01** is removably assembled with the upper cover assembly **001** by a fastener **005** when the first trimming assembly **100** is mounted in the upper cover assembly **001**. In this embodiment, the fastener **005** is configured as a bolt. The upper cover assembly **001** has a raised pillar **101** in the bottom center and the pillar **101** is provided with a threaded hole **102** in the center. The first base **111** is set on the outer surface of the pillar **101**, and the first lower cover **01** is mounted at the threaded hole **102** by the bolt.

(17) Referring to FIG. 3, the first cutting member and the first base **111** are clamped to the first lower cover **01** by the upper cover assembly **001**. The first base **111** is configured to be made of a hard material with a certain elasticity and is further configured as an oblong plate with a round projection in the center, and the projection is provided with a first connection part **118** adapted to the outer surface of the pillar **101**. Each end of the first base **111** is provided with a first extension part **119** with the same cross-section as the connection hole **003** and facing the same side of the plate. In this embodiment, the extending direction of the first extension part **119** is generally perpendicular to the extending direction of the first base **111**. The plate surface opposite the round projection is provided with a second connection part **117** provided symmetrically about the first connection part **118**. In this embodiment, the first connection part **118** is configured as a hole adapted to the pillar **101**, and the second connection part **117** is configured to include at least one projection. Both of the first extension parts **119** corresponding to the connection holes **003** are extruded inward from the opening side of the upper cover assembly **001**. A first fixing part **12** is provided on the outer side of the end of the first extension part **119** to make it easy to mount at the initial stage. By extruding the first base **111**, the first fixing part **12** is conflict with the inner wall around the corresponding connection hole **003**. By continuing to apply the extrusion force, the first base **111** produces elastic deformation. Referring to FIG. 7, the conflict between the two disappears until the first base **111** is pushed into the connection hole **003**, then the first base **111** returns to the initial state. A clearance **115** used to mount the first cutting member is on the side of the connection

hole **003** towards the second connection part **117** when mounted.

(18) The first cutting member includes a holder **112** and a blade **114**. The holder **112** is configured to be removably connected to the first base **111**. In this embodiment, the blade **114** is configured to be movably connected to the holder **112** by a connector **113**. In other embodiments, the blade **114** may also be configured to be integrally formed with the holder **112**. One end of the holder **112** passes through the connection hole **003** into the upper cover assembly **001** and is connected to the first base, and the other end of the holder **112** is mounted with a blade **114**. The holder **112** is configured as an oblong plate with a width the same as or slightly smaller than the connection hole **003**. One end of the plate surface is provided with a third connection part **116** adapted to the second connection part **117**, and the other end of the plate surface is thickened and is provided with a fourth connection part **120** with the connector **113**. The end of the third connection part **116** of the holder **112** passes through the clearance **115** and the third connection part **116** is connected to the second connection part **117**. The other end of the holder **112** is exposed outside the upper cover assembly **001**. The bottom of the first lower cover **01** is pressed against the holder **112**, so that the upper and lower positions of the holder **112** are limited. At the same time, the position of the holder **112** on both sides has been limited by the connection hole **003** in the upper cover assembly **001**, so the position of the holder **112** is completely limited, so that the blade **114** on the holder **112** can be positioned by the connector **113**. In this embodiment, the first trimming assembly **100** includes two blades **114**. In other embodiments, the number of blades can also be one, three, four, etc., just by changing the number of the corresponding connection holes **003** and making corresponding adjustments to the number and the structure of the adapting parts in the holder assembly **110**. In this embodiment, the second connection part **117** is configured as a projection and the third connection part **116** is configured as a hole adapted to the projection. In other embodiments, the third connection part **116** is configured as a projection and the second connection part **117** is configured as a hole adapted to the projection.

(19) Referring to FIG. 7, when mounting the first trimming assembly **100**, firstly to place the opening of the upper cover **001** upward, and then to place the first base **111** into the upper cover **001** with the first connection part **118** corresponding to the pillar **101**, and the first base **111** is pressed to touch the bottom of the upper cover **001**. At this time, the two first extension parts **119** are inserted into the corresponding connection holes **003**. Then the holder **112** passes through the clearance **115** from the outside and is inserted by the second connection part **117** referring to FIG. 8. The thickened end of the plate surface of the holder **112** is exposed to the outer wall of the upper cover **001**. The first lower cover **01** is connected to the upper cover **001** by the fastener **005**. After the connection, at least one rib of the first lower cover **01** presses against the holder **112**, and the first base **111** and the holder **112** are pressed together at the bottom of the upper cover assembly **001**. The holder **112** has been limited to both sides by a connection hole before, so the position of the holder **112** is completely limited by pressing. Finally, the blade **114** is mounted on the holder **112** through the connector **113**, and all connections are completed since then. In some embodiments, the blade **114** and the holder **112** may be pre-mounted together. In other embodiments, the holder **112**, the connector **113**, and the blade **114** may be sold and used as an assembly.

(20) Referring to FIGS. 2, 4 and 6, a trimming head is disclosed and includes an upper cover assembly **001** and a second trimming assembly. The second trimming assembly **200** is configured to include a second lower cover **02**, a second cutting member, and a second base **210**. In this embodiment, the second base **210** is movably connected to the upper cover assembly **001** when the second trimming assembly **200** is mounted. The second lower cover **02** includes a second fixing part which is at least partially inserted into the connection hole **003** when the second trimming assembly **200** is mounted. The connection hole **003** provides space for the second fixing part **22** in the second lower cover **02** to engage when the second trimming assembly **200** is used.

(21) Referring to FIG. 4, the second lower cover **02** is configured to include at least one second

extension part **021** being configured to be generally perpendicular to the second lower cover **02**; the second fixing part **22** is configured to be provided on the outside of the end of the second extension part **021** away from the second lower cover **02**. The second fixing part **22** is inserted into the connection hole **003** to engage when the second lower cover **02** is assembled with the upper cover assembly **001**. In this embodiment, two second extension parts **021** are provided on the second lower cover **02** symmetrically about the center axis of rotation.

(22) The second trimming assembly **200** is provided with at least one trimming line **211**. In this embodiment, the trimming line is wound on a wire reel with at least one end extending from the wire reel and extending out of the upper cover assembly **001**. Further, in this embodiment, the both ends of the trimming line extend from the wire reel and extend out of the upper cover assembly **001**. The side wall of the upper cover assembly **001** is provided with an opening **002** for the trimming line **211** to pass through. The opening **002** is used to limit the position of the trimming line **211**. Referring to FIG. 4, the second base **210** is configured to include a wire reel, and the second lower cover **02** is covered outside the second base **210**, which surrounds the second base **210** as a whole.

(23) Further, two longitudinal ribs **006** are provided along the inner side wall on both sides of the connection hole **003** to strengthen the connection hole **003**, and also to guide the first base **111** or the second lower cover **02** when mounting.

(24) The first lower cover **01**, the first base **111**, the holder **112**, the connector **113** and the blade **114** involved in the first trimming assembly **100** are removed in the opposite order of mounting when replacing the first trimming assembly **100** with the second trimming assembly **200**; in some embodiments, the holder **112**, the connector **113** and the blade **114** are used as an assembly which can be removed as a whole. Then, the second base **210** is mounted into the upper cover assembly **001**, and then the second fixing part **22** on the second lower cover **02** is pressed downward against the position of the connection hole **003**. The two longitudinal ribs provided on both sides of the connection hole **003** are used to guide the second fixing part **22**. The second lower cover **02** is provided with elastic material, which makes the second fixing part **22** have better elastic restoration ability. The second fixing part **22** is deformed by pressure and bends or shrinks inward when the second fixing part **22** enters the inner wall of the second lower cover **02**. The second fixing part **22** is inserted into the connection hole **003** and returns to its original status, and then the mounting is completed.

(25) An embodiment also discloses a trimmer including the above mentioned trimmer head.

(26) The upper cover assembly **001** is designed to be used in two modes, so the connection hole **003** in the side wall of the upper cover assembly **001** plays different roles in different modes. The connection hole **003** provides the mounting area for the first trimming assembly **100** when using the blade trimming mode; the connection hole **003** provides space for the second fixing part **22** in the second lower cover **02** to engage when using the second trimming assembly **200**. On the one hand, with the above-mentioned embodiments of the trimming head, only need to replace the blade and string components and the corresponding lower cover accordingly when the type of the cutting member need to be changed, and the upper cover assembly as the largest volume part is shared. In this way, the components that need to be replaced in the two trimming modes are relatively independent and compact, so that the cost of manufacturing and maintenance replacement can be reduced accordingly. On the other hand, the trimming line of the second trimming assembly is provided in the middle position of the lower cover, thus solving the problem of low efficiency when cutting grass with the conventional trimmer head, and reducing the difficulty of controlling the flatness of the lawn. In addition, the overall structure shape of the upper cover is used to provide a connection hole in its side wall, and the first base and holder are mounted inside the upper cover. One end of the holder extends from the connection hole, and the first cutting member is mounted at the part of the holder extending from the connection hole, and the part is closely adapted to the width direction of the connection hole. The holder, the first base and the upper cover

are in a fastened state after the lower cover is fixedly connected, that is, the holder and the first base are equivalent to a whole. When the blade is impacted during the cutting, the part where the blade is mounted is under a huge circumferential force, and the circumferential force is transferred to the holder and the first base and is absorbed by the connection part between the holder and the first base and the connection hole. And the holder and the first base clamped by the lower cover can also share the force of the connection part. So, the impact resistance can be greatly enhanced under the combination.

(27) The descriptions of the various embodiments of the present disclosure have been presented for purposes of illustration, but are not intended to be exhaustive or limited to the embodiments disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the disclosure. The terminology used herein was chosen to best explain the principles of the embodiment, the practical application or technical improvement over technologies found in the marketplace, or to enable others of ordinary skill in the art to understand the embodiments disclosed herein.

Claims

1. A trimmer head, comprising: an upper cover assembly being connected to and driven by a motor, wherein the upper cover assembly is configured to be removably connected to at least one of a first trimming assembly or a second trimming assembly different from the first trimming assembly selectively, and is provided with at least one connection hole in its side wall; the first trimming assembly is configured to include a first lower cover, a first cutting member, and a first base; the second trimming assembly is configured to include a second lower cover, a second cutting member, and a second base; and wherein the first base is at least partially inserted into the connection hole when the first trimming assembly is selectively mounted to the upper cover assembly, and the second lower cover is at least partially inserted into the connection hole when the second trimming assembly is selectively mounted to the upper cover assembly.
2. The trimmer head in accordance with claim 1, wherein the first base is connected to the upper cover assembly when the first trimming assembly is selectively mounted to the upper cover assembly.
3. The trimmer head in accordance with claim 1, wherein the second base is movably connected to the upper cover assembly when the second trimming assembly is selectively mounted to the upper cover assembly.
4. The trimmer head in accordance with claim 1, wherein the first cutting member passes at least partially through the connection hole when the first trimming assembly is mounted.
5. The trimmer head in accordance with claim 1, wherein the first base is configured to include a first fixing part, and the second lower cover is configured to include a second fixing part; wherein the first fixing part is at least partially inserted into the connection hole when the first trimming assembly is selectively mounted to the upper cover assembly, and the second fixing part is at least partially inserted into the connection hole when the second trimming assembly is selectively mounted to the upper cover assembly.
6. The trimmer head in accordance with claim 5, wherein the first base is configured to include a first connection part and a second connection part; the first connection part and the second connection part are configured to be spaced along an extending direction of the first base; and the first connection part is configured to be removably connected to the upper cover assembly and the second connection part is configured to be removably connected to the first cutting member.
7. The trimmer head in accordance with claim 6, wherein the first base is provided with a first extension part at an end away from the first connection part, and an extending direction of the first extension part is generally perpendicular to the extending direction of the first base; and the first fixing part is disposed a greater radial distance from a rotational axis of the trimmer head than the

first extension part.

8. The trimmer head in accordance with claim 6, wherein the first cutting member is configured to include a holder and a blade; and wherein the holder passes at least partially through the connection hole when the first trimming assembly is selectively mounted to the upper cover assembly, and an end of the holder that is inside the upper cover assembly is removably connected to the first base.
 9. The trimmer head in accordance with claim 8, wherein the holder is configured to include a third connection part and a fourth connection part; the third connection part is configured to be removably connected to the second connection part; and the fourth connection part is configured to be connected to the blade.
 10. The trimmer head in accordance with claim 9, wherein the second connection part is configured to include at least one projection, and the third connection part is configured to include at least one hole adapted to the projection.
 11. The trimmer head in accordance with claim 9, wherein the blade is configured to be movably connected to the fourth connection part.
 12. The trimmer head in accordance with claim 8, wherein the holder is configured as an oblong plate with a width adapted to the connection hole.
 13. The trimmer head in accordance with claim 8, wherein the thickness of the holder is adapted to a clearance that is between the first fixing part and the connection hole when the first base is selectively connected to the upper cover assembly.
 14. The trimmer head in accordance with claim 8, wherein the bottom of the first lower cover abuts on the holder when the first trimming assembly is selectively mounted to the upper cover assembly.
 15. The trimmer head in accordance with claim 8, wherein the first lower cover is provided with a rib; and the rib presses against the holder when the first trimming assembly is selectively mounted to the upper cover assembly.
 16. The trimmer head in accordance with claim 6, wherein the upper cover assembly is configured to include a pillar; and the first connection part is configured as a hole adapted to the pillar.
 17. The trimmer head in accordance with claim 5, wherein the second lower cover is configured to include a second extension part being configured to be generally perpendicular to the second lower cover; and the second fixing part is configured to be provided on the outside of the end of the second extension part away from the second lower cover.
 18. The trimmer head in accordance with claim 1, wherein the second base is configured as a wire reel and the second cutting member is configured as a trimmer line; the upper cover assembly is provided with at least one opening in the side wall separate from the connection hole; and the trimmer line passes through the opening when the second trimming assembly is mounted.
 19. The trimmer head in accordance with claim 1, wherein the first lower cover is selectively connected to the upper cover assembly by a fastener.
 20. A trimmer comprising a trimmer head: wherein the trimmer head comprises an upper cover assembly being connected to and driven by a motor, wherein the upper cover assembly is configured to be removably connected to at least one of a first trimming assembly or a second trimming assembly different from the first trimming assembly selectively, and is provided with at least one connection hole in its side wall; the first trimming assembly is configured to include a first lower cover, a first cutting member and a first base; the second trimming assembly is configured to include a second lower cover, a second cutting member and a second base; and wherein the first base is at least partially inserted into the connection hole when the first trimming assembly is selectively mounted to the upper cover assembly, and the second lower cover is at least partially inserted into the connection hole when the second trimming assembly is selectively mounted to the upper cover assembly.
-