

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12402890

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Lark; Robert K. et al.

Medical cutting devices having a working blade body with static components and related methods of use

Abstract

Medical cutting device having a working blade body with static components and related methods of use are disclosed. According to an aspect, a cutting device includes a working blade body having a top surface and a bottom surface. The working blade body defines a plurality of apertures extending between the top surface and the bottom surface. Further, the cutting device includes a plurality of static components each having a top portion and a bottom portion. Each static component is associated with one of the apertures and has a middle portion that is between the top portion and the bottom portion and positioned within the associated aperture. The top portion and the bottom portion extend past the top surface and the bottom surface, respectively, of the working blade body.

Inventors: Lark; Robert K. (Chapel Hill, NC), Skolnick; Edward C. (Denville, NJ), Kaeslin; Antoine R. (Bethel, CT)

Applicant: Innovations 4 Surgery, LLC (Chapel Hill, NC)

Family ID: 86766808

Assignee: Innovations 4 Surgery, LLC (Chapel Hill, NC)

Appl. No.: 18/087766

Filed: December 22, 2022

Prior Publication Data

Document Identifier

US 20230190304 A1

Publication Date

Jun. 22, 2023

Related U.S. Application Data

us-provisional-application US 63292438 20211222

Publication Classification

Int. Cl.: **A61B17/14** (20060101); **A61B17/00** (20060101); **A61B17/32** (20060101); **A61B17/56** (20060101)

U.S. Cl.:

CPC **A61B17/142** (20161101); **A61B17/32002** (20130101); **A61B17/320068** (20130101); A61B2017/00101 (20130101); A61B2017/00115 (20130101); A61B2017/00123 (20130101); A61B2017/320075 (20170801); A61B2017/564 (20130101); A61B2217/007 (20130101)

Field of Classification Search

CPC: A61B (17/142); A61B (2017/320028); A61B (2017/32002); A61B (2017/320068); A61B (2017/320077)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4008720	12/1976	Brinckmann et al.	N/A	N/A
5087261	12/1991	Ryd et al.	N/A	N/A
5122142	12/1991	Pascaloff	N/A	N/A
5188102	12/1992	Idemoto et al.	N/A	N/A
5261922	12/1992	Hood	N/A	N/A
5728130	12/1997	Ishikawa	N/A	N/A
6379371	12/2001	Novak	N/A	N/A
6443969	12/2001	Novak	N/A	N/A
8343178	12/2012	Novak	N/A	N/A
8348880	12/2012	Messerly et al.	N/A	N/A
D680218	12/2012	Darian	N/A	N/A
9320528	12/2015	Voic	N/A	N/A
9554809	12/2016	Lark	N/A	N/A
10238415	12/2018	Naono	N/A	N/A
10702296	12/2019	Boudreaux	N/A	N/A
2003/0176867	12/2002	Long	606/79	A61B 17/142
2003/0204199	12/2002	Novak	N/A	N/A
2005/0273127	12/2004	Novak	N/A	N/A
2008/0009848	12/2007	Paraschiv	N/A	N/A
2013/0204256	12/2012	Wang	606/82	B23D 61/006
2013/0204285	12/2012	Gouery	N/A	N/A
2015/0005771	12/2014	Voic	N/A	N/A
2015/0088137	12/2014	Manna	N/A	N/A
2016/0089155	12/2015	Lark	N/A	N/A
2017/0056052	12/2016	Dickerson	N/A	N/A
2017/0340339	12/2016	Madan	N/A	N/A
2017/0340344	12/2016	Boudreaux	N/A	N/A
2017/0340345	12/2016	Yates	N/A	N/A

2018/0344346	12/2017	Naono	N/A	N/A
2019/0240751	12/2018	Skolnick	N/A	A61B 17/142
2020/0001494	12/2019	Gisler	N/A	A61B 17/142
2021/0113215	12/2020	Gisler	N/A	A61B 17/1637
2021/0121195	12/2020	Richards	N/A	N/A
2021/0186525	12/2020	Lark	N/A	N/A
2023/0190327	12/2022	Lark	606/167	A61B 17/320068
2024/0307070	12/2023	Uhri	N/A	A61B 17/142

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
202008017023	12/2008	DE	A61B 17/14
102008062880	12/2009	DE	A61B 17/14

Primary Examiner: Lawson; Matthew J

Attorney, Agent or Firm: Olive Law Group, PLLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application No. 63/292,438, filed Dec. 22, 2021, and titled MEDICAL DEVICES AND RELATED METHODS FOR TRANSFORMING BONE, OTHER TISSUE, OR MATERIAL, the content of which is incorporated herein by reference in its entirety. (2) This application is related to U.S. Nonprovisional patent application Ser. No. 18/087,715, filed Dec. 22, 2022, and titled MEDICAL CUTTING DEVICES WITH A STATIC CASING AND A BLADE WORKING BODY OF GREATER WIDTH AND RELATED METHODS. (3) This application is related to U.S. Nonprovisional patent application Ser. No. 18/087,727, filed Dec. 22, 2022, and titled MEDICAL CUTTING DEVICES WITH STATIC COMPONENTS HAVING TEMPERATURE SENSORS AND RELATED METHODS. (4) This application is related to U.S. Nonprovisional patent application Ser. No. 18/087,741, filed Dec. 22, 2022, and titled MEDICAL CUTTING DEVICES WITH COOLANT MODULES AND CHANNELS AND ASSOCIATED METHODS. (5) This application is related to U.S. Nonprovisional patent application Ser. No. 18/087,749, filed Dec. 22, 2022, and titled MEDICAL CUTTING DEVICES HAVING A BLADE WORKING BODY THAT DEFINES AN OPENING FOR EMITTING COOLANT THEREFROM AN RELATED METHODS.

TECHNICAL FIELD

(1) The presently disclosed subject matter relates generally to medical devices. Particularly, the presently disclosed subject matter relates to medical cutting device having a working blade body with static components and related methods of use.

BACKGROUND

(2) Traditional surgical saws, such as oscillating saws and reciprocating saws, allow users to cut bones (i.e. perform osteotomies) of relatively large diameters, such as the tibia and femur. These types of surgical saws, however, which are similar in many ways to the toothed saws used to cut wood, metal, and plastic, have significant disadvantages with respect to a patient's well-being. Because surgical saws utilize rapid motion of the saw blade to cut biological tissues, such as bone and cartilage, a significant amount of heat is generated along the blade and particularly at the blade and bone interface. This can be harmful to the patient since prolonged exposure of bone cells to temperatures at or in excess of 47° C. leads to necrosis of those osteocytes. Another disadvantage

of these oscillating and reciprocating bone saws is that they produce uneven cuts, preventing ideal realignment and reduction of the osteotomy gap, which is detrimental to efficient healing of the bone. Oscillating and, in particular, reciprocating bone saws, which utilize a number of sharpened teeth along their cutting edges, can tear neighboring soft tissues that are inadvertently caught in the serrations of the rapidly moving blade. Tearing of these soft tissues leads to significant blood loss and potential nerve damage, which undoubtedly hampers the health of the patient.

(3) Traditional oscillating and reciprocating bone saws have employed a variety of different measures to address these disadvantages. With respect to the generation of excessive heat, these surgical saws can utilize irrigation systems to flush the surgical site near the blade and bone interface. These irrigation systems can be separate, requiring an additional device at the surgical site, or integrated. Although effective at flushing a surgical site of unwanted sources of added friction, these irrigation systems are relatively ineffective at actually cooling the blade at the blade and bone interface. For example, one design for a surgical saw that incorporates a means for irrigation comprises a channel between otherwise parallel portions of a saw blade through which fluid can flow out into the surgical site (See U.S. Pat. No. 5,087,261). This channel, though, can be easily compacted with surgical debris, rendering the integrated irrigation system unusable. In addition, providing a channel between parallel portions of the saw blade necessarily increases the likelihood of a wider, more uneven cut. Other designs for an oscillating bone saw include outlets along the blade's edge to facilitate irrigation along the blade and bone interface (See U.S. Pat. Nos. 4,008,720 and 5,122,142). However, these channels can be similarly compacted with surgical debris, rendering them useless. More so, channels along the very blade edge result in a blade edge that is not continuous, which reduces the cutting efficiency of the blade. Despite any potential efficacy in flushing a site of surgical debris, these systems do very little to actually cool the very blade edge, specifically at the blade and bone interface. Additionally, having copious amounts of irrigation fluid in the surgical site can hamper the surgeon's ability to visualize important anatomic structures.

(4) Just as with saws used to cut wood, metal, and plastic, a user can avoid rough or uneven cuts by using a saw blade that incorporates more teeth along the edge of the blade and/or teeth having differing angles. While this can produce a relatively finer cut, the resulting cut still leaves much to be desired in terms of producing smooth, even bone surfaces. Cutting guides, which help to stabilize the blade and keep it on a prescribed plane, are often utilized during an osteotomy to improve the precision of the cut. Still, the improvement is not substantial enough to consider these measures a long-term solution with respect to producing smooth bone cuts. In fact, adding teeth or guiding the blade edge have little effect in preventing inadvertent tearing of neighboring soft tissues. Although efforts are taken to protect soft tissues from damage and prevent significant blood loss, the inherently close confines typical in performing any osteotomy make it extremely difficult to completely eliminate such damage, especially to those tissues that are unseen or positioned beneath the bone being cut. This is compounded by the fact that the saw blades used with many oscillating and reciprocating bone saws are relatively large.

(5) A variety of ultrasonic surgical devices are now utilized in a number of surgical procedures, including surgical blades that are capable of cutting biological tissues such as bone and cartilage. These types of saw blades are powered by high-frequency and high-amplitude sound waves, consequent vibrational energy being concentrated at the blade's edge by way of an ultrasonic horn. Being powered by sound waves, neighboring soft tissues are not damaged by these types of blades because the blade's edge effectively rebounds due to the elasticity of the soft tissue. Thus, the significant blood loss common with use of traditional bone saws is prevented. In addition, significantly more precise cuts are possible using ultrasonic bone cutting devices, in part, because the blade's edge does not require serrations. Instead, a continuous and sharpened edge, similar to that of a typical scalpel, enables a user to better manipulate the surgical device without the deflection caused by serrations, which is common when using oscillating and reciprocating bone

saws. Although ultrasonic cutting blades are advantageous in that they are less likely to tear neighboring soft tissues and more likely to produce relatively more even cuts, these types of blades still generate considerable amounts of heat.

(6) As with traditional bone saws, separate or integrated irrigation systems are often utilized in order to flush the surgical site and generally provide some measure of cooling effect to the blade. However, many of these blades suffer from the same disadvantages as traditional bone saws that have tried to incorporate similar measures. For example, providing openings along the blade's edge through which fluid flows introduces voids in the cutting edge, thereby inhibiting the cutting efficiency of the blade (See U.S. Pat. No. 5,188,102). In addition, these fluid openings can be readily compacted with surgical debris, rendering them useless for their intended function. In other blade designs, the continuity of the blade is maintained and a fluid outlet is positioned just before the blade's edge (See U.S. Pat. No. 8,348,880). However, this fluid outlet merely irrigates the surgical site since it is positioned too far from the blade and bone interface to actually provide the necessary cooling effect. Also, it irrigates only one side of the blade. Another design for an ultrasonic cutting device, which claims to cool the blade, incorporates an irrigation output located centrally along the longitudinal axis of the blade (See U.S. Pat. No. 6,379,371). A recess in the center of the blade tip allows fluid to flow out of this output and toward the blade's edge, flow that is propelled by a source of pressure. However, the positioning of this irrigation output within the contour of the blade tip results in a bifurcation or splitting of the irrigation flow, such splitting tending to distribute fluid at an angle away from the blade's edge. Mentioned above, the excessive heat generated using any cutting blade, including an ultrasonic cutting blade, is focused most significantly at the blade and bone interface. This example for an ultrasonic blade with cooling capabilities, then, does little to actually cool the blade at the blade and bone interface, but instead serves merely to flush debris from the surgical site. Again, having copious amounts of irrigation fluid in the surgical site can hamper the surgeon's ability to visualize important anatomic structures. Furthermore, this ultrasonic blade is not well-suited to cutting large cross-sections of bone and is used almost exclusively in spine, oral or maxillofacial surgeries, which involve cutting of small bones.

(7) Even assuming that any of the irrigation systems incorporated into the various bone saws provide some measure of cooling, thermal burning of both neighboring soft tissues and bone surfaces remains a significant problem. Because the working surface of the blade also moves rapidly, considerable heat is generated along its length, too. The dynamic motion of the surf contacts neighboring soft tissues, potentially burning them. With respect to an osteotomy, as the blade passes through the cross-section of bone, the freshly-cut bone surfaces remain in constant and direct contact with the rapidly vibrating shaft of the blade. As a result, it is not uncommon to burn the bone, produce smoke and, more importantly, kill osteocytes. In fact, simply lengthening an ultrasonic blade to accommodate large cross-sections of bone tissue, for example, increases the surface area through which heat can transfer and, thus, is avoided by manufacturers of these types of blades. While irrigation directed specifically toward the blade's leading edge may provide some measure of cooling at the blade and bone interface, irrigation alone is insufficient in trying to avoid prolonged exposure of bone tissue, for example, to temperatures in excess of 47° C. Therefore, there remains a need for a surgical device that is capable of cutting bones with large cross-sections, such as the femur, while maintaining a working temperature along the entirety of the blade shaft that does not inhibit proper healing of the bone tissue.

(8) In some applications, there is a need to Protecting the viability of the bone can allow for the use of a cementless implant to allow for bone in-growth/osteointegration.

(9) For at least the aforementioned reasons, there is a need for improved surgical devices and techniques.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Having thus described the presently disclosed subject matter in general terms, reference will now be made to the accompanying Drawings, which are not necessarily drawn to scale, and wherein:

(2) FIG. 1 is a top perspective view of a cutting device in accordance with embodiments of the present disclosure;

(3) FIG. 2 is a top perspective view of the blade working body and static components shown in FIG. 1;

(4) FIGS. 3-5 depict top views of the blade working body shown in FIGS. 1 and 2 at different positions of operation for cutting or transforming a material;

(5) FIG. 6 illustrates a side, cross-sectional view of a portion of the working blade body and one static component as shown in FIGS. 1-5; and

(6) FIGS. 7-9 illustrate side views of a blade working body at different positions cutting into a material according to embodiments of the present disclosure.

SUMMARY

(7) The presently disclosed subject matter relates to medical cutting device having a working blade body with static components and related methods of use. According to an aspect, a cutting device includes a working blade body having a top surface and a bottom surface. The working blade body defines a plurality of apertures extending between the top surface and the bottom surface. Further, the cutting device includes a plurality of static components each having a top portion and a bottom portion. Each static component is associated with one of the apertures and has a middle portion that is between the top portion and the bottom portion and positioned within the associated aperture. The top portion and the bottom portion extend past the top surface and the bottom surface, respectively, of the working blade body.

(8) According to another aspect, a method includes providing a cutting device. The cutting device has a working blade body with static components and related methods of use. According to an aspect, a cutting device includes a working blade body having a top surface and a bottom surface. The working blade body defines a plurality of apertures extending between the top surface and the bottom surface. Further, the cutting device includes a plurality of static components each having a top portion and a bottom portion. Each static component is associated with one of the apertures and has a middle portion that is between the top portion and the bottom portion and positioned within the associated aperture. The top portion and the bottom portion extend past the top surface and the bottom surface, respectively, of the working blade body. The method also includes applying a force to the working blade body for cutting a material.

DETAILED DESCRIPTION

(9) The following detailed description is made with reference to the figures. Exemplary embodiments are described to illustrate the disclosure, not to limit its scope, which is defined by the claims. Those of ordinary skill in the art will recognize a number of equivalent variations in the description that follows.

(10) Articles “a” and “an” are used herein to refer to one or to more than one (i.e. at least one) of the grammatical object of the article. By way of example, “an element” means at least one element and can include more than one element.

(11) “About” is used to provide flexibility to a numerical endpoint by providing that a given value may be “slightly above” or “slightly below” the endpoint without affecting the desired result.

(12) The use herein of the terms “including,” “comprising,” or “having,” and variations thereof is meant to encompass the elements listed thereafter and equivalents thereof as well as additional elements. Embodiments recited as “including,” “comprising,” or “having” certain elements are also

contemplated as “consisting essentially of” and “consisting” of those certain elements.

(13) Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein. For example, if a range is stated as between 1%-50%, it is intended that values such as between 2%-40%, 10%-30%, or 1%-3%, etc. are expressly enumerated in this specification. These are only examples of what is specifically intended, and all possible combinations of numerical values between and including the lowest value and the highest value enumerated are to be considered to be expressly stated in this disclosure.

(14) Unless otherwise defined, all technical terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs.

(15) As referred to herein, the term “cutting device” can be any suitable component movable for cutting into or generally transforming a material (e.g., bone). The cutting device can include a blade that operates through large or small (e.g., vibrations) mechanical motion. The motion can be in a specific direction(s). For example, the cutting device can be moved in an oscillating manner, flexing, bending, rotating, torsionally, longitudinally, and the like.

(16) FIG. 1 illustrates a top perspective view of a cutting device **100** in accordance with embodiments of the present disclosure. Referring to FIGS. 1-4, the cutting device **100** includes handle **101** and a housing **102**. Although these components are not shown in FIG. 1, the housing **102** may contain in an interior space therein for components, such as any suitable transducer or motor, to produce a desired mechanical motion with a cutting end, generally designated **106**. It is noted that in this example the device **100** is described as being an oscillating saw blade, but it may alternatively be of any other suitable type (e.g., such as an ultrasonic transducer driving the blade through piezoelectric elements and smaller vibrations). The oscillating motor, which may be suitably powered to produce motion through the working surface of the blade to its blade edge, can be operatively attached to an end of a blade working body **108** that is closest to the housing **102**. Oscillatory motion produced by the transducer/motor can propagate along a main body of the blade working body **108** towards an end of the blade working body **108** that opposes the end of the blade working body **108** that is attached to the oscillatory transducer/motor. It is noted that any other suitable motion may be produced alternative to mechanical oscillations such as those produced by traditional bone saws (e.g., such as those produced by ultrasonic cutting devices that use smaller scale vibrations). A static insert can be stationary or at least substantially stationary with respect to a source of movement since its motion is decoupled from that of the blade working body. The air gap present created by the static insert **114** can reduce transfer of energy from the blade working body **108** and, thus, heat to the surrounding bone. It is noted that the static insert may be made of any suitable insulative material, such as ceramic/polymer/rubber or any other suitable medical grade material, for preventing or minimizing heat transfer to the bone. Air can be present around the static insert and/or blade.

(17) The cutting end **106** can be a blade tip configured to cut, ablate, abrade or otherwise transform, for example, bone or other tissue. The cutting end **106** includes a top surface **110** and an opposing bottom surface (not shown in FIG. 1). The cutting end **106** defines at least one blade edge **112**. In this example, the blade edge **112** has serrations for cutting, ablating, abrading, or otherwise transforming bone or other tissue. In the alternative, the blade edge **112** is a continuous, planar arc, and sharpened along its entirety for cutting, ablating, abrading, or otherwise transforming bone or other tissue.

(18) With continuing reference to FIG. 1, the cutting device **100** includes multiple static components **114** operable to move relative to the motion of the blade working body **108** in accordance with embodiments of the present disclosure. The static components **114** can support load (i.e. to help prevent blade binding), allow for free flow of bone debris, and create an air gap during cutting. The static components **114** can be positioned as shown or otherwise positioned or in

any number along the working surface of the blade to prevent contact with bone or other material being cut or transformed. These components also decouple the motion of the blade working body **108** from the adjacent bone or other material being cut or transformed. The static components **114** provide sufficient circumferential clearance that they capture all blade excursion/motion produced by the blade working body **108**. Specifically, the clearance around the static components **114** are designed to be larger than the desired excursion so as to ensure they can remain static during the cutting process relative to the dynamic motion of the blade working body **108**.

(19) FIG. 2 illustrates a top perspective view of the blade working body **108** and static components **114** shown in FIG. 1. Referring to FIG. 2, as shown an end of the blade working body **108** that opposes the blade edge **112** includes a clip portion **200** for attachment to another component of the cutting device **100**. The clip portion **200** defines a rounded feature **202** that can fit to and pivot about a vertical member (not shown) for rotational movement about axis, indicated by a broken line **204**.

(20) FIGS. 3-5 illustrate tops views of the blade working body **108** shown in FIGS. 1 and 2 at different positions of operation for cutting or transforming a material, such as bone. Referring to FIGS. 3-5 it can be recognized that the blade working body **108** is at different positions with respect to static components **114**. The blade edge **112** can be move back-and-forth generally in the directions indicated by double arrow **300**. This back-and-forth motion occurs when the blade working body **108** pivot about axis **204**. FIG. 3 depicts the blade working body **108** in a “neutral” position or approximately midway between an extent of movement to the left and to the right. FIG. 4 depicts the blade working body **108** at a position farthest to the right. FIG. 5 depicts the blade working body **108** at a position farthest to the left.

(21) FIG. 6 illustrates a side, cross-sectional view of a portion of the working blade body **108** and one static component **114** as shown in FIGS. 1-5. The static component **114** comprises a flexible perimeter joint **600** and a load-sharing member **602**. The flexible perimeter joint **600** encircles and is fitted to the load-sharing member **602**. The flexible perimeter joint **600** is fitted into an aperture **604** formed within the working blade body **108** such that the joint **600** and the load-sharing member **602** are planar or substantially planar with respect to the plane of the working blade body **108**. Particularly, the joint **600** is fitted within the aperture **604** such that the aperture functions as a socket to hold the static component **114**. The static component **114** is thereby loosely held by the aperture **604**. As a result of this configuration, the flexible nature of the joint **600** mechanically separates the load-sharing member **602** from the surrounding blade body **108**.

(22) It is noted that the load-sharing member **602** has a height profile greater than the thickness of the blade body **108**, such that the load-sharing member **602** extends perpendicularly some measure from both the top surface **110** and a bottom surface **606** of the blade working body **108**. Although, it is noted that the components may have any other suitable height with respect to each other. In an example, a top end and a bottom end of the load-sharing member **602** are convex or curved in shape. The load-sharing member **602** and the flexible perimeter joint **600** can be one functional unit that move together and are not directly attached to the blade working body **108**. Rather, their motion is constrained by the bounds of the countersunk aperture **604** in which they reside. Edges **608** of the aperture **604** are further countersunk in the surrounding blade body **108** such that the edge of the flexible perimeter joint **600** is the same height or subflush to the surface of the surrounding blade body **108**. This allows the material being cut to more easily ride up on the static component. Specifically, as the blade working body **108** moves within the cutting plane the adjacent bone rides up on the static component **114**. This can create an airgap to prevent direct conduction of heat to adjacent bone and allows for bone debris to flow away from the cutting site. It is believed that freely moving bone particulate matter can alleviate a significant amount of frictional forces that would otherwise be generated between the bone surfaces and the blade body **108**. Airgaps are present circumferentially all around the flexible perimeter joint as well. Finally, this mechanism of the bone riding up on the static component **114** effectively supports loading on

the top and bottom of the blade working body, which allows it to continue operation without frictional sliding interactions and prevents it from binding. It should be noted that fitting the flexible perimeter joint **600** to the load-sharing member **602** and fitting the flexible perimeter joint **600** within the aperture **604** can be accomplished using any variety of press-fit, slip-fit, snap-fit, adhesive, any combination thereof, or other suitable means. The flexible perimeter joint **600** can be made of a material having a low thermal conductivity including, but not limited to, rubber, silicone, or the like. The load-sharing member **602** can be made of a high strength medical grade material like stainless steel, cobalt chrome, and the like.

(23) FIGS. **7-9** illustrate side views of a blade working body **108** at different positions cutting into a material **700** (e.g. bone) according to embodiments of the present disclosure. Referring to FIG. **7**, the blade working body **108** is at an initial position for cutting into the material **700**. At this position, the blade edge **112** has cut into the material to a distance such that the most distal static casing **114** has not reached the material **700**.

(24) Now turning to FIG. **8**, the blade edge **112** has cut farther into the material **700** such that a portion **800** of the static casing **114** is within a gap **802** cut into the material **700**. At the position shown in FIG. **8**, the static casing **114** is carrying load from contact with the material **700** for alleviating strain on the blade working body **108**. FIG. **9** shows the blade edge **112** having farther cut into the material **700** such that a large portion **900** of the static casing **114** is within the gap **802**. In this position, a greater portion of the static casing **114** is carrying the load of the material **700**.

(25) It is noted that embodiments of the present disclosure are described as producing or having oscillatory saw blade movement or any other suitable source for motion. It is noted that in the alternative the movement may be any suitable type of movement produced by any suitable source (e.g., such as an ultrasonic transducer driving the blade through piezoelectric elements and smaller vibrations)). Further, cutting may be applied to any suitable material or technical field. Suitable mechanical sources could include anything from piezoceramics, electro-mechanical motors, user generated hand motion, etc. However, its important to note that all types of mechanisms can produce equivalent types of movements. These could include, but are not limited to, axial motion, bending motion, torsional motion, flexural motion, etc. It is also feasible that the source of mechanical motion can combine all of these modes of motion to create more complex movements. Regardless of the motion and/or the manner in which it is produced, there would be a resultant motion at the end of the functional device/blade edge. This motion would, under the claims of this patent, be captured within the bounds of the static casing which function to share load, decouple motion, and prevent heat transfer to the functional working surfaces. Examples include oscillating/sagittal/reciprocating medical bone cutting saws, medical rotary drills, medical rotary burs, construction hammer drills, construction rotary hammer, wood cutting axes, construction oscillating multi-tools, oscillating medical cast saws, cutting saws, etc. The principles of the claims presented in this patent could be applied to all of these devices with equivalently realized benefits.

(26) While the embodiments have been described in connection with the various embodiments of the various figures, it is to be understood that other similar embodiments may be used, or modifications and additions may be made to the described embodiment for performing the same function without deviating therefrom. Therefore, the disclosed embodiments should not be limited to any single embodiment, but rather should be construed in breadth and scope in accordance with the appended claims.

Claims

1. A cutting device comprising: a working blade body having a top surface and a bottom surface, wherein the working blade body defines a plurality of apertures extending between the top surface and the bottom surface, wherein the working blade body defines a plurality of countersunk edge pairs that each substantially surround a corresponding one of the apertures at the top surface and

the bottom surface, wherein the working blade body is substantially within a plane; and a plurality of static components each having a top portion and a bottom portion, wherein each static component is associated with one of the apertures and has a middle portion that is between the top portion and the bottom portion and positioned within the associated aperture, and wherein the top portion and the bottom portion of each static component are moveable within the countersunk edge pairs; wherein each static component comprises a joint and load-sharing member, wherein the joint attaches the load-sharing member to the working blade body, and wherein each load-sharing member is defined to fit to a respective aperture and countersunk edge pairs with spacings such that a respective static component is moveable within the aperture and along the plane and moveable in a substantially less amount in directions outside of the plane for substantially maintaining movement of the static component with the plane of the working blade body.

2. The cutting device of claim 1, wherein the working blade body includes a blade edge positioned at a distal end.
3. The cutting device of claim 2, wherein the working blade body includes a proximal end, wherein the plurality of apertures and the associated static components are spaced apart between the proximal and distal ends of the working blade body.
4. The cutting device of claim 3, wherein the plurality of apertures and the associated static components are in substantial alignment.
5. The cutting device of claim 1, wherein each joint encircles its associated load-sharing member.
6. The cutting device of claim 1, wherein each joint is made of a rigid material.
7. The cutting device of claim 1, the top surface and the bottom surface are separated by a distance, and wherein a height of each static component is greater than the distance separating the top surface and the bottom surface.
8. The cutting device of claim 1, wherein the top portion and the bottom portion are each curved in shape.
9. The cutting device of claim 1, wherein each static component is substantially disk-like in shape.
10. The cutting device of claim 1, wherein each joint is substantially disk-like in shape.
11. The cutting device of claim 10, wherein each joint defines an aperture therein, and wherein the associated load-sharing member fits inside the aperture of the joint.
12. The cutting device of claim 1, wherein the working blade body is operatively attached to a source of movement for moving the working blade body.
13. A method comprising: providing a cutting device comprising: a working blade body having a top surface and a bottom surface, wherein the working blade body defines a plurality of apertures extending between the top surface and the bottom surface, wherein the working blade body defines a plurality of countersunk edge pairs that each substantially surround a corresponding one of the apertures at the top surface and the bottom surface, wherein the working blade body is substantially within a plane; and a plurality of static components each having a top portion and a bottom portion, wherein each static component is associated with one of the apertures and has a middle portion that is between the top portion and the bottom portion and positioned within the associated aperture, and wherein the top portion and the bottom portion of each static component are moveable within the countersunk edge pairs; wherein each static component comprises a joint and load-sharing member, wherein the joint attaches the load-sharing member to the working blade body, and wherein each load-sharing member is defined to fit to a respective aperture and countersunk edge pairs with spacings such that a respective static component is moveable within the aperture and along the plane and moveable in a substantially less amount in directions outside of the plane for substantially maintaining movement of the static component with the plane of the working blade body, and applying a force to the working blade body for cutting a material.
14. The method of claim 13, wherein the working blade body includes a blade edge positioned at a distal end.
15. The method of claim 14, wherein the working blade body includes a proximal end, wherein the

plurality of apertures and the associated static components are spaced apart between the proximal and distal ends of the working blade body.
