

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404724
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Johnson; Benjamin et al.

Ladder stabilizer attachment device

Abstract

A ladder stabilizer attachment device secures a ladder stabilizer to a ladder. The device includes a sleeve including an outer wall. The outer wall has an outer face, an inner face, an upper end, and a lower end. The lower end is open. A slot extends into the inner face from the lower end to receive a top end of a ladder side rail and an uppermost rung of the ladder into the slot. A top edge of the slot defines a stop whereby the stop rests upon the uppermost rung of the ladder. A coupler is mounted to the sleeve. The coupler releasably engages the uppermost rung of the ladder.

Inventors: Johnson; Benjamin (Salem, SD), Johnson; Chad (Salem, SD), Slunecka; Les (Sioux Falls, SD)

Applicant: Bighorn Products, LLC (Salem, SD)

Family ID: 86898394

Appl. No.: 17/565105

Filed: December 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230203889 A1	Jun. 29, 2023

Publication Classification

Int. Cl.: E06C7/00 (20060101); E06C7/48 (20060101); E06C7/06 (20060101)

U.S. Cl.:

CPC E06C7/488 (20130101); E06C7/486 (20130101); E06C7/06 (20130101)

Field of Classification Search

CPC: E06C (7/488); E06C (7/486); E06C (7/06); E06C (7/188); E06C (7/48); E06C (7/182)

USPC: 182/21; 182/106; 182/107; 182/122

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2140828	12/1937	Carle	248/214	E06C 1/36
4311209	12/1981	Primerano	N/A	N/A
5012895	12/1990	Santos	N/A	N/A
7322442	12/2007	Clark	182/106	E06C 7/182
9593531	12/2016	Ballard	N/A	N/A
11913283	12/2023	MacKarvich	N/A	E06C 7/48
2008/0190692	12/2007	Feik	182/107	E06C 7/182
2011/0011676	12/2010	DeLair	N/A	N/A
2016/0215563	12/2015	Ellis	N/A	E06C 1/04
2020/0224495	12/2019	Johnson	N/A	E06C 7/486
2020/0248507	12/2019	Moss	N/A	E06C 7/182
2024/0183221	12/2023	Miner	N/A	E06C 1/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10110511	12/2009	CN	N/A
201934004	12/2010	CN	N/A
1077191131	12/2016	CN	N/A
2459118	12/2008	GB	N/A
2008285967	12/2007	JP	N/A
WO-2017031523	12/2016	WO	N/A

Primary Examiner: Wilkens; Janet M

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

(3) Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

(4) Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR

(5) Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(6) The disclosure relates to ladder stabilizing device and more particularly pertains to a new ladder stabilizing device for securing a ladder stabilizer to a ladder.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(7) The prior art relates to ladder stabilizing devices. Known prior art attaches to rungs or rails but provide for attachment in a manner which would benefit from improved stabilization and inhibition of movement during use.

BRIEF SUMMARY OF THE INVENTION

(8) An embodiment of the disclosure meets the needs presented above by generally comprising a sleeve including an outer wall. The outer wall has an outer face, an inner face, an upper end, and a lower end. The lower end is open. A slot extends into the inner face from the lower end to receive a top end of a ladder side rail and an uppermost rung of the ladder into the slot. A top edge of the slot defines a stop whereby the stop rests upon the uppermost rung of the ladder. A coupler is mounted to the sleeve. The coupler releasably engages the uppermost rung of the ladder.

(9) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(10) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

(1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

(2) FIG. 1 is a top front side perspective view of a pair of ladder stabilizer attachment devices according to an embodiment of the disclosure.

(3) FIG. 2 is an exploded top front side perspective view of an embodiment of the disclosure.

(4) FIG. 3 is a partial cut-away side view of an embodiment of the disclosure attached to a ladder.

(5) FIG. 4 is a cross-sectional view of an embodiment of the disclosure taken along line 4-4 of FIG. 3.

(6) FIG. 5 is a top front side perspective view of an embodiment of the disclosure.

(7) FIG. 6 is a side view of an embodiment of the disclosure in use.

DETAILED DESCRIPTION OF THE INVENTION

(8) With reference now to the drawings, and in particular to FIGS. 1 through 6 thereof, a new ladder stabilizing device embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral 10 will be described.

(9) As best illustrated in FIGS. 1 through 6, the ladder stabilizer attachment device 10 generally comprises a sleeve 12 including an outer wall 14. The outer wall 14 has an outer face 16, an inner face 18, an upper end 20, and a lower end 22. The lower end 22 is open. The outer wall 14 of the sleeve 12 has opposed side faces 24 extending between the inner face 18 and the outer face 16 and between the upper end 20 and the lower end 22. A slot 26 extends into the inner face 18 from the lower end 22 such that the sleeve 12 is shaped to receive a top end 28 of a ladder side rail 30 and an uppermost rung 32 of a ladder 34 into the slot 26. A top edge 36 of the slot 26 defines a stop 38 whereby the stop 38 is positioned to rest upon the uppermost rung 32 of the ladder 34 when the

ladder **34** is fully inserted into the lower end **22** of the sleeve **12**.

(10) A coupler **40** is mounted to the sleeve **12**. The coupler **40** is configured to releasably engage the uppermost rung **32** of the ladder **34** preventing the sleeve **12** from detaching from the ladder **34**. The coupler **40** is pivotally mounted on the inner face **18** of the sleeve **12**. The coupler **40** comprises a shaft **42** having an attached end **44** rotatably coupled to the sleeve **12** and a distal end **46** relative to the attached end **44**. A projection **48** extends from the shaft **42** adjacent to the distal end **46** to define a hook **50** configured for extending under the uppermost rung **32** of the ladder **34**. The projection **48** has ends **52** coupled to the shaft **42** to define an opening **54** in the coupler **40** adjacent to the distal end **46** of the shaft **42**. The projection **48** comprises a bearing surface **56** extending away from the distal end **46** of the shaft **42** and towards the attached end **44** of the shaft **42**. Thus, the bearing surface **56** is angled relative to the shaft **42** such that the coupler **40** is configured to pivot as the bearing surface **56** abuts the uppermost rung **32** of the ladder **34** as the sleeve **12** is positioned onto the ladder **34**. An upper surface **58** of the projection **48** is concave to facilitate extension under the uppermost rung **32** of the ladder **34**. The concavity of the upper surface **58** also inhibits pivoting of the coupler **40** out of engagement with the uppermost rung **32**. A biasing member **60** is coupled to the sleeve **12** and engages the coupler **40** wherein the biasing member **60** is configured to urge the coupler **40** into engagement with the uppermost rung **32** of the ladder **34**.

(11) A first aperture **62** extends through a first one **24A** of the opposed side faces **24**. The first aperture **62** is threaded. A first locking member **64** is insertable through the first aperture **62** wherein the first locking member **64** is configured to engage the ladder side rail **30** to inhibit movement of the ladder side rail **30** relative to the sleeve **12**. The first locking member **64** is threaded complementary to the first aperture **62**. Similarly, a second aperture **66** extends through the first one **24A** of the opposed side faces **24**. The second aperture **66** is spaced from the first aperture **62**. The second aperture **66** is threaded. A second locking member **68** is insertable through the second aperture **66** wherein the second locking member **68** is configured to engage the ladder side rail **30** to inhibit movement of the ladder side rail **30** relative to the sleeve **12**. The second locking member **68** is threaded complementary to the second aperture **66**. The second locking member **68**. Each of the first locking member **64** and the second locking member **68** has a respective head **70** exposed outside of the sleeve **12**.

(12) Each of a plurality of guards **72** is coupled to the first one **24A** of the opposed side faces **24**. Each guard **72** is positioned proximate to an associated one of the first locking member **64** and the second locking member **68** such that each guard **72** is configured to inhibit unintentional contact with the head **70** of the associated one of the first locking member **64** and the second locking member **68**. A distance each guard **72** extends from the first one **24A** of the opposed side faces **24** is greater than a distance of the head **70** of the associated one of the first locking member **64** and the second locking member **68** when the associated one of the first locking member **64** and the second locking member **68** is inserted into a respective one of the first aperture **62** and the second aperture **66**. Each guard comprises a pair of angle members **74**. The angle members **74** are spaced on the first one **24A** of the opposed side faces **24** and positioned on opposite sides of a respective one of the first aperture **62** and the second aperture **66**.

(13) A stabilizer mount **76** is attached to the sleeve **12**. The stabilizer mount **76** extends outwardly from the outer face **16** of the outer wall **14** of the sleeve **12**. The stabilizer mount **76** comprises a tube **78** having a bottom end **80** coupled to the sleeve **12**. The tube **78** has a bend **82** such that an upper section **84** of the tube **78** extends spaced and parallel to the sleeve **12**. A brace **86** is coupled to and extends between the outer surface **16** of the outer wall **14** of the sleeve **12** and the upper section **84** of the tube **78**. A stabilizer **88** is couplable to the stabilizer mount **76** such that the stabilizer **88** is positionable on a roof **90** to stabilize the ladder **34**. The stabilizer **88** extends upwardly and forwardly of the sleeve **12**. The stabilizer **88** comprises an arm **92** attachable to the stabilizer mount **76** to extend forward and upwardly from the stabilizer mount **76**. The arm **92** has a

distal end **94** with respect to the stabilizer mount **76**. A leg **96** is attached to the arm **92** extending forward and downwardly from the distal end **94**. The leg **96** has a free end **98**. A foot **100** is pivotally attached to the free end **98** for abutting the roof **90**. A catch **102** is coupled to the stabilizer mount **76** and is configured to engage a gutter **104** positioned on the roof **90**. The catch **102** includes a loop **106** extending around the tube **78** with an L-shaped extension **108** from the loop **106** such that the extension **108** can extend over and into the gutter **104**.

(14) In use, the sleeve **12** is placed onto the ladder **34** and the coupler **40** is positioned to secure the sleeve **12** on the ladder **34**. To further stabilize the sleeve and prevent movement of the ladder side rail **30** within the sleeve **12**, the first locking member **64** is tightened. Where present, the second locking member **68** is also tightened to further stabilize the ladder side rail **30** within the sleeve **12**. The stabilizer **88** is attached to the stabilizer mount **76** and can be adjusted to fit the specific roof **90**. A second sleeve **12** is placed onto a second ladder side rail such that a pair of the described devices **10** are used together to safely attach two stabilizers **88** to the ladder **34**.

(15) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(16) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A ladder stabilizer attachment device configured to releasably engage a ladder and be abutted against a roof, the device comprising: a sleeve including an outer wall, the outer wall having an outer face, an inner face, an upper end, and a lower end, the lower end being open; a slot extending into the inner face from the lower end wherein the sleeve is configured to receive a top end of a ladder side rail and an uppermost rung of the ladder into the slot, a top edge of the slot defining a stop whereby the stop is configured to rest upon the uppermost rung of the ladder; and a coupler being mounted to the sleeve, the coupler being configured to releasably engage the uppermost rung of the ladder, the coupler being pivotally mounted on the inner face of the sleeve, wherein the coupler comprises a shaft having an attached end rotatably coupled to the sleeve and a distal end relative to the attached end; and a projection extending from the shaft adjacent to the distal end to define a hook configured for extending under the uppermost rung of the ladder, the projection having ends coupled to the shaft to define an opening in the coupler adjacent to the distal end of the shaft.

2. The ladder stabilization attachment device of claim 1, further comprising the projection comprising a bearing surface extending away from the distal end of the shaft and towards the attached end of the shaft wherein the bearing surface is angled relative to the shaft such that the coupler is configured to pivot as the bearing surface abuts the uppermost rung of the ladder as the sleeve is positioned onto the ladder.

3. The ladder stabilization attachment device of claim 1, further comprising an upper surface of the

projection being concave.

4. The ladder stabilization attachment device of claim 1, further comprising a biasing member coupled to the sleeve and engaging the coupler wherein the biasing member is configured to urge the coupler into engagement with the uppermost rung of the ladder.

5. The ladder stabilization attachment device of claim 1, further comprising: the outer wall of the sleeve having opposed side faces extending between the inner face and the outer face and between the upper end and the lower end; an aperture extending through a first one of the opposed side faces; and a locking member insertable through the aperture wherein the locking member is configured to engage the ladder side rail to inhibit movement of the ladder side rail relative to the sleeve.

6. The ladder stabilization attachment device of claim 5, further comprising: the aperture being threaded; and the locking member being threaded complementary to the aperture.

7. The ladder stabilization attachment device of claim 6, further comprising: the locking member having a head exposed outside of the sleeve; and a guard coupled to the first one of the opposed side faces, the guard being positioned proximate to the locking member such that the guard is configured to inhibit unintentional contact with the head of the locking member.

8. The ladder stabilization attachment device of claim 5, further comprising: the aperture being a first aperture extending through the first one of the opposed side faces; the locking member being a first locking member insertable through the first aperture; a second aperture extending through the first one of the opposed side faces, the second aperture being spaced from the first aperture; and a second locking member being insertable through the second aperture wherein the second locking member is configured to engage the ladder side rail to inhibit movement of the ladder side rail relative to the sleeve.

9. The ladder stabilization attachment device of claim 1, further comprising a stabilizer mount being attached to the sleeve.

10. The ladder stabilization attachment device of claim 9, further comprising the stabilizer mount extending outwardly from the outer face of the outer wall of the sleeve.

11. The ladder stabilization attachment device of claim 9, further comprising a stabilizer coupled to the stabilizer mount wherein the stabilizer is positionable on a roof to stabilize the ladder, the stabilizer extending upwardly and forwardly of the sleeve.

12. The ladder stabilization attachment device of claim 11, wherein the stabilizer comprises: an arm being attached to the stabilizer mount and extending forward and upwardly from the stabilizer mount, the arm having a distal end with respect to the stabilizer mount; and a leg being attached to the arm and extending forward and downwardly from the distal end, the leg having a free end.

13. The ladder stabilization attachment device of claim 9, further comprising a catch coupled to the stabilizer mount and being configured to engage a gutter positioned on the roof.

14. The ladder stabilization attachment device of claim 1, further comprising: the outer wall of the sleeve having opposed side faces extending between the inner face and the outer face and between the upper end and the lower end; the projection comprising a bearing surface extending away from the distal end of the shaft and towards the attached end of the shaft wherein the bearing surface is angled relative to the shaft such that the coupler is configured to pivot as the bearing surface abuts the uppermost rung of the ladder as the sleeve is positioned onto the ladder, an upper surface of the projection being concave; a biasing member coupled to the sleeve and engaging the coupler wherein the biasing member is configured to urge the coupler into engagement with the uppermost rung of the ladder; a first aperture extending through the first one of the opposed side faces, the first aperture being threaded; a first locking member insertable through the first aperture wherein the locking member is configured to engage the ladder side rail to inhibit movement of the ladder side rail relative to the sleeve, the first locking member being threaded complementary to the first aperture; a second aperture extending through the first one of the opposed side faces, the second aperture being spaced from the first aperture, the second aperture being threaded; a second locking

member being insertable through the second aperture wherein the second locking member is configured to engage the ladder side rail to inhibit movement of the ladder side rail relative to the sleeve, the second locking member being threaded complementary to the second aperture, the second locking member having a head exposed outside the sleeve; wherein each of the first locking member and the second locking member has a respective head exposed outside of the sleeve; a plurality of guards, each guard being coupled to the first one of the opposed side faces, each guard being positioned proximate to an associated one of the first locking member and the second locking member such that each guard is configured to inhibit unintentional contact with the head of the associated one of the first locking member and the second locking member, a distance each guard extends from the first one of the opposed side faces being greater than a distance of the head of the associated one of the first locking member and the second locking member when the associated one of the first locking member and the second locking member is inserted into a respective one of the first aperture and the second aperture, wherein each guard comprises a pair of angle members, the angle members being spaced on the first one of the opposed side faces and positioned on opposite sides of a respective one of the first aperture and the second aperture; a stabilizer mount being attached to the sleeve, the stabilizer mount extending outwardly from the outer face of the outer wall of the sleeve, wherein the stabilizer mount comprises a tube having a bottom end coupled to the sleeve, the tube having a bend such that an upper section of the tube extends spaced and parallel to the sleeve, and a brace coupled to and extending between the outer surface of the outer wall of the sleeve and the upper section of the tube; a stabilizer coupled to the stabilizer mount wherein the stabilizer is positionable on a roof to stabilize the ladder, the stabilizer extending upwardly and forwardly of the sleeve, wherein the stabilizer comprises an arm being attached to the stabilizer mount and extending forward and upwardly from the stabilizer mount, the arm having a distal end with respect to the stabilizer mount, and a leg being attached to the arm and extending forward and downwardly from the distal end, the leg having a free end; and a catch coupled to the stabilizer mount and being configured to engage a gutter positioned on the roof.

15. A ladder stabilizer attachment device configured to releasably engage a ladder and be abutted against a roof, the device comprising: a sleeve including an outer wall, the outer wall having an outer face, an inner face, an upper end, and a lower end, the lower end being open; a slot extending into the inner face from the lower end wherein the sleeve is configured to receive a top end of a ladder side rail and an uppermost rung of the ladder into the slot, a top edge of the slot defining a stop whereby the stop is configured to rest upon the uppermost rung of the ladder; a coupler being mounted to the sleeve, the coupler being configured to releasably engage the uppermost rung of the ladder; the outer wall of the sleeve having opposed side faces extending between the inner face and the outer face and between the upper end and the lower end; an aperture extending through a first one of the opposed side faces, the aperture being threaded; a locking member insertable through the aperture wherein the locking member is configured to engage the ladder side rail to inhibit movement of the ladder side rail relative to the sleeve, the locking member being threaded complementary to the aperture, the locking member having a head exposed outside of the sleeve; a guard coupled to the first one of the opposed side faces, the guard being positioned proximate to the locking member such that the guard is configured to inhibit unintentional contact with the head of the locking member; and wherein the guard comprises a pair of angle members, the angle members being spaced on the first one of the opposed side faces and positioned on opposite sides of the aperture.

16. The ladder stabilization attachment device of claim 15, further comprising a distance each guard extends from the first one of the opposed side faces being greater than a distance of the head of the locking member when the locking member is inserted into the aperture.

17. A ladder stabilizer attachment device configured to releasably engage a ladder and be abutted against a roof the device comprising: a sleeve including an outer wall, the outer wall having an outer face, an inner face, an upper end, and a lower end, the lower end being open; a slot extending

into the inner face from the lower end wherein the sleeve is configured to receive a top end of a ladder side rail and an uppermost rung of the ladder into the slot, a top edge of the slot defining a stop whereby the stop is configured to rest upon the uppermost rung of the ladder; a coupler being mounted to the sleeve, the coupler being configured to releasably engage the uppermost rung of the ladder; a stabilizer mount being attached to the sleeve, the stabilizer mount extending outwardly from the outer face of the outer wall of the sleeve; and wherein the stabilizer mount comprises a tube having a bottom end coupled to the sleeve, the tube having a bend such that an upper section of the tube extends spaced and parallel to the sleeve; and a brace coupled to and extending between the outer surface of the outer wall of the sleeve and the upper section of the tube.
