

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404886
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tseng; Ying-Chih et al.

Fixing device

Abstract

A fixing device includes a docking element having a through hole on the base thereof and two fixing portions at two sides of the base for fixing to a preset first panel, a positioning mechanism, and a rotating mechanism. Turning the rotating element generates linkage between the rotating sleeve and positioning element, and forms a rotating and lifting displacement for the positioning sleeve set inside the rotating sleeve to generate a clamp and cause the positioning element to generate a rotating and lifting displacement. Through the positioning portion of the positioning element, it passes through the through hole of the docking element and is held against the base of the docking element to achieve a solid combination of the preset first panel and the preset second panel. It has the purpose of being stable and not easy to loosen and break away, and has the effect of easy operation.

Inventors: Tseng; Ying-Chih (New Taipei, TW), Wu; Ming-De (New Taipei, TW), Chang; Ching-Kai (New Taipei, TW)

Applicant: HANWIT PRECISION INDUSTRIES LTD. (New Taipei, TW)

Family ID: 86691787

Assignee: HANWIT PRECISION INDUSTRIES LTD. (New Taipei, TW)

Appl. No.: 18/358146

Filed: July 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240209879 A1	Jun. 27, 2024

Foreign Application Priority Data

TW	111214305	Dec. 23, 2022
----	-----------	---------------

Publication Classification

Int. Cl.: F16B2/18 (20060101); F16B5/06 (20060101)

U.S. Cl.:

CPC F16B2/185 (20130101); F16B5/0607 (20130101)

Field of Classification Search

CPC: F16B (2/00); F16B (2/185); F16B (21/00); F16B (21/02); F16B (21/04); F16B (5/00); F16B (5/0607)

USPC: 292/257; 411/552; 403/4; 403/13; 403/43; 403/44; 403/45; 403/46; 403/52; 403/204; 403/205; 403/220

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6619875	12/2002	Chiang	403/374.1	F16B 21/165
2012/0195711	12/2011	Chiu	411/103	F16B 5/0208
2018/0058487	12/2017	Wu	N/A	F16B 5/0657
2018/0065746	12/2017	Jones	N/A	B64D 1/12
2019/0366940	12/2018	Peters	N/A	B62J 50/225

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102018009976	12/2019	DE	N/A
2629913	12/2023	GB	N/A
202126916	12/2020	TW	N/A

Primary Examiner: Cumar; Nathan

Attorney, Agent or Firm: MUNCY, GEISSLER, OLDS & LOWE, P.C.

Background/Summary

(1) This application claims the priority benefit of Taiwan patent application number 111214305, filed on Dec. 23, 2022.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present invention relates to a fixing device, especially referring to turning the rotating element to generate linkage between the rotating sleeve and positioning element, and to form a rotating and lifting displacement for the positioning sleeve set inside the rotating sleeve to generate a clamp and cause the positioning element to generate a rotating and lifting displacement. Through the positioning portion of the positioning element, it passes through the through hole of the docking element and is held against the base of the docking element to achieve a solid combination of the

preset first panel and the preset second panel. It has the purpose of being stable and not easy to loosen and break away, and has the effect of easy operation.

2. Description of the Related Art

(3) General panels (board-to-board) are assembled and joined by using positioning screws with knobs, collars and screws to lock, and the screws and collars can be fixed on the panels. First turn the knob to allow the screw to be locked into the inner panel to form a preset position, and then use a hand tool to lock the screw, so that the outer panel and the inner panel are locked into one. This kind of locking method of multi-layer boards is used for boards that can be used in machine tools or other board-to-board connections. However, there are the following deficiencies that need to be improved urgently during the operation process through the locking method described above: 1. These machine tools need to use panels to lock joints, most of which are power devices or speed adjustment devices, and various power devices and speed adjustment devices are located inside the space formed by the tool shell, which can be assembled, locked, disassembled. When the power device breaks down, crashes or is damaged, or the speed adjustment device changes or adjusts the speed, remove the panels for related maintenance and adjustment operations. The panels are locked with a plurality of positioning screws. Therefore, it is easy to cause the positioning screws to fall off or be lost during the disassembly process, and the panels cannot be re-locked back to their original position, which will affect the inconvenience and trouble of assembly and disassembly operations, and then affect the stability and quality of the assembly process. 2. Under the requirement of modularized mass production and processing efficiency nowadays, the cumbersome manual assembly process using screws will seriously affect the progress of the manufacturer's shipment. Moreover, due to the small size of the screws, the screws are easy to lose during the process of locking the two panels, and due to the difference in the size of the screw holes at the position where the screws are locked or the number of teeth and the pitch of the screw holes do not match, it is easy to cause difficulties in assembly, alignment or locking. Moreover, the space available for operating screws between the two opposite panels is quite narrow, and the assembly and disassembly of the screws are easily hindered by surrounding objects. Not only is it time-consuming and inconvenient, but it will also lead to an increase in the overall production cost, which in turn will increase the burden on the industry.

(4) It can be seen from the above that the above-mentioned fixing devices still have poor assembly efficiency, are prone to loss, etc., and there is room for improvement, which is the key point to be studied and improved by those who are engaged in this industry.

SUMMARY OF THE INVENTION

(5) Therefore, in view of the above-mentioned problems and deficiencies, the inventor has collected relevant information, evaluated and considered in many ways, and based on years of experience accumulated in this industry, through continuous trial and modification, he designed this new patent with a fixing device. born.

(6) It is therefore a main object of the present invention to provide a fixing device, where the rotating sleeve is set on the positioning sleeve, and there are convex portions and stoppers in the accommodating space of the rotating sleeve, and a channel is formed between each convex portion and each stopper. As a result, the locking portions of the positioning sleeve are moved up and down from each notch along the edge of each convex portion to each channel by using the rotating sleeve, and the locking portions touch the stoppers to form a rotation stop, so that the rotating sleeve is linked with the positioning portion of the positioning element to produce a rotating lift to pass through the through hole of the docking element into the positioning space and form a support against the base of the docking element. In this way, the preset first panel and the preset second panel can be firmly integrated into one body. It has the purpose of being stable and not easy to loosen and disengage, and it does not need to use any hand tools. It only needs to achieve time-saving and labor-saving effects through simple and easy operation.

(7) Another object of the present invention is that the rotating element of the rotating mechanism is

assembled on the pivot joint of the rotating sleeve, and comprises a wrenching portion, two opposing extension arms extending from one side of the wrenching portion in the same direction, a wrenching space formed between the two opposing extension arms, and two through-shaped pivot holes respectively formed on the extension arms in communication with the wrenching space. Then, use the pivoting element of the rotating mechanism to penetrate each through-shaped pivot hole, each pivot joint groove and perforation respectively, so that the rotating element forms an active pivot state. This provides users with simple and fast labor-saving effect on operation intuition, and can also produce pivotal bending to save space.

(8) Still another object of the present invention is that the rotating element can only be rotated back and forth in one direction in the direction of turning in, so that the user has an obvious difference in the operating feel, and the user can easily identify and judge whether the positioning mechanism is in a combined state or a disengaged state by whether it can be rotated clockwise or counterclockwise. In this way, it further has a good anti-fooling effect, so as to achieve the effect of improving the convenience and fluency of installation or disassembly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an oblique top elevational view of the present invention.
- (2) FIG. 2 is an exploded view of the present invention.
- (3) FIG. 3 is another exploded view of the present invention.
- (4) FIG. 4 is a sectional elevation view of the rotating sleeve of the present invention.
- (5) FIG. 5 is the side view (I) of the action of the present invention.
- (6) FIG. 6 is the side view (II) of the action of the present invention.
- (7) FIG. 7 is the side view (III) of the action of the present invention.
- (8) FIG. 8 is the side view (IV) of the action of the present invention.
- (9) FIG. 9 is a sectional side view of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

(10) In order to achieve the above objects and effect, the technical means used in the present invention and its structure, implementation method, etc., the preferred embodiment of the present invention is hereby described in detail and its features and functions are as follows, so as to be fully understood.

(11) Please refer to FIGS. 1, 2, 3, and 4, which are an oblique top elevational view of the present invention, an exploded view of the present invention, another exploded view of the present invention, and a sectional elevation view of the rotating sleeve of the present invention. It can be clearly seen from the drawings that the fixing device of the present invention comprises a docking element 1, a positioning mechanism 2 and a rotating mechanism 3.

(12) The docking element 1 comprises a base 11, a long rectangular through hole 111 provided on the surface of the base 11, two fixing portions 12 respectively and obliquely extending from two opposite sides of the base 11, a fixing hole 121 respectively provided on the surface of each of the two fixing portions 12 for fixing on a preset first panel 4, and a positioning space 13 formed between the two fixing portions 12 and between one side of the through hole 111 the preset first panel 4.

(13) The positioning mechanism 2 is assembled on the base 11 of the docking element 1, and comprises a positioning element 21, a positioning sleeve 22 and an elastic element 23. The positioning element 21 has a shank 211, a positioning portion 212 located on one end of the shank 211 and movably worn on the through hole 111 of the docking element 1 to be located in the positioning space 13 for rotational alignment and lifting displacement, a long rectangular stop block 2121 provided with the positioning portion 212 corresponding to the through hole 111, and a

perforation **213** provided in a transverse direction on the other end of the shank **211** opposite to the positioning portion **212**.

(14) Based on the above, the positioning sleeve **22** is movably sleeved onto the positioning element **21**. The positioning sleeve **22** comprises a sliding space **220** therein for the positioning element **21** to move and wear, a tube-shaped fitting portion **221** with an enlarged outer diameter externally protruded from one end of the sliding space **220** to be fixed in a preset fitting hole **50** of a preset second panel **5**, a tube-shaped sleeve portion **222** externally protruded from an opposite end of the sliding space **220** to be sleeved with the elastic element **23**, a storage groove **2211** with an enlarged aperture recessed on the surface of the tube-shaped fitting portion **221** in communication with the sliding space **220** for receiving the positioning portion **212** of the positioning element **21**, a limiting shoulder **2212** formed at the adjacent position of the sliding space **220** and the storage groove **2211** to limit the positioning portion **212** from detaching from the tube-shaped sleeve portion **222**, a disc-shaped resisting portion **223** provided on the outside of the tube-shaped fitting portion **221** for the preset second panel **5** to resist and limit when it is applied, and two relatively protruding rectangular locking portions **224** provided on the outside of the tube-shaped sleeve portion **222**. The surface of one side of the rectangular locking portions **224** is used for one end of the elastic element **23** to form a resisting effect. The tube-shaped fitting portion **221** is pushed in along the direction of the shank **211** of the positioning element **21** through the sliding space **220** at the storage groove **2211**, so that the positioning sleeve **22** is movably worn outside the positioning element **21**.

(15) The rotating mechanism **3** is assembled on the positioning mechanism **2**, and comprises a rotating sleeve **31** movably mounted on the positioning element **21** and the positioning sleeve **22**, a rotating element **32** movably assembled on the rotating sleeve **31**, and a pivoting element **33** movably inserted between the positioning element **21** and the rotating sleeve **31** and the rotating element **32**. The rotating sleeve **31** comprises an accommodating space **310** concavely formed therein, a pivot joint **311** provided on one side thereof opposite to the accommodating space **310** for the pivoting of the rotating element **32**, a through hole **312** located on one side of the accommodating space **310** towards the pivot joint **311** for the positioning element **21** of the positioning mechanism **2** to be movably inserted, two pivot joint grooves **313** respectively recessed on the surface of the through hole **312** on two opposite sides of the pivot joint **311**, two opposite convex portions **314** arranged transversely on two opposite wall surfaces of the accommodating space **310** remote from the pivot joint **311**, opposing stoppers **315** longitudinally provided with each convex portion **314** at the junctions, a channel **316** formed between each convex portion **314** and each stopper **315** for the rectangular locking portions **224** of the positioning sleeve **22** to rotate and penetrate, a notch **317** respectively formed on an outer side of each stopper **315** for the rectangular locking portions **224** to be rotated and aligned for lifting and displacement, and a supporting shoulder **318** formed at the inner wall surface thereof between the accommodating space **310** and the pivot joint **311** for the other end of the elastic element **23** to form a supporting function.

(16) Based on the above, the rotating element **32** is assembled on the pivot joint **311** of the rotating sleeve **31**, and comprises a wrenching portion **321**, two opposing extension arms **322** extending from one side of the wrenching portion **321** in the same direction, a wrenching space **323** formed between the two opposing extension arms **322**, and two through-shaped pivot holes **324** respectively formed on the extension arms **322** in communication with the wrenching space **323**.

(17) When the above-mentioned components are assembled, the docking element **1** is first fixed on the preset first panel **4** through each fixing hole **121**, and then push the other side of the positioning element **21** relative to the positioning portion **212** into the sliding space **220** in the direction of the tube-shaped fitting portion **221** of the positioning sleeve **22** to form a movable wear. At this time, the limiting shoulder **2212** of the tube-shaped fitting portion **221** is used for the positioning portion **212** to form a side limit. Then the tube-shaped sleeve portion **222** is sleeved with the elastic

element **23**, so that the positioning sleeve **22** is movable and placed outside the positioning element **21**. Then, the rotating sleeve **31** of the rotating mechanism **3** is aligned along the direction of the shank **211** of the positioning element **21** through the other side of the accommodating space **310** relative to the pivot joint **311**, and the notches **317** of the rotating sleeve **31** are respectively aligned with the rectangular locking portions **224** of the positioning sleeve **22** after push in to form the rotating sleeve **31** to fit on the positioning mechanism **2**, so that one end of the elastic element **23** is held against the surface of the rectangular locking portions **224**, and the other end is held against the supporting shoulder **318** of the rotating sleeve **31**. After the positioning element **21** of the positioning mechanism **2** extends into the through hole **312** of the rotating sleeve **31**, each pivot joint groove **313** of the rotating sleeve **31** corresponds to the perforation **213** of the positioning element **21**, and the through-shaped pivot holes **324** of the rotating element **32** of the rotating mechanism **3** are respectively aligned with the perforation **213** of the positioning element **21** on the other side relative to the pivot joint grooves **313**. Then, the pivoting element **33** is inserted through each through-shaped pivot hole **324**, each pivot joint groove **313** and the perforation **213**, so that the rotating element **32** forms a movable pivot state. Then, the tube-shaped fitting portion **221** of the positioning sleeve **22** of the positioning mechanism **2** is fixed in the preset fitting hole **50** of the preset second panel **5**, and then the positioning portion **212** of the positioning element **21** of the positioning mechanism **2** is rotated along the through hole **111** of the docking element **1** and placed in the positioning space **13** to form a combination of the positioning mechanism **2** and the docking element **1**. In this way, the docking element **1**, the positioning mechanism **2** and the rotating mechanism **3** constitute the fixing device of the present invention.

(18) In addition, the through hole **111** of the above-mentioned docking element **1** and the stop block **2121** of the positioning portion **212** of the positioning element **21** are in the shape of a long rectangle, and can also be triangular, trapezoidal, rhombus or irregular, so that the positioning portion **212** of the positioning element **21** can be held in the positioning space **13** through the through hole **111** of the docking element **1** during actual application and implementation. When the fixing holes **121** of the docking element **1** are combined with the preset first panel **4**, they can be firmly combined by locking, riveting, welding, etc. Moreover, the pivot joint grooves **313** of the rotating sleeve **31** can also be holes through which the rotating element **32** can generate a pivoting state during actual application and implementation. Thus, pull rotating element **32** can form linkage with the rotating sleeve **31** and the positioning element **21**. The positioning element **21** is in the shape of a rod, and the positioning sleeve **22** movably sleeved on the positioning element **21** is in the shape of a tube.

(19) Please refer to FIGS. **5**, **6**, **7**, **8**, and **9**, which are the side view (I) of the action of the present invention, the side view (II) of the action of the present invention, the side view (III) of the action of the present invention, the side view (IV) of the action of the present invention, and the sectional side view of the present invention. It can be clearly seen from the drawings that the fixing device of the present invention is fixed on the preset first panel **4** through the docking element **1** during actual application and implementation. The positioning sleeve **22** of positioning mechanism **2** is fixed on the preset second panel **5**, and the docking element **1** is used for the positioning mechanism **2** and the rotating mechanism **3** to be assembled on the docking element **1**. By applying force to the rotating sleeve **31** in the direction of the positioning sleeve **22** to form a lifting displacement, the elastic element **23** is elastically squeezed. Then, rotate the rotating element **32** of the rotating mechanism **3** (rotation is about 90 degrees) to simultaneously drive the rotating sleeve **31** and positioning element **21** to generate axial rotation. By means of rotation and lifting of the rotating sleeve **31**, the rectangular locking portions **224** of the positioning sleeve **22** located in the accommodating space **310** of the rotating sleeve **31** are moved from the notches **317** to the channels **316** along the edges of the convex portions **314**. After the rectangular locking portions **224** touch the stoppers **315**, a rotation stop is formed. Then put the positioning portion **212** of the positioning element **21** of the positioning mechanism **2** into the positioning space **13** along the through hole

111 of the docking element **1**. Through the rotating sleeve **31** to generate the rotation and lifting, the stop block **2121** of the positioning portion **212** of the positioning element **21** passes through the through hole **111** of the docking element **1** to the positioning space **13**. Then through rotating element **32** to generate rotation (rotation is about 90 degrees), the stop block **2121** is held against the surface of side of the base **11** of the docking element **1**. In this way, the preset first panel **4** and the preset second panel **5** can be firmly integrated into one body that is stable and not easy to loosen or fall apart. The rotating element **32** generates a pivoting state through the pivoting element **33**, and can also generate pivotal bending to save space.

(20) If you want to release the combined state of the preset first panel **4** and the preset second panel **5**, you must turn the rotating element **32** of rotating mechanism **3** again to rotate in the opposite direction (reverse rotation is about 90 degrees), and then drive the rotating sleeve **31** and the positioning element **21** to produce a backward axial rotation at the same time. As a result, the rectangular locking portions **224** of the positioning sleeve **22** located in the accommodating space **310** of the rotating sleeve **31** are reversely rotated through the rotating sleeve **31** to move from each channel **316** to each notch **317** along the edge of each convex portion **314**, and the elastic element **23** is elastically released, so that the rotating sleeve **31** produces a reverse lifting displacement, and then the stop block **2121** of the positioning portion **212** of the positioning element **21** is linked to generate a reverse rotation lifting through the rotating element **32** (the reverse rotation is about 90 degrees), and no resistance is formed on the surface of one side of the base **11** of the docking element **1**. Then through the rotating sleeve **31** to generate reverse rotation lift, the stop block **2121** of the positioning portion **212** of the positioning element **21** passes back through the through hole **111** of the docking element **1** to the storage groove **2211**, so as not to have a resistance effect. The preset first panel **4** can then be separated from the preset second panel **5**, and the preset first panel **4** and the preset second panel **5** can be combined firmly again, so as to achieve the convenience and rapid assembly of the preset first panel **4** and the preset second panel **5** with bare hands. It can effectively save operation time, reduce preparatory work and complicated steps.

(21) Therefore, the present invention has the following advantages: 1. By turning the rotating mechanism **3**, the positioning element **21** of the positioning mechanism **2** is driven to rotate to form a resisting effect, and the rectangular locking portions **224** of the positioning sleeve **22** of the positioning mechanism **2** are used to form a holding effect. In this way, the positioning element **21** is driven to vertically move up and down in the positioning sleeve **22** in a rotating manner. It does not need to use any hand tools, and only needs to combine (lock) or disengage (unlock) the preset first panel **4** and the preset second panel **5** through simple and easy operations, thereby saving time and effort. 2. When it is necessary to combine or disengage a large number of preset panels, the fast operation also saves a lot of time. 3. The rotating element **32** of the rotating mechanism **3** can only be rotated back and forth in one direction in the direction of turning in, so that the user has an obvious difference in the operating feel, and the user can easily identify and judge whether the positioning mechanism **2** is in a combined state or a disengaged state by whether it can be rotated clockwise or counterclockwise. In this way, it is easy and fast for users to operate intuitively, and further has a good anti-fooling effect, so as to achieve the effect of improving the convenience and fluency of installation or disassembly. 4. The elastic element **23** is elastically released and held against the surface of the rectangular locking portions **224** of the positioning sleeve **22** and the supporting shoulder **318** of the rotating sleeve **31**, so that the positioning element **21** is driven to form a lifting displacement in the through hole **312** of the rotating sleeve **31**. In this way, the rotating element **32** of the rotating mechanism **3** is positioned outside the pivot joint **311** when the rotating element **32** is in a vertical or horizontal state through the linkage of the positioning element **21**.

(22) The description is only a preferred embodiment of the present invention, and does not limit the patent scope of the present invention. Therefore, all simple modifications and equivalent structural changes made by using the description and drawings of the present invention should be included in

the patent scope of the present invention in the same way.

(23) To sum up, the fixing device of the present invention can indeed achieve its function and purpose when used. Therefore, the present invention is indeed an invention with excellent practicability. In order to meet the requirements for the application of new patents, an application is filed in accordance with the law. I hope that the review committee will approve this case as soon as possible to protect the hard work of the inventor. If the review committee has any doubts, please feel free to send us a letter to instruct, and the inventor will do his best to cooperate.

Claims

1. A fixing device, comprising a docking element, a positioning mechanism and a rotating mechanism: said docking element comprises a base, a through hole provided on a surface of said base, two fixing portions respectively extending from two opposite sides of said base, and a positioning space formed between said two fixing portions and between one side of said through hole and a preset first panel; said positioning mechanism is assembled on said base of said docking element, and comprises a positioning element, a positioning sleeve and an elastic element, said positioning element comprising a positioning portion located on one end thereof and movably worn on said through hole of said docking element to be located in said positioning space for rotational alignment and lifting displacement and a perforation provided on an opposite end thereof opposite to said positioning portion, said positioning sleeve being movably sleeved onto said positioning element, said positioning sleeve comprising a sliding space therein for said positioning element to move and wear, a tube-shaped fitting portion externally protruded from one end of said sliding space to be fixed in a preset fitting hole of a preset second panel, a tube-shaped sleeve portion externally protruded from an opposite end of said sliding space to be sleeved with said elastic element, a resisting portion provided on an outside of said tube-shaped fitting portion for said preset second panel to resist and limit and two rectangular locking portions externally provided adjacent to said tube-shaped sleeve portion; said rotating mechanism is assembled on said positioning mechanism, and comprises a rotating sleeve movably mounted on said positioning element and said positioning sleeve, a rotating element movably assembled on said rotating sleeve and a pivoting element movably inserted between said positioning element and said rotating sleeve and said rotating element, said rotating sleeve comprising an accommodating space with a through hole therein for said positioning element of said positioning mechanism to be movably inserted, a pivot joint provided an outside said through hole for pivoting of said rotating element, two pivot joint grooves respectively provided on two opposite sides of said through hole for pivoting of said pivoting element, two opposite convex portions arranged on two opposite wall surfaces of said accommodating space remote from said pivot joint, opposing stoppers respectively provided with each said convex portion at the junctions, a channel formed between each said convex portion and each said stopper for said rectangular locking portions of said positioning sleeve to rotate and penetrate and a notch respectively formed on an outer side of each said stopper for said rectangular locking portions to be rotated and aligned for lifting and displacement.

2. The fixing device as claimed in claim 1, wherein said through hole of said docking element is a long rectangular through hole; said positioning element further comprises a long rectangular stop block provided with said positioning portion corresponding to said through hole of said docking element.

3. The fixing device as claimed in claim 1, wherein said rotating element is movably assembled on said pivot joint of said rotating sleeve, said rotating element comprising a wrenching portion, two opposing extension arms extending from one side of said wrenching portion in the same direction, a wrenching space formed between said two opposing extension arms, and two through-shaped pivot holes respectively formed on said extension arms in communication with said wrenching space; said pivoting element is inserted through each said through-shaped pivot hole, each said

pivot joint groove and said perforation, so that said rotating element forms a movable pivot state.

4. The fixing device as claimed in claim 1, wherein said rotating sleeve further comprises a supporting shoulder formed at an inner wall surface thereof between said accommodating space and said pivot joint; said elastic element is set on said tube-shaped sleeve portion of said positioning sleeve with one end thereof held against a surface of said rectangular locking portion and an opposite end thereof held against said supporting shoulder in an elastic deformation state.

5. The fixing device as claimed in claim 1, wherein said positioning sleeve further comprises a storage groove recessed on a surface of said tube-shaped fitting portion in communication with said sliding space for said positioning portion of said positioning element to be rotated and aligned along said through hole of said docking element in a storage state of lifting displacement, and a limiting shoulder formed at an adjacent position of said sliding space and said storage groove for said positioning portion of said positioning element to form a limiting state.

6. The fixing device as claimed in claim 1, wherein said docking element further comprises a fixing hole respectively provided on a surface of each of said two fixing portions for fixing on said preset first panel.

7. The fixing device as claimed in claim 1, wherein said positioning element is a rod-shaped configuration and further comprises a shank, and said positioning portion is located on one end of said shank and movably worn on said through hole of said docking element to be located in said positioning space for rotational alignment and lifting displacement.

8. The fixing device as claimed in claim 1, wherein said positioning sleeve is a tube-shaped configuration; said fitting portion is a tube-shaped fitting portion with an enlarged outer diameter externally protruded from one end of said sliding space to be fixed in said preset fitting hole of said preset second panel; said sleeve portion is a tube-shaped sleeve portion externally protruded from an opposite end of said sliding space; said resisting portion is disc-shaped and is provided an outside said positioning sleeve adjacent to said tube-shaped fitting portion; said locking portions are rectangular locking portions arranged an outside said positioning sleeve adjacent to said tube-shaped sleeve portion.
