

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405426
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Ku; Kai-Ning et al.

Optical element

Abstract

An optical element includes a substrate, a first insulating layer, a first optical waveguide layer, a first edge coupler, and a first micro-optical element. The first insulating layer is disposed on the substrate. The first optical waveguide layer is disposed on the first insulating layer to transmit a light beam. The first edge coupler is disposed on the first insulating layer and coupled to an end of the first optical waveguide layer. The first micro-optical element is disposed on the substrate and includes a first inclined surface. The first micro-optical element is located within a first groove formed between the substrate, the first insulating layer, the first optical waveguide layer, and the first edge coupler. The light beam is sequentially transmitted from the first optical waveguide layer to the first edge coupler, emitted from the first edge coupler, and reflected by the first inclined surface to an optical fiber connector.

Inventors: Ku; Kai-Ning (Hsinchu County, TW), Wu; Ming-Hsien (Hsinchu County, TW)

Applicant: Industrial Technology Research Institute (Hsinchu, TW)

Family ID: 86499860

Assignee: Industrial Technology Research Institute (Hsinchu, TW)

Appl. No.: 18/070413

Filed: November 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230168433 A1	Jun. 01, 2023

Foreign Application Priority Data

TW	111143816	Nov. 16, 2022
----	-----------	---------------

Related U.S. Application Data

us-provisional-application US 63284002 20211129

Publication Classification

Int. Cl.: G02B6/30 (20060101)

U.S. Cl.:

CPC G02B6/30 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6406196	12/2001	Uno	385/47	G02B 6/4214
6925238	12/2004	Lee et al.	N/A	N/A
7224174	12/2006	Malendevich et al.	N/A	N/A
8855452	12/2013	Andry et al.	N/A	N/A
9459177	12/2015	Dong et al.	N/A	N/A
9588298	12/2016	Novack et al.	N/A	N/A
9759634	12/2016	Pitwon	N/A	G01M 11/33
2003/0044119	12/2002	Sasaki	385/49	G02B 6/4246
2004/0013378	12/2003	Lee	385/125	G01M 11/35
2004/0114869	12/2003	Fike et al.	N/A	N/A
2004/0197052	12/2003	Toyoda	385/137	G02B 6/3636
2005/0244106	12/2004	Fukuyama	385/48	G02B 6/4249
2007/0263957	12/2006	Shimizu	385/14	G02B 6/30
2011/0073972	12/2010	Heck et al.	N/A	N/A
2012/0076465	12/2011	Chen et al.	N/A	N/A
2013/0182998	12/2012	Andry	385/33	G02B 6/4204
2014/0205234	12/2013	Rong et al.	N/A	N/A
2015/0285996	12/2014	Selvaraja	N/A	N/A
2016/0238801	12/2015	Lee	N/A	G02B 6/136
2017/0131469	12/2016	Kobrinisky	N/A	G02B 6/4257
2020/0363594	12/2019	Lu	N/A	G02B 6/4228

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101010609	12/2006	CN	N/A
107346053	12/2016	CN	N/A
112698448	12/2020	CN	N/A
2006178001	12/2005	JP	N/A
201346360	12/2012	TW	N/A

1489162	12/2014	TW	N/A
2013048411	12/2012	WO	N/A
2020246042	12/2019	WO	N/A

OTHER PUBLICATIONS

“Office Action of Taiwan Counterpart Application”, issued on Oct. 5, 2023, p. 1-p. 5. cited by applicant

Robert Polster et al., “Wafer-scale high-density edge coupling for high throughput testing of silicon photonics”, 2018 Optical Fiber Communications Conference and Exposition (OFC), Mar. 11-15, 2018, pp. 1-3. cited by applicant

Mareike Trappen et al., “3D-printed optical probes for wafer-level testing of photonic integrated circuits”, Optics Express, vol. 28, No. 25, Dec. 7, 2020, pp. 37996-38007. cited by applicant

Primary Examiner: Rahll; Jerry

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application claims the priority benefit of U.S. provisional application Ser. No. 63/284,002, filed on Nov. 29, 2021, and Taiwan application serial no. 111143816, filed on Nov. 16, 2022. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

TECHNICAL FIELD

(1) The technical field relates to an optical element.

BACKGROUND

(2) Data centers have increasing demands for equipment bandwidth and speed. In recent years, the co-packaged optics (CPO) architecture has emerged. As the bandwidth of network switches enters the 51.2T generation, the optical fiber packaging density will encounter a bottleneck. Therefore, wavelength division multiplexing (WDM) components need to be introduced into photonic chips to alleviate the optical fiber density issue.

(3) Grating couplers have been used as the input/output couplers (I/O couplers) for photonic chips, but they are not suitable for use in series with wavelength division multiplexing components because of narrow optical bandwidth. On the contrary, an edge coupler has a large optical bandwidth and is suitable for connecting in series with wavelength division multiplexing components, but there remains a problem that the measurement efficiency is very low, making it difficult to be introduced into mass production.

SUMMARY

(4) The disclosure provides an optical element which facilitates measurement and thus is suitable for mass production.

(5) An exemplary embodiment of the disclosure provides an optical element including a substrate, a first insulating layer, a first optical waveguide layer, a first edge coupler, and a first micro-optical element. The first insulating layer is disposed on the substrate. The first optical waveguide layer is disposed on the first insulating layer and configured to transmit a light beam. The first edge coupler is disposed on the first insulating layer and coupled to an end of the first optical waveguide layer. The first micro-optical element is disposed on the substrate and includes a first inclined surface. A first groove is formed between the substrate, the first insulating layer, the first optical waveguide

layer, and the first edge coupler. The first micro-optical element is located within the first groove. The light beam is sequentially transmitted from the first optical waveguide layer to the first edge coupler, emitted from the first edge coupler, and reflected by the first inclined surface to an optical fiber connector.

(6) Based on the above, according to an embodiment of the disclosure, since the optical element is provided with the first edge coupler, the optical element is suitable for connecting wavelength division multiplexing components in series. Furthermore, the optical element is provided with the first micro-optical element and uses the first micro-optical element to couple the light beam to the optical fiber connector. Therefore, the optical element according to the embodiment of the disclosure effectively solves the problem of low wafer-level measurement efficiency and facilitates mass production of the overall system.

(7) Several exemplary embodiments accompanied with drawings are described in detail below to further describe the disclosure in details.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate exemplary embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

(2) FIG. 1 is a schematic diagram of the optical element according to the first embodiment of the disclosure.

(3) FIG. 2 is an enlarged schematic diagram of the portion of the first micro-optical element in FIG. 1.

(4) FIG. 3 is a schematic diagram of the optical element according to the second embodiment of the disclosure.

(5) FIG. 4 is a schematic diagram of the optical element according to the third embodiment of the disclosure.

(6) FIG. 5A is a schematic diagram of the optical element according to the fourth embodiment of the disclosure.

(7) FIG. 5B is an enlarged schematic diagram of the portion of the lens in FIG. 5A.

(8) FIG. 6 is a schematic diagram of the optical element according to the fifth embodiment of the disclosure.

(9) FIG. 7 is a schematic diagram of the optical element according to the sixth embodiment of the disclosure.

(10) FIG. 8 is a schematic diagram of the optical element according to the seventh embodiment of the disclosure.

DETAILED DESCRIPTION OF DISCLOSED EMBODIMENTS

(11) In the following detailed description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed embodiments. It will be apparent, however, that one or more embodiments may be practiced without these specific details. In other instances, well-known structures and devices are schematically shown in order to simplify the drawing.

(12) FIG. 1 is a schematic diagram of the optical element according to the first embodiment of the disclosure. Referring to FIG. 1, an embodiment of the disclosure provides an optical element 10, which includes a substrate 100, a first insulating layer 200, a first optical waveguide layer 300, a first edge coupler 400, and a first micro-optical element 500. The first insulating layer 200 is disposed on the substrate 100. The first optical waveguide layer 300 is disposed on the first

insulating layer **200** and configured to transmit a light beam **L1**. The first edge coupler **400** is disposed on the first insulating layer **200** and coupled to an end of the first optical waveguide layer **300**. The first micro-optical element **500** is disposed on the substrate **100** and includes a first inclined surface **500S1**. A first groove **G** is formed between the substrate **100**, the first insulating layer **200**, the first optical waveguide layer **300**, and the first edge coupler **400**. The first micro-optical element **500** is located within the first groove **G**. The light beam **L1** is sequentially transmitted from the first optical waveguide layer **300** to the first edge coupler **400**, emitted from the first edge coupler **400**, and reflected by the first inclined surface **500S1** to an optical fiber connector **F**. In an embodiment, the light beam **L1** may be sequentially transmitted from the optical fiber connector **F** to the first inclined surface **500S1**, reflected by the first inclined surface **500S1** to the first edge coupler **400**, and transmitted from the first edge coupler **400** to the first optical waveguide layer **300**.

(13) In detail, the first groove **G** is formed by, for example, deep etching the edges of the first edge coupler **400**, the first optical waveguide layer **300**, and the first insulating layer **200**. The first micro-optical element **500** is a micro-optical element having the first inclined surface **500S1** manufacturing by, for example, wet-etching a semiconductor material (such as silicon (Si), silicon nitride (SiN), and silicon oxynitride (SiON)) or metal, which is then packaged in the first groove **G** with high precision by using a flip chip bonder or the like. Alternatively, the first micro-optical element **500** is a micro-optical element having the first inclined surface **500S1** formed by 3D printing technology with use of, for example, a polymer, which is then packaged in the first groove **G** with high precision by picking and placing. In another embodiment, the first micro-optical element **500** may also be a mixed structure of silicon, silicon nitride, silicon oxynitride, polymer, metal, etc., and have a refractive index in a range of 1.45 to 3.5, for example, but the disclosure is not limited thereto.

(14) In this embodiment, the first inclined surface **500S1** is coated with a reflective metal layer **520**, so that the light beam **L1** can be reflected by the first inclined surface **500S1**.

(15) In this embodiment, the first micro-optical element **500** further includes a bottom surface **500S2**. The bottom surface **500S2** is connected to the first inclined surface **500S1**. The first micro-optical element **500** is connected to the substrate **100** through the bottom surface **500S2**. An included angle θ between the first inclined surface **500S1** and the bottom surface **500S2** is in a range of 30 degrees to 60 degrees.

(16) In this embodiment, an air gap **A** is formed between the first micro-optical element **500** and the first edge coupler **400**. A distance **d** between the first micro-optical element **500** and the first edge coupler **400** is in a range of 0.5 μm to 10 μm to keep the transmission distance of the light beam **L1** in air short.

(17) FIG. 2 is an enlarged schematic diagram of the portion of the first micro-optical element in FIG. 1. Referring to FIG. 1 and FIG. 2, in this embodiment, a length **L** of the first micro-optical element **500** in the direction perpendicular to the transmission direction of the light beam **L1** in the first optical waveguide layer **300** and perpendicular to the direction from the substrate **100** to the first optical waveguide layer **300** is in a range of 10 μm to 1 mm. The first micro-optical element **500** is disposed beside the first edge coupler **400**, and the function of the inclined surface **500S1** is to reflect the light beam **L1**, turn the light beam **L1** upward, and transmit the light beam **L1** toward the optical fiber connector **F**. The geometrical length **L** of the first micro-optical element **500** is in a range of 10 μm to 1 mm.

(18) In this embodiment, a width **W2** of the first micro-optical element **500** in the transmission direction of the light beam **L1** in the first optical waveguide layer **300** is in a range of 5 μm to 125 μm .

(19) In this embodiment, a height **H** of the first micro-optical element **500** in the direction from the substrate **100** to the first optical waveguide layer **300** is in a range of 1 μm to 62.5 μm .

(20) Based on the above, according to an embodiment of the disclosure, since the optical element

10 is provided with the first edge coupler **400**, the optical element **10** is suitable for connecting wavelength division multiplexing components in series. Furthermore, the optical element **10** is provided with the first micro-optical element **500** and uses the first micro-optical element **500** to couple the light beam **L1** to the optical fiber connector **F**. Therefore, compared with the conventional optical element using an edge coupler, which needs to cut the wafer in order to measure the photonic chip, the optical element **10** according to the embodiment of the disclosure effectively solves the problem of low wafer-level measurement efficiency and facilitates mass production of the overall system.

(21) In the manufacturing process of the micro-optical element **500**, the inclined surface **500S1** may be formed on the optical element **10** by using an etching process directly. Furthermore, the micro-optical element **500** may also be integrated on a side of the first edge coupler **400** by a packaging method (such as a flip-chip bonder) to form a 45-degree reflective inclined surface **500S1**, which has several advantages: (1) the geometric structure of the micro-optical element **500** has a large degree of flexibility (as shown in FIG. 3, FIG. 4, FIG. 5A, FIG. 5B, FIG. 6, and FIG. 7); (2) the reflective inclined surface **500S1** is formed by a relatively simple process without using an acid or alkali solution for wet etching; and (3) the temperature for bonding between the micro-optical element **500** and the bottom surface **500S2** is low (for example, 80° C. to 100° C. by PDMS bonding), which does not affect other components that have been completed in the front-end process (note: the thermal budget of a general CMOS back-end process is about 400° C. or less).

(22) FIG. 3 is a schematic diagram of the optical element according to the second embodiment of the disclosure. Referring to FIG. 3, the optical element **10A** is substantially the same as the optical element **10** of FIG. 1, and the main differences are as follows. In this embodiment, the first micro-optical element **500A** further includes a second inclined surface **500S3**. The second inclined surface **500S3** is opposite to the first inclined surface **500S1** and faces the substrate **100**. The second inclined surface **500S3** helps to align the first micro-optical element **500A** with the first groove **G** in the process of picking and placing the first micro-optical element **500A**, so as to allow the first micro-optical element **500A** to slide into the first groove **G** automatically.

(23) In this embodiment, in the direction from the first optical waveguide layer **300** to the substrate **100**, a bottom position **P1** of the first inclined surface **500S1** is lower than a bottom **P2** of the first optical waveguide layer **300**, which helps to improve the light coupling efficiency of the light beam **L1** from the first edge coupler **400** to the first inclined surface **500S1**.

(24) Moreover, in this embodiment, the first inclined surface **500S1** is coated with a reflective metal layer **520**, so that the light beam **L1** can be reflected by the first inclined surface **500S1**. The other advantages of the optical element **10A** are similar to those of the optical element **10**, and will not be repeated here.

(25) FIG. 4 is a schematic diagram of the optical element according to the third embodiment of the disclosure. Referring to FIG. 4, the optical element **10B** is substantially the same as the optical element **10A** of FIG. 3, and the main differences are as follows. In this embodiment, the optical element **10B** further includes a cantilever structure **600**. The cantilever structure **600** is connected to the first micro-optical element **500A**. In another embodiment, the cantilever structure **600** may be integrally formed with the first micro-optical element **500A**. The cantilever structure **600** is configured to lean on the first edge coupler **400**, so that a bottom position of the first inclined surface **500S1** is lower than a bottom of the first optical waveguide layer **300**, which improves the light coupling efficiency of the light beam **L1** from the first edge coupler **400** to the first inclined surface **500S1**. For example, if the first groove **G** becomes too deep after the etching process, the height at which the first inclined surface **500S1** is arranged may be too low and affect the light coupling efficiency of the optical element. Therefore, providing the cantilever structure **600** can avoid the problem that the first groove **G** is too deep.

(26) Moreover, in this embodiment, the first inclined surface **500S1** is coated with a reflective metal layer **520**, so that the light beam **L1** can be reflected by the first inclined surface **500S1**. The

other advantages of the optical element **10B** are similar to those of the optical element **10A**, and will not be repeated here.

(27) FIG. 5A is a schematic diagram of the optical element according to the fourth embodiment of the disclosure. FIG. 5B is an enlarged schematic diagram of the portion of the lens in FIG. 5A. Referring to FIG. 5A and FIG. 5B, the optical element **10C** is substantially the same as the optical element **10B** of FIG. 4, and the main differences are as follows. In this embodiment, the optical element **10C** further includes a lens **700**. The lens **700** is disposed on the first inclined surface **500S1** and disposed on the transmission path of the light beam **L1**, and is configured to collimate the light beam **L1**. In another embodiment, the lens **700** may be integrally formed with the cantilever structure **600**, or the lens **700** may be integrally formed with the cantilever structure **600** and the first micro-optical element **500A**. After the light beam **L1** is emitted from the first edge coupler **400**, the light beam **L1** is reflected to the lens **700** by the first inclined surface **500S1**, passes through the lens **700**, and then is transmitted to the optical fiber connector **F**. Alternatively, the light beam **L1** is sequentially transmitted from the optical fiber connector **F** to the lens **700**, transmitted to the first inclined surface **500S1** through the lens **700**, and then reflected to the first edge coupler **400** by the first inclined surface **500S1**.

(28) In this embodiment, a diameter **D** of the lens **700** may correspond to the diameter of the optical fiber connector **F**. For example, the diameter **D** falls between the diameter of a single-mode optical fiber connector and the diameter of a multi-mode optical fiber connector. In an embodiment, the diameter **D** of the lens **700** is in a range of 8 μm to 62.5 μm .

(29) In this embodiment, a distance **S** of an overlapping area between the lens **700** and the first edge coupler **400** is in a range of 0 μm to **D/2**. A thickness **t** of the lens **700** is in a range of 50 μm to 1 mm. Since the optical element **10C** is provided with the lens **700**, the light coupling efficiency is improved.

(30) Moreover, in this embodiment, the first inclined surface **500S1** is coated with a reflective metal layer **520**, so that the light beam **L1** can be reflected by the first inclined surface **500S1**. The other advantages of the optical element **10C** are similar to those of the optical element **10B**, and will not be repeated here.

(31) FIG. 6 is a schematic diagram of the optical element according to the fifth embodiment of the disclosure. Referring to FIG. 6, the optical element **10D** is substantially the same as the optical element **10A** of FIG. 3, and the main differences are as follows. In this embodiment, the first inclined surface **500S1** and the second inclined surface **500S3** of the first micro-optical element **500D** are directly connected to each other.

(32) Moreover, in this embodiment, the first inclined surface **500S1** is coated with a reflective metal layer **520**, so that the light beam **L1** can be reflected by the first inclined surface **500S1**. The other advantages of the optical element **10D** are similar to those of the optical element **10A**, and will not be repeated here.

(33) FIG. 7 is a schematic diagram of the optical element according to the sixth embodiment of the disclosure. Referring to FIG. 7, the optical element **10E** is substantially the same as the optical element **10** of FIG. 1, and the main differences are as follows. In this embodiment, the first micro-optical element **500E** further includes a vertical surface **500S4**. Two ends of the vertical surface **500S4** are respectively connected to the first inclined surface **500S1** and the bottom surface **500S2**.

(34) Moreover, in this embodiment, the first inclined surface **500S1** is coated with a reflective metal layer **520**, so that the light beam **L1** can be reflected by the first inclined surface **500S1**. The other advantages of the optical element **10E** are similar to those of the optical element **10**, and will not be repeated here.

(35) FIG. 8 is a schematic diagram of the optical element according to the seventh embodiment of the disclosure. Referring to FIG. 8, the optical element **10F** is substantially the same as the optical element **10** of FIG. 1, and the main differences are as follows. In this embodiment, the optical element **10F** further includes at least one second insulating layer **200'**, at least one second optical

waveguide layer (not shown in the drawing), at least one second edge coupler **400'**, and at least one second micro-optical element **500'**. The second insulating layer **200'** is disposed on the substrate **100**. Similar to the first optical waveguide layer **300** of FIG. 1, the second optical waveguide layer is disposed on the second insulating layer **200'**. The second edge coupler **400'** is disposed on the second insulating layer **200'** and is coupled to an end of the second optical waveguide layer (in the direction perpendicular to the paper surface of FIG. 6). The second micro-optical element **500'** is disposed on the substrate **100**, and the second micro-optical element **500'** is located beside the first micro-optical element **500**. Each second micro-optical element **500'** includes a third inclined surface **500S1'**. At least one second groove **G'** is formed between the substrate **100**, the second insulating layer **200'**, the second optical waveguide layer, and the second edge coupler **400'**, and the second groove **G'** is located beside the first groove **G**. The second micro-optical element **500'** is located within the second groove **G'**.

(36) Each of the first micro-optical element **500** and the second micro-optical elements **500'** corresponds to one optical fiber connector on the optical path. That is, the first micro-optical element **500** and the second micro-optical elements **500'** may be integrated into the optical element **10F** by single transfer or bulk transfer, thereby increasing the data throughput of the overall wafer-level measurement.

(37) Moreover, in this embodiment, the first inclined surface **500S1** and the third inclined surface **500S1'** are coated with reflective metal layers **520**, so that the light beams can be reflected by the first inclined surface **500S1** or the third inclined surface **500S1'**. The other advantages of the optical element **10F** are similar to those of the optical element **10**, and will not be repeated here.

(38) To sum up, according to an embodiment of the disclosure, since the optical element is provided with the first edge coupler, the optical element is suitable for connecting wavelength division multiplexing components in series. Furthermore, the optical element is provided with the first micro-optical element and uses the first micro-optical element to couple the light beam to the optical fiber connector. Therefore, compared with the conventional optical element using an edge coupler, which needs to cut the wafer in order to measure the photonic chip, the optical element according to the embodiment of the disclosure effectively solves the problem of low wafer-level measurement efficiency and facilitates mass production of the overall system.

(39) It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the disclosed embodiments without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the disclosure cover modifications and variations of this disclosure provided they fall within the scope of the following claims and their equivalents.

Claims

1. An optical element, comprising: a substrate; a first insulating layer disposed on the substrate; a first optical waveguide layer disposed on the first insulating layer and configured to transmit a light beam; a first edge coupler disposed on the first insulating layer and coupled to an end of the first optical waveguide layer; and a first micro-optical element disposed on the substrate and comprising a first inclined surface, a first groove is formed between the substrate, the first insulating layer, the first optical waveguide layer, and the first edge coupler, and the first micro-optical element is located within the first groove, and the light beam is sequentially transmitted from the first optical waveguide layer to the first edge coupler, emitted from the first edge coupler, and reflected by the first inclined surface to an optical fiber connector, wherein the first micro-optical element further comprises a second inclined surface, and the second inclined surface is opposite to the first inclined surface and faces the substrate, and a bottom position of the first inclined surface is lower than a bottom of the first optical waveguide layer in a direction from the first optical waveguide layer to the substrate.

2. The optical element according to claim 1, wherein the first inclined surface is coated with a reflective metal layer.
3. The optical element according to claim 1, wherein the first micro-optical element further comprises a bottom surface, the bottom surface is connected to the first inclined surface, and the first micro-optical element is connected to the substrate through the bottom surface, and an included angle between the first inclined surface and the bottom surface is in a range of 30 degrees to 60 degrees.
4. The optical element according to claim 3, wherein the first micro-optical element further comprises a vertical surface, and two ends of the vertical surface are respectively connected to the first inclined surface and the bottom surface.
5. The optical element according to claim 1, wherein an air gap is formed between the first micro-optical element and the first edge coupler.
6. The optical element according to claim 1, wherein the first inclined surface and the second inclined surface are directly connected to each other.
7. The optical element according to claim 1, further comprising: at least one second insulating layer disposed on the substrate; at least one second optical waveguide layer disposed on the at least one second insulating layer; at least one second edge coupler disposed on the at least one second insulating layer and coupled to an end of the at least one second optical waveguide layer; and at least one second micro-optical element disposed on the substrate, wherein each of the at least one second micro-optical element comprises a third inclined surface, wherein at least one second groove is formed between the substrate, the at least one second insulating layer, the at least one second optical waveguide layer, and the at least one second edge coupler, and the at least one second micro-optical element is located within the at least one second groove.
8. The optical element according to claim 1, further comprising: a lens arranged on the first inclined surface, disposed on a transmission path of the light beam, and configured to collimate the light beam, wherein the light beam is emitted from the first edge coupler and then reflected to the lens by the first inclined surface.
9. The optical element according to claim 8, wherein a distance of an overlapping area between the lens and the first edge coupler is in a range of $0\ \mu\text{m}$ to $D/2$, where D is a diameter of the lens.
10. An optical element, comprising: a substrate; a first insulating layer disposed on the substrate; a first optical waveguide layer disposed on the first insulating layer and configured to transmit a light beam; a first edge coupler disposed on the first insulating layer and coupled to an end of the first optical waveguide layer; and a first micro-optical element disposed on the substrate and comprising a first inclined surface, a first groove is formed between the substrate, the first insulating layer, the first optical waveguide layer, and the first edge coupler, and the first micro-optical element is located within the first groove, and the light beam is sequentially transmitted from the first optical waveguide layer to the first edge coupler, emitted from the first edge coupler, and reflected by the first inclined surface to an optical fiber connector, wherein the first micro-optical element is in direct contact with the substrate at a surface of the first groove farthest away from the first edge coupler in a direction of the first micro-optical element towards the substrate, wherein the first micro-optical element further comprises a second inclined surface, and the second inclined surface is opposite to the first inclined surface and faces the substrate, and a bottom position of the first inclined surface is lower than a bottom of the first optical waveguide layer in a direction from the first optical waveguide layer to the substrate.
11. The optical element according to claim 10, further comprising: at least one second insulating layer disposed on the substrate; at least one second optical waveguide layer disposed on the at least one second insulating layer; at least one second edge coupler disposed on the at least one second insulating layer and coupled to an end of the at least one second optical waveguide layer; and at least one second micro-optical element disposed on the substrate, wherein each of the at least one second micro-optical element comprises a third inclined surface, wherein at least one second

groove is formed between the substrate, the at least one second insulating layer, the at least one second optical waveguide layer, and the at least one second edge coupler, and the at least one second micro-optical element is located within the at least one second groove.

12. The optical element according to claim 10, wherein the first inclined surface is coated with a reflective metal layer.

13. The optical element according to claim 10, wherein the first micro-optical element further comprises a bottom surface, the bottom surface is connected to the first inclined surface, and the first micro-optical element is connected to the substrate through the bottom surface, and an included angle between the first inclined surface and the bottom surface is in a range of 30 degrees to 60 degrees.

14. The optical element according to claim 13, wherein the first micro-optical element further comprises a vertical surface, and two ends of the vertical surface are respectively connected to the first inclined surface and the bottom surface.

15. The optical element according to claim 10, wherein an air gap is formed between the first micro-optical element and the first edge coupler.

16. The optical element according to claim 1, wherein the first inclined surface and the second inclined surface are directly connected to each other.

17. The optical element according to claim 10, further comprising: a lens arranged on the first inclined surface, disposed on a transmission path of the light beam, and configured to collimate the light beam, wherein the light beam is emitted from the first edge coupler and then reflected to the lens by the first inclined surface.

18. The optical element according to claim 17, wherein a distance of an overlapping area between the lens and the first edge coupler is in a range of 0 μm to $D/2$, where D is a diameter of the lens.
