

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406448
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Gurgul; Piotr et al.

Enhanced reading with AR glasses

Abstract

Systems, methods, and computer readable media for enhanced augmented reality (AR) reading are provided, where the methods include entering a reading mode, capturing an image of a section of reading materials such as a page of a book, identifying a code within the image, and identifying a code module corresponding to the code. The methods further include executing the code module, the code module providing an augmented reality object or virtual reality object related to an object depicted on the section or page, entering a sleep mode for a sleep duration based on an estimated reading time duration of a section or page, awaking after the sleep duration, and capturing a next image. The sleep duration is adjusted based on times when identifiers of the sections of the reading materials such as numbers are captured. The user may manually wake the AR reading device using an external user interface.

Inventors:	Gurgul; Piotr (Hergiswil, CH), Zakrzewski; Tomasz (Lachen, CH)
Applicant:	Snap Inc. (Santa Monica, CA)
Family ID:	86992045
Assignee:	Snap Inc. (Santa Monica, CA)
Appl. No.:	18/374519
Filed:	September 28, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240029370 A1	Jan. 25, 2024

Related U.S. Application Data

continuation parent-doc US 17651147 20220215 US 11861801 child-doc US 18374519
us-provisional-application US 63295460 20211230

Publication Classification

Int. Cl.: G06T19/00 (20110101); G06F3/01 (20060101); H04W4/80 (20180101)

U.S. Cl.:

CPC G06T19/006 (20130101); G06F3/017 (20130101); H04W4/80 (20180201);

Field of Classification Search

CPC: G06T (19/006); G06F (3/017); G06F (3/015); G06F (3/013); G06F (3/016); G06F (3/011); H04W (4/80); H04W (52/0209)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5170159	12/1991	Kawabata	348/730	G04G 15/00
6553501	12/2002	Yokoe	N/A	N/A
7971156	12/2010	Albertson et al.	N/A	N/A
8144639	12/2011	Ghaus	455/574	H04W 76/28
8581844	12/2012	Ho	345/158	G06F 1/1626
8922487	12/2013	Ho et al.	N/A	N/A
9094539	12/2014	Noble	N/A	H04N 21/00
9165381	12/2014	Latta	N/A	G06F 16/338
9225897	12/2014	Sehn et al.	N/A	N/A
9229231	12/2015	Small	N/A	G06F 3/167
9239618	12/2015	Cho et al.	N/A	N/A
9276886	12/2015	Samaranayake	N/A	N/A
9286692	12/2015	Lucas-Woodley	N/A	G06T 7/74
9310882	12/2015	Kochi	N/A	A63F 13/65
9317486	12/2015	Story, Jr. et al.	N/A	N/A
9349218	12/2015	Keating	N/A	G06F 3/011
9541986	12/2016	Rohrweck	N/A	N/A
9595115	12/2016	Cederlof	N/A	N/A
9606622	12/2016	Brothers	N/A	G06F 3/013
9705831	12/2016	Spiegel	N/A	N/A
9742713	12/2016	Spiegel et al.	N/A	N/A
9805511	12/2016	Hintermeister et al.	N/A	N/A
9883110	12/2017	Martin et al.	N/A	N/A
10043407	12/2017	Murdock et al.	N/A	N/A
10055641	12/2017	Krishnan	N/A	G06V 20/20
10102423	12/2017	Shaburov et al.	N/A	N/A
10140766	12/2017	Lucas-Woodley	N/A	G06T 19/006
10268175	12/2018	Sugama et al.	N/A	N/A
10270985	12/2018	Kamhi et al.	N/A	N/A
10284508	12/2018	Allen et al.	N/A	N/A
10387570	12/2018	VanBlon	N/A	G06F 40/30
10439972	12/2018	Spiegel et al.	N/A	N/A

10509466	12/2018	Miller et al.	N/A	N/A
10514876	12/2018	Sehn	N/A	N/A
10614855	12/2019	Huang	N/A	N/A
10657968	12/2019	Raman	N/A	G16H 20/70
10748347	12/2019	Li et al.	N/A	N/A
10762928	12/2019	Camus	N/A	H04N 21/42201
10770035	12/2019	Giusti	N/A	H04M 1/724
10777019	12/2019	Feng et al.	N/A	N/A
10795527	12/2019	Legge	N/A	G06F 3/0482
10817582	12/2019	Brown et al.	N/A	N/A
10958608	12/2020	Allen et al.	N/A	N/A
10962809	12/2020	Castañeda	N/A	N/A
10996846	12/2020	Robertson et al.	N/A	N/A
10997787	12/2020	Ge et al.	N/A	N/A
11012390	12/2020	Al Majid et al.	N/A	N/A
11030454	12/2020	Xiong et al.	N/A	N/A
11036368	12/2020	Al Majid et al.	N/A	N/A
11062498	12/2020	Voss et al.	N/A	N/A
11087728	12/2020	Canberk et al.	N/A	N/A
11092998	12/2020	Castañeda et al.	N/A	N/A
11106342	12/2020	Al Majid et al.	N/A	N/A
11126206	12/2020	Meisenholder et al.	N/A	N/A
11143867	12/2020	Rodriguez, II	N/A	N/A
11169600	12/2020	Canberk et al.	N/A	N/A
11227626	12/2021	Krishnan Gorumkonda et al.	N/A	N/A
11507169	12/2021	Agrawal	N/A	A61B 5/746
11861801	12/2023	Gurgul	N/A	G06F 3/013
11867904	12/2023	Choi	N/A	G06V 10/945
11995899	12/2023	Wu	N/A	G06V 20/63
2012/0223968	12/2011	Kashimoto	345/633	G06T 19/006
2012/0262486	12/2011	Raghoebardajal et al.	N/A	N/A
2012/0324213	12/2011	Ho et al.	N/A	N/A
2013/0147687	12/2012	Small	345/8	G06F 3/015
2013/0171603	12/2012	Self et al.	N/A	N/A
2013/0307855	12/2012	Lamb et al.	N/A	N/A
2014/0002491	12/2013	Lamb	345/633	G02B 27/017
2014/0071166	12/2013	Ho et al.	N/A	N/A
2014/0108842	12/2013	Frank et al.	N/A	N/A
2014/0118257	12/2013	Baldwin	345/158	G06F 3/017
2014/0210710	12/2013	Shin et al.	N/A	N/A
2015/0123966	12/2014	Newman	N/A	N/A
2015/0316983	12/2014	Park et al.	N/A	N/A
2016/0187976	12/2015	Levesque	345/156	G06F 3/013
2016/0328607	12/2015	Krishnan	N/A	G06F 16/9574
2017/0134553	12/2016	Jeon et al.	N/A	N/A
2018/0300897	12/2017	Woods	N/A	G06T 7/74

2018/0365384	12/2017	Althoff	N/A	A61B 5/4815
2020/0143773	12/2019	Tholfesen et al.	N/A	N/A
2020/0334914	12/2019	Haines	N/A	N/A
2021/0011612	12/2020	Dancie et al.	N/A	N/A
2021/0074016	12/2020	Li et al.	N/A	N/A
2021/0166732	12/2020	Shaburova et al.	N/A	N/A
2021/0241529	12/2020	Cowburn et al.	N/A	N/A
2021/0303075	12/2020	Cowburn et al.	N/A	N/A
2021/0303077	12/2020	Anvaripour et al.	N/A	N/A
2021/0303140	12/2020	Mourkogiannis	N/A	N/A
2021/0382564	12/2020	Blachly et al.	N/A	N/A
2021/0397000	12/2020	Rodriguez, II	N/A	N/A
2022/0075438	12/2021	Palmer	N/A	G06F 1/3228
2022/0197028	12/2021	Choi	N/A	G06V 20/47
2022/0236845	12/2021	Alam	N/A	G06F 3/0483
2022/0245574	12/2021	Cella et al.	N/A	N/A
2022/0413047	12/2021	Jiang et al.	N/A	N/A
2023/0020265	12/2022	Min et al.	N/A	N/A
2023/0064572	12/2022	Park	N/A	G06F 1/3275
2023/0171341	12/2022	Lee	455/411	A61B 5/7405
2023/0215107	12/2022	Gurgul	345/633	G06T 19/006

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
118475898	12/2023	CN	N/A
WO-2023129380	12/2022	WO	N/A

OTHER PUBLICATIONS

“U.S. Appl. No. 17/651,147, Non Final Office Action mailed Mar. 1, 2023”, 24 pgs. cited by applicant

“U.S. Appl. No. 17/651,147, Notice of Allowance mailed Jun. 28, 2023”, 9 pgs. cited by applicant

“U.S. Appl. No. 17/651,147, Response filed May 8, 2023 to Non Final Office Action mailed Mar. 1, 2023”, 10 pgs. cited by applicant

“International Application Serial No. PCT/US2022/052828, International Search Report mailed Apr. 21, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2022/052828, Written Opinion mailed Apr. 21, 2023”, 8 pgs. cited by applicant

Kon Patentability mailed Jul. 11, 2024“, 10 pgs ”International Application Serial No. PCT/US2022/052828, International Preliminary Report. cited by applicant

Primary Examiner: Good-Johnson; Motilewa

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CLAIM OF PRIORITY (1) This application is a continuation of U.S. patent application Ser. No. 17/651,147, filed on Feb. 15, 2022, which claims the benefit of priority to U.S. Provisional

TECHNICAL FIELD

(1) Examples of the present disclosure relate generally to enhanced reading with augmented reality (AR) glasses. More particularly, but not by way of limitation, examples of the present disclosure relate to reducing power needed to provide enhanced reading where AR modules are launched based on codes embedded in reading materials such as a book, magazine, news paper, and so forth.

BACKGROUND

(2) As the popularity of virtual reality (VR), mixed reality (MR), and augmented reality (AR) systems continues to grow, users increasingly want to interact with virtual media content items in the mixed reality and VR environment. However, providing the virtual media content can be power intensive particularly for wearable devices such as AR glasses. Additionally, determining which or what virtual media content the user would like to be provided for a particular context is increasingly difficult to determine as the availability of virtual media content increases.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced. Some nonlimiting examples are illustrated in the figures of the accompanying drawings in which:

(2) FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some examples.

(3) FIG. 2 is a diagrammatic representation of a messaging system, in accordance with some examples, that has both client-side and server-side functionality.

(4) FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some examples.

(5) FIG. 4 is a diagrammatic representation of a message, in accordance with some examples.

(6) FIG. 5 is a flowchart for an access-limiting process, in accordance with some examples.

(7) FIG. 6 illustrates a system for enhanced reading with AR glasses, in accordance with some examples.

(8) FIG. 7 illustrates a flow diagram of the operation of the wearable electronic device **602**, in accordance with some examples.

(9) FIG. 8 illustrates a method of enhanced reading with AR glasses, in accordance with some examples.

(10) FIG. 9 illustrates a book with codes, in accordance with some examples.

(11) FIG. 10 illustrates a book with codes, in accordance with some examples.

(12) FIG. 11 illustrates examples of a wearable electronic device in the form of glasses, in accordance with some examples.

(13) FIG. 12 illustrates a user interface for module selection, in accordance with some examples.

(14) FIG. 13 illustrates a method for enhanced reading with AR glasses, in accordance with some examples.

(15) FIG. 14 is a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, in accordance with some examples.

(16) FIG. 15 is a block diagram showing a software architecture within which examples may be implemented.

(17) FIG. 16 is a diagrammatic representation of a processing environment, in accordance with some examples.

DETAILED DESCRIPTION

(18) The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative examples of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various examples of the inventive subject matter. It will be evident, however, to those skilled in the art, that examples of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

(19) Reading is still an important and popular activity. In some examples, printed codes are added that enable an enhanced reading experience, where the printed codes are printed in traditional printed media (e.g., paper books, magazines, etc.) or included in electronic media (e.g., electronic books, electronic magazines, etc.) and enable the reader to seamlessly experience virtual objects overlaid in the physical world while reading. The reader uses a wearable electronic device such as AR glasses that identify the printed codes included in the text and seamlessly provides virtual objects within a mixed reality environment for the reader to interact with while reading. A code module is associated with each printed code and the AR glasses match the printed code to the code module and execute the code module. The code module is often highly contextualized to text or an image included in a written material (e.g., on the page of a book). The code module provides virtual objects and a mixed reality interaction for the reader of the written material. For example, if a reader is reading a textbook on gases, a code module may provide virtual gas molecules where the user can interact with the supersized gas molecules to understand the relationship between volume and pressure.

(20) AR glasses, though, have a limited battery life compared with the time that many people spend reading materials such as books. For example, often the battery life of AR glasses with displays and being actively used is 30 minutes or less. Additionally, readers often find that it is burdensome to turn AR glasses on and off many times while reading.

(21) Accordingly, there is a technical problem of how to provide a mixed reality experience to a reader of printed material that includes printed codes with AR glasses that have limited battery life. Examples address this technical problem by providing a reading mode for the AR glasses that causes the AR glasses go to sleep, or portions of the AR glasses to go to sleep, and wake up at intervals to capture images of subsequent sections of a written material (e.g., pages of the book). The AR glasses then identify any printed codes in each section of the written material and execute associated code modules. The AR glasses may adjust a sleep time to learn the reading habits of the reader. By putting displays and other components of the AR glasses to sleep and waking them up to scan for codes, the battery life of the AR glasses may be extended to last for several hours or more, which is typically long enough for an average user when reading. As a result, the functioning of the AR glasses is greatly improved. Moreover, the AR glasses limit other features of the AR glasses during the reading mode in order to reduce energy consumption.

(22) Additionally, the code modules may require a lot of energy to download to the AR glasses from a backend server. The communication hardware and software of the AR glasses consume a great deal of energy. Examples address this technical problem by managing the downloading of the code modules. In some examples, the code modules for an entire written material are downloaded to the AR glasses at once when the AR glasses have a good signal with a host or backend and then the communication hardware of the AR glasses are put into a sleep mode to conserve energy. In some examples, the AR glasses download the code modules for an entire written material so that the AR glasses do not have to connect with another device while the a users is reading the written material. In some examples, the AR glasses use low-energy communication protocols to download the code modules to conserve energy. In some examples, the communications hardware is kept in a

sleep mode and awakened to download code modules when needed.

(23) Networked Computing Environment

(24) FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple instances of a client device **102**, each of which hosts a number of applications, including a messaging client **104** and other applications **106**. Each messaging client **104** is communicatively coupled to other instances of the messaging client **104** (e.g., hosted on respective other client devices **102**), a messaging server system **108** and third-party servers **110** via a network **112** (e.g., the Internet). A messaging client **104** can also communicate with locally-hosted applications **106** using Applications Program Interfaces (APIs).

(25) A messaging client **104** is able to communicate and exchange data with other messaging clients **104** and with the messaging server system **108** via the network **112**. The data exchanged between messaging clients **104**, and between a messaging client **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(26) The messaging server system **108** provides server-side functionality via the network **112** to a particular messaging client **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client **104** or by the messaging server system **108**, the location of certain functionality either within the messaging client **104** or the messaging server system **108** may be a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108** but to later migrate this technology and functionality to the messaging client **104** where a client device **102** has sufficient processing capacity.

(27) The messaging server system **108** supports various services and operations that are provided to the messaging client **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client **104**. This data may include message content, client device information, geolocation information, media augmentation and overlays, message content persistence conditions, social network information, and live event information, as examples. Data exchanges within the messaging system **100** are invoked and controlled through functions available via user interfaces (UIs) of the messaging client **104**.

(28) Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **116** is coupled to, and provides a programmatic interface to, application servers **114**. The application servers **114** are communicatively coupled to a database server **120**, which facilitates access to a database **126** that stores data associated with messages processed by the application servers **114**. Similarly, a web server **128** is coupled to the application servers **114**, and provides web-based interfaces to the application servers **114**. To this end, the web server **128** processes incoming network requests over the Hypertext Transfer Protocol (HTTP) and several other related protocols.

(29) The Application Program Interface (API) server **116** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application servers **114**. Specifically, the Application Program Interface (API) server **116** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client **104** in order to invoke functionality of the application servers **114**. The Application Program Interface (API) server **116** exposes various functions supported by the application servers **114**, including account registration, login functionality, the sending of messages, via the application servers **114**, from a particular messaging client **104** to another messaging client **104**, the sending of media files (e.g., images or video) from a messaging client **104** to a messaging server **118**, and for possible access by another messaging client **104**, the settings of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the addition and deletion of entities (e.g., friends) to an entity graph (e.g., a social

graph), the location of friends within a social graph, and opening an application event (e.g., relating to the messaging client **104**).

(30) The application servers **114** host a number of server applications and subsystems, including for example a messaging server **118**, an image processing server **122**, and a social network server **124**. The messaging server **118** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available to the messaging client **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server **118**, in view of the hardware requirements for such processing.

(31) The application servers **114** also include an image processing server **122** that is dedicated to performing various image processing operations, typically with respect to images or video within the payload of a message sent from or received at the messaging server **118**.

(32) The social network server **124** supports various social networking functions and services and makes these functions and services available to the messaging server **118**. To this end, the social network server **124** maintains and accesses an entity graph **308** (as shown in FIG. 3) within the database **126**. Examples of functions and services supported by the social network server **124** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following,” and also the identification of other entities and interests of a particular user.

(33) Returning to the messaging client **104**, features and functions of an external resource (e.g., an application **106** or applet) are made available to a user via an interface of the messaging client **104**. In this context, “external” refers to the fact that the application **106** or applet is external to the messaging client **104**. The external resource is often provided by a third party but may also be provided by the creator or provider of the messaging client **104**. The messaging client **104** receives a user selection of an option to launch or access features of such an external resource. The external resource may be the application **106** installed on the client device **102** (e.g., a “native app”), or a small-scale version of the application (e.g., an “applet”) that is hosted on the client device **102** or remote of the client device **102** (e.g., on third-party servers **110**). The small-scale version of the application includes a subset of features and functions of the application (e.g., the full-scale, native version of the application) and is implemented using a markup-language document. In one example, the small-scale version of the application (e.g., an “applet”) is a web-based, markup-language version of the application and is embedded in the messaging client **104**. In addition to using markup-language documents (e.g., a *.ml file), an applet may incorporate a scripting language (e.g., a *.js file or a .json file) and a style sheet (e.g., a *.ss file).

(34) In response to receiving a user selection of the option to launch or access features of the external resource, the messaging client **104** determines whether the selected external resource is a web-based external resource or a locally-installed application **106**. In some cases, applications **106** that are locally installed on the client device **102** can be launched independently of and separately from the messaging client **104**, such as by selecting an icon, corresponding to the application **106**, on a home screen of the client device **102**. Small-scale versions of such applications can be launched or accessed via the messaging client **104** and, in some examples, no or limited portions of the small-scale application can be accessed outside of the messaging client **104**. The small-scale application can be launched by the messaging client **104** receiving, from a third-party server **110** for example, a markup-language document associated with the small-scale application and processing such a document.

(35) In response to determining that the external resource is a locally-installed application **106**, the messaging client **104** instructs the client device **102** to launch the external resource by executing

locally-stored code corresponding to the external resource. In response to determining that the external resource is a web-based resource, the messaging client **104** communicates with the third-party servers **110** (for example) to obtain a markup-language document corresponding to the selected external resource. The messaging client **104** then processes the obtained markup-language document to present the web-based external resource within a user interface of the messaging client **104**.

(36) The messaging client **104** can notify a user of the client device **102**, or other users related to such a user (e.g., “friends”), of activity taking place in one or more external resources. For example, the messaging client **104** can provide participants in a conversation (e.g., a chat session) in the messaging client **104** with notifications relating to the current or recent use of an external resource by one or more members of a group of users. One or more users can be invited to join in an active external resource or to launch a recently-used but currently inactive (in the group of friends) external resource. The external resource can provide participants in a conversation, each using respective messaging clients **104**, with the ability to share an item, status, state, or location in an external resource with one or more members of a group of users into a chat session. The shared item may be an interactive chat card with which members of the chat can interact, for example, to launch the corresponding external resource, view specific information within the external resource, or take the member of the chat to a specific location or state within the external resource. Within a given external resource, response messages can be sent to users on the messaging client **104**. The external resource can selectively include different media items in the responses, based on a current context of the external resource.

(37) The messaging client **104** can present a list of the available external resources (e.g., applications **106** or applets) to a user to launch or access a given external resource. This list can be presented in a context-sensitive menu. For example, the icons representing different ones of the application **106** (or applets) can vary based on how the menu is launched by the user (e.g., from a conversation interface or from a non-conversation interface).

(38) System Architecture

(39) FIG. 2 is a block diagram illustrating further details regarding the messaging system **100**, according to some examples. Specifically, the messaging system **100** is shown to comprise the messaging client **104** and the application servers **114**. The messaging system **100** embodies a number of subsystems, which are supported on the client-side by the messaging client **104** and on the server-side by the application servers **114**. These subsystems include, for example, an ephemeral timer system **202**, a collection management system **204**, an augmentation system **208**, a map system **210**, a game system **212**, an external resource system **214**, and an enhanced reading system **216**.

(40) The ephemeral timer system **202** is responsible for enforcing the temporary or time-limited access to content by the messaging client **104** and the messaging server **118**. The ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, or collection of messages (e.g., a story), selectively enable access (e.g., for presentation and display) to messages and associated content via the messaging client **104**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

(41) The collection management system **204** is responsible for managing sets or collections of media (e.g., collections of text, image video, and audio data). A collection of content (e.g., messages, including images, video, text, and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **204** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client **104**.

(42) The collection management system **204** furthermore includes a curation interface **206** that

allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **206** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **204** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain examples, compensation may be paid to a user for the inclusion of user-generated content into a collection. In such cases, the collection management system **204** operates to automatically make payments to such users for the use of their content.

(43) The augmentation system **208** provides various functions that enable a user to augment (e.g., annotate or otherwise modify or edit) media content associated with a message. For example, the augmentation system **208** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The augmentation system **208** operatively supplies a media overlay or augmentation (e.g., an image filter) to the messaging client **104** based on a geolocation of the client device **102**. In another example, the augmentation system **208** operatively supplies a media overlay to the messaging client **104** based on other information, such as social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo, a digital object) at the client device **102**. For example, the media overlay may include text or image that can be overlaid on top of a photograph taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the augmentation system **208** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **126** and accessed through the database server **120**.

(44) In some examples, the augmentation system **208** provides a user-based publication platform that enables users to select a geolocation on a map and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The augmentation system **208** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(45) In other examples, the augmentation system **208** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the augmentation system **208** associates the media overlay of the highest bidding merchant with a corresponding geolocation for a predefined amount of time.

(46) The map system **210** provides various geographic location functions and supports the presentation of map-based media content and messages by the messaging client **104**. For example, the map system **210** enables the display of user icons or avatars (e.g., stored in profile data **316**) on a map to indicate a current or past location of “friends” of a user, as well as media content (e.g., collections of messages including photographs and videos) generated by such friends, within the context of a map. For example, a message posted by a user to the messaging system **100** from a specific geographic location may be displayed within the context of a map at that particular location to “friends” of a specific user on a map interface of the messaging client **104**. A user can furthermore share his or her location and status information (e.g., using an appropriate status avatar) with other users of the messaging system **100** via the messaging client **104**, with this location and status information being similarly displayed within the context of a map interface of the messaging client **104** to selected users.

(47) The game system **212** provides various gaming functions within the context of the messaging client **104**. The messaging client **104** provides a game interface providing a list of available games

that can be launched by a user within the context of the messaging client **104** and played with other users of the messaging system **100**. The messaging system **100** further enables a particular user to invite other users to participate in the play of a specific game, by issuing invitations to such other users from the messaging client **104**. The messaging client **104** also supports both voice and text messaging (e.g., chats) within the context of gameplay, provides a leaderboard for the games, and also supports the provision of in-game rewards (e.g., coins and items).

(48) The external resource system **214** provides an interface for the messaging client **104** to communicate with remote servers (e.g., third-party servers **110**) to launch or access external resources, e.g., applications or applets. Each third-party server **110** hosts, for example, a markup language (e.g., HTML5) based application or small-scale version of an application (e.g., game, utility, payment, or ride-sharing application). The messaging client **104** may launch a web-based resource (e.g., application) by accessing the HTML5 file from the third-party servers **110** associated with the web-based resource. In certain examples, applications hosted by third-party servers **110** are programmed in JavaScript leveraging a Software Development Kit (SDK) provided by the messaging server **118**. The SDK includes Application Programming Interfaces (APIs) with functions that can be called or invoked by the web-based application. In certain examples, the messaging server **118** includes a JavaScript library that provides a given external resource access to certain user data of the messaging client **104**. HTML5 is used as an example technology for programming games, but applications and resources programmed based on other technologies can be used.

(49) In order to integrate the functions of the SDK into the web-based resource, the SDK is downloaded by a third-party server **110** from the messaging server **118** or is otherwise received by the third-party server **110**. Once downloaded or received, the SDK is included as part of the application code of a web-based external resource. The code of the web-based resource can then call or invoke certain functions of the SDK to integrate features of the messaging client **104** into the web-based resource.

(50) The SDK stored on the messaging server **118** effectively provides the bridge between an external resource (e.g., applications **106** or applets and the messaging client **104**. This provides the user with a seamless experience of communicating with other users on the messaging client **104**, while also preserving the look and feel of the messaging client **104**. To bridge communications between an external resource and a messaging client **104**, in certain examples, the SDK facilitates communication between third-party servers **110** and the messaging client **104**. In certain examples, a Web ViewJavaScriptBridge running on a client device **102** establishes two one-way communication channels between an external resource and the messaging client **104**. Messages are sent between the external resource and the messaging client **104** via these communication channels asynchronously. Each SDK function invocation is sent as a message and callback. Each SDK function is implemented by constructing a unique callback identifier and sending a message with that callback identifier.

(51) By using the SDK, not all information from the messaging client **104** is shared with third-party servers **110**. The SDK limits which information is shared based on the needs of the external resource. In certain examples, each third-party server **110** provides an HTML5 file corresponding to the web-based external resource to the messaging server **118**. The messaging server **118** can add a visual representation (such as a box art or other graphic) of the web-based external resource in the messaging client **104**. Once the user selects the visual representation or instructs the messaging client **104** through a GUI of the messaging client **104** to access features of the web-based external resource, the messaging client **104** obtains the HTML5 file and instantiates the resources necessary to access the features of the web-based external resource.

(52) The messaging client **104** presents a graphical user interface (e.g., a landing page or title screen) for an external resource. During, before, or after presenting the landing section of reading materials such as a page or title screen, the messaging client **104** determines whether the launched

external resource has been previously authorized to access user data of the messaging client **104**. In response to determining that the launched external resource has been previously authorized to access user data of the messaging client **104**, the messaging client **104** presents another graphical user interface of the external resource that includes functions and features of the external resource. In response to determining that the launched external resource has not been previously authorized to access user data of the messaging client **104**, after a threshold period of time (e.g., 3 seconds) of displaying the landing page or title screen of the external resource, the messaging client **104** slides up (e.g., animates a menu as surfacing from a bottom of the screen to a middle of or other portion of the screen) a menu for authorizing the external resource to access the user data. The menu identifies the type of user data that the external resource will be authorized to use. In response to receiving a user selection of an accept option, the messaging client **104** adds the external resource to a list of authorized external resources and allows the external resource to access user data from the messaging client **104**. In some examples, the external resource is authorized by the messaging client **104** to access the user data in accordance with an OAuth 2 framework.

(53) The messaging client **104** controls the type of user data that is shared with external resources based on the type of external resource being authorized. For example, external resources that include full-scale applications (e.g., an application **106**) are provided with access to a first type of user data (e.g., only two-dimensional avatars of users with or without different avatar characteristics). As another example, external resources that include small-scale versions of applications (e.g., web-based versions of applications) are provided with access to a second type of user data (e.g., payment information, two-dimensional avatars of users, three-dimensional avatars of users, and avatars with various avatar characteristics). Avatar characteristics include different ways to customize a look and feel of an avatar, such as different poses, facial features, clothing, and so forth.

(54) The enhanced reading system **216** provides functions and routines for providing enhanced augmented reality book reading. The enhanced reading system **216** provides the functions and routines as described herein and in FIG. 6. The enhanced reading system **216** captures images of sections of reading material, e.g., pages of a book, as it is being read and detects quick response codes or codes in the book that correspond to code modules that provide a mixed reality experience for the sections of reading material, e.g., page of the book. The enhanced reading system **216** retrieves the code modules and executes the code modules. The enhanced reading system **216** provides power-saving features such as going into a sleep mode and waking up to execute the code modules. The enhanced reading system **216** may retrieve all the code modules for a book prior to reading and then cause the communications hardware and software to go into a sleep mode to save power.

(55) Data Architecture

(56) FIG. 3 is a schematic diagram illustrating data structures **300**, which may be stored in the database **126** of the messaging server system **108**, according to certain examples. While the content of the database **126** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

(57) The database **126** includes message data stored within a message table **302**. This message data includes, for any particular one message, at least message sender data, message recipient (or receiver) data, and a payload. Further details regarding information that may be included in a message, and included within the message data stored in the message table **302** is described below with reference to FIG. 4.

(58) An entity table **306** stores entity data, and is linked (e.g., referentially) to an entity graph **308** and profile data **316**. Entities for which records are maintained within the entity table **306** may include individuals, corporate entities, organizations, objects, places, events, and so forth. Regardless of entity type, any entity regarding which the messaging server system **108** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity

type identifier (not shown).

(59) The entity graph **308** stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

(60) The profile data **316** stores multiple types of profile data about a particular entity. The profile data **316** may be selectively used and presented to other users of the messaging system **100**, based on privacy settings specified by a particular entity. Where the entity is an individual, the profile data **316** includes, for example, a user name, telephone number, address, settings (e.g., notification and privacy settings), as well as a user-selected avatar representation (or collection of such avatar representations). A particular user may then selectively include one or more of these avatar representations within the content of messages communicated via the messaging system **100**, and on map interfaces displayed by messaging clients **104** to other users. The collection of avatar representations may include “status avatars,” which present a graphical representation of a status or activity that the user may select to communicate at a particular time.

(61) Where the entity is a group, the profile data **316** for the group may similarly include one or more avatar representations associated with the group, in addition to the group name, members, and various settings (e.g., notifications) for the relevant group.

(62) The database **126** also stores augmentation data, such as overlays or filters, in an augmentation table **310**. The augmentation data is associated with and applied to videos (for which data is stored in a video table **304**) and images (for which data is stored in an image table **312**).

(63) Filters, in one example, are overlays that are displayed as overlaid on an image or video during presentation to a recipient user. Filters may be of various types, including user-selected filters from a set of filters presented to a sending user by the messaging client **104** when the sending user is composing a message. Other types of filters include geolocation filters (also known as geo-filters), which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the messaging client **104**, based on geolocation information determined by a Global Positioning System (GPS) unit of the client device **102**.

(64) Another type of filter is a data filter, which may be selectively presented to a sending user by the messaging client **104**, based on other inputs or information gathered by the client device **102** during the message creation process. Examples of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device **102**, or the current time.

(65) Other augmentation data that may be stored within the image table **312** includes augmented reality content items (e.g., corresponding to applying Lenses or augmented reality experiences). An augmented reality content item may be a real-time special effect and sound that may be added to an image or a video.

(66) As described above, augmentation data includes augmented reality content items, overlays, image transformations, AR images, and similar terms refer to modifications that may be applied to image data (e.g., videos or images). This includes real-time modifications, which modify an image as it is captured using device sensors (e.g., one or multiple cameras) of a client device **102** and then displayed on a screen of the client device **102** with the modifications. This also includes modifications to stored content, such as video clips in a gallery that may be modified. For example, in a client device **102** with access to multiple augmented reality content items, a user can use a single video clip with multiple augmented reality content items to see how the different augmented reality content items will modify the stored clip. For example, multiple augmented reality content items that apply different pseudorandom movement models can be applied to the same content by selecting different augmented reality content items for the content. Similarly, real-time video capture may be used with an illustrated modification to show how video images currently being captured by sensors of a client device **102** would modify the captured data. Such data may simply

be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the modifications (or both). In some systems, a preview feature can show how different augmented reality content items will look within different windows in a display at the same time. This can, for example, enable multiple windows with different pseudorandom animations to be viewed on a display at the same time.

(67) Data and various systems using augmented reality content items or other such transform systems to modify content using this data can thus involve detection of objects (e.g., faces, hands, bodies, cats, dogs, surfaces, objects, etc.), tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various examples, different methods for achieving such transformations may be used. Some examples may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other examples, tracking of points on an object may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further examples, neural network analysis of video frames may be used to place images, models, or textures in content (e.g., images or frames of video). Augmented reality content items thus refer both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

(68) Real-time video processing can be performed with any kind of video data (e.g., video streams, video files, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using a computer animation model, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

(69) In some examples, when a particular modification is selected along with content to be transformed, elements to be transformed are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream. Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of object's elements characteristic points for each element of an object are calculated (e.g., using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh is used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A first set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method, a background of the modified object can be changed or distorted as well by tracking and modifying the background.

(70) In some examples, transformations changing some areas of an object using its elements can be performed by calculating characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus transforming the frames of the video stream. Depending on the specific request for modification properties of the mentioned areas can be transformed in different ways. Such modifications may involve changing color of areas;

removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various examples, any combination of such modifications or other similar modifications may be used. For certain models to be animated, some characteristic points can be selected as control points to be used in determining the entire state-space of options for the model animation.

(71) In some examples of a computer animation model to transform image data using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g., Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

(72) Other methods and algorithms suitable for face detection can be used. For example, in some examples, features are located using a landmark, which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left eye pupil may be used. If an initial landmark is not identifiable (e.g., if a person has an eyepatch), secondary landmarks may be used. Such landmark identification procedures may be used for any such objects. In some examples, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

(73) In some examples, a search for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector is started. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable, and the shape model pools the results of the weak template matches to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

(74) A transformation system can capture an image or video stream on a client device (e.g., the client device **102**) and perform complex image manipulations locally on the client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on the client device **102**.

(75) In some examples, a computer animation model to transform image data can be used by a system where a user may capture an image or video stream of the user (e.g., a selfie) using a client device **102** having a neural network operating as part of a messaging client **104** operating on the client device **102**. The transformation system operating within the messaging client **104** determines the presence of a face within the image or video stream and provides modification icons associated with a computer animation model to transform image data, or the computer animation model can be present as associated with an interface described herein. The modification icons include changes that may be the basis for modifying the user's face within the image or video stream as part of the modification operation. Once a modification icon is selected, the transform system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). A modified image or video stream may be presented in a graphical user interface displayed on the client device **102** as soon as the image or video stream is captured, and a specified modification is selected. The transformation system may implement a complex convolutional neural network on a portion of the image or video stream to generate and apply the selected modification. That is, the user may capture the image or video stream and be presented

with a modified result in real-time or near real-time once a modification icon has been selected. Further, the modification may be persistent while the video stream is being captured, and the selected modification icon remains toggled. Machine taught neural networks may be used to enable such modifications.

(76) The graphical user interface, presenting the modification performed by the transform system, may supply the user with additional interaction options. Such options may be based on the interface used to initiate the content capture and selection of a particular computer animation model (e.g., initiation from a content creator user interface). In various examples, a modification may be persistent after an initial selection of a modification icon. The user may toggle the modification on or off by tapping or otherwise selecting the face being modified by the transformation system and store it for later viewing or browse to other areas of the imaging application. Where multiple faces are modified by the transformation system, the user may toggle the modification on or off globally by tapping or selecting a single face modified and displayed within a graphical user interface. In some examples, individual faces, among a group of multiple faces, may be individually modified, or such modifications may be individually toggled by tapping or selecting the individual face or a series of individual faces displayed within the graphical user interface.

(77) A story table **314** stores data regarding collections of messages and associated image, video, or audio data, which are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **306**). A user may create a “personal story” in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the messaging client **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

(78) A collection may also constitute a “live story,” which is a collection of content from multiple users that is created manually, automatically, or using a combination of manual and automatic techniques. For example, a “live story” may constitute a curated stream of user-submitted content from various locations and events. Users whose client devices have location services enabled and are at a common location event at a particular time may, for example, be presented with an option, via a user interface of the messaging client **104**, to contribute content to a particular live story. The live story may be identified to the user by the messaging client **104**, based on his or her location. The end result is a “live story” told from a community perspective.

(79) A further type of content collection is known as a “location story,” which enables a user whose client device **102** is located within a specific geographic location (e.g., on a college or university campus) to contribute to a particular collection. In some examples, a contribution to a location story may require a second degree of authentication to verify that the end-user belongs to a specific organization or other entity (e.g., is a student on the university campus).

(80) As mentioned above, the video table **304** stores video data that, in one example, is associated with messages for which records are maintained within the message table **302**. Similarly, the image table **312** stores image data associated with messages for which message data is stored in the entity table **306**. The entity table **306** may associate various augmentations from the augmentation table **310** with various images and videos stored in the image table **312** and the video table **304**.

(81) Data Communications Architecture

(82) FIG. 4 is a schematic diagram illustrating a structure of a message **400**, according to some examples, generated by a messaging client **104** for communication to a further messaging client **104** or the messaging server **118**. The content of a particular message **400** is used to populate the message table **302** stored within the database **126**, accessible by the messaging server **118**. Similarly, the content of a message **400** is stored in memory as “in-transit” or “in-flight” data of the client device **102** or the application servers **114**. A message **400** is shown to include the following example components: message identifier **402**: a unique identifier that identifies the message **400**. message text payload **404**: text, to be generated by a user via a user interface of the client device

102, and that is included in the message **400**. message image payload **406**: image data, captured by a camera component of a client device **102** or retrieved from a memory component of a client device **102**, and that is included in the message **400**. Image data for a sent or received message **400** may be stored in the image table **312**. message video payload **408**: video data, captured by a camera component or retrieved from a memory component of the client device **102**, and that is included in the message **400**. Video data for a sent or received message **400** may be stored in the video table **304**. message audio payload **410**: audio data, captured by a microphone or retrieved from a memory component of the client device **102**, and that is included in the message **400**. message augmentation data **412**: augmentation data (e.g., filters, stickers, or other annotations or enhancements) that represents augmentations to be applied to message image payload **406**, message video payload **408**, or message audio payload **410** of the message **400**. Augmentation data for a sent or received message **400** may be stored in the augmentation table **310**. message duration parameter **414**: parameter value indicating, in seconds, the amount of time for which content of the message (e.g., the message image payload **406**, message video payload **408**, message audio payload **410**) is to be presented or made accessible to a user via the messaging client **104**. message geolocation parameter **416**: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter **416** values may be included in the payload, each of these parameter values being associated with respect to content items included in the content (e.g., a specific image into within the message image payload **406**, or a specific video in the message video payload **408**). message story identifier **418**: identifier values identifying one or more content collections (e.g., “stories” identified in the story table **314**) with which a particular content item in the message image payload **406** of the message **400** is associated. For example, multiple images within the message image payload **406** may each be associated with multiple content collections using identifier values. message tag **420**: each message **400** may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload **406** depicts an animal (e.g., a lion), a tag value may be included within the message tag **420** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition. message sender identifier **422**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the Client device **102** on which the message **400** was generated and from which the message **400** was sent. message receiver identifier **424**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** to which the message **400** is addressed.

(83) The contents (e.g., values) of the various components of message **400** may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload **406** may be a pointer to (or address of) a location within an image table **312**. Similarly, values within the message video payload **408** may point to data stored within a video table **304**, values stored within the message augmentations **412** may point to data stored in an augmentation table **310**, values stored within the message story identifier **418** may point to data stored in a story table **314**, and values stored within the message sender identifier **422** and the message receiver identifier **424** may point to user records stored within an entity table **306**.

(84) Time-Based Access Limitation Architecture

(85) FIG. 5 is a schematic diagram illustrating an access-limiting process **500**, in terms of which access to content (e.g., an ephemeral message **502**, and associated multimedia payload of data) or a content collection (e.g., an ephemeral message group **504**) may be time-limited (e.g., made ephemeral).

(86) An ephemeral message **502** is shown to be associated with a message duration parameter **506**, the value of which determines an amount of time that the ephemeral message **502** will be displayed to a receiving user of the ephemeral message **502** by the messaging client **104**. In one example, an

ephemeral message **502** is viewable by a receiving user for up to a maximum of 10 seconds, depending on the amount of time that the sending user specifies using the message duration parameter **506**.

(87) The message duration parameter **506** and the message receiver identifier **424** are shown to be inputs to a message timer **510**, which is responsible for determining the amount of time that the ephemeral message **502** is shown to a particular receiving user identified by the message receiver identifier **424**. In particular, the ephemeral message **502** will only be shown to the relevant receiving user for a time period determined by the value of the message duration parameter **506**. The message timer **510** is shown to provide output to a more generalized ephemeral timer system **202**, which is responsible for the overall timing of display of content (e.g., an ephemeral message **502**) to a receiving user.

(88) The ephemeral message **502** is shown in FIG. 5 to be included within an ephemeral message group **504** (e.g., a collection of messages in a personal story, or an event story). The ephemeral message group **504** has an associated group duration parameter **508**, a value of which determines a time duration for which the ephemeral message group **504** is presented and accessible to users of the messaging system **100**. The group duration parameter **508**, for example, may be the duration of a music concert, where the ephemeral message group **504** is a collection of content pertaining to that concert. Alternatively, a user (either the owning user or a curator user) may specify the value for the group duration parameter **508** when performing the setup and creation of the ephemeral message group **504**.

(89) Additionally, each ephemeral message **502** within the ephemeral message group **504** has an associated group participation parameter **512**, a value of which determines the duration of time for which the ephemeral message **502** will be accessible within the context of the ephemeral message group **504**. Accordingly, a particular ephemeral message group **504** may “expire” and become inaccessible within the context of the ephemeral message group **504**, prior to the ephemeral message group **504** itself expiring in terms of the group duration parameter **508**. The group duration parameter **508**, group participation parameter **512**, and message receiver identifier **424** each provide input to a group timer **514**, which operationally determines, firstly, whether a particular ephemeral message **502** of the ephemeral message group **504** will be displayed to a particular receiving user and, if so, for how long. Note that the ephemeral message group **504** is also aware of the identity of the particular receiving user as a result of the message receiver identifier **424**.

(90) Accordingly, the group timer **514** operationally controls the overall lifespan of an associated ephemeral message group **504**, as well as an individual ephemeral message **502** included in the ephemeral message group **504**. In one example, each and every ephemeral message **502** within the ephemeral message group **504** remains viewable and accessible for a time period specified by the group duration parameter **508**. In a further example, a certain ephemeral message **502** may expire, within the context of ephemeral message group **504**, based on a group participation parameter **512**. Note that a message duration parameter **506** may still determine the duration of time for which a particular ephemeral message **502** is displayed to a receiving user, even within the context of the ephemeral message group **504**. Accordingly, the message duration parameter **506** determines the duration of time that a particular ephemeral message **502** is displayed to a receiving user, regardless of whether the receiving user is viewing that ephemeral message **502** inside or outside the context of an ephemeral message group **504**.

(91) The ephemeral timer system **202** may furthermore operationally remove a particular ephemeral message **502** from the ephemeral message group **504** based on a determination that it has exceeded an associated group participation parameter **512**. For example, when a sending user has established a group participation parameter **512** of 24 hours from posting, the ephemeral timer system **202** will remove the relevant ephemeral message **502** from the ephemeral message group **504** after the specified 24 hours. The ephemeral timer system **202** also operates to remove an

ephemeral message group **504** when either the group participation parameter **512** for each and every ephemeral message **502** within the ephemeral message group **504** has expired, or when the ephemeral message group **504** itself has expired in terms of the group duration parameter **508**.

(92) In certain use cases, a creator of a particular ephemeral message group **504** may specify an indefinite group duration parameter **508**. In this case, the expiration of the group participation parameter **512** for the last remaining ephemeral message **502** within the ephemeral message group **504** will determine when the ephemeral message group **504** itself expires. In this case, a new ephemeral message **502**, added to the ephemeral message group **504**, with a new group participation parameter **512**, effectively extends the life of an ephemeral message group **504** to equal the value of the group participation parameter **512**.

(93) Responsive to the ephemeral timer system **202** determining that an ephemeral message group **504** has expired (e.g., is no longer accessible), the ephemeral timer system **202** communicates with the messaging system **100** (and, for example, specifically the messaging client **104**) to cause an indicium (e.g., an icon) associated with the relevant ephemeral message group **504** to no longer be displayed within a user interface of the messaging client **104**. Similarly, when the ephemeral timer system **202** determines that the message duration parameter **506** for a particular ephemeral message **502** has expired, the ephemeral timer system **202** causes the messaging client **104** to no longer display an indicium (e.g., an icon or textual identification) associated with the ephemeral message **502**.

(94) Enhanced Book Reading with Ar Glasses

(95) FIG. **6** illustrates a system **600** for enhanced book reading with AR glasses, in accordance with some examples. The system **600** includes wearable electronic device **602** and a backend **604**. The wearable electronic device **602** may be the glasses **1100**. The VR module **621** of the wearable electronic device **602** provides a mixed reality or augmented reality experience for the user. For example, images may be projected on the lenses or display **620** of the glasses **1100**. Additionally, the camera **612**, for example cameras **1169** of FIG. **11**, captures images of the real environment and the VR module **621** uses this information to provide a VR interactive environment. For example, the hands of the person using the wearable electronic device **602** are projected on the display **620** and the person may interact with the virtual images presented on the display **620**. The display **620** includes display hardware and software and/or firmware to control the display. The display **620** is transparent so the user can see both the images presented on the display as well as the real world objects that are visible through the display.

(96) The module executor **624** runs or executes modules such as the books module **606** on the wearable electronic device **602**. The module presenter **626** is a module that presents other modules for execution by the module executor **624**. The communications **622** is wireless communications hardware and software for communicating with the backend **604**. For example, the communications **622** includes an antenna and software or hardware to implement communication protocols such as IEEE 802.11 or Blue Tooth®. The communications **622** may include processing circuitry that is configured to implement one or more communication protocols and control transceiver circuitry that is coupled to the processing circuitry and an antenna.

(97) The reading module **606** adds enhancements for reading physical books. The reading module **606** includes or may call code detection module **608**, camera module **614**, display module **616**, navigation module **618**, and code module fetcher **610**. The code detection module **608** takes an image and determines whether there is a depiction of a code **613** such as code **902**, **1002**, and **1004** within the image **611** or whether the image **611** contains a code **613**, which may be termed a printed code, QR code, Snapcode®, or another name. The camera module **614** controls or causes the camera **612** to capture an image and make it available for other modules. The camera **612** is camera hardware and software or firmware to control the camera **612**. The display module **616** displays or causes to be displayed text and images for a user of the wearable electronic device **602**. The navigation module **618** manages the execution of code modules **630**, which may reside on the

wearable electronic device **602** and/or the backend **604**. The code modules **630** correspond to codes **613** that the code detection module **608** detects. The code to code module map **609** provides a mapping from codes to code module **630**. The code modules **630** include a recommended sleep time or duration between sections of reading material, e.g., pages, in accordance with some embodiments. The reading module **606** causes the camera module **614** to capture an image **611**. The reading module **606** causes the code detection module **608** to determine if there are codes **613** in the image **611**. If there are codes **613** in the image **611**, then the reading module **606** determines which code module **630** to cause the module executor **624** to execute in response to the code **613** being present in the image **611**. In some examples, the reading module **606** decodes the code **613** and sends the information encoded in the code **613** to the backend **604**. The backend **604** determines which code module **630** should be executed based on the information encoded in the code **613**. In some examples, the code **613** indicates an entire reading material, such as an entire book, which corresponds to a number of code modules **630**. In some examples, the reading module **606** refrains from turning on display hardware unless the code **613** is identified or a physical user interface item **629** is selected. The camera **612**, display **620**, and communications **622** have a low-energy consumption mode where either a portion of the circuitry has power lowered or turned off or the entire circuitry has its power lowered or turned off. In some examples, camera **612**, display **620**, and communications **622** each include at least two different circuits where one circuit has power keep to the circuit for turning on and off the remaining circuitry. The camera **612**, display **620**, and communications **622** can be placed in a low power or lower power mode by turning off the circuitry except for the low power circuit. The low power mode puts the hardware in a low energy consumption mode.

(98) In some examples, the code modules **630** provide a mixed reality experience where an initial location of virtual reality objects is related to the objects depicted on the section of the reading material, such as a page of the book, in the image **611**. For example, referring to FIG. 9, the code module **630** corresponding to code **902** initially depicts a virtual reality dragon in the location of the dragon **906** where the VR or AR dragon then flies off the page of the book. The code module **630** may access the camera module **614** to provide a live image of the section of the reading material, e.g., a page of a book, which is augmented with VR objects and interactive UI elements or items. In other embodiments, the code module **630** presents AR objects and interactive UI elements or items so that the user sees them on a screen as well as seeing the real world objects through the screen. In some embodiments, the AR objects and interactive UI elements or items are projected on the eye of the user.

(99) In response to detecting that the code **613** corresponds to a piece of reading material, e.g., a book, the code module fetcher **610** checks if the code modules **630** associated with the code are preloaded at to the wearable electronic device **602**. If so, the code module fetcher **610** may access the code modules **630** locally from the wearable electronic device **602**. Alternatively, if the code modules **630** are not preloaded, the code module fetcher **610** may make a request for the code modules **630** from the backend **604**. In some examples, the code module fetcher **610** requests some or all of the code modules **630** for a piece of reading material, e.g., a book, when the code module fetcher **610** determines that a particular book is being read, which may be inferred from the image **611** comprising a code **613** that indicates the a piece of reading material, e.g., book. In some examples, the code module fetcher **610** waits to load a code module **630** from the backend **604** until the code **613** corresponding to the code module **630** has been detected in the image **611**. The code module fetcher **610** may cache code modules **630** at the wearable electronic device **602** based on knowing which piece of reading material, e.g., book, is being read. For example, the code module fetcher **610** may request the next several code modules **630** after a code module **630** corresponding to a code **613** that has been detected.

(100) The module executor **624** takes the selected code module **630** and executes it. The navigation module **618** may be executed with the code module **630** to manage the code module **630** exiting

and returning back to the reading module **606**. The code module **630** provides a mixed reality experience for the reader of a piece of reading material, e.g., book. The a piece of reading material, e.g., book, may be a physical such as paper or may be a reading material that is being electronically read. The mixed reality experience includes six degrees of freedom in accordance with some examples. The mixed reality experience includes interactive objects such as user interface objects. The user may terminate the code module **630** or the code module **630** may timeout. The navigation module **618** determines when there is a timeout and returns control to the reading module **606** when there is a timeout.

(101) User data **627** is collected for how the user is reading the reading material, e.g., book. Some of the data that may be collected is how often a section of reading material is changed, e.g., a page is turned for a book, whether the user interacted with a code module **630**, how often the user reads, and so forth. The user data **627** is stored collectively to protect privacy, in accordance with some examples. The user data **627** is encrypted to protect privacy, in accordance with some examples.

(102) The reading module **606** detects when the reading material, e.g., book, is no longer being read based on the images **611**. For example, the images **611** may no longer include the reading material, e.g., book, which may be used to infer that the reading material, e.g., book, is no longer being read. The image **611** may be of a different piece of reading material, e.g., a different book, in which case the reading module **606** may determine to exit or to scan the image **611** for codes **613**. The reading module **606** may be executed or selected by the user.

(103) The user interface item **629** is a means for the user of the wearable electronic device **602** to interact with the wearable electronic device **602**. In some examples, the user interface item **629** is an external button.

(104) Reading mode, e.g., a book rading mode, can be selected from a module carousel **1214** and causes the remaining user interface to stop being displayed. The wearable electronic device **602** enters a mode where the display **620** is turned off to conserve the battery **631**. The reading module **606** is executing and non-essential services are shutdown.

(105) The sleep module **615** will periodically request that the camera module **614** controls the camera **612** to capture an image **611** or frame. In some examples, the sleep module **615** will request that the camera module **614** capture an image **611** from the camera every 15 seconds, which corresponds to $\frac{1}{8}$ th of the time spent on average on a page of text of a book. The code detection module **608** then checks the image **611** for codes **613**. If no codes **613** are found, the image **611** is discarded. If code detection module **608** detects a code **613**, then the code to code module map **609** looks to see if a corresponding code module **630** is loaded in the wearable electronic device **602**. If the code module **630** is not loaded, then the code module fetcher **610** manages retrieving the code module **630** from the backend **604** via the communications **622** by sending packets or communications **628** to the backend **604**.

(106) In some examples, the sleep module **615** places the hardware of the AR glasses into a sleep state for a sleep duration or sleep time where user interface item **629** selections are still recognized and where a timer or interrupt circuit is still powered to awake the wearable electronic device **602**. In some examples, the sleep module **615** places the display **620** and camera **612** hardware into a low power consumption state. The sleep time or sleep duration is based on an amount of time to read a section of reading material, e.g., a page of a book, with a goal of awaking once for every section of the reading material, e.g., page of the book. The sleep time or sleep duration is an estimate of the reading time of a section of reading material, e.g., page of the book, and may be from less than a second to several minutes. The sleep time or sleep duration may be adjusted depending on the reading habits of the user. The sleep module **615** may determine to enter a sleep mode based on the code module **630** reporting an explicit user input to exit the code module **630**, a timeout period where the user has not interacted with the code module **630** for a predetermined duration of time, or if the code module **630** detects that the user has turned to a different section of reading material, e.g., page, or is no longer focused on the book. The code module **630** may use the

camera **612** during operation to provide a mixed reality experience and may be responsible for ensuring that the user is still focused on the same section of the reading material, e.g., page of the book.

(107) The sleep module **615** puts the communications **622** into a sleep mode after the code modules **630** have been retrieved for a piece of reading material, e.g., a book, until the reading mode, e.g., book reading mode, is exited or another piece of reading material, e.g., a book, is determined to be within an image **611**. The sleep module **615** may power down the communications **622** and then power up the communications **622** when the reading mode, e.g., book reading mode, is exited. In some examples, the communications **622** have a low power mode where power is maintained to a portion of the circuitry to permit high-priority communications but that requires powering up the remainder of the communications **622** prior to use.

(108) If a code module **630** is matched to the code **613**, then the display module **616** turns the display **620** on and the navigation module **618** launches the code module **630**. The reading module **606** is paused while the code module **630** executes or runs. When the user is finished with the code module **630** the navigation module **618** terminates the code module **630** and returns to the reading module **606**. The user may indicate they are done with the code module **630** via an interaction with the code module **630** such as a hand gesture, a timeout, or another interaction such as with the user interface item **629**.

(109) The sleep module **615** may use different times to wake up and request that the camera module **614** capture an image. The sleep module **615** is configured to wake-up when the user interface item **629** is selected, in accordance with some examples. For example, a button on a side of the glasses **1100** may wake-up the sleep module **615**.

(110) For example, fifteen seconds may be too long for the sleep module **615** to wake-up. The sleep module **615** may adjust the time for waking up based on user data **627**. In some examples, the code detection module **608** determines a section of reading material, e.g., page of the book, that is being read and stores this in the user data **627**. If the page numbers are not sequential, for example, a first page is page 2 and a second page is page 4, then the sleep module **615** may reduce the wake-up time to 5 seconds to ensure that every page is captured by an image **611** to search for codes **613**. In some examples, the code **613** is associated with a page of the book so that sleep module **615** can determine if sections of reading material, e.g., pages, have been skipped from being captured by the camera module **614**. The sleep module **615** reduces the sleep time if pages are being skipped.

(111) The sleep module **615** enables the wearable electronic device **602** to sleep and be more energy-efficient since an image **611** is captured only once every 15 seconds or so, and the wearable electronic device **602** can go into a sleep mode when it is not capturing and analyzing images **611**.

(112) Having the code detection module **608** resident in the wearable electronic device **602** means that the wearable electronic device **602** does not have to send the image **611** over the communications **622** to be analyzed, which reduces network usage and may save time and battery **631** usage. In some examples, when the code module **630** is being executed other user interfaces are not presented, which may save battery **631** usage. The wearable electronic device **602** may enter a passive mode where the user would have to exit the code module **630** to access additional user interface options other than a physical user interface item **629** such as a button. The code module **630** may have a user interface item to exit or terminate the code module **630** such as a press of a button when the user interface item **629** is a button or a hand jester. In some examples, when the code module **630** is executing images **611**, the code module **630** is configured to detect a change in the section of the reading material, e.g., a turn of the page, which terminates the code module **630** and causes another image **611** to be captured and analyzed by the code detection module **608** for codes **613**.

(113) In an offline mode of reading module **606**, a target piece of reading material, e.g., a target book, may have a special code **613** that indicates that all of the code modules **630** of the target book should be downloaded to the wearable electronic device **602** so that the communications **622** does

not have to be used during the reading of the target book. In some examples, the wearable electronic device **602** has an option that when a code **613** is read from a book, then the code module fetcher **610** retrieves all the code modules **630** for that book so that the communications **622** does not have to be used during the reading of the book. The communications **622** is powered off until a new book is detected or until the book mode is exited. A new book may be detected if the code **613** indicates a different book than a current book that is being read. Book is used but it is understood that other reading materials may be used.

(114) In some examples, the book mode of FIG. **12** may be for specific reading materials, e.g., books. For example, the highlighted **1210** may be for a specific book with a “<Book title>”. The icon that is highlighted **1210** may be a special icon for a specific book. Selecting the highlighted **1210** would cause a reading module **606** to be executed that is specific to that book. The code modules **630** are loaded into the wearable electronic device **602** so that the communications **622** do not have to be used during the reading of the specific book.

(115) The backend **604** is a server in the messaging server system **108** or a client device **102**. In some examples, the backend **604** is a client device **102** that passes the communications from the wearable electronic device **602** to the server in the messaging server system **108** and sends the code modules **630** to the wearable electronic device **602**. The client device **102** acts as a cache where the client device **102** recognizes that a new piece of reading material, e.g., book, is being read. The client device **102** requests all the code modules **630** from the server and acts as the backend **604**. In some examples, the client device **102** acting as a cache enables a lower energy communication protocol to be used.

(116) FIG. **7** illustrates a flow diagram **700** of the operation of the wearable electronic device **602**, in accordance with some examples. The flow diagram **700** begins with module presentation **702**. The module presenter **626** presents different modules or applications from which the user may select. For example, module carousel **1214** illustrated in FIG. **12** is presented on the display **620** of a mobile device **1202**. The wearable electronic device **602**, e.g., AR glasses, may be paired another device such as a client device (e.g., mobile device **1202**) and that the controls can be set through use of the client device, (e.g., as shown in FIG. **12**). In other embodiments the controls, e.g., the module carousel **1214**, is displayed on the wearable electronic device **602**, e.g., displayed on the screen of the AR glasses.

(117) The flow diagram **700** continues at reading module in focus **704**. For example, the user moves the reading module **606** to the highlighted **1210** position of the module carousel **1214**. The flow diagram **700** continues with the reading module highlighted **706**. The flow diagram **700** continues with reading module selected **708**. For example, the finger **1212** selects highlighted **1210**. The flow diagram **700** continues with books module **714**, which is now executing. For example, the reading module **606** may be executed by the module executor **624**, which may be called by the module presenter **626** in response to the reading module **606** being selected by the finger **1212** of a user.

(118) The flow diagram **700** continues with process sections of reading material, pages, and looks for codes **716**, which is performed by the code detection module **608**. For example, the sleep module **615** may have the camera module **614** capture an image **611**. The code detection module **608** looks for a code **613**. The reading module **606** displays **724** that a code was found using the display module **616**.

(119) The code module fetcher **722** fetches a code module **630** corresponding to the found code **613**. The navigation module **618** manages the execution of the code module **630**. The code module **630** uses the display module **616** to present an interactive augmented reality experience to the user. The AR module **621** is used to provide user interface items that are interactive. The module executor **624** is used by the navigation module **618** to execute the code module **630**. The navigation module **618** detects that there is an exit **732** from the code module **630** and moves to a state of module exit **726** where control is returned to the reading module **606**. In some examples, the

reading module **606** continues to run during execution of the reading module **606**. The reading module **606** captures images **611** periodically while the code module **630** executes and determines an identifier for a section of reading materials, e.g., a page number. The exit **732** is triggered by a change the identifier for the section of the reading material, e.g., in page number, being detected by the reading module **606**.

(120) FIG. **8** illustrates a method **800** of enhanced reading with AR glasses, in accordance with some examples. The method **800** is performed by the reading module **606** or, more specifically, the sleep module **615**, in accordance with some examples. The method **800** starts in a sleep state **802** where a reading material state, e.g., a book state, is already entered. For example, the highlighted **1210** book icon is selected as illustrated in FIG. **12**. The sleep state **802** periodically checks if it is a wake time **804**. For example, the sleep state **802** may wake every 1 to 30 seconds. If it is not yet wake time, then sleep module **615** returns to the sleep state **802**. In some examples, an interrupt is used to wake the sleep module **615** based on a time set by the sleep module **615**.

(121) If it is a wake time **804**, then the sleep module **615** takes and processes an image **806** as described herein. In some examples, the sleep module **615** is awakened from a manual waken **808**. For example, a user may press a button, which may be a user interface item **629**.

(122) After the take and process an image **806** state, the sleep module **615** determines whether to exit **812**. For example, the image captured in take and process an image **806** may indicate that the user is no longer reading a reading material, e.g., a book. If the sleep module **615** determines to exit, then the sleep module **615** returns to the reading module **810**. For example, the reading module **606** may be called to determine what action should be taken next. In some examples, if the reading module **606** determines that the identifier for the section of the reading material, a page number of page, in the image **611** is the same as a previous image, then the reading module **606** reenters the sleep state **802**. In some examples, adjust sleep time **820** is performed before reentering the sleep state **802**.

(123) If the determination is not to exit, then the sleep module **615** determines whether to enter a continuous state **814**. For example, the image may indicate that the user is flipping through the book quickly, so the sleep module **615** determines to enter a continuous state **816** where images are captured relatively frequently such as every one second.

(124) When the sleep module **615** determines to exit the continuous state **816**, the sleep module **615** determines whether to adjust sleep time **818**. For example, if the image indicates that sections of the reading material, e.g., pages, have been skipped, then the sleep module **615** may determine to adjust sleep time **820**. In another example, the sleep module **615** may determine that the image is of a same page as one or more previous images and determine to adjust sleep time **820**. If the sleep time is not to be adjusted, then the state returns to sleep state **802**. Otherwise, the state is to adjust sleep time **820**, which uses the user data **672**. The sleep time may be increased or decreased based on the reading speed of the user as determined by keeping track of which page the user is on in the book based on the captured images. In some examples, the sleep time or sleep duration is adjust to an estimated time for the user to read a section of reading material, e.g., a page of the book, based on the user data **627** including page numbers of the book and timestamps of when images of the pages with the page numbers were captured. In some examples, the sleep time is increased by a fraction of a second if an image is of the same page as a previous image. In some examples, the sleep time is decreased by a fraction of a second if an image is a different image than a previous image. In this way the sleep duration is constantly being adjusted to accommodate the reading speed of the wearer of the wearable electronic device **602**. In some examples the sleep duration is from one second to one-hundred and twenty seconds.

(125) FIG. **9** illustrates a book **900** with codes, in accordance with some examples. The book **900** includes a page number **904** of page 5, an illustration of a dragon **906**, and a code **902**. The code **902** is identified by code detection module **608** from an image **611** captured by camera module **614**. The code to code module map **609** determines a code module **630** corresponding to the identified

code **902**. The code module fetcher **610** retrieves the appropriate code module **630**. The navigation module **618** and module executor **624** execute the code module **630**. In this case the code module **630** presents a three-dimensional dragon on the display **620** of the wearable electronic device **602**. The code module **630** may include a mixed reality experience where the wearer of the wearable electronic device **602** can interact with a virtual reality dragon. A book is illustrated in FIG. **9** but it is understood that other types of reading material may be used.

(126) FIG. **10** illustrates a book **1000** with codes, in accordance with some examples. The book **1000** includes page number **1006** of page 5 and page number **1008** of page 6, code **1002**, and code **1004**. The code **1002** and code **1004** are identified by code detection module **608** from an image **611** captured by camera module **614**. The code to code module map **609** determines a code module **630** corresponding to the identified code **1002** and a code module **603** corresponding to the identified code **1004**. The code module fetcher **610** retrieves the appropriate code modules **630**. In some examples, the code module **630** corresponding to code **1002** is executed first and then the code module **630** corresponding to code **1004**. In some examples, a menu or option is presented to the wearer of the wearable electronic device **602** regarding which code module **630** the wearer would like to execute first or execute no code modules **630**. The navigation module **618** and module executor **624** execute the selected code module **630**. In this case the code module **630** presents further instruction to aid in the instruction of the properties of gases. The code module **630** may include a mixed reality experience where the wearer of the wearable electronic device **602** can interact with virtual reality gases. A book is illustrated in FIG. **10** but it is understood that other types of reading material may be used.

(127) FIG. **11** illustrates examples of a wearable electronic device in the form of glasses **1100**, in accordance with some examples. The wearable electronic device in the form of glasses **1100**. The glasses **1110** are an article of eyewear constituted by electronics, which operate within a network system for communicating image and video content. FIG. **11** illustrates a front perspective view of the glasses **1100**. In some examples, the wearable electronic device is termed AR glasses. The glasses **1100** can include a frame **1132** made from any suitable material such as plastic or metal, including any suitable shape memory alloy. The frame **1132** can have a front piece **1133** that can include a first or left lens, display, or optical element holder **1136** and a second or right lens, display, or optical element holder **1137** connected by a bridge **1138**. The front piece **1133** additionally includes a left end portion **1141** and a right end portion **1142**. A first or left optical element **1144** and a second or right optical element **1143** can be provided within respective left and right optical element holders **1136**, **1137**. Each of the optical elements **1143**, **1144** can be a lens, a display, a display assembly, or a combination of the foregoing. In some examples, for example, the glasses **1100** are provided with an integrated near-eye display mechanism that enables, for example, display to the user of preview images for visual media captured by cameras **1169** of the glasses **1100**.

(128) The frame **1132** additionally includes a left arm or temple piece **1146** and a right arm or temple piece **1147** coupled to the respective left and right end portions **1141**, **1142** of the front piece **1133** by any suitable means such as a hinge (not shown), so as to be coupled to the front piece **1133**, or rigidly or fixedly secured to the front piece **1133** so as to be integral with the front piece **1133**. Each of the temple pieces **1146** and **1147** can include a first portion **1151** that is coupled to the respective end portion **1141** or **1142** of the front piece **1133** and any suitable second portion **1152**, such as a curved or arcuate piece, for coupling to the ear of the user. In one example, the front piece **1133** can be formed from a single piece of material, so as to have a unitary or integral construction. In one example, the entire frame **1132** can be formed from a single piece of material so as to have a unitary or integral construction.

(129) The glasses **1100** include a computing device, such as a computer **1161**, which can be of any suitable type so as to be carried by the frame **1132** and, in one example, of a suitable size and shape, so as to be at least partially disposed in one or more of the temple pieces **1146** and **1147**. In

one example, the computer **1161** has a size and shape similar to the size and shape of one of the temple pieces **1146**, **1147** and is thus disposed almost entirely if not entirely within the structure and confines of such temple pieces **1146** and **1147**.

(130) In one example, the computer **1161** can be disposed in both of the temple pieces **1146**, **1147**. The computer **1161** can include one or more processors with memory, wireless communication circuitry, and a power source. The computer **1161** comprises low-power circuitry, high-speed circuitry, location circuitry, and a display processor. Various other examples may include these elements in different configurations or integrated together in different ways. Additional details of aspects of the computer **1161** may be implemented as described with reference to the description that follows.

(131) The computer **1161** additionally includes a battery **1162** or other suitable portable power supply. In one example, the battery **1162** is disposed in one of the temple pieces **1146** or **1147**. In the glasses **1100** shown in FIG. **11**, the battery **1162** is shown as being disposed in the left temple piece **1146** and electrically coupled using a connection **1174** to the remainder of the computer **1161** disposed in the right temple piece **1147**. One or more input and output devices can include a connector or port (not shown) suitable for charging a battery **1162** accessible from the outside of the frame **1132**, a wireless receiver, transmitter, or transceiver (not shown), or a combination of such devices.

(132) The glasses **1100** include digital cameras **1169**. Although two cameras **1169** are depicted, other examples contemplate the use of a single or additional (i.e., more than two) cameras **1169**. For ease of description, various features relating to the cameras **1169** will further be described with reference to only a single camera **1169**, but it will be appreciated that these features can apply, in suitable examples, to both cameras **1169**. Digital cameras **1169** are the camera **612** of FIG. **6**, which may include two or more cameras.

(133) In various examples, the glasses **1100** may include any number of input sensors or peripheral devices in addition to the cameras **1169**. The front piece **1133** is provided with an outward-facing, forward-facing, front, or outer surface **1166** that faces forward or away from the user when the glasses **1100** are mounted on the face of the user, and an opposite inward-facing, rearward-facing, rear, or inner surface **1167** that faces the face of the user when the glasses **1100** are mounted on the face of the user. Such sensors can include inward-facing video sensors or digital imaging modules such as cameras **1169** that can be mounted on or provided within the inner surface **1167** of the front piece **1133** or elsewhere on the frame **1132** so as to be facing the user, and outward-facing video sensors or digital imaging modules such as the cameras **1169** that can be mounted on or provided with the outer surface **1166** of the front piece **1133** or elsewhere on the frame **1132** so as to be facing away from the user. Such sensors, peripheral devices, or peripherals can additionally include biometric sensors, location sensors, accelerometers, or any other such sensors. In some examples, projectors (not illustrated) are used to project images on the inner surface of the optical elements **1143**, **1144** (or lenses) to provide a mixed reality or augmented reality experience for the user of the glasses **1100**.

(134) The glasses **1100** further include an example of a camera control mechanism or user input mechanism comprising a camera control button mounted on the frame **1132** for haptic or manual engagement by the user. The camera control button provides a bi-modal or single-action mechanism in that it is disposable by the user between only two conditions, namely an engaged condition and a disengaged condition. In this example, the camera control button is a pushbutton that is by default in the disengaged condition, being depressible by the user to dispose it to the engaged condition. Upon release of the depressed camera control button, it automatically returns to the disengaged condition.

(135) In other examples, the single-action input mechanism can instead be provided by, for example, a touch-sensitive button comprising a capacitive sensor mounted on the frame **1132** adjacent to its surface for detecting the presence of a user's finger, to dispose the touch-sensitive

button to the engaged condition when the user touches a finger to the corresponding spot on the outer surface **1166** of the frame **1132**. It will be appreciated that the above-described camera control button and capacitive touch button are but two examples of a haptic input mechanism for single-action control of the camera **1169**, and that other examples may employ different single-action haptic control arrangements.

(136) The computer **1161** is configured to perform the methods described herein. The computer **1161** is an example of a wearable electronic device **602**, in accordance with some examples. In some examples, the computer **1161** is coupled to one or more antennas for reception of signals from a GNSS and circuitry for processing the signals where the antennas and circuitry are housed in the glasses **1100**. In some examples, the computer **1161** is coupled to one or more wireless antennas and circuitry for transmitting and receiving wireless signals where the antennas and circuitry are housed in the glasses **1100**. In some examples, there are multiple sets of antennas and circuitry housed in the glasses **1100**. In some examples, the antennas and circuitry are configured to operate in accordance with a communication protocol such as Bluetooth™, Low-energy Bluetooth™, IEEE 802, IEEE 802.11az/be, and so forth. In some examples, PDR sensors are housed in glasses **1100** and coupled to the computer **1161**. In some examples, the glasses **1100** are VR headsets.

(137) FIG. **12** illustrates a user interface **1200** for module selection, in accordance with some examples. Illustrated is a mobile device **1202** with a camera **1204** and screen **1206**. A module for the wearable electronic device **602** is being selected on the mobile device **1202**, which may be a client device **102**. The module carousel **1214** is a user interface item where modules that are available for the user to select may be scrolled through by swiping the finger **1212**. The module in the center is highlighted. Here the reading mode, e.g., a book mode, is in the center of the carousel and is highlighted **1210**. The highlighted **1210** module has an explanation of the module highlighted **1210**, which here is plain text. The explanation of module **1208** may be an animation, an image, text, an interactive mixed reality experience, or something else to explain the functions of the highlighted **1210** module. The mobile device **1202** accepts the selection of the book mode and sends it to the wearable electronic device **602**. In some examples, the wearable electronic device **602** presents the user interface **1200**. For example, the module carousel **1214** may be a mixed reality or virtual reality user interface item and the finger **1212** may be a rendered image of the user's finger. The back interface item **1216** exits the user interface **1200**.

(138) FIG. **13** illustrates a method **1300** for enhanced reading with AR glasses, in accordance with some examples. The method **1300** at operation **1302** with entering a reading mode. For example, referring to FIG. **7**, when reading module is selected **708**, then the reading mode, e.g., book mode, is entered and the wearable electronic device **602** runs the reading module **606**. The method **1300** continues at operation **1304** with capturing a first image of a section of reading material. For example, the camera module **614** causes the camera **612** to capture an image **611** such as book **1000**. The method **1300** continues at operation **1306** with identifying a code within the first image. For example, code detection module **608** detects code **613** within the image **611** such as with the image **611** being book **1000** and the code **613** being code **1002**.

(139) The method **1300** continues at operation **1308** with identifying a code module corresponding to the code where the code module includes content corresponding to the section of the reading material. For example, code to code module map **609** takes the code **613** and maps it to a corresponding code module **630**. The code module fetcher **610** fetches the corresponding code module **630**. For example, for code **1002** of FIG. **10**, then the code module **630** is a code module that provides a mixed reality experience for learning about the property of gases.

(140) The method **1300** continues at operation **1310** with executing the code module where the code module provides a virtual reality object related to an object depicted on the section of the reading materials, e.g., the page of the book. For example, module executor **624** with the navigation module **618** executes the corresponding code module **630** to provide the mixed reality

experience of the gases.

(141) The method **1300** continues at operation **1312** with entering a sleep mode for a sleep duration where the sleep duration is based on an estimated reading time duration of a section not reading material, e.g., a page of the book. For example, a time duration may have passed where the user was inactive with the code module **630**, the user may have turned to a different section of the reading materials, e.g., turned the page of the book, or the user may provide an explicit user input such as a hand wave to terminate the code module **630**.

(142) The method **1300** continues at operation **1314** with reentering the reading mode after the sleep duration. The sleep module **615** places the wearable electronic device **602** into a sleep state **802** upon termination of the code module **630**. The method continues at operation **1316** with capturing a second image. For example, the sleep module **615** wakes up the wearable electronic device **602** and begins the process anew by capturing a new image **611** to determine if a section of the reading material, e.g., page, change has occurred and whether codes **613** are included in the image **611**.

(143) The method **1300** may include one or more additional operations. Operations of method **1300** may be performed in a different order. One or more of the operations of method **1300** may be optional. The method **1300** may be performed by the client device **102**, VR wearable electronic device **602**, and/or the wearable electronic device in the form of VR glasses **1100**. Portions of the functionality may be performed on a server computer or host computer.

(144) The term book may be used as an exemplary but it should be understood that other reading material may be used such as news papers, menus, magazines, pamphlets, instructions, mail, and so forth. The term page may be used as an exemplary but it should be understood that other sections of reading material may be used such as a leaf of a menu, a portion of a billboard, and so forth. The term page is being used to represent a section of a reading materials that a user may be attentive to.

(145) Machine Architecture

(146) FIG. **14** is a diagrammatic representation of the machine **1400** within which instructions **1410** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1400** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1410** may cause the machine **1400** to execute any one or more of the methods described herein. The instructions **1410** transform the general, non-programmed machine **1400** into a particular machine **1400** programmed to carry out the described and illustrated functions in the manner described. The machine **1400** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1400** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1400** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smartphone, a mobile device, a wearable device (e.g., a smartwatch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1410**, sequentially or otherwise, that specify actions to be taken by the machine **1400**. Further, while only a single machine **1400** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1410** to perform any one or more of the methodologies discussed herein. The machine **1400**, for example, may comprise the client device **102** or any one of a number of server devices forming part of the messaging server system **108**. In some examples, the machine **1400** may also comprise both client and server systems, with certain operations of a particular method or algorithm being performed on the server-side and with certain operations of the particular method or algorithm being performed on the client-side.

(147) The machine **1400** may include processors **1404**, memory **1406**, and input/output I/O

components **1402**, which may be configured to communicate with each other via a bus **1440**. In an example, the processors **1404** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) Processor, a Complex Instruction Set Computing (CISC) Processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an Application Specific Integrated Circuit (ASIC), a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1408** and a processor **1412** that execute the instructions **1410**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **14** shows multiple processors **1404**, the machine **1400** may include a single processor with a single-core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

(148) The memory **1406** includes a main memory **1414**, a static memory **1416**, and a storage unit **1418**, both accessible to the processors **1404** via the bus **1440**. The main memory **1406**, the static memory **1416**, and storage unit **1418** store the instructions **1410** embodying any one or more of the methodologies or functions described herein. The instructions **1410** may also reside, completely or partially, within the main memory **1414**, within the static memory **1416**, within machine-readable medium **1420** within the storage unit **1418**, within at least one of the processors **1404** (e.g., within the Processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1400**.

(149) The I/O components **1402** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1402** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1402** may include many other components that are not shown in FIG. **14**. In various examples, the I/O components **1402** may include user output components **1426** and user input components **1428**. The user output components **1426** may include visual components (e.g., a display such as a plasma display panel (PDP), a light-emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The user input components **1428** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(150) In further examples, the I/O components **1402** may include biometric components **1430**, motion components **1432**, environmental components **1434**, or position components **1436**, among a wide array of other components. For example, the biometric components **1430** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye-tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **1432** include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope).

(151) The environmental components **1434** include, for example, one or cameras (with still image/photograph and video capabilities), illumination sensor components (e.g., photometer),

temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment.

(152) With respect to cameras, the client device **102** may have a camera system comprising, for example, front cameras on a front surface of the client device **102** and rear cameras on a rear surface of the client device **102**. The front cameras may, for example, be used to capture still images and video of a user of the client device **102** (e.g., “selfies”), which may then be augmented with augmentation data (e.g., filters) described above. The rear cameras may, for example, be used to capture still images and videos in a more traditional camera mode, with these images similarly being augmented with augmentation data. In addition to front and rear cameras, the client device **102** may also include a 360° camera for capturing 360° photographs and videos.

(153) Further, the camera system of a client device **102** may include dual rear cameras (e.g., a primary camera as well as a depth-sensing camera), or even triple, quad or penta rear camera configurations on the front and rear sides of the client device **102**. These multiple cameras systems may include a wide camera, an ultra-wide camera, a telephoto camera, a macro camera and a depth sensor, for example.

(154) The position components **1436** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(155) Communication may be implemented using a wide variety of technologies. The I/O components **1402** further include communication components **1438** operable to couple the machine **1400** to a network **1422** or devices **1424** via respective coupling or connections. For example, the communication components **1438** may include a network interface Component or another suitable device to interface with the network **1422**. In further examples, the communication components **1438** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1424** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(156) Moreover, the communication components **1438** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1438** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1438**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

(157) The various memories (e.g., main memory **1414**, static memory **1416**, and memory of the processors **1404**) and storage unit **1418** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **1410**), when executed by processors **1404**, cause various operations to implement the disclosed examples.

(158) The instructions **1410** may be transmitted or received over the network **1422**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **1438**) and using any one of several well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1410** may be transmitted or received using a transmission medium via a coupling (e.g., a peer-to-peer coupling) to the devices **1424**.

(159) Software Architecture

(160) FIG. **15** is a block diagram **1500** illustrating a software architecture **1504**, which can be installed on any one or more of the devices described herein. The software architecture **1504** is supported by hardware such as a machine **1502** that includes processors **1520**, memory **1526**, and I/O components **1538**. In this example, the software architecture **1504** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1504** includes layers such as an operating system **1512**, libraries **1510**, frameworks **1508**, and applications **1506**. Operationally, the applications **1506** invoke API calls **1550** through the software stack and receive messages **1552** in response to the API calls **1550**.

(161) The operating system **1512** manages hardware resources and provides common services. The operating system **1512** includes, for example, a kernel **1514**, services **1516**, and drivers **1522**. The kernel **1514** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **1514** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services **1516** can provide other common services for the other software layers. The drivers **1522** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1522** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., USB drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

(162) The libraries **1510** provide a common low-level infrastructure used by the applications **1506**. The libraries **1510** can include system libraries **1518** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1510** can include API libraries **1524** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1510** can also include a wide variety of other libraries **1528** to provide many other APIs to the applications **1506**.

(163) The frameworks **1508** provide a common high-level infrastructure that is used by the applications **1506**. For example, the frameworks **1508** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1508** can provide a broad spectrum of other APIs that can be used by the applications **1506**, some of which may be specific to a particular operating system or platform.

(164) In an example, the applications **1506** may include a home application **1536**, a contacts application **1530**, a browser application **1532**, a reader application **1534**, a location application **1542**, a media application **1544**, a messaging application **1546**, a game application **1548**, and a broad assortment of other applications such as a third-party application **1540**. The applications **1506** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1506**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural

programming languages (e.g., C or assembly language). In a specific example, the third-party application **1540** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party application **1540** can invoke the API calls **1550** provided by the operating system **1512** to facilitate functionality described herein.

(165) Processing Components

(166) Turning now to FIG. **16**, there is shown a diagrammatic representation of a processing environment **1600**, which includes a processor **1602**, a processor **1606**, and a processor **1608** (e.g., a GPU, CPU or combination thereof).

(167) The processor **1602** is shown to be coupled to a power source **1604**, and to include (either permanently configured or temporarily instantiated) modules, namely a code detection component **1610**, reading material component **1612**, and a communication component **1614**. The code detection component **1610** detects codes in images **611**. Referring to FIG. **6**, the code detection component **1610** performs the functions associated with the code detection module **608**.

(168) The reading material module component **1612** performs the functions associated with providing enhanced AR for reading. The reading module component **1612** performs the functions associated with the reading module **606** of FIG. **6**. The communication component **1614** is coupled to communications hardware and is configured to implement communication protocols. The communications component **1614** performs functions associated with communications **622**. As illustrated, the processor **1602** is communicatively coupled to both the processor **1606** and the processor **1608**.

Glossary

(169) “Carrier signal” refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by the machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device.

(170) “Client device” refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, an AR glasses, a VR glasses, an AR wearable device, a desktop computer, a laptop, a portable digital assistants (PDAs), smartphones, tablets, ultrabooks, netbooks, laptops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, or any other communication device that a user may use to access a network.

(171) “Communication network” refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network and the coupling may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other types of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications

System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

(172) “Component” refers to a device, physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various examples, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an application specific integrated circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software), may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. Considering examples in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time. Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In examples in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A

further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information). The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some examples, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other examples, the processors or processor-implemented components may be distributed across a number of geographic locations.

(173) “Computer-readable storage medium” refers to both machine-storage media and transmission media. Thus, the terms include both storage devices/media and carrier waves/modulated data signals. The terms “machine-readable medium,” “computer-readable medium” and “device-readable medium” mean the same thing and may be used interchangeably in this disclosure.

(174) “Ephemeral message” refers to a message that is accessible for a time-limited duration. An ephemeral message may be a text, an image, a video and the like. The access time for the ephemeral message may be set by the message sender. Alternatively, the access time may be a default setting or a setting specified by the recipient. Regardless of the setting technique, the message is transitory.

(175) “Machine storage medium” refers to a single or multiple storage devices and media (e.g., a centralized or distributed database, and associated caches and servers) that store executable instructions, routines and data. The term shall accordingly be taken to include, but not be limited to, solid-state memories, and optical and magnetic media, including memory internal or external to processors. Specific examples of machine-storage media, computer-storage media and device-storage media include non-volatile memory, including by way of example semiconductor memory devices, e.g., erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), FPGA, and flash memory devices; magnetic disks such as internal hard disks and removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The terms “machine-storage medium,” “device-storage medium,” “computer-storage medium” mean the same thing and may be used interchangeably in this disclosure. The terms “machine-storage media,” “computer-storage media,” and “device-storage media” specifically exclude carrier waves, modulated data signals, and other such media, at least some of which are covered under the term “signal medium.”

(176) “Non-transitory computer-readable storage medium” refers to a tangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine.

(177) “Signal medium” refers to any intangible medium that is capable of storing, encoding, or carrying the instructions for execution by a machine and includes digital or analog communications signals or other intangible media to facilitate communication of software or data. The term “signal

medium” shall be taken to include any form of a modulated data signal, carrier wave, and so forth. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. The terms “transmission medium” and “signal medium” mean the same thing and may be used interchangeably in this disclosure.

Claims

1. An augmented reality (AR) electronic device comprising: at least one processor; and at least one memory storing instructions that, when executed by the at least one processor, configure the AR electronic device to perform operations comprising: entering a reading mode; capturing a first image of a section of reading material, the section comprising a first page; providing an augmented reality object related to an object depicted in the section of reading material; in response to entering a sleep mode for a sleep duration, causing wireless communication processing circuitry of the AR electronic device to enter a lower-energy consumption mode, causing camera hardware of the AR electronic device to enter a lower-energy consumption mode, and causing display hardware of the AR electronic device to enter a lower-energy consumption mode, wherein the sleep duration is based on an estimated reading time duration of the section of the reading material for a user; reentering the reading mode after the sleep duration; capturing a second image; identifying a second page within the second image; increasing the sleep duration when the first page and the second page are a same page; and decreasing the sleep duration when the first page and the second page are different pages.
2. The AR electronic device of claim 1, wherein the operations further comprise: identifying a code within the first image; and identifying a code module corresponding to the code, the code module comprising content corresponding to the section of the reading material.
3. The AR electronic device of claim 2, wherein the providing further comprises: executing the code module, the code module providing the augmented reality object related to the object depicted on the section of the reading material.
4. The AR electronic device of claim 2, wherein the operations further comprise: retrieving the code module from a backend server via a lower-energy wireless communications protocol.
5. The AR electronic device of claim 2, wherein the operations further comprise: in response to the code identifying the reading material, retrieving a plurality of code modules including the code module from a backend server via wireless communication processing circuitry, the plurality of code modules corresponding to a plurality of codes contained within the reading material; powering down the wireless communication processing circuitry; and in response to leaving the reading mode or detecting a new reading material, powering up the wireless communication processing circuitry.
6. The AR electronic device of claim 2, wherein entering the reading mode comprises: refraining from turning on display hardware unless the code is identified or a physical user interface item is selected.
7. The AR electronic device of claim 1, wherein the section is a page and the reading material is a book.
8. The AR electronic device of claim 1, wherein the section is a first page and wherein the operations further comprises: identifying the second page within a second image; and reentering the sleep mode when the first page and the second page are a same page.
9. The AR electronic device of claim 1, wherein the sleep duration is from one second to one-hundred and twenty seconds.
10. The AR electronic device of claim 1 wherein the sleep duration is increased or decreased by a fraction of a second.
11. The AR electronic device of claim 1, wherein the operations further comprise: storing a number of the section with a time in the at least one memory; and adjusting the sleep duration based on a

plurality of numbers of sections of the reading material associated with a plurality of times.

12. The AR electronic device of claim 1, wherein the operations further comprise: determining the second image is of a different piece of reading material; and exiting the reading mode.

13. The AR electronic device of claim 1, wherein entering the sleep mode further comprises: in response to a hand gesture by a wearer of the AR electronic device, entering the sleep mode for the sleep duration, the sleep duration based on a reading time duration of the section of the reading material.

14. The AR electronic device of claim 1, wherein the operations further comprise: refraining from displaying user interface items for invoking functions of the AR electronic device during the providing the augmented reality object.

15. The AR electronic device of claim 1, wherein the AR electronic device is a mixed reality wearable electronic device, an AR wearable electronic device, AR glasses, or MR glasses.

16. A non-transitory computer-readable storage medium, the computer-readable storage medium including instructions that when executed by a virtual reality (VR) or augmented reality (AR) wearable electronic device, cause the VR wearable electronic device to perform operations comprising: entering a reading mode; capturing a first image of a section of reading material, the section comprising a first page; providing an augmented reality object related to an object depicted in the section of reading material; in response to entering a sleep mode for a sleep duration, causing wireless communication processing circuitry of the AR electronic device to enter a lower-energy consumption mode, causing camera hardware of the AR electronic device to enter a lower-energy consumption mode, and causing display hardware of the AR electronic device to enter a lower-energy consumption mode, wherein the sleep duration is based on an estimated reading time duration of the section of the reading material for a user; reentering the reading mode after the sleep duration; capturing a second image; identifying a second page within the second image; increasing the sleep duration when the first page and the second page are a same page; and decreasing the sleep duration when the first page and the second page are different pages.

17. The non-transitory computer-readable storage medium of claim 16, wherein the operations further comprise: capturing a first image of a section of reading material; identifying a code within the first image; and identifying a code module corresponding to the code, the code module comprising content corresponding to the section of the reading material.

18. The non-transitory computer-readable storage medium of claim 17, wherein the providing further comprises: executing the code module, the code module providing the augmented reality object related to the object depicted on the section of the reading material.

19. The non-transitory computer-readable storage medium of claim 17, wherein the operations further comprise: retrieving the code module from a backend server via a lower-energy wireless communications protocol.

20. A method performed on an augmented reality (AR) wearable electronic device, the method comprising: entering a reading mode; capturing a first image of a section of reading material, the section comprising a first page; providing an augmented reality object related to an object depicted in the section of reading material; in response to entering a sleep mode for a sleep duration, causing wireless communication processing circuitry of the AR electronic device to enter a lower-energy consumption mode, causing camera hardware of the AR electronic device to enter a low-energy lower-energy consumption mode, and causing display hardware of the AR electronic device to enter a lower-energy consumption mode, wherein the sleep duration is based on an estimated reading time duration of the section of the reading material for a user; and reentering the reading mode after the sleep duration; capturing a second image; identifying a second page within the second image; increasing the sleep duration when the first page and the second page are a same page; and decreasing the sleep duration when the first page and the second page are different pages.
