

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12406962

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Elsherbini; Adel A. et al.

Power delivery through capacitor-dies in a multi-layered microelectronic assembly

Abstract

Embodiments of the present disclosure provide a microelectronic assembly comprising: an integrated circuit (IC) die in a first layer and a plurality of IC dies in a second layer, at least two adjacent IC dies in the plurality being electrically coupled along their proximate edges by the IC die. The first layer and the second layer are electrically and mechanically coupled by interconnects having a pitch of less than 10 micrometers between adjacent interconnects, and the IC die comprises capacitors and voltage regulator circuitry.

Inventors: Elsherbini; Adel A. (Tempe, AZ), Lambert; William J. (Chandler, AZ), Bharath; Krishna (Phoenix, AZ), Liff; Shawna M. (Scottsdale, AZ), Butzen; Nicolas (Portland, OR), Dogiamis; Georgios (Chandler, AZ), Pasdast; Gerald S. (San Jose, CA), Rajan; Vivek Kumar (Portland, OR), Tiagaraj; Sathya Narasimman (San Jose, CA), Schmidt; Timothy Francis (San Jose, CA)

Applicant: Intel Corporation (Santa Clara, CA)

Family ID: 86384263

Assignee: Intel Corporation (Santa Clara, CA)

Appl. No.: 17/531374

Filed: November 19, 2021

Prior Publication Data

Document Identifier

US 20230163098 A1

Publication Date

May. 25, 2023

Publication Classification

Int. Cl.: H01L25/065 (20230101); H01L23/00 (20060101); H01L23/48 (20060101);
H01L23/522 (20060101); H01L25/18 (20230101)

U.S. Cl.:

CPC H01L25/0652 (20130101); H01L23/481 (20130101); H01L23/5223 (20130101);
H01L24/08 (20130101); H01L25/18 (20130101); H01L2224/08145 (20130101)

Field of Classification Search

CPC: H01L (25/0652); H01L (25/18); H01L (2224/08145); H01L (25/16); H01L (23/481);
H01L (23/5223); H01L (24/08); H01L (24/13); H01L (24/16); H01L (24/17); H01L
(24/81); H01L (2225/06513); H01L (2225/06517); H01L (2225/06541); H01L
(2225/06548)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0098621	12/2019	Bharath	N/A	H01L 25/18
2020/0105653	12/2019	Elsherbini	N/A	H01L 23/642
2022/0077109	12/2021	Chava	N/A	H01L 25/0657
2022/0392881	12/2021	Yu	N/A	H01L 25/167

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
114582836	12/2021	CN	H01L 21/304

Primary Examiner: Diallo; Mamadou L

Attorney, Agent or Firm: Akona IP PC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to techniques, methods, and apparatus directed to power delivery through capacitor-dies in a multi-layered microelectronic assembly associated with semiconductor integrated circuit (IC) packaging technologies.

BACKGROUND

(2) Electronic circuits when commonly fabricated on a wafer of semiconductor material, such as silicon, are called ICs. The wafer with such ICs is typically cut into numerous individual dies. The dies may be packaged into an IC package containing one or more dies along with other electronic components such as resistors, capacitors, and inductors. The IC package may be integrated onto an electronic system, such as a consumer electronic system, or servers, such as mainframes.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Embodiments will be readily understood by the following detailed description in conjunction with the accompanying drawings. To facilitate this description, like reference numerals designate like structural elements. Embodiments are illustrated by way of example, and not by way of limitation, in the figures of the accompanying drawings.
- (2) FIG. 1A is a simplified cross-sectional view of an example microelectronic assembly, according to some embodiments of the present disclosure.
- (3) FIG. 1B illustrates details of a portion of the example microelectronic assembly of FIG. 1A, according to an embodiment of the present disclosure.
- (4) FIG. 1C illustrates details of a portion of the example microelectronic assembly of FIG. 1A, according to another embodiment of the present disclosure.
- (5) FIG. 1D illustrates details of a portion of the example microelectronic assembly of FIG. 1A, according to another embodiment of the present disclosure.
- (6) FIG. 2 is a simplified cross-sectional view of details of hybrid interconnects used in various embodiments of the microelectronic assembly according to the present disclosure.
- (7) FIG. 3 is a simplified cross-sectional view of a portion of an example microelectronic assembly, according to various embodiments of the present disclosure.
- (8) FIG. 4 is a simplified cross-sectional view of a portion of another example microelectronic assembly, according to various embodiments of the present disclosure.
- (9) FIG. 5A is a simplified cross-sectional view of an example microelectronic assembly having capacitor-dies, according to various embodiments of the present disclosure.
- (10) FIG. 5B is a simplified top view of the example microelectronic assembly of FIG. 5A, according to various embodiments of the present disclosure.
- (11) FIG. 6 is a simplified block diagram of an example power delivery network of the microelectronic assembly, according to various embodiments of the present disclosure.
- (12) FIG. 7 is a simplified block diagram of another example power delivery network of the microelectronic assembly, according to various embodiments of the present disclosure.
- (13) FIG. 8 is a simplified block diagram of an example arrangement among components of the microelectronic assembly, according to various embodiments of the present disclosure.
- (14) FIG. 9 is a simplified block diagram of another example arrangement among components of the microelectronic assembly, according to various embodiments of the present disclosure.
- (15) FIG. 10 is a is a simplified block diagram of yet another example arrangement among components of the microelectronic assembly, according to various embodiments of the present disclosure.
- (16) FIG. 11 is a simplified top view of an example configuration of the microelectronic assembly according to various embodiments of the present disclosure.
- (17) FIG. 12 is a cross-sectional view of a device package that includes one or more microelectronic assemblies in accordance with any of the embodiments disclosed herein.
- (18) FIG. 13 is a cross-sectional side view of a device assembly that includes one or more microelectronic assemblies in accordance with any of the embodiments disclosed herein.
- (19) FIG. 14 is a block diagram of an example computing device that includes one or more microelectronic assemblies in accordance with any of the embodiments disclosed herein.

DETAILED DESCRIPTION

Overview

- (20) For purposes of illustrating IC packages described herein, it is important to understand phenomena that may come into play during assembly and packaging of ICs. The following foundational information may be viewed as a basis from which the present disclosure may be properly explained. Such information is offered for purposes of explanation only and, accordingly, should not be construed in any way to limit the broad scope of the present disclosure and its

potential applications.

(21) In a general sense, today's ICs are manufactured with increasingly higher performance, reduced costs, and increased miniaturization of components and devices. Many ICs such as processors, controllers, logic devices, memory devices and the like may be housed in a package including a substrate which supports a semiconductor die (also called IC die) and which further has internal electrical connections to provide interconnections (i.e., power, ground, and data) to the die. The package includes external electrical connections to enable the package to be electrically connected to, for example, a socket that may be adapted on a circuit board such as a motherboard or the like.

(22) For many electronic technologies, the drive toward smaller devices with greater functionality runs up against challenges in power delivery network (PDN) design. In a general sense, a typical PDN consists of all interconnections in a power supply pathway from voltage regulator modules to circuits, called herein as intellectual property (IP) cores on the die. For example, the PDN comprises printed circuit board (PCB) PDN, including voltage regulators (VRs) bulk decoupling capacitors, power, and ground planes, any intervening vias, traces and relevant leads, multi-layer ceramic capacitors; package PDN, including power ground shapes, vias, traces, solder balls, wire-bonds, package capacitors, etc. of various components in the IC packages, and die PDN, comprising on-die capacitors and power grid for IC dies electrically coupled together for a particular functionality. An "IP core" as used herein may include any number and any combination of memory, multiplexer, logic gate, register, arithmetic logic unit, datapath, microprocessor core, digital signal processor, random control logic, network processor, peripheral, input/output interfaces, and other circuits with particularized functionality and input/output interfaces such that a combination of such logic circuits suitably electrically coupled to each other enables the IC die in which the logic circuits are situated to function according to its intended purposes. Input/output interfaces can comprise registers for memory (e.g., double data rate (DDR) DDRx, low power DDR (LPDDR) LPDDRx), peripheral component interconnect express (PCIE) PCIEx, universal serial bus (USB) USBx, serial advanced technology attachment (SATA) SATAx, display, High-Definition Multimedia Interface (HDMI) HDMIx, phased lock loop (PLL), etc.

(23) In particular, two correlated important requirements in heterogeneous integration in the area of high-performance computing associated with PDNs are: (1) ability to deliver high power to the IP cores with high overall efficiency and (2) ability to accommodate fast power transients with low voltage droop. These requirements can be accommodated through integrated voltage regulators and added on-core or near-core high frequency capacitors in a way that minimizes the cost while maintaining the needed performance.

(24) Voltage regulators and metal-insulator-metal capacitors (MIM) capacitors may be integrated into the logic die comprising the IP core, however, such a configuration requires relatively expensive logic area and may impact the overall die yield. They may also be added as individual IC dies, for example, in a 3D stacked packaging architecture, such as Intel's omni-directional interconnect (ODI), which helps avoid the yield impact and allows using optimum technology for the voltage regulators. However, the organic dielectric in many of these 3D stacked packaging architectures can only accommodate low pitch interconnects (e.g., pitch greater than around 50 micrometers) between layers in the package, thereby preventing true 3D stacking.

(25) In contrast, embodiments of the present disclosure provide a microelectronic assembly comprising: an IC die in a first layer and a plurality of IC dies in a second layer, at least two adjacent IC dies in the plurality being electrically coupled along their proximate edges by the IC die. The first layer and the second layer are electrically and mechanically coupled by interconnects having a pitch of less than 10 micrometers between adjacent interconnects, and the IC die comprises capacitors of a PDN in the microelectronic assembly.

(26) In some embodiments, the interconnects between adjacent layers are distributed with silicon-level interconnect density. As used herein, the term "silicon-level" interconnect density comprises

interconnect density greater than 10,000 connections per square millimeter. The term refers to trace pitch and/or via density that is generally found within an IC die (e.g., in metallization stacks of the IC die above the active region) as opposed to interconnect density between IC dies of older packaging technologies (e.g., solder-based C4 or larger interconnects). Interconnects with silicon-level interconnect density may have pitch ranging between 0.5 micrometer and 10 micrometers (i.e., in one embodiment, the interconnects may have a pitch of 0.5 micrometer; in another embodiment, the interconnects may have a pitch of 2 micrometer; etc.).

(27) Embodiments of the present disclosure also provide an IC package comprising: a package substrate in a first layer; a first IC die in a second layer between the first layer and a third layer; and a second IC die and a third IC die in the third layer. The first IC die comprises capacitors, the first IC die electrically couples the second IC die and the third IC die, and the second layer and the third layer are electrically coupled by interconnects having a pitch of less than 10 micrometers between adjacent interconnects.

(28) Embodiments of the present disclosure further provide an IC structure comprising: a metallization stack comprising a plurality of metal layers having conductive routing separated by an interlayer dielectric (ILD), the metal layers electrically coupled by conductive vias through the ILD; an inorganic substrate proximate to the metallization stack; a plurality of capacitors; and interconnects having a pitch of less than 10 micrometers proximate to the metallization stack. The IC structure is coupled by the interconnects in a multi-layered structure comprising IC dies distributed in several layers, and at least some IC dies in the multi-layered structure is surrounded by a dielectric and through-dielectric vias (TDVs).

(29) Each of the structures, assemblies, packages, methods, devices, and systems of the present disclosure may have several innovative aspects, no single one of which is solely responsible for all the desirable attributes disclosed herein. Details of one or more implementations of the subject matter described in this specification are set forth in the description below and the accompanying drawings.

(30) In the following detailed description, various aspects of the illustrative implementations may be described using terms commonly employed by those skilled in the art to convey the substance of their work to others skilled in the art.

(31) The terms “circuit” and “circuitry” mean one or more passive and/or active electrical and/or electronic components that are arranged to cooperate with one another to provide a desired function. The terms also refer to analog circuitry, digital circuitry, hard wired circuitry, programmable circuitry, microcontroller circuitry and/or any other type of physical hardware electrical and/or electronic component.

(32) The term “integrated circuit” means a circuit that is integrated into a monolithic semiconductor or analogous material.

(33) In some embodiments, the IC dies disclosed herein may comprise substantially monocrystalline semiconductors, such as silicon or germanium, as a base material on which integrated circuits are fabricated with traditional semiconductor processing methods. The semiconductor base material may include, for example, N-type or P-type materials. Dies may include, for example, a crystalline base material formed using a bulk silicon (or other bulk semiconductor material) or a semiconductor-on-insulator (SOI, e.g., a silicon-on-insulator) structure. In some other embodiments, the base material of one or more of the IC dies may comprise alternate materials, which may or may not be combined with silicon, that include but are not limited to germanium, indium antimonide, silicon carbide, lead telluride, indium arsenide, indium phosphide, gallium arsenide, indium gallium arsenide, gallium antimonide, or other combinations of group III-N, group III-V, group II-VI, or group IV materials. In yet other embodiments, the base material may comprise compound semiconductors, for example, with a first sub-lattice of at least one element from group III of the periodic table (e.g., Al, Ga, In), and a second sub-lattice of at least one element of group V of the periodic table (e.g., P, As, Sb). In yet

other embodiments, the base material may comprise an intrinsic IV or III-V semiconductor material or alloy, not intentionally doped with any electrically active impurity; in alternate embodiments, nominal impurity dopant levels may be present. In still other embodiments, dies may comprise a non-crystalline material, such as polymers; for example, the base material may comprise silica-filled epoxy. In other embodiments, the base material may comprise high mobility oxide semiconductor material, such as tin oxide, antimony oxide, indium oxide, indium tin oxide, titanium oxide, zinc oxide, indium zinc oxide, indium gallium zinc oxide (IGZO), gallium oxide, titanium oxynitride, ruthenium oxide, or tungsten oxide. In general, the base material may include one or more of tin oxide, cobalt oxide, copper oxide, antimony oxide, ruthenium oxide, tungsten oxide, zinc oxide, gallium oxide, titanium oxide, indium oxide, titanium oxynitride, indium tin oxide, indium zinc oxide, nickel oxide, niobium oxide, copper peroxide, IGZO, indium telluride, molybdenite, molybdenum diselenide, tungsten diselenide, tungsten disulfide, N- or P-type amorphous or polycrystalline silicon, germanium, indium gallium arsenide, silicon germanium, gallium nitride, aluminum gallium nitride, indium phosphide, and black phosphorus, each of which may possibly be doped with one or more of gallium, indium, aluminum, fluorine, boron, phosphorus, arsenic, nitrogen, tantalum, tungsten, and magnesium, etc. Although a few examples of the material for dies are described here, any material or structure that may serve as a foundation (e.g., base material) upon which IC circuits and structures as described herein may be built falls within the spirit and scope of the present disclosure.

(34) Unless described otherwise, IC dies described herein include one or more IC structures (or, simply, “ICs”) implementing (i.e., configured to perform) certain functionality. In one such example, the term “memory die” may be used to describe a die that includes one or more ICs implementing memory circuitry (e.g., ICs implementing one or more of memory devices, memory arrays, control logic configured to control the memory devices and arrays, etc.). In another such example, the term “compute die” may be used to describe a die that includes one or more ICs implementing logic/compute circuitry (e.g., ICs implementing one or more of input/output (I/O) functions, arithmetic operations, pipelining of data, etc.).

(35) In another example, the terms “package” and “IC package” are synonymous, as are the terms “die” and “IC die.” Note that the terms “chip,” “die,” and “IC die” are used interchangeably herein.

(36) The term “insulating” means “electrically insulating,” the term “conducting” means “electrically conducting,” unless otherwise specified. With reference to optical signals and/or devices, components and elements that operate on or using optical signals, the term “conducting” can also mean “optically conducting.”

(37) The terms “oxide,” “carbide,” “nitride,” etc. refer to compounds containing, respectively, oxygen, carbon, nitrogen, etc.

(38) The term “high-k dielectric” refers to a material having a higher dielectric constant than silicon oxide, while the term “low-k dielectric” refers to a material having a lower dielectric constant than silicon oxide.

(39) The term “insulating material” refers to solid materials (and/or liquid materials that solidify after processing as described herein) that are substantially electrically nonconducting. They may include, as examples and not as limitations, organic polymers and plastics, and inorganic materials such as ionic crystals, porcelain, glass, silicon and alumina or a combination thereof. They may include dielectric materials, high polarizability materials, and/or piezoelectric materials. They may be transparent or opaque without departing from the scope of the present disclosure. Further examples of insulating materials are underfills and molds or mold-like materials used in packaging applications, including for example, materials used in organic interposers, package supports and other such components.

(40) In various embodiments, elements associated with an IC may include, for example, transistors, diodes, power sources, resistors, capacitors, inductors, sensors, transceivers, receivers, antennas, etc. In various embodiments, elements associated with an IC may include those that are

monolithically integrated within an IC, mounted on an IC, or those connected to an IC. The ICs described herein may be either analog or digital and may be used in a number of applications, such as microprocessors, optoelectronics, logic blocks, audio amplifiers, etc., depending on the components associated with the IC. The ICs described herein may be employed in a single IC die or as part of a chipset for executing one or more related functions in a computer.

(41) In various embodiments of the present disclosure, transistors described herein may be field-effect transistors (FETs), e.g., metal-oxide semiconductor field-effect transistors (MOSFETs). In general, a FET is a three-terminal device that includes source, drain, and gate terminals and uses electric field to control current flowing through the device. A FET typically includes a channel material, a source region and a drain regions provided in and/or over the channel material, and a gate stack that includes a gate electrode material, alternatively referred to as a “work function” material, provided over a portion of the channel material (the “channel portion”) between the source and the drain regions, and optionally, also includes a gate dielectric material between the gate electrode material and the channel material.

(42) In a general sense, an “interconnect” refers to any element that provides a physical connection between two other elements. For example, an electrical interconnect provides electrical connectivity between two electrical components, facilitating communication of electrical signals between them; an optical interconnect provides optical connectivity between two optical components, facilitating communication of optical signals between them. As used herein, both electrical interconnects and optical interconnects are comprised in the term “interconnect.” The nature of the interconnect being described is to be understood herein with reference to the signal medium associated therewith. Thus, when used with reference to an electronic device, such as an IC that operates using electrical signals, the term “interconnect” describes any element formed of an electrically conductive material for providing electrical connectivity to one or more elements associated with the IC or/and between various such elements. In such cases, the term “interconnect” may refer to both conductive traces (also sometimes referred to as “lines,” “wires,” “metal lines” or “trenches”) and conductive vias (also sometimes referred to as “vias” or “metal vias”). Sometimes, electrically conductive traces and vias may be referred to as “conductive traces” and “conductive vias”, respectively, to highlight the fact that these elements include electrically conductive materials such as metals. Likewise, when used with reference to a device that operates on optical signals as well, such as a photonic IC (PIC), “interconnect” may also describe any element formed of a material that is optically conductive for providing optical connectivity to one or more elements associated with the PIC. In such cases, the term “interconnect” may refer to optical waveguides (e.g., structures that guide and confine light waves), including optical fiber, optical splitters, optical combiners, optical couplers, and optical vias.

(43) The term “conductive trace” may be used to describe an electrically conductive element isolated by an insulating material. Within IC dies, such insulating material comprises interlayer low-k dielectric that is provided within the IC die. Within package substrates, and PCBs such insulating material comprises organic materials such as Ajinomoto Buildup Film (ABF), polyimides, or epoxy resin. Such conductive lines are typically arranged in several levels, or several layers, of metallization stacks.

(44) The term “conductive via” may be used to describe an electrically conductive element that interconnects two or more conductive lines of different levels of a metallization stack. To that end, a via may be provided substantially perpendicularly to the plane of an IC die/chip or a support structure over which an IC structure is provided and may interconnect two conductive lines in adjacent levels or two conductive lines in non-adjacent levels.

(45) The term “metallization stack” may be used to refer to a stack of one or more interconnects for providing connectivity to different circuit components of an IC die/chip and/or a package substrate.

(46) In context of a stack of dies coupled to one another or in context of a die coupled to a package substrate, the term “interconnect” may also refer to, respectively, die-to-die (DTD) interconnects

and die-to-package substrate (DTPS) interconnects.

(47) Although not specifically shown in all of the present illustrations in order to not clutter the drawings, when DTD or DTPS interconnects are described, a surface of a first die may include a first set of conductive contacts, and a surface of a second die or a package substrate may include a second set of conductive contacts. One or more conductive contacts of the first set may then be electrically and mechanically coupled to some of the conductive contacts of the second set by the DTD or DTPS interconnects.

(48) In some embodiments, the pitch of the DTD interconnects may be different from the pitch of the DTPS interconnects, although, in other embodiments, these pitches may be substantially the same.

(49) The DTPS interconnects disclosed herein may take any suitable form. In some embodiments, a set of DTPS interconnects may include solder (e.g., solder bumps or balls that are subject to a thermal reflow to form the DTPS interconnects). DTPS interconnects that include solder may include any appropriate solder material, such as lead/tin, tin/bismuth, eutectic tin/silver, ternary tin/silver/copper, eutectic tin/copper, tin/nickel/copper, tin/bismuth/copper, tin/indium/copper, tin/zinc/indium/bismuth, or other alloys. In some embodiments, a set of DTPS interconnects may include an anisotropic conductive material, such as an anisotropic conductive film or an anisotropic conductive paste. An anisotropic conductive material may include conductive materials dispersed in a non-conductive material. In some embodiments, an anisotropic conductive material may include microscopic conductive particles embedded in a binder or a thermoset adhesive film (e.g., a thermoset biphenyl-type epoxy resin, or an acrylic-based material). In some embodiments, the conductive particles may include a polymer and/or one or more metals (e.g., nickel or gold). For example, the conductive particles may include nickel-coated gold or silver-coated copper that is in turn coated with a polymer. In another example, the conductive particles may include nickel. When an anisotropic conductive material is uncompressed, there may be no conductive pathway from one side of the material to the other. However, when the anisotropic conductive material is adequately compressed (e.g., by conductive contacts on either side of the anisotropic conductive material), the conductive materials near the region of compression may contact each other so as to form a conductive pathway from one side of the film to the other in the region of compression.

(50) The DTD interconnects disclosed herein may take any suitable form. In some embodiments, some, or all of the DTD interconnects in a microelectronic assembly or an IC package as described herein may be metal-to-metal interconnects (e.g., copper-to-copper interconnects, or plated interconnects). In such embodiments, the conductive contacts on either side of the DTD interconnect may be bonded together (e.g., under elevated pressure and/or temperature) without the use of intervening solder or an anisotropic conductive material. In some metal-to-metal interconnects, a dielectric material (e.g., silicon oxide, silicon nitride, silicon carbide) may be present between the metals bonded together (e.g., between copper pads or posts that provide the associated conductive contacts). In some embodiments, one side of a DTD interconnect may include a metal pillar (e.g., a copper pillar), and the other side of the DTD interconnect may include a metal contact (e.g., a copper contact) recessed in a dielectric. In some embodiments, some of all of the DTD interconnects may include hybrid bonds (e.g., metal-to-metal and oxide-to-oxide bonds), also called hybrid direct bonds, or direct bond interconnects. In some embodiments, a metal-to-metal interconnect (e.g., a copper-to-copper interconnect) may include a noble metal (e.g., gold) or a metal whose oxides are conductive (e.g., silver). In some embodiments, a metal-to-metal interconnect may include metal nanostructures (e.g., nanorods) that may have a reduced melting point. Metal-to-metal interconnects may be capable of reliably conducting a higher current than other types of interconnects; for example, some solder interconnects may form brittle intermetallic compounds when current flows, and the maximum current provided through such interconnects may be constrained to mitigate mechanical failure.

(51) In some embodiments, the dies on either side of a set of DTD interconnects may be

unpackaged dies.

(52) In some embodiments, the DTD interconnects may include solder. For example, the DTD interconnects may include conductive bumps or pillars (e.g., copper bumps or pillars) attached to the respective conductive contacts by solder. In some embodiments, a thin cap of solder may be used in a metal-to-metal interconnect to accommodate planarity, and this solder may become an intermetallic compound during processing. In some embodiments, the solder used in some or all of the DTD interconnects may have a higher melting point than the solder included in some or all of the DTPS interconnects. For example, when the DTD interconnects in an IC package are formed before the DTPS interconnects are formed, solder-based DTD interconnects may use a higher-temperature solder (e.g., with a melting point above 200 degrees Celsius), while the DTPS interconnects may use a lower-temperature solder (e.g., with a melting point below 200 degrees Celsius). In some embodiments, a higher-temperature solder may include tin; tin and gold; or tin, silver, and copper (e.g., 96.5% tin, 3% silver, and 0.5% copper). In some embodiments, a lower-temperature solder may include tin and bismuth (e.g., eutectic tin bismuth), tin, silver, bismuth, indium, indium and tin, or gallium.

(53) In some embodiments, a set of DTD interconnects may include an anisotropic conductive material, such as any of the materials discussed above for the DTPS interconnects. In some embodiments, the DTD interconnects may be used as data transfer lanes, while the DTPS interconnects may be used for power and ground lines, among others.

(54) In microelectronic assemblies or IC packages as described herein, some or all of the DTD interconnects may have a finer pitch than the DTPS interconnects. In some embodiments, the DTPS interconnects disclosed herein may have a pitch between about 80 microns and 300 microns, while the DTD interconnects disclosed herein may have a pitch between about 0.5 microns and 100 microns. In some embodiments, the DTD interconnects may have too fine a pitch to couple to the package substrate directly (e.g., too fine to serve as DTPS interconnects). The DTD interconnects may have a smaller pitch than the DTPS interconnects due to the greater similarity of materials in the different dies on either side of a set of DTD interconnects than between a die and a package substrate on either side of a set of DTPS interconnects. In particular, the differences in the material composition of dies and package substrates may result in differential expansion and contraction of the die dies and package substrates due to heat generated during operation (as well as the heat applied during various manufacturing operations). To mitigate damage caused by this differential expansion and contraction (e.g., cracking, solder bridging, etc.), the DTPS interconnects in any of the microelectronic assemblies or IC packages as described herein may be formed larger and farther apart than DTD interconnects, which may experience less thermal stress due to the greater material similarity of the pair of dies on either side of the DTD interconnects.

(55) It will be recognized that one or more levels of underfill (e.g., organic polymer material such as benzotriazole, imidazole, polyimide, or epoxy) may be provided in an IC package described herein and may not be labeled in order to avoid cluttering the drawings. In various embodiments, the levels of underfill may comprise the same or different insulating materials. In some embodiments, the levels of underfill may comprise thermoset epoxies with silicon oxide particles; in some embodiments, the levels of underfill may comprise any suitable material that can perform underfill functions such as supporting the dies and reducing thermal stress on interconnects. In some embodiments, the choice of underfill material may be based on design considerations, such as form factor, size, stress, operating conditions, etc.; in other embodiments, the choice of underfill material may be based on material properties and processing conditions, such as cure temperature, glass transition temperature, viscosity, and chemical resistance, among other factors; in some embodiments, the choice of underfill material may be based on both design and processing considerations.

(56) In some embodiments, one or more levels of solder resist (e.g., epoxy liquid, liquid photoimageable polymers, dry film photoimageable polymers, acrylics, solvents) may be provided

in an IC package described herein and may not be labeled or shown to avoid cluttering the drawings. Solder resist may be a liquid or dry film material including photo-imageable polymers. In some embodiments, solder resist may be non-photo-imageable.

(57) The terms “substantially,” “close,” “approximately,” “near,” and “about,” generally refer to being within $\pm 20\%$ of a target value (e.g., within $\pm 5\%$ or 10% of a target value) based on the context of a particular value as described herein or as known in the art.

(58) Terms indicating orientation of various elements, e.g., “coplanar,” “perpendicular,” “orthogonal,” “parallel,” or any other angle between the elements, generally refer to being within $\pm 5\%$ – 20% of a target value based on the context of a particular value as described herein or as known in the art.

(59) The term “connected” means a direct connection (which may be one or more of a mechanical, electrical, and/or thermal connection) between the things that are connected, without any intermediary devices, while the term “coupled” means either a direct connection between the things that are connected, or an indirect connection through one or more passive or active intermediary devices.

(60) The description uses the phrases “in an embodiment” or “in embodiments,” which may each refer to one or more of the same or different embodiments.

(61) Furthermore, the terms “comprising,” “including,” “having,” and the like, as used with respect to embodiments of the present disclosure, are synonymous.

(62) The disclosure may use perspective-based descriptions such as “above,” “below,” “top,” “bottom,” and “side”; such descriptions are used to facilitate the discussion and are not intended to restrict the application of disclosed embodiments.

(63) The terms “over,” “under,” “between,” and “on” as used herein refer to a relative position of one material layer or component with respect to other layers or components. For example, one layer disposed over or under another layer may be directly in contact with the other layer or may have one or more intervening layers. Moreover, one layer disposed between two layers may be directly in contact with one or both of the two layers or may have one or more intervening layers. In contrast, a first layer described to be “on” a second layer refers to a layer that is in direct contact with that second layer. Similarly, unless explicitly stated otherwise, one feature disposed between two features may be in direct contact with the adjacent features or may have one or more intervening layers.

(64) The term “dispose” as used herein refers to position, location, placement, and/or arrangement rather than to any particular method of formation.

(65) The term “between,” when used with reference to measurement ranges, is inclusive of the ends of the measurement ranges.

(66) For the purposes of the present disclosure, the phrase “A and/or B” means (A), (B), or (A and B). For the purposes of the present disclosure, the phrase “A, B, and/or C” means (A), (B), (C), (A and B), (A and C), (B and C), or (A, B, and C). When used herein, the notation “A/B/C” means (A), (B), and/or (C).

(67) Although certain elements may be referred to in the singular herein, such elements may include multiple sub-elements. For example, “an electrically conductive material” may include one or more electrically conductive materials. In another example, “a dielectric material” may include one or more dielectric materials.

(68) Unless otherwise specified, the use of the ordinal adjectives “first,” “second,” and “third,” etc., to describe a common object, merely indicate that different instances of like objects are being referred to and are not intended to imply that the objects so described must be in a given sequence, either temporally, spatially, in ranking or in any other manner.

(69) In the following detailed description, reference is made to the accompanying drawings that form a part hereof, and in which is shown, by way of illustration, embodiments that may be practiced. It is to be understood that other embodiments may be utilized, and structural or logical

changes may be made without departing from the scope of the present disclosure. Therefore, the following detailed description is not to be taken in a limiting sense.

(70) The accompanying drawings are not necessarily drawn to scale.

(71) In the drawings, same reference numerals refer to the same or analogous elements/materials shown so that, unless stated otherwise, explanations of an element/material with a given reference numeral provided in context of one of the drawings are applicable to other drawings where element/materials with the same reference numerals may be illustrated. Further, the singular and plural forms of the labels may be used with reference numerals to denote a single one and multiple ones respectively of the same or analogous type, species, or class of element.

(72) Furthermore, in the drawings, some schematic illustrations of example structures of various devices and assemblies described herein may be shown with precise right angles and straight lines, but it is to be understood that such schematic illustrations may not reflect real-life process limitations which may cause the features to not look so “ideal” when any of the structures described herein are examined using, e.g., images of suitable characterization tools such as scanning electron microscopy (SEM) images, transmission electron microscope (TEM) images, or non-contact profilometer. In such images of real structures, possible processing and/or surface defects could also be visible, e.g., surface roughness, curvature or profile deviation, pit or scratches, not-perfectly straight edges of materials, tapered vias or other openings, inadvertent rounding of corners or variations in thicknesses of different material layers, occasional screw, edge, or combination dislocations within the crystalline region(s), and/or occasional dislocation defects of single atoms or clusters of atoms. There may be other defects not listed here but that are common within the field of device fabrication and/or packaging.

(73) In the drawings, a particular number and arrangement of structures and components are presented for illustrative purposes and any desired number or arrangement of such structures and components may be present in various embodiments.

(74) Further, unless otherwise specified, the structures shown in the figures may take any suitable form or shape according to material properties, fabrication processes, and operating conditions.

(75) For convenience, if a collection of drawings designated with different letters are present (e.g., FIGS. **10A-10C**), such a collection may be referred to herein without the letters (e.g., as “FIG. **10**”). Similarly, if a collection of reference numerals designated with different letters are present (e.g., **110a-110e**), such a collection may be referred to herein without the letters (e.g., as “**110**”).

(76) Various operations may be described as multiple discrete actions or operations in turn in a manner that is most helpful in understanding the claimed subject matter. However, the order of description should not be construed as to imply that these operations are necessarily order dependent. In particular, these operations may not be performed in the order of presentation. Operations described may be performed in a different order from the described embodiment. Various additional operations may be performed, and/or described operations may be omitted in additional embodiments.

Example Embodiments

(77) FIG. **1A** is a simplified top view of a microelectronic assembly **100** according to some embodiments of the present disclosure. Microelectronic assembly **100** comprises layers **102** and **104** having capacitor-die **106** (singly “capacitor-die **106**” and collectively “capacitor-dies **106**”) and IC dies **108** (singly “IC die **108**” and collectively “IC dies **108**”), respectively. Capacitor-die **106** comprises an IC die having capacitors therein as described further. Although only few layers and IC dies are shown in the figure, it may be understood that microelectronic assembly **100** may comprise multiple such layers with multiple such IC dies therein. Capacitor-die **106** in layer **102** electrically couples at least two adjacent IC dies **108** in layer **104** along their proximate edges. In some embodiments, capacitor-die **106** functions as a bridge die, providing routing resources with silicon-level interconnection density to enable signals to travel between IC dies **108**. In some other embodiments, capacitor-die **106** functions as more than a bridge die, providing additional

functionalities, such as voltage regulation, for IC dies **108** in layer **104**.

(78) Layers **102** and **104** are electrically and mechanically coupled by DTD interconnects **110** having a pitch of less than 10 micrometers along a common interface **112**. In some embodiments (e.g., as shown), DTD interconnects **110** may be disposed only between interconnected IC dies (e.g., capacitor-die **106** and IC dies **108**); in other embodiments (not shown), DTD interconnects **110** may be disposed all along interface **112**. Layer **102** (and in some embodiments, other layers, such as layer **104**) may comprise a dielectric material **114** surrounding capacitor-die **106** therein. TDVs **116** may be disposed in dielectric material **114** suitably, for example, to enable power delivery directly from a package substrate **120** to IC dies **108** in layer **104**.

(79) In some embodiments, dielectric material **114** may comprise inorganic materials (e.g., silicon oxide, silicon carbonitride, silicon oxynitride, silicon nitride). In other embodiments, dielectric material **114** may comprise organic materials (e.g., mold compound, polyimide, epoxy resin). In such embodiments, TDVs **116** may also be referred to as through-mold vias (TMVs) where the material is mold compound. Although dielectric material **114** and TDVs **116** are shown in reference to layer **102**, any other such layer in microelectronic assembly **100** may also comprise similar dielectric material **114** and TDVs **116**. In various embodiments, selection of the material for dielectric material **114** may be appropriately based on recursive re-implementation and hierarchical coupling of microelectronic assembly **100**. In some embodiments, dielectric material **114** may comprise silicon oxide, silicon nitride or other inorganic dielectric materials compatible with semiconductor manufacturing process. In some other embodiments, dielectric material **114** may alternatively comprise organic dielectric materials, such as polyimide materials, glass reinforced epoxy matrix materials, organic materials such as silica-filled epoxy, or a low-k or ultra-low-k dielectric (e.g., carbon-doped dielectrics, fluorine-doped dielectrics, porous dielectrics, organic polymeric dielectrics, photoimageable dielectrics, and/or benzocyclobutene-based polymers).

(80) Package substrate **120** may be coupled to layer **102** by DTPS interconnects **122**, which may comprise solder-based interconnections (as shown) or other types of interconnects as described previously. Although not shown so as not to clutter the drawings, one or more of layers **102** and **104** (and others where applicable) may comprise redistribution layers (RDL) comprising dielectric (e.g., polyimide, silicon oxide, silicon nitride) with electrical pathways therein to route or reroute between interconnects of a first pitch to interconnects of a different, second pitch. For example, such RDL may facilitate routing at an interface between layer **102** and **104** (e.g., to route between TDVs **116** in the respective layers).

(81) In some embodiments, package substrate **120** may comprise an organic substrate; in other embodiments, package substrate **120** may comprise an inorganic interposer (e.g., made of glass, ceramic or semiconductor materials). In some embodiments, package substrate **120** may comprise multiple layers of conductive traces embedded in one or more layers of organic dielectric. For example, package substrate **120** may comprise a laminate substrate with several layers of metal planes or traces that are interconnected to each other by through-hole plated vias, with input/output (I/O) routing planes on the top and bottom layers, while the inner layers are used as a ground and power plane. In yet other embodiments, package substrate **120** may comprise a composite of organic and inorganic materials, for example, with an embedded semiconductor die in an organic substrate. In some embodiments, package substrate **120** may comprise an inorganic interposer with active circuits therein; in other embodiments, package substrate **120** may comprise an inorganic interposer with no active circuits therein.

(82) In various embodiments, IC dies **108** may comprise an inorganic substrate **124**, for example, a semiconductor, and a metallization stack **126**, comprising a plurality of conductive metal routing separated by ILD and coupled by conductive vias in the ILD. Likewise, capacitor-die **106** may comprise an inorganic substrate **128** and a metallization stack **130** comprising a plurality of conductive metal routing separated by ILD and coupled by conductive vias in the ILD. Through-substrate vias (TSVs) **132** in substrate **128** may facilitate electrical coupling between DTPS

interconnects **122** and interconnects **110** of capacitor-die **106**. In various embodiments, TSV **132** may have a diameter of 12 micrometers and be disposed with a pitch of 180 micrometers. In the example embodiment shown, capacitor-die **106** is coupled to IC dies **108** in a face-to-face (FTF) configuration; various other configuration, for example, face-to-back (FTB) or back-to-back (BTB) configurations may also be used within the broad scope of the embodiments depending on particular needs, with TSVs providing electrical coupling through the respective substrates as appropriate.

(83) According to various embodiments, capacitor-die **106** (also referred herein as capacitor-dies **106** in the plural) comprise capacitors **134**. In a general sense, DTD interconnects **110** with pitch less than 10 micrometers enables a shorter routing path between IC dies **108** through capacitor-die **106** than with interconnects having larger pitch. If the size of capacitor-die **106** is determined based only on the length of the routing path between IC dies **108**, then the resulting capacitor-die **106** may have a high aspect ratio (e.g., length-to-width ratio), causing difficulties in high-volume manufacturing, for example, in dicing, handling, etc. Hence, capacitor-dies **106** may be manufactured with greater width than is needed for bridging; such larger available area may be utilized for provisioning added functionalities, including capacitors **134**. Cost-wise, provisioning capacitors **134** in capacitor-die **106** in layer **102** may be preferable to added capacitance on IC dies **108** that are typically high-performance, active devices with various cost, process steps and temperature limitations.

(84) In some embodiments, capacitors **134** are part of a PDN in microelectronic assembly **100**. Note that capacitance of capacitors **134** in capacitor-die **106** is not the same as parasitic capacitance in a conductive pathway. Parasitic capacitance, or stray capacitance, is an unavoidable and unwanted capacitance that exists between conductive parts of an electronic circuit simply because of proximity to each other within an electric field. Such parasitic capacitance is uncontrolled and non-programmable. In contrast, capacitors **134** are controlled, configured, designed, programmed, etc. to be part of a PDN or other circuit in microelectronic assembly **100**.

(85) FIG. **1B** illustrates a portion **140** of a cross-section of capacitor-die **106** in greater detail. In some embodiments, capacitor-die **106** may include an active region **142** (also called in the art as front-end-of-line (FEOL)) between metallization stack **130** (also called in the art as back-end-of-line (BEOL)) and substrate **128**. Active region **142** comprises isolated transistors, diodes, and other active electronic components disposed over substrate **128**. In some embodiments, active region **142** may be absent, and metallization stack **130** may be disposed directly over substrate **128**.

(86) Metallization stack **130** may include various layers of conductive routing **146** and ILD **148** comprising ILD layers, the layers of conductive routing **146** electrically coupled by conductive vias through ILD **148**. Other materials or/and layers, not specifically shown in FIG. **1B** may also be provided as may be known to those skilled in the art. Electrical signals, such as power and/or input/output (I/O) signals, may be routed to and/or from logic circuit elements (e.g., the transistors) of active region **142** through one or more conductive interconnect layers situated in metallization stack **130** including conductive routing **146**, which may comprise one or more power grids (e.g., an arrangement of conductive lines, planes and vias, that is used to provide power), signal grids (e.g., an arrangement of conductive lines, planes and vias that is used to provide signals (e.g., data)), and/or ground grids (e.g., an arrangement of conductive lines, planes and vias that is used to provide ground connection).

(87) In some embodiments, conductive routing **146** may include lines and/or vias filled with an electrically conductive material such as aluminum or copper. The lines comprising conductive routing **146** may be arranged to route electrical signals in a direction of a plane that is substantially parallel with a surface of substrate **128**. For example, the lines may route electrical signals in a direction in and out of the page from the perspective of FIG. **1B**. Vias may be arranged to route electrical signals in a direction of a plane that is substantially perpendicular to the surface of substrate **128**. In some embodiments, the vias may electrically couple lines of different conductive

routing layers together.

(88) ILD layers of ILD **148** may be deposited over and in between conductive routing **146** of the metallization stack. The ILD layers may be formed using dielectric materials known for their applicability in IC structures, such as low-k dielectric materials. Examples of dielectric materials for ILD **148** include, but are not limited to, silicon dioxide (SiO_2), carbon-doped oxide (CDO), silicon nitride, organic polymers such as perfluorocyclobutane or polytetrafluoroethylene, fluorosilicate glass (FSG), and organosilicates such as silsesquioxane, siloxane, or organosilicate glass. The ILD layers may include pores or air gaps to further reduce their dielectric constant. Note that ILD **148** may comprise a homogeneous material, or a heterogeneous layered composite comprising more than one layer of material, or a heterogeneous matrix comprising a mixture of materials in any suitable arrangement known in the art.

(89) In various embodiments, TSV **132** may be disposed through active region **142** into portions of metallization stack **130**, providing a conductive pathway from DTPS interconnects **122** through capacitor-die **106**. TSV **132** may be electrically coupled to other components in capacitor-die **106**, for example, to a power grid or a ground grid as appropriate, or to DTD interconnects **110**. The electrical coupling may be achieved using suitable conductive routing **146**.

(90) In some embodiments (as shown), capacitor **134** may be situated in metallization stack **130**, with vias in conductive routing **146** coupling capacitor **134** with IC dies **108** as appropriate through interconnects **110**. In a general sense, the simplest type of capacitors consists of two overlapping parallel conductive plates separated by a dielectric. When a voltage difference is applied across the conductors, an electric field is created across the dielectric, which causes a positive charge to collect on one plate and a negative charge on the other plate. The capacitance (C) between the plates is a function of the area of the overlapping plates (A), the dielectric constant (E), and the distance (d) between the plates ($C=EA/d$); capacitance C is also the ratio of the electric charge (Q) on each conductor to the voltage difference (V) between them ($C=Q/V$). In various embodiments, capacitors **134**, including their type, number, and location may be chosen, disposed, and/or otherwise fabricated based on the desired capacitance in the circuitry in which they are used.

(91) In some embodiments, capacitor **134** may comprise a first electrode **150**, separated from a second electrode **152** by a dielectric material **154**. In various embodiments, first electrode **150** may be situated in one conductive routing layer in metallization stack **130** and second electrode **152** may be situated in an adjacent conductive routing layer in metallization stack **130**. In other embodiments, first electrode **150** may be situated in one conductive routing layer in metallization stack **130** and second electrode **152** may be situated in a non-adjacent conductive routing layer in metallization stack **130**. In some embodiments, dielectric material **154** may comprise the same material as ILD **148**; in other embodiments, dielectric material **154** may comprise a material different from ILD **148**.

(92) In some embodiments, dielectric material **154** may include a material such as tantalum and oxygen (e.g., in the form of tantalum oxide), zirconium and oxygen (e.g., in the form of zirconium oxide), hafnium and oxygen (e.g., in the form of hafnium oxide), or titanium and oxygen (e.g., in the form of titanium oxide), or silicon and oxygen (e.g., in the form of silicon oxide); or carbon along with silicon and oxygen (e.g., in the form of carbon-doped silicon oxide); or tantalum and nitrogen (e.g., in the form of tantalum nitride); or a polymer such as benzocyclobutene (BCB); or inorganic amorphous materials such as phosphorus glass (PSG) and fluorocarbon glass (FSG); or a combination of the above. In some embodiments, dielectric material **154** may include one or more layers of metal oxides (e.g., titanium oxide), for example, with layers having different dielectric constants. In some such embodiments, thickness of dielectric material **154** may be less than 100 nanometers. In some embodiments, dielectric material **154** may include an ultra-high-k material (e.g., a material having a dielectric constant greater than 120). In some such embodiments, dielectric material **154** may include barium, strontium, titanium, and oxygen (e.g., in the form of barium strontium titanate); or barium, titanium, and oxygen (e.g., in the form of barium titanate).

Dielectric material **154** may be fabricated using any suitable technique for integrated capacitors known in the art, such as physical vapor deposition (PVD), chemical vapor deposition (CVD), and spin-on deposition (SOD).

(93) Capacitor **134** may be disposed anywhere within capacitor-die **106** within the scope of the present disclosure. For example, in some embodiments, capacitor **134** may be disposed in metallization stack **130** closer to active region **142** than to DTD interconnects **110**; in other embodiments, capacitor **134** may be disposed in metallization stack **130** closer to DTD interconnects **110** than to active region **142**; in yet other embodiments, capacitor **134** may be disposed mid-way between active region **142** and DTD interconnects **110** in metallization stack **130**. In some embodiments, capacitor **134** may be disposed in active region **142**. In yet other embodiments, capacitor **134** may be disposed in substrate **128** proximate to DTPS interconnects **122**. In some embodiments where capacitor-die **106** comprises a plurality of capacitors **134**, some capacitors may be disposed in metallization stack **130** closer to DTD interconnects **110** than to active region **142**, some other capacitors **134** may be disposed in metallization stack **130** closer to active region **142** than to DTD interconnects **110**, yet other capacitors **134** may be disposed in active region **142** and still other capacitors **134** may be disposed in substrate **128**, or in any other combination of such locations, depending on the number of capacitors **134**, the functions or circuitry of which they are part, and other considerations based on particular needs.

(94) In some embodiments, capacitors **134** may comprise MIM capacitors or metal-oxide-metal (MOM) capacitors, fabricated using processes known in the art. In other embodiments, capacitors **134** may comprise other types of capacitors, such as deep-trench capacitors (DTC). Any suitable type of capacitor known in the art and fabricated in an IC die may be used within the broad scope of the embodiments. In some embodiments, capacitors **134** in metallization stack **130** may comprise interdigitated conductive fingers as electrodes **150** and **152** in some embodiments; in other embodiments, capacitors **134** may comprise uniform sheets of metal as electrodes **150** and **152**, punctured as needed for vias. In yet other embodiments, capacitors **134** may comprise corrugated conductors as electrodes **150** and **152**.

(95) As shown in FIG. 1C, capacitor **134** disposed in metallization stack **130** may comprise a corrugated shape, and in such embodiments, may be referred to as a “corrugated capacitor.” First electrode **150** may be electrically coupled to a power line, and second electrode **152** may be electrically coupled to a ground line in some embodiments, with dielectric material **154** comprising the same material as ILD **148**. Corrugated capacitors have larger surface area for a given footprint than corresponding plate capacitors because of the undulating corrugated shape of the electrodes. In some embodiments, at least one capacitor **134** in capacitor-die **106** may comprise a conventional plate capacitor, where first electrode **150** and second electrode **152** are comprised of relatively flat and parallel layers of conductive material, and at least another capacitor **134** in capacitor-die **106** may comprise a corrugated capacitor.

(96) As shown in FIG. 1D, capacitor **134** may comprise a DTC disposed in part of substrate **128**. In some embodiments, capacitor **134** comprising the DTC may be located in a region between metallization stack **130** and substrate **128** that does not comprise any active electronic components, such as diodes and transistors. In a general sense, the DTC known in the art is a three-dimensional vertical capacitor formed by etching a deep-trench into a silicon substrate, such as substrate **128**. An advantage of using DTCs over package decoupling capacitors is that they can be freely placed as close as possible to the desired active device in active region **142**. Additionally, DTCs may provide higher capacitance per unit area over other solutions such as a MIM capacitors. In capacitor **134** formed as a DTC, first electrode **150** may be coupled to conductive routing **146** coupled to a power grid and second electrode **152** may be coupled to conductive routing **146** coupled to a ground grid. In some embodiments, first electrode **150** and second electrode **152** may comprise different materials. For example, first electrode **150** may comprise arsenic-doped silicon, and second electrode **152** may comprise arsenic-doped polysilicon in some embodiments, with

dielectric material **154** comprising any suitable high-k dielectric known in the art. In another embodiment, both first electrode **150** and second electrode **152** may comprise polysilicon. In some embodiments, first electrode **150** may be formed in a trench **156** comprising N-type semiconductor in a P-type substrate **128** (or vice versa), permitting capacitor **134** to be highly proximate to an active device to which it is electrically coupled, for example, by way of conductive routing **146**. (97) Turning back to FIG. **1A**, such a quasi-monolithic hierarchical architecture as depicted in the figure allows IC dies of disparate manufacturing technologies (e.g., technology node, or process node, or simply node) to be coupled together seamlessly within microelectronic assembly **100**. In other words, microelectronic assembly **100** may allow heterogeneous integration. In a general sense, different processes often imply different circuit generations and architectures. Smaller (or more recent) the processing technology, smaller are the feature sizes, and consequently, the resulting transistors are both faster and more power efficient. For example, microelectronic assembly **100** may include IC die **108** manufactured using gallium nitride process, IC die **106** manufactured using 22 nm process and another IC die **108** manufactured using 45 nm process. (98) In some embodiments, one or more IC dies of microelectronic assembly **100** that are not constrained by any size limitations from any functional specifications may comprise any size, including ultra-small footprint less than 10 mm.^{sup.2}. In yet other embodiments, one or more IC dies in any layer except layer **202** may comprise other microelectronic assemblies, such as microelectronic assembly **100**, in a recursive (e.g., nested, hierarchical) arrangement. For example, capacitor-die **106** may comprise structures and components substantially similar to microelectronic assembly **100**. In yet other embodiments, one or more of the IC dies on any layer may comprise a plurality of semiconductor dies (e.g., IC dies) stacked one on top of another, electrically coupled with high-density DTD interconnects.

(99) FIG. **2** is a simplified cross-sectional view of a DTD interconnect **110** comprising a hybrid bond. The example applies to any DTD interconnect having pitch of less than 10 micrometers in the various embodiments disclosed herein. At interface **112** between layer **102** and layer **104**, conductive contact **222** of layer **102** (e.g., belonging to capacitor-die **106**) may bond with conductive contact **224** of layer **104** (e.g., belonging to IC die **108**); likewise, dielectric material **226** (e.g., silicon oxide, silicon nitride, silicon oxynitride, etc.) in layer **102** (e.g., belonging to capacitor-die **106**) may bond with dielectric material **228** (e.g., silicon oxide, silicon nitride, silicon oxynitride, etc.) in layer **104** (e.g., belonging to IC die **108**). The bonded interconnects form DTD interconnects **110**, comprising hybrid bonds, providing electrical and mechanical coupling between layer **102** and layer **104**.

(100) FIG. **3** is a simplified cross-sectional view of microelectronic assembly **100** according to various embodiments of the present disclosure. In the example embodiment shown, capacitor-die **106** may be coupled in a FTF configuration, with metallization stack **126** of IC die **108** proximate to metallization stack **130**. In some such embodiments, electrical pathways between IC dies **108** through capacitor-die **106** may be provisioned in a portion **302** of conductive routing **146** having a first pitch, and another portion **304** of conductive routing **146** may have a second pitch greater than the first pitch. For example, the first pitch may be 1 micrometer or smaller; the second pitch may be larger than 1 micrometer. In such embodiments, capacitor **134** may be provisioned in portion **304** having the second pitch. In the example embodiment shown, portion **302** is closer to interface **112** than portion **304**. In other embodiments, portion **302** may be farther from interface **112** than portion **304**.

(101) FIG. **4** is a simplified cross-sectional view of microelectronic assembly **100** according to various embodiments of the present disclosure. In the example embodiment shown, capacitor-die **106** may be coupled in a FTB configuration, with metallization stack **126** of IC die **108** distant from metallization stack **130** and proximate to package substrate **120**. In some such embodiments, electrical pathways between IC dies **108** through capacitor-die **106** may be provisioned through TSVs **132** and portion **302** of conductive routing **146** having the first pitch, which may be at a

different location in capacitor-die **106** than in embodiments with the FTF configuration between IC dies **108** and capacitor-die **106**, as shown in FIG. **3**. Capacitor **134** may be provisioned in portion **304** having the second pitch, which may be greater than the first pitch. In the example embodiment shown, portion **302** is closer to interface **112** than portion **304**. In other embodiments, portion **302** may be farther from interface **112** than portion **304**.

(102) In some embodiments, capacitors **134** may be disposed in capacitor-die **106** on both sides, for example, as shown in FIG. **3** and FIG. **4**. In such embodiments, a first set of capacitors **134** may be proximate to a first side of capacitor-die **106**, for example, the side coupled to IC dies **108** as in FIG. **3**; a second set of capacitors **134** may be proximate to a second side of capacitor-die **106** opposite to the first side, for example, the side coupled to package substrate **120** as in FIG. **4**. In some embodiments, the first set may support (e.g., operate at) a first voltage domain operating at a first voltage (e.g., 5V), and the second set may support a second voltage domain operating at a second voltage (e.g., 1.8V). Any number of voltages and corresponding voltage domains may be supported by different capacitors **134** in one or more capacitor-dies **106** in microelectronic assembly **100**.

(103) FIG. **5A** is a simplified cross-sectional view of a microelectronic assembly **100** according to various embodiments. Microelectronic assembly **100** comprises a layer **502** having IC dies **504** in addition to layers **102** and **104** as described in the embodiment of FIG. **1A**. Capacitor-dies **106** having capacitors **134** are in layer **102** and also in layers **104** and **502**. Further, IC dies **506** may be in layer **102** in addition to capacitor-die **106**. Any number of such layers and IC dies may be comprised in microelectronic assembly **100** within the broad scope of the embodiments. Each layer **102**, **104**, **502**, etc. may comprise dielectric material **114** and TDVs **116** therethrough. In some embodiments, the material of dielectric material **114** may be the same in all the layers; in other embodiments, the material of dielectric material **114** may be different.

(104) In various embodiments, each one of capacitor-die **106** may comprise a capacitor-die having no electronic components other than capacitors **134**. In some embodiments, capacitor-die **106** may also comprise on-die inductors with or without magnetic materials to enable improved process for power conversion efficiency, etc. In some embodiments, some of capacitor-dies **106** may also comprise voltage regulator circuitry (not shown so as not to clutter the drawings), whereas other capacitor-dies **106** may not comprise voltage regulator circuitry. In some embodiments, all capacitor-die **106** may comprise voltage regulator circuitry. In some embodiments, none of capacitor-die **106** having capacitors **134** may comprise voltage regulator circuitry.

(105) Capacitor-dies **106** comprising capacitors may be distributed laterally in any single layer (e.g., **102**), and vertically among the layers (e.g., **102**, **104**, **502**, etc.). Such placement of capacitor-dies **106** may help support high transient current for different kinds of workloads or provide additional capacitance for regulators that use capacitors.

(106) A top view of a plane **510** along axis **BB'** is shown in FIG. **5B**, illustrating example placement of capacitor-dies **106** comprising capacitors **134** in layer **102** of microelectronic assembly **100**. Note that the locations of capacitor-die **106** are shown merely for ease of explanation; capacitor-dies **106** may be provisioned anywhere in layer **102** (and other layers) based on particular needs. In some embodiments, capacitor-dies **106** may be provisioned as an array, for example, forming a capacitor array in any one layer (e.g., layer **102**).

(107) FIG. **6** is a schematic block diagram of an example PDN **600** in microelectronic assembly **100** according to various embodiments of the present disclosure. PDN **600** may comprise at least two voltage domains **602**: a first voltage domain **602(1)** operating at a first voltage **V1** (e.g., 5V, 7V, etc.) and a second voltage domain **602(2)** operating at a second voltage **V2** (e.g., 0.8V, 0.35V, etc.). A power supply **604** may supply power at first voltage **V1** to a voltage regulator **606**. Voltage regulator **606** may facilitate switching the voltage of the power from first voltage **V1** to second voltage **V2** of second voltage domain **602(2)** at which an IP core **608** (e.g., logic circuit, memory, etc.) operates. IP core **608** may be provisioned in any IC die in microelectronic assembly **100**, for

example, IC dies **108, 505, 506**, etc.

(108) Voltage regulator **606** may be provisioned in one or more of IC dies **108, 504, 506**, etc. In some embodiments, voltage regulator **606** may be provisioned in the same IC die as IP core **608**. In other embodiments, voltage regulator **606** may be provisioned in an IC die different from IP core **608**. In yet other embodiments, voltage regulator **606** may be provisioned in capacitor-die **106** having capacitors **134**. In various embodiments, voltage regulator **606** may comprise circuitry corresponding to low drop-out (LDO) regulator, switched capacitor regulator or buck regulator in different embodiments, depending on the relative voltage values of **V1** and **V2**, noise requirements, etc.

(109) A first set of capacitors **134(1)** in one or more capacitor-die **106** may comprise part of PDN **600** between power supply **604** and voltage regulator **606** in first voltage domain **602(1)**. A second set of capacitors **134(2)** in one or more capacitor-die **106** may comprise part of PDN **600** between voltage regulator **606** and IP core **608** in second voltage domain **602(2)**. In some embodiments, first set of capacitors **134(1)** and second set of capacitors **134(2)** may be provisioned in the same capacitor-die **106**. In other embodiments, first set of capacitors **134(1)** and second set of capacitors **134(2)** may be provisioned in different capacitor-dies **106** in the same layer (e.g., **102**). In yet other embodiments, first set of capacitors **134(1)** and second set of capacitors **134(2)** may be provisioned in different capacitor-dies **106** in different layers (e.g., capacitors **134(1)** in layer **102** and capacitors **134(2)** in layer **104**).

(110) FIG. 7 is a schematic block diagram of an example PDN **600** in microelectronic assembly **100** according to various embodiments of the present disclosure. PDN **600** may comprise at least three voltage domains **602**: first voltage domain **602(1)** operating at first voltage **V1** (e.g., >30V, 5V, 7V, etc.), second voltage domain **602(2)** operating at second voltage **V2** (e.g., 2V, 1.8V, etc.), and a third voltage domain **602(3)** operating at a third voltage **V3** (e.g., 0.8V, 0.35V, etc.). Power supply **604** may supply power at first voltage **V1** to first voltage regulator **606(1)**. Voltage regulator **606(1)** may change the voltage level of the power from first voltage **V1** to an intermediate third voltage **V3**. A second voltage regulator **606(2)** may change the voltage level of the power from third voltage **V3** to second voltage **V2** at which IP core **608** operates. In some embodiments, voltage regulators **606(1)** and **606(2)** may be part of a two-stage voltage regulator circuitry in PDN **600**. In other embodiments, voltage regulator **606(1)** and **606(2)** may be two separate voltage regulator circuitry in PDN **600**.

(111) Voltage regulators **606** (e.g., **606(1)**, **606(2)**) may be provisioned in one or more of IC dies **108, 504, 506**, etc. In some embodiments, voltage regulators **606** may be provisioned in the same IC die as IP core **608**. In other embodiments, voltage regulators **606** may be provisioned in an IC die different from IP core **608**. In yet other embodiments, voltage regulators **606** may be provisioned in capacitor-die **106** having capacitors **134**. In various embodiments, voltage regulators **606** may comprise circuitry corresponding to LDO regulator, switched capacitor regulator or buck regulator in different embodiments, depending on the relative voltage values of **V1** and **V2**, noise requirements, etc.

(112) First set of capacitors **134(1)** in one or more capacitor-die **106** may comprise part of PDN **600** between power supply **604** and first voltage regulator **606(1)**. Second set of capacitors **134(2)** in one or more capacitor-die **106** may comprise part of PDN **600** between second voltage regulator **606(2)** and IP core **608**. A third set of capacitors **134(3)** in one or more capacitor-die **106** may comprise part of PDN **600** between voltage regulators **606(1)** and **606(2)**. In some embodiments, first set of capacitors **134(1)**, second set of capacitors **134(2)**, and third set of capacitors **134(3)** may be provisioned in the same capacitor-die **106**. In other embodiments, first set of capacitors **134(1)**, second set of capacitors **134(2)** and third set of capacitors **134(3)** may be provisioned in different capacitor-dies **106** in the same layer (e.g., **102**). In yet other embodiments, first set of capacitors **134(1)**, second set of capacitors **134(2)**, and third set of capacitors **134(3)** may be provisioned in different capacitor-dies **106** in different layers (e.g., capacitor-die **134(1)** in layer

102 and capacitor-die **134(2)** in layer **104**).

(113) In some embodiments, voltage regulator **606(1)** may be provisioned in IC die **506** in layer **102**; voltage regulator **606(2)** may be provisioned in different IC die **108** in layer **104**; capacitors **134(1)**, **134(2)** and **134(3)** may be provisioned in capacitor-die **106** in layer **102**, and IP core **608** may be provisioned in IC die **504** in layer **502**. Various other combinations are also possible with different IC dies in microelectronic assembly **100** within the broad scope of the embodiments. For example, in some embodiments, voltage regulators **606(1)** and **606(2)** may be provisioned in the same capacitor-die **106** as capacitors **134(1)**, **134(2)** and **134(3)** in layer **102**; capacitor-die **106** may also function as a bridge die in some such embodiments, electrically coupling adjacent ones of IC dies **108** in layer **104**.

(114) FIG. **8** is a simplified block diagram illustrating example configurations **800** of microelectronic assembly **100**. Microelectronic assembly **100** comprises IP cores **608** and capacitor-dies **106**. In some embodiments, any one IP core, for example, IP core **608(1)** is coupled to multiple ones of the plurality of capacitor-dies, for example, **106(1)**, **106(2)**, and **106(3)**. In some embodiments, any one capacitor-die, for example, **106(3)** is coupled to multiple IP cores, for example, **608(2)** and **608(3)**. In some embodiments, any one IP core, for example, IP core **608(4)** is coupled to a separate one of one of the plurality of capacitor-dies, for example **106(4)**. Various other combinations of numbers and relationships are possible between IP cores **608** and capacitor-dies **106** comprising capacitors **134** based on the number of capacitors, voltage domains, IP cores, etc. within the broad scope of the embodiments.

(115) FIG. **9** is a simplified block diagram illustrating an example configuration **900** in microelectronic assembly **100** according to various embodiments. Capacitor-die **106** comprises a plurality of capacitors **134(1)**, **134(2)**, **134(3)** and **134(4)**. Any number of capacitors **134** may be provisioned in capacitor-die **106** within the broad scope of the embodiments. Numerous IP cores **608**, for example, **608(1)**, **608(2)**, **608(3)** and **608(4)** may be coupled to one or more capacitors **134** in capacitor-die **106** as described further. Any number of IP cores **608** may be provisioned in microelectronic assembly **100** without departing from the broad scope of the embodiments. In the example embodiment shown, any one IP core, for example, IP core **608(1)** is coupled to multiple ones of capacitors, for example, **134(1)**, and **134(2)**. In some embodiments, any one capacitor, for example, **134(3)** is coupled to multiple IP cores, for example, **608(2)** and **608(3)**. In some embodiments, any one IP core, for example, IP core **608(4)** is coupled to a separate one of the plurality of capacitors, for example **134(4)**. Various other combinations of numbers and relationships are possible between IP cores **608** and capacitors **134** based on the number of capacitors, voltage domains, IP cores, etc. within the broad scope of the embodiments.

(116) FIG. **10** is a simplified block diagram illustrating an example configuration **1000** in microelectronic assembly **100** according to various embodiments. Capacitor-die **106** comprises a plurality of capacitors **134(1)**, **134(2)**, and **134(3)**. Some capacitors, for example, **134(1)** and **134(2)** may support voltage domain **602(1)** operating at first voltage **V1**, and some other capacitors, for example, **134(3)** may support voltage domain **602(2)** operating at second voltage **V2**. Various other combinations of numbers and relationships are possible between voltage domains **602** and capacitors **134** based on the different operating voltages, capacitors, voltage regulators, etc. in microelectronic assembly **100**.

(117) FIG. **11** is a simplified top view of an example embodiment of microelectronic assembly **100** according to embodiments of the present disclosure. Capacitor-dies **106** comprising capacitors **134** may be arranged in a one-to-one, many-to-one, and one-to-many relationship as appropriate with IC dies **108**. IC dies **108** may comprise one or more IP cores (not shown), for example a processing element or memory. Some of capacitor-dies **106** may be provisioned in a one-to-one relationship with IC die **108**, with a single capacitor-die **106** providing capacitors used by IP cores in IC die **108**. Some capacitor-dies **106** may be shared among multiple ones of IC dies **108**. For example, four adjacent IC dies **108** may share a single capacitor-die **106**. In another example, three

successively adjacent IC dies **108** may share a single capacitor-die **106** that spans across such IC dies **108**. Various other combinations and configurations are possible within the broad scope of the embodiments. Although all the IC dies shown are IC dies **108**, it may be noted that in other embodiments, IC dies **506**, **508** etc., may also be provisioned suitably with capacitor-dies **106**, based on particular needs and other considerations.

(118) In various embodiments, any of the features discussed with reference to any of FIGS. **1-11** herein may be combined with any other features to form a package with one or more ICs as described herein, for example, to form a modified microelectronic assembly **100**. Some such combinations are described above, but, in various embodiments, further combinations and modifications are possible.

Example Devices and Components

(119) The packages disclosed herein, e.g., any of the embodiments shown in FIGS. **1-11** or any further embodiments described herein, may be included in any suitable electronic component. FIGS. **12-14** illustrate various examples of packages, assemblies, and devices that may be used with or include any of the IC packages as disclosed herein.

(120) FIG. **12** is a side, cross-sectional view of an example IC package **2200** that may include IC packages in accordance with any of the embodiments disclosed herein. In some embodiments, the IC package **2200** may be a system-in-package (SiP).

(121) As shown in the figure, package substrate **2252** may be formed of an insulator (e.g., a ceramic, a buildup film, an epoxy film having filler particles therein, etc.), and may have conductive pathways extending through the insulator between first face **2272** and second face **2274**, or between different locations on first face **2272**, and/or between different locations on second face **2274**. These conductive pathways may take the form of any of the interconnect structures comprising lines and/or vias.

(122) Package substrate **2252** may include conductive contacts **2263** that are coupled to conductive pathway **2262** through package substrate **2252**, allowing circuitry within dies **2256** and/or interposer **2257** to electrically couple to various ones of conductive contacts **2264** (or to other devices included in package substrate **2252**, not shown).

(123) IC package **2200** may include interposer **2257** coupled to package substrate **2252** via conductive contacts **2261** of interposer **2257**, first-level interconnects **2265**, and conductive contacts **2263** of package substrate **2252**. First-level interconnects **2265** illustrated in the figure are solder bumps, but any suitable first-level interconnects **2265** may be used, such as solder bumps, solder posts, or bond wires.

(124) IC package **2200** may include one or more dies **2256** coupled to interposer **2257** via conductive contacts **2254** of dies **2256**, first-level interconnects **2258**, and conductive contacts **2260** of interposer **2257**. Conductive contacts **2260** may be coupled to conductive pathways (not shown) through interposer **2257**, allowing circuitry within dies **2256** to electrically couple to various ones of conductive contacts **2261** (or to other devices included in interposer **2257**, not shown). First-level interconnects **2258** illustrated in the figure are solder bumps, but any suitable first-level interconnects **2258** may be used, such as solder bumps, solder posts, or bond wires. As used herein, a “conductive contact” may refer to a portion of electrically conductive material (e.g., metal) serving as an interface between different components; conductive contacts may be recessed in, flush with, or extending away from a surface of a component, and may take any suitable form (e.g., a conductive pad or socket).

(125) In some embodiments, underfill material **2266** may be disposed between package substrate **2252** and interposer **2257** around first-level interconnects **2265**, and mold **2268** may be disposed around dies **2256** and interposer **2257** and in contact with package substrate **2252**. In some embodiments, underfill material **2266** may be the same as mold **2268**. Example materials that may be used for underfill material **2266** and mold **2268** are epoxies as suitable. Second-level interconnects **2270** may be coupled to conductive contacts **2264**. Second-level interconnects **2270**

illustrated in the figure are solder balls (e.g., for a ball grid array (BGA) arrangement), but any suitable second-level interconnects **2270** may be used (e.g., pins in a pin grid array arrangement or lands in a land grid array arrangement). Second-level interconnects **2270** may be used to couple IC package **2200** to another component, such as a circuit board (e.g., a motherboard), an interposer, or another IC package, as known in the art and as discussed below with reference to FIG. **13**.

(126) In various embodiments, any of dies **2256** may be microelectronic assembly **100** as described herein. In embodiments in which IC package **2200** includes multiple dies **2256**, IC package **2200** may be referred to as a multi-chip package (MCP). Dies **2256** may include circuitry to perform any desired functionality. For example, besides one or more of dies **2256** being microelectronic assembly **100** as described herein, one or more of dies **2256** may be logic dies (e.g., silicon-based dies), one or more of dies **2256** may be memory dies (e.g., high-bandwidth memory), etc. In some embodiments, any of dies **2256** may be implemented as discussed with reference to any of the previous figures. In some embodiments, at least some of dies **2256** may not include implementations as described herein.

(127) Although IC package **2200** illustrated in the figure is a flip-chip package, other package architectures may be used. For example, IC package **2200** may be a BGA package, such as an embedded wafer-level ball grid array (eWLB) package. In another example, IC package **2200** may be a wafer-level chip scale package (WL CSP) or a panel fanout (FO) package. Although two dies **2256** are illustrated in IC package **2200**, IC package **2200** may include any desired number of dies **2256**. IC package **2200** may include additional passive components, such as surface-mount resistors, capacitors, and inductors disposed over first face **2272** or second face **2274** of package substrate **2252**, or on either face of interposer **2257**. More generally, IC package **2200** may include any other active or passive components known in the art.

(128) In some embodiments, no interposer **2257** may be included in IC package **2200**; instead, dies **2256** may be coupled directly to conductive contacts **2263** at first face **2272** by first-level interconnects **2265**.

(129) FIG. **13** is a cross-sectional side view of an IC device assembly **2300** that may include components having one or more microelectronic assembly **100** in accordance with any of the embodiments disclosed herein. IC device assembly **2300** includes a number of components disposed over a circuit board **2302** (which may be, e.g., a motherboard). IC device assembly **2300** includes components disposed over a first face **2340** of circuit board **2302** and an opposing second face **2342** of circuit board **2302**; generally, components may be disposed over one or both faces **2340** and **2342**. In particular, any suitable ones of the components of IC device assembly **2300** may include any of the one or more microelectronic assembly **100** in accordance with any of the embodiments disclosed herein; e.g., any of the IC packages discussed below with reference to IC device assembly **2300** may take the form of any of the embodiments of IC package **2200** discussed above with reference to FIG. **12**.

(130) In some embodiments, circuit board **2302** may be a PCB including multiple metal layers separated from one another by layers of insulator and interconnected by electrically conductive vias. Any one or more of the metal layers may be formed in a desired circuit pattern to route electrical signals (optionally in conjunction with other metal layers) between the components coupled to circuit board **2302**. In other embodiments, circuit board **2302** may be a non-PCB package substrate.

(131) As illustrated in the figure, in some embodiments, IC device assembly **2300** may include a package-on-interposer structure **2336** coupled to first face **2340** of circuit board **2302** by coupling components **2316**. Coupling components **2316** may electrically and mechanically couple package-on-interposer structure **2336** to circuit board **2302**, and may include solder balls (as shown), male and female portions of a socket, an adhesive, an underfill material, and/or any other suitable electrical and/or mechanical coupling structure.

(132) Package-on-interposer structure **2336** may include IC package **2320** coupled to interposer

2304 by coupling components **2318**. Coupling components **2318** may take any suitable form depending on desired functionalities, such as the forms discussed above with reference to coupling components **2316**. In some embodiments, IC package **2320** may be or include IC package **2200**, e.g., as described above with reference to FIG. **12**. In some embodiments, IC package **2320** may include at least one microelectronic assembly **100** as described herein. Microelectronic assembly **100** is not specifically shown in the figure in order to not clutter the drawing.

(133) Although a single IC package **2320** is shown in the figure, multiple IC packages may be coupled to interposer **2304**; indeed, additional interposers may be coupled to interposer **2304**. Interposer **2304** may provide an intervening package substrate used to bridge circuit board **2302** and IC package **2320**. Generally, interposer **2304** may redistribute a connection to a wider pitch or reroute a connection to a different connection. For example, interposer **2304** may couple IC package **2320** to a BGA of coupling components **2316** for coupling to circuit board **2302**.

(134) In the embodiment illustrated in the figure, IC package **2320** and circuit board **2302** are attached to opposing sides of interposer **2304**. In other embodiments, IC package **2320** and circuit board **2302** may be attached to a same side of interposer **2304**. In some embodiments, three or more components may be interconnected by way of interposer **2304**.

(135) Interposer **2304** may be formed of an epoxy resin, a fiberglass-reinforced epoxy resin, a ceramic material, or a polymer material such as polyimide. In some implementations, interposer **2304** may be formed of alternate rigid or flexible materials that may include the same materials described above for use in a semiconductor substrate, such as silicon, germanium, and other group III-V and group IV materials. Interposer **2304** may include metal interconnects **2308** and vias **2310**, including but not limited to TSVs **2306**. Interposer **2304** may further include embedded devices **2314**, including both passive and active devices. Such devices may include, but are not limited to, capacitors, decoupling capacitors, resistors, inductors, fuses, diodes, transformers, sensors, electrostatic discharge (ESD) devices, and memory devices. More complex devices such as radio frequency (RF) devices, power amplifiers, power management devices, antennas, arrays, sensors, and microelectromechanical systems (MEMS) devices may also be formed on interposer **2304**. Package-on-interposer structure **2336** may take the form of any of the package-on-interposer structures known in the art.

(136) In some embodiments, IC device assembly **2300** may include an IC package **2324** coupled to first face **2340** of circuit board **2302** by coupling components **2322**. Coupling components **2322** may take the form of any of the embodiments discussed above with reference to coupling components **2316**, and IC package **2324** may take the form of any of the embodiments discussed above with reference to IC package **2320**.

(137) In some embodiments, IC device assembly **2300** may include a package-on-package structure **2334** coupled to second face **2342** of circuit board **2302** by coupling components **2328**. Package-on-package structure **2334** may include an IC package **2326** and an IC package **2332** coupled together by coupling components **2330** such that IC package **2326** is disposed between circuit board **2302** and IC package **2332**. Coupling components **2328** and **2330** may take the form of any of the embodiments of coupling components **2316** discussed above, and IC packages **2326** and/or **2332** may take the form of any of the embodiments of IC package **2320** discussed above. Package-on-package structure **2334** may be configured in accordance with any of the package-on-package structures known in the art.

(138) FIG. **14** is a block diagram of an example computing device **2400** that may include one or more components having one or more IC packages in accordance with any of the embodiments disclosed herein. For example, any suitable ones of the components of computing device **2400** may include a microelectronic assembly (e.g., **100**) in accordance with any of the embodiments disclosed herein. In another example, any one or more of the components of computing device **2400** may include any embodiments of IC package **2200** (e.g., as shown in FIG. **12**). In yet another example, any one or more of the components of computing device **2400** may include an IC device

assembly **2300** (e.g., as shown in FIG. 13).

(139) A number of components are illustrated in the figure as included in computing device **2400**, but any one or more of these components may be omitted or duplicated, as suitable for the application. In some embodiments, some or all of the components included in computing device **2400** may be attached to one or more motherboards. In some embodiments, some or all of these components are fabricated onto a single system-on-chip (SOC) die.

(140) Additionally, in various embodiments, computing device **2400** may not include one or more of the components illustrated in the figure, but computing device **2400** may include interface circuitry for coupling to the one or more components. For example, computing device **2400** may not include a display device **2406**, but may include display device interface circuitry (e.g., a connector and driver circuitry) to which display device **2406** may be coupled. In another set of examples, computing device **2400** may not include an audio input device **2418** or an audio output device **2408**, but may include audio input or output device interface circuitry (e.g., connectors and supporting circuitry) to which audio input device **2418** or audio output device **2408** may be coupled.

(141) Computing device **2400** may include a processing device **2402** (e.g., one or more processing devices). As used herein, the term “processing device” or “processor” may refer to any device or portion of a device that processes electronic data from registers and/or memory to transform that electronic data into other electronic data that may be stored in registers and/or memory. Processing device **2402** may include one or more digital signal processors (DSPs), ASICs, CPUs, GPUs, crypto-processors (specialized processors that execute cryptographic algorithms within hardware), server processors, or any other suitable processing devices. Computing device **2400** may include a memory **2404**, which may itself include one or more memory devices such as volatile memory (e.g., dynamic random-access memory (DRAM)), nonvolatile memory (e.g., read-only memory (ROM)), flash memory, solid state memory, and/or a hard drive. In some embodiments, memory **2404** may include memory that shares a die with processing device **2402**. This memory may be used as cache memory and may include embedded dynamic random-access memory (eDRAM) or spin transfer torque magnetic random-access memory (STT-MRAM).

(142) In some embodiments, computing device **2400** may include a communication chip **2412** (e.g., one or more communication chips). For example, communication chip **2412** may be configured for managing wireless communications for the transfer of data to and from computing device **2400**. The term “wireless” and its derivatives may be used to describe circuits, devices, systems, methods, techniques, communications channels, etc., that may communicate data through the use of modulated electromagnetic radiation through a nonsolid medium. The term does not imply that the associated devices do not contain any wires, although in some embodiments they might not.

(143) Communication chip **2412** may implement any of a number of wireless standards or protocols, including but not limited to Institute for Electrical and Electronic Engineers (IEEE) standards including Wi-Fi (IEEE 802.11 family), IEEE 802.16 standards (e.g., IEEE 802.16-2005 Amendment), Long-Term Evolution (LTE) project along with any amendments, updates, and/or revisions (e.g., advanced LTE project, ultramobile broadband (UMB) project (also referred to as “3GPP2”), etc.). IEEE 802.16 compatible Broadband Wireless Access (BWA) networks are generally referred to as WiMAX networks, an acronym that stands for Worldwide Interoperability for Microwave Access, which is a certification mark for products that pass conformity and interoperability tests for the IEEE 802.16 standards. The communication chip **2412** may operate in accordance with a Global System for Mobile Communication (GSM), General Packet Radio Service (GPRS), Universal Mobile Telecommunications System (UMTS), High-Speed Packet Access (HSPA), Evolved HSPA (E-HSPA), or LTE network. The communication chip **2412** may operate in accordance with Enhanced Data for GSM Evolution (EDGE), GSM EDGE Radio Access Network (GERAN), Universal Terrestrial Radio Access Network (UTRAN), or Evolved UTRAN

(E-UTRAN). A communication chip **2412** may operate in accordance with Code Division Multiple Access (CDMA), Time Division Multiple Access (TDMA), Digital Enhanced Cordless Telecommunications (DECT), Evolution-Data Optimized (EV-DO), and derivatives thereof, as well as any other wireless protocols that are designated as 3G, 4G, 5G, and beyond. Communication chip **2412** may operate in accordance with other wireless protocols in other embodiments.

Computing device **2400** may include an antenna **2422** to facilitate wireless communications and/or to receive other wireless communications (such as AM or FM radio transmissions).

(144) In some embodiments, communication chip **2412** may manage wired communications, such as electrical, optical, or any other suitable communication protocols (e.g., the Ethernet). As noted above, communication chip **2412** may include multiple communication chips. For instance, a first communication chip **2412** may be dedicated to shorter-range wireless communications such as Wi-Fi or Bluetooth, and a second communication chip **2412** may be dedicated to longer-range wireless communications such as global positioning system (GPS), EDGE, GPRS, CDMA, WiMAX, LTE, EV-DO, or others. In some embodiments, a first communication chip **2412** may be dedicated to wireless communications, and a second communication chip **2412** may be dedicated to wired communications.

(145) Computing device **2400** may include battery/power circuitry **2414**. Battery/power circuitry **2414** may include one or more energy storage devices (e.g., batteries or capacitors) and/or circuitry for coupling components of computing device **2400** to an energy source separate from computing device **2400** (e.g., AC line power).

(146) Computing device **2400** may include a display device **2406** (or corresponding interface circuitry, as discussed above). Display device **2406** may include any visual indicators, such as a heads-up display, a computer monitor, a projector, a touchscreen display, a liquid crystal display (LCD), a light-emitting diode display, or a flat panel display, for example.

(147) Computing device **2400** may include audio output device **2408** (or corresponding interface circuitry, as discussed above). Audio output device **2408** may include any device that generates an audible indicator, such as speakers, headsets, or earbuds, for example.

(148) Computing device **2400** may include audio input device **2418** (or corresponding interface circuitry, as discussed above). Audio input device **2418** may include any device that generates a signal representative of a sound, such as microphones, microphone arrays, or digital instruments (e.g., instruments having a musical instrument digital interface (MIDI) output).

(149) Computing device **2400** may include a GPS device **2416** (or corresponding interface circuitry, as discussed above). GPS device **2416** may be in communication with a satellite-based system and may receive a location of computing device **2400**, as known in the art.

(150) Computing device **2400** may include other output device **2410** (or corresponding interface circuitry, as discussed above). Examples of other output device **2410** may include an audio codec, a video codec, a printer, a wired or wireless transmitter for providing information to other devices, or an additional storage device.

(151) Computing device **2400** may include other input device **2420** (or corresponding interface circuitry, as discussed above). Examples of other input device **2420** may include an accelerometer, a gyroscope, a compass, an image capture device, a keyboard, a cursor control device such as a mouse, a stylus, a touchpad, a bar code reader, a Quick Response (QR) code reader, any sensor, or a radio frequency identification (RFID) reader.

(152) Computing device **2400** may have any desired form factor, such as a handheld or mobile computing device (e.g., a cell phone, a smart phone, a mobile internet device, a music player, a tablet computer, a laptop computer, a netbook computer, an ultrabook computer, a personal digital assistant (PDA), an ultramobile personal computer, etc.), a desktop computing device, a server or other networked computing component, a printer, a scanner, a monitor, a set-top box, an entertainment control unit, a vehicle control unit, a digital camera, a digital video recorder, or a wearable computing device. In some embodiments, computing device **2400** may be any other

electronic device that processes data.

SELECT EXAMPLES

(153) The following paragraphs provide various examples of the embodiments disclosed herein.

(154) Example 1 provides a microelectronic assembly (e.g., **100**, FIG. **1A**), comprising: an IC die (e.g., **106**) in a first layer (e.g., **102**); and a plurality of IC dies (e.g., **108**) in a second layer (e.g., **104**), at least two adjacent IC dies in the plurality being coupled by conductive pathways in the IC die, in which: the first layer and the second layer are electrically and mechanically coupled by interconnects (e.g., **110**) having a pitch of less than 10 micrometers between adjacent interconnects, and the IC die comprises capacitors (e.g., **134**) and voltage regulator circuitry.

(155) Example 2 provides the microelectronic assembly of example 1, in which more than two adjacent IC dies in the plurality share the capacitors in the IC die.

(156) Example 3 provides the microelectronic assembly of any one of examples 1-2, in which: the first layer comprises a dielectric material (e.g., **114**) surrounding the IC die, and the first layer further comprises TDVs (e.g., **116**) in the dielectric material.

(157) Example 4 provides the microelectronic assembly of example 3, in which the dielectric material comprises an organic mold compound.

(158) Example 5 provides the microelectronic assembly of example 3, in which the dielectric material comprises a compound of silicon and at least one of oxygen, carbon, and nitrogen.

(159) Example 6 provides the microelectronic assembly of any one of examples 1-5, in which (e.g., FIGS. **6**, **7**): a first sub-set of the capacitors (e.g., **134(1)**) is configured to operate at a first voltage, a second sub-set of the capacitors (e.g., **134(2)**) is configured to operate at a second voltage, and the first voltage is higher than the second voltage.

(160) Example 7 provides the microelectronic assembly of example 6, in which: the first sub-set of capacitors is coupled to a first voltage regulator (e.g., **606(1)**), and the second sub-set of the capacitors is coupled to a second voltage regulator (e.g., **606(2)**).

(161) Example 8 provides the microelectronic assembly of any one of examples 1-7, in which the capacitors comprise metal-insulator-metal (MIM) capacitors embedded in a metallization stack of the IC die (e.g., FIG. **1B**).

(162) Example 9 provides the microelectronic assembly of any one of examples 1-7, in which the capacitors comprise corrugated capacitors embedded in a metallization stack of the IC die (e.g., FIG. **1C**).

(163) Example 10 provides the microelectronic assembly of any one of examples 1-7, in which the capacitors comprise DTC embedded in a substrate of the IC die (e.g., FIG. **1D**).

(164) Example 11 provides the microelectronic assembly of any one of examples 1-10, in which the capacitors comprise a capacitor array distributed in the IC die.

(165) Example 12 provides the microelectronic assembly of any one of examples 1-11, in which the capacitors comprise decoupling capacitors of a PDN.

(166) Example 13 provides the microelectronic assembly of any one of examples 1-12, in which (e.g., FIG. **5A**): the IC die in the first layer comprises a first IC die, and a second IC die in the second layer comprises other capacitors of the PDN.

(167) Example 14 provides the microelectronic assembly of example 13, in which (e.g., FIG. **5A**): the interconnects comprise first interconnects, and the microelectronic assembly further comprises a third layer (e.g., **502**) comprising a third IC die (e.g., **504**) having yet other capacitors of the PDN, the first layer and the third layer being electrically and mechanically coupled by second interconnects having a pitch of less than 10 micrometers between adjacent ones of the second interconnects.

(168) Example 15 provides the microelectronic assembly of example 14, in which the third layer is coupled to a package substrate.

(169) Example 16 provides an IC package, comprising: a package substrate (e.g., **120**) in a first layer; a first IC die (e.g., **106**) in a second layer (e.g., **102**); and a second IC die (e.g., **108**) and a

third IC die (e.g., **108**) in a third layer (e.g., **104**), in which: the second layer is between the first layer and the third layer, the first IC die comprises capacitors, conductive pathways in the first IC die couples the second IC die and the third IC die, and the second layer and the third layer are electrically and mechanically coupled by interconnects (e.g., **110**) having a pitch of less than 10 micrometers between adjacent interconnects.

(170) Example 17 provides the IC package of example 16, in which the second layer comprises a dielectric material with TDVs around the second IC die.

(171) Example 18 provides the IC package of any one of examples 16-17, further comprising a fourth layer between the first layer and the second layer, the fourth layer comprising a fourth IC die that includes other capacitors.

(172) Example 19 provides the IC package of example 18, in which the fourth layer comprises a dielectric material with TDVs around the fourth IC die.

(173) Example 20 provides the IC package of any one of examples 18-19, further comprising a fifth IC die in the third layer, the fifth IC die comprising further capacitors.

(174) Example 21 provides the IC package of any one of examples 16-20, in which the capacitors are in at least one of a metallization stack (e.g., **130**) and a substrate (e.g., **128**) of the first IC die.

(175) Example 22 provides the IC package of example 21, in which (e.g., FIG. 3): the metallization stack of the first IC die is proximate to the second IC die and the third IC die, and vias in the metallization stack of the first IC die are configured to electrically couple the capacitors to the second IC die and the third IC die.

(176) Example 23 provides the IC package of example 21, in which (e.g., FIG. 4): the metallization stack of the first IC die is proximate to the package substrate, and TSVs in the first IC die and vias in the metallization stack of the first IC die are configured to electrically couple the capacitors to the second IC die and the third IC die.

(177) Example 24 provides the IC package of any one of examples 21-23, in which the capacitors comprise at least one of: MIM capacitors and corrugated capacitors in the metallization stack.

(178) Example 25 provides the IC package of any one of examples 21-23, in which the capacitors comprise deep-trench capacitors in the substrate.

(179) Example 26 provides an IC structure, comprising (e.g., FIGS. 1A, 1B): a metallization stack (e.g., **130**) comprising a plurality of layers of conductive routing (e.g., **146**) separated by an ILD (e.g., **148**), the plurality of layers of conductive traces being coupled by conductive vias through the ILD; an inorganic substrate (e.g., **128**) proximate to the metallization stack; a plurality of capacitors (e.g., **134**); and interconnects (e.g., **110**) having a pitch of less than 10 micrometers proximate to the metallization stack, in which: the IC structure is coupled by the interconnects in a multi-layered structure (e.g., **100**) comprising IC dies distributed in several layers (e.g., **102**, **104**), and at least some IC dies in the multi-layered structure is surrounded by a dielectric material (e.g., **114**) and TDVs (e.g., **116**).

(180) Example 27 provides the IC structure of example 26, in which: the interconnects comprise a first set of interconnects, the IC structure further comprises a second set of interconnects distant from the metallization stack, and the second set of interconnects is coupled to the metallization stack by TSVs (e.g., **132**) through the inorganic substrate.

(181) Example 28 provides the IC structure of any one of examples 26-27, in which at least one of the capacitors comprises a MIM capacitor.

(182) Example 29 provides the IC structure of example 28, in which: a first portion of the metallization stack comprises first conductive traces having a first pitch between adjacent ones of the first conductive traces, a second portion of the metallization stack comprises second conductive traces having a second pitch between adjacent ones of the second conductive traces, the second pitch is larger than the first pitch, and the MIM capacitor is in the second portion.

(183) Example 30 provides the IC structure of any one of examples 26-29, in which: a first sub-set of the capacitors is configured to operate in a first voltage domain, the first sub-set of the capacitors

is proximate to a first side of the IC structure, a second sub-set of the capacitors is configured to operate in a second voltage domain, the second sub-set of the capacitors is proximate to a second side of the IC structure opposite to the first side, and the first voltage domain is configured to operate at a different voltage than the second voltage domain.

(184) Example 31 provides the IC structure of any one of examples 26-30, in which: a voltage regulation circuitry on one or more IC dies in the multi-layered structure is coupled to one or more of the plurality of capacitors, and the voltage regulation circuitry comprises at least one of a low drop-out regulator, a switched capacitor regulator and a buck regulator.

(185) Example 32 provides the IC structure of example 31, in which: the voltage regulation circuitry comprises at least two stages, a first stage is configured to convert from a first voltage to a second voltage, the first stage is in a first IC die in the multi-layered structure, a second stage is configured to convert from the second voltage to a third voltage, the second stage is in a second IC die in the multi-layered structure, and the first IC die and the second IC die are coupled to the plurality of capacitors in the IC structure.

(186) Example 33 provides the IC structure of any one of examples 26-32, in which at least one of the capacitors comprises a corrugated capacitor in the metallization stack.

(187) Example 34 provides the IC structure of any one of examples 26-32, in which: the inorganic substrate comprises a semiconductor material, and at least one of the capacitors comprises a deep-trench capacitor in the inorganic substrate.

(188) Example 35 provides the IC structure of any one of examples 26-34, in which: a first capacitor in the plurality of capacitors is configured to operate at a first voltage, and a second capacitor in the plurality of capacitors is configured to operate at a second voltage different from the first voltage.

(189) Example 36 provides a microelectronic assembly, comprising (e.g., FIG. 5A): a plurality of IC dies in a layer, a sub-set of the IC dies comprising IP cores; and a plurality of capacitor-dies (e.g., **106**) in one or more other layers, in which: adjacent layers are electrically and mechanically coupled by interconnects having a pitch of less than 10 micrometers between adjacent interconnects, and each capacitor-die in the plurality of capacitor-dies comprises an IC die having capacitors.

(190) Example 37 provides the microelectronic assembly of example 36 (e.g., FIG. 8), in which one of the IP cores (e.g., **608(4)**) is coupled to a separate one of the plurality of capacitor-dies (e.g., **106(4)**).

(191) Example 38 provides the microelectronic assembly of example 36 (e.g., FIG. 8), in which one of the IP cores (e.g., **608(1)**) is coupled to multiple ones of the plurality of capacitor-dies (e.g., **106(1)-106(3)**).

(192) Example 39 provides the microelectronic assembly of example 36 (e.g., FIG. 8), in which one of the capacitor-dies (e.g., **106(3)**) is coupled to multiple IP cores (e.g., **608(2)**, **608(3)**).

(193) Example 40 provides the microelectronic assembly of any one of examples 36-39, further comprising at least one capacitor-die in the layer.

(194) Example 41 provides the microelectronic assembly of any one of examples 36-40, in which: a first sub-set of the plurality of capacitor-dies is configured to operate at a first voltage, and a second sub-set of the plurality of capacitor-dies is configured to operate at a second voltage different from the first voltage.

(195) Example 42 provides the microelectronic assembly of any one of examples 36-41, in which: a first sub-set of capacitors in at least one capacitor-die is configured to operate at a first voltage, and a second sub-set of capacitors in the at least one capacitor-die is configured to operate at a second voltage different from the first voltage.

(196) Example 43 provides the microelectronic assembly of any one of examples 36-43, in which at least one of the one or more other layers comprises more than one capacitor-die.

(197) Example 44 provides the microelectronic assembly of any one of examples 36-43, in which:

the microelectronic assembly comprises two or more other layers, and the plurality of capacitor-dies is laterally and vertically distributed across the two or more other layers.

(198) Example 45 provides the microelectronic assembly of any one of examples 36-44, in which the capacitor-dies comprise no active devices, nor any passive components other than capacitors.

(199) The above description of illustrated implementations of the disclosure, including what is described in the abstract, is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. While specific implementations of, and examples for, the disclosure are described herein for illustrative purposes, various equivalent modifications are possible within the scope of the disclosure, as those skilled in the relevant art will recognize.

Claims

1. A microelectronic assembly, comprising: an integrated circuit (IC) die in a first layer; and a plurality of IC dies in a second layer, at least two adjacent IC dies in the plurality being coupled by conductive pathways in the IC die, wherein: the first layer and the second layer are coupled by interconnects, and the IC die comprises capacitors and voltage regulator circuitry.
2. The microelectronic assembly of claim 1, wherein: the first layer comprises a dielectric material at least partially surrounding the IC die, and the first layer further comprises through-dielectric vias (TDVs) in the dielectric material.
3. The microelectronic assembly of claim 2, wherein the dielectric material comprises a compound of silicon and at least one of oxygen, carbon, or nitrogen.
4. The microelectronic assembly of claim 1, wherein: a first sub-set of the capacitors is to operate at a first voltage, a second sub-set of the capacitors is to operate at a second voltage, and the first voltage is higher than the second voltage.
5. The microelectronic assembly of claim 4, wherein: the first sub-set of capacitors is coupled to a first voltage regulator, and the second sub-set of the capacitors is coupled to a second voltage regulator.
6. The microelectronic assembly of claim 1, wherein the capacitors comprise metal-insulator-metal (MIM) capacitors embedded in a metallization stack of the IC die.
7. The microelectronic assembly of claim 1, wherein the capacitors comprise corrugated capacitors embedded in a metallization stack of the IC die.
8. The microelectronic assembly of claim 1, wherein the capacitors comprise deep-trench capacitors (DTC) embedded in a substrate of the IC die.
9. The microelectronic assembly of claim 1, wherein the interconnects have a pitch of less than 10 micrometers between adjacent interconnects.
10. An IC package, comprising: a package substrate in a first layer; a first IC die in a second layer; a second IC die and a third IC die in a third layer; and a fourth IC die in a fourth layer, wherein: the second layer is between the first layer and the third layer, the fourth layer is between the first layer and the second layer, the first IC die includes capacitors, the fourth IC die includes other capacitors, conductive pathways in the first IC die couples the second IC die and the third IC die, and the second layer and the third layer are coupled by interconnects having a pitch of less than 10 micrometers between adjacent interconnects.
11. The IC package of claim 10, wherein the capacitors are in at least one of a metallization stack and a substrate of the first IC die.
12. The IC package of claim 11, wherein: the metallization stack of the first IC die is proximate to the second IC die and the third IC die, and vias in the metallization stack of the first IC die are to couple the capacitors to the second IC die and the third IC die.
13. The IC package of claim 11, wherein: the metallization stack of the first IC die is proximate to the package substrate, and through-substrate vias (TSVs) in the first IC die and vias in the metallization stack of the first IC die are to couple the capacitors to the second IC die and the third

IC die.

14. An IC structure, comprising: a metallization stack comprising a plurality of layers of conductive traces separated by a first dielectric material, and further comprising conductive vias in the first dielectric material; an inorganic substrate proximate to the metallization stack; a plurality of capacitors; and interconnects proximate to the metallization stack, wherein: the IC structure is coupled by the interconnects in a multi-layered structure comprising IC dies distributed in two or more layers, and at least one of the IC dies is surrounded by a second dielectric material and through-dielectric vias (TDVs) in the second dielectric material.

15. The IC structure of claim 14, wherein at least one of the capacitors comprises a metal-insulator-metal (MIM) capacitor.

16. The IC structure of claim 15, wherein: a first portion of the metallization stack comprises first conductive traces having a first pitch, a second portion of the metallization stack comprises second conductive traces having a second pitch, the second pitch is larger than the first pitch, and the MIM capacitor is in the second portion.

17. The IC structure of claim 14, wherein: a first sub-set of the capacitors is to operate at a first voltage, the first sub-set of the capacitors is proximate to a first side of the IC structure, a second sub-set of the capacitors is to operate at a second voltage, the second sub-set of the capacitors is proximate to a second side of the IC structure opposite to the first side, and the first voltage is different from the second voltage.

18. The IC structure of claim 14, wherein: a voltage regulation circuitry on one or more IC dies in the multi-layered structure is coupled to one or more of the plurality of capacitors, and the voltage regulation circuitry comprises at least one of a low drop-out regulator, a switched capacitor regulator and a buck regulator.

19. The IC structure of claim 18, wherein: the voltage regulation circuitry comprises at least two stages, a first stage is to convert from a first voltage to a second voltage, the first stage is in a first IC die in the multi-layered structure, a second stage is to convert from the second voltage to a third voltage, the second stage is in a second IC die in the multi-layered structure, and the first IC die and the second IC die are coupled to the plurality of capacitors in the IC structure.

20. The IC structure of claim 14, wherein the interconnects have a pitch of less than 10 micrometers.
