

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416182
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kim; Jeongkil et al.

Latch module and an appliance using the same

Abstract

A latch module incorporated with an automatic opening function and a secure lock function includes a latch, a spring that applies a force to move the latch in a first direction, a drive to move the latch in a second direction, a cam that transmits power of the drive to the latch, and first and second switches that are turned on and off by the cam. The first and second switches are in a first mode in which the two switches are turned on and the latch is disposed at a manual lock position, a second mode in which the first switch is turned on and the second switch is turned off and the latch is disposed at an opening position, a third mode in which the first switch is turned off and the second switch is turned on and the latch is in a secure lock position.

Inventors: Kim; Jeongkil (Seoul, KR), Shin; Myeong Jun (Seoul, KR), Shin; Jangmo (Seoul, KR), Jeong; Seongho (Seoul, KR)

Applicant: LG ELECTRONICS INC. (Seoul, KR)

Family ID: 1000008821694

Assignee: LG ELECTRONICS INC. (Seoul, KR)

Appl. No.: 17/990308

Filed: November 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230124655 A1	Apr. 20, 2023

Foreign Application Priority Data

KR	10-2018-0044152	Apr. 16, 2018
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **E05B47/00** (20060101); **E05B15/04** (20060101); **E05F1/04** (20060101); **E05F15/611** (20150101); **E05F15/70** (20150101)

U.S. Cl.:

CPC **E05B47/0001** (20130101); **E05B15/04** (20130101); **E05F1/043** (20130101); **E05F15/611** (20150115); **E05F15/70** (20150115); E05B2047/0024 (20130101)

Field of Classification Search

CPC: E05B (47/0001); E05B (47/023); E05B (2047/0024); E05B (17/0029); E05B (2015/0496); E05F (15/611); E05F (15/70); E05F (1/043); E04B (15/04); F24C (15/022); F24C (15/023); H05B (6/6414); Y10T (292/1082); Y10S (292/69)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4927996	12/1989	Genbauffe	126/197	F24C 15/022
5220153	12/1992	Malone	219/412	F24C 15/022
6079756	12/1999	Phillips	292/229	E05B 47/0002
6302098	12/2000	Smith	292/109	F24C 15/022
6315336	12/2000	Swartzell	292/201	E05B 47/0012
6698418	12/2003	Ramsey	219/398	F24C 15/022
7040673	12/2005	Smock	292/201	F24C 15/022
7156428	12/2006	Smith	292/201	F24C 15/022
7334823	12/2007	Courter	292/201	F24C 15/022
7556033	12/2008	Kim	292/201	F24C 15/022
8430089	12/2012	Kim et al.	N/A	N/A
11261634	12/2021	Shin	N/A	E05B 17/0029
2003/0041852	12/2002	Ramsey	219/398	F24C 15/022
2004/0011347	12/2003	Ramsey	126/192	F24C 15/022
2005/0121918	12/2004	Smock	292/109	E05B 17/0029
2005/0173932	12/2004	Lomicka	292/201	F24C 15/022
2005/0248163	12/2004	Kim	292/201	E05B 47/0012
2006/0001273	12/2005	Smith	292/204	F24C 15/022
2006/0090742	12/2005	Priest	126/192	F24C 15/022
2006/0201928	12/2005	Smith et al.	N/A	N/A
2006/0213898	12/2005	Beaudoin	N/A	N/A
2006/0232077	12/2005	Courter	292/201	F24C 15/022
2007/0296224	12/2006	Courter	292/109	E05C 19/10
2008/0271727	12/2007	Collene	126/197	F24C 15/022
2008/0305938	12/2007	Hayasaka	494/12	E05C 3/045
2013/0291337	12/2012	Vanini	16/287	E05F 1/1246

2019/0301203	12/2018	Shin	N/A	E05C 19/12
2019/0316400	12/2018	Shin	N/A	F24C 15/022
2019/0353353	12/2018	White	N/A	E05F 3/20
2021/0215346	12/2020	Jang	N/A	F24C 15/32

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
206091628	12/2016	CN	N/A
0632180	12/1994	EP	N/A
2927603	12/2014	EP	N/A
1020050081374	12/2004	KR	N/A
10-2009-0103293	12/2008	KR	N/A
WO 2013133774	12/2012	WO	N/A
2015150050	12/2014	WO	N/A

Primary Examiner: Mills; Christine M

Assistant Examiner: Sidky; Yahya

Attorney, Agent or Firm: Bryan Cave Leighton Paisner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a Divisional Application of U.S. patent application Ser. No. 16/384,388, filed on Apr. 15, 2019, which claims priority to and the benefit of Korean Patent Applications No. 10-2018-0044152 filed on Apr. 16, 2018, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

Field of the Disclosure

(1) The present disclosure relates to a latch module having an automatic opening function and a secure lock function incorporated therewith, a method of controlling such latch module, and a cooking device applying such latch module.

Background

(2) A cooking device such as an oven or a microwave oven includes a rectangular parallelepiped appearance. The cooking device includes an inner cooking chamber having an open front thereof, and a door in front of the cooking chamber.

(3) The door may be opened in various ways. For example, a hinge-connected door connected by a hinge method rotates about a rotational shaft. The hinge type door may have a handle or groove that the user may grip.

(4) A cooking device may have an automatic opening function of a door thereof to improve the quality of use. Of course, even if the automatic opening function of the door is applied, for convenience of the user, the door may be designed to be manually opened or closed.

(5) Further, a self-cleaning function is added to the cooking device so that the cooking chamber is easily cleaned. The self-cleaning function enables heating the inside of the cooking chamber to a high temperature so that food attached to an inner wall of the cooking chamber is burned, or treating the food attached to the inner wall of the cooking chamber with high-temperature steam, so that the food is softened and conveniently removed during cleaning. In order to prevent a safety accident, the door of the cooking device may be securely closed during a self-cleaning operation.

(6) U.S. Pat. No. 7,726,294 and US Patent Publication No. 2007/0296224 disclose an operating

structure of a hook for maintaining a door in a securely closed state during the self-cleaning operation. By rotating a drive such as a motor and the like, and applying a link structure, when the door needs to be maintained in a securely closed state, the hook is operated by the drive so that the hook is engaged with the door, and when the door no longer needs to be maintained in the securely closed state, the hook is operated again by the drive so that the hook is released from the door.

(7) With the operating structure of a hook described above, after the hook is released from the door, a door lock device enables closing the door and does not enable automatically opening the door. That is, the door lock device has no means for automatically opening the door.

(8) A secure (secure lock, self-cleaning lock) device that serves to securely lock the door during the self-cleaning operation and an automatic opening (auto door open) device that serves to automatically open the door may be applied individually. That is, U.S. Pat. No. 7,726,294 and US Patent Publication No. 2007/0296224 provide a drive (a motor) that provides power and a power transmission structure to securely lock the door, and another drive (another motor) that provides power and another power transmission structure to automatically open the door.

SUMMARY

(9) It is not easy to incorporate a secure lock function of a door for self-cleaning with a separate automatic opening function of the door when a manual opening and closing function of the door needs to be implemented as well.

(10) However, when new functions are added, the modules for implementing the functions are added individually, thereby increasing the number of components and production costs, as well as increasing the occupied volume in the cooking device, thereby decreasing the volume of the cooking chamber.

(11) It is desirable to have a module incorporated with various functions. However, in situations described above, when the module is incorporated with a safety function for preventing accidents, the function for preventing the accidents needs to be robust and reliable.

(12) Accordingly, a door control module capable of incorporating all functions as well as minimizing the number of parts, and having a safety function for preventing an accident is highly desirable.

(13) On the other hand, when the door control module is incorporated with various functions, the drive control also becomes complicated, and more switches for controlling the parts that drive the door control module may need to be installed. However, an increase in the number of installed switches not only increases an occupied volume in the door control module, but also raises production costs.

(14) Further, when the functions are incorporated, initializing the door control module is required when the cooking device is initially supplied with power. However, if the door control module does not have a proper initialization structure and operated, for example, the door may accidentally open automatically during initialization of the door control module, and the user may think that the cooking device is operating incorrectly or the cooking device has failed. Therefore, the door control module should not automatically open the door when the door control module is initialized.

(15) The present disclosure solves the above-mentioned problems. The present disclosure provides a latch module that implements a manual lock function of a door and a secure lock function of a door for self-cleaning operation of a cooking chamber with one latch and a cooking device applying such latch module.

(16) The present disclosure further provides a latch module that implements a manually opening and closing function of a door and an automatic opening function of a door and a secure lock function of a door by operating with one latch and a cooking device applying such latch module.

(17) The present disclosure also provides a latch module that implements a manually opening and closing function of a door and an automatic opening function of a door and a secure lock function of the door by operating with one latch with one drive source and one power transmission structure, and a cooking device applying such latch module.

(18) The present disclosure also provides a latch module that implements a secure lock and unlock function of a door by means of a kinematic interference between the two components while one latch implements the two functions and a cooking device applying such latch module.

(19) The present disclosure also provides a structure capable of accurately controlling a latch module while minimizing the number of switches to be installed, a method of controlling such latch module, and a cooking device applying such latch module.

(20) The present disclosure also provides a structure of a latch module in which a user may not mistakenly consider the operation of the cooking device as malfunctioning or failure at the beginning of the driving of the cooking device and a method of controlling such latch module.

(21) The present disclosure may be applied to an appliance such as a cooking device including a main body having a cooking chamber (a cavity), a door that opens and closes an open front of the cooking chamber, and an opening or closing rotational shaft as a center of rotation of opening and closing a movement of the door.

(22) The opening and closing rotational shaft rotatably connects the door with respect to the main body about a horizontal rotational shaft extending in a left-right direction and disposed at a front lower portion of the main body. Accordingly, the door may have a pull-down structure in which the door is rotated forward about the rotational shaft and descends and is opened.

(23) The door may be connected to the main body via a hinge module including the opening and closing rotational shaft. The hinge module may apply an elastic force so as to move the door in an opening direction in a range of initial opening angle and may apply an elastic force the door in a closing direction thereof in a range in which an opening angle of the door exceeds the initial opening angle.

(24) The door may be opened by its own weight at the initial opening angle. A damper starts to damp an opening speed of the door at a damping beginning angle greater than the initial opening angle. The opening speed is controlled until the door is opened to a completely opened angle so that the door is opened slowly.

(25) The cooking device may have a self-cleaning function of raising a temperature inside of the cooking chamber to a high temperature. Accordingly, the door is prevented from being opened in advance when the door is securely locked to perform the self-cleaning function.

(26) The cooking device may further apply a structure that automatically opens the door by means of command input by a user. Generally, the door also may be manually opened and closed.

(27) According to the present disclosure, all of these functions are implemented by one latch module. The latch module may be installed on the main body and a rear upper portion of the door may have a pin which is an engaged structure that is engaged with or released from a latch of the latch module. The position at which the latch may move may include a first basic position, a second basic position, and a third basic position.

(28) Each of the first basic position and the third basic position may be a position in which the latch is engaged with the engaging structure so as to maintain a state in which the door is closed.

(29) The second basic position may be a position in which the latch is not engaged with the engaging structure.

(30) The first basic position may be a position in which, when an external force is applied to the door in a direction of opening the door, the latch is released from the engaging structure so that the door is opened, while the third basic position may be a position in which, even if the external force is applied to the door in a direction of opening the door, a state in which the latch is engaged with the engaging structure is maintained.

(31) The latch may be moved to at least one position of the three positions by the controller. In other words, the controller may control the position of the latch.

(32) The hinge module may apply a force in a direction of opening the door at a position in which the door is closed. Thus, when the latch is in the second basic position, the door may be opened by the force of the hinge module.

(33) In order to solve the above-described problems, according to the present disclosure, the latch module may include a bracket as a base of the latch module; a latch installed in the bracket rotatable about a pivot shaft and having a hook engaged with the pin, an elastic body that moves the latch to rotate in a first direction; a drive that provides a power for rotating the latch in a second direction which is an opposite to the first direction using a force greater than an elastic force of the elastic body; and a power transmission that transmits the power of the drive to the latch.

(34) The hook is opened toward the first direction, and an engaging surface that is engaged with the pin is provided inside of the hook. An inclined insertion surface may be provided on a surface opposed to the engaging surface of the hook.

(35) The engaging surface includes a disengaged inclined surface arranged closer to the first direction and a secure lock surface arranged closer to the second direction. The two surfaces are connected to each other via a soft curved surface so that a sliding of a pin about the two surfaces is smooth.

(36) Depending on a rotation position of the latch, the portions of the engaging surface in contact with the pin are varied. The pin contacts the disengaged inclined surface or contacts the secure lock surface depending on the rotation position of the latch.

(37) In a general state, that is, in a manual lock state where the user may manually open and close the door, a rear surface of the pin of the door contacts the disengaged inclined surface when the door is closed. In order to allow the user to manually open the door, when the latch is rotated so as to be in a state in which the disengaged inclined surface contacts the pin, the disengaged inclined surface has a surface inclined in the opening direction of the door toward the first direction. When the user pulls the door in an opening direction thereof, the latch may rotate in the second direction by using a force in which the pin pushes the disengaged inclined surface, which is greater than the elastic force, and thereby the door may be manually opened.

(38) When the user closes the door in a state where the door is opened, the surface of the pin of the door contacts the inclined insertion surface. In order for the user to manually close the door, when the latch rotates so as to be in the state in which the inclined insertion surface contacts the pin, the inclined insertion surface has a surface inclined in the closing direction of the door toward the first direction.

(39) The inclined insertion surface may be provided not only in a position range opposed to the disengaged inclined surface but also in a position range opposed to the secure lock surface. It is possible to close the opened door regardless of whether the latch is in any position (the manual lock position and the secure lock position).

(40) In a general state, the elastic body is involved in the operation of the latch for a manual opening and closing operation.

(41) In a completely locked state where the user does not manually open the door for self-cleaning and the like, that is, in the secure lock state, the pin of the door contacts the secure lock surface. The latch is further rotated in the first direction than in the manual lock state and the pin of the door is relatively positioned deeply inward the hook (actually, the pin remains its position and the hook is further rotated).

(42) In order for the hook to completely securely lock the door, the secure lock surface may have a surface inclined in the closing direction of the door toward the first direction. Then, when the user pulls the door, a force applied by the pin of the door to the hook further rotates the hook in the first direction. That is, the more the user opens the door, the deeper the pin is positioned deeply inward the hook. In other words, the more the user opens the door, the more the hook securely locks the pin.

(43) Similar result is obtained if the secure lock surface has a surface perpendicular to the opening direction of the door. That is, even if the user opens the door, such force does not lead to the rotation of the latch.

(44) An elasticity of the elastic body contributes to rotate the latch from a manual lock position to a

secure lock position.

(45) As described above, according to the present disclosure, the engaging surface of the hook of the latch for opening and closing the door has a portion capable of manually opening and closing the door and a complete secure lock portion. It is possible to determine which one of the two portions contacts the pin of the door depending on a rotation displacement of the latch so that both the manual lock state and the secure lock state of the door may be implemented by one latch.

(46) The automatic opening operation of the door and the secure lock operation of the door may be implemented with one latch, one drive and power transmission that drive the latch.

(47) The power transmission is a cam in contact with a contact surface provided on the side of the latch. A center of rotation of the cam may be disposed in adjacent to a first direction, than a side of the latch to which the cam contacts. It is possible to determine a position of the latch by changing the radius of the cam that contacts the latch depending on the rotational displacement of the cam.

(48) As the elastic body elastically supports the latch so as to rotate in the first direction and the center of rotation of the cam is disposed in adjacent to the first direction than the latch, a degree in which the latch may move in the first direction may be determined depending on the radius of the cam that contacts the latch. Of course, even in this state, the latch may move in the second direction by a force greater than the elastic force of the elastic body. When the force greater than the elastic force of the elastic body disappears, the latch is rotated and returned again by the elastic body to the position in contact with the cam in the first direction.

(49) A combination of the elastic body that elastically forces the latch in the first direction and the cam disposed in adjacent to the first direction than the latch may simply enable a basic position of the latch to be adjusted by adjusting a radius of the cam in contact with the latch. Adjusting the basic positions of the latch may be a method of determining which one of the disengaged inclined surface and the secure lock surface in the engaged surface of the hook of the latch contacts the pin of the door.

(50) The cam may include the radiuses having at least three different radiuses in a circumferential direction thereof at the outer circumference thereof. The first radius enables the latch to be in the first basic position and the second radius enables the latch to be in the second basic position, and the third radius enables the latch to be in the third basic position.

(51) When the latch is moved in a second direction in the first basic position, the latch may reach the second basic position. When the latch is moved in a first direction in the first basic position, the latch may reach the third basic position.

(52) The first radius as a reference enables a latch to be in a general basic position, that is, a position where the user may manually open and close the door (a manual lock position). The pin of the door contacts the disengaged inclined surface of the hook of the latch at a position where the first radius contacts the contact surface of the latch.

(53) The second radius has a radius greater than the first radius. The second radius is connected to the first radius via a connecting surface having a smooth curved surface. Therefore, when the cam rotates in a first rotational direction such that a contact portion of the cam and the latch is moved from the first radius to the second radius, a basic position of the latch further moves in the second direction. When the second radius contacts the latch, the hook of the latch moves to the open position and may no longer be engaged with the pin of the door. That is, the pin is relatively away from the hook.

(54) Accordingly, when the latch in contact with the first radius contacts the second radius as the cam rotates, the door is moved by the elastic force by the hinge module so that the door is opened to the initial opening angle and the door is completely opened by the weight of the door itself.

(55) The third radius has a radius less than the first radius. The third radius is connected to the first radius via a connection surface having the smooth curved surface. Therefore, when the cam rotates in a second rotational direction (a direction opposite to the first rotational direction) so that the contact portion of the cam the latch is moved from the first radius to the third radius, the basic

position of the latch is further moved in the first direction to move to the secure lock position. When the third radius contacts the latch, the hook is engaged with the pin of the door deeply inward. That is, the pin of the door contacts the secure lock surface of the hook of the latch. (56) According to the present disclosure, the operation of moving the latch from the first basic position to the third basic position may be made by the elastic body. However, if the latch is engaged with the first basic position due to an unexpected state, the elastic force applied by the elastic body in the first direction may not enable the latch to move from the first basic position to the third basic position.

(57) According to the present disclosure, while the cam rotates from the first mode to the third mode, the surface of the cam and the latch are kinematically interfered with each other, and power of the drive is transmitted to the latch so as to be applied in a direction of moving from the first basic position to the third basic position.

(58) Further, due to the kinematic interference of the cam and the latch when the cam is in a third mode and the latch is also in the third basic position, the present disclosure provides a structure in which the latch is prevented from deviating from the third basic position toward the first basic position.

(59) To this end, according to the present disclosure, the latch further provides an extension that may be kinematically interfered with the cam. The extension has a sub-contact surface that approaches the cam as the latch moves in the second direction and is away from the cam as the latch moves in the first direction. Meanwhile, the contact surface **55** approaches the cam **70** as the latch **50** moves in the first direction and is away from the cam **70** as the latch **50** moves in the second direction.

(60) The cam **70** may transmit the power of the drive to the latch by the contact surface **55** so that the latch moves in the second direction. The cam **70** may transmit the power of the drive to the latch by the sub-contact surface **59** so that the latch moves in the first direction. The latch may be prevented from moving in the second direction in a state where the sub-contact surface is interfered with the cam **70**.

(61) In the first mode where the first radius of the cam contacts the contact surface of the latch so that the latch is in the first basic position (the manual lock state), the extension may not disturb the manual opening and closing rotation of the latch.

(62) To this end, the cam surface that faces the sub-contact surface when the cam is in the first mode may have a radius so that a movement for the sub-contact surface to approach the cam surface is allowed even if the latch is moved from the first basic position to the second basic position.

(63) In other words, a distance between a position of the sub-contact surface and a center of rotation of the cam while the cam is in the first mode and the latch is in the first basic position may be greater than a radius of the cam surface in contact with the sub-contact surface when the first radius of the cam contacts the contact surface of the latch. A distance between a position of the sub-contact surface and the center of rotation of the cam while the cam is in the first mode and the latch is in the second basic position may be equal to or greater than a radius of the cam surface that faces the sub-contact surface while the first radius of the cam contacts the contact surface of the latch.

(64) In the first mode where the first radius of the cam contacts the contact surface of the latch, the cam surface that faces the sub-contact surface may be the first radius, the third radius or the connecting surface that connects the first radius and the third radius.

(65) In order for the latch to be moved by the cam from the first basic position to the second basic position (the automatic opening position), when the cam rotates in the first rotational direction from the position when the cam is in the first mode to the position when the cam is in the second mode, the extension moves in the direction of approaching the cam. In this step, the extension may not contact the cam or may not be interfered with the cam.

(66) While a contact point of the cam and the contact surface of the latch is moved from the first

radius to the second radius as the cam rotates, the sub-contact surface is not interfered with the surface of the cam.

(67) In a second state where the second radius of the cam contacts the contact surface of the latch, the sub-contact surface may face the first radius of the cam and the sub-contact surface may not contact the surface of the cam.

(68) A distance between a position of the sub-contact surface and the center of rotation 7 of the cam while the latch is in the second basic position may be equal to or greater than a radius of the cam surface that faces the sub-contact surface while the second radius 7 of the cam contacts the contact surface of the latch.

(69) In order for the latch to be moved from the first basic position to the third basic position (the secure lock position), while the cam rotates in the second rotational direction from the position when the cam is in the first mode to the position when the cam is in the third mode, when the latch is not smoothly moved in the first direction in spite of a force of applying the elasticity of the elastic body, the cam may force the latch to move to the first direction by interfering the cam with the extension of the latch.

(70) To this end, while the contact point of the cam and the contact surface of the latch is moved from the first radius to the third radius as the cam rotates, the radius of the surface of the cam that faces the sub-contact surface may be set to exceed the distance between the position of the sub-contact surface and the center of rotation of the cam when the latch is in the first basic position.

(71) The radius of the cam surface that faces the sub-contact surface when the third radius of the cam contacts the contact surface of the latch may be greater than the distance between the position of the sub-contact surface and the center of rotation of the cam when the latch is in the first basic position.

(72) Even if the latch is stopped, the cam may forcibly push the latch to move the latch.

(73) The cam surface that faces the sub-contact surface may be the second radius when the third radius of the cam contacts the contact surface of the latch.

(74) The radius of the cam surface that faces the sub-contact surface when the third radius of the cam contacts the contact surface of the latch may be substantially equal to the distance between the position of the sub-contact surface and the center of rotation of the cam when the latch is in the third basic position, then the latch is fundamentally prevented from being rotated in the second direction by an unexpected external force when the latch is in the secure lock position due to the interference between the sub-contact surface and the cam.

(75) If the latch position adjusting profile of the cam may be designed so that the second radius is disposed at one side of the first radius (a contact surface for manual lock) and the third radius is disposed at the other side of the first radius and the cam may be rotated in one direction or rotated in the other direction, the position of the latch may be simply adjusted. In order to implement the adjustment of the position of the latch more simply, the drive may be a motor rotatable in both directions. More simply, the cam may be directly connected to a rotational shaft of the motor.

(76) According to the present disclosure, both the operations of the automatic opening and the complete secure lock of the door are implemented with one latch, which is determined by the basic position of the latch. The basic position of the latch may be determined by the cam and the cam may be controlled by a controller.

(77) If the cam is only rotatable in one direction, the latch may contact the cam in an order of the first radius.fwdarw.the second radius.fwdarw.the third radius.fwdarw.the first radius, or in an order of the first radius.fwdarw.the third radius.fwdarw.the second radius.fwdarw.the first radius.

(78) If the latch contacts the cam in the order of the first radius.fwdarw.the second radius.fwdarw.the third radius.fwdarw.the first radius, the door may be automatically opened before the secure lock of the door, it would be difficult to implement the secure lock function of the door. On the other hand, if the latch contacts the cam in the order of the first radius.fwdarw.the third radius.fwdarw.the second radius.fwdarw.the first radius, the door may be opened by automatic

opening after carrying out the secure lock function of the door. Therefore, if the motor rotatable in one direction only is used, the latch is installed such that the motor rotates in a direction in which the latch may contact the cam in the order of the first radius.fwdarw.the third radius.fwdarw.the second radius.fwdarw.the first radius.

(79) The rotational displacement of the cam may be controlled by pressing or releasing the switches installed around the cam as the cam rotates. When the button of the switch is pressed, the switch may be turned on. When the button of the switch is released, the switch may be turned off.

(80) Basically, in order to determine a rotational displacement of the cam based on the three basic positions of the latch (the manual lock position as the position of the latch in a state in which the first radius of the cam contacts the contact surface of the latch, the opening position as the position of the latch in a state in which the second radius of the cam contacts the contact surface of the latch, and the secure lock position as the position of the latch in a state in which the third radius of the cam contacts the contact surface of the latch), three switches may be installed in the positions, respectively, and a pressing boss that presses the switch may be provided in the cam. The first radius contacts the latch when the first switch is pressed and the second radius contacts the latch when the second switch is pressed and the third radius contacts the latch when the third switch is pressed. Then, the basic position of the latch may be adjusted through a control that the motor continues to rotate while no switch is pressed, and the rotation is stopped when the switch is pressed.

(81) It is also possible to control the three basic positions of the latch by using the two switches. The latch module may further include a first switch and a second switch installed at the bracket.

(82) The cam may implement a first mode in which both the first switch and the second switch are pressed, a second mode in which the first switch is pressed and the second switch is not pressed, the third mode in which the second switch is pressed and the first switch is not pressed, and the fourth mode in which both the first switch and the second switch are not pressed depending on a rotation position of the cam.

(83) The cam may further include a switch pressing profile capable of implementing the four modes, separate from the latch position adjusting profile. In other words, the cam may include the latch position adjusting profile and the switch pressing profile and the latch position adjusting profile and the switch pressing profile may be provided separately.

(84) When the cam is rotated so that any one mode (first selected mode) of the first to fourth modes is implemented by the switch pressing profile, the first radius may contact the latch. When the cam is rotated so that the switch pressing profile is in another mode (second selected mode) of the first to fourth modes, the second radius may contact the latch. When the cam is rotated so that the switch pressing profile is in yet another mode (third selected mode) of the first to fourth modes, the third radius may contact the latch. The other mode of the first to fourth modes may be the fourth selected mode. The first selected mode may be the first mode, the second selected mode may be the second mode, the third selected mode may be the third mode, and the fourth selected mode may be the fourth mode.

(85) The first switch and the second switch may be disposed at substantially the same distance from the center of rotation of the cam. The switch pressing profile may include a first pressing boss that presses the first switch or the second switch or does not press both the first switch and the second switch depending on the rotation position of the cam, and a second pressing boss that presses the first switch or the second switch or does not press both the first switch and the second switch depending on the rotation position of the cam.

(86) The cam may be in a range in the first mode in which the first pressing boss and the second pressing boss press the first switch and the second switch at the same time, respectively, or a range in the second mode in which the second pressing boss presses the first switch and the first pressing boss does not press the second switch, and a range in the third mode in which the first pressing boss presses the second switch and the second pressing boss does not press the first switch, and a

range in the fourth mode in which the first pressing boss and the second pressing boss do not both the first switch and the second switch depending on the rotation angle thereof.

(87) The button of the first switch and the button of the second switch have a predetermined angle with respect to the center of rotation of the cam. The first pressing boss and the second pressing boss may also have a predetermined angle with respect to the center of rotation of the cam. The angle may be less than 180° such that the two switches are not arranged on the same straight line passing through the center of rotation of the cam and the two pressing bosses are not arranged on the same straight line passing through the center of rotation of the cam. Preferably, the angle may be 90° or more or less than 180° or may have an obtuse angle. More preferably, the angle may be about 120° .

(88) In the rotation range (the range in the first mode) of the cam where both the first switch and the second switch are pressed, the first radius may contact the latch. In the rotation range (the range in the second mode) of the cam in which the first switch is pressed and the second switch is not pressed, the second radius may contact the latch. In the rotation range (the range in the third mode) of the cam in which the first switch is not pressed and the second switch is pressed, the third radius may contact the latch.

(89) The latch module may be controlled by a controller controlling the operation of automatically opening the door, controlling the operation of securely locking the door, and controlling the operation of securely unlocking the door.

(90) Controlling the operation of automatically opening the door is performed by rotating the cam in the first rotational direction in the first selected mode of the above modes to change the cam to the second selected mode so as to stop the rotation of the cam, and by rotating the cam in the second rotational direction which is an opposite direction of the first rotational direction in the second selected mode to return the cam to the first selected mode so as to stop the rotation of the cam.

(91) Controlling the operation of securely locking the door is performed by rotating the cam in the second rotational direction in the first selected mode to change the cam in the third selected mode to stop the rotation of the cam, so that the door is securely locked, thereby preventing the door being manually opened by the user.

(92) Controlling the operation of releasing the door from the securely locked state is performed by rotating the cam in the first rotational direction in the third selected mode to change the cam in the first selected mode so as to stop the rotation of the cam, so that the door is returned to the state where the secure lock of the door is released and the door is manually opened and closed.

(93) According to the present disclosure, a method of controlling the latch module further includes a position search and a sequence of an initialization control of the cam of the latch module. The search and initialization control may be executed when the cam is in the fourth selected mode in the initial drive of the latch module.

(94) First, the cam is rotated in the second rotational direction. According to the present disclosure, when the initial search drive step of rotating the cam in the second direction is performed in the fourth mode, an error that the door is opened may not occur. Specifically, after the initial search drive step, the cam is changed from the fourth selected mode (the fourth mode) to the first selected mode (the first mode) or to the third selected mode (the third mode).

(95) When the cam is changed from the fourth selected mode (the fourth mode) to the first selected mode (the first mode), the drive of the cam is terminated.

(96) When the cam is changed from the fourth selected mode (the fourth mode) to the third selected mode (the third mode), the cam is rotated in the first rotational direction. Then, the cam is changed to the first selected mode (the first mode) via the fourth selected mode (the fourth mode). When the first mode is thus set, the drive of the cam is terminated.

(97) While the user uses the cooking device, the cam may not be in the second selected mode (the second mode) during the initial search drive step. However, just after manufacturing the product,

the cam may be in the second mode during the initial search drive step, for just one chance. In this case, during the initial search drive step, after the cam is changed to the second selected mode, the cam is further rotated in the second rotational direction, and the cam is changed to the first selected mode (the first mode), the drive of the cam may be terminated.

(98) The present disclosure further provides a cooking device to which the latch module and the method of controlling such latch module are applied. Further, the present disclosure may be applied not only to the cooking device, but also to an appliance including a main body having a cavity and a door that opens and closes such main body.

(99) According to the present disclosure, a structure of the latch module applied to a cooking device may implement a manual lock function of the door and a secure lock function of a door for an operation of self-cleaning by one latch.

(100) Further, according to the present disclosure, the structure of the latch module may implement an automatic opening function of a door and a secure lock function of a door while one latch, one drive, and one power transmission are applied.

(101) Further, according to the present disclosure, in the structure of the latch module, it is possible to manually open and close the door by an elastic body, and also to perform a secure lock of the door by the elastic body. In addition, an interference structure of the latch and the cam complements a secure lock function of the elastic body. Therefore, even if abnormality occurs during operation of the elastic body, an operation of securely locking the door may be made by the cam.

(102) Further, according to the present disclosure, the structure of the latch module may prevent the latch in the secure lock state from being released by an unexpected external force due to the interference between the cam and the latch. Therefore, all operations may be implemented by one latch and one cam.

(103) Further, according to the present disclosure, in the structure of the latch module, the automatic opening of the door and secure lock of the door may be controlled through the two switches and a simple control.

(104) Further, according to the present disclosure, a method of controlling the latch module may only perform the initial position search of the cam and the latch with a simple control algorithm and the door may not be opened unintentionally in the initial search step.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side view of a cooking device including a latch module according to an embodiment of the invention.

(2) FIG. 2 is a transparent perspective view of a hinge module that connects a door and a main body of a cooking device according to an embodiment of the invention.

(3) FIG. 3 is a side view of FIG. 2.

(4) FIG. 4 is a perspective view of a latch module according to an embodiment of the invention.

(5) FIG. 5 is an exploded perspective view of the latch module of FIG. 4.

(6) FIG. 6 is a top view of a latch of the latch module of FIG. 4.

(7) FIG. 7 is a plan view of a cam of the latch module of FIG. 4.

(8) FIG. 8 is a graph of a radius of the cam depending on an angular position of the cam of FIG. 7.

(9) FIG. 9(a) is a bottom view of a cooking device having the latch module of FIG. 4, and FIG.

9(b) is a plan view of the cam and a part of the latch in contact with the cam, both representing a state where the latch is engaged with a pin of a door while the latch is in a manual lock position.

(10) FIG. 10(a) is the bottom view of the cooking device, and FIG. 10(b) is the plan view of the cam and the part of the latch in contact with the cam, both representing a state where the latch

module is operated and the latch moves to the open position.

(11) FIG. **11(a)** is the bottom view of the cooking device, and FIG. **11(b)** is the plan view of the cam and the part of the latch in contact with the cam, both representing a state where the latch is disengaged from the pin of the door and the door is opened to an initial open angle.

(12) FIG. **12(a)** is the bottom view of the cooking device, and FIG. **12(b)** is the plan view of the cam and the part of the latch in contact with the cam, both representing a state where the latch module operates and the latch is in the manual lock position while the latch is disengaged from the pin of the door.

(13) FIG. **13(a)** is the bottom view of the cooking device, and FIG. **13(b)** is the plan view of the cam, both representing a state where the latch module operates and the latch is moved to the secure lock position.

(14) FIG. **14** is a graph showing a range of the cam in contact with a contact surface of the latch, a contact position of the cam in contact with the contact surface of the latch, a movement of the contact position of the cam in contact with the contact surface of the latch, and a position in which the cam presses a switch together, in addition to FIG. **8**.

(15) FIG. **15** shows a first case in which the cam is in a fourth mode.

(16) FIG. **16** shows a second case in which the cam is in the fourth mode.

(17) FIG. **17** shows a third case in which the cam is in the fourth mode.

(18) FIG. **18** is a schematic view of an algorithm for searching and setting an initial position of the cam.

(19) FIG. **19** shows a control system including a controller.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

(20) Hereinafter, the present disclosure will describe in detail embodiments of the invention with reference to the accompanying drawings.

(21) The present disclosure may be implemented in many different manners and is not limited to the embodiments set forth herein. Certain features of the embodiments may be omitted and features of one embodiment may be combined with features of another embodiment. The embodiments are provided so that this disclosure will be thorough and complete, and will enable those skilled in the art to make and use of the invention.

(22) Hereinafter, according to an embodiment, an overall structure of a cooking device to which a method of automatically opening a door is applied will be described. However, it should be noted that the embodiments are not limited to a cooking device. The embodiments may be applied to all appliances having a pull-down door. An appliance may be that used in a home or commercially.

(23) Referring to FIG. **1**, according to an embodiment of the invention, an oven as a cooking device will be described as an example of an appliance. According to the present disclosure, the appliance is not limited to a cooking device and a cooking device is not limited to an oven.

(24) The cooking device includes a main body **10** having a substantially rectangular parallelepiped shape, an open front, and a cavity, and a door **20** installed at a front of the main body **10** that can cover the cavity.

(25) The main body **10** includes an outer housing (not shown in FIG. **1** to show an inner structure of the main body) that defines an outer appearance of the cooking device and an inner housing **11** installed in the outer housing. The inner housing may be provided with the cavity opened forward. The cavity forms a cooking chamber. In an upper portion, a lower portion, a rear portion, and side portion of the main body **10**, various components needed for operation of the cooking appliance may be provided.

(26) The door **20** has a pull-down opening and closing structure about a horizontal hinge shaft **314** disposed at a lower end of the door. In other words, the door **20** is rotated forward and downward with respect to the main body to be opened and is rotated rearward and upward with respect to the main body to be closed.

(27) As shown in FIG. **1**, the door **20** may open or close the front of the cooking chamber, and may

cover not only the cooking chamber but also a front of an upper space of the cooking chamber. A display and a touch panel, and the like may be installed on a front surface of the door **20** with respect to the upper space of the cooking chamber. As shown in FIG. **19**, the display **90** and the touch panel **100** are connected to the controller **80**. The controller **80** may be installed on an upper space of the cooking chamber or in the door **20** corresponding to the upper space of the cooking chamber.

(28) A latch module **4** is provided at an upper side of the main body **10**. The latch module **4** maintains a state where the door **20** is closed, or allows for manually opening or closing of the door **20**, or automatically opens the door **20**, or securely locks the door **20** so that the door cannot to be manually opened. A pin **22** that is engaged with or released from a hook **51** of a latch **50** of the latch module **4** and an accommodation **21** that has the pin **22** are provided on a rear surface of the door **20** (see, for example, FIG. **9(a)**). The accommodation **21** provides a space capable of accommodating the hook **51**.

(29) The latch module **4** may be installed on the main body **10** and a distal end of the latch **50** of the latch module **4**, i.e., the hook **51** may protrude forward from the front surface of the main body **10**.

(30) The latch module **4** may be installed at one side on the door or on both sides of the door, and the pin **22** and the accommodation **21** of the door may be provided corresponding to the latch module.

(31) FIGS. **2** and **3** illustrate a hinge module **300** that connects a door and a main body of a cooking device according to an embodiment of the invention. The hinge module **300** includes a spring **323**, a damper **350**, and a sub-spring **370**, and is connected to a front lower portion of the main body and a lower portion of the door. The spring **323** applies a force of moving the door in a direction of rotating a door **20** rearward and upward, i.e., the direction of closing the door. Accordingly, the spring **323** opposes a force opening the door while the door is being opened and descending.

(32) Further, while the door is being opened, the damper **350** damps a rotational force of the door to cause the door to be opened slowly. As necessary, the damper **350** may only provide a damping force while the door is being opened, or may provide the damping force while the door is being opened and while the door is being closed. The damping force may be provided in all rotation angles in which the door is opened and/or closed, or the damping force may be provided in a range among the rotation angles.

(33) The damper **350** may damp a force of opening the door at a predetermined opening angle section of the door and may not provide the damping force in a section beyond the opening angle section in which the damping force is provided. FIG. **1** shows a structure in which the damper is damping in an opening angle section of an opening door corresponding to $a2$ to $a3$. A damping beginning in angle $a2$ in which the damping starts when the door is being opened may be $35 \pm 5^\circ$.

(34) The sub-spring **370** applies a force in a direction of opening the door **20**. An opening angle range in which the sub-spring **370** applies the force in the direction of opening the door may be 0° to $a1$.

(35) Hereinafter, an operation of automatically opening a door will be described with reference to FIGS. **1** to **3**. In this embodiment, when a user touches a touch panel and the like to input a command of opening the door, a latch module **4**, which will be described later, releases an engaged state of the closed door. The door is opened by an elastic force of the sub-spring **370** of the hinge module **300** to an initial opening angle $a1$. The predetermined angle $a1$ may be set to such an extent that the door may be subsequently further opened by the weight of the door itself. The angle $a1$ may be, for example, about 10° .

(36) The hinge module **300** connecting the main body **10** and the door **20** includes a door bar **340** fixed to the door **20** and a housing **310** fixed to the main body **10** that rotate about an opening and closing rotational shaft **314**. In another embodiment, the bar may be fixed to the main body and the housing may be fixed to the door.

(37) In the housing **310**, an inner link housing **330** is provided which is movable along a longitudinal direction of the housing. A distal end of the inner link housing **330** is connected to the door bar **340** by a door bar connecting hinge **331**. As the door bar connecting hinge **331** is disposed eccentric from the opening and closing rotational shaft **314** by a distance of r , when the door **20** (the door bar **340**) opens, the door bar connecting hinge **331** rotates about the opening and closing rotational shaft **314** and moves forward. Accordingly, the inner link housing **330** also moves forward in the housing **310**.

(38) As the door **20** or the door bar **340** is opened from a closed state (vertical state) to an opened state (horizontal state) while being rotated forward of the main body, a maximum opening angle α_3 is 90° . Accordingly, the connecting hinge **331** also rotates by 90° about the opening and closing rotational shaft **314**. The inner link housing **330** also moves forward by a horizontal distance d_3 in which the opening and closing rotational shaft **314** rotates by 90° .

(39) An insert pin **361** is installed in front of the inner link housing **330**. A slot pin **362** provided in front of the insert pin **361** and is fitted into a guide slot **333** formed longitudinally at both sides of the inner link housing **330**. Accordingly, the insert pin **361** is slidably installed forwardly and rearwardly in the inner link housing **330** within a range allowed by the guide slot **333**. The insert pin **361** is inserted into the sub-spring **370**. A front portion of the sub-spring **370** is supported by the slot pin **362** and the rear portion thereof is supported by the inner link housing **330**. Accordingly, the sub-spring **370** applies the force of moving the slot pin **362** forward through the guide slot **333**.

(40) A contact surface **363** of the slot pin **362** pushes an inclined surface provided at a lower rear end of the door bar **340** forward. As shown in FIGS. 2 and 3, as a height at which the slot pin **362** pushes the inclined surface forward is higher than a position of the opening and closing rotational shaft **314**, at the beginning of opening the door, in the state where the door bar **340** stands vertically (closed state), the sub-spring **370** applies the force of moving the door bar **340** in a direction of rotating the door bar **340** forward and downward. Accordingly, at the beginning of opening the door, the sub-spring **370** opens the door by the initial opening angle α_1 . After the slot pin **362** moves to the foremost position of the guide slot **333**, the slot pin **362** does not move further and the sub-spring **370** does not apply force on the door bar **340**.

(41) Of course, in the section corresponding to the state where the door is closed to the state where the opening angle of the door is the initial opening angle α_1 , a pressing force of the spring **323** in the direction of closing the door is less than a pressing force of the sub-spring **370** in the direction of opening the door. Thus, in this section, the net force is a force applied to the door in the opening direction thereof.

(42) Note that in a closed state of the door, a force which is transferred from the pin **22** to the hook **51** of the latch **50** to move the latch in a second direction w_2 (see FIG. 6) by an opening force of the sub-spring **370** is weaker than a force which is applied to the latch **50** to move the latch in a first direction w_1 by a spring in the latch module **4** (for example, see FIG. 4), when the latch **50** is in a manual lock state, and thus the door maintains the closed state in spite of the force of the sub-spring **370** of a hinge module **300** to open the door.

(43) After the door reaches the initial opening angle α_1 from the closed state, the door starts to open by the weight of the door itself. As the door bar **340** rotates about the housing **310** to further open the door, a damping force along with an opposing force against the door being opened are exerted on the door bar **340** by a damper **350** and a spring **323** to be described later.

(44) A second insert pin **320** inserted inside of the spring **323** is installed at a rear of the inner link housing **330**. The second insert pin **320** is connected to the rear of the inner link housing **330** through a joint pin **322** at the inner housing. Both ends of the joint pin **322** at the inner housing are fitted to a guide slot **315** provided at the housing **310**. The guide slot **315** for the joint pin **322** has an elongated shape extending along the longitudinal direction of the housing **310**.

(45) The second insert pin **320** is inserted into the compressed coil spring **323** having greater elasticity in a compressed state. The second insert pin **320** may slidably move along the

longitudinal direction of the housing **310** through a spring-engaged plate **311** fixed to the housing **310**. However; the distal end of the compressed coil spring **323** is engaged with the spring-engaged plate **311** of the housing **310** and a supporting pin **312** that supports the spring-engaged plate **311** may be installed in the housing **310** so as to maintain the force of the compressed coil spring **323**.

(46) A spring supporting pin **321** that fixes a rear end of the spring **323** is installed at a rear end of the second insert pin **320**. The spring supporting pin **321** does not interfere with the housing **310**.

(47) Accordingly, when the door bar **340** opens from the main body **20**, the joint pin **322** of the inner link housing **330** is guided by the guide slot **315** of the housing **310**, and the inner link housing **330** and the second insert pin **320** are moved forward. Accordingly, the spring **323** starts to compress between the spring-engaged plate **311** and the spring supporting pin **321**, and the elastic force is gradually increased. The compression length $d3$ of the spring **323** corresponds to the horizontal movement distance $d3$ of the inner link housing **330** in which the opening and closing rotational shaft **314** rotates by 90° . When the opening angle of the door is less, the elastic force of the spring **323** is less. However, as the opening angle of the door is increased, the elastic force of the spring **323** is increased. The elastic force is applied in a direction of opposing the door being opened.

(48) A force in which the spring **323** pushes the door in the closing direction thereof when the door is opening is gradually increased from the opening angle $a1$ to the opening angle $a3$ of the door. As the force of the spring **323** at the opening angle $a1$ of the door is less than the force (the opening force) in which the door is opened by the weight of the door itself at the opening angle $a1$, the door pushed to the opening angle $a1$ by the sub-spring **370** starts to open by itself.

(49) The damper **350** is installed in the inner link housing **330**. A piston **351** of the damper **350** is supported by a damper pushing surface **332** integrally fixed to the inner link housing **330**. The piston **351** is inserted into a cylinder **352**. A slot **353**, in which a damper supporting pin **313** fixed to the housing **310** is fitted into is provided at the cylinder **352**. That is, the cylinder **352** may move forward or backward by the length of the slot **353**. FIG. 3 shows a position between the slot **353** of the damper **350** and the damper supporting pin **313** of the housing **310** while the door is closed.

(50) As the door opens and is rotated by a predetermined angle $a2$, the inner link housing **330** moves forward in the horizontal direction by distance $d2$. Accordingly, the damper **350** is moved forward by the damper pushing surface **332** of the inner link housing **330** and moves together. As the damper is pushed forward, the damper pushing surface **332** pushes the piston **351** forward; however, the slot **353** of the cylinder **352** has not engaged with the damper supporting pin **313**. Thus, the piston **351** and the cylinder **352** move forward together with the inner link housing **330**, and does not generate any damping force.

(51) As soon as the opening angle of the door exceeds $a2$, the slot **353** of the damper **350**, which has been moving forward, is engaged with the damper supporting pin **313**, so that the cylinder **352** stops moving and the piston **351** engages with the cylinder **352** such that the damper **350** starts to compress. The damping force generated when the damper **350** compresses enables opening the door at a controlled speed in the section corresponding to the opening angle $a2$ to $a3$.

(52) For reference, a maximum damping distance (L_{max}) of the damper **350** itself, that is, a maximum stroke capable of generating the damping force by compressing in the damper, is set to be equal to or greater than the distance $d3-d2$ in which the inner link housing **330** moves while the damping force is applied to the door.

(53) When the closed door is opening to opening angle $a2$, the door bar connecting hinge **331** also rotates by angle $a2$, so that the inner link housing **330** and the second insert pin **320** move forward by distance $d2$. While the inner link housing **330** and the second insert pin **320** inserted inside of the spring **323** move by the distance $d2$, the slot **353** of the damper **350** moves without interference from the damper supporting pin **313** of the housing **330**, and thus the piston **351** and the cylinder **352** of the damper do not engage. That is, in the section corresponding to the opening angle of 0 to $a2$ of the door, the elastic force of the spring **323** is applied in a direction opposite to the opening

force of the door to control the opening speed of the door, but the damping force is not applied.

(54) When the closed door is opening to opening angle a_3 , the door bar connecting hinge **331** also rotates by angle a_3 , so that the inner link housing **330** and the second insert pin **320** move forward by distance d_3 . That is, the spring **323** is compressed by distance d_3 . That is, the elastic force of the spring **323** is applied in a direction opposite to the opening force of the door in the section from 0° to a_3 of the opening angle, and an opening speed of the door is controlled by the elastic force.

(55) The maximum opening angle a_3 may be regulated by the guide slot **315** of the housing **310** by regulating a slidable movement distance of the joint pin **322** of the inner link housing **330** within the guide slot **315**.

(56) The angle range in which the damper **350** damps the opening force of the door may start when the door is rotated about 30° to 40° , for example, and may be continued until the door is rotated by 90° . To summarize, the door is opened in a closed state by the sub-spring **370** to the initial opening angle a_1 , and then opened by its own weight while being opposed by the elastic force of the spring **323**. When the door is rotated by opening angle a_2 (about 30° to 40°), the damping force of the damper **350** is applied to the door so that the opening speed of the door is slowed down. The manner of opening the door as described above makes the user feel comfortable.

(57) Note that if the damping starts too early as the door is opening, time for waiting for the door to be completely opened may take too long, resulting in an inconvenience to the user. On the other hand, if the damping of the door starts too late, the door may be opening too quickly to an extent that the opening speed of the door is too fast, and thereby the user may be surprised or feel uncomfortable, or the user may get injured by the quickly opening door.

(58) Thus, according to the embodiment, the damping beginning angle a_2 at which the damper **350** starts to damp the opening force of the door is $35 \pm 5^\circ$.

(59) The damping force may be continuously applied up to 90° at which the door is completely opened or up to 85° which is about 5° less. It is also conceivable that the damping force is not applied for an opening angle greater than 85° to prevent the door from being opened less than 1° to 2° of the 90° required to completely open the door.

(60) As described above, the damping beginning angle a_2 is set to be greater than the forcedly opened angle a_1 . A section between the forcedly opened angle a_1 and the damping beginning angle a_2 , for example, a range of 10° or more and 30° to 40° or less is configured so that the door is opened by the weight of the door itself without being damped by any damper **350**. Of course, even in this section, the above-described elastic force of the spring **323** is applied in a direction that opposes the opening of the door, so that the opening of the door is sufficiently prevented from opening too quickly in the section in which the door is opening by the weight of the door itself.

(61) When such a structure of automatically opening the door is applied, it is possible to reduce user anxiety, and increase a quality of the door being opened automatically, and there may be no need to install a handle protruding forward from the door, thereby providing excellent appearance to the user in the built-in installation.

(62) Hereinafter, according to an embodiment, a latch module **4** capable of automatically opening a door or completely locking a door of a cooking device will be described with reference to FIGS. **4** to **13(b)**.

(63) According to the embodiment, the latch module **4** includes a bracket **40** as an overall base. The bracket **40** may be made of sheet metal. An edge of a rectangular metal plate is bent downward or upward. Accordingly, a structure in which the latch module **4** may be fixed to another body and a structure in which various parts, such as a drive **60**, an elastic body **90**, and the like may be installed in the bracket **40** are provided.

(64) The bracket **40** includes a cam accommodating hole **42** that provides a space that accommodates a cam **70** which is a power transmitting portion and an through-hole **41** capable of regulating a section in which a latch **50** pivotally installed in the bracket **40** pivots.

(65) The latch **50** is pivotally installed on the bracket **40**. The latch **50** has a structure having a bent

long metal plate, and a rear end of the latch **50** is provided with a pivot shaft **54** as a center of pivot of the latch **50** about the bracket **40**. As the pivot shaft **54** is installed in a pivot hole (not shown), the latch **50** is pivotally installed on the bracket **40**.

(66) A rear portion of the latch **50** including the pivot shaft **54** is arranged over the bracket **40**. On one side of the latch **50** arranged over the bracket **40**, a contact surface **55** is provided to be in contact with a latch position adjusting profile **73** of the cam **70** and an extension **58** is provided that interacts with the cam **70** to mechanically complement an operation error of the latch **50**. The extension **58** extends vertically from the contact surface **55** and a substantially 'L'-shape is formed between the contact surface **55** and the extension **58**.

(67) An insertion portion **56** is formed at an intermediate portion of the latch **50** that is bent downward and forward so as to decline from a front end of the rear portion and is inserted through the through-hole **41** of the bracket **40**. The through-hole **41** has an arc shape and has a size that accommodates a locus of the swivel of the latch **50** when the insertion portion **56** is inserted into the through-hole **41**.

(68) An arc-shaped sliding bead surface **43** that supports the pivoting of the latch **50** is provided at a position closer to the pivot shaft **54** than the through-hole **41** at the bracket **40**. The sliding bead surface **43** protrudes from the surface of the bracket **40** to contact a bottom surface of the latch **50**, thereby preventing friction from occurring via a direct contact of a top surface of the bracket **40** and the bottom surface of the latch **50**.

(69) A front end of the insertion portion **56** is bent forward again to extend forward in the horizontal direction, i.e., parallel with the rear portion. A hook **51** is provided at a distal end of the latch **50**. The hook **51** engages with or releases from a pin **22** of the door.

(70) The latch **50** includes a hole **57** capable of engaging with an end of a spring **90** that acts as an elastic force. The spring **90** has one end fixed to the hole **57** and an other end fixed to the bracket **40**. Accordingly, the spring **90** pulls the latch **50** towards the spring. The spring **90** is arranged to be adjacent to a first direction **w1** of the pivoting direction of the latch **50** and applies a force so as to pivot the latch **50** in the first direction **w1**.

(71) The cam **70** is rotatably installed to be adjacent to the first direction **w1** of the latch **50**. A hole **711** as the center of rotation of the cam **70** is disposed vertically on the cam so that the cam **70** has a vertical rotational axis. The cam **70** is installed into the cam accommodating hole **42** of the bracket **40** so that an upper portion of the cam **70** is exposed over the bracket **40** and a lower portion of the cam **70** is exposed below the bracket **40**.

(72) The cam **70** includes the latch position adjusting profile **73** that contacts the contact surface **55** of the latch **50** described above and adjusts the position of the latch **50** based on a rotational position of the latch position adjusting profile **73**, and a switch pressing profile **72** that presses the switches **81** and **82** to be described later or press-releases the switches **81** and **82**.

(73) The latch position adjusting profile **73** is provided at the upper portion of the cam, and the switch pressing profile **72** is provided at the lower portion of the cam. The latch position adjusting profile **73** is exposed above the bracket **40** and contacts the contact surface **55** of the latch **50** when the cam **70** is installed on the bracket **40**. The switch pressing profile **72** is exposed below the bracket **40** and presses or press-releases the switches **81** and **82** to be described later provided at the lower portion of the bracket **40**.

(74) For reference, a material of the cam **70** may be a synthetic resin having good strength and heat resistance, such as poly phenylene sulfide (PPS), and thereby abrasion generated when the cam rotates is minimized and stability in an environment of the home appliance having high temperature may be provided.

(75) The cam **70** is rotationally driven by a motor **60** as a driver. According to the embodiment, the cam **70** may be directly connected to the rotational shaft **61** of the motor **60**. The motor **60** may be a bi-directional rotational motor capable of both clockwise rotation and counter-clockwise rotation. The motor **60** is fixed to the upper portion of the bracket **40** such that the rotational shaft **61**

extends downward and the rotational shaft **61** is inserted into the axis hole **711** of the cam **70**.

(76) The first switch **81** and the second switch **82** are installed at the bottom surface of the bracket **40**. The first switch **81** and the second switch **82** may be a micro switch having buttons **811** and **821**, respectively. The buttons **811** and **821** of the switches provided on the bracket protrude to substantially face a center of the cam. The buttons **811** and **821** are arranged with an angle b of 90° or more and less than 180° with respect to the center of rotation **711** of the cam and may be arranged at the same distance from the center of rotation of the cam. Preferably, the angle b may be in the range of 110° to 160° , and more preferably in the range of 120° .

(77) Referring to FIG. 6, a latch according to an embodiment will be described. The hook **51** is provided at the distal end of the latch **50**, that is, a front end thereof, is opened laterally, specifically, in a first direction $w1$ in which the latch **50** pivots. Inward of the hook **51**, an engaging surface **52** that engages with the pin **22** of the door is provided. The engaging surface **52** includes a disengaging inclined surface **521** and a secure lock surface **522**. The disengaging inclined surface **521** is arranged closer to the first direction $w1$ on the engaging surface **52** and the secure lock surface **522** is arranged closer to a second direction $w2$ in which the latch **50** pivots in the engaging surface **52**. That is, the disengaging inclined surface **521** is arranged closer to the opening end of the hook **51** than the secure lock surface **522** which is arranged deeper into the hook **51**.

(78) The disengaging inclined surface **521** has a surface inclined with respect to a horizontal axis in an opening direction of the door toward the first direction $w1$. When the latch **50** pivots about a pivot shaft **54** in the first direction $w1$, the pin **22** of the door contacts the disengaging inclined surface **521** and the latch **50** is disposed in the manual lock position.

(79) The secure lock surface **522** has a surface inclined with respect to the horizontal axis in the closing direction of the door toward the second direction $w2$. When the latch **50** pivots further in the first direction $w1$, the pin **22** contacts the secure lock surface **522** and the latch **50** is disposed in a secure lock position.

(80) The disengaging inclined surface **521** and the secure lock surface **522** are connected with a smooth curved surface. Thus, as the latch **50** pivots, when the pin **22** of the door is in contact with the disengaging inclined surface **521** slides adjacent to the secure lock surface **522**, the sliding may be smoothly made over to the secure lock surface **522**. In particular, as the movement of the latch **50** is made by an elastic force of the spring **90**, the movement of the latch **50** may be more reliably made if the sliding between the disengaging inclined surface **521** and the secure lock surface **522** is made smooth.

(81) An inclined insertion surface **53** is provided on an outer surface of the hook **51** opposite to the disengaging inclined surface **521**. The inclined insertion surface **53** is inclined with respect to the horizontal axis in the closing direction of the door toward the second direction $w2$ when the latch **50** is in the manual lock position. The inclined insertion surface **53** contacts the surface of the pin **22** of the door when the latch is in the manual lock position. That is, the hook **51** has a shape that gradually becomes thinner, that is, sharper, toward the end by the disengaging inclined surface **521** and the inclined insertion surface **53**. The inclined insertion surface **53** may extend to the outer surface of the hook **51** that is opposite to the secure lock surface **522**.

(82) The contact surface **55** of the latch **50** in contact with the cam **70** is provided at the side of the latch **50**. The contact surface **55** is arranged adjacent to a second direction $w2$ about the center of rotation of the cam. An extension **58** extending outward from the contact surface **55** is further provided at one end of the contact surface **55**. The extension **58** and the contact surface **55** have a substantially shape and the contact surface **55** and the extension **58** are arranged to surround the cam **70**.

(83) A sub-contact surface **59** is provided laterally with respect to an extending direction of the extension **58**, which faces the cam, and in some cases contacts and interacts with the surface of the cam. The sub-contact surface **59** protrudes from the extension **58** so that other than the sub-contact surface **59**, other portions of the extension **58** does not interact with the cam **70**.

(84) The sub-contact surface **59** approaches the cam **70** when the latch **50** pivots in the second direction **w2**. The sub-contact surface **59** moves in a direction away from the cam as the latch **50** pivots in the first direction **w1**.

(85) The extension **58** is not necessarily integrally formed with a body of the latch **50**, but may be manufactured as a separate component and then assembled. The extension **58** does not have to behave like a rigid body with the body of the latch **50**. It is enough for the extension **58** to transmit such a force to the body of the latch **50** that the cam **70** moves the extension **58** in the first direction **w1** and the latch **50** moves from a first basic position (see FIG. **9(b)**) to a third basic position (see FIG. **13(b)**) or the latch is in the third basic position.

(86) When the force is applied to the contact surface **55** of the latch **50** by the cam **70** in the second direction **w2**, that is, the latch **50** is pivoted from the first basic position to the second basic position (see FIG. **10(b)**) by the cam **70**, the extension **58** does not interact with the cam **70**.

(87) A feature of the sub-contact surface **59** will now be described. The cam may include an oblong shape. When the cam **70** rotates and the radius of the cam **70** in contact with the contact surface **55** of the latch **50** is reduced, the latch **50** pivots in the first direction **w1**, and the radius of the cam **70** that faces the sub-contact surface **59** of the latch **50** increases. When the latch **50** does not pivot in the first direction **w1** although the radius of the cam **70** contacting the contact surface **55** of the latch is reduced so that the latch **50** can pivot in the first direction **w1**, the radius of the cam **70** that faces the sub-contact surface **59** increases sufficiently as to interact with the sub-contact surface **59**, and the sub-contact surface **59** is pushed in a direction away from the cam **70** so that the latch **50** may be forcedly pivoted in the first direction **w1**.

(88) A distance d_{mp} between the center of rotation of the cam **70** and the sub-contact surface **59** when the latch **50** is in the first basic position (see FIG. **9(b)**) and a distance d_{op} between a center of rotation of the cam **70** and the sub-contact surface **59** when the latch **50** is in the second basic position (see FIG. **10(b)**), and a distance d_{lp} between the center of rotation of the cam and the sub-contact surface when the latch is in the third basic position (see FIG. **13(b)**) has a relationship of $d_{op} < d_{mp} < d_{lp}$.

(89) Referring to FIGS. **5**, **7**, and **8**, a cam according to an embodiment will be described. A latch position adjusting profile **73** of the cam **70** includes three surfaces having different radii from one another, that is, a contact surface for manual lock **731**, a contact surface for automatic opening **732** and a contact surface for secure lock **733**. The three surfaces have different radii from one another and are connected to each other by a connecting surface **734** that has a gradually increasing or reducing radius, respectively.

(90) The contact surface for manual lock **731** includes a first radius. The first radius may be configured such that the latch **50** is disposed at a position where the door may be manually opened and closed in a state in which the first radius contacts the latch **50**. In this state, the pin **22** of the door contacts the disengaging inclined surface **521** or the inclined insertion surface **53** of the hook **51**. Accordingly, the spring **90** pulls the latch **50** in the first direction **w1** and the contact surface for manual lock **731** of the cam **70** contacts the latch **50** (see FIG. **9(a)**, **9(b)** or **12(a)**, **12(b)**). In this state, when the user pulls the door in the opening direction thereof, the door may be opened. When the user closes the door, the door may be closed.

(91) The contact surface for automatic opening **732** includes a second radius. The second radius is configured so that the latch **50** may be rotated in the second direction **w2** to the position in which the latch **50** is released from the pin **22** of the door in a state in which the second radius contacts the latch **50**. The second radius has a radius greater than the first radius. That is, when the spring **90** pulls the latch **50** in the first direction **w1** and the contact surface for automatic opening **732** of the cam contacts the latch **50** (see FIG. **10(a)**, **10(b)** or **11(a)**, **11(b)**), the latch **50** is released from the pin **22** of the door.

(92) The contact surface for secure lock **733** includes a third radius. The third radius is configured such that the latch **50** completely securely locks the door while being in contact with the latch **50** so

that the door cannot be opened even when the door is pulled to open by the user. In this state, the pin **22** of the door contacts the secure lock surface **522** of the hook **51**. Thus, when the spring **90** pulls the latch **50** in the first direction **w1** and the contact surface for secure lock **733** of the cam **70** contacts the latch **50** (see FIGS. **13(a)**, **13(b)**), even if the user pulls the door in the opening direction, the door may not open. That is, the state may be referred to as a completely locked state, for example, for self-cleaning.

(93) A diameter **rM1** of a cam surface in contact with the sub-contact surface **59** when the cam is in the first mode and the first radius of the cam contacts the contact surface of the latch (see FIG. **9(b)**), a diameter **rM2** of a cam surface that faces the sub-contact surface **59** when the cam is in the second mode and the second radius of the cam contacts the contact surface of the latch (see FIG. **10(b)**), and a diameter **rM3** of a cam surface that faces the sub-contact surface **59** when the cam is in the third mode and the third radius of the cam contacts the contact surface of the latch (see FIG. **13(b)**) have a relation of $rM2 \leq rM1 \leq rM3$.

(94) When the cam is in the first mode state, and the first radius **731** contacts the contact surface **55** of the latch **50**, a portion of the cam surface that faces the sub-contact surface **59** may be the first radius **731**, the third radius **733** or a connecting surface **734** connecting the first radius **731** and the third radius **733**. According to the present disclosure, FIGS. **9(b)** and **12(b)** show that the cam surface that faces the sub-contact surface **59** is the first radius **731**.

(95) When the cam is in the second mode, and the second radius **732** is in a position in contact with the contact surface **55** of the latch **50**, the cam surface that faces the sub-contact surface **59** may be the first radius **731** (see FIGS. **10(b)** and **1(b)**).

(96) When the cam is in the third mode, and the third radius **733** is in the position in contact with the contact surface **55** of the latch **50**, the cam surface in contact with the sub-contact surface **59** may be the second radius **732** (see FIG. **13(b)**).

(97) As shown in FIG. **9(b)**, when the cam **70** is in the first mode state, and the first radius **731** contacts the contact surface **55** of the latch **50**, the radius **rM1** of the cam surface that faces the sub-contact surface **59** is less than a distance **dmp** between a position **mp** of the sub-contact surface **59** and the center of rotation **711** of the cam **70** when the latch **50** is in the first basic position, and is equal to or less than the distance **dop** between the position **op** of the sub-contact surface **59** and the center of rotation **711** of the cam **70** when the latch **50** is in the second basic position (see FIG. **10(b)**). That is, the relation of $rM1 \leq dop < dmp$ is satisfied.

(98) As shown in FIG. **10(b)**, when the cam **70** is in the second mode state, and the second radius **732** contacts the contact surface **55** of the latch **50**, the radius **rM2** of the cam surface that faces the sub-contact surface **59** is equal to or less than the distance **dop** between the position **op** of the sub-contact surface **59** and the center of rotation **711** of the cam **70** when the latch **50** is in the second basic position. That is, $rM2 \leq dop$.

(99) As shown in FIGS. **9(b)** and **10(b)**, the relation of $rM1 \leq rM2 \leq dop < dmp$ may be expressed based on the conditions.

(100) As shown in FIG. **13(b)**, when the cam is in the third mode state, and the third radius **733** of the cam **70** contacts the contact surface **55** of the latch **50**, a radius **rM3** of the cam surface that faces the sub-contact surface **59** is greater than a distance **dmp** between the position **mp** of the sub-contact surface **59** and the center of rotation **711** of the cam **70** with the latch **50** being in the first basic position and is equal to or less than a distance **dlp** between a position **1p** of the sub-contact surface **59** and the center of rotation **711** of the cam **70** with the latch **50** is in the third basic position. That is, the relation of $dmp < rM3 \leq dlp$ is satisfied.

(101) All of the above conditions are expressed as follows:

$rM1 \leq rM2 \leq dop < dmp < rM3 \leq dlp$.

(102) On the other hand, a switch pressing profile **72** of the cam **70** has two pressing bosses having substantially the same radius. A first pressing boss **721** and a second pressing boss **722** are not arranged in a straight line, that is 180° opposite from each other, but are disposed at an obtuse

angle. The angle of the two pressing bosses may correspond to an angle between the buttons **811** and **821** of the first switch and the second switch, and the radius of the two pressing bosses may be configured such that the pressing boss presses or press-releases the button as the cam rotates.

(103) The first pressing boss may press the first switch or the second switch or not press the two switches depending on the rotational position of the cam. The second pressing boss may press the first switch or the second switch or not press both switches depending on the rotational direction of the cam.

(104) Since the angle of the two pressing bosses corresponds to the angle of the buttons of the two switches, the state where the first pressing boss presses the first switch and the second pressing boss presses the second switch, that is, a first mode state where the two pressing bosses press the two switches, a second mode state where the second pressing boss presses the first switch and the first pressing boss does not press a switch, a third mode state where the first pressing boss presses the second switch and the second pressing boss does not press a switch, and a fourth mode state where the two pressing bosses do not press any switches may be implemented.

(105) Each mode of the switch pressing profile **72** and the latch position adjusting profile **73** may be related to each other. That is, in the first mode, the contact surface for manual lock **731** may contact the latch to dispose the latch in the manual lock state. In the second mode, the contact surface for automatic opening **732** may contact the latch so that the latch is in the open position. In the third mode, the contact surface for secure lock **733** may contact the latch so that the latch is disposed in the secure lock position.

(106) Hereinafter, an operation of a latch module according to an embodiment will be described with reference to FIGS. **9** to **13(b)**.

(107) <Manual Lock State>

(108) FIGS. **9(a)** and **9(b)** illustrate a manual lock state. A latch module is provided. That is, when the two pressing bosses **721** and **722** press the buttons **811** and **812** of the two switches, respectively, a contact surface for manual lock **731** which is a first radius of the latch position adjusting profile **73** contacts a contact surface **55** of a latch **50**. The spring **90** pulls the latch **50** in the first direction **w1** (a direction in which the hook **51** pivots leftward in FIG. **9(a)**).

(109) When the user pulls the door **20** in such a manual lock state, a rear surface of the pin **22** presses on the disengaging inclined surface **521** of the hook **51**. The disengaging inclined surface **521** is inclined outward toward the first direction **w1** so that the force is applied to the hook **50** in the second direction **w2** by a force in which the pin **22** presses on the disengaging inclined surface **521**, and accordingly, the latch **50** pivots in the second direction **w2** with a force greater than the elastic force of the spring **90** (i.e., as the latch **50** pivots in the second direction **w2**, the contact surface **55** of the latch moves away from the contact surface for manual lock **731**). As a result, the hook **51** that is engaged with the pin **22** is released so that the door is opened.

(110) As described above, as the relation of $r_{M1} \leq d_{op} < d_{mp}$ is satisfied, the extension **58** does not interact with the cam during the pivot of the latch **50** in the second direction **w2** for the manual opening of the door and the latch **50** may freely rotate in the second direction **w2**.

(111) When the door is opened and the pin **22** is released from the hook **51**, as a force in which the pin **22** pushes the hook **51** in the second direction disappears, the latch **50** pivots in the first direction **w1** by means of the spring **90** until the contact surface **55** of the latch **50** contacts the contact surface for manual lock **731**, so that the latch is returned to a manual lock position as shown in FIGS. **12(a)** and **12(b)**.

(112) In this state, when the user closes the door as shown in FIG. **12(a)**, the surface of the pin **22** pushes the inclined insertion surface **53** of the hook **51**. As the inclined insertion surface **53** has a form inclined to a closing direction of the door toward the first direction **w1**, a force of pivoting in the second direction **w2** is applied to the hook **51** in which the surface of the pin **22** presses against the inclined insertion surface **53** in the closing direction. Then, the latch **50** pivots in the second direction **w2** with a force greater than the elastic force of the spring **90**. As the door is closed, the

force on the hook **51** is released from a locus of the moving pin **22**. As shown in FIG. **9(a)**, when the door is closed, via the elastic force of the spring **90**, the latch pivots again and returns in the first direction **w2** by the elastic force of the spring until the contact surface **55** of the latch **50** contacts the contact surface for manual lock **731**.

(113) Similarly, as the relation of $rM1 \leq dop < dmp$ is satisfied, during the pivot of the latch **50** in the second direction **w2** for manual closing the door, the extension **58** is not interfered with the cam **70** and the latch **50** may freely move in the second direction **w2**.

(114) As described above, according to the embodiment, with the latch module **4**, it is possible to open the door by manually pulling the door by the user, or close the door by pushing the door toward the main body.

(115) <Automatic Opening Operation>

(116) An Automatic opening operation of the latch module according to an embodiment will now be described. As shown in FIG. **9(a)**, when the user inputs an automatic opening command of a door through an input device, a bidirectional rotational motor **60** rotates in any one direction, that is, a first rotational direction by a controller **80**, and the cam **70** is rotated in a first rotational direction **c1**. Then, a pressed state of the two switches is released, and the cam **70** continues to rotate. As shown in FIG. **10(a)**, the rotation of the cam **70** continues until a second pressing boss **722** presses a first switch **81**. When the second pressing boss **722** presses the first switch **81**, the bidirectional rotational motor **60** is stopped by the controller **80** that senses the pressed state, and the rotation of the cam in the first rotational direction **c1** is also stopped. That is, the cam **70** is rotated in the first rotational direction **c1** by an angle **b** of the two pressing bosses and stopped (see FIG. **7**).

(117) As shown in FIG. **10(a)**, as the first pressing boss **721** and the second pressing boss **722** are not on a straight line passing through a center of rotation **711** of the cam **70** and have an obtuse angle, the second pressing boss **722** presses the first switch **81** while the first pressing boss **721** does not press the second switch **82**.

(118) As the latch **50** is elastically supported by the spring in a direction in contact with the cam **70**, the latch pivots while being in contact with the latch position adjusting profile **73** of the cam **70** depending on the radius of the latch position adjusting profile **73** during the rotation of the cam **70**. As the cam **70** is rotated by the angle **b** in the first rotational direction **c1**, a position of the latch position adjusting profile **73** contacting the contact surface **55** of a latch **50** is moved from the contact surface for manual lock **731** to the contact surface for automatic opening **732** (as shown in FIG. **8**, the position of the latch position adjusting profile **73** contacting the contact surface **55** of the latch **50** is moved from a vicinity of 250° (a contact surface for manual lock **731**) to a vicinity of 20° (a contact surface for automatic opening **732**) in a direction of increasing angle). As shown in FIGS. **10(a)** and **10(b)**, as the radius of the cam **70** in contact with the latch **50** is increased from the first radius to the second radius, the cam **70** pushes the contact surface **55** of the latch **50** in a second direction **w2** with a force greater than an elastic force of the spring **90**. Accordingly, the hook that is locked with the pin **22** of the door is released.

(119) As described above, the relation of $rM1 \leq rM2 \leq dop < dmp$ is satisfied. Further, while the cam **70** is moved from a first mode to a second mode, a condition in which the radiuses $rM1$ and $rM2$ of a cam surface that faces the sub-contact surface **59** is less than distances dmp and dop between the sub-contact surface **59** and the center of rotation of the cam is continuously satisfied. Therefore, when the cam is rotated in the first rotational direction **c1** for automatically opening the door and the latch is pivoted in the second direction **w2**, the cam **70** does not interact with the extension **58** and the latch **50** may freely rotate in the second direction **w2**.

(120) When the door is closed, that is, when an opening angle thereof is 0° , according to an embodiment, the sub-spring **370** of the hinge module **300** applies the elastic force in the direction of opening the door. Therefore, as shown in FIG. **10(a)**, the door is moved in an opening direction **od** when the hook **51** is no longer locked with the pin **22** as the latch **50** is moved in the second

direction **w2** by the cam. As the sub-spring **370** of the hinge module **300** applies the elastic force in a direction of opening the door when the opening angle is 0° , an operation of opening the door instantly occurs when the lock of the hook **51** with respect to the pin is released.

(121) For reference, the door would be opened at the position at which sum of the force transmitted from the sub-spring **370** of the hinge module to the hook **51** to move the latch **50** in the second direction **w2** and the force of the drive **60** is greater than the applied force of moving the latch **50** in a first direction **w1** by the elastic force of the spring **90**, as the force of the drive **60** is transmitted to the latch **50** and the latch **50** moves in the second direction **w2**.

(122) Accordingly, when the door is opened by an initial opening angle **a1**, the door may automatically opened by its own weight.

(123) As shown in FIG. **11(a)**, as the bi-directional rotational motor **60** rotates in the other direction, that is, a second rotational direction **c2**, the cam rotates in a second rotational direction **c2**. Then, the pressing of the second pressing boss **722** with respect to the first switch **81** is released. As shown in FIG. **12(a)**, the rotation of the cam **70** in the second rotational direction **c2** continues until the two pressing bosses **721** and **722** push the two switches **81** and **82**, respectively. That is, the cam **70** is rotated in the second rotational direction **c2** by the angle **b** of the two pressing bosses and then stopped (see FIG. **7**).

(124) As described above, the automatic opening operation may be performed continuously. That is, as shown in FIG. **9(a)**, when the command of automatically opening the door is inputted, as the cam **70** is rotated in the first rotational direction **c1**, the cam is moved to the position shown in FIGS. **10(a)** and **11(b)** by the angle **b**. Accordingly, the second pressing boss **722** presses the first switch **81**, the cam **70** inversely rotates again in the second rotational direction **c2** so that the cam **70** is returned to the state as shown in FIG. **9(a)**. As described above, the command of automatically opening the door enables rotating the cam **70** in the first mode by the angle **b1** in the first rotational direction **c1** and moving the cam **70** in the second mode, and immediately returning the cam to the first mode again. That is, in accordance with the command of automatically opening the door, the cam operates in the order of the first mode.fwdarw.the rotation in the first rotational direction (the fourth mode).fwdarw.the second mode.fwdarw.the rotation in the second rotational direction (the fourth mode).fwdarw.the first mode.

(125) A secure lock operation according to an embodiment will now be described. As shown in FIG. **9(a)** in a general state, when a user inputs a self-cleaning command through the input device, the controller **80** determines whether the door is closed through a door sensor **88**. If the door is closed, the controller **80** controls the bidirectional rotational motor **60** to rotate in a second rotational direction so that a cam **70** rotates in a second rotational direction **c2**. The pressed state of the two switches are released and the cam **70** continues to rotate. As shown in FIG. **13(a)**, the rotation of the cam **70** continues until a first pressing boss **721** presses a second switch **82**. When the first pressing boss **721** presses the second switch **82**, the bidirectional rotational motor **60** is stopped by the controller **80**, and accordingly, the rotation of the cam in the second rotational direction **c2** is stopped. That is, the cam **70** is stopped after being rotated in the second rotational direction **c2** by the angle **b** of the two pressing bosses.

(126) As the first pressing boss and the second pressing boss are not on a straight line passing through the center of rotation of the cam **70** and have an obtuse angle, as shown in FIG. **13(a)**, the first pressing boss **721** presses the second switch **82** while the second pressing boss **722** does not press the first switch **81**.

(127) As the latch **50** has elastic force in the direction in contact with the cam **70** by the spring **90**, while the cam **70** rotates, the latch **50** pivots depending on the contact of radius of the latch position adjusting profile **73** of the cam **70**. As the cam rotates in the second rotational direction **c2** by the angle **b**, the position of the latch position adjusting profile **73** contacting the contact surface **55** of the latch **50** is moved from the contact surface for manual lock **731** to the contact surface for secure lock **733** (as shown in FIG. **8**, the radius of the cam is decreased from about 250° (contact surface

for manual lock 731) to 110° (contact surface for secured lock 733)). Accordingly, the radius of the cam 70 that contacts the latch 50 is reduced from the first radius to the third radius, so that the spring 90 further pulls the latch 50 in the first direction w1 into the hook 51 as shown in FIG. 13(a). Accordingly, as the pin 22 of the door moves deeply into the hook 51, the rear surface of the pin 22 contacts the secure lock surface 522 of the hook 51. As the pin 22 of the door moves from the disengaging inclined surface 521 to the secure lock surface 522, the disengaging inclined surface 521 and the secure lock surface 522 may be connected via a smooth curved surface. When the spring 90 pulls the latch 50, the pin may be naturally moved smoothly from the disengaging inclined surface 521 to the secure lock surface 522.

(128) The movement of the latch 50 in the first direction w1 is made by the elasticity of the spring 90. Therefore, if the pin 22 of the door is not completely moved inside the hook 51 and is stuck in a transitory position in the hook, or if the pivoting of the latch becomes stiff or is stuck due to foreign substances and the like, even if the cam 70 rotates in the second rotational direction c2 and moves from the first mode to the third mode, the latch 50 may not pivot correspondingly to reach the third basic position from the first basic position.

(129) However, as described above, the relation of $dop < dmp < rM3 \leq dlp$ is satisfied. That is, a point at which the cam 70 contacts the contact surface 55 of the latch 50 is moved from the first radius 731 to the third radius 733 as the cam 70 rotates, the radius of the surface of the cam 70 that faces the sub-contact surface 59 may exceed the distance dmp between the position mp of the sub-contact surface 59 and the center of rotation 711 of the cam 70 when the latch 50 is in the first basic position.

(130) Therefore, even if the latch is engaged in the first basic position or between the first basic position and the second basic position, which is further away from the first basic position, while the cam 70 is rotated from the first mode to the third mode, the cam surface contacts the sub-contact surface 59 of the latch 50 and pushes the sub-contact surface 59 in the direction away from the cam, causing a kinematic interference such that the latch 50 is forcedly rotated in the first direction w1. Thus, the latch is surely moved to the third basic position.

(131) As shown in FIG. 13(a), as the secure lock surface 522 is inclined in a closing direction toward the first direction w1, when the user pulls on the door, the hook receives more force to pivot in the first direction w1. Therefore, even if the user pulls on the door, the door may not be opened.

(132) In particular, if the relation of $rM3 = dlp$ is satisfied, the latch 50 may surely reach the third basic position. When an external force is applied to the latch 50 disposed in the third basic position and the latch is pivoted in the second direction w2, as the cam 70 already contacts the sub-contact surface 59 of the latch 50, the pivoting of the latch 50 in the second direction w2 may be surely prevented via the kinematic interference.

(133) In this state, a self-cleaning operation may proceed. The cavity is heated to 400°C . and maintained for a few minutes. An inner temperature of the cavity is measured by a temperature sensor 85. Even if the self-cleaning operation is completed, an internal temperature of the cavity is continuously monitored by the controller until the internal temperature falls.

(134) When the internal temperature is lowered to a safe level, the controller 80 rotates the bidirectional rotational motor 60 in the first rotational direction c1 and rotates the cam 70 in the first rotational direction c1. Then, the pressing of the first pressing boss 721 with respect to the second switch 82 is released. As shown in FIG. 9(a), the rotation of the cam 70 in the first rotational direction c1 continues until the two pressing bosses 721 and 722 press the two switches 81 and 82, respectively. That is, the cam 70 is rotated in the first rotational direction c1 by the angle b of the two pressing and then stopped.

(135) From the position shown in FIG. 9(a), when the self-cleaning command is inputted, the cam 70 is rotated by the angle b in the second rotational direction c2 to the position shown in FIG. 13(a), and the first pressing boss 721 presses the second switch 82, the rotation of the bidirectional rotational motor 60 and the cam 70 is stopped. Then, self-cleaning operation proceeds. After the

self-cleaning operation is completed, the cam **70** rotates in the first rotational direction **c1** and return to the state as shown in FIG. **9(a)**.

(136) As described above, the self-cleaning command enables rotating the cam **70** in the first mode by the angle **b** in the second rotational direction **c2**. After the self-cleaning operation, the cam returns to the first mode again. That is, according to the self-cleaning command of the door, the cam is operated in the order of the first mode.fwdarw.the rotation in the second rotational direction (the fourth mode).fwdarw.the third mode.fwdarw.the rotation in the first rotational direction (fourth mode).fwdarw.the first mode.

(137) As described above, according to the embodiment, both the manual lock state of the door, the automatic opening operation of the door, and the secure lock operation of the door may be implemented by one latch, one drive and one power transmitting portion.

(138) Referring to FIG. **14**, an initial position search control of latch module will be described. The latch is in three basic positions such as the manual lock position, the automatic opening position, and the secure lock position, depending on whether the contact surface **55** of a latch **50** contacts any of the radiuses **731**, **732**, **733** of the latch position adjusting profile **73**.

(139) As described above, the rotational displacement of the cam **70** is controlled by the two switches **81** and **82** and the switch pressing profile **72** of the cam **70**. The controller **80** determines a rotational direction and a rotation or non-rotation of a bidirectional rotational motor based on four modes of the two switches **81** and **82** (the first mode in which the two switches are pressed, the second mode in which the first switch is only pressed, the third mode in which the second switch is only pressed, and the fourth mode in which the two switches are not pressed) to control a rotational angle or a rotation or non-rotation of the cam.

(140) As shown in FIG. **14**, in a first mode **M1** in which the switch pressing profile **72** presses the two switches, the manual lock state (the state of FIGS. **10(a)** and **12(a)**) in which the first radius **731** of the latch position adjusting profile **73** contacts the latch **10**.

(141) In this state, when the cam **70** rotates in the first rotational direction **C1**, the position of the latch position adjusting profile **73** in contact with the latch **50** is moved to the right side of the graph in FIG. **14**. In this process, a first pressing boss **721** of the cam **70** is moved in an angle between the two switches shown in FIG. **15**.

(142) When the switch pressing profile **72** of the cam **70** is moved to a position corresponding to the second mode **M2** in which the first switch is only pressed and then stopped, it can be confirmed that the cam **70** and the latch **50** are in the automatic opening state (the state of FIGS. **10(a)** and **11(a)**), that is, the state in which the second radius **732** of the latch position adjusting profile **73** of the cam **70** contacts the latch **50**. The cam **70** that has reached the second mode rotates again in the second rotational direction **c2** and moves from the second mode **M2** to the first mode **M1**.

(143) When the cam rotates in the second rotational direction **C2** in the first mode **M1**, the latch position adjusting profile **73** in contact with the latch **50** is moved to the left of the graph in FIG. **14**. In this process, the a second pressing boss **722** of the cam **70** is moved between the angles of the two switches shown in FIG. **16**.

(144) When the switch pressing profile **72** of the cam **70** is moved to a position corresponding to a third mode **M3** in which the second switch is only pressed and then stopped, it can be confirmed that the cam **70** and the latch **50** are in the secure lock state (the state of FIG. **13(a)**), that is, the state in which the third radius **733** of the latch position adjusting profile **73** of the cam **70** contacts the latch **50**. After the self-cleaning operation, the cam **70** that has reached the third mode rotates again in the first rotational direction **c1** and moves from the third mode **M3** to the first mode **M1**.

(145) As described above, the controller **80** determines the position of the cam **70** and controls the rotation of the cam **70** based on the state where at least one of the switches is pressed, that is, the first mode, the second mode and the third mode.

(146) However, in situations such as where the cooking device is turned off due to a power failure, and the like and the cooking device is turned on again, the controller needs to determine whether

the current position of the cam is in any one mode from the first mode to the fourth mode.

(147) As a result of determination, if the cam is currently in any one mode of the first mode, the second mode and the third mode depending on the pressed state of the switch, the current position of the cam may be clearly determined. Therefore, it is possible to precisely control the state of the latch module (the manual lock, the automatic opening, and the secure lock) by controlling the drive and the cam.

(148) However, as a result of the determination, if the cam is in the fourth mode state where none of the switches are pressed, it is not possible to clearly determine the current position of the cam. For example, referring to FIG. 14, all the remaining ranges except for the first mode M1, the second mode M2 and the third mode M3 shown are the fourth mode M4.

(149) According to the embodiment, when a current state of the cam and the latch cannot be determined in the initial operation of the cooking device, the position is initialized, which may be a position search and an initial position setting operations.

(150) When the cam is in the fourth mode, with respect to searching the position and setting the initial position, the initial position may be searched by rotating the cam in any one direction and determining an initially pressed switch. For example, when the cam and the latch are positioned where the cam in the fourth mode, the cam is rotated in any direction to reach any one of the first mode M1, the second mode M2 and the third mode M3.

(151) However, according to the embodiment, as the latch module 4 is incorporated with an automatic opening function of the door, there is a problem that the door may be automatically opened when the controller 80 reaches the second mode M2 while searching for the initial position of the cam 70. That is, the cam should not reach the second mode M2 during the rotation of the cam while determining the initial position of the cam.

(152) Thus, according to the embodiment, the switches 81 and 82 are arranged so that the buttons 811 and 812 have a predetermined angle θ so that the buttons 811 and 812 are not arranged on a straight line on the center of rotation of the cam, and the cam has a switch pressing profile 72 having two pressing bosses 721 and 722 having an angle corresponding thereto, and the bidirectional rotational motor 60 is used as the drive 60.

(153) The motor 60 is driven in the first rotational direction c1 to switch the cam 70 to the second mode M2 when the automatic opening function is performed based on the first mode M1 in the manual lock state, and the motor 60 is driven again in the second rotational direction c1 to be returned to the first mode M1.

(154) Further, the motor 60 is driven in the second rotational direction c1 to switch the cam to the third mode M3 when the secure lock function is performed based on the first mode M1 in the manual locked state, and the motor 60 is driven again in the first rotational direction c2 to be returned to the first mode M1.

(155) According to the above-described control method, the position of the latch position adjusting profile 73 in contact with the contact surface of the latch 50 is only within a contact range R of FIG. 14. Based on this principle, According to the embodiment, in an initial operation of the cooking device, assuming the position of the cam 70 is in the fourth mode in which the two switches are not pressed, the cam 70 is rotated in the second rotational direction c2 in order to determine the initial positions of the cam 70 and the latch 50.

(156) When the cam 70 is in the fourth mode in the normal operation range R, the position of the cam 70 in contact with the latch 50 is between the third mode and the first mode of FIG. 14 (between about 120° and 240°), and between the first mode and the second mode (about 260° to 370° (10°)). Therefore, when the cam 70 is rotated in the second rotational direction c2, the cam 70 reaches the third mode or reaches the first mode, but does not reach the second mode. Therefore, when the cam 70 is rotated in the second rotational direction c2, the door does not in the initial position search step.

(157) Geometrically, a position range in which the cam 70 does not press both the switches are

three cases, for example, a first case in which the second pressing boss **722** is within the angle of the two switches as shown in FIG. **15**, a second case in which the first pressing boss **721** is within the angle of the two switches as shown in FIG. **16**, and a third case in which the two pressing bosses **721** and **722** deviate from the angle of the two switches as shown in FIG. **17**.

(158) Among these cases, the state as shown in FIG. **15** may be between the second mode and the first mode (between about 260° to 370° (10°) of FIG. **14**. The state as shown in FIG. **16** may be the case where the cam is in the first mode and the third mode (about 120° to 240°).

(159) Specifically, if the cam was initially in the position shown in FIG. **15**, the cam reaches the first mode **M1** after the cam is rotated in the second rotational direction **c2** for searching the initial position of the cam. The controller **80** stops driving the motor **60** when the two switches **81**, **82** are pressed. The cam **70** and the latch **50** are disposed in the manual locked state.

(160) If the cam **70** is initially in the position shown in FIG. **16**, the cam **70** reaches the third mode **M3** after the cam is rotated in the second rotational direction **c2** for searching the initial position of the cam. As the third mode is the secure lock position, the door is not automatically opened. When the second switch **82** is pressed and the first switch **81** is not pressed, the controller drives the motor **60** again in the opposite direction to rotate the cam in the first rotational direction **c1**. The cam reaches the first mode **M1**. The controller stops driving the motor **60** when both switches **81**, **82** are pressed. The cam and latch may be in the manually locked position.

(161) That is, within a normal operating range **R**, case 1 and case 2 as shown in FIG. **18** are provided as an example of searching an initial position of the cam **70**. Therefore, the door may not be automatically opened during search of the cam **70** with respect to the initial position.

(162) However, it may not exclude that the position of the cam **70** is in the state shown in FIG. **17**. For example, the initial position of the cam during manufacturing of the latch module **4** may be in the state as shown in FIG. **17**. According to the embodiment, the controller **80** causes the cam **70** to rotate in the second rotational direction **c2** when the cam is in the fourth mode during the initial driving of the cooking device. If the cam rotates in the second rotational direction **c2** and reaches the second mode **M2**, that is, if the first switch **81** is only pressed and the second switch **82** is not pressed, the cam is further rotated in the second rotational direction **c2** as shown in case 3 in FIG. **18**. As a result, the cam enters the first mode **M1**. The controller stops the driving the motor **60** when both switches **81**, **82** are pressed. The cam and latch may be in the manually locked position.

(163) In such a state, the door may be opened. However, when the power is supplied to the latch module **4** before the latch module **4** is installed in the cooking device during the manufacturing of the product, the cam **70** and the latch **50** become the first mode **M1** through the initial search step as described above. Further, during the manufacturing of the product, when the latch module **4** is installed in the cooking device and the power is supplied to the cooking device for inspection of the cooking device, the above-described initial search step is performed and the cam and the latch are in the first mode **M1**. Therefore, when the consumer purchases the cooking device and first uses the cooking device, the cam may not be in the state as shown in FIG. **17**.

(164) FIG. **19** is block diagram of an electronic system to implement an automatic opening structure and the control method as described above according to an embodiment of the invention. The electronic system includes, but not limited to, controller **80**, the input device **100**, such as a touch panel, the display **90**, switches **81**, **82**, the temperature sensor **85**, and the door sensor **88**. The display **90** may display time, various operation status of the home appliance, and the like. The input device **100** may be used to input instructions pertaining to the operation of the cooking device and the like. The controller **80** receives various signals and instructions and controls the cooking device based on the received signals and instructions. For instance, the controller **80** may receive instructions from the input device **100**. The controller **80** may receive signals from the switches **81**, **82**, the door sensor **88**, and the temperature sensor **85**. The controller **80** may control the motor **60** to drive the cam **70**, which in turn interacts with the latch **50**.

(165) As described above, the controller **80** may control the position of the latch **50** by controlling

the rotational displacement of the cam **70** through the switches **81** and **82** and the motor **60**. In other words, the controller **80** may control such that the position of the latch **50** is at least one of the first basic position, the second basic position (the automatic opening position) and the third basic position (the secure lock position). Further, as described above, the control as shown in FIG. **18** may also be possible through the controller **80**.

(166) The controller may be a microprocessor, specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), and the like.

(167) While the present disclosure has been described with reference to exemplary embodiments thereof, it is to be understood that the disclosure is not limited to the disclosed embodiments and drawings, and it will be apparent that various modifications may be made by those skilled in the art within the range of the technical idea of the present disclosure. For example, in the embodiment of the present disclosure, a structure in which a cam is applied as a power transmitting portion is exemplified, but a power transmission structure that adjusts a basic position of the latch is implemented through a combination of various other kinematic structures such as a long hole, a hinge, and a link, and the like.

(168) While the present disclosure does not explicitly describe the working effects based on the configuration of the present disclosure in the description of the embodiments of the present disclosure, it is to be noted that the expectable effects are acknowledged based on the configuration.

Claims

1. A latch module for opening and closing a door of an appliance, comprising: a latch; a spring that applies an elastic force to the latch; a drive that provides power to move the latch; a cam that transmits the power of the drive to the latch, wherein the spring and the cam move the latch in a first basic position, a second basic position in which the latch is moved in a second direction from the first basic position, and a third basic position in which the latch is moved in a first direction from the first basic position, and wherein the first basic position is a position in which, when an external force greater than the elastic force of the spring is applied to the door, the external force on the door causes the latch to move in the second direction and releases the latch from an engaging structure so that the door is opened, the second basic position is a position in which the latch is not engaged with the engaging structure, and, the third basic position is a position in which, even if the external force is applied to the door, a state in which the latch is engaged with the engaging structure is maintained.
2. The latch module of claim 1, wherein the cam including a switch pressing profile, and a first switch and a second switch that are turned on or off by the switch pressing profile of the cam, wherein the switch pressing profile comprises a first pressing protrusion that presses the first switch or the second switch depending on a rotational position thereof, and a second pressing protrusion that presses the first switch or the second switch depending on a rotational position thereof.
3. The latch module of claim 2, wherein the first switch and the second switch have a predetermined angle less than 180° therebetween based on a center of rotation of the cam, and wherein the first pressing protrusion and the second pressing protrusion have an angle therebetween corresponding to the predetermined angle between the first switch and the second switch.
4. The latch module of claim 2, wherein depending on a rotation position of the cam, in a first mode of the switch pressing profile, the first switch and the second switch are both pressed, in a second mode of the switch pressing profile, the first switch is pressed and the second switch is not pressed, in a third mode of the switch pressing profile, the first switch is not pressed and the second

switch is pressed, the latch is in the first basic position when the switch pressing profile is in the first mode, the latch is in the second basic position when the switch pressing profile is in the second mode, and the latch is in the third basic position when the switch pressing profile is in the third mode.

5. The latch module of claim 1, wherein the first direction is opposite to the second direction.

6. The latch module of claim 1, wherein the cam comprises a latch position adjusting profile that contacts the latch, and the latch position adjusting profile comprises a first radius that has a radius such that the latch is disposed in the first basic position when the first radius contacts a contact surface of the latch, a second radius that has a radius such that the latch is disposed in the second basic position when the second radius contacts the contact surface of the latch, and a third radius that has a radius such that the latch is disposed in the third basic position when the third radius contacts the contact surface of the latch.

7. The latch module of claim 6, wherein a center of rotation of the cam is disposed further in a direction of the first direction than the contact surface of the latch that contacts the cam, the radius of the second radius is greater than the radius of the first radius, and the radius of the third radius is less than the radius of the first radius.

8. The latch module of claim 1, wherein the drive comprises a bi-directional rotational motor.

9. The latch module of claim 1, wherein the latch comprises an inclined surface to cause the latch to be released from the engaging structure when the external force is applied to the door in the first basic position.
