

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417426
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Brandão; Débora Setton et al.

Systems and methods for computer memory optimization for the storage of delivery time information for a product sold online

Abstract

In e-commerce, web content (such as a checkout page) may include delivery time information associated with a product. To obtain the delivery time information, the computer may send an application programming interface (API) request to the fulfillment network. However, a fulfillment network is often delayed in responding to an API request. Also, there may be data privacy concerns with this approach. Alternatively, precomputed delivery time information may be sent from the fulfillment network, but this may result in a large amount of data that must be stored. In some embodiments, a data structure may be generated that includes a product-to-schedule mapping and a set of delivery schedule tables. Each of the delivery schedule tables may be based on a respective different set of one or more categories to which multiple ones of a plurality of products map. Computer memory resources may be saved.

Inventors: Brandão; Débora Setton (Montreal, CA), Tzavelas; George (Carp, CA), Damus; Linda (Ottawa, CA), Zhao; Lin (Kanata, CA), Salvetti; Djoume (Ottawa, CA)

Applicant: SHOPIFY INC. (Ottawa, CA)

Family ID: 1000008821689

Assignee: SHOPIFY INC. (Ottawa, CA)

Appl. No.: 17/983945

Filed: November 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240062142 A1	Feb. 22, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: G06Q10/0833 (20230101)

U.S. Cl.:

CPC G06Q10/0833 (20130101);

Field of Classification Search

CPC: G06Q (10/083); G06Q (10/087); H04W (4/029); G06F (9/451); G06F (3/04812); G06F (3/0487); H04L (67/18)

USPC: 705/330

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8666846	12/2013	Chenault	705/28	G06Q 10/087
11526831	12/2021	Rafii	N/A	G06F 3/0487
11593751	12/2022	Shiely	N/A	G06Q 10/06311
11893751	12/2023	Ansari	N/A	G06T 7/74
2020/0090119	12/2019	Shiely	N/A	G06Q 30/0625

OTHER PUBLICATIONS

“Consumer Marketing Strategy and E-Commerce in the Last Decade: A Literature Review”
Published by Journal of Theoretical and Applied Electronic Commerce Research (Year: 2021).
cited by examiner

Primary Examiner: Elchanti; Zeina

Attorney, Agent or Firm: Hickman Becker Bingham Ledesma LLP

Background/Summary

(1) The present application claims the benefit under 35 U.S.C § 119(e) of U.S. Provisional Patent Application Ser. No. 63/398,255, entitled “Systems and Methods for Computer Memory Optimization for the Storage of Delivery Time Information for a Product Sold Online”, which was filed on Aug. 16, 2022, and which is incorporated herein by reference.

FIELD

(1) The present application relates to computer memory optimization for storage of delivery time information in e-commerce.

BACKGROUND

(2) In an e-commerce system, a user can purchase an item that is physically located far away from

the user. The product may be shipped to the user. The delivery time, i.e., the time between the purchase of the product by the user and the arrival of the product at the destination address chosen by the user, can vary depending on many factors.

(3) When a user is interacting with the web content of an online store or online marketplace, it is sometimes desirable for the web content to display information related to the delivery time of the product. For example, when a user requests a product page (i.e., a web page that conveys information related to a product offered for sale), it may be desired that the returned web content include information related to the delivery time of that product. In another example, during an online checkout process it may be desired that the generated web content includes information related to delivery time of the product.

SUMMARY

(4) The information related to the delivery time of a product sold online needs to be reliable. For example, the information might form the basis of a delivery promise provided to a user ahead of purchase on a product page, e.g. “Purchase now and receive the product by Wednesday”. As another example, the information might form the basis of a delivery promise provided to a user on a “checkout” page.

(5) Some of the information required to compute delivery time information may not be known or inferable until immediately before the delivery time information must be generated. For example, a request for web content received from a user device may provide some of the information required for the computation of the delivery time information, e.g. the request may include an identification of the product and/or information used to determine a destination address associated with the user. Since the web content rendered must include the delivery time information, the computation must be executed in the time between receiving the request for the web content and returning the web content, which in the context of online web browsing is a very small window.

(6) For example, a user may click a hyperlink for a product page. The request for the product page (e.g. HTTP or HTTPS request) sent from the user device may include an identity of the product. The identity may be or map to a stock keeping unit (SKU) number for that product. In response, the computer generating the web content needs to retrieve the identity of the product from the request (because it is not known in advance of receiving the request), and then compute delivery time information. The computer then needs to include that delivery time information in response to the request so that the loaded webpage on the user device includes the delivery time information.

(7) An e-commerce system may work with a fulfillment network, which may be an integrated fulfillment service or may be provided by one or more third-party logistics providers (3PLs). A fulfillment network may manage the storage of inventory, as well as the shipping and delivery of products that are purchasable using the e-commerce system. For example, the e-commerce system may host the online store of a first merchant whose products are managed by a first 3PL, and may host the online store of a second merchant whose products are managed by a second, different 3PL. For a given product sold on the e-commerce system, the fulfillment network responsible for the delivery of that product may be responsible for computing delivery time information, and upon purchase of that product by a user, ensuring that the product is delivered according to the delivery time information. Accordingly, the computer generating web content for a user may request delivery time information from the fulfillment network, so that an accurate delivery promise may be surfaced to a user on the e-commerce platform regarding the product.

(8) The computer generating the web content is faced with the following technical problems. To be able to display delivery time information associated with a product to a user as part of web content, the computer may send an application programming interface (API) request to the fulfillment network responsible for delivering the product. The API request may contain information required for the fulfillment network to be able to compute the delivery time information, such as an identifier for the product and an indication of the shipping destination (e.g. a destination address or area of the user). At least some of this information sent in the API request may originate from the

information in the request for web content received from the user. The response from the API request is incorporated into the web content returned to the user. However, a fulfillment network is often delayed in responding to such an API request, leading to a delay in generating and displaying the web content. Even a delay of two seconds to receive a reply to the API request may be too long in the context of web browsing in real-time in which the user expects immediate return of requested web content. This in turn may result in user frustration and/or a loss of customer or transaction.

(9) Moreover, there may be data privacy concerns related to sending API requests to a fulfillment network, such as a 3PL, before users have actually purchased products on the e-commerce platform. For example, if the computer sends an API request when a user simply clicks on a product page or adds an item to their online “cart”, the fulfillment network receiving the API request would implicitly gain knowledge about products that are of interest to users of the e-commerce platform. This may be undesirable both from the perspective of the user and the online store or commerce platform on which the user is performing their online shopping.

(10) To address the issues related to delayed API request responses and privacy, the computer may, for each product available on an e-commerce platform, request for the fulfillment network responsible for the delivery of the product to precompute delivery time information and send that information to the computer. A product may have multiple product variants, for example a product that is available in different sizes and colors. In this case, each product variant might or might not be considered a different product when tracking inventory and requesting delivery time information, depending upon the implementation. The delivery time information may be received by the computer and stored in memory for quick access when generating web content. However, this results in a large amount of data that must be stored by the computer. In particular, for each product available on the e-commerce platform, the fulfillment network must compute the delivery time information associated with every possible destination address or area. For each product available on the e-commerce platform, there would need to be at least one data table (or equivalent structure) containing information related to delivery time for every possible destination address or area. There may even be multiple tables per product, e.g., one for each fulfillment center at which the product is stocked. The number of tables received by the computer would therefore be equal to or greater than the number of products available for purchase on the e-commerce platform, and they would all need to be stored locally for quick access, e.g. in a fast-access cache or random access memory (RAM). As the number of products available on the e-commerce platform grows, and may reach into the millions or tens of millions, the amount of data that must be stored by the computer may be too large to be stored locally, and may need to be stored in the computer's long-term memory, which may take longer to retrieve, and thereby add further to the delay when loading web content for a user. Further, since delivery time information must be frequently updated (e.g., as the expiry deadline for a delivery promise is passed), these large volumes of data must be continually received and stored by the computer. This also poses a data transmission problem between the fulfillment network and computer due to the large volume of data having to be continually re-sent.

(11) Therefore, there is a need for a system which can more quickly and dynamically incorporate reliable delivery time information into web content transmitted to a user of an e-commerce platform, without requiring so much data to be continually sent by the fulfillment network and locally stored, and while still addressing issues related to delayed API request responses and privacy.

(12) In some embodiments, a data structure may be generated. The data structure may include a product-to-schedule mapping, and a set of delivery schedule tables. The data structure may be generated and sent by a fulfillment network, received and stored by the computer generating web content, and used by the computer during web browsing to quickly generate reliable delivery time information based on data in a request for web content.

(13) In some embodiments, the data structure may be stored in a contiguous portion of memory. In

other embodiments, one or more portions of the data structure (e.g., a delivery schedule table) might not be stored in contiguous memory, e.g. storage of the data structure may be distributed. In some embodiments, some or all of the data structure (e.g. a delivery schedule table) may be represented as a linked list or binary tree.

(14) The delivery schedule tables, which may be lookup tables, may be computed and generated based on categories which can be applied to all products, such as weight classes, dimensions, fulfillment center locations, etc. For example, a fulfillment network may decide to categorize products by weight class and available fulfillment center locations (e.g. by creating and using intermediate mappings between, e.g., product and weight class, and product and available fulfillment center locations). The number of delivery schedule tables may then correspond to the number of weight class and fulfillment center combinations. The number of delivery schedule tables in the data structure may be relatively small when compared to the number of purchasable products on the e-commerce platform. As a result, the storing and updating of the delivery schedule tables may take up much less data than the alternative of storing and updating delivery schedule tables where each purchasable product has its own unique one or more delivery schedule tables. Accordingly, by grouping products into different categories (e.g., different weight categories and/or different inventory location categories) having similar delivery timeframes, there may be a much smaller set of delivery schedule tables. This smaller set of delivery schedule tables is more compact and so may be more easily stored in local memory as compared to the alternative, and result in much less data to be transferred over a network from the fulfillment network.

(15) The product-to-schedule mapping may map an identifier for a product (e.g., an SKU number of the product) to a delivery schedule table. When the computer requires delivery time information for a product, the computer may use the product-to-schedule mapping information to know which delivery schedule table should be consulted to find the delivery time information for that product.

(16) In some embodiments, there is provided a computer-implemented method. The method may include a step of receiving, from a user device over a network, a request for web content associated with one of a plurality of products sold on an e-commerce platform. The method may further include a step of replying to the request. The replying step may include extracting, from a data structure, delivery schedule information for the one product. The data structure may include a plurality of delivery schedule tables, and a mapping of each of the plurality of products sold on the e-commerce platform to a respective one of the plurality of delivery schedule tables. Each of the plurality of delivery schedule tables may be based on a respective different set of one or more categories to which multiple ones of the plurality of products map. The replying step may further include, based on the delivery schedule information extracted from the data structure, generating an indication including delivery time information relating to the one product. The replying step may further include incorporating the indication into the web content, and transmitting the web content over the network for display on the user device.

(17) In some embodiments, a total number of the plurality of delivery schedule tables may be less than a total number of the plurality of products sold on the e-commerce platform. In some embodiments, the replying may occur within a timing constraint associated with providing the web content during a user's real-time online interaction with the e-commerce platform. In some embodiments, the replying step may further include obtaining, from the request for web content, information related to a delivery destination associated with the user device, and the delivery destination may be used to extract the delivery schedule information from the data structure during the replying. In some embodiments, the information related to the delivery destination associated with the user device may be an Internet Protocol address of the user device.

(18) In some embodiments, the replying step may include obtaining, from the request for web content, an identifier that uniquely identifies the one of the plurality of products. The identifier may be used to extract the delivery schedule information from the data structure during the replying step.

(19) In some embodiments, the replying step may include obtaining, from the request for content, information related to a delivery destination associated with the user device and an identifier that uniquely identifies the one of the plurality of products. The extracting may include using the identifier to consult the mapping of each of the plurality of products to the respective one of the plurality of delivery schedule tables, to determine a delivery schedule table of the plurality of delivery schedule tables that corresponds with the one of the plurality of products. The extracting may further include using the delivery destination to extract the delivery schedule information from the delivery schedule table.

(20) In some embodiments, different delivery schedule tables may correspond to different product characteristic categories. In some embodiments, the different product characteristic categories may include different weight categories, each of the weight categories defining a different weight range. In some embodiments, different delivery schedule tables may correspond to different fulfillment center location categories.

(21) In some embodiments, the plurality of delivery schedule tables and the mapping may be updated to reflect a most current version of the plurality of delivery schedule tables and a most current version of the mapping. In some embodiments, the update of the delivery schedule tables may occur at a different frequency from the update of the mapping. In some embodiments, at least one of the plurality of delivery schedule tables may be updated in response to expired delivery time information, and the mapping may be updated in response to a particular inventory change.

(22) In some embodiments, in response to inventory for a particular product at a particular fulfillment center dropping to zero or dropping below a threshold, the mapping may be updated to no longer map the particular product to the respective delivery schedule table to which the particular product was mapped. In some embodiments, the particular product may instead be mapped to a different delivery schedule table.

(23) A system is also disclosed that is configured to perform the methods disclosed herein. For example, the system may include at least one processor to directly perform (or instruct the system to perform) the method steps, e.g. when the at least one processor executes instructions stored in memory. The system may further include memory to store the data structure.

(24) In some embodiments, there is provided a computer readable medium having stored thereon computer-executable instructions that, when executed by a computer, cause the computer to perform operations of the methods disclosed herein. The computer readable medium may be non-transitory.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments will be described, by way of example only, with reference to the accompanying figures wherein:

(2) FIG. 1 is a block diagram of an e-commerce platform, according to some embodiments;

(3) FIG. 2 is an example of a home page of an administrator, according to some embodiments; and

(4) FIG. 3 illustrates the e-commerce platform of FIG. 1, but including a delivery time information generator.

(5) FIG. 4 is a block diagram illustrating an example system for generating information relating to the delivery time of a product sold online, according to some embodiments;

(6) FIG. 5 illustrates a computer-implemented method, according to some embodiments;

(7) FIG. 6 illustrates an example diagram of product-to-schedule mappings associated with products sold online, and a set of delivery schedule tables, according to some embodiments;

(8) FIG. 7 illustrates an example system overview for generating information relating to the delivery time of a product sold online, according to some embodiments;

- (9) FIG. 8 illustrates an example flow for generating information relating to the delivery time of a product sold online, according to some embodiments; and
- (10) FIGS. 9-11 illustrate example web pages which may be provided to a user via a user interface of a user device, according to some embodiments.

DETAILED DESCRIPTION

(11) For illustrative purposes, specific embodiments will now be explained in greater detail below in conjunction with the figures.

(12) An Example e-Commerce Platform

(13) Although integration with a commerce platform is not required, in some embodiments, the methods disclosed herein may be performed on or in association with a commerce platform such as an e-commerce platform. Therefore, an example of a commerce platform will be described.

(14) FIG. 1 illustrates an example e-commerce platform **100**, according to some embodiments. The e-commerce platform **100** may be used to provide merchant products and services to customers. While the disclosure contemplates using the apparatus, system, and process to purchase products and services, for simplicity the description herein will refer to products. All references to products throughout this disclosure should also be understood to be references to products and/or services, including, for example, physical products, digital content (e.g., music, videos, games), software, tickets, subscriptions, services to be provided, and the like.

(15) While the disclosure throughout contemplates that a ‘merchant’ and a ‘customer’ may be more than individuals, for simplicity the description herein may generally refer to merchants and customers as such. All references to merchants and customers throughout this disclosure should also be understood to be references to groups of individuals, companies, corporations, computing entities, and the like, and may represent for-profit or not-for-profit exchange of products. Further, while the disclosure throughout refers to ‘merchants’ and ‘customers’, and describes their roles as such, the e-commerce platform **100** should be understood to more generally support users in an e-commerce environment, and all references to merchants and customers throughout this disclosure should also be understood to be references to users, such as where a user is a merchant-user (e.g., a seller, retailer, wholesaler, or provider of products), a customer-user (e.g., a buyer, purchase agent, consumer, or user of products), a prospective user (e.g., a user browsing and not yet committed to a purchase, a user evaluating the e-commerce platform **100** for potential use in marketing and selling products, and the like), a service provider user (e.g., a shipping provider **112**, a financial provider, and the like), a company or corporate user (e.g., a company representative for purchase, sales, or use of products; an enterprise user; a customer relations or customer management agent, and the like), an information technology user, a computing entity user (e.g., a computing bot for purchase, sales, or use of products), and the like. Furthermore, it may be recognized that while a given user may act in a given role (e.g., as a merchant) and their associated device may be referred to accordingly (e.g., as a merchant device) in one context, that same individual may act in a different role in another context (e.g., as a customer) and that same or another associated device may be referred to accordingly (e.g., as a customer device). For example, an individual may be a merchant for one type of product (e.g., shoes), and a customer/consumer of other types of products (e.g., groceries). In another example, an individual may be both a consumer and a merchant of the same type of product. In a particular example, a merchant that trades in a particular category of goods may act as a customer for that same category of goods when they order from a wholesaler (the wholesaler acting as merchant).

(16) The e-commerce platform **100** provides merchants with online services/facilities to manage their business. The facilities described herein are shown implemented as part of the platform **100** but could also be configured separately from the platform **100**, in whole or in part, as stand-alone services. Furthermore, such facilities may, in some embodiments, may, additionally or alternatively, be provided by one or more providers/entities.

(17) In the example of FIG. 1, the facilities are deployed through a machine, service or engine that

executes computer software, modules, program codes, and/or instructions on one or more processors which, as noted above, may be part of or external to the platform **100**. Merchants may utilize the e-commerce platform **100** for enabling or managing commerce with customers, such as by implementing an e-commerce experience with customers through an online store **138**, applications **142A-B**, channels **110A-B**, and/or through point of sale (POS) devices **152** in physical locations (e.g., a physical storefront or other location such as through a kiosk, terminal, reader, printer, 3D printer, and the like). A merchant may utilize the e-commerce platform **100** as a sole commerce presence with customers, or in conjunction with other merchant commerce facilities, such as through a physical store (e.g., 'brick-and-mortar' retail stores), a merchant off-platform website **104** (e.g., a commerce Internet website or other internet or web property or asset supported by or on behalf of the merchant separately from the e-commerce platform **100**), an application **142B**, and the like. However, even these 'other' merchant commerce facilities may be incorporated into or communicate with the e-commerce platform **100**, such as where POS devices **152** in a physical store of a merchant are linked into the e-commerce platform **100**, where a merchant off-platform website **104** is tied into the e-commerce platform **100**, such as, for example, through 'buy buttons' that link content from the merchant off platform website **104** to the online store **138**, or the like.

(18) The online store **138** may represent a multi-tenant facility comprising a plurality of virtual storefronts. In embodiments, merchants may configure and/or manage one or more storefronts in the online store **138**, such as, for example, through a merchant device **102** (e.g., computer, laptop computer, mobile computing device, and the like), and offer products to customers through a number of different channels **110A-B** (e.g., an online store **138**; an application **142A-B**; a physical storefront through a POS device **152**; an electronic marketplace, such, for example, through an electronic buy button integrated into a website or social media channel such as on a social network, social media page, social media messaging system; and/or the like). A merchant may sell across channels **110A-B** and then manage their sales through the e-commerce platform **100**, where channels **110A** may be provided as a facility or service internal or external to the e-commerce platform **100**. A merchant may, additionally or alternatively, sell in their physical retail store, at pop ups, through wholesale, over the phone, and the like, and then manage their sales through the e-commerce platform **100**. A merchant may employ all or any combination of these operational modalities. Notably, it may be that by employing a variety of and/or a particular combination of modalities, a merchant may improve the probability and/or volume of sales. Throughout this disclosure the terms online store **138** and storefront may be used synonymously to refer to a merchant's online e-commerce service offering through the e-commerce platform **100**, where an online store **138** may refer either to a collection of storefronts supported by the e-commerce platform **100** (e.g., for one or a plurality of merchants) or to an individual merchant's storefront (e.g., a merchant's online store).

(19) In some embodiments, a customer may interact with the platform **100** through a customer device **150** (e.g., computer, laptop computer, mobile computing device, or the like), a POS device **152** (e.g., retail device, kiosk, automated (self-service) checkout system, or the like), and/or any other commerce interface device known in the art. The e-commerce platform **100** may enable merchants to reach customers through the online store **138**, through applications **142A-B**, through POS devices **152** in physical locations (e.g., a merchant's storefront or elsewhere), to communicate with customers via electronic communication facility **129**, and/or the like so as to provide a system for reaching customers and facilitating merchant services for the real or virtual pathways available for reaching and interacting with customers.

(20) In some embodiments, and as described further herein, the e-commerce platform **100** may be implemented through a processing facility. Such a processing facility may include a processor and a memory. The processor may be a hardware processor. The memory may be and/or may include a non-transitory computer-readable medium. The memory may be and/or may include random access

memory (RAM) and/or persisted storage (e.g., magnetic storage). The processing facility may store a set of instructions (e.g., in the memory) that, when executed, cause the e-commerce platform **100** to perform the e-commerce and support functions as described herein. The processing facility may be or may be a part of one or more of a server, client, network infrastructure, mobile computing platform, cloud computing platform, stationary computing platform, and/or some other computing platform, and may provide electronic connectivity and communications between and amongst the components of the e-commerce platform **100**, merchant devices **102**, payment gateways **106**, applications **142A-B**, channels **110A-B**, shipping providers **112**, customer devices **150**, point of sale devices **152**, etc. In some implementations, the processing facility may be or may include one or more such computing devices acting in concert. For example, it may be that a plurality of co-operating computing devices serves as/to provide the processing facility. The e-commerce platform **100** may be implemented as or using one or more of a cloud computing service, software as a service (SaaS), infrastructure as a service (IaaS), platform as a service (PaaS), desktop as a service (DaaS), managed software as a service (MSaaS), mobile backend as a service (MBaaS), information technology management as a service (ITMaaS), and/or the like. For example, it may be that the underlying software implementing the facilities described herein (e.g., the online store **138**) is provided as a service, and is centrally hosted (e.g., and then accessed by users via a web browser or other application, and/or through customer devices **150**, POS devices **152**, and/or the like). In some embodiments, elements of the e-commerce platform **100** may be implemented to operate and/or integrate with various other platforms and operating systems.

(21) In some embodiments, the facilities of the e-commerce platform **100** (e.g., the online store **138**) may serve content to a customer device **150** (using data **134**) such as, for example, through a network connected to the e-commerce platform **100**. For example, the online store **138** may serve or send content in response to requests for data **134** from the customer device **150**, where a browser (or other application) connects to the online store **138** through a network using a network communication protocol (e.g., an internet protocol). The content may be written in machine readable language and may include Hypertext Markup Language (HTML), template language, JavaScript, and the like, and/or any combination thereof.

(22) In some embodiments, online store **138** may be or may include service instances that serve content to customer devices and allow customers to browse and purchase the various products available (e.g., add them to a cart, purchase through a buy-button, and the like). Merchants may also customize the look and feel of their website through a theme system, such as, for example, a theme system where merchants can select and change the look and feel of their online store **138** by changing their theme while having the same underlying product and business data shown within the online store's product information. It may be that themes can be further customized through a theme editor, a design interface that enables users to customize their website's design with flexibility. Additionally or alternatively, it may be that themes can, additionally or alternatively, be customized using theme-specific settings such as, for example, settings as may change aspects of a given theme, such as, for example, specific colors, fonts, and pre-built layout schemes. In some implementations, the online store may implement a content management system for website content. Merchants may employ such a content management system in authoring blog posts or static pages and publish them to their online store **138**, such as through blogs, articles, landing pages, and the like, as well as configure navigation menus. Merchants may upload images (e.g., for products), video, content, data, and the like to the e-commerce platform **100**, such as for storage by the system (e.g., as data **134**). In some embodiments, the e-commerce platform **100** may provide functions for manipulating such images and content such as, for example, functions for resizing images, associating an image with a product, adding and associating text with an image, adding an image for a new product variant, protecting images, and the like.

(23) As described herein, the e-commerce platform **100** may provide merchants with sales and marketing services for products through a number of different channels **110A-B**, including, for

example, the online store **138**, applications **142A-B**, as well as through physical POS devices **152** as described herein. The e-commerce platform **100** may, additionally or alternatively, include business support services **116**, an administrator **114**, a warehouse management system, and the like associated with running an on-line business, such as, for example, one or more of providing a domain registration service **118** associated with their online store, payment services **120** for facilitating transactions with a customer, shipping services **122** for providing customer shipping options for purchased products, fulfillment services for managing inventory, risk and insurance services **124** associated with product protection and liability, merchant billing, and the like. Services **116** may be provided via the e-commerce platform **100** or in association with external facilities, such as through a payment gateway **106** for payment processing, shipping providers **112** for expediting the shipment of products, and the like.

(24) In some embodiments, the e-commerce platform **100** may be configured with shipping services **122** (e.g., through an e-commerce platform shipping facility or through a third-party shipping carrier), to provide various shipping-related information to merchants and/or their customers such as, for example, shipping label or rate information, real-time delivery updates, tracking, and/or the like.

(25) FIG. 2 depicts a non-limiting embodiment for a home page of an administrator **114**. The administrator **114** may be referred to as an administrative console and/or an administrator console. The administrator **114** may show information about daily tasks, a store's recent activity, and the next steps a merchant can take to build their business. In some embodiments, a merchant may log in to the administrator **114** via a merchant device **102** (e.g., a desktop computer or mobile device), and manage aspects of their online store **138**, such as, for example, viewing the online store's **138** recent visit or order activity, updating the online store's **138** catalog, managing orders, and/or the like. In some embodiments, the merchant may be able to access the different sections of the administrator **114** by using a sidebar, such as the one shown on FIG. 2. Sections of the administrator **114** may include various interfaces for accessing and managing core aspects of a merchant's business, including orders, products, customers, available reports and discounts. The administrator **114** may, additionally or alternatively, include interfaces for managing sales channels for a store including the online store **138**, mobile application(s) made available to customers for accessing the store (Mobile App), POS devices, and/or a buy button. The administrator **114** may, additionally or alternatively, include interfaces for managing applications (apps) installed on the merchant's account; and settings applied to a merchant's online store **138** and account. A merchant may use a search bar to find products, pages, or other information in their store.

(26) More detailed information about commerce and visitors to a merchant's online store **138** may be viewed through reports or metrics. Reports may include, for example, acquisition reports, behavior reports, customer reports, finance reports, marketing reports, sales reports, product reports, and custom reports. The merchant may be able to view sales data for different channels **110A-B** from different periods of time (e.g., days, weeks, months, and the like), such as by using drop-down menus. An overview dashboard may also be provided for a merchant who wants a more detailed view of the store's sales and engagement data. An activity feed in the home metrics section may be provided to illustrate an overview of the activity on the merchant's account. For example, by clicking on a 'view all recent activity' dashboard button, the merchant may be able to see a longer feed of recent activity on their account. A home page may show notifications about the merchant's online store **138**, such as based on account status, growth, recent customer activity, order updates, and the like. Notifications may be provided to assist a merchant with navigating through workflows configured for the online store **138**, such as, for example, a payment workflow, an order fulfillment workflow, an order archiving workflow, a return workflow, and the like.

(27) The e-commerce platform **100** may provide for a communications facility **129** and associated merchant interface for providing electronic communications and marketing, such as utilizing an electronic messaging facility for collecting and analyzing communication interactions between

merchants, customers, merchant devices **102**, customer devices **150**, POS devices **152**, and the like, to aggregate and analyze the communications, such as for increasing sale conversions, and the like. For instance, a customer may have a question related to a product, which may produce a dialog between the customer and the merchant (or an automated processor-based agent/chatbot representing the merchant), where the communications facility **129** is configured to provide automated responses to customer requests and/or provide recommendations to the merchant on how to respond such as, for example, to improve the probability of a sale.

(28) The e-commerce platform **100** may provide a financial facility **120** for secure financial transactions with customers, such as through a secure card server environment. The e-commerce platform **100** may store credit card information, such as in payment card industry data (PCI) environments (e.g., a card server), to reconcile financials, bill merchants, perform automated clearing house (ACH) transfers between the e-commerce platform **100** and a merchant's bank account, and the like. The financial facility **120** may also provide merchants and buyers with financial support, such as through the lending of capital (e.g., lending funds, cash advances, and the like) and provision of insurance. In some embodiments, online store **138** may support a number of independently administered storefronts and process a large volume of transactional data on a daily basis for a variety of products and services. Transactional data may include any customer information indicative of a customer, a customer account or transactions carried out by a customer such as, for example, contact information, billing information, shipping information, returns/refund information, discount/offer information, payment information, or online store events or information such as page views, product search information (search keywords, click-through events), product reviews, abandoned carts, and/or other transactional information associated with business through the e-commerce platform **100**. In some embodiments, the e-commerce platform **100** may store this data in a data facility **134**. Referring again to FIG. 1, in some embodiments the e-commerce platform **100** may include a commerce management engine **136** such as may be configured to perform various workflows for task automation or content management related to products, inventory, customers, orders, suppliers, reports, financials, risk and fraud, and the like. In some embodiments, additional functionality may, additionally or alternatively, be provided through applications **142A-B** to enable greater flexibility and customization required for accommodating an ever-growing variety of online stores, POS devices, products, and/or services. Applications **142A** may be components of the e-commerce platform **100** whereas applications **142B** may be provided or hosted as a third-party service external to e-commerce platform **100**. The commerce management engine **136** may accommodate store-specific workflows and in some embodiments, may incorporate the administrator **114** and/or the online store **138**.

(29) Implementing functions as applications **142A-B** may enable the commerce management engine **136** to remain responsive and reduce or avoid service degradation or more serious infrastructure failures, and the like.

(30) Although isolating online store data can be important to maintaining data privacy between online stores **138** and merchants, there may be reasons for collecting and using cross-store data, such as, for example, with an order risk assessment system or a platform payment facility, both of which require information from multiple online stores **138** to perform well. In some embodiments, it may be preferable to move these components out of the commerce management engine **136** and into their own infrastructure within the e-commerce platform **100**.

(31) Platform payment facility **120** is an example of a component that utilizes data from the commerce management engine **136** but is implemented as a separate component or service. The platform payment facility **120** may allow customers interacting with online stores **138** to have their payment information stored safely by the commerce management engine **136** such that they only have to enter it once. When a customer visits a different online store **138**, even if they have never been there before, the platform payment facility **120** may recall their information to enable a more rapid and/or potentially less-error prone (e.g., through avoidance of possible mis-keying of their

information if they needed to instead re-enter it) checkout. This may provide a cross-platform network effect, where the e-commerce platform **100** becomes more useful to its merchants and buyers as more merchants and buyers join, such as because there are more customers who checkout more often because of the ease of use with respect to customer purchases. To maximize the effect of this network, payment information for a given customer may be retrievable and made available globally across multiple online stores **138**.

(32) For functions that are not included within the commerce management engine **136**, applications **142A-B** provide a way to add features to the e-commerce platform **100** or individual online stores **138**. For example, applications **142A-B** may be able to access and modify data on a merchant's online store **138**, perform tasks through the administrator **114**, implement new flows for a merchant through a user interface (e.g., that is surfaced through extensions/API), and the like. Merchants may be enabled to discover and install applications **142A-B** through application search, recommendations, and support **128**. In some embodiments, the commerce management engine **136**, applications **142A-B**, and the administrator **114** may be developed to work together. For instance, application extension points may be built inside the commerce management engine **136**, accessed by applications **142A** and **142B** through the interfaces **140B** and **140A** to deliver additional functionality, and surfaced to the merchant in the user interface of the administrator **114**.

(33) In some embodiments, applications **142A-B** may deliver functionality to a merchant through the interface **140A-B**, such as where an application **142A-B** is able to surface transaction data to a merchant (e.g., App: “Engine, surface my app data in the Mobile App or administrator **114**”), and/or where the commerce management engine **136** is able to ask the application to perform work on demand (Engine: “App, give me a local tax calculation for this checkout”).

(34) Applications **142A-B** may be connected to the commerce management engine **136** through an interface **140A-B** (e.g., through REST (REpresentational State Transfer) and/or GraphQL APIs) to expose the functionality and/or data available through and within the commerce management engine **136** to the functionality of applications. For instance, the e-commerce platform **100** may provide API interfaces **140A-B** to applications **142A-B** which may connect to products and services external to the platform **100**. The flexibility offered through use of applications and APIs (e.g., as offered for application development) enable the e-commerce platform **100** to better accommodate new and unique needs of merchants or to address specific use cases without requiring constant change to the commerce management engine **136**. For instance, shipping services **122** may be integrated with the commerce management engine **136** through a shipping or carrier service API, thus enabling the e-commerce platform **100** to provide shipping service functionality without directly impacting code running in the commerce management engine **136**.

(35) Depending on the implementation, applications **142A-B** may utilize APIs to pull data on demand (e.g., customer creation events, product change events, or order cancelation events, etc.) or have the data pushed when updates occur. A subscription model may be used to provide applications **142A-B** with events as they occur or to provide updates with respect to a changed state of the commerce management engine **136**. In some embodiments, when a change related to an update event subscription occurs, the commerce management engine **136** may post a request, such as to a predefined callback uniform resource locator (URL). The body of this request may contain a new state of the object and a description of the action or event. Update event subscriptions may be created manually, in the administrator facility **114**, or automatically (e.g., via the API **140A-B**). In some embodiments, update events may be queued and processed asynchronously from a state change that triggered them, which may produce an update event notification that is not distributed in real-time or near-real time.

(36) In some embodiments, the e-commerce platform **100** may provide one or more of application search, recommendation and support **128**. Application search, recommendation and support **128** may include developer products and tools to aid in the development of applications, an application dashboard (e.g., to provide developers with a development interface, to administrators for

management of applications, to merchants for customization of applications, and the like), facilities for installing and providing permissions with respect to providing access to an application **142A-B** (e.g., for public access, such as where criteria must be met before being installed, or for private use by a merchant), application searching to make it easy for a merchant to search for applications **142A-B** that satisfy a need for their online store **138**, application recommendations to provide merchants with suggestions on how they can improve the user experience through their online store **138**, and the like. In some embodiments, applications **142A-B** may be assigned an application identifier (ID), such as for linking to an application (e.g., through an API), searching for an application, making application recommendations, and the like.

(37) Applications **142A-B** may be grouped roughly into three categories: customer-facing applications, merchant-facing applications, integration applications, and the like. Customer-facing applications **142A-B** may include an online store **138** or channels **110A-B** that are places where merchants can list products and have them purchased (e.g., the online store, applications for flash sales (e.g., merchant products or from opportunistic sales opportunities from third-party sources), a mobile store application, a social media channel, an application for providing wholesale purchasing, and the like). Merchant-facing applications **142A-B** may include applications that allow the merchant to administer their online store **138** (e.g., through applications related to the web or website or to mobile devices), run their business (e.g., through applications related to POS devices), to grow their business (e.g., through applications related to shipping (e.g., drop shipping), use of automated agents, use of process flow development and improvements), and the like. Integration applications may include applications that provide useful integrations that participate in the running of a business, such as shipping providers **112** and payment gateways **106**.

(38) As such, the e-commerce platform **100** can be configured to provide an online shopping experience through a flexible system architecture that enables merchants to connect with customers in a flexible and transparent manner. A typical customer experience may be better understood through an embodiment example purchase workflow, where the customer browses the merchant's products on a channel **110A-B**, adds what they intend to buy to their cart, proceeds to checkout, and pays for the content of their cart resulting in the creation of an order for the merchant. The merchant may then review and fulfill (or cancel) the order. The product is then delivered to the customer. If the customer is not satisfied, they might return the products to the merchant.

(39) In some embodiments, a customer may browse a merchant's products through a number of different channels **110A-B** such as, for example, the merchant's online store **138**, a physical storefront through a POS device **152**; an electronic marketplace, through an electronic buy button integrated into a website or a social media channel). In some cases, channels **110A-B** may be modeled as applications **142A-B**. A merchandising component in the commerce management engine **136** may be configured for creating, and managing product listings (using product data objects or models for example) to allow merchants to describe what they want to sell and where they sell it. The association between a product listing and a channel may be modeled as a product publication and accessed by channel applications, such as via a product listing API. A product may have many attributes and/or characteristics, like size and color, and many variants that expand the available options into specific combinations of all the attributes, like a variant that is size extra-small and green, or a variant that is size large and blue. Products may have at least one variant (e.g., a “default variant”) created for a product without any options. To facilitate browsing and management, products may be grouped into collections, provided product identifiers (e.g., stock keeping unit (SKU)) and the like. Collections of products may be built by either manually categorizing products into one (e.g., a custom collection), by building rulesets for automatic classification (e.g., a smart collection), and the like. Product listings may include 2D images, 3D images or models, which may be viewed through a virtual or augmented reality interface, and the like.

(40) In some embodiments, a shopping cart object is used to store or keep track of the products that

the customer intends to buy. The shopping cart object may be channel specific and can be composed of multiple cart line items, where each cart line item tracks the quantity for a particular product variant. Since adding a product to a cart does not imply any commitment from the customer or the merchant, and the expected lifespan of a cart may be in the order of minutes (not days), cart objects/data representing a cart may be persisted to an ephemeral data store.

(41) The customer then proceeds to checkout. A checkout object or page generated by the commerce management engine **136** may be configured to receive customer information to complete the order such as the customer's contact information, billing information and/or shipping details. If the customer inputs their contact information but does not proceed to payment, the e-commerce platform **100** may (e.g., via an abandoned checkout component) transmit a message to the customer device **150** to encourage the customer to complete the checkout. For those reasons, checkout objects can have much longer lifespans than cart objects (hours or even days) and may therefore be persisted. Customers then pay for the content of their cart resulting in the creation of an order for the merchant. In some embodiments, the commerce management engine **136** may be configured to communicate with various payment gateways and services **106** (e.g., online payment systems, mobile payment systems, digital wallets, credit card gateways) via a payment processing component. The actual interactions with the payment gateways **106** may be provided through a card server environment. At the end of the checkout process, an order is created. An order is a contract of sale between the merchant and the customer where the merchant agrees to provide the goods and services listed on the order (e.g., order line items, shipping line items, and the like) and the customer agrees to provide payment (including taxes). Once an order is created, an order confirmation notification may be sent to the customer and an order placed notification sent to the merchant via a notification component. Inventory may be reserved when a payment processing job starts to avoid over-selling (e.g., merchants may control this behavior using an inventory policy or configuration for each variant). Inventory reservation may have a short time span (minutes) and may need to be fast and scalable to support flash sales or “drops”, which are events during which a discount, promotion or limited inventory of a product may be offered for sale for buyers in a particular location and/or for a particular (usually short) time. The reservation is released if the payment fails. When the payment succeeds, and an order is created, the reservation is converted into a permanent (long-term) inventory commitment allocated to a specific location. An inventory component of the commerce management engine **136** may record where variants are stocked, and may track quantities for variants that have inventory tracking enabled. It may decouple product variants (a customer-facing concept representing the template of a product listing) from inventory items (a merchant-facing concept that represents an item whose quantity and location is managed). An inventory level component may keep track of quantities that are available for sale, committed to an order or incoming from an inventory transfer component (e.g., from a vendor).

(42) The merchant may then review and fulfill (or cancel) the order. A review component of the commerce management engine **136** may implement a business process merchant's use to ensure orders are suitable for fulfillment before actually fulfilling them. Orders may be fraudulent, require verification (e.g., ID checking), have a payment method which requires the merchant to wait to make sure they will receive their funds, and the like. Risks and recommendations may be persisted in an order risk model. Order risks may be generated from a fraud detection tool, submitted by a third-party through an order risk API, and the like. Before proceeding to fulfillment, the merchant may need to capture the payment information (e.g., credit card information) or wait to receive it (e.g., via a bank transfer, check, and the like) before it marks the order as paid. The merchant may now prepare the products for delivery. In some embodiments, this business process may be implemented by a fulfillment component of the commerce management engine **136**. The fulfillment component may group the line items of the order into a logical fulfillment unit of work based on an inventory location and fulfillment service. The merchant may review, adjust the unit of work, and trigger the relevant fulfillment services, such as through a manual fulfillment service

(e.g., at merchant managed locations) used when the merchant picks and packs the products in a box, purchase a shipping label and input its tracking number, or just mark the item as fulfilled. Alternatively, an API fulfillment service may trigger a third-party application or service to create a fulfillment record for a third-party fulfillment service. Other possibilities exist for fulfilling an order. If the customer is not satisfied, they may be able to return the product(s) to the merchant. The business process merchants may go through to “un-sell” an item may be implemented by a return component. Returns may consist of a variety of different actions, such as a restock, where the product that was sold actually comes back into the business and is sellable again; a refund, where the money that was collected from the customer is partially or fully returned; an accounting adjustment noting how much money was refunded (e.g., including if there was any restocking fees or goods that weren't returned and remain in the customer's hands); and the like. A return may represent a change to the contract of sale (e.g., the order), and where the e-commerce platform **100** may make the merchant aware of compliance issues with respect to legal obligations (e.g., with respect to taxes). In some embodiments, the e-commerce platform **100** may enable merchants to keep track of changes to the contract of sales over time, such as implemented through a sales model component (e.g., an append-only date-based ledger that records sale-related events that happened to an item).

(43) Generating Delivery Time Information for a Product Sold Online in the e-Commerce Platform **100**

(44) In the context of browsing through an online shop, a customer may wish to know an amount of time required for a product that may be purchased online to be delivered to them. The expected delivery time may influence the customer's decision to purchase the product from a particular online merchant for various reasons, for example due to the expectation of receiving a product within a particular timeframe, or due to needing the product before a certain date or event. As such, a system for generating delivery time information might allow for delivery time information, such as a delivery promise or an expected delivery time, to be provided to the customer while, for instance, browsing a product page of an online store/marketplace, and/or within channels relating to selling via a search engine or social media, and/or while completing an online checkout process. The preceding list is not limiting, and delivery promise or expected delivery time may also be provided to the customer elsewhere while online.

(45) As mentioned previously, there are various technical challenges to being able to provide timely delivery time information. Some of the information required to compute delivery time information may not be known or inferable until immediately before the delivery time information must be generated. While an API request may be sent to a fulfillment network responsible for managing and delivering the product, the fulfillment network is often delayed in returning the API. The API response may be too slow in the context of browsing, which may discourage users from continuing their online shopping. Additionally, there may be data privacy concerns related to sending API requests to a fulfillment network before users have actually purchased products on the e-commerce platform. While a potential solution may be for the e-commerce platform to request from the fulfillment network precomputed delivery time information, as mentioned previously this creates additional issues related to storage, efficiency, transmission, and delays.

(46) FIG. 3 illustrates the e-commerce platform **100** of FIG. 1, but with the additions of a delivery time information generator **300** and a memory **204**. The delivery time information generator **300** may be embodied as part of the commerce management engine **136**. The delivery time information generator **300** performs the delivery time information generating methods disclosed herein, such as receiving a request for web content associated with a product sold online, and extracting delivery schedule information relating to the product. The delivery time information generator **300** may be implemented by one or more general-purpose processors that execute instructions stored in a memory (e.g. in memory **204**) or stored in another computer-readable medium. The instructions, when executed, may cause the delivery time information generator **300** to perform the operations of

the delivery time information generator **300**, e.g., operations relating to the generation of delivery time information to be displayed in association with a product sold in a merchant's online store **138**. Alternatively, some or all of the delivery time information generator **300** may be located inside the e-commerce platform **100** but external to, and coupled to, the commerce management engine **136**. In some embodiments, the delivery time information generator **300** may instead be located externally to the e-commerce platform **100** and possibly coupled to the commerce management engine **136**.

(47) Although the delivery time information generator **300** in FIG. **3** is illustrated as a distinct component of the e-commerce platform **100** in commerce management engine **136**, this is only an example. The delivery time information generator **300** could also or instead be provided by another component residing within or external to the e-commerce platform **100**. In some embodiments, either or both of the applications **142A-B** may provide a delivery time information generator **300** that implements the functionality described herein. The location of the delivery time information generator **300** is implementation specific. In some implementations, the delivery time information generator **300** is provided at least in part by an e-commerce platform, either as a core function of the e-commerce platform or as an application or service supported by or communicating with the e-commerce platform. In some embodiments, at least a portion of the delivery time information generator **300** may be implemented in a user device (e.g. merchant device **102** and/or customer device **150**). For example, the customer device **150** might store and run at least some of the delivery time information generator **300** locally as a software application.

(48) Although the embodiments described herein may be implemented using the delivery time information generator **300** in e-commerce platform **100**, the embodiments are not limited to the specific e-commerce platform **100** of FIGS. **1** to **3** and could be used in connection with any e-commerce platform. Also, the embodiments described herein need not necessarily be implemented in association with an e-commerce platform, although e-commerce platform, as used herein, has a broad meaning and includes online marketplaces and standalone online stores. To encompass all possibilities, the embodiments below will be described more generally.

(49) Example System for Generating Delivery Time Information

(50) FIG. **4** is a block diagram illustrating an example system **400** for generating delivery time information associated with a product sold by a merchant, according to some embodiments. The system **400** includes a delivery time information generator **402**, a network **420**, a user device **430**, and a fulfillment network **440**.

(51) The delivery time information generator **402** may be part of an e-commerce platform, such as e-commerce platform **100**. As illustrated, the delivery time information generator **402** includes a processor **404**, memory **406**, and a network interface **408**.

(52) The processor **404** directly performs, or instructs the delivery time information generator **402** to perform, the operations described herein as being performed by the delivery time information generator **402**, such as extracting delivery schedule information for a product or providing content for display on a user interface of a user device such as user device **430**. The processor **404** may be implemented by one or more general purpose processors that execute instructions stored in a memory (e.g. in memory **406**) or stored in another computer-readable medium. The instructions, when executed, cause the processor **404** to directly perform, or instruct the delivery time information generator **402** to perform the operations described herein. Alternatively, the processor **404** may be implemented using dedicated circuitry, such as a programmed FPGA, a GPU, or an ASIC.

(53) The memory **406** may store instructions and data used or generated by the delivery time information generator **402**. For example, the memory **406** may store software instructions or modules configured to implement some or all of the functionality and/or embodiments described herein and that are executed by the processor **404**. The memory **406** may include a delivery data structure **410**, which includes delivery schedule tables **412** and product-to-schedule mappings **414**,

as described herein. As well, the memory **406** includes web content **416**, which may be transmitted over the network **420** for display on a user device. A single memory **414** is shown in FIG. **4**, but in implementation the memory **406** may be distributed. Web content **416** may include web content transmitted to a user device, such as an online store product page or an online checkout page. Content from web content **416** may be dynamically modified by delivery time information generator **402**, based on data stored in data structure **410**, before being transmitted over network **420** for display on user device **430**.

(54) The network interface **408** is provided for communicating over a network, e.g. to communicate with user device **430**. The network interface **408** may be implemented as a network interface card (NIC), and/or a computer port (e.g. a physical outlet to which a plug or cable connects), and/or a network socket, etc., depending upon the implementation.

(55) In some embodiments, the processor **404**, memory **406**, and/or network interface **408** may be located outside of the delivery time information generator **402**.

(56) The network **420** may be a computer network implementing wired and/or wireless connections between different devices, including the delivery time information generator **402** and the user device **430**. The network **420** may implement any communication protocol known in the art. Non-limiting examples of network **420** include a local area network (LAN), a wireless LAN, an internet protocol (IP) network, and a cellular network.

(57) The user device **430** includes a processor **432**, a memory **434**, a user interface **436**, and a network interface **438**. Although only one user device **430** is illustrated in FIG. **4** for ease of explanation, a plurality of user devices may communicate with the delivery time information generator **402** over network **420**.

(58) The processor **432** of user device **430** directly performs or instructs all of the operations performed by the user device **430**. Examples of these operations include sending a request for web content relating to a product to the delivery time information generator **402**, and receiving a reply which includes the requested web content including delivery time information relating to the product, which is then displayed via the user interface **436** of user device **430**. The processor **432** may be implemented by one or more processors that execute instructions stored in the memory **434** or in another computer readable medium. Alternatively, some or all of the processor **432** may be implemented using dedicated circuitry, such as an ASIC, a GPU, or a programmed FPGA.

(59) The network interface **438** is provided for communicating over the network **420**. The structure of the network interface **438** will depend on how user device **430** interfaces with the network **420**. For example, if user device **430** is a wireless device such as a mobile phone, headset or tablet, then the network interface **438** may include a transmitter/receiver with an antenna to send and receive wireless transmissions to/from the network **420**. If the user device is a personal computer connected to the network with a network cable, then the network interface **438** may include, for example, a NIC, a computer port, and/or a network socket. The user interface **436** may be implemented as a display screen (which may be a touch screen), and/or a keyboard, and/or a mouse, etc., depending upon the implementation.

(60) The fulfillment network **440** may communicate with delivery time information generator **402** as described herein. The fulfillment network **440** may send to the delivery time information generator **402**, at least a part of the data to be stored in delivery data structure **410** of memory **406**. For example, fulfillment network **440** may send delivery schedule tables to be stored in delivery schedule tables **412** of memory **406**, and/or product-to-schedule mappings to be stored in product-to-schedule mappings **414** of memory **406**. Alternatively or additionally, fulfillment network **440** may send data associated with delivery time of a product sold online, which is processed and/or altered by the delivery time information generator **402** before it is stored in delivery schedule tables **412** and/or product-to-schedule mappings **414**. Fulfillment network **440** may communicate with delivery time information generator **402** through the network **420**, although this is not necessary. Although only one fulfillment network **440** is illustrated in FIG. **4** for ease of explanation, delivery

time information generator **402** may communicate with a plurality of fulfillment networks. Fulfillment network **710** shown in FIG. 7 (described later) is one example of fulfillment network **440**.

(61) In some embodiments, at least a portion of the data structure **410** may be stored on a shared database between the fulfillment network **440** and the delivery time information generator **402**, as opposed to being sent by the fulfillment network and subsequently received and stored in memory **406** of delivery time information generator **402**. For example, the set of delivery schedule tables and/or the product-to-schedule mapping for a fulfillment network, such as a 3PL, may be stored on a shared database which delivery time information generator **402** can access (e.g., by read-only access) and the 3PL can modify with updated information.

(62) FIG. 5 illustrates a computer-implemented method **500**, according to some embodiments. The steps of method **500** are described as being performed by the processor **404** of delivery time information generator **402** of FIG. 4, but this is only an example. At least a portion or all of the method **500** may instead be performed elsewhere, such as at another processor separate from the delivery time information generator **402**, or at the user device **430**.

(63) At step **502**, processor **404** may receive, from a user device over a network, a request for web content associated with one of a plurality of products sold on an e-commerce platform. The user device may be user device **430**, which may communicate with delivery time information generator **402** via network **420**, and may request web content stored in web content **416** of delivery time information generator **402**. For example, a user of user device **430** may request web content (e.g. using a HTTP or HTTPS request) such as a product details page or a checkout page associated with a product sold on an online store. FIG. 11 illustrates an embodiment in which a user has requested, for example using user interface **436** of user device **430**, a checkout summary page **1100** for a product **912** which the user wishes to purchase. The requested web content, such as a product details page, may be stored in web content **416** of memory **406**. The request may be sent through network interface **438** of user device **430** and received at network interface **408** of delivery time information generator **402**. Checkout summary page **1100** may include a delivery/shipping address **1102** to which the product **912** should be delivered after purchase, and a message **1104** displaying delivery time information associated with the product **912**.

(64) Returning to FIG. 5, at step **504**, processor **404** may reply to the request for web content by the user device. The replying step **504** may include a step **504a** of extracting, from a data structure, delivery schedule information for the product. The request for web content may include information that may be used by processor **404** to extract delivery schedule information from the data structure relating to the product. The data structure may include a plurality of delivery schedule tables as well as a mapping of each of the plurality of products sold on the e-commerce platform to a respective one of the plurality of delivery schedule tables. The data structure may be data structure **410** of delivery time information generator **402**, and the plurality of delivery schedule tables and the mappings may be stored within delivery schedule tables **412** and product-to-schedule mappings **414**, of data structure **410**, respectively. For example, FIG. 6 shows a plurality of delivery schedule tables **612**, **614**, **616**, **618**, and a set of mappings **611**. The mappings **611** map each of a plurality of products, labelled based on a stock keeping unit (SKU) number, to a respective one of the plurality of delivery schedule tables **612**, **614**, **616**, **618**. Using the mappings **611** and the delivery schedule tables, processor **404** may extract delivery schedule information for any of the plurality of products. For example, for a product **603**, processor **404** may use mappings **611** to determine that delivery schedule table **612** must be consulted to extract the respective delivery schedule information.

(65) Each of the plurality of delivery schedule tables may be based on a respective different set of one or more categories to which multiple ones of the plurality of products map. For example, in FIG. 6 the delivery schedule tables **612**, **614**, **616**, **618** are based on categories of weight and fulfillment center or warehouse location. For instance, delivery schedule table **612** contains

delivery schedule information for relatively heavy items which are stocked at a California location, while delivery schedule table **614** contains delivery schedule information for relatively light items which are stocked at a California location.

(66) Returning to FIG. 5, the replying step **504** may further include a step **504b** of generating an indication including delivery time information relating to the one product based on the delivery schedule information extracted from the data structure. The indication may be or include a message. For example, based on the extracted delivery schedule information for the product **603** in FIG. 6, processor **404** may generate an indication, the indication that the product **603** may be delivered to a user having an address with a 90002 zip code by June 11. As another example, based on extracted delivery schedule information for the product **912** in FIGS. 9-11, processor **404** may generate an indication that the product **912** may be delivered to a user having a 10001 zip code by June 10, as shown by message **1104** in FIG. 11.

(67) The replying step **504** may further include a step **504c** of incorporating the indication into the web content. Processor **404** may dynamically modify the requested web content, such as the checkout summary page **1100** of FIG. 11, to incorporate the indication including delivery time information related to the product. The replying step **504** may further include a step **504d** of transmitting the web content over the network for display on the user device. This may include the processor **404** of the delivery time information generator **402** instructing transmission of the requested web content having the indication by instructing network interface **408** to send the web content to the user device **430** (e.g. as a response to an HTTP or HTTPS request for the content). For example, the summary checkout page **1100** may be transmitted to user device **430** and presented to the user via the user interface **436** of the user device, as shown in FIG. 11. The summary checkout page **1100** may include the indication as the message **1104** which recites, "Get it by June 10."

(68) The replying step **504** described above, including all of steps **504a-d**, may occur within a timing constraint associated with providing web content during a user's real-time online interaction with an e-commerce platform, such as e-commerce platform **100**. For example, the replying step **504** may occur under two seconds, and may more likely occur under half of a second.

(69) FIG. 6 is an example diagram including product-to-schedule mappings and a set of delivery schedule tables associated with products sold online, according to some embodiments.

(70) FIG. 6 shows three online shops **602**, **606**, **610** which may be hosted by a computer of an e-commerce platform. Each shop may sell a plurality of items, and each of the items may be or map to an SKU. For example, product **603** sold by shop **602** may be or map to an SKU labelled "SKU-1.1" in FIG. 6. All of the items sold by the three online shops **602**, **606**, **610** may be managed by one fulfillment network, for example fulfillment network **440** of FIG. 4 or fulfillment network **710** of FIG. 7.

(71) FIG. 6 also shows product-to-schedule mappings **611**, which are illustrated by arrows, and a set of delivery schedule tables which include delivery schedule tables **612**, **614**, **616**, and **618**. The mappings **611** and delivery schedule tables **612**, **614**, **616**, **618** may form part of a data structure, such as data structure **410** of memory **406**, and may be used by the delivery time information generator **402** to extract delivery schedule information for any of the plurality of products sold by the shops **602**, **606**, and **610**. For example, mappings **611** may be stored in product-to-schedule mappings **414** and the delivery schedule tables **612**, **614**, **616**, **618** may be stored in delivery schedule tables **412** of data structure **410**.

(72) Each individual mapping in the product-to-schedule mappings **611** may map one product sold by one of shops **602**, **606** or **610**, to a respective delivery schedule table, such as delivery schedule tables **612**, **614**, **616**, **618**, such that all of the products sold by shops **602**, **606**, **610** is mapped to a delivery schedule table. For example, for the product **603**, FIG. 6 shows a product-to-schedule mapping which maps the product **603** to delivery schedule table **612**. Accordingly, product **603** may be a relatively heavy item which is currently stocked at a California warehouse location of

fulfillment network **440**.

(73) Each of the delivery schedule tables may contain delivery schedule information for different delivery destinations. The different delivery destinations may represent all of the possible destinations to which a respective product may be delivered within a certain region. In FIG. 6 for example, each of the delivery schedule tables **612**, **614**, **616**, **618** may contain delivery schedule information for different zip code areas in the United States. The different delivery destinations may be recorded as individual addresses, or alternatively may be divided into larger blocks, such as zip code areas or regions. Organizing the different delivery destinations by zip code area as shown in FIG. 6, as opposed to individual addresses, may be beneficial as zip code areas remain largely unchanged, while organizing by individual address may require for the delivery schedule tables to be updated frequently, e.g., whenever a new address is created. The different delivery destinations may be alternatively or additionally categorized into different types, e.g. a P.O. box address type, a residential address type, or a commercial address type. Categorizing by address type may increase the accuracy of computed delivery time information.

(74) For each of the delivery destinations, each of the delivery schedule tables **612**, **614**, **616**, **618** may include an earliest delivery date and a latest delivery date, the earliest and latest delivery dates representing the earliest and latest date which the product may be delivered to a user living at the respective delivery destination, barring unforeseen circumstances. The earliest delivery date and the latest delivery date may be the same date, or may be different dates.

(75) Each of the delivery schedule tables, including delivery schedule tables **612**, **614**, **616**, **618**, may have an expiry time, after which time the information contained with the delivery schedule table (e.g., the earliest and latest delivery dates) may not be accurate. For example, the delivery schedule tables **612**, **614**, **616**, **618** in FIG. 6 have an expiry time of 3 PM PST. Therefore, in some embodiments, delivery schedule tables **412** of memory **406** may store a plurality of versions for each table. For example, for each delivery schedule table, the delivery time information generator **402** may receive and store in memory **406** a first delivery schedule table version (a “current” delivery schedule table) which expires some time (e.g., 3 PM PST) during the current day, and a second delivery schedule table version (a “future” delivery schedule table) which expires at some time during the next day. At a defined time, e.g., at the start of a new day, or at the expiry point of the “current” delivery schedule table, or at a point in time prior to such events, the delivery time information generator **402** may receive and store in memory **406** a delivery schedule table version for the day subsequent to the day in which the “future” delivery schedule table expires. Upon expiry, the “current” delivery schedule table may be deleted from the computer's memory. At this point, the “future” delivery schedule table becomes the “current” delivery schedule, while the most recently received delivery schedule table version becomes the “future” delivery schedule. This process may be repeated such that delivery time information generator **402** may always have quick access to accurate and reliable delivery schedule information for an item purchased even just past the expiry time of a delivery schedule table.

(76) Each of the delivery schedule tables **612**, **614**, **616**, **618** may be based on a respective different set of one or more categories to which multiple ones of the plurality of products map. For example, it can be seen in FIG. 6 that the delivery schedule tables **612**, **614**, **616**, **618** are based on weight, i.e., whether an item is “light” or “heavy”, and available fulfillment center locations, i.e., whether an item is stocked in California, New York, or both (the tables showing delivery schedules for an item stocked only in New York are omitted for simplicity). In the example depicted in FIG. 6, there may be six categories: “light items”, “heavy items”, “stocked in California”, “stocked in New York” and “stocked in California and New York”. Delivery schedule table **612** may be based on the different set of categories {“heavy items”, “stocked in California”}; delivery schedule table **614** may be based on the different set of categories {“light items”, “stocked in California”}; delivery schedule table **616** may be based on the different set of categories {“heavy items”, “stocked in California and New York”}; and delivery schedule table **618** may be based on the different set of

categories {"light items", "stocked in California and New York"}. Delivery schedule tables **612**, **614**, **616**, **618** may be lookup tables as shown in FIG. 6, but this is not necessary.

(77) The categories upon which the delivery schedule tables of FIG. 6 are based are just an example of the types of categories. Examples of types of categories may include: categories based on product characteristics, such as product dimension and product "type" (e.g., bulky, dangerous, etc.); categories based on location (e.g. which set of warehouses have the product in stock), and/or permutations or combinations thereof.

(78) In some embodiments, the product-to-schedule mappings may be factored or decomposed into two or more component mappings, such as, e.g., a product-to-weight-class mapping and a weight-class-to-schedule mapping. The factorization or decomposition may be selected so that the resultant component mappings can be updated at different frequencies, and/or because they must be updated at different frequencies. For example, the product-to-weight-class mapping may need to be more frequently updated (e.g. to add new products) than the weight-class-to-schedule mapping. The factorization or decomposition may additionally or alternatively, take latency into account so that, for example, mappings that take longer to update are separated from mappings that are quicker to update.

(79) Although not immediately evident from the illustration of FIG. 6, the total number of the delivery schedule tables may be less than the total number of the number of products sold by shops **602**, **606**, **610**. Generally speaking, the total number of the delivery schedule tables (and thus number of mappings) may be less than the total number of the number of products for which the delivery schedule tables (and mappings) are generated. In some embodiments, the total number of the delivery schedule tables may be multiple orders of magnitude less than the total number of products for which the delivery schedule tables are generated. For example, in some embodiments, the number of delivery schedule tables may reach into the tens or hundreds, while the number of products sold on an e-commerce platform may reach into the millions. Therefore, in a solution where the e-commerce platform requests, for each product sold on the platform, a fulfillment network to precompute delivery schedule information for each possible delivery destination, it is evident why it poses storage, efficiency, and delay concerns. In comparison, the generation and transmission of the delivery schedule tables and mappings as described herein may be much more storage-friendly, efficient, and quick.

(80) FIG. 7 illustrates an example system overview **700** for generating information relating to the delivery time of a product sold online, according to some embodiments. The system overview **700** includes an e-commerce platform **730** and a fulfillment network **710**.

(81) E-commerce platform **730** may be or may be included in e-commerce platform **100** of FIGS. 1-3. As shown, e-commerce platform **730** may include product-to-schedule mappings (which may be or may be included in product-to-schedule mappings **414**), delivery schedule tables (which may be or may be included in delivery schedule tables **412**), and a delivery date platform **732** which may be or may include delivery time information generator **402**. E-commerce platform **730** communicates with a buyer (which may be a user or a user device such as user device **430**) and with fulfillment network **710**.

(82) Fulfillment network **710** may be a fulfillment service integrated with e-commerce platform **730**, or may be provided by one or more third-party logistics providers (3PLs). Fulfillment network **710** may be or may be included in fulfillment network **440** of FIG. 4. Fulfillment network **710** may be responsible for generating delivery date schedules (which may be delivery schedule tables, such as delivery schedule tables **612**, **614**, **616**, **618**) and product-to-schedule mappings (which may be mappings, such as mappings **611**) to be sent to the e-commerce platform **730**. Fulfillment network **710** may communicate with a fulfillment center, illustrated in FIG. 7 as warehouse **720**. Although only one warehouse **720** is shown for ease of explanation, fulfillment network **710** may communicate with a plurality of warehouses.

(83) As shown, the fulfillment network **710** may generate delivery date schedules based on various

factors, such as fulfillment center attributes and carrier service attributes. Example carrier service attributes include operating days, processing time, and capacity. For example, a statutory holiday or warehouse closures may affect the earliest and latest delivery dates for some products managed by fulfillment network **710**. Example fulfillment center attributes include pickup times, capacity, transit days, delivery days, time in transit, cost, type (e.g., air, ground), product characteristic categories, and fulfillment center (or warehouse) locations. Example product characteristic categories include weight classes of a product, dimension classes of a product, and “type” of product (e.g., dangerous, fragile, etc.). For example, weight classes may be “light” or “heavy”, or may be further specified or broken down, such as into a first weight class for items under 1 pound, a second weight class for items between 1-4 pounds, a third weight class for items between 4-9 pounds, and a fourth weight class for items heavier than 9 pounds. These weight classes may be determined based on an analysis of items that are commonly stored for delivery at the fulfillment network **710**.

(84) The product characteristic categories and fulfillment center locations may affect how delivery schedule tables are created, and how many are created. For example, in FIG. **6**, since the product weight classes were either “light” or “heavy”, and assuming that the items sold from shops **602**, **606**, **610** were stocked only at one or both of California and New York fulfillment center locations, there may be six delivery schedule tables in total. If instead the weight classes were further divided (such as into the four classes mentioned previously), and/or there were more fulfillment center locations (e.g. a fulfillment center in Washington), there may be more delivery schedule tables, e.g.: one for items weighing less than 1 pound and stocked only at the New York location, another for items weighing between 1 and 4 pounds and stocked only at the New York location, another for items weighing between 4 and 9 pounds and stocked only at the New York location, and so on. Thus, depending on the number of product characteristic categories, and the number of different fulfillment center locations, the number of generated delivery schedule tables may increase or decrease.

(85) In some embodiments where the delivery schedule tables are based on categories which include fulfillment center locations, as the number of fulfillment centers grow, the number of delivery schedule tables and thus the data structure which stores the delivery schedule tables (e.g., data structure **410**) may be additionally optimized by grouping the fulfillment centers into regions rather than viewing them as isolated singular centers.

(86) The fulfillment network **710** may generate product-to-schedule mappings based on various factors such as inventory availability data and product characteristic categories. For each product, the respective product-to-schedule mapping (i.e., the delivery schedule table to which the product is mapped) may depend on the product characteristic categories under which the product falls, and inventory availability data, i.e., which warehouse or fulfillment center location(s) have the product in stock. For example, alluding to FIG. **6**, if the product characteristic categories were weight categories of “light” and “heavy”, and the possible warehouse locations for stocking products were in California and New York, for an item that falls into the “light” category and is currently stocked at both California and New York locations, the fulfillment network **710** would generate a mapping for that product such that it maps to delivery schedule table **618**.

(87) Once fulfillment network **710** generates the delivery date schedules and the product to schedule mappings, the fulfillment network may send them to e-commerce platform **730**, as illustrated by arrow **740**. The generated delivery date schedules may be stored in delivery schedule tables of the e-commerce platform **730**, and the generated product to schedule mappings may be stored in product to schedule mappings of the e-commerce platform **730**. The delivery schedule tables and product to schedule mappings may then be used by delivery date platform **732** (which may be or may include delivery time information generator **402**) to obtain delivery schedule information for any product sold on the e-commerce platform **730** and managed by fulfillment network **710**.

(88) In order to obtain such delivery schedule information and provide delivery time information for display on user device **430**, delivery date platform **732** does not require additional data from the fulfillment network aside from the product-to-schedule mapping and the delivery schedule tables. In other words, delivery date platform **732** need not know of the categories and other considerations used by the one or more fulfillment network **710** to generate the delivery schedule tables. Thus, regardless of the factors and constraints that different fulfillment networks use to compute delivery time information, the e-commerce system may be compatible with any fulfillment network as long as the product-to-schedule mapping and delivery schedule tables are sent by the fulfillment network. In the context of FIG. **6**, for example, the delivery time information generator **402** need not know that product **603** is considered to be a heavy item and is currently stocked at a California fulfillment center location, nor need it know that table **612** is based on heavy items which are stocked at a California fulfillment center. Instead, delivery time information generator **402** may only be aware that product **603** maps to table **612** (via mappings **611**), and that by consulting table **612**, delivery time information generator **402** can extract delivery schedule information for product **603** for a user residing at any destination location listed within table **612**. Not only does this allow for compatibility with different fulfillment networks, but it also allows for each fulfillment network to maintain as private the different factors and constraints used by that fulfillment network to generate its delivery schedule tables and product-to-schedule mapping.

(89) Certain changes, such as changes in inventory availability data or product characteristic categories, may result in a change of the product-to-schedule mapping for one or more products managed by fulfillment network **710**. Certain other changes, such as the addition of a new product, may result in a new product-to-schedule mapping. For example, the addition of a new product onto e-commerce platform **730** which is to be managed by fulfillment network **710**, may result in a new mapping once fulfillment network **710** has stocked inventory of the new product and could provide reliable delivery information. In some embodiments, warehouse **720** may send updates to fulfillment network **710**, the updates including information on product inventory or warehouse changes. Examples of such changes include the inventory of a product managed by the fulfillment network **710** at a particular warehouse location running out or dropping below a particular threshold, a product being newly stocked at an additional warehouse location, a new product being stocked at one or more warehouse locations, a warehouse shutting down permanently or temporarily due to severe weather events, etc. This may then result in a changed mapping for the product. For example, in FIG. **6**, if product **603** became stocked in New York in addition to California, mappings **611** may be updated such that product **603** is mapped to delivery schedule table **616** instead of **612**. If the New York warehouse then had to suddenly shut down due to bad weather, or the inventory of product **603** dropped to zero or below a threshold level at the New York warehouse, mappings **611** may be updated again such that product **603** is mapped again to delivery schedule **612**. Any changes which affect the mapping of one or more products may be communicated as soon as possible by the fulfillment network **710** to the e-commerce platform **730**, such that the delivery time information generator **402** may generate and transmit accurate delivery schedule information in replying to a request for web content by a user device.

(90) In some embodiments, the delivery schedule tables may need to be frequently updated, for example as the expiry deadline for a delivery promise is passed, and/or to account for factors such as carrier pickup schedules, holidays, etc. The tables may only be updated at certain times and/or on certain days of the week. In comparison, the product-to-schedule mappings may need to be updated less frequently, such as upon the occurrence of an event as described above, which alters the mapping for one or more products, or results in a new mapping.

(91) In some embodiments, delivery date platform **732** may request one or more updated delivery schedule tables on demand, for example, if a delivery schedule table, or a portion of a delivery schedule table, has expired and there is no updated table. Alternatively, in such scenarios, delivery date platform **732** may use an expired delivery schedule table, however this may be avoided where

possible.

(92) In some embodiments, updating the delivery schedule tables generated by fulfillment network **710** may involve receiving from the fulfillment network **710**, all of the delivery schedule tables populated with updated information. In some embodiments, updating the delivery schedule tables generated by fulfillment network **710** may involve receiving, from fulfillment network **710**, only data that is different from the current delivery schedule tables, which may further reduce the amount of data needed to be transmitted between the fulfillment network and e-commerce platform **730**. The same applies for the product-to-schedule mapping, i.e., in some embodiments when the product-to-schedule mapping changes, only the difference may be communicated to the computer, rather than a new copy of the mapping.

(93) In some embodiments, the updates sent by warehouse **720** may be voluntary, i.e., initiated at the warehouse **720** side, for example in response to some trigger such as a drop in inventory below a threshold level. In some embodiments, queries may additionally or alternatively be made by fulfillment network **710** to warehouse **720**. For example, the fulfillment network **710** may query or ping warehouse **720** for information associated with the product characteristics that are used to generate delivery schedule tables. Fulfillment network **710** may continue to query warehouse **720**, for example to determine how the inventory stock level at a fulfillment center has changed, to generate updated product-to-schedule mapping.

(94) FIG. **8** shows an example flow for generating information relating to the delivery time of a product sold online. A user of user device **430** may request for a product details page associated with a product sold online. As mentioned previously, to realize this, user device **430** may send a request for web content, the request being received by the delivery time information generator **402**. The request is illustrated by the arrow pointing towards the delivery time information generator **402**. The browser used by user device **430** to issue the URL may turn the URL into an HTTP or HTTPS request. For example, FIG. **8** shows an HTTP request **810**. The HTTP request **810** may include information required for the delivery time generator **402** to load the requested web content. For example, in FIG. **8**, the user may have wished to view a product details page for a product (such as product details page **1000** of FIG. **10**), such that the URL of the web page recites “/productdetails . . .” or something similar in the HTTP request **810**. The HTTP request **810** may also include information required for the delivery time information generator **402** to extract delivery schedule information for the product from data structure **410** of memory **406**. For example, HTTP request **810** in FIG. **8** includes a product identifier component **812** and an address component **814**. The product identifier component **812** may contain a unique identifier for the product, e.g., an SKU number, and the address component **814** may contain a delivery destination, e.g., a zip code.

(95) Using the information contained in the product identifier component **812** and the address component **814**, the delivery time information generator **402** may access the data structure **410** of memory **406** to extract the delivery schedule information for the product, generate an indication based on the extracted information, incorporate that indication into the requested web content, and transmit the web content over the network for display on user device **430**. For example in FIG. **8**, the product identifier component **812** may contain an SKU number which corresponds with product **603** sold by shop **602** shown in FIG. **6**. Using the product identifier component **812** of the HTTP request **810**, the delivery time information generator **402** may use the mappings **611** (which may be stored in the product-to-schedule mappings **414**) to determine that for product **603**, delivery schedule table **612** should be consulted for the delivery schedule information. The delivery time information generator **402** may then use the information contained in address component **814**—in this case, zip code 10001—to look up and extract the respective delivery schedule information in delivery schedule table **612**. As shown, the earliest guaranteed delivery date is June 11, and the latest guaranteed delivery date is June 12. Delivery time information generator **402** may generate an indication based on this extracted delivery schedule information, and incorporate this indication

into the requested web content, as shown by a HTTP reply **820**. HTTP reply **820** may be transmitted by delivery time information generator **402** and received at user device **430**, as represented by the shaded arrow pointing towards the user device **430**. The indication may be or may include the following text shown in the HTTP reply **820**: “. . . get this by June 12 if you buy it in the next 4 hours!” June 12, i.e., the latest delivery date, may be chosen as the date to be included in the indication since the user would be guaranteed to have the product delivered by that date (barring unforeseen circumstances). The HTTP reply **820** may be received at network interface **438**, and the requested web content having the indication may be displayed on user interface **436** of the user device **430**. An example of the web content may be product details page **100** of FIG. **10**.

(96) Note that in the example in FIG. **8**, instead of an explicit address component **814** in the HTTP request **810**, the address component may be implicit, e.g. the IP address of the user device may be used to infer a geographic region or location, which may be mapped to a representative address (e.g. a ZIP code area). The representative address is assumed to be the shipping/delivery address. In such embodiments, an indication of the geographic region or location or representative address may also be incorporated into the web content to provide the user with context, e.g. “Get this by June 12 if you buy it in the next 4 hours (assuming shipping to an address in New York City)”.

(97) In FIG. **8** and other examples herein, the preparing and sending of the HTTP or HTTPS response, i.e. the replying, can occur within a timing constraint associated with providing the web content during a user's real-time online interaction with the e-commerce platform. This is because of the use of product-to-schedule mappings and delivery schedule tables, which allows for quick retrieval of the required data in a delivery schedule table using the information (such as delivery destination information and/or product identifier) in the HTTP or HTTPS request.

(98) Examples of Web Content Will Now be Described in More Detail

(99) FIG. **9** shows a products page **900** which may be provided to a user via a user interface of a user device (such as user device **430**), according to some embodiments. The products page **900** may display products being offered for sale online by a particular merchant owning an online shop **910**. Online shop **910** may be hosted by an e-commerce platform, such as e-commerce platform **100** of FIGS. **1-3** or e-commerce platform **730** of FIG. **7**.

(100) The product page **900** may also display a widget **920**, which may prompt a user to optionally enter in a delivery address or a more generalized delivery destination such as a city name, or zip code. Once the user does so, user device **430** may store the user's delivery destination in memory **434**. User device **430** may then send the delivery destination as part of an HTTP request for web content associated with a product sold on online shop **910** of the e-commerce platform. Delivery time information generator **402** may use the delivery destination to extract delivery schedule information for the product.

(101) Of the products offered for sale on online shop **910**, the user may find a product **912** of interest, and may decide to view a product details page for the product **912**, e.g., to view product specifications, cost, available colors, etc. To do so, the user may click on an icon or text for the product **912**. Alternative ways (e.g., pressing, performing hand motion, verbally reciting instructions, etc.) may be possible to request the product details page, depending on the user device being used. The user may then be provided with a product details page, such as the one shown in FIG. **10**.

(102) FIG. **10** shows a product details page **1000** for the product **912**, the product details page **1000** displaying information relating to the delivery time of product **912** for a user, according to some embodiments. Product page **1000** may be provided to a user via a user interface of user device **430**. In the embodiment shown in FIG. **10**, the product details page **1000** displays a message **1012**, which reads, “Customer A, get this by June 12 if you buy it in the next 4 hours!”. To load the product details page **1000**, user device **430** may send an HTTP request over the network **420**. The HTTP request may contain a product identifier component and an address component. The product identifier component may include a unique identifier for the product **912**, such as an SKU number.

The address component may include the delivery destination that was entered by the user using widget **920** and stored by the user device **430**. Using the product identifier component and the address component, delivery time information generator **402** may obtain delivery time information relating to product **912** for the user's delivery destination, using the processes as described herein. The delivery time information generator **402** may generate an indication including the delivery time information, dynamically modify product page **1000** to include the indication as message **1012**, and transmit the product page **1000** for display on user device **430**.

(103) The product details page **1000** displaying information relating to the delivery time of product **912** is only an example of a web page incorporating delivery schedule information and is not intended to be limiting. In some embodiments, the delivery time information may appear based on an interaction with the product details page **1000** such as hovering a cursor over an “Add to cart” button **1010**. In some embodiments, the delivery time information may be incorporated into the regular text matter on the product page **1300**. In some embodiments, widget **920** may be displayed on product details page **1000** in addition to or instead of on products page **900**. Upon a user inputting a delivery destination in widget **920**, user device **430** may send an HTTP request to modify and reload at least a portion of product details page **1000** with delivery schedule information incorporated in the page.

(104) In the embodiments described above in relation to FIGS. **9** and **10**, a zip code entered by a user may be used by the delivery time information generator **402** to extract delivery schedule information, however this is only an example and is not meant to be limiting. There are various ways that a delivery destination of a user may be obtained. For example, in some embodiments, when a user is browsing a product page, user device **430** may or may be instructed to perform geo-detection using the IP address of the user device. In some embodiments, a user may be logged in to an account associated with an online store or e-commerce platform. For instance, it can be seen in FIGS. **9-11** that the user is signed into an account with the online store **910** of e-commerce platform, and the online store **910** knows the user as “Customer A”. The account might have saved information associated with the user, such as a default delivery address for the user. The request for a web page sent to the delivery time information generator **402** may include the saved default address, or it may already be stored in memory **406** of the delivery time information generator **402** for use by the delivery time information generator **402** in extracting delivery schedule information from data structure **410**. In some embodiments, the delivery destination may not be known or may not be used by the delivery time information generator **402** to obtain delivery time information until the user is on a checkout page.

(105) FIG. **11** shows a checkout summary page **1100** for a user who wishes to purchase the product **912**. Checkout summary page **1100** may be a web page provided to a user as part of an online checkout process. In order to arrive at checkout summary page **1100**, the user may have previously entered in a delivery address **1102** to which the product **912** should be delivered, e.g., at a “shipping” web page of the online checkout process, and then clicked on an icon or otherwise interacted with user device **430** to be provided with checkout summary page **1100**. Alternatively, the user's address may already have been saved as part of an online account associated with the user. When user device **430** sends an HTTP request to load checkout summary page **1100**, an address component of the request may include the delivery address **1102**. Delivery time information generator **402** may use this address **1102**, in addition to the unique product identifier for product **912** in order to obtain delivery time information relating to product **912** for the user's delivery destination, using the processes as described herein. The delivery time information generator **402** may then generate an indication including the delivery time information, dynamically modify checkout summary page **1100** to include the indication as message **1104**, and transmit the checkout summary page **1100** for display on user device **430**. The checkout summary page **1100** incorporating the delivery time information as message **1104** is only an example of a web page including delivery time information, and is not intended to be limiting. The display of

delivery time information on a checkout page shown on a customer device can appear in any form.

(106) In some embodiments, the delivery time information displayed on a web page, such as on product details page **1000**, may be a preliminary delivery promise provided to a user before or during the purchase of the product from the online store. A secondary delivery promise may be provided to the customer following the purchase of the product, for example, in a purchase confirmation email. The secondary delivery promise may be a revised version of the preliminary promise based on the inclusion of new or updated information, such as weather or traffic reports.

(107) Note that “web content”, as used herein, includes any content retrieved by a device over the Internet, including content retrieved by a native app over the Internet, not just necessarily HTTP/HTTPS requests. Also, a “table” as used herein is not limited to a lookup table or a structure having rows and columns. A “table” refers to a partition in memory storing data/information that can be referenced. The partition in memory may be contiguous or distributed.

(108) Note that the expression “at least one of A or B”, as used herein, is interchangeable with the expression “A and/or B”. It refers to a list in which you may select A or B or both A and B. Similarly, “at least one of A, B, or C”, as used herein, is interchangeable with “A and/or B and/or C” or “A, B, and/or C”. It refers to a list in which you may select: A or B or C, or both A and B, or both A and C, or both B and C, or all of A, B and C. The same principle applies for longer lists having a same format.

(109) The scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed, that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

(110) Any module, component, or device exemplified herein that executes instructions may include or otherwise have access to a non-transitory computer/processor readable storage medium or media for storage of information, such as computer/processor readable instructions, data structures, program modules, and/or other data. A non-exhaustive list of examples of non-transitory computer/processor readable storage media includes magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, optical disks such as compact disc read-only memory (CD-ROM), digital video discs or digital versatile disc (DVDs), Blu-ray Disc™, or other optical storage, volatile and non-volatile, removable and non-removable media implemented in any method or technology, random-access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), flash memory or other memory technology. Any such non-transitory computer/processor storage media may be part of a device or accessible or connectable thereto. Any application or module herein described may be implemented using computer/processor readable/executable instructions that may be stored or otherwise held by such non-transitory computer/processor readable storage media.

(111) Memory, as used herein, may refer to memory that is persistent (e.g. read-only-memory (ROM) or a disk), or memory that is volatile (e.g. random access memory (RAM)). The memory may be distributed, e.g. a same memory may be distributed over one or more servers or locations.

Claims

1. A computer-implemented method comprising: storing, in a memory, a data structure comprising: a plurality of delivery schedule tables, and a mapping of each of a plurality of products sold on an e-commerce platform to a respective one of the plurality of delivery schedule tables, wherein each

of the plurality of delivery schedule tables corresponds to a respective category, of a plurality of categories, to which multiple ones of the plurality of products map, and wherein each entry of each of the plurality of delivery schedule tables stores pre-computed delivery schedule information, for the respective category, for each destination of a plurality of destinations; receiving, from a user device over a network during an online interaction by a user with the e-commerce platform, a request for web content associated with a particular product of the plurality of products sold on the e-commerce platform; and replying to the request during the online interaction in real time, the replying comprising: obtaining, from the request for web content, information related to a delivery destination associated with the user device and an identifier that uniquely identifies the particular product; identifying a particular delivery schedule table, of the plurality of delivery schedule tables in the memory, to which the particular product maps based on the identifier, wherein the particular delivery schedule table corresponds to a particular category of the particular product; extracting delivery schedule information and from a particular entry of the particular delivery schedule table that corresponds to the delivery destination; based on the delivery schedule information extracted from the particular entry, generating an indication including delivery time information relating to the particular product; incorporating the indication into the web content; and transmitting the web content over the network for display on the user device.

2. The computer-implemented method of claim 1, wherein a total number of the plurality of delivery schedule tables is less than a total number of the plurality of products sold on the e-commerce platform.
3. The computer-implemented method of claim 1, wherein the replying occurs within a timing constraint associated with providing the web content during a user's real-time online interaction with the e-commerce platform.
4. The computer-implemented method of claim 1, wherein the information related to the delivery destination associated with the user device is an Internet Protocol address of the user device.
5. The computer-implemented method of claim 1, wherein: the extracting comprises: using the identifier to consult the mapping of each of the plurality of products to a respective one of the plurality of delivery schedule tables, to determine a delivery schedule table of the plurality of delivery schedule tables that corresponds with the particular product, and using the delivery destination to extract the delivery schedule information from the delivery schedule table.
6. The computer-implemented method of claim 1, wherein different delivery schedule tables correspond to different product characteristic categories.
7. The computer-implemented method of claim 6, wherein the different product characteristic categories include different weight categories, each of the weight categories defining a different weight range.
8. The computer-implemented method of claim 1, wherein different delivery schedule tables correspond to different fulfillment center location categories.
9. The computer-implemented method of claim 1, wherein the plurality of delivery schedule tables and the mapping are updated to reflect a current version of the plurality of delivery schedule tables and a current version of the mapping, and wherein the update of the delivery schedule tables occurs at a different frequency from the update of the mapping.
10. The computer-implemented method of claim 9, wherein at least one of the plurality of delivery schedule tables is updated in response to expired delivery time information, and wherein the mapping is updated in response to a particular inventory change.
11. The computer-implemented method of claim 10, wherein in response to inventory for a given product at a particular fulfillment center dropping to zero or dropping below a threshold, the mapping is updated to no longer map the given product to the respective delivery schedule table to which the given product was mapped.
12. The computer-implemented method of claim 11, wherein the given product is instead mapped to a different delivery schedule table.

13. A system comprising: at least one processor; and a memory storing processor-executable instructions that, when executed, cause the at least one processor to: store, in the memory, a data structure comprising: a plurality of delivery schedule tables, and a mapping of each of a plurality of products sold on an e-commerce platform to a respective one of the plurality of delivery schedule tables, wherein each of the plurality of delivery schedule tables corresponds to a respective category, of a plurality of categories, to which multiple ones of a plurality of products map, and wherein each entry of each of the plurality of delivery schedule tables stores pre-computed delivery schedule information, for the respective category, for each destination of a plurality of destinations; receive, from a user device over a network during an online interaction by a user with the e-commerce platform, a request for web content associated with a particular product of the plurality of products sold on the e-commerce platform; and reply to the request during the online interaction in real time, wherein the step of replying comprises: obtaining, from the request for web content, information related to a delivery destination associated with the user device and an identifier that uniquely identifies the particular product; identifying a particular delivery schedule table, of the plurality of delivery schedule tables in the memory, to which the particular product maps based on the identifier, wherein the particular delivery schedule table corresponds to a particular category of the particular product; extracting delivery schedule information from a particular entry of the particular delivery schedule table that corresponds to the delivery destination; based on the delivery schedule information extracted from the particular entry, generate an indication including delivery time information relating to the particular product; incorporating the indication into the web content; and transmitting the web content over the network for display on the user device.
14. The system of claim 13, wherein a total number of the plurality of delivery schedule tables is less than a total number of the plurality of products sold on the e-commerce platform.
15. The system of claim 13, wherein the step of replying occurs within a timing constraint associated with providing the web content during a user's real-time online interaction with the e-commerce platform.
16. The system of claim 13, wherein: the step of extracting comprises: using the identifier to consult the mapping of each of the plurality of products to a respective one of the plurality of delivery schedule tables, to determine a delivery schedule table of the plurality of delivery schedule tables that corresponds with the particular product, and using the delivery destination to extract the delivery schedule information from the delivery schedule table.
17. The system of claim 13, wherein different delivery schedule tables correspond to different product characteristic categories.
18. The system of claim 13, wherein the plurality of delivery schedule tables and the mapping are updated to reflect a current version of the plurality of delivery schedule tables and a current version of the mapping, and wherein the update of the delivery schedule tables occurs at a different frequency from the update of the mapping.
19. The system of claim 13, wherein the information related to the delivery destination associated with the user device is an Internet Protocol address of the user device.
20. The system of claim 13, wherein different delivery schedule tables correspond to different fulfillment center location categories.
21. The system of claim 13, wherein the plurality of delivery schedule tables and the mapping are updated to reflect a most current version of the plurality of delivery schedule tables and a most current version of the mapping, and wherein the update of the delivery schedule tables occurs at a different frequency from the update of the mapping.
22. The system of claim 21, wherein at least one of the plurality of delivery schedule tables is updated in response to expired delivery time information, and wherein the mapping is updated in response to a particular inventory change.
23. A non-transitory computer readable medium having stored thereon computer-executable instructions that, when executed by a computer, cause the computer to perform operations

comprising: storing, in a memory, a data structure comprising: a plurality of delivery schedule tables, and a mapping of each of a plurality of products sold on an e-commerce platform to a respective one of the plurality of delivery schedule tables, wherein each of the plurality of delivery schedule tables corresponds to a respective category, of a plurality of categories, to which multiple ones of a plurality of products map and wherein each entry of each of the plurality of delivery schedule tables stores pre-computed delivery schedule information, for the respective category, for each destination of a plurality of destinations; receiving, from a user device over a network during an online interaction by a user with the e-commerce platform, a request for web content associated with a particular product of the plurality of products sold on the e-commerce platform; and replying to the request during the online interaction in real time, the replying comprising: obtaining, from the request for web content, information related to a delivery destination associated with the user device and an identifier that uniquely identifies the particular product; identifying a particular delivery schedule table, of the plurality of delivery schedule tables in the memory, to which the particular product maps based on the identifier, wherein the particular delivery schedule table corresponds to a particular category of the particular product; extracting delivery schedule information from a particular entry of the particular delivery schedule table that corresponds to the delivery destination; based on the delivery schedule information extracted from the particular entry, generating an indication including delivery time information relating to the particular product; incorporating the indication into the web content; and transmitting the web content over the network for display on the user device.
