

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414598
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lee; Jin Hwan et al.

Chin guard pivoting mechanism

Abstract

The present disclosure relates to a chin guard pivoting mechanism, and the chin guard pivoting mechanism (100) according to the present disclosure is provided in a helmet which comprises a helmet body (10), a chin guard (20) pivotally coupled to the helmet body (10), and a shield (30) pivotally coupled to the helmet body (10). When the chin guard (20) is pivoted from the front of a user's chin up to a first predetermined angle (A) with respect to the helmet body (10), the shield (30) is pivoted upward, and when the chin guard (20) is pivoted up to a second predetermined angle (B) greater than the first predetermined angle (A) with respect to the helmet body (10), the shield (30) is pivoted downward. Alternatively, when the chin guard (20) is pivoted from the front of a user's chin up to the first predetermined angle (A) with respect to the helmet body (10), the shield (30) is pivoted upward, and when the shield (30) is pivoted downward, the chin guard (20) is pivoted up to the second predetermined angle (B) with respect to the helmet body (10).

Inventors:	Lee; Jin Hwan (Gyeonggi-do, KR), Nam; Ki Young (Seoul, KR)
Applicant:	HJC CORP. (Gyeonggi-do, KR)
Family ID:	1000008820844
Assignee:	HJC CORP. (Gyeonggi-do, KR)
Appl. No.:	18/263912
Filed (or PCT Filed):	November 22, 2021
PCT No.:	PCT/KR2021/017166
PCT Pub. No.:	WO2022/173097
PCT Pub. Date:	August 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240081463 A1	Mar. 14, 2024

Foreign Application Priority Data

KR

10-2021-0018412

Feb. 09, 2021

Publication Classification

Int. Cl.: A42B3/32 (20060101); A42B3/22 (20060101)

U.S. Cl.:

CPC A42B3/326 (20130101); A42B3/222 (20130101);

Field of Classification Search

CPC: A42B (3/205); A42B (3/04); A42B (3/222); A42B (3/223); A42B (3/326)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0129440	12/2001	Hong	2/422	A42B 3/326
2008/0196148	12/2007	Morin	2/10	A42B 3/222
2009/0100576	12/2008	Kim	2/9	A42B 3/326
2011/0302701	12/2010	Kuo	2/424	A42B 3/326
2012/0284906	12/2011	Kuo	2/424	A42B 3/223
2013/0340148	12/2012	Arai	2/421	A42B 3/326
2018/0213877	12/2017	Liao	N/A	A42B 3/225
2020/0178639	12/2019	Jwa	N/A	A42B 3/205
2021/0274877	12/2020	Liao	N/A	A42B 3/205
2024/0081463	12/2023	Lee	N/A	A42B 3/326
2024/0180282	12/2023	Lee	N/A	A42B 3/223

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0797935	12/1996	EP	N/A
3001919	12/2015	EP	A42B 3/223
20220143270	12/2021	KR	N/A
WO-2006128833	12/2005	WO	A42B 3/222

Primary Examiner: Mangine; Heather

Attorney, Agent or Firm: DUANE MORRIS LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a § 371 national stage entry of International Application No.

PCT/KR2021/017166, filed on Nov. 22, 2021, which claims priority to Korean Patent Application No. 10-2021-0018412, filed on Feb. 9, 2021, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a chin guard pivoting mechanism.

BACKGROUND

(3) In general, it is mandatory to wear a helmet while driving a two wheeled vehicle with high speed to protect the wearer's head. The helmet has a front open portion to ensure the wearer's frontal field of view. Additionally, the helmet may include a shield that can selectively open and close the open portion to keep out wind, dust, etc. while driving.

(4) Meanwhile, the helmet according to the prior art includes a chin guard to protect the wearer's chin as disclosed by the patent literature of the related literatures as described below.

RELATED LITERATURES

Patent Literature

(5) (Patent Literature 1) KR10-2014-0001141 A

SUMMARY

(6) An aspect of the present disclosure is directed to a chin guard pivoting mechanism for pivoting a chin guard and a shield in tandem.

(7) A chin guard pivoting mechanism according to an embodiment of the present disclosure is provided in a helmet including a helmet body, a chin guard pivotally coupled to the helmet body and a shield pivotally coupled to the helmet body, and upon pivoting of the chin guard from a front side of a wearer's chin to a first predetermined angle with respect to the helmet body, the shield pivots upward, and upon pivoting of the chin guard to a second predetermined angle which is larger than the first predetermined angle with respect to the helmet body, the shield pivots downward, or upon pivoting of the chin guard from the front side of the wearer's chin to the first predetermined angle with respect to the helmet body, the shield pivots upward, and upon downward pivoting of the shield, the chin guard pivots to the second predetermined angle with respect to the helmet body.

(8) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, upon pivoting of the chin guard from the first predetermined angle to a third predetermined angle between the first predetermined angle and the second predetermined angle with respect to the helmet body, the shield does not pivot.

(9) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, the chin guard pivoting mechanism includes a link having one side coupled to the chin guard, and an arm which pivots the shield at one side, and the link and the arm pivot in tandem.

(10) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, the link includes a first link and a second link, the chin guard is coupled to one side of the first link and one side of the second link, and the other side of the first link pivots around a first rotation axis, and the other side of the second link pivots around a second rotation axis.

(11) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, upon pivoting of the chin guard from the front side of the wearer's chin with respect to the helmet body, one side of the first link is disposed in front of one side of the second link, then disposed above one side of the second link, and subsequently disposed at rear of one side of the second link.

(12) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, the arm has a sliding portion along a lengthwise direction, and upon the pivoting of the chin guard, a coupling portion of the first link is slidable along the sliding portion.

(13) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, the sliding portion includes a first sliding portion extended in an arc shape, and a second sliding portion extended from an end of the first sliding portion in an arc shape.

(14) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present

disclosure, upon the upward pivoting of the shield with the pivoting of the chin guard from the front side of the wearer's chin to the first predetermined angle with respect to the helmet body, the coupling portion slides along the first sliding portion, and upon the downward pivoting of the shield with the pivoting of the chin guard to the second predetermined angle with respect to the helmet body, or upon the pivoting of the chin guard to the second predetermined angle with respect to the helmet body with the downward pivoting of the shield, the coupling portion slides along the first sliding portion.

(15) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, upon pivoting of the chin guard from the first predetermined angle to a third predetermined angle between the first predetermined angle and the second predetermined angle with respect to the helmet body, and not pivoting of the shield, the coupling portion slides along the second sliding portion.

(16) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, a radius of curvature of the second sliding portion corresponds to a distance between the coupling portion and the first rotation axis.

(17) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, the arm is provided with the other side, which is configured to slide along a pivoting portion extended in an arc shape, such that the arm rotates as the other side slides in the pivoting portion.

(18) Additionally, the chin guard pivoting mechanism according to an embodiment of the present disclosure includes a fastening portion which is coupled to the link, and is separated from the link upon the pivoting of the chin guard with respect to the helmet body.

(19) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, a first hook portion of the fastening portion is fastened to a second hook portion of the link, and upon the pivoting of the chin guard with respect to the helmet body, the link pivots and accordingly the fastening portion pivots, and the first hook portion is separated from the second hook portion.

(20) Additionally, in the chin guard pivoting mechanism according to an embodiment of the present disclosure, an elastic force is applied to the fastening portion in a direction in which the first hook portion is fastened to the second hook portion.

(21) The features and advantages of the present disclosure will be apparent from the following detailed description in accordance with the accompanying drawings.

(22) Prior to the description, it should be understood that the terms or words used in the specification and the appended claims should not be construed as limited to general and dictionary meanings, but rather interpreted based on the meanings and concepts corresponding to the technical spirit of the present disclosure on the basis of the principle that the inventor is allowed to define terms appropriately for the best explanation.

(23) According to the present disclosure, since the chin guard and the shield pivot in tandem, when the chin guard pivots, the shield pivots, so it is easy for the wearer to wear the helmet.

(24) In addition, according to the present disclosure, since the chin guard and the shield pivot in tandem, when the chin guard is disposed above and the shield pivots downward, the chin guard may automatically pivot to the rear side of the helmet body.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a side view of a helmet including a chin guard pivoting mechanism according to an embodiment of the present disclosure.

(2) FIG. 2 is an exploded perspective view of a chin guard pivoting mechanism according to an

embodiment of the present disclosure.

(3) FIGS. 3 to 7 are side views showing an operation process of a helmet including a chin guard pivoting mechanism according to an embodiment of the present disclosure and an operation process of the chin guard pivoting mechanism.

DETAILED DESCRIPTION

(4) The objectives, particular advantages and new features of the present disclosure will be apparent from the following detailed description and exemplary embodiments in association with the accompanying drawings. In affixing the reference numbers to the elements of each drawing in the present disclosure, it should be noted that identical elements are given as identical numbers as possible although they are depicted in different drawings. Additionally, the terms such as “first”, “second” or the like are used to distinguish one element from another, and the elements are not limited by the terms. Hereinafter, in describing the present disclosure, when it is determined that a certain description of related known technology may unnecessarily obscure the subject matter of the present disclosure, the detailed description is omitted.

(5) Hereinafter, exemplary embodiments of the present disclosure will be described in detail with reference to the accompanying drawings.

(6) FIG. 1 is a side view of a helmet including a chin guard pivoting mechanism according to an embodiment of the present disclosure, and FIG. 2 is an exploded perspective view of the chin guard pivoting mechanism according to an embodiment of the present disclosure.

(7) As shown in FIGS. 1 and 2, the chin guard pivoting mechanism **100** according to this embodiment is provided in a helmet including a helmet body **10**, a chin guard **20** pivotably coupled to the helmet body **10** and a shield **30** pivotably coupled to the helmet body **10**, and when the chin guard **20** pivots from the front side of a wearer's chin to a first predetermined angle with respect to the helmet body **10**, the shield **30** pivots upward, and when the chin guard **20** pivots to a second predetermined angle that is larger than the first predetermined angle with respect to the helmet body **10**, the shield **30** pivots downward, or when the chin guard **20** pivots from the front side of the wearer's chin to the first predetermined angle with respect to the helmet body **10**, the shield **30** pivots upward, and when the shield **30** pivots downward, the chin guard **20** pivots to the second predetermined angle with respect to the helmet body **10**.

(8) Basically, the helmet body **10** plays a role in protecting the wearer's head. The helmet body **10** may be made of a shock absorbing material. For example, the helmet body **10** may include an outer shell of hard synthetic resin and having high strength, and an absorber disposed in the outer shell, made of an expanded polystyrene (EPS) foam and having proper strength and elasticity. A pad may be present inside the absorber to improve a snug fit.

(9) Additionally, the chin guard **20** plays a role in protecting the wearer's chin, and may be extended in an arc shape as a whole so that it is disposed in front of the wearer's chin. In this instance, the chin guard **20** is, at two ends, rotatably coupled to two sides (for example, a ratchet **40**) of the helmet body **10**, and is pivotable from a first predetermined position to a third predetermined position. For example, the first predetermined position may refer to a position (Full Face Mode) when the chin guard **20** is disposed in front of the wearer's chin (see FIG. 3A), the second predetermined position may refer to a position (Wearing Mode) when the chin guard **20** is disposed above the helmet body **10** (see FIG. 6A), and the third predetermined position may refer to a position (Open Face Mode) when the chin guard **20** is disposed at the rear of the helmet body **10** (see FIG. 7A).

(10) Additionally, the shield **30** plays a role in opening and closing a front open portion of the helmet body **10**, and is pivotably coupled to the two sides (for example, the ratchet **40**) of the helmet body **10**, so that the shield **30** is rotatable around the helmet body **10** and pivotable from a first position to a second position. For example, the first position may refer to a position in which the shield **30** closes the open portion (see FIG. 3A), and the second position may refer to a position in which the shield **30** opens the open portion (see FIG. 4A).

(11) The chin guard **20** and the shield **30** pivot in tandem by the chin guard pivoting mechanism **100** according to this embodiment, and hereinafter, the chin guard pivoting mechanism **100** will be described in detail.

(12) As shown in FIGS. **3A** to **4A**, when the chin guard **20** pivots from the front side of the wearer's chin to the first predetermined angle **A** with respect to the helmet body **10**, the shield **30** may also pivot upward and the open portion may be opened. That is, when the chin guard **20** pivots by the first predetermined angle **A** from the first predetermined position (Full Face Mode), the shield **30** may pivot from the first position (the closed position of the open portion) to the second position (the open position of the open portion). In this instance, the first predetermined angle **A** of the chin guard **20** is not limited to a particular angle, but may be, for example, between 15° and 35° .

(13) Subsequently, as shown in FIGS. **5A** to **6A**, when the chin guard **20** pivots from the first predetermined angle **A** to a third predetermined angle **C** that is larger than the first predetermined angle **A** with respect to the helmet body **10**, the shield **30** may stay in place, not pivoting. That is, while the chin guard **20** pivots to the second predetermined position (Wearing Mode), the shield **30** may be kept in the second position (the open position of the open portion). In this instance, the third predetermined angle **C** of the chin guard **20** is not limited to a particular angle, but may be, for example, between 140° and 160° .

(14) Subsequently, as shown in FIG. **7A**, when the chin guard **20** pivots to the second predetermined angle **B** that is larger than the first and third predetermined angles **A**, **C** with respect to the helmet body **10**, the shield **30** may pivot downward and the open portion may be closed. That is, when the chin guard **20** pivots to the third predetermined position (Open Face Mode), the shield **30** may pivot to the first position (the closed position of the open portion). In this instance, the second predetermined angle **B** of the chin guard **20** is not limited to a particular angle, but may be, for example, between 190° and 210° .

(15) However, when the chin guard **20** pivots, the shield **30** does not necessarily pivot, and when the shield **30** pivots downward to close the open portion, the chin guard may pivot to the second predetermined angle **B** with respect to the helmet body **10**. That is, when the shield **30** pivots from the second position (the open position of the open portion) to the first position (the closed position of the open portion), the chin guard **20** may pivot to the third predetermined position (Open Face Mode).

(16) In the end, since the chin guard **20** and the shield **30** pivot in tandem, when the chin guard **20** pivots, the shield **30** pivots, and when the chin guard **20** is in the second predetermined position (Wearing Mode, see FIG. **6A**), the shield **30** is in the second position (the open position of the open portion), so it is easy for the wearer to wear the helmet.

(17) Additionally, since the chin guard **20** and the shield **30** pivot in tandem, when the chin guard **20** is disposed above and the shield **30** pivots downward (when the shield **30** pivots from the second position (the open position of the open portion) to the first position (the closed position of the open portion) (see FIGS. **6A** to **7A**)), the chin guard may automatically pivot to the third predetermined position (Open Face Mode) at the rear of the helmet body **10**.

(18) As shown in FIG. **2**, the chin guard pivoting mechanism **100** may be included in, for example, the ratchet **40**, and basically, may include a link **200** and an arm **230**. Specifically, the link **200** may be, at one side, coupled to the chin guard **20**, and the arm **230** may, at one side, support the shield **30** to pivot the shield **30**. That is, the link **200** may be coupled to the chin guard **20**, and the arm **230** may support the shield **30**, and in this instance, the link **200** and the arm **230** may pivot in tandem, and accordingly the chin guard **20** and the shield **30** may pivot in tandem.

(19) More specifically, the link **200** may include a first link **210** and a second link **220**. Here, the end of the chin guard **20** is coupled to one side of the first link **210** and one side of the second link **220** at the same time. For example, when one side of the first link **210** and one side of the second link **220** are coupled to a connection portion **250** having two connection holes **253**, one side of the first link **210** and one side of the second link **220** may be connected to each other. Additionally,

when the connection portion **250** is coupled to a fixing portion **25** at the end of the chin guard **20**, as a result, one side of the first link **210** and one side of the second link **220** may be coupled to the chin guard **20** at the same time.

(20) On the other hand, the other side of the first link **210** pivots around a first rotation axis **211** of the ratchet **40**, and the other side of the second link **220** pivots around a second rotation axis **221** (different from the first rotation axis **211**) of the ratchet **40**. In this instance, since one side of the first link **210** and one side of the second link **220** are coupled to the end of the chin guard **20** at the same time, when the chin guard **20** pivots, the first link **210** and the second link **220** may pivot in tandem.

(21) Additionally, the arm **230** may have, on one surface, a sliding portion **240** recessed along the lengthwise direction, and a coupling portion **213** that protrudes from the end of the first link **210** may be inserted into the sliding portion **240** of the arm **230** and slide along the sliding portion **240**. Specifically, when the chin guard **20** pivots, the first link **210** may pivot around the first rotation axis **211**, and the coupling portion **213** of the first link **210** may slide along the sliding portion **240**. More specifically, the sliding portion **240** may include a first sliding portion **240a** and a second sliding portion **240b**. Here, the first sliding portion **240a** is extended in an arc shape, and the second sliding portion **240b** is extended from the end of the first sliding portion **240a** in an arc shape. In this instance, the center of the arc of the first sliding portion **240a** and the center of the arc of the second sliding portion **240b** are different from each other. Accordingly, a point at which the first sliding portion **240a** and the second sliding portion **240b** meet may have a bent shape. In the end, when the chin guard **20** pivots, the coupling portion **213** of the first link **210** may slide along the first sliding portion **240a**, then slide along the second sliding portion **240b**, and finally, slide along the first sliding portion **240a** again.

(22) Meanwhile, a support portion **300** may be disposed above one side of the arm **230**. In this instance, the support portion **300** may be coupled to the shield **30** and pivot by the guidance of the ratchet **40**. Accordingly, when the arm **230** pivots, the arm **230** may press the support portion **300**, and the support portion **300** and the shield **30** may pivot. Additionally, the arm **230** is provided with the other side (different from one side supporting the support portion **300**), which is configured to slide along a pivoting portion **260** (disposed in the ratchet **40**) extended in an arc shape, such that the arm **230** rotates as the other side slides in the pivoting portion **260**. That is, the arm **230** may pivot in the vertical direction along the pivoting portion **260** extended in an arc shape.

(23) The operation relationship of the first link **210**, the second link **220** and the arm **230** will be described in detail below.

(24) As shown in FIGS. **3** and **4**, when the chin guard **20** pivots from the front side of the wearer's chin to the first predetermined angle A with respect to the helmet body **10** and the shield **30** pivots upward, the coupling portion **213** of the first link **210** may slide along the first sliding portion **240a** of the arm **230**. Specifically, when the chin guard **20** pivots in one direction (the clockwise direction), the first link **210** and the second link **220** coupled to the chin guard **20** pivot in the other direction (the counterclockwise direction), and as the coupling portion **213** of the first link **210** slides along the first sliding portion **240a** of the arm **230**, the arm **230** pivots in one direction (the clockwise direction), and the shield **30** supported on the arm **230** pivots upward (in one direction). In the end, when the chin guard **20** pivots by the first predetermined angle A from the first predetermined position (Full Face Mode), the shield **30** may pivot from the first position (the closed position of the open portion) to the second position (the open position of the open portion).

(25) As shown in FIGS. **5** and **6**, when the chin guard **20** pivots from the first predetermined angle A to the third predetermined angle C with respect to the helmet body **10** and the shield **30** does not pivot, the coupling portion **213** of the first link **210** may slide along the second sliding portion **240b** of the arm **230**. Specifically, when the chin guard **20** pivots in one direction (the clockwise direction), the first link **210** and the second link **220** coupled to the chin guard **20** pivot in the other direction (the counterclockwise direction), and the coupling portion **213** of the first link **210** slides

along the second sliding portion **240b** of the arm **230** (see FIG. 5B). Subsequently, when the chin guard **20** additionally pivots in one direction (the clockwise direction), the first link **210** and the second link **220** coupled to the chin guard **20** pivot in one direction (the clockwise direction) and the other direction (the counterclockwise direction), respectively, and the coupling portion **213** of the first link **210** slides along the second sliding portion **240b** of the arm **230** (see FIG. 6B). In the end, the coupling portion **213** of the first link **210** slides from one end (an end connected to the first sliding portion **240a**) of the second sliding portion **240b** of the arm **230** to the other end (see FIG. 5B), and then slides from the other end of the second sliding portion **240b** to one end (see FIG. 6B). In this instance, the radius of curvature of the second sliding portion **240b** may correspond to the distance between the coupling portion **213** and the first rotation axis **211**. Accordingly, while the coupling portion **213** of the first link **210** moves along the two ends of the second sliding portion **240b**, the arm **230** does not pivot, and accordingly the shield **30** supported on the arm **230** does not pivot, either. In the end, while the chin guard **20** pivots to the second predetermined position (Wearing Mode), the shield **30** may be kept in the second position (the open position of the open portion).

(26) As shown in FIG. 7, when the chin guard **20** pivots from the third predetermined angle C to the second predetermined angle B with respect to the helmet body **10** and the shield **30** pivots downward, the coupling portion **213** of the first link **210** may slide along the first sliding portion **240a** of the arm **230**. Specifically, when the chin guard **20** pivots in one direction (the clockwise direction), the first link **210** and the second link **220** coupled to the chin guard **20** pivot in one direction (the clockwise direction) (in this instance, a pivot angle of the second link **220** is smaller than that of the first link **210**), and as the coupling portion **213** of the first link **210** slides along the first sliding portion **240a** of the arm **230**, the arm **230** pivots in the other direction (the counterclockwise direction), and the shield **30** supported on the arm **230** pivots downward (in the other direction). In the end, when the chin guard **20** pivots from the second predetermined position (Wearing Mode) to the third predetermined position (Open Face Mode), the shield **30** may pivot to the first position (the closed position of the open portion).

(27) However, the present disclosure is not necessarily limited to the downward pivoting of the shield **30** with the pivoting of the chin guard **20**, and may include pivoting of the chin guard **20** with the downward pivoting of the shield **30**. That is, when the shield **30** pivots downward and the chin guard **20** pivots to the second predetermined angle B with respect to the helmet body **10**, the coupling portion **213** of the first link **210** may slide along the first sliding portion **240a** of the arm **230**. Specifically, when the shield **30** pivots in the other direction (the counterclockwise direction), the arm **230** supporting the shield **30** pivots in the other direction (the counterclockwise direction), and as the coupling portion **213** of the first link **210** slides along the first sliding portion **240a** of the arm **230**, the first link **210** and the second link **220** pivot in one direction (the clockwise direction), and accordingly the chin guard **20** coupled to the first link **210** and the second link **220** may pivot in one direction (the clockwise direction). In the end, when the shield **30** pivots from the second position (the open position of the open portion) to the first position (the closed position of the open portion), the chin guard **20** may pivot from the second predetermined position (Wearing Mode) to the third predetermined position (Open Face Mode).

(28) Overall, one side of the first link **210** and one side of the second link **220** coupled to the chin guard **20** are reversed by the pivoting of the chin guard **20**. Specifically, when the chin guard **20** pivots from the front side of the wearer's chin with respect to the helmet body **10**, one side of the first link **210** may be disposed in front of one side of the second link **220** (see FIGS. 3B and 4B), then disposed above one side of the second link **220** (see FIGS. 5B and 6B), and subsequently, disposed at the rear of one side of the second link **220** (see FIG. 7B).

(29) Meanwhile, to guide the movement path of one side of the first link **210** and one side of the second link **220**, the ratchet **40** may have a guide hole **500** on the front surface. Specifically, the guide hole **500** may include a first guide hole **510** and a second guide hole **520**. Here, the first

guide hole **510** plays a role in guiding the movement path of one side of the first link **210**, and the second guide hole **520** plays a role in guiding the movement path of one side of the second link **220**. Accordingly, the radius of curvature of the first guide hole **510** may correspond to the distance between one side of the first link **210** and the first rotation axis **211**, and the radius of curvature of the second guide hole **520** may correspond to the distance between one side of the second link **220** and the second rotation axis **221**.

(30) In addition, the ratchet **40** may include a fastening portion **400** to fix the link **200**. Here, when the chin guard **20** is disposed in front of the wearer's chin or at the rear of the helmet body **10**, the fastening portion **400** may be coupled to the link **200** (the first link **210**) to prevent arbitrary pivoting of the link **200** (the first link **210**). Accordingly, it is possible to prevent arbitrary pivoting of the chin guard **20** coupled to the link **200** (the first link **210**) by the fastening portion **400**. However, when the wearer manipulates the chin guard **20** to pivot the chin guard **20** with respect to the helmet body **10**, the fastening portion **400** may be separated from the link **200** (the first link **210**).

(31) Specifically, when the chin guard **20** is disposed in front of the wearer's chin or at the rear of the helmet body **10**, a first hook portion **410** of the fastening portion **400** may be fastened to a second hook portion **215** of the link **200** (the first link **210**) to prevent arbitrary pivoting of the link **200** (the first link **210**). However, when the wearer manipulates the chin guard **20** to pivot the chin guard **20** with respect to the helmet body **10**, the link **200** (the first link **210**) may pivot, and accordingly, the fastening portion **400** may pivot, and the first hook portion **410** may be separated from the second hook portion **215**. In this instance, an elastic force may be applied to the fastening portion **400** in a direction in which the first hook portion **410** is fastened to the second hook portion **215**. For example, a torsion spring may be coupled to the fastening portion **400**.

(32) While the present disclosure has been hereinabove described in detail through the specific embodiments, this is provided to describe the present disclosure in detail, and the present disclosure is not limited thereto, and it is obvious that modifications or changes may be made thereto by those having ordinary skill in the art within the technical spirit of the present disclosure.

(33) Such modifications and changes of the present disclosure fall in the scope of the present disclosure, and the scope of protection of the present disclosure will be apparent by the appended claims.

(34) TABLE-US-00001 List of Main Elements 10: Helmet body 20: Chin guard 30: Shield 40: Ratchet 100: Chin guard pivoting mechanism 200: Link 210: First link 211: First rotation axis 213: Coupling portion 215: Second hook portion 220: Second link 221: Second rotation axis 230: Arm 240: Sliding portion 240a: First sliding portion 240b: Second sliding portion 250: Connection portion 260: Pivoting portion 300: Support portion 400: Fastening portion 410: First hook portion 500: Guide hole 510: First guide hole 520: Second guide hole

(35) The present disclosure provides the chin guard pivoting mechanism for pivoting the chin guard and the shield in tandem.

Claims

1. A chin guard pivoting mechanism configured to couple to a helmet comprising a helmet body, a chin guard pivotally coupled to the helmet body and a shield pivotally coupled to the helmet body, the chin guard pivoting mechanism comprising: a link comprising a first link and a second link, wherein the first link comprises a first side and a second side, and the second link comprises a first side and a second side, wherein the first side of the first link is configured to couple to the chin guard and the first side of the second link is configured to couple to the chin guard, and wherein the second side of the first link is configured to pivot around a first rotation axis, and the second side of the second link is configured to pivot around a second rotation axis; an arm configured to pivot the shield on a first side of the arm, wherein the link and the arm are configured to pivot in tandem;

and wherein upon pivoting of the chin guard from a location configured to be on a front side of a wearer's chin to a first predetermined angle with respect to the helmet body, the arm is configured to pivot the shield upward, and upon pivoting of the chin guard to a second predetermined angle which is larger than the first predetermined angle with respect to the helmet body, the arm is configured to pivot the shield downward, or wherein upon pivoting of the chin guard from the location configured to be on the front side of the wearer's chin to the first predetermined angle with respect to the helmet body, the arm is configured to pivot the shield upward, and the arm is configured to pivot the shield downwards, causing the chin guard to pivot to the second predetermined angle with respect to the helmet body.

2. The chin guard pivoting mechanism according to claim 1, wherein upon pivoting of the chin guard from the first predetermined angle to a third predetermined angle between the first predetermined angle and the second predetermined angle with respect to the helmet body, the arm is configured to not pivot the shield.

3. The chin guard pivoting mechanism according to claim 1, wherein upon pivoting of the chin guard from the location configured to be on the front side of the wearer's chin with respect to the helmet body, the first side of the first link is disposed in front of the first side of the second link, then disposed above the first side of the second link, and subsequently disposed behind the first side of the second link.

4. The chin guard pivoting mechanism according to claim 1, wherein the arm has a sliding portion being formed in a lengthwise direction of the arm, and wherein upon the pivoting of the chin guard, a coupling portion of the first link is slidable along the sliding portion.

5. The chin guard pivoting mechanism according to claim 4, wherein the sliding portion includes: a first sliding portion extended in an arc shape; and a second sliding portion extended from an end of the first sliding portion in an arc shape.

6. The chin guard pivoting mechanism according to claim 5, wherein the coupling portion slides along the first sliding portion when the arm pivots the shield upward, and wherein the coupling portion slides along the first sliding portion when the arm pivots the shield downward.

7. The chin guard pivoting mechanism according to claim 6, wherein upon pivoting of the chin guard from the first predetermined angle to a third predetermined angle between the first predetermined angle and the second predetermined angle with respect to the helmet body, and not pivoting of the shield, the coupling portion slides along the second sliding portion.

8. The chin guard pivoting mechanism according to claim 7, wherein a radius of curvature of the second sliding portion corresponds to a distance between the coupling portion and the first rotation axis.

9. The chin guard pivoting mechanism according to claim 1, wherein a second side of the arm comprises a sliding portion that is configured to slide along a pivoting portion extended in an arc shape, such that the arm rotates as the sliding portion of the arm slides in the pivoting portion.

10. The chin guard pivoting mechanism according to claim 1, further comprising a fastening portion which is coupled to the link, and is separated from the link upon the pivoting of the chin guard with respect to the helmet body.

11. The chin guard pivoting mechanism according to claim 10, wherein a first hook portion of the fastening portion is fastened to a second hook portion of the link, and upon the pivoting of the chin guard with respect to the helmet body, the link pivots and accordingly the fastening portion pivots, and the first hook portion is separated from the second hook portion.

12. The chin guard pivoting mechanism according to claim 11, wherein the fastening portion is configured to receive an elastic force to rotate the fastening portion such that the first hook portion becomes fastened to the second hook portion.
