

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414838
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Altamura; Michael

Systems and methods for retractor holder

Abstract

Systems and methods for a vaginal speculum holder are disclosed. In some aspects, a system may include a retractor and a holder. The retractor may include a blade assembly, a base, and one or more supports attached to the base and the blade assembly. In some aspects, the holder may include a receptacle configured to receive the base, and a fastener configured to secure the holder to an object. In some aspects, the method may include using a fastener of a holder to secure the holder to an object and using a receptacle of the holder to receive a base of a retractor.

Inventors:	Altamura; Michael (Croton-on-Hudson, NY)
Applicant:	Altasurgical LLC (Union City, NJ)
Family ID:	1000008820724
Assignee:	Altasurgical LLC (Union City, NJ)
Appl. No.:	18/085965
Filed:	December 21, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230218367 A1	Jul. 13, 2023

Related U.S. Application Data

us-provisional-application US 63302725 20220125
us-provisional-application US 63297930 20220110

Publication Classification

Int. Cl.: B25B1/00 (20060101); A61B90/57 (20160101)

U.S. Cl.:

CPC **A61B90/57** (20160201); A61B2090/571 (20160201)

Field of Classification Search

CPC: B25B (1/22); B25B (1/2421); B25B (1/2457); B25B (3/00); B25B (1/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4119305	12/1977	Anderson	269/238	B25B 1/22
4214739	12/1979	Dailey	269/75	B25B 1/22
5165673	12/1991	Newton, Jr.	269/69	A01K 97/28
5775679	12/1997	Strub	269/95	A01K 97/28
5809686	12/1997	Abby	269/69	A01K 97/28
5826867	12/1997	Roby	269/74	F16M 11/14
7566022	12/2008	McKinley	269/221	A01K 97/28
7950638	12/2010	Su	269/95	A01K 97/28
2009/0045310	12/2008	Koesema, Jr.	248/65	F16L 3/13
2023/0218367	12/2022	Altamura	600/227	A61B 90/57

Primary Examiner: Wilson; Lee D

Attorney, Agent or Firm: Rothwell, Figg, Ernst & Manbeck, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of priority to U.S. Provisional Application Ser. No. 63/302,725, filed Jan. 25, 2022, and U.S. Provisional Application Ser. No. 63/297,930, filed Jan. 10, 2022, which are incorporated herein by reference in their entireties.

FIELD OF INVENTION

(1) The present disclosure relates generally to the field of medical tools and devices. More specifically, the present disclosure relates to systems and methods for a retractor holder and use thereof.

BACKGROUND

(2) Retractors are medical instruments used to create space in a body (e.g., for visualization and/or access during examination and/or surgery). Surgical vaginal speculums are self-retaining retractors used to obtain exposure to the vaginal canal to permit vaginal surgery. The existing speculums are composed of a blade which is inserted into the vaginal canal and a stem or handle which may or may not incorporate a weight to cause depression of the posterior vaginal wall to create space. The length of the blade for each speculum is fixed for which reason the operating room has to have an array of speculums of different sizes to adjust for the depth of the vagina. Furthermore, the existing speculums have a fixed angle between the blade and the stem. Therefore, they are not always a proper fit corresponding to the pitch of the vagina which depends on the pliability of the posterior

wall. This can affect the degree of exposure created by the speculum. Because the pitch of the vagina depends on the pliability of the posterior vaginal wall, the angled speculums, which are meant to be self-retaining, cannot be properly inserted in those cases where the vaginal canal has little or no pliability. In this case, a 90 degree angle speculum is used which requires an assistant to apply downward pressure on the blade, as these speculums do not incorporate a weight.

(3) Existing retractors (e.g., speculums) use means such as a clamp to secure the retractor to an operating table. Other existing retractors just have a weight and are not attached to the operating table, which may cause the retractors to slip out of the vagina due the fixed blade length and fixed angle of the retractor.

SUMMARY

(4) Clamps used to secure retractors (e.g., speculums) to operating tables can cause stability issues, particularly if the clamp is merely a general clamp and is not configured to hold the retractor to the table. Furthermore, a retractor that has been clamped to an operating table cannot generally be moved (e.g., side-to-side) relative to the operating site. Therefore, there exists a need for a holder for a retractor that is capable of both securing the retractor to an object (e.g., an operating table) while still enabling the retractor to be moved at least side-to-side by an operator.

(5) Aspects of the invention may overcome one or more the problems associated with the existing solutions for securing retractors to objects (e.g., operating tables) by providing a retractor holder.

(6) One aspect of the invention may provide a system including a retractor and a holder. The retractor may include a blade assembly, a base, and one or more supports attached to the base and the blade assembly. The holder may include a receptacle configured to receive the base and a fastener configured to secure the holder to an object.

(7) In some aspects, the retractor may be a speculum. In some aspects, the object may be an operating room table. In some aspects, the one or more supports may include one or more columns.

(8) In some aspects, the fastener may be a clip. In some aspects, the receptacle may include a sleeve. In some aspects, the receptacle may be made of plastic.

(9) In some aspects, the receptacle may be configured to prevent rotation of the base about a longitudinal axis of the base. In some aspects, the holder may be configured to maintain the base of the retractor at a constant height. In some aspects, the holder may be configured to maintain a longitudinal axis of the one or more supports in a vertical orientation. In some aspects, the receptacle of the holder may be configured such that the base of the retractor is capable of side-to-side movement within the receptacle.

(10) Another aspect of the invention may provide a holder including a receptacle configured to receive a base of a retractor and a fastener configured to secure the receptacle to an object.

(11) In some aspects, the object may be an operating room table. In some aspects, the fastener may be a clip. In some aspects, the receptacle may include a sleeve.

(12) In some aspects, the receptacle may be configured to prevent rotation of the base about a longitudinal axis of the base. In some aspects, the holder may be configured to maintain the base of the retractor at a constant height. In some aspects, the retractor may include one or more supports attached to the base, and the holder is configured to maintain a longitudinal axis of the one or more supports in a vertical orientation. In some aspects, the receptacle of the holder configured such that the base of the retractor is capable of side-to-side movement within the receptacle.

(13) Still another aspect of the invention may provide a method. The method may include using a fastener of a holder to secure the holder to an object. The method may include using a receptacle of the holder to receive a base of a retractor.

(14) In some aspects, the method further include moving the base of the retractor from one side of the receptacle to another side of the receptacle.

(15) Further variations encompassed within the systems, holders, and methods are described in the detailed description below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The accompanying drawings, which are incorporated herein and form part of the specification, illustrate various, non-limiting aspects of the present invention. In the drawings, like reference numbers indicate identical or functionally similar elements.
- (2) FIG. 1 shows an isometric view of an exemplary system wherein the retractor holder houses the base assembly, according to some aspects.
- (3) FIG. 2 shows a back view of an exemplary system wherein the base assembly indicates the side-to-side movement inside the retractor holder, according to some aspects.
- (4) FIG. 3 shows an isometric view of an exemplary system wherein the blade is extended and at the top most position on the supports, according to some aspects.
- (5) FIG. 4 shows a close-up isometric view of a system wherein the blade is extended and the ratchet back side in view, according to some aspects.
- (6) FIG. 5 shows a close-up isometric view of an exemplary system wherein the blade is extended, the ratchet back side in view, and the blade assembly is pivoted, according to some aspects.
- (7) FIG. 6 shows a close-up front view of an exemplary system wherein the blade is at the top most position on the supports and the blade assembly is pivoted, according to some aspects.
- (8) FIG. 7 shows an isometric view of an exemplary system looking from the bottom up wherein the blade is extended and at the top most position on the supports indicating the rotational angle of the blade motion, according to some aspects.
- (9) FIG. 8 shows a side view of an exemplary system wherein the blade is at the top most position on the supports, according to some aspects.
- (10) FIG. 9 shows a side view of an exemplary system wherein the blade is on an angle and at the top most position on the supports, according to some aspects.
- (11) FIG. 10 shows a side view of an exemplary system wherein the blade is at the bottom most position on the supports, according to some aspects.
- (12) FIG. 11 shows a side view of an exemplary system wherein the blade is on an angle and at the bottom most position on the supports, according to some aspects.
- (13) FIG. 12 shows an exploded view of an exemplary system indicating the three main assemblies, according to some aspects.
- (14) FIG. 13 shows a front view of an exemplary system wherein the blade is at the middle position on the supports, according to some aspects.
- (15) FIG. 14 shows an isometric view of another aspect of an exemplary system that uses a pivoting mechanism and support structure to enable 360 degree rotation of the blade assembly, according to some aspects.
- (16) FIG. 15 shows a close-up isometric view of another aspect of an exemplary system wherein the blade is extended and the ratchet back side in view, according to some aspects.
- (17) FIG. 16 shows a close-up isometric view of another aspect of an exemplary system wherein the blade is extended, the ratchet back side in view, and the blade assembly is pivoted, according to some aspects.
- (18) FIG. 17 shows a close-up view of another aspect of an exemplary system wherein the blade assembly is pivoted, according to some aspects.
- (19) FIG. 18 is a flowchart illustrating a process according to some aspects.

PARTS LIST

- (20) **100.** System **102.** Retractor **104.** Holder **1.** Movable vacuum blade **2.** Fixed blade **3.** Spring loaded ratchet parts **4.** Suction Plate **5.** One or more supports **6.** Slider **7.** Slider track **8.** Screws **9.** Base **10.** Suction Holes **11.** Suction Connection **12.** Receptacle **13.** Blade Assembly **14.** Ratchet Assembly **15.** Base Assembly **16.** Light Assembly **17.** Pivot Connection **18.** Support Structure **19.**

DETAILED DESCRIPTION

(21) FIGS. **1** and **2** illustrate a system **100** including a retractor **102** and a holder **104**. In some aspects, the retractor **102** may be, for example and without limitation, a vaginal speculum. In some alternative aspects, the retractor **102** may be another type of retractor (e.g., a rectal speculum, a nasal speculum, or an ear speculum). In some aspects, as shown in FIG. **1**, the retractor **102** may include a blade assembly **13**. In some aspects, the blade assembly **13** may include a movable blade **1** and a fixed blade **2**. In some aspects, the moveable blade **1** may glide over a fixed blade **2** (e.g., to adjust to the length of the vaginal canal of a patient undergoing surgery). In some aspects, the moveable blade **1** may be a vacuum sleeve. In some aspects, the retractor **102** may include a base **9**, which may act as the fulcrum for the retractor **102**.

(22) In some aspects, as shown in FIGS. **1** and **2**, the holder **104** may be fastened or otherwise attached to an object (e.g., an operating table). In some aspects, the holder **104** may allow for movement (e.g., side-to-side movement) of the base **9** in the holder **104** (e.g., for adjustment of the position of the retractor **102** relative to an operating site). In some aspects, the retractor holder **104** may include a receptacle **12** configured to receive and hold the base **9** of the retractor **102**. In some aspects, the retractor holder **104** may also include a fastener **20**. In some aspects, the fastener **102** may be configured to secure the holder **104** to an object (e.g., an operating table). In some aspects, as shown in FIGS. **1** and **2**, the fastener **20** may be a clip. In some alternative aspects, a different structure (e.g., a bolt and nut, a screw, or a clamp) may be used for the fastener **20**.

(23) In some aspects, the holder **104** may be configured to maintain the base **9** of the retractor **102** at a constant height (e.g., relative to an operating site and/or the object) when the fastener **20** secures the holder **104** to the object and the base **9** of the retractor **102** is in the receptacle **12** of the holder **104**. In some aspects, the holder **104** may additionally or alternatively be configured to maintain a longitudinal axis of one or more supports **5** of the retractor **102** in a vertical orientation. In some aspects, the receptacle **12** of the holder **104** may be configured to prevent rotation of the base **9** of the retractor **102** about a longitudinal axis of the base **9** (e.g., so that one or more supports **5** of the retractor **102** remains in a vertical orientation while the base **9** of the retractor **102** is in the receptacle **12** of the holder **104**).

(24) As further shown in at least FIG. **2**, in some aspects, the retractor **102** may include spring-loaded ratchet parts **3** that allow for changing of the angle of the blade assembly **13** in an upward or downward direction. In some aspects, the spring-loaded ratchet parts **3** may allow the angle of the blade assembly **13** to be adjusted (e.g., so that it corresponds to the vaginal pitch and thereby gains as much exposure as possible). For example, the spring-loaded ratchet parts **3** may be adjusted so that it corresponds to the vaginal pitch and thereby gains as much exposure as possible. In some alternative aspects, other mechanisms to adjust an angle may be used.

(25) FIGS. **3-14** further illustrate the retractor **102** according to some aspects. As shown in at least FIG. **3**, in some aspects, the blade assembly **13** may be attached to a slider track **7** that allows rotation of the blade assembly **13** (e.g., at least 15 degrees to the right of the midline and at least 15 degrees to the left of the midline for the vertical position). FIG. **3** further shows, in some aspects, the sliding motion of the movable vacuum sleeve **1**.

(26) As shown in at least FIG. **4**, in some aspects, the movable blade **1** may include an internal cavity with small openings **10** near the front edge and, as shown in FIG. **7**, a suction connection **11** on the rear edge to connect to standard medical vacuum tubing. In some aspects, the suction connection **11** provides suction to remove surgical and bodily fluids present during operation.

(27) As shown in at least FIGS. **5** and **6**, in some aspects, the retractor **102** may include a slider track **7** (e.g., a curved slider track), which allows the blade assembly **13** to pivot from side to side, improving access to the side walls of the vaginal canal.

(28) As shown in at least FIGS. **7**, **8**, and **13**, in some aspects, the blade **2** and ratchet parts **3** may be assembled into the slider **6** parts with one or more screws **8** (identified in FIG. **7**), which will

allow the blade assembly **13** to travel up and down along one or more supports **5**. In some aspects, and as shown in at least FIG. 7, the slider track **7** may slide along the one or more supports **5**, which may allow for height adjustment of the retractor **102** from the surface of, for example, an operating table to the posterior angle of the vaginal opening. In FIGS. 7 and 8, the retractor **102** is shown as having been moved to an upper position on the one or more supports **5**. In FIG. 13, the retractor **102** is shown as having been moved to a lower position on the one or more supports **5** by the slider track **7**.

(29) As shown in at least FIGS. 9, 10, and 11, in some aspects, the blade assembly **13** may be pitched, by means of the ratchet parts **3**, up and down, for example, to enable improved access to the vaginal canal. In some aspects, the system **100** may have the blade assembly **13** pitched, by means of the ratchet parts **3**, and also moved up and down the one or more supports **5**, by means of the slider track **7**.

(30) As shown in FIG. 12, in some aspects, the retractor **102** may have multiple assemblies, including, for example and without limitation, a blade assembly **13**, a ratchet assembly **14**, and a base assembly **15**.

(31) FIGS. 14-17 illustrate the retractor **102** according to some alternative aspects. In some aspects, as shown in FIGS. 14-17, the retractor **102** may include a pivoting mechanism **19**, a pivot connection **17**, a light track **16**, and a support structure **18**. In some aspects, the pivot mechanism **19** may allow the blade assembly **13** to pivot (e.g., pivot 360 degrees). In some aspects, the pivot mechanism **19**, pivot connection **17**, light track **16**, and support structure **18** may allow for the retractor **102** to have improved access to the vaginal canal.

(32) In addition, in some aspects, all the parts of the retractor **102** may be made out of plastic and/or metal (e.g., stainless steel). In some aspects, the retractor **102** may be single use, which may help to minimize the sterilization process and/or rate of infection.

(33) In some aspects, the retractor **102** may adjust to the exact vaginal depth and to the individual posterior vaginal angle. In some aspects, the blades may be rotated for maximum exposure. In some aspects, the suction chamber in the extension blade may allow for a surgical field free of smoke during fulguration and elimination of blood pooling. In some aspects, the retractor **102** may include lighting. In some aspects, the retractor **102** may be self-retaining, may adjust for variable vaginal depths, may adjust for variable posterior vaginal angle, and/or may adjust for increased access to the side walls, thus allowing for maximum exposure of the canal. However, in some alternative aspects, a different retractor **102** (e.g., a retractor **102** that does not adjust for various vaginal depths and/or does not adjust for increased access to side walls) may be used with the holder **104**. For example, in some aspects, the holder **104** may be used with a retractor **102** having a fixed blade length and/or a fixed angle between the blade and stem or supports.

(34) FIG. 18 illustrates a process **1800** according to some aspects. In some aspects, as shown in FIG. 18, the process **1800** may include a step **1802** of using a fastener **20** of a holder **104** to secure the holder **104** to an object. In some aspects, as shown in FIG. 18, the process **1800** may include a step **1804** of using a receptacle **12** of the holder **104** to receive a base **9** of a retractor **102**. In some aspects, as shown in FIG. 18, the process **1800** may include an optional step **1806** of moving the base **9** of the retractor **102** from one side of the receptacle **12** to another side of the receptacle **12**. In some aspects (e.g., some aspects in which the retractor **102** is a vaginal speculum), the process **1800** may additionally include one or more of (i) extending the movable blade **1** of the retractor **102** to match a patient's depth of the vagina, (ii) adjusting the height of the blade assembly **13** such that the blades lie on the surface of the posterior wall of the vagina, (iii) using the blade angle mechanism (e.g., ratchet assembly **14** including spring-loaded ratchet parts **3**) and/or the blade pivoting mechanism (e.g., slider **6** and slider track **7** or pivot connection **17**) to achieve optimal exposure without undue pressure against the vaginal wall, and/or (iv) after reaching the maximal achievable exposure without undue pressure on the posterior wall, using the ratchet assembly **14** to keep the blade in this fixed position.

(35) While various aspects are described herein, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of this disclosure should not be limited by any of the above-described exemplary aspects. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

Claims

1. A system comprising: a retractor including: a blade assembly; a base; and one or more supports attached to the base and the blade assembly; and a holder including: a receptacle configured to receive the base, wherein the receptacle comprises: a front end; a bottom surface; a top surface; a cavity defined by at least the front end, the bottom surface, and the top surface; and an opening to the cavity at a rear end of the receptacle, wherein the rear end is opposite the front end; wherein the top surface comprises a recess at the rear end, and the receptacle is configured such that, when the base of the retractor is received by the receptacle, at least a portion of the base of the retractor is within the cavity, and the one or more supports of the retractor pass through the recess in the top surface of the receptacle; and a clip on the top surface of the receptacle, wherein the clip is configured to secure the holder to an object.
2. The system of claim 1, wherein the receptacle is configured to prevent rotation of the base about a longitudinal axis of the base.
3. The system of claim 1, wherein the holder is configured to maintain the base of the retractor at a constant height.
4. The system of claim 1, wherein the holder is configured to maintain a longitudinal axis of the one or more supports in a vertical orientation.
5. The system of claim 1, wherein the receptacle is made of plastic.
6. The system of claim 1, wherein the receptacle of the holder is configured such that the base of the retractor is capable of side-to-side movement within the receptacle.
7. The system of claim 1, wherein the object is an operating room table.
8. The system of claim 1, wherein the one or more supports comprise one or more columns.
9. The system of claim 1, wherein the retractor is a speculum.
10. A holder comprising: a receptacle comprising: a front end; a bottom surface; a top surface; a cavity defined by at least the front end, the bottom surface, and the top surface; and an opening to the cavity at a rear end of the receptacle, wherein the rear end is opposite the front end; wherein the top surface comprises a recess at the rear end; and a clip on the top surface of the receptacle, wherein the clip is configured to secure the receptacle to an object.
11. The holder of claim 10, wherein the receptacle is configured to receive a base of a retractor, the retractor comprises one or more supports attached to the base, and the receptacle is configured such that, when the base of the retractor is received by the receptacle, at least a portion of the base of the retractor is within the cavity, and the one or more supports of the retractor pass through the recess in the top surface of the receptacle.
12. The holder of claim 11, wherein the holder is configured to maintain the base of the retractor at a constant height.
13. The holder of claim 11, wherein the holder is configured to maintain a longitudinal axis of the one or more supports in a vertical orientation.
14. The holder of claim 10, wherein the object is an operating room table.
15. The holder of claim 11, wherein the receptacle of the holder is configured such that the base of the retractor is capable of side-to-side movement within the cavity of the receptacle.
16. The holder of claim 11, wherein the receptacle is configured to prevent rotation of the base about a longitudinal axis of the base.
17. The holder of claim 11, wherein the receptacle is configured such that, when the base of the

retractor is received by the receptacle, the one or more supports of the retractor abut a front edge of the recess in the top surface of the receptacle.

18. The holder of claim 17, wherein the receptacle is configured such that, when the base of the retractor is received by the receptacle, the one or more supports of the retractor abut the clip.

19. The holder of claim 10, wherein the front end of the receptacle is tapered.

20. The holder of claim 10, wherein the clip abuts the recess in the top surface of the receptacle.

21. A method comprising: using a clip on a top surface of a receptacle of a holder to secure the holder to an object; and using the receptacle of the holder to receive a base of a retractor, wherein the receptacle comprises: a front end; a bottom surface; a top surface; a cavity defined by at least the front end, the bottom surface, and the top surface; and an opening to the cavity at a rear end of the receptacle, wherein the rear end is opposite the front end; wherein the top surface comprises a recess at the rear end, and, when the base of the retractor is received by the receptacle, at least a portion of the base of the retractor is within the cavity, and one or more supports of the retractor that are attached to the base of the retractor pass through the recess in the top surface of the receptacle.

22. The method of claim 21, further comprising moving the base of the retractor from one side of the receptacle to another side of the receptacle.
